Exhibit 11: SAR Test Report: IHDT56AA1

Date of test:	12/06/2000 – 12/08/2000
Laboratory:	Motorola Personal Communications Sector Product Safety Laboratory 2001 N. Division Room: AS228 Harvard, Illinois 60033
Test Responsible:	Steven Hauswirth Staff Engineer
Accreditation:	ISO Guide 25 Accredited Lab, A2LA certificate #1651-01
Statement of Compliance:	Motorola declares under its sole responsibility that portable cellular telephone FCC ID IHDT56AA1 to which this declaration relates, is in conformity with the appropriate RF exposure standards, recommendations and guidelines. It also declares that the product was tested in accordance with the appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below: -None-

©Motorola
This test report shall not be reproduced in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

1) Introduction 3

2) Description of the Device Under Test 3
Antenna description 3
Device description 3

3) Test Results 3

4) Test Equipment 4
4.1 Dosimetric system 4
4.2 Additional equipment used 5

5) Electrical parameters of the tissue simulating liquid 5

6) System Accuracy Verification 5

Reference Notes

Appendix 1: SAR distribution comparison for the system accuracy verification 6

Appendix 2: SAR distribution plots for Phantom Head Adjacent Use 7

Appendix 3: SAR distribution plots for Body Worn Configuration 9

Appendix 4: Photographs of the device under test 10

1. Introduction

The Motorola Personal Communications Sector Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of portable cellular phone FCC ID IHDT56AA1. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with the latest available test guidelines. The SAR values found for the portable cellular phone (FCC ID IHDT56AA1) are below the maximum recommended levels of 1.6 W/kg. Detailed procedures of the test are described in the *Motorola Exhibit 11 Reference SAR Test Report*.

2. Description of the Device Under Test

Antenna description

Type	Extendable whip
Location	Right Side
Configuration	Helix with Analog output power cutback when antenna is retracted.

Device description

FCC ID Number	IHDT56AA1			
Serial number	A07526			
Mode(s) of Operation	AMPS800	AMPS800	CDMA800	CDMA1900
Modulation Mode(s)	AMPS	AMPS	CDMA	CDMA
Maximum Output Power Setting	26.3dBm (Ant Ext)	24.3dBm(Ant Ret)	23.9dBm	23.2dBm
Duty Cycle	1:1	1:1	1:1	1:1
Transmitting Frequency Rang(s)	824-849MHz	824-849MHz	824-849MHz	1851-1909MHz

3. Test Results

The SAR results shown in tables 1 and 2 are maximum SAR values averaged over 1 gram of phantom tissue. Also shown are the measured conducted output powers and the temperature of the test facility during the test.

The test sample was operated in a test mode that allows control of the transmitter without the need to place actual phone calls. For the purposes of this test the unit is commanded to test mode and manually set to the proper channel, transmitter power level and transmit mode of operation. The phone was then placed in the SAR measurement system with a fully charged battery.

A full data set output of two test conditions with the highest SAR values from the Dasy™ measurement system is included as appendix 2 and 3. The test conditions included are indicated as bold numbers in the following table. All other test conditions measured lower SAR values than those included. Note that digital mode SAR data was measured only for the test conditions that resulted in the highest analog SAR values. This is because the only difference between analog and digital modes that can impact SAR is the average transmitter power.

f (MHz)	Description	Conducted Output Power (dBm)	SAR, 1g (W/kg) Left Head Ant Ext	Left Head Ant Ret	Right Head Ant Ext	Right Head Ant Ret
Analog 800MHz	Channel 991	26.3 Ext/ 24.3 Ret	0.98	0.87	1.04	0.97
	Channel 384	27.1 Ext/ 25.0 Ret	**1.27**	**1.32**	1.05	0.94
	Channel 799	27.0 Ext/ 25.0 Ret	1.23	1.29	1.04	0.94
CDMA	Channel 384	24.0	0.65	1.1		
Digital 1900MHz	Channel 25	23.6	**1.16**	1.32	1.05	1.22
	Channel 650	23.9	1.14	**1.33**	1.11	1.26
	Channel 1175	23.5	0.99	1.16	0.93	1.07

Table 1: SAR measurement results for the portable cellular telephone FCC ID IHDT56AA1 at highest possible output power. Measured against the head.

f (MHz)	Description	Conducted Output Power (dBm)	SAR, 1g (W/kg) Plastic Belt Clip Ant Ext	Plastic Belt Clip Ant Ret
Analog 800MHz	Channel 991	26.3 Ext/ 24.3 Ret	0.59	0.46
	Channel 384	27.1 Ext/ 25.0 Ret	0.62	**0.46**
	Channel 799	27.0 Ext/ 24.0 Ret	**0.63**	0.46
Digital 800MHz	Channel 384	24.0		0.32
	Channel 779	23.9	0.11	
Digital 1900MHz	Channel 25	23.6	0.38	**0.42**
	Channel 650	23.9	**0.40**	0.40
	Channel 1175	23.5	0.32	0.32

Table 2: SAR measurement results for the portable cellular telephone FCC ID IHDT56AA1 at highest possible output power. Measured against the body.

4. Test Equipment Used

4.1 Dosimetric System

The Motorola Personal Communications Sector Product Safety Laboratory utilizes a Dosimetric Assessment System (Dasy3™) SAR measurement system manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. The overall RSS uncertainty of the measurement system is ±12.0% (K=1).

Description	Serial Number	Cal Due Date
DASY3 DAE V1	SN385	5/2001
E-Field Probe ETDV6	SN1390	2/2001
Dipole Validation Kit, DV835V2	SN416	2/2002
Dipole Validation Kit, DV1800V2	SN246	8/2001

4.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3847A04810	1/31/01
Power Meter E4419B	GB39511087	3/13/01
Power Sensor E9301A	US39211008	3/20/01

5. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity, ε_r, and the conductivity, σ, of the tissue simulating liquids were measured with HP85070 Dielectric Probe Kit These values are shown in the table below. The mass density, ρ, used by the dosimetric system is also given. Recommended limits for maximum permittivity, minimum conductivity and maximum mass density are also shown. These come from the Federal Communication Commission, "Tissue Dielectric Properties" web site at http://www.fcc.gov/fcc-bin/dielec.sh. It is seen that the measured parameters are satisfactory for compliance testing.

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			e_r	s (S/m)	r (g/cm^3)
836	**Head**	**Measured,** 12/6/00	43.39	0.86	1.00
		Recommended Limits	46.08	0.74	1.03
	Body	**Measured,** 12/8/00	50.5	1.08	1.00
		Recommended Limits	56.11	0.94	1.04
1880	**Head**	**Measured,** 12/7/00	39.47	1.43	1.00
		Recommended Limits	43.4	1.19	1.03
	Body	**Measured,** 12/8/00	48.76	1.64	1.00
		Recommended Limits	54.33	1.43	1.04

6. System Accuracy Verification

A system accuracy verification of the DASY3 was performed using the measurement equipment listed in Section 4. The test was conducted on the same day as the measurement of the DUT. The obtained results are displayed in the table below. The distributions of SAR compare well with those of the reference measurements (see Appendix 1).

f (MHz)	Description	SAR (W/kg), 1gram	Dielectric Parameters		Temp (°C)
			e_r	s (S/m)	
835	**Measured**	8.72	43.51	0.83	23
	Recommended Limits	9.12	44.30	0.80	NA
1800	**Measured**	38.09	39.65	1.72	23
	Recommended Limits	38.39	41.20	1.68	NA

Appendix 1

SAR distribution comparison for the system accuracy verification

Dipole 835 MHz

835 MHz Dipole Validation / Dipole Sn# 416 / Forward Power = 246mW
Acceptable Temp Range is 15-25°C, Temp at time of measurement = 23
Amy Twin Optics OFF; Section 1
Probe: ET3DV6 - SN1390 - Validation; ConvF(6.75,6.75,6.75); Crest factor: 1.0; Validation 835 MHz: σ = 0.83 mho/m ε_r = 43.5 ρ = 1.00 g/cm^3
Cubes (2): Peak: 3.31 mW/g ± 0.07 dB, SAR (1g): 2.17 mW/g ± 0.06 dB, SAR (10g): 1.43 mW/g ± 0.05 dB, (Worst-case extrapolation)



Dipole 1800 MHz

1800 MHz Dipole Validation / Dipole Sn#246 / Forward Power = 246mW
Acceptable Temp Range is 15-25°C, Temp at time of measurement = 23
Amy Twin Optics OFF; Section 1
Probe: ET3DV6 - SN1390 - Validation; ConvF(5.94,5.94,5.94); Crest factor: 1.0; Validation 1800 MHz: σ = 1.72 mho/m ε_r = 39.6 ρ = 1.00 g/cm^3
Cubes (2): Peak: 18.1 mW/g ± 0.05 dB, SAR (1g): 9.37 mW/g ± 0.05 dB, SAR (10g): 4.74 mW/g ± 0.05 dB, (Worst-case extrapolation)



Appendix 2

SAR distribution plots for Phantom Head Adjacent Use

s/n A07526

Ch# 384 / Pwr Step: 02 / Antenna Position: Extended
Left Head (Barney) Phantom; Left Head Section; Position: (80°,180°); Frequency: 837 MHz
Probe: ET3DV6 - SN1390 - Head (Sugar Water); ConvF(6.75,6.75,6.75); Crest factor: 1.0; Head 835 MHz: σ = 0.86 mho/m ε_r = 43.4 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 1.27 mW/g, SAR (10g): 0.880 mW/g, (Worst-case extrapolation)
Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0
Penetration depth: 17.2 (15.1, 19.0) [mm]
Powerdrift: -0.03 dB



s/n A07526

Ch# 384 / Pwr Step: 02 / Antenna Position: Retracted
Left Head (Barney) Phantom; Left Head Section; Position: (80°,180°); Frequency: 837 MHz
Probe: ET3DV6 - SN1390 - Head (Sugar Water); ConvF(6.75,6.75,6.75); Crest factor: 1.0; Head 835 MHz: σ = 0.86 mho/m ε_r = 43.4 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 1.32 mW/g, SAR (10g): 0.910 mW/g, (Worst-case extrapolation)
Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0
Penetration depth: 16.4 (14.7, 18.0) [mm]
Powerdrift: -0.02 dB



s/n A07526

Ch# 25 / Antenna Position: extended / Type of Modulation: 1900 CDMA
Left Head (Desi) Phantom; Left Head Section; Position: (80°,180°); Frequency: 1850 MHz
Probe: ET3DV6 - SN1390 - Head (Glycol); ConvF(5.37,5.37,5.37); Crest factor: 1.0; Head Glycol 1900 MHz: σ = 1.43 mho/m ε_r = 39.5 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 1.16 mW/g, SAR (10g): 0.737 mW/g, (Worst-case extrapolation)
Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0
Penetration depth: 12.1 (11.4, 12.8) [mm]
Powerdrift: -0.13 dB



s/n A07526

Ch# 650 / Antenna Position: Retracted / Type of Modulation: 1900 CDMA
Left Head (Desi) Phantom; Left Head Section; Position: (80°,180°); Frequency: 1882 MHz
Probe: ET3DV6 - SN1390 - Head (Glycol); ConvF(5.37,5.37,5.37); Crest factor: 1.0; Head Glycol 1900 MHz: σ = 1.43 mho/m ε_r = 39.5 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 1.33 mW/g, SAR (10g): 0.852 mW/g * Max outside, (Worst-case extrapolation)
Coarse: Dx = 10.0, Dy = 10.0, Dz = 10.0
Penetration depth: 11.8 (11.5, 12.2) [mm]
Powerdrift: -0.05 dB





Figure 1. Front of Phone with typical 800MHz Contour Plot Overlaid.



Figure 2. Front of Phone with typical 1900MHz Contour Plot Overlaid.

Appendix 3

SAR distribution plots for Body Worn Configuration

s/n A07526

Ch# 799/ Pwr Step:02 / Antenna Position: extended / Body Worn
Amy Twin Optics OFF Phantom; Section2 Section; Position: (0°,0°); Frequency: 848 MHz
Probe: ET3DV6 - SN1390 - Muscle (Sugar Water); ConvF(6.70,6.70,6.70); Crest factor: 1.0; Muscle 835 MHz: σ = 1.08 mho/m ε_r = 50.5 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 0.632 mW/g, SAR (10g): 0.429 mW/g, (Worst-case extrapolation)
Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0
Penetration depth: 13.8 (12.5, 15.4) [mm]
Powerdrift: -0.00 dB





s/n A07526

Ch# 384/ Pwr Step:02 / Antenna Position: RETRACTED / Body Worn
Amy Twin Optics OFF Phantom; Section2 Section; Position: (0°,0°); Frequency: 836 MHz
Probe: ET3DV6 - SN1390 - Muscle (Sugar Water); ConvF(6.70,6.70,6.70); Crest factor: 1.0; Muscle 835 MHz: σ = 1.08 mho/m ε_r = 50.5 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 0.464 mW/g, SAR (10g): 0.318 mW/g, (Worst-case extrapolation)
Coarse: Dx = 15.0, Dy = 13.0, Dz = 10.0
Penetration depth: 14.3 (13.3, 15.5) [mm]
Powerdrift: -0.04 dB





s/n A07526

Ch# 650 / Antenna Position: Extended / Type of Modulation: 1900 CDMA
Amy Twin Optics OFF Phantom; Section2 Section; Position: (0°,0°); Frequency: 1882 MHz
Probe: ET3DV6 - SN1390- Muscle (Glycol); ConvF(5.09,5.09,5.09); Crest factor: 1.0; Muscle Glycol 1900 MHz: σ = 1.64 mho/m ε_r = 48.8 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 0.398 mW/g, SAR (10g): 0.246 mW/g, (Worst-case extrapolation)
Coarse: Dx = 15.0, Dy = 15.0, Dz = 10.0
Penetration depth: 10.3 (9.0, 12.4) [mm]
Powerdrift: -0.14 dB



s/n A07526

Ch# 25 / Antenna Position: Retracted / Type of Modulation: 1900 CDMA
Amy Twin Optics OFF Phantom; Section2 Section; Position: (0°,0°); Frequency: 1851 MHz
Probe: ET3DV6 - SN1390- Muscle (Glycol); ConvF(5.09,5.09,5.09); Crest factor: 1.0; Muscle Glycol 1900 MHz: σ = 1.64 mho/m ε_r = 48.8 ρ = 1.00 g/cm^3
Cube 5x5x7: SAR (1g): 0.419 mW/g, SAR (10g): 0.259 mW/g, (Worst-case extrapolation)
Coarse: Dx = 15.0, Dy = 13.0, Dz = 10.0
Penetration depth: 10.7 (9.2, 12.8) [mm]
Powerdrift: -0.17 dB



Appendix 4

Photographs of the device under test

Figure 3. Front of Phone with Antenna Extended

Figure 4. Front of Phone with Antenna Retracted

Figure 5. Side of Phone with Antenna Extended

Figure 6. Side of Phone with Antenna Retracted

Figure 7. Phone against Phantom Head with Antenna Extended.

Figure 8. Phone against Phantom Head with Antenna Retracted.



Figure 9. Phone is Supplied Belt Clip.