



# FCC RF Test Report

APPLICANT : Motorola Mobility LLC  
EQUIPMENT : Mobile Cellular Phone  
BRAND NAME : Motorola  
MODEL NAME : XT2243-1  
FCC ID : IHDT56AF5  
STANDARD : FCC Part 15 Subpart C §15.247  
CLASSIFICATION : (DSS) Spread Spectrum Transmitter  
TEST DATE(S) : May 27, 2022 ~ Jun. 20, 2022

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia



Approved by: Jason Jia

**Sporton International Inc. (ShenZhen)**

**1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055**

**People's Republic of China**



## TABLE OF CONTENTS

|                                                                 |           |
|-----------------------------------------------------------------|-----------|
| <b>REVISION HISTORY.....</b>                                    | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                             | <b>4</b>  |
| <b>1 GENERAL DESCRIPTION.....</b>                               | <b>5</b>  |
| 1.1 Applicant.....                                              | 5         |
| 1.2 Manufacturer.....                                           | 5         |
| 1.3 Product Feature of Equipment Under Test.....                | 5         |
| 1.4 Product Specification of Equipment Under Test.....          | 5         |
| 1.5 Modification of EUT .....                                   | 6         |
| 1.6 Testing Location .....                                      | 6         |
| 1.7 Test Software.....                                          | 6         |
| 1.8 Applicable Standards.....                                   | 7         |
| 1.9 Specification of Accessory.....                             | 7         |
| <b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....</b>        | <b>8</b>  |
| 2.1 Carrier Frequency Channel .....                             | 8         |
| 2.2 Test Mode.....                                              | 9         |
| 2.3 Connection Diagram of Test System.....                      | 10        |
| 2.4 Support Unit used in test configuration and system .....    | 10        |
| 2.5 EUT Operation Test Setup .....                              | 10        |
| 2.6 Measurement Results Explanation Example.....                | 11        |
| <b>3 TEST RESULT .....</b>                                      | <b>12</b> |
| 3.1 Number of Channel Measurement .....                         | 12        |
| 3.2 Hopping Channel Separation Measurement .....                | 14        |
| 3.3 Dwell Time Measurement.....                                 | 24        |
| 3.4 20dB and 99% Bandwidth Measurement .....                    | 27        |
| 3.5 Output Power Measurement.....                               | 46        |
| 3.6 Conducted Band Edges Measurement.....                       | 47        |
| 3.7 Conducted Spurious Emission Measurement .....               | 60        |
| 3.8 Radiated Band Edges and Spurious Emission Measurement ..... | 79        |
| 3.9 AC Conducted Emission Measurement.....                      | 83        |
| 3.10 Antenna Requirements.....                                  | 85        |
| <b>4 LIST OF MEASURING EQUIPMENT.....</b>                       | <b>86</b> |
| <b>5 UNCERTAINTY OF EVALUATION.....</b>                         | <b>87</b> |
| <b>APPENDIX A. CONDUCTED TEST RESULTS</b>                       |           |
| <b>APPENDIX B. AC CONDUCTED EMISSION TEST RESULT</b>            |           |
| <b>APPENDIX C. RADIATED SPURIOUS EMISSION</b>                   |           |
| <b>APPENDIX D. DUTY CYCLE PLOTS</b>                             |           |
| <b>APPENDIX E. SETUP PHOTOGRAPHS</b>                            |           |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FR242301A  | Rev. 01 | Initial issue of report | Jun. 29, 2022 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule           | Description                                        | Limit                                  | Result      | Remark                                    |
|----------------|--------------------|----------------------------------------------------|----------------------------------------|-------------|-------------------------------------------|
| 3.1            | 15.247(a)(1)       | Number of Channels                                 | $\geq 15\text{Chs}$                    | Pass        | -                                         |
| 3.2            | 15.247(a)(1)       | Hopping Channel Separation                         | $\geq 2/3$ of 20dB BW                  | Pass        | -                                         |
| 3.3            | 15.247(a)(1)       | Dwell Time of Each Channel                         | $\leq 0.4\text{sec}$ in 31.6sec period | Pass        | -                                         |
| 3.4            | 15.247(a)(1)       | 20dB Bandwidth                                     | -                                      | Report only | -                                         |
| 3.4            | -                  | 99% Bandwidth                                      | -                                      | Report only | -                                         |
| 3.5            | 15.247(b)(1)       | Peak Output Power                                  | $\leq 125\text{ mW}$                   | Pass        | -                                         |
| 3.6            | 15.247(d)          | Conducted Band Edges                               | $\leq 20\text{dBc}$                    | Pass        | -                                         |
| 3.7            | 15.247(d)          | Conducted Spurious Emission                        | $\leq 20\text{dBc}$                    | Pass        | -                                         |
| 3.8            | 15.247(d)          | Radiated Band Edges and Radiated Spurious Emission | 15.209(a) & 15.247(d)                  | Pass        | Under limit<br>13.13 dB at<br>940.830 MHz |
| 3.9            | 15.207             | AC Conducted Emission                              | 15.207(a)                              | Pass        | Under limit<br>5.04 dB at<br>0.150 MHz    |
| 3.10           | 15.203 & 15.247(b) | Antenna Requirement                                | 15.203 & 15.247(b)                     | Pass        | -                                         |

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



# 1 General Description

## 1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

## 1.3 Product Feature of Equipment Under Test

| Product Feature |                                                                                                                                         |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Equipment       | Mobile Cellular Phone                                                                                                                   |
| Brand Name      | Motorola                                                                                                                                |
| Model Name      | XT2243-1                                                                                                                                |
| IMEI Code       | Conducted: 353593830017874/353593830017882<br>Conduction: 353593830020878/353593830020886<br>Radiation: 353593830019656/353593830019664 |
| FCC ID          | IHDT56AF5                                                                                                                               |
| HW Version      | DVT2                                                                                                                                    |
| SW Version      | SSJ32.60                                                                                                                                |
| EUT Stage       | Identical Prototype                                                                                                                     |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Product Specification of Equipment Under Test

| Standards-related Product Specification |                                                                                                                                                                                                                                                                                                                |
|-----------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Tx/Rx Frequency Range                   | 2402 MHz ~ 2480 MHz                                                                                                                                                                                                                                                                                            |
| Number of Channels                      | 79                                                                                                                                                                                                                                                                                                             |
| Carrier Frequency of Each Channel       | 2402+n*1 MHz; n=0~78                                                                                                                                                                                                                                                                                           |
| Maximum Output Power to Antenna         | <Ant 1><br>Bluetooth BR(1Mbps) : 11.40 dBm (0.0138 W)<br>Bluetooth EDR (2Mbps) : 10.90 dBm (0.0123 W)<br>Bluetooth EDR (3Mbps) : 11.00 dBm (0.0126 W)<br><Ant 2><br>Bluetooth BR(1Mbps) : 11.40 dBm (0.0138 W)<br>Bluetooth EDR (2Mbps) : 11.10 dBm (0.0129 W)<br>Bluetooth EDR (3Mbps) : 11.20 dBm (0.0132 W) |
| 99% Occupied Bandwidth                  | <Ant 1><br>Bluetooth BR(1Mbps) : 0.842MHz<br>Bluetooth EDR (2Mbps) : 1.172MHz<br>Bluetooth EDR (3Mbps) : 1.178MHz<br><Ant 2><br>Bluetooth BR(1Mbps) : 0.839MHz                                                                                                                                                 |

|                            |                                                                                                         |
|----------------------------|---------------------------------------------------------------------------------------------------------|
|                            | Bluetooth EDR (2Mbps) : 1.181MHz<br>Bluetooth EDR (3Mbps) : 1.181MHz                                    |
| <b>Antenna Type / Gain</b> | <Ant 1><br>IFA Antenna with gain -3.40 dBi<br><Ant 2><br>IFA Antenna with gain -6.10 dBi                |
| <b>Type of Modulation</b>  | Bluetooth BR (1Mbps) : GFSK<br>Bluetooth EDR (2Mbps) : $\pi/4$ -DQPSK<br>Bluetooth EDR (3Mbps) : 8-DPSK |

Note: Ant.1 corresponding to EUT photo Antenna 5, Ant.2 corresponding to EUT photo Antenna 3.

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.

## 1.6 Testing Location

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

|                           |                                                                                                                                                                         |                            |                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sporton International Inc. (Shenzhen)                                                                                                                                   |                            |                                       |
| <b>Test Site Location</b> | 1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China<br>TEL: +86-755-86379589<br>FAX: +86-755-86379595 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                 | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | CO01-SZ<br>TH01-SZ                                                                                                                                                      | CN1256                     | 421272                                |

|                           |                                                                                                                                                                                           |                            |                                       |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sporton International Inc. (Shenzhen)                                                                                                                                                     |                            |                                       |
| <b>Test Site Location</b> | 101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103<br>TEL: +86-755-33202398 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                                   | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | 03CH04-SZ                                                                                                                                                                                 | CN1256                     | 421272                                |

## 1.7 Test Software

| Item | Site      | Manufacturer | Name | Version     |
|------|-----------|--------------|------|-------------|
| 1.   | 03CH04-SZ | AUDIX        | E3   | 6.2009-8-24 |
| 2.   | CO01-SZ   | AUDIX        | E3   | 6.120613b   |

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.247
- ♦ FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ♦ ANSI C63.10-2013

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

## 1.9 Specification of Accessory

| Specification of Accessory       |            |                    |            |                       |
|----------------------------------|------------|--------------------|------------|-----------------------|
| AC Adapter (US)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-681L               |
| AC Adapter (EU)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-682L               |
| AC Adapter (UK)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-683L               |
| AC Adapter (AU)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-685L               |
| AC Adapter (AR)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-686L               |
| AC Adapter (BR)                  | Brand Name | Motorola (Salcomp) | Model Name | MC-687L               |
| AC Adapter (PRC)                 | Brand Name | Motorola (Salcomp) | Model Name | MC-688L               |
| AC Adapter (CHILE)               | Brand Name | Motorola (Salcomp) | Model Name | MC-689L               |
| Battery 1                        | Brand Name | Motorola (ATL)     | Model Name | NP44                  |
| Battery 2                        | Brand Name | Motorola (Sunwoda) | Model Name | NP44                  |
| Earphone 1                       | Brand Name | Motorola (Lyand)   | Model Name | MD211(SH38D20195)     |
| Earphone 2                       | Brand Name | Motorola (LCHSE)   | Model Name | MD211(SH38D41948)     |
| USB Cable                        | Brand Name | Motorola (Saibao)  | Model Name | SC18D58980\SC18D24968 |
| Type C to HDMI HDMI/USBC Cable 1 | Brand Name | Motorola (Linxee)  | Model Name | SC18D02146            |
| Type C to HDMI HDMI/USBC Cable 2 | Brand Name | Motorola (Linxee)  | Model Name | SC18D38847            |



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

| Frequency Band  | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) | Channel | Freq.<br>(MHz) |
|-----------------|---------|----------------|---------|----------------|---------|----------------|
| 2400-2483.5 MHz | 0       | 2402           | 27      | 2429           | 54      | 2456           |
|                 | 1       | 2403           | 28      | 2430           | 55      | 2457           |
|                 | 2       | 2404           | 29      | 2431           | 56      | 2458           |
|                 | 3       | 2405           | 30      | 2432           | 57      | 2459           |
|                 | 4       | 2406           | 31      | 2433           | 58      | 2460           |
|                 | 5       | 2407           | 32      | 2434           | 59      | 2461           |
|                 | 6       | 2408           | 33      | 2435           | 60      | 2462           |
|                 | 7       | 2409           | 34      | 2436           | 61      | 2463           |
|                 | 8       | 2410           | 35      | 2437           | 62      | 2464           |
|                 | 9       | 2411           | 36      | 2438           | 63      | 2465           |
|                 | 10      | 2412           | 37      | 2439           | 64      | 2466           |
|                 | 11      | 2413           | 38      | 2440           | 65      | 2467           |
|                 | 12      | 2414           | 39      | 2441           | 66      | 2468           |
|                 | 13      | 2415           | 40      | 2442           | 67      | 2469           |
|                 | 14      | 2416           | 41      | 2443           | 68      | 2470           |
|                 | 15      | 2417           | 42      | 2444           | 69      | 2471           |
|                 | 16      | 2418           | 43      | 2445           | 70      | 2472           |
|                 | 17      | 2419           | 44      | 2446           | 71      | 2473           |
|                 | 18      | 2420           | 45      | 2447           | 72      | 2474           |
|                 | 19      | 2421           | 46      | 2448           | 73      | 2475           |
|                 | 20      | 2422           | 47      | 2449           | 74      | 2476           |
|                 | 21      | 2423           | 48      | 2450           | 75      | 2477           |
|                 | 22      | 2424           | 49      | 2451           | 76      | 2478           |
|                 | 23      | 2425           | 50      | 2452           | 77      | 2479           |
|                 | 24      | 2426           | 51      | 2453           | 78      | 2480           |
|                 | 25      | 2427           | 52      | 2454           | -       | -              |
|                 | 26      | 2428           | 53      | 2455           | -       | -              |


## 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

| Summary table of Test Cases                                                                                                                                                                                                             |                                                                                                           |                                       |                               |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------|---------------------------------------|-------------------------------|
| Test Item                                                                                                                                                                                                                               | Data Rate / Modulation                                                                                    |                                       |                               |
|                                                                                                                                                                                                                                         | Bluetooth BR 1Mbps<br>GFSK                                                                                | Bluetooth EDR 2Mbps<br>$\pi/4$ -DQPSK | Bluetooth EDR 3Mbps<br>8-DPSK |
| Conducted<br>Test Cases                                                                                                                                                                                                                 | Mode 1: CH00_2402 MHz                                                                                     | Mode 4: CH00_2402 MHz                 | Mode 7: CH00_2402 MHz         |
|                                                                                                                                                                                                                                         | Mode 2: CH39_2441 MHz                                                                                     | Mode 5: CH39_2441 MHz                 | Mode 8: CH39_2441 MHz         |
|                                                                                                                                                                                                                                         | Mode 3: CH78_2480 MHz                                                                                     | Mode 6: CH78_2480 MHz                 | Mode 9: CH78_2480 MHz         |
| Radiated<br>Test Cases                                                                                                                                                                                                                  | Bluetooth BR 1Mbps GFSK                                                                                   |                                       |                               |
|                                                                                                                                                                                                                                         | Mode 1: CH00_2402 MHz<br>Mode 2: CH39_2441 MHz<br>Mode 3: CH78_2480 MHz                                   |                                       |                               |
| AC<br>Conducted<br>Emission                                                                                                                                                                                                             | Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable (Charging from Adapter) + Battery 1 |                                       |                               |
| Remark:                                                                                                                                                                                                                                 |                                                                                                           |                                       |                               |
| 1. For radiated test cases, the worst mode data rate 1Mbps was reported only, because this data rate has the highest RF output power at preliminary tests, and no other significantly frequencies found in conducted spurious emission. |                                                                                                           |                                       |                               |
| 2. For Radiated Test Cases, The tests were performed with Adapter and USB Cable.                                                                                                                                                        |                                                                                                           |                                       |                               |

## 2.3 Connection Diagram of Test System



## 2.4 Support Unit used in test configuration and system

| Item | Equipment          | Trade Name | Model Name | FCC ID      | Data Cable | Power Cord      |
|------|--------------------|------------|------------|-------------|------------|-----------------|
| 1.   | Base Station(LTE)  | Anritsu    | MT8820C    | N/A         | N/A        | Unshielded,1.8m |
| 2.   | Base Station       | R&S        | CBT32      | N/A         | N/A        | Unshielded,1.8m |
| 3.   | WLAN AP            | Dlink      | DIR-820L   | KA2IR820LA1 | N/A        | Unshielded,1.8m |
| 4.   | Bluetooth Earphone | Samsung    | EO-MG900   | PYAHS-107W  | N/A        | N/A             |

## 2.5 EUT Operation Test Setup

For Bluetooth function, the engineering test program was provided and enabled to make EUT connect with Bluetooth base station to continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.



## 2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 1.50 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 1.50 + 10 = 11.50(\text{dB})\end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup




##### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.




For Ant 1

Number of Hopping Channel Plot on Channel 00 - 78



Date: 1.JUN.2022 20:49:39

Number of Hopping Channel Plot on Channel 00 - 78



Date: 1.JUN.2022 20:49:53

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


### 3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup






### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

For Ant 1


<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 1.JUN.2022 19:52:30


Channel Separation Plot on Channel 39 - 40



Date: 1.JUN.2022 19:57:20




### Channel Separation Plot on Channel 77 - 78



Date: 1 JUN 2022 20:05:08

### <2Mbps>


### Channel Separation Plot on Channel 00 - 01



Date: 1 JUN 2022 20:11:02




### Channel Separation Plot on Channel 39 - 40



Date: 1.JUN.2022 20:17:19

### Channel Separation Plot on Channel 77 - 78




Date: 1.JUN.2022 20:24:39




<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 1.JUN.2022 20:31:31


Channel Separation Plot on Channel 39 - 40



Date: 1.JUN.2022 20:44:00



### Channel Separation Plot on Channel 77 - 78




Date: 1 JUN 2022 20:48:34

For Ant 2

<1Mbps>


### Channel Separation Plot on Channel 00 - 01



Date: 1 JUN 2022 21:30:05




### Channel Separation Plot on Channel 39 - 40



Date: 1.JUN.2022 21:33:48

### Channel Separation Plot on Channel 77 - 78




Date: 1.JUN.2022 21:40:59




<2Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 1.JUN.2022 21:48:25


Channel Separation Plot on Channel 39 - 40



Date: 1.JUN.2022 21:53:41




### Channel Separation Plot on Channel 77 - 78



Date: 1.JUN.2022 22:02:14

### <3Mbps>


### Channel Separation Plot on Channel 00 - 01



Date: 1.JUN.2022 22:27:16




### Channel Separation Plot on Channel 39 - 40



Date: 1 JUN 2022 22:33:11

### Channel Separation Plot on Channel 77 - 78



Date: 1 JUN 2022 22:39:59

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


#### 3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup






### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

For Ant 1:


Package Transfer Time Plot



Date: 27.MAY.2022 13:39:12

For Ant 2:

Package Transfer Time Plot



Date: 27.MAY.2022 13:37:01

**Remark:**

1. In normal mode, hopping rate is 1600 hops/s with 6 slots (5 Transmit and 1 Receive slot) in 79 hopping channels.  
With channel hopping rate  $(1600 / 6 / 79)$  in Occupancy Time Limit  $(0.4 \times 79)$  (s),  
Hops Over Occupancy Time comes to  $(1600 / 6 / 79) \times (0.4 \times 79) = 106.67$  hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels.  
With channel hopping rate  $(800 / 6 / 20)$  in Occupancy Time Limit  $(0.4 \times 20)$  (s),  
Hops Over Occupancy Time comes to  $(800 / 6 / 20) \times (0.4 \times 20) = 53.33$  hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only


#### 3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
The RBW is set to 1% to 5% of the 99% OBW, the VBW is set to 3 times the RBW;  
Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup





### 3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

#### 20 dB Bandwidth Plot on Channel 00



Date: 1 JUN 2022 19:47:24


#### 20 dB Bandwidth Plot on Channel 39



Date: 1 JUN 2022 19:54:20




### 20 dB Bandwidth Plot on Channel 78



Date: 1 JUN 2022 19:59:04

### <2Mbps>


### 20 dB Bandwidth Plot on Channel 00



Date: 1 JUN 2022 20:06:18




### 20 dB Bandwidth Plot on Channel 39



Date: 1.JUN.2022 20:12:06

### 20 dB Bandwidth Plot on Channel 78



Date: 1.JUN.2022 20:18:44




<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 1.JUN.2022 20:26:01


20 dB Bandwidth Plot on Channel 39



Date: 1.JUN.2022 20:32:52



### 20 dB Bandwidth Plot on Channel 78




Date: 1.JUN.2022 20:44:55

For Ant 2:

<1Mbps>


### 20 dB Bandwidth Plot on Channel 00



Date: 1.JUN.2022 21:25:16




### 20 dB Bandwidth Plot on Channel 39



Date: 1.JUN.2022 21:31:12

### 20 dB Bandwidth Plot on Channel 78




Date: 1.JUN.2022 21:35:21




<2Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 1.JUN.2022 21:42:35


20 dB Bandwidth Plot on Channel 39



Date: 1.JUN.2022 21:49:31




### 20 dB Bandwidth Plot on Channel 78



Date: 1.JUN.2022 21:55:36

### <3Mbps>


### 20 dB Bandwidth Plot on Channel 00



Date: 1.JUN.2022 22:44:48




### 20 dB Bandwidth Plot on Channel 39



Date: 1 JUN 2022 22:29:14

### 20 dB Bandwidth Plot on Channel 78



Date: 1 JUN 2022 22:34:05




### 3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

For Ant 1:


<1Mbps>

#### 99% Occupied Bandwidth Plot on Channel 00



Date: 1.JUN.2022 19:48:27


#### 99% Occupied Bandwidth Plot on Channel 39



Date: 1.JUN.2022 19:54:55




99% Occupied Bandwidth Plot on Channel 78



Date: 1.JUN.2022 20:00:44

<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 1.JUN.2022 20:07:33




### 99% Occupied Bandwidth Plot on Channel 39



Date: 1 JUN 2022 20:12:47

### 99% Occupied Bandwidth Plot on Channel 78




Date: 1 JUN 2022 20:19:52




<3Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 1.JUN.2022 20:27:39


99% Occupied Bandwidth Plot on Channel 39



Date: 1.JUN.2022 20:33:36



99% Occupied Bandwidth Plot on Channel 78



Date: 1.JUN.2022 20:45:55

For Ant 2:

<1Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 1.JUN.2022 21:26:11




### 99% Occupied Bandwidth Plot on Channel 39



Date: 1.JUN.2022 21:31:48

### 99% Occupied Bandwidth Plot on Channel 78




Date: 1.JUN.2022 21:37:40




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 1.JUN.2022 21:43:55


99% Occupied Bandwidth Plot on Channel 39



Date: 1.JUN.2022 21:50:11




99% Occupied Bandwidth Plot on Channel 78



Date: 1 JUN 2022 21:57:24

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 1 JUN 2022 22:23:48




### 99% Occupied Bandwidth Plot on Channel 39



Date: 1.JUN.2022 22:29:52

### 99% Occupied Bandwidth Plot on Channel 78



Date: 1.JUN.2022 22:49:02

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts. The power limit for 1Mbps, 2Mbps, 3Mbps and AFH modes are 0.125 watts.


### 3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.


### 3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges

For Ant 1:


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 1.JUN.2022 19:47:46

#### High Band Edge Plot on Channel 78




Date: 1.JUN.2022 20:00:04




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 1 JUN 2022 20:06:49


High Band Edge Plot on Channel 78



Date: 1 JUN 2022 20:19:11


<3Mbps>

### Low Band Edge Plot on Channel 00



Date: 1.JUN.2022 20:26:40

### High Band Edge Plot on Channel 78




Date: 1.JUN.2022 20:45:18



For Ant 2:


<1Mbps>

### Low Band Edge Plot on Channel 00



Date: 1.JUN.2022 21:25:37

### High Band Edge Plot on Channel 78




Date: 1.JUN.2022 21:36:48




<2Mbps>

### Low Band Edge Plot on Channel 00



Date: 1.JUN.2022 21:42:55


### High Band Edge Plot on Channel 78



Date: 1.JUN.2022 21:56:01


**<3Mbps>**

### Low Band Edge Plot on Channel 00



Date: 1.JUN.2022 22:45:27

### High Band Edge Plot on Channel 78



Date: 1.JUN.2022 22:48:06



### 3.6.6 Test Result of Conducted Hopping Mode Band Edges

For Ant 1:


<1Mbps>

#### Hopping Mode Low Band Edge Plot



Date: 1.JUN.2022 20:49:16

#### Hopping Mode High Band Edge Plot




Date: 1.JUN.2022 20:50:16




<2Mbps>

### Hopping Mode Low Band Edge Plot



Date: 1.JUN.2022 20:55:11

### Hopping Mode High Band Edge Plot



Date: 1.JUN.2022 20:55:57