



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2301-1
FCC ID : IHDT56AH1
STANDARD : 47 CFR Part 2, 22(H), 24(E), 27(D), 27(F), 27(H),
27(L), 27(M), 27(N), 90(R)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Nov. 01, 2022

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	6
1.1 Applicant	6
1.2 Manufacturer	6
1.3 Product Feature of Equipment Under Test	6
1.4 Product Specification of Equipment Under Test	6
1.5 Modification of EUT	7
1.6 Testing Location	7
1.7 Test Software	7
1.8 Applicable Standards	8
1.9 Specification of Accessory	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system	10
2.4 Frequency List of Low/Middle/High Channels	11
3 RADIATED TEST ITEMS	14
3.1 Measuring Instruments	14
3.2 Test Setup	14
3.3 Test Result of Radiated Test	15
3.4 Radiated Spurious Emission	16
4 LIST OF MEASURING EQUIPMENT	18
5 UNCERTAINTY OF EVALUATION	19
APPENDIX A. TEST RESULTS OF RADIATED TEST	
APPENDIX B. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG292622I	Rev. 01	Initial issue of report	Dec. 12, 2022



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
-	§2.1046	Conducted Output Power	-	Report Only	1
	§22.913(a)(5)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	1
	§27.50(b)(10) §27.50(c)(10) §90.542 (a)(7)	Effective Radiated Power (Band 12) (Band 13) (Band 14)	ERP < 3 Watt		1
	§24.232(c)	Equivalent Isotropic Radiated Power (Band 2)	EIRP < 2Watt		1
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4) (Band 66)	EIRP < 1Watt		1
	§27.50 (a)(3)	EIRP (Band 30)	EIRP < 250mW/5MHz		1
	§27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 7)	EIRP < 2Watt		1
-	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	1
-	§2.1049	Occupied Bandwidth	-	Report Only	1
-	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2)(4) §27.53(g) §27.53(h) §90.543 (e)(2)(3) §27.53 (a)(4)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 66)(Band 14) (Band 30)	< 43+10log ₁₀ (P[Watts])	PASS	1
	§2.1051 §27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	§27.53(m)(4)		
-	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(g) §27.53(h) §90.543 (e)(3)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 66) (Band 14)	< 43+10log ₁₀ (P[Watts])	PASS	1
	§2.1051 §27.53 (a)(4)	Conducted Spurious Emission (Band 30)	< 70+10log ₁₀ (P[Watts])		
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log ₁₀ (P[Watts])		
-	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22	PASS	1
	§90.539 (e)		< ±1.25 ppm		
	§2.1055 §24.235 §27.54		Within Authorized Band		

3.4	§2.1053 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(f) §27.53(g) §27.53(h) §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 66) (Band 14)	$< 43 + 10\log_{10}(P[\text{Watts}])$	PASS	Under limit 13.24 dB at 9222.000 MHz
	§27.53 (a)(4)	Radiated Spurious Emission (Band 30)	$< 70 + 10\log_{10}(P[\text{Watts}])$		
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	$< 55 + 10\log_{10}(P[\text{Watts}])$		

Remark 1 : The test items of inter band CA were cover by LTE single carrier due to the CA power is reduced according to 3GPP MPR.

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2301-1
FCC ID	IHDT56AH1
IMEI Code	Radiation: 350007550014055/350007550014063
HW Version	DVT2
SW Version	TTR33.124
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7 : 2500 MHz ~ 2570 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 14 : 788 MHz ~ 798 MHz LTE Band 30 : 2305 MHz ~ 2315 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 7 : 2620 MHz ~ 2690 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 13 : 746 MHz ~ 756 MHz LTE Band 14 : 758 MHz ~ 768 MHz LTE Band 30 : 2350 MHz ~ 2360 MHz LTE Band 66 : 2110 MHz ~ 2200 MHz
Uplink CA Bands	2A-4A, 2A-5A, 2A-7A, 2A-12A, 2A-13A, 2A-14A, 2A-30A, 2A-66A 4A-2A, 4A-5A, 4A-12A, 4A-13A 5A-2A, 5A-4A, 5A-7A, 5A-30A, 5A-66A

	7A-2A, 7A-5A, 12A-2A, 12A-4A, 12A-30A, 12A-66A 13A-2A, 13A-4A, 13A-66A 14A-2A, 14A-30A, 14A-66A 30A-2A, 30A-5A, 30A-12A, 30A-14A, 66A-2A, 66A-5A, 66A-12A, 66A-13A, 66A-14A
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City Guangdong Province China 518103 TEL: +86-755-33202398		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH03-SZ	CN1256	421272

1.7 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH03-SZ	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(D), 27(F), 27(H), 27(L) , 27(M), 27(N), 90(R)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Chenyang)	Model Name	MC-681N
AC Adapter 2(US)	Brand Name	Motorola (Acbel)	Model Name	MC-681N
Battery 1	Brand Name	Motorola(SCUD)	Model Name	PC51
Earphone 1	Brand Name	Motorola (Lyand)	Model Name	MI181C(SH38D62338)
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18D24968
C to HDMI HDMI/USBC Cable 1	Brand Name	Motorola(Linxee)	Model Name	SC18D02146
C to HDMI HDMI/USBC Cable 2	Brand Name	Motorola(Linxee)	Model Name	SC18D38847



2 Test Configuration of Equipment Under Test

2.1 Test Mode


Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Radiated Spurious Emission	2A-4A	Worst Case														v	
	2A-5A	Worst Case														v	
	2A-7A	Worst Case														v	
	2A-12A	Worst Case														v	
	2A-13A	Worst Case														v	
	2A-14A	Worst Case														v	
	2A-30A	Worst Case														v	
	2A-66A	Worst Case														v	
	4A-2A	Worst Case														v	
	4A-5A	Worst Case														v	
	4A-12A	Worst Case														v	
	4A-13A	Worst Case														v	
	5A-2A	Worst Case														v	
	5A-4A	Worst Case														v	
	5A-7A	Worst Case														v	
	5A-30A	Worst Case														v	
	5A-66A	Worst Case														v	
	7A-2A	Worst Case														v	
	7A-5A	Worst Case														v	
	12A-2A	Worst Case														v	
	12A-4A	Worst Case														v	
	12A-30A	Worst Case														v	
	12A-66A	Worst Case														v	
	13A-2A	Worst Case														v	
	13A-4A	Worst Case														v	
	13A-66A	Worst Case														v	
	14A-2A	Worst Case														v	
	14A-30A	Worst Case														v	
	14A-66A	Worst Case														v	
	30A-2A	Worst Case														v	
	30A-5A	Worst Case														v	
	30A-12A	Worst Case														v	
	30A-14A	Worst Case														v	
	66A-2A	Worst Case														v	

	66A-5A	Worst Case		v	
	66A-12A	Worst Case		v	
	66A-13A	Worst Case		v	
	66A-14A	Worst Case		v	
Note	1. The mark "v" means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.				

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m



2.4 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3



LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5

LTE Band 14 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5

LTE Band 30 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	27710	-
	Frequency	-	2310	-
5	Channel	27685	27710	27735
	Frequency	2307.5	2310	2312.5

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3


3 Radiated Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 For radiated test below 30MHz



3.2.2 For radiated test from 30MHz to 1GHz



3.2.3 For radiated test above 1GHz



3.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix A.

3.4 Radiated Spurious Emission

3.4.1 Description of Radiated Spurious Emission

For LTE Band 2, 4, 5, 12, 14, 66

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

For LTE Band 14

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

For LTE Band 30

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $70 + 10 \log (P)$ dB.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP\ (dBm) = S.G.\ Power - Tx\ Cable\ Loss + Tx\ Antenna\ Gain$
11. $ERP\ (dBm) = EIRP - 2.15$
12. For Band 2, 4, 5, 12, 13, 14, 66
The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10\log(P)]\ (dB)$
 $= [30 + 10\log(P)]\ (dBm) - [43 + 10\log(P)]\ (dB)$
 $= -13dBm.$
13. For Band 30:
The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
The limit line is derived from $70 + 10\log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [70 + 10\log(P)]\ (dB)$
 $= [30 + 10\log(P)]\ (dBm) - [70 + 10\log(P)]\ (dB)$
 $= -40dBm.$
14. For Band 7:
The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver&SA	KEYSIGHT	N9038A	MY54450083	20Hz~8.4GHz	Apr. 06, 2022	Nov. 01, 2022	Apr. 05, 2023	Radiation (03CH03-SZ)
Loop Antenna	R&S	HFH2-Z2	100354	9kHz~30MHz	Jun. 28, 2022	Nov. 01, 2022	Jun. 27, 2024	Radiation (03CH03-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150246	10Hz~44GHz;	Apr. 06, 2022	Nov. 01, 2022	Apr. 05, 2023	Radiation (03CH03-SZ)
Bilog Antenna	TeseQ	CBL6112D	35408	30MHz~2GHz	Aug. 09, 2021	Nov. 01, 2022	Aug. 08, 2023	Radiation (03CH03-SZ)
Double Ridge Horn Antenna	SCHWARZBECK	BBHA9120D	9120D-1355	1GHz~18GHz	Apr. 08, 2022	Nov. 01, 2022	Apr. 07, 2023	Radiation (03CH03-SZ)
Amplifier	Burgeon	BPA-530	102211	0.01Hz ~3000MHz	Oct. 19, 2022	Nov. 01, 2022	Oct. 18, 2023	Radiation (03CH03-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 06, 2022	Nov. 01, 2022	Jul. 05, 2023	Radiation (03CH03-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 10, 2022	Nov. 01, 2022	Apr. 09, 2023	Radiation (03CH03-SZ)
Amplifier	Agilent Technologies	83017A	MY39501302	500MHz~26.5GHz	Dec. 27,2021	Nov. 01, 2022	Dec. 26,2022	Radiation (03CH03-SZ)
AC Power Source	Chroma	61601	616010002729	N/A	Nov. 10, 2022	Nov. 01, 2022	Nov. 09, 2023	Radiation (03CH03-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Nov. 01, 2022	NCR	Radiation (03CH03-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Nov. 01, 2022	NCR	Radiation (03CH03-SZ)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.0dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.60dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.80dB
---	--------



Appendix A. Test Results of Radiated Test

Radiated Spurious Emission

ULCA_2A-4A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-53.85	-13	-40.85	-68.28	-60.60	5.85	12.60	H
	5613.27	-51.95	-13	-38.95	-68.79	-57.75	7.30	13.10	H
	7484.36	-55.81	-13	-42.81	-78.19	-58.96	8.35	11.50	H
	3742.18	-57.74	-13	-44.74	-72.38	-64.49	5.85	12.60	V
	5613.27	-45.65	-13	-32.65	-62.4	-51.45	7.30	13.10	V
	7484.36	-54.60	-13	-41.60	-76.91	-57.75	8.35	11.50	V
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-63.46	-13	-50.46	-75.80	-70.21	5.85	12.60	H
	5170.77	-61.24	-13	-48.24	-78.51	-67.04	7.30	13.10	H
	6894.36	-58.55	-13	-45.55	-78.91	-61.70	8.35	11.50	H
	3447.18	-62.82	-13	-49.82	-75.71	-69.57	5.85	12.60	V
	5170.77	-61.16	-13	-48.16	-78.38	-66.96	7.30	13.10	V
	6894.36	-58.46	-13	-45.46	-78.73	-61.61	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_2A-5A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3782.18	-62.01	-13	-49.01	-76.51	-68.76	5.85	12.60	H
	5673.27	-59.85	-13	-46.85	-76.85	-65.65	7.30	13.10	H
	7564.36	-56.18	-13	-43.18	-78.38	-59.33	8.35	11.50	H
	3782.18	-62.12	-13	-49.12	-76.75	-68.87	5.85	12.60	V
	5673.27	-58.39	-13	-45.39	-75.36	-64.19	7.30	13.10	V
	7564.36	-55.06	-13	-42.06	-77.08	-58.21	8.35	11.50	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1679.18	-66.77	-13	-53.77	-72.87	-70.02	4.00	9.40	H
	2518.77	-63.70	-13	-50.70	-73.87	-67.27	4.88	10.60	H
	3358.36	-63.69	-13	-50.69	-75.51	-68.62	5.52	12.60	H
	1679.18	-67.33	-13	-54.33	-73.17	-70.58	4.00	9.40	V
	2518.77	-64.05	-13	-51.05	-74.55	-67.62	4.88	10.60	V
	3358.36	-63.38	-13	-50.38	-75.62	-68.31	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 2A-7A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-55.55	-13	-42.55	-69.98	-62.30	5.85	12.60	H
	5613.27	-52.74	-13	-39.74	-69.58	-58.54	7.30	13.10	H
	7484.36	-55.30	-13	-42.30	-77.68	-58.45	8.35	11.50	H
	3742.18	-60.47	-13	-47.47	-75.11	-67.22	5.85	12.60	V
	5613.27	-54.02	-13	-41.02	-70.77	-59.82	7.30	13.10	V
	7484.36	-53.26	-13	-40.26	-75.57	-56.41	8.35	11.50	V
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.18	-59.99	-25	-34.99	-77.41	-65.55	7.14	12.70	H
	7578.27	-55.19	-25	-30.19	-77.35	-58.49	8.30	11.60	H
	10104.36	-52.30	-25	-27.30	-79.19	-53.82	10.48	12.00	H
	5052.18	-59.82	-25	-34.82	-77.17	-65.38	7.14	12.70	V
	7578.27	-55.85	-25	-30.85	-77.81	-59.15	8.30	11.60	V
	10104.36	-52.87	-25	-27.87	-79.27	-54.39	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 2A-12A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.98	-13	-48.98	-76.41	-68.73	5.85	12.60	H
	5613.27	-59.57	-13	-46.57	-76.41	-65.37	7.30	13.10	H
	7484.36	-56.30	-13	-43.30	-78.68	-59.45	8.35	11.50	H
	3742.18	-61.66	-13	-48.66	-76.3	-68.41	5.85	12.60	V
	5613.27	-58.28	-13	-45.28	-75.03	-64.08	7.30	13.10	V
	7484.36	-55.49	-13	-42.49	-77.8	-58.64	8.35	11.50	V
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-64.75	-13	-51.75	-72.71	-68.00	4.00	9.40	H
	2109	-63.47	-13	-50.47	-73.13	-67.04	4.88	10.60	H
	2812	-62.94	-13	-49.94	-74.80	-67.87	5.52	12.60	H
	1406	-64.36	-13	-51.36	-72.40	-67.61	4.00	9.40	V
	2109	-64.49	-13	-51.49	-74.52	-68.06	4.88	10.60	V
	2812	-62.99	-13	-49.99	-75.09	-67.92	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 2A-13A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.57	-13	-48.57	-76.00	-68.32	5.85	12.60	H
	5613.27	-55.14	-13	-42.14	-71.98	-60.94	7.30	13.10	H
	7484.36	-55.71	-13	-42.71	-78.09	-58.86	8.35	11.50	H
	3742.18	-61.31	-13	-48.31	-75.95	-68.06	5.85	12.60	V
	5613.27	-55.21	-13	-42.21	-71.96	-61.01	7.30	13.10	V
	7484.36	-55.36	-13	-42.36	-77.67	-58.51	8.35	11.50	V
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-65.65	-13	-52.65	-72.33	-68.90	4.00	9.40	H
	2332.5	-62.81	-13	-49.81	-73.51	-66.38	4.88	10.60	H
	3110	-62.85	-13	-49.85	-75.49	-67.78	5.52	12.60	H
	1555	-65.78	-13	-52.78	-72.67	-69.03	4.00	9.40	V
	2332.5	-62.83	-13	-49.83	-73.92	-66.40	4.88	10.60	V
	3110	-62.28	-13	-49.28	-75.43	-67.21	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 2A-14A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.52	-13	-48.52	-75.95	-68.27	5.85	12.60	H
	5613.27	-59.24	-13	-46.24	-76.08	-65.04	7.30	13.10	H
	7484.36	-55.65	-13	-42.65	-78.03	-58.80	8.35	11.50	H
	3742.18	-61.04	-13	-48.04	-75.68	-67.79	5.85	12.60	V
	5613.27	-56.16	-13	-43.16	-72.91	-61.96	7.30	13.10	V
	7484.36	-52.98	-13	-39.98	-75.29	-56.13	8.35	11.50	V
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-66.62	-13	-53.62	-73.05	-69.87	4.00	9.40	H
	2365.5	-63.48	-13	-50.48	-74.05	-67.05	4.88	10.60	H
	3154	-62.81	-13	-49.81	-75.63	-67.74	5.52	12.60	H
	1577	-66.17	-13	-53.17	-72.82	-69.42	4.00	9.40	V
	2365.5	-62.90	-13	-49.90	-73.87	-66.47	4.88	10.60	V
	3154	-62.31	-13	-49.31	-75.68	-67.24	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 2A-30A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-60.60	-13	-47.60	-78.47	-67.35	5.85	12.60	H
	5613.27	-50.66	-13	-37.66	-72.92	-56.46	7.30	13.10	H
	7484.36	-57.93	-13	-44.93	-84.26	-61.08	8.35	11.50	H
	3742.18	-63.94	-13	-50.94	-81.73	-70.69	5.85	12.60	V
	5613.27	-50.11	-13	-37.11	-72.56	-55.91	7.30	13.10	V
	7484.36	-56.38	-13	-43.38	-82.7	-59.53	8.35	11.50	V
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.50	-59.24	-40	-19.24	-80.25	-65.49	6.45	12.70	H
	6916.50	-61.33	-40	-21.33	-87.04	-64.73	8.40	11.80	H
	9222.00	-53.44	-40	-13.44	-85.16	-55.79	9.65	12.00	H
	4611.50	-59.96	-40	-19.96	-81.35	-66.21	6.45	12.70	V
	6916.50	-60.67	-40	-20.67	-86.86	-64.07	8.40	11.80	V
	9222.00	-53.83	-40	-13.83	-84.73	-56.18	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 2A-66A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.79	-13	-48.79	-76.22	-68.54	5.85	12.60	H
	5613.27	-48.98	-13	-35.98	-65.82	-54.78	7.30	13.10	H
	7484.36	-55.70	-13	-42.70	-78.08	-58.85	8.35	11.50	H
	3742.18	-61.30	-13	-48.30	-75.94	-68.05	5.85	12.60	V
	5613.27	-51.24	-13	-38.24	-67.99	-57.04	7.30	13.10	V
	7484.36	-53.04	-13	-40.04	-75.35	-56.19	8.35	11.50	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.21	-13	-50.21	-76.06	-69.96	5.85	12.60	H
	5238	-61.49	-13	-48.49	-78.22	-67.29	7.30	13.10	H
	6984	-57.61	-13	-44.61	-78.40	-60.76	8.35	11.50	H
	3492	-62.67	-13	-49.67	-76.05	-69.42	5.85	12.60	V
	5238	-61.19	-13	-48.19	-77.86	-66.99	7.30	13.10	V
	6984	-57.32	-13	-44.32	-78.27	-60.47	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_4A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-61.34	-13	-48.34	-73.68	-68.09	5.85	12.60	H
	5170.77	-53.80	-13	-40.80	-71.07	-59.60	7.30	13.10	H
	6894.36	-58.59	-13	-45.59	-78.95	-61.74	8.35	11.50	H
	3447.18	-60.38	-13	-47.38	-73.27	-67.13	5.85	12.60	V
	5170.77	-59.69	-13	-46.69	-76.91	-65.49	7.30	13.10	V
	6894.36	-58.13	-13	-45.13	-78.4	-61.28	8.35	11.50	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.55	-13	-48.55	-75.98	-68.30	5.85	12.60	H
	5613.27	-60.84	-13	-47.84	-77.68	-66.64	7.30	13.10	H
	7484.36	-55.66	-13	-42.66	-78.04	-58.81	8.35	11.50	H
	3742.18	-61.31	-13	-48.31	-75.95	-68.06	5.85	12.60	V
	5613.27	-59.32	-13	-46.32	-76.07	-65.12	7.30	13.10	V
	7484.36	-55.87	-13	-42.87	-78.18	-59.02	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_4A-5A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-58.85	-13	-45.85	-71.19	-65.70	5.65	12.50	H
	5170.77	-60.36	-13	-47.36	-77.63	-66.03	7.13	12.80	H
	6894.36	-58.82	-13	-45.82	-79.18	-62.22	8.40	11.80	H
	3447.18	-59.93	-13	-46.93	-72.82	-66.78	5.65	12.50	V
	5170.77	-54.58	-13	-41.58	-71.8	-60.25	7.13	12.80	V
	6894.36	-58.69	-13	-45.69	-78.96	-62.09	8.40	11.80	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-67.57	-13	-54.57	-73.68	-70.82	4.00	9.40	H
	2496.27	-61.85	-13	-48.85	-72.04	-65.42	4.88	10.60	H
	3328.36	-64.11	-13	-51.11	-76.08	-69.04	5.52	12.60	H
	1664.18	-67.38	-13	-54.38	-73.26	-70.63	4.00	9.40	V
	2496.27	-63.66	-13	-50.66	-74.19	-67.23	4.88	10.60	V
	3328.36	-63.88	-13	-50.88	-76.26	-68.81	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 4A-12A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-57.77	-13	-44.77	-70.11	-64.62	5.65	12.50	H
	5170.77	-51.39	-13	-38.39	-68.66	-57.06	7.13	12.80	H
	6894.36	-58.83	-13	-45.83	-79.19	-62.23	8.40	11.80	H
	3447.18	-58.56	-13	-45.56	-71.45	-65.41	5.65	12.50	V
	5170.77	-55.41	-13	-42.41	-72.63	-61.08	7.13	12.80	V
	6894.36	-58.10	-13	-45.10	-78.37	-61.50	8.40	11.80	V
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-64.85	-13	-51.85	-72.81	-68.10	4.00	9.40	H
	2109	-64.61	-13	-51.61	-74.27	-68.18	4.88	10.60	H
	2812	-62.89	-13	-49.89	-74.75	-67.82	5.52	12.60	H
	1406	-64.66	-13	-51.66	-72.70	-67.91	4.00	9.40	V
	2109	-64.79	-13	-51.79	-74.82	-68.36	4.88	10.60	V
	2812	-62.78	-13	-49.78	-74.88	-67.71	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 4A-13A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-60.29	-13	-47.29	-72.63	-63.54	4.00	9.40	H
	5170.77	-58.31	-13	-45.31	-75.58	-61.88	4.88	10.60	H
	6894.36	-58.51	-13	-45.51	-78.87	-63.44	5.52	12.60	H
	3447.18	-63.04	-13	-50.04	-75.93	-66.29	4.00	9.40	V
	5170.77	-54.86	-13	-41.86	-72.08	-58.43	4.88	10.60	V
	6894.36	-58.86	-13	-45.86	-79.13	-63.79	5.52	12.60	V
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-66.30	-13	-53.30	-72.98	-73.05	5.85	12.60	H
	2332.5	-55.27	-13	-42.27	-65.97	-61.07	7.30	13.10	H
	3110	-63.05	-13	-50.05	-75.69	-66.20	8.35	11.50	H
	1555	-66.38	-13	-53.38	-73.27	-73.13	5.85	12.60	V
	2332.5	-53.24	-13	-40.24	-64.33	-59.04	7.30	13.10	V
	3110	-62.77	-13	-49.77	-75.92	-65.92	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 5A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-59.94	-13	-46.94	-66.05	-63.19	4.00	9.40	H
	2496.27	-46.43	-13	-33.43	-56.62	-50.00	4.88	10.60	H
	3328.36	-63.84	-13	-50.84	-75.81	-68.77	5.52	12.60	H
	1664.18	-63.84	-13	-50.84	-69.72	-67.09	4.00	9.40	V
	2496.27	-49.61	-13	-36.61	-60.14	-53.18	4.88	10.60	V
	3328.36	-63.49	-13	-50.49	-75.87	-68.42	5.52	12.60	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3702.18	-61.87	-13	-48.87	-76.21	-68.62	5.85	12.60	H
	5553.27	-61.45	-13	-48.45	-78.09	-67.25	7.30	13.10	H
	7404.36	-55.90	-13	-42.90	-78.54	-59.05	8.35	11.50	H
	3702.18	-61.74	-13	-48.74	-76.37	-68.49	5.85	12.60	V
	5553.27	-61.82	-13	-48.82	-78.51	-67.62	7.30	13.10	V
	7404.36	-55.80	-13	-42.80	-78.48	-58.95	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 5A-4A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-61.34	-13	-48.34	-67.45	-64.59	4.00	9.40	H
	2496.27	-52.79	-13	-39.79	-62.98	-56.36	4.88	10.60	H
	3328.36	-64.11	-13	-51.11	-76.08	-69.04	5.52	12.60	H
	1664.18	-65.94	-13	-52.94	-71.82	-69.19	4.00	9.40	V
	2496.27	-51.89	-13	-38.89	-62.42	-55.46	4.88	10.60	V
	3328.36	-63.77	-13	-50.77	-76.15	-68.70	5.52	12.60	V
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-57.31	-13	-44.31	-69.65	-64.16	5.65	12.50	H
	5170.77	-61.29	-13	-48.29	-78.56	-66.96	7.13	12.80	H
	6894.36	-58.99	-13	-45.99	-79.35	-62.39	8.40	11.80	H
	3447.18	-60.27	-13	-47.27	-73.16	-67.12	5.65	12.50	V
	5170.77	-58.92	-13	-45.92	-76.14	-64.59	7.13	12.80	V
	6894.36	-58.88	-13	-45.88	-79.15	-62.28	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 5A-7A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-63.89	-13	-50.89	-70.00	-70.42	4.00	9.40	H
	2496.27	-49.13	-13	-36.13	-59.32	-50.86	4.88	10.60	H
	3328.36	-64.19	-13	-51.19	-76.16	-76.06	5.52	12.60	H
	1664.18	-65.17	-13	-52.17	-71.05	-72.63	4.00	9.40	V
	2496.27	-51.07	-13	-38.07	-61.60	-62.83	4.88	10.60	V
	3328.36	-63.74	-13	-50.74	-76.12	-76.14	5.52	12.60	V
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.18	-60.18	-25	-35.18	-77.60	-65.74	7.14	12.70	H
	7578.27	-50.60	-25	-25.60	-72.76	-53.90	8.30	11.60	H
	10104.36	-52.96	-25	-27.96	-79.85	-54.48	10.48	12.00	H
	5052.18	-59.54	-25	-34.54	-76.89	-65.10	7.14	12.70	V
	7578.27	-48.52	-25	-23.52	-70.48	-51.82	8.30	11.60	V
	10104.36	-53.75	-25	-28.75	-80.15	-55.27	10.48	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 5A-30A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1679.18	-58.70	-13	-45.70	-64.80	-61.95	4.00	9.40	H
	2518.77	-49.47	-13	-36.47	-59.64	-53.04	4.88	10.60	H
	3358.36	-63.45	-13	-50.45	-75.27	-68.38	5.52	12.60	H
	1679.18	-62.96	-13	-49.96	-68.80	-66.21	4.00	9.40	V
	2518.77	-50.28	-13	-37.28	-60.78	-53.85	4.88	10.60	V
	3358.36	-63.45	-13	-50.45	-75.69	-68.38	5.52	12.60	V
LTE B30 BW 100MHz Middle 1RB0,QPSK	4611.50	-62.04	-40	-22.04	-58.98	-68.29	6.45	12.70	H
	6916.50	-61.77	-40	-21.77	-61.70	-65.17	8.40	11.80	H
	9222.00	-53.91	-40	-13.91	-62.70	-56.26	9.65	12.00	H
	4611.50	-62.31	-40	-22.31	-59.1	-68.56	6.45	12.70	V
	6916.50	-61.94	-40	-21.94	-61.83	-65.34	8.40	11.80	V
	9222.00	-54.11	-40	-14.11	-62.48	-56.46	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 5A-66A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-64.31	-13	-51.31	-73.68	-70.42	4.00	9.40	H
	2496.27	-40.67	-13	-27.67	-72.04	-50.86	4.88	10.60	H
	3328.36	-64.09	-13	-51.09	-76.08	-76.06	5.52	12.60	H
	1664.18	-66.75	-13	-53.75	-73.26	-72.63	4.00	9.40	V
	2496.27	-52.30	-13	-39.30	-74.19	-62.83	4.88	10.60	V
	3328.36	-63.76	-13	-50.76	-76.26	-76.14	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.58	-13	-50.58	-76.43	-70.43	5.65	12.50	H
	5238	-61.84	-13	-48.84	-78.57	-67.51	7.13	12.80	H
	6984	-58.09	-13	-45.09	-78.88	-61.49	8.40	11.80	H
	3492	-63.26	-13	-50.26	-76.64	-70.11	5.65	12.50	V
	5238	-50.82	-13	-37.82	-67.49	-56.49	7.13	12.80	V
	6984	-57.98	-13	-44.98	-78.93	-61.38	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 7A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.18	-60.74	-25	-35.74	-78.16	-66.30	7.14	12.70	H
	7578.27	-56.17	-25	-31.17	-78.33	-59.47	8.30	11.60	H
	10104.36	-53.02	-25	-28.02	-79.91	-54.54	10.48	12.00	H
	5052.18	-60.94	-25	-35.94	-78.29	-66.50	7.14	12.70	V
	7578.27	-56.04	-25	-31.04	-78	-59.34	8.30	11.60	V
	10104.36	-53.64	-25	-28.64	-80.04	-55.16	10.48	12.00	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-59.51	-13	-46.51	-73.94	-66.26	5.85	12.60	H
	5613.27	-53.12	-13	-40.12	-69.96	-58.92	7.30	13.10	H
	7484.36	-56.19	-13	-43.19	-78.57	-59.34	8.35	11.50	H
	3742.18	-59.00	-13	-46.00	-73.64	-65.75	5.85	12.60	V
	5613.27	-57.59	-13	-44.59	-74.34	-63.39	7.30	13.10	V
	7484.36	-56.24	-13	-43.24	-78.55	-59.39	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_7A-5A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B7 BW 20MHz Middle 1RB0,QPSK	5052.18	-60.41	-25	-35.41	-77.83	-65.97	7.14	12.70	H
	7578.27	-43.39	-25	-18.39	-65.55	-46.69	8.30	11.60	H
	10104.36	-53.18	-25	-28.18	-80.07	-54.70	10.48	12.00	H
	5052.18	-60.11	-25	-35.11	-77.46	-65.67	7.14	12.70	V
	7578.27	-49.69	-25	-24.69	-71.65	-52.99	8.30	11.60	V
	10104.36	-53.61	-25	-28.61	-80.01	-55.13	10.48	12.00	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-67.30	-13	-54.30	-73.41	-70.42	4.00	9.40	H
	2496.27	-64.28	-13	-51.28	-74.47	-50.86	4.88	10.60	H
	3328.36	-64.27	-13	-51.27	-76.24	-76.06	5.52	12.60	H
	1664.18	-67.52	-13	-54.52	-73.40	-72.63	4.00	9.40	V
	2496.27	-63.87	-13	-50.87	-74.40	-62.83	4.88	10.60	V
	3328.36	-63.84	-13	-50.84	-76.22	-76.14	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_12A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-62.09	-13	-49.09	-70.05	-65.34	4.00	9.40	H
	2109	-51.79	-13	-38.79	-61.45	-55.36	4.88	10.60	H
	2812	-62.72	-13	-49.72	-74.58	-67.65	5.52	12.60	H
	1406	-63.94	-13	-50.94	-71.98	-67.19	4.00	9.40	V
	2109	-54.23	-13	-41.23	-64.26	-57.80	4.88	10.60	V
	2812	-62.66	-13	-49.66	-74.76	-67.59	5.52	12.60	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.64	-13	-48.64	-76.07	-68.39	5.85	12.60	H
	5613.27	-60.68	-13	-47.68	-77.52	-66.48	7.30	13.10	H
	7484.36	-55.44	-13	-42.44	-77.82	-58.59	8.35	11.50	H
	3742.18	-61.35	-13	-48.35	-75.99	-68.10	5.85	12.60	V
	5613.27	-60.83	-13	-47.83	-77.58	-66.63	7.30	13.10	V
	7484.36	-55.95	-13	-42.95	-78.26	-59.10	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 12A-4A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-59.26	-13	-46.26	-67.22	-62.51	4.00	9.40	H
	2109	-47.45	-13	-34.45	-57.11	-51.02	4.88	10.60	H
	2812	-63.20	-13	-50.20	-75.06	-68.13	5.52	12.60	H
	1406	-62.74	-13	-49.74	-70.78	-65.99	4.00	9.40	V
	2109	-50.18	-13	-37.18	-60.21	-53.75	4.88	10.60	V
	2812	-62.72	-13	-49.72	-74.82	-67.65	5.52	12.60	V
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-63.70	-13	-50.70	-76.04	-70.55	5.65	12.50	H
	5170.77	-61.43	-13	-48.43	-78.70	-67.10	7.13	12.80	H
	6894.36	-58.76	-13	-45.76	-79.12	-62.16	8.40	11.80	H
	3447.18	-63.31	-13	-50.31	-76.2	-70.16	5.65	12.50	V
	5170.77	-60.77	-13	-47.77	-77.99	-66.44	7.13	12.80	V
	6894.36	-58.85	-13	-45.85	-79.12	-62.25	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 12A-30A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-58.70	-13	-45.70	-68.82	-61.95	4.00	9.40	H
	2109	-42.12	-13	-29.12	-54.78	-45.69	4.88	10.60	H
	2812	-62.96	-13	-49.96	-78.87	-67.89	5.52	12.60	H
	1406	-63.26	-13	-50.26	-72.94	-66.51	4.00	9.40	V
	2109	-46.58	-13	-33.58	-59.19	-50.15	4.88	10.60	V
	2812	-62.63	-13	-49.63	-78.73	-67.56	5.52	12.60	V
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.50	-57.50	-40	-17.50	-78.51	-63.75	6.45	12.70	H
	6916.50	-61.59	-40	-21.59	-87.30	-64.99	8.40	11.80	H
	9222.00	-53.54	-40	-13.54	-85.26	-55.89	9.65	12.00	H
	4611.50	-61.83	-40	-21.83	-83.22	-68.08	6.45	12.70	V
	6916.50	-61.47	-40	-21.47	-87.66	-64.87	8.40	11.80	V
	9222.00	-54.36	-40	-14.36	-85.26	-56.71	9.65	12.00	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 12A-66A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-62.83	-13	-49.83	-70.79	-66.08	4.00	9.40	H
	2109	-61.67	-13	-48.67	-71.33	-65.24	4.88	10.60	H
	2812	-62.78	-13	-49.78	-74.64	-67.71	5.52	12.60	H
	1406	-63.92	-13	-50.92	-71.96	-67.17	4.00	9.40	V
	2109	-60.48	-13	-47.48	-70.51	-64.05	4.88	10.60	V
	2812	-62.56	-13	-49.56	-74.66	-67.49	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.55	-13	-50.55	-76.40	-70.30	5.85	12.60	H
	5238	-62.27	-13	-49.27	-79.00	-68.07	7.30	13.10	H
	6984	-58.23	-13	-45.23	-79.02	-61.38	8.35	11.50	H
	3492	-63.08	-13	-50.08	-76.46	-69.83	5.85	12.60	V
	5238	-62.39	-13	-49.39	-79.06	-68.19	7.30	13.10	V
	6984	-58.11	-13	-45.11	-79.06	-61.26	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 13A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-62.21	-13	-49.21	-68.89	-68.96	5.85	12.60	H
	2332.5	-47.73	-13	-34.73	-58.43	-53.53	7.30	13.10	H
	3110	-62.79	-13	-49.79	-75.43	-65.94	8.35	11.50	H
	1555	-62.21	-13	-49.21	-69.1	-68.96	5.85	12.60	V
	2332.5	-50.04	-13	-37.04	-61.13	-55.84	7.30	13.10	V
	3110	-62.58	-13	-49.58	-75.73	-65.73	8.35	11.50	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.61	-13	-48.61	-76.04	-64.86	4.00	9.40	H
	5613.27	-58.96	-13	-45.96	-75.80	-62.53	4.88	10.60	H
	7484.36	-55.82	-13	-42.82	-78.20	-60.75	5.52	12.60	H
	3742.18	-61.37	-13	-48.37	-76.01	-64.62	4.00	9.40	V
	5613.27	-61.15	-13	-48.15	-77.90	-64.72	4.88	10.60	V
	7484.36	-56.11	-13	-43.11	-78.42	-61.04	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_13A-4A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-64.68	-13	-51.68	-71.36	-71.43	5.85	12.60	H
	2332.5	-46.55	-13	-33.55	-57.25	-52.35	7.30	13.10	H
	3110	-63.47	-13	-50.47	-76.11	-66.62	8.35	11.50	H
	1555	-65.86	-13	-52.86	-72.75	-72.61	5.85	12.60	V
	2332.5	-49.03	-13	-36.03	-60.12	-54.83	7.30	13.10	V
	3110	-63.03	-13	-50.03	-76.18	-66.18	8.35	11.50	V
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447.18	-63.75	-13	-50.75	-76.09	-67.00	4.00	9.40	H
	5170.77	-55.43	-13	-42.43	-72.70	-59.00	4.88	10.60	H
	6894.36	-58.91	-13	-45.91	-79.27	-63.84	5.52	12.60	H
	3447.18	-63.25	-13	-50.25	-76.14	-66.50	4.00	9.40	V
	5170.77	-56.70	-13	-43.70	-73.92	-60.27	4.88	10.60	V
	6894.36	-59.09	-13	-46.09	-79.36	-64.02	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_13A-66A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-54.07	-13	-41.07	-60.75	-57.32	4.00	9.40	H
	2332.5	-38.79	-13	-25.79	-49.49	-42.36	4.88	10.60	H
	3110	-63.46	-13	-50.46	-76.10	-68.39	5.52	12.60	H
	1555	-58.47	-13	-45.47	-65.36	-61.72	4.00	9.40	V
	2332.5	-43.69	-13	-30.69	-54.78	-47.26	4.88	10.60	V
	3110	-62.78	-13	-49.78	-75.93	-67.71	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.82	-13	-50.82	-76.67	-70.57	5.85	12.60	H
	5238	-62.21	-13	-49.21	-78.94	-68.01	7.30	13.10	H
	6984	-58.34	-13	-45.34	-79.13	-61.49	8.35	11.50	H
	3492	-63.40	-13	-50.40	-76.78	-70.15	5.85	12.60	V
	5238	-62.54	-13	-49.54	-79.21	-68.34	7.30	13.10	V
	6984	-58.16	-13	-45.16	-79.11	-61.31	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 14A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-63.50	-13	-50.50	-69.93	-70.25	5.85	12.60	H
	2365.5	-52.35	-13	-39.35	-62.92	-58.15	7.30	13.10	H
	3154	-62.72	-13	-49.72	-75.54	-65.87	8.35	11.50	H
	1577	-59.36	-13	-46.36	-66.01	-66.11	5.85	12.60	V
	2365.5	-46.84	-13	-33.84	-57.81	-52.64	7.30	13.10	V
	3154	-62.41	-13	-49.41	-75.78	-65.56	8.35	11.50	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3702.18	-61.92	-13	-48.92	-76.26	-65.17	4.00	9.40	H
	5553.27	-61.73	-13	-48.73	-78.37	-65.30	4.88	10.60	H
	7404.36	-56.19	-13	-43.19	-78.83	-61.12	5.52	12.60	H
	3702.18	-61.38	-13	-48.38	-76.01	-64.63	4.00	9.40	V
	5553.27	-61.81	-13	-48.81	-78.50	-65.38	4.88	10.60	V
	7404.36	-55.95	-13	-42.95	-78.63	-60.88	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 14A-30A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-60.17	-13	-47.17	-66.60	-66.92	5.85	12.60	H
	2365.5	-43.77	-13	-30.77	-54.34	-49.57	7.30	13.10	H
	3154	-62.87	-13	-49.87	-75.69	-66.02	8.35	11.50	H
	1577	-60.42	-13	-47.42	-67.07	-67.17	5.85	12.60	V
	2365.5	-44.64	-13	-31.64	-55.61	-50.44	7.30	13.10	V
	3154	-62.33	-13	-49.33	-75.7	-65.48	8.35	11.50	V
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.5	-62.09	-40	-22.09	-67.07	-65.34	4.00	9.40	H
	6916.5	-61.61	-40	-21.61	-55.61	-65.18	4.88	10.60	H
	9222	-53.84	-40	-13.84	-75.70	-58.77	5.52	12.60	H
	4611.5	-61.80	-40	-21.80	-58.59	-65.05	4.00	9.40	V
	6916.5	-61.73	-40	-21.73	-61.62	-65.30	4.88	10.60	V
	9222	-54.15	-40	-14.15	-62.52	-59.08	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 14A-66A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-63.13	-13	-50.13	-69.56	-69.88	5.85	12.60	H
	2365.5	-43.63	-13	-30.63	-54.20	-49.43	7.30	13.10	H
	3154	-62.81	-13	-49.81	-75.63	-65.96	8.35	11.50	H
	1577	-63.89	-13	-50.89	-70.54	-70.64	5.85	12.60	V
	2365.5	-47.05	-13	-34.05	-58.02	-52.85	7.30	13.10	V
	3154	-62.56	-13	-49.56	-75.93	-65.71	8.35	11.50	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.27	-13	-50.27	-76.12	-66.52	4.00	9.40	H
	5238	-61.94	-13	-48.94	-78.67	-65.51	4.88	10.60	H
	6984	-57.93	-13	-44.93	-78.72	-62.86	5.52	12.60	H
	3492	-62.74	-13	-49.74	-76.12	-65.99	4.00	9.40	V
	5238	-61.54	-13	-48.54	-78.21	-65.11	4.88	10.60	V
	6984	-57.53	-13	-44.53	-78.48	-62.46	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 30A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.50	-60.08	-40	-20.08	-81.09	-66.33	6.45	12.70	H
	6916.50	-59.86	-40	-19.86	-85.57	-63.26	8.40	11.80	H
	9222.00	-53.24	-40	-13.24	-84.96	-55.59	9.65	12.00	H
	4611.50	-60.10	-40	-20.10	-81.49	-66.35	6.45	12.70	V
	6916.50	-61.30	-40	-21.30	-87.49	-64.70	8.40	11.80	V
	9222.00	-53.67	-40	-13.67	-84.57	-56.02	9.65	12.00	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-63.83	-13	-50.83	-81.70	-70.58	5.85	12.60	H
	5613.27	-61.29	-13	-48.29	-83.55	-67.09	7.30	13.10	H
	7484.36	-58.30	-13	-45.30	-84.63	-61.45	8.35	11.50	H
	3742.18	-63.37	-13	-50.37	-81.16	-70.12	5.85	12.60	V
	5613.27	-59.40	-13	-46.40	-81.85	-65.20	7.30	13.10	V
	7484.36	-56.82	-13	-43.82	-83.14	-59.97	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_30A-5A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.50	-62.04	-40	-22.04	-58.98	-68.29	6.45	12.70	H
	6916.50	-57.91	-40	-17.91	-57.84	-61.31	8.40	11.80	H
	9222.00	-53.83	-40	-13.83	-62.62	-56.18	9.65	12.00	H
	4611.50	-58.46	-40	-18.46	-55.25	-64.71	6.45	12.70	V
	6916.50	-57.97	-40	-17.97	-57.86	-61.37	8.40	11.80	V
	9222.00	-54.26	-40	-14.26	-62.63	-56.61	9.65	12.00	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-67.34	-13	-54.34	-73.45	-70.59	4.00	9.40	H
	2496.27	-64.15	-13	-51.15	-74.34	-67.72	4.88	10.60	H
	3328.36	-64.25	-13	-51.25	-76.22	-69.18	5.52	12.60	H
	1664.18	-67.22	-13	-54.22	-73.10	-70.47	4.00	9.40	V
	2496.27	-64.18	-13	-51.18	-74.71	-67.75	4.88	10.60	V
	3328.36	-63.63	-13	-50.63	-76.01	-68.56	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_30A-12A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.50	-56.94	-40	-16.94	-77.95	-63.19	6.45	12.70	H
	6916.50	-61.30	-40	-21.30	-87.01	-64.70	8.40	11.80	H
	9222.00	-53.92	-40	-13.92	-85.64	-56.27	9.65	12.00	H
	4611.50	-61.16	-40	-21.16	-82.55	-67.41	6.45	12.70	V
	6916.50	-59.06	-40	-19.06	-85.25	-62.46	8.40	11.80	V
	9222.00	-54.43	-40	-14.43	-85.33	-56.78	9.65	12.00	V
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-64.00	-13	-51.00	-74.12	-67.25	4.00	9.40	H
	2109	-64.23	-13	-51.23	-76.89	-67.80	4.88	10.60	H
	2812	-62.45	-13	-49.45	-78.36	-67.38	5.52	12.60	H
	1406	-64.28	-13	-51.28	-73.96	-67.53	4.00	9.40	V
	2109	-63.96	-13	-50.96	-76.57	-67.53	4.88	10.60	V
	2812	-62.29	-13	-49.29	-78.39	-67.22	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 30A-14A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B30 BW 10MHz Middle 1RB0,QPSK	4611.5	-60.81	-40	-20.81	-57.75	-67.56	5.85	12.60	H
	6916.5	-53.94	-40	-13.94	-53.87	-59.74	7.30	13.10	H
	9222	-53.47	-40	-13.47	-62.26	-56.62	8.35	11.50	H
	4611.5	-60.74	-40	-20.74	-57.53	-67.49	5.85	12.60	V
	6916.5	-60.82	-40	-20.82	-60.71	-66.62	7.30	13.10	V
	9222	-54.04	-40	-14.04	-62.41	-57.19	8.35	11.50	V
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-66.74	-13	-53.74	-73.17	-69.99	4.00	9.40	H
	2365.5	-61.26	-13	-48.26	-71.83	-64.83	4.88	10.60	H
	3154	-63.31	-13	-50.31	-76.13	-68.24	5.52	12.60	H
	1577	-66.57	-13	-53.57	-73.22	-69.82	4.00	9.40	V
	2365.5	-63.47	-13	-50.47	-74.44	-67.04	4.88	10.60	V
	3154	-62.70	-13	-49.70	-76.07	-67.63	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 66A-2A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.52	-13	-50.52	-76.37	-70.27	5.85	12.60	H
	5238	-57.61	-13	-44.61	-74.34	-63.41	7.30	13.10	H
	6984	-57.81	-13	-44.81	-78.60	-60.96	8.35	11.50	H
	3492	-62.86	-13	-49.86	-76.24	-69.61	5.85	12.60	V
	5238	-54.26	-13	-41.26	-70.93	-60.06	7.30	13.10	V
	6984	-57.37	-13	-44.37	-78.32	-60.52	8.35	11.50	V
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742.18	-61.21	-13	-48.21	-75.64	-67.96	5.85	12.60	H
	5613.27	-61.06	-13	-48.06	-77.90	-66.86	7.30	13.10	H
	7484.36	-55.76	-13	-42.76	-78.14	-58.91	8.35	11.50	H
	3742.18	-61.64	-13	-48.64	-76.28	-68.39	5.85	12.60	V
	5613.27	-60.51	-13	-47.51	-77.26	-66.31	7.30	13.10	V
	7484.36	-55.28	-13	-42.28	-77.59	-58.43	8.35	11.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_66A-5A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-60.92	-13	-47.92	-73.77	-67.77	5.65	12.50	H
	5238	-53.77	-13	-40.77	-70.50	-59.44	7.13	12.80	H
	6984	-58.09	-13	-45.09	-78.88	-61.49	8.40	11.80	H
	3492	-61.78	-13	-48.78	-75.16	-68.63	5.65	12.50	V
	5238	-52.35	-13	-39.35	-69.02	-58.02	7.13	12.80	V
	6984	-56.75	-13	-43.75	-77.7	-60.15	8.40	11.80	V
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664.18	-66.97	-13	-53.97	-73.08	-70.42	4.00	9.40	H
	2496.27	-61.99	-13	-48.99	-72.18	-50.86	4.88	10.60	H
	3328.36	-63.95	-13	-50.95	-75.92	-76.06	5.52	12.60	H
	1664.18	-67.36	-13	-54.36	-73.24	-72.63	4.00	9.40	V
	2496.27	-62.35	-13	-49.35	-72.88	-62.83	4.88	10.60	V
	3328.36	-63.86	-13	-50.86	-76.24	-76.14	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_66A-12A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 20MHz Middle 1RB0,QPSK	3492	-63.22	-13	-50.22	-76.07	-69.97	5.85	12.60	H
	5238	-62.40	-13	-49.40	-79.13	-68.20	7.30	13.10	H
	6984	-58.14	-13	-45.14	-78.93	-61.29	8.35	11.50	H
	3492	-63.12	-13	-50.12	-76.5	-69.87	5.85	12.60	V
	5238	-62.13	-13	-49.13	-78.8	-67.93	7.30	13.10	V
	6984	-55.80	-13	-42.80	-76.75	-58.95	8.35	11.50	V
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-64.23	-13	-51.23	-72.19	-67.48	4.00	9.40	H
	2109	-63.88	-13	-50.88	-73.54	-67.45	4.88	10.60	H
	2812	-62.84	-13	-49.84	-74.70	-67.77	5.52	12.60	H
	1406	-64.32	-13	-51.32	-72.36	-67.57	4.00	9.40	V
	2109	-64.31	-13	-51.31	-74.34	-67.88	4.88	10.60	V
	2812	-62.61	-13	-49.61	-74.71	-67.54	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA 66A-13A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 10MHz Middle 1RB0,QPSK	3492	-60.67	-13	-47.67	-73.52	-67.42	5.85	12.60	H
	5238	-60.92	-13	-47.92	-77.65	-66.72	7.30	13.10	H
	6984	-58.28	-13	-45.28	-79.07	-61.43	8.35	11.50	H
	3492	-59.97	-13	-46.97	-73.35	-66.72	5.85	12.60	V
	5238	-59.31	-13	-46.31	-75.98	-65.11	7.30	13.10	V
	6984	-56.19	-13	-43.19	-77.14	-59.34	8.35	11.50	V
LTE B13 BW 10MHz Middle 1RB0,QPSK	1555	-66.48	-13	-53.48	-73.16	-69.73	4.00	9.40	H
	2332.5	-58.11	-13	-45.11	-68.81	-61.68	4.88	10.60	H
	3110	-63.23	-13	-50.23	-75.87	-68.16	5.52	12.60	H
	1555	-66.74	-13	-53.74	-73.63	-69.99	4.00	9.40	V
	2332.5	-63.18	-13	-50.18	-74.27	-66.75	4.88	10.60	V
	3110	-62.40	-13	-49.40	-75.55	-67.33	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA 66A-14A									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 10MHz Middle 1RB0,QPSK	3492	-63.27	-13	-50.27	-76.12	-70.02	5.85	12.60	H
	5238	-60.40	-13	-47.40	-77.13	-66.20	7.30	13.10	H
	6984	-57.51	-13	-44.51	-78.30	-60.66	8.35	11.50	H
	3492	-62.75	-13	-49.75	-76.13	-69.50	5.85	12.60	V
	5238	-61.85	-13	-48.85	-78.52	-67.65	7.30	13.10	V
	6984	-57.53	-13	-44.53	-78.48	-60.68	8.35	11.50	V
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-62.75	-13	-49.75	-69.18	-66.00	4.00	9.40	H
	2365.5	-52.47	-13	-39.47	-63.04	-56.04	4.88	10.60	H
	3154	-62.86	-13	-49.86	-75.68	-67.79	5.52	12.60	H
	1577	-63.10	-13	-50.10	-69.75	-66.35	4.00	9.40	V
	2365.5	-57.00	-13	-44.00	-67.97	-60.57	4.88	10.60	V
	3154	-62.02	-13	-49.02	-75.39	-66.95	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.