FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2403-1, XT2403-2
FCC ID	:	IHDT56AQ5
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System
TEST DATE(S)	:	Dec. 23, 2023 ~ Jan. 22, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Specification of Accessory 7
1.7 Testing Location 8
1.8 Test Software 8
1.9 Applicable Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**
2.1 Carrier Frequency Channel 9
2.2 Test Mode 10
2.3 Connection Diagram of Test System 11
2.4 Support Unit used in test configuration and system 11
2.5 EUT Operation Test Setup 12
2.6 Measurement Results Explanation Example 12
3 TEST RESULT **13**
3.1 6dB and 99% Bandwidth Measurement 13
3.2 Output Power Measurement 14
3.3 Power Spectral Density Measurement 15
3.4 Conducted Band Edges and Spurious Emission Measurement 16
3.5 Radiated Band Edges and Spurious Emission Measurement 17
3.6 AC Conducted Emission Measurement 21
3.7 Antenna Requirements 23
4 LIST OF MEASURING EQUIPMENT **24**
5 MEASUREMENT UNCERTAINTY **25**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION AND PLOTS
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR3D1818B	Rev. 01	Initial issue of report	Jan. 26, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Report only	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 4.78 dB at 2483.500 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 13.08 dB at 0.162 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2403-1, XT2403-2
FCC ID	IHDT56AQ5
IMEI Code	Conducted: 354958440024652 Conduction: 354958440030899 Radiation: 354958440023837
HW Version	DVT2
SW Version	U2UM34.9
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two models: XT2403-1 is pSIM+pSIM sample, XT2403-2 is pSIM + eSIM sample, no other difference, full test with the model XT2403-2.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel (37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	<Ant 6> BLE 1Mbps: 14.43 dBm (0.0277 W) BLE 2Mbps: 14.53 dBm (0.0284 W) <Ant 3> BLE 1Mbps: 13.93 dBm (0.0247 W) BLE 2Mbps: 14.07 dBm (0.0255 W)
99% Occupied Bandwidth	<Ant 6> BLE 1Mbps: 1.019 MHz BLE 2Mbps: 2.006 MHz <Ant 3> BLE 1Mbps: 1.019 MHz BLE 2Mbps: 2.010 MHz
Antenna Type / Gain	<Ant 6>: Metal Antenna Type with gain -6.70 dBi <Ant 3>: Metal Antenna Type with gain -5.70 dBi
Type of Modulation	Bluetooth LE : GFSK

Note: BLE Ant.6 & Ant.3 does not support MIMO mode.

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Accessories Information				
AC Adapter 1(US)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1251
AC Adapter 1(EU)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1252
AC Adapter 1(UK)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1253
AC Adapter 1(AU)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1255
AC Adapter 1(AR)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1256
AC Adapter 1(BR)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-1257
AC Adapter 2(US)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1251
AC Adapter 2(EU)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1252
AC Adapter 2(UK)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1253
AC Adapter 2(AU)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1255
AC Adapter 2(AR)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1256
AC Adapter 2(BR)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1257
AC Adapter 2(CHILE)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1259
AC Adapter 2(IN)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-1254
AC Adapter 3(IN)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-684N
Battery	**Brand Name**	Motorola (ATL)	**Model Name**	QM45
USB Cable 1	**Brand Name**	Saibao	**Model Name**	SC18D71644
USB Cable 2	**Brand Name**	Luxshare	**Model Name**	SC18E08104
Wireless Earphone	**Brand Name**	Motorola	**Model Name**	XT2441-1
Wireless Charging dock	**Marketing Name**	Turbo Power 50W Wireless Charging Stand	**Model Name**	MW-02

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	CO01-KS 03CH06-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	Tonscend	JS1120-3 test system China_210602	3.3.10
2.	03CH06-KS	AUDIX	E3	210616
3.	CO01-KS	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 2Mbps Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 2Mbps
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter1)
Remark: For Radiated Test Cases, The tests were performance with Adapter 1, USB Cable 1	

2.3 Connection Diagram of Test System



This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
3.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
4.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
5.	SD Card	Kingston	8GB	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 2.3dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 2.3 + 10 = 12.3 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1% to 5% of the 99% OBW and the VBW is set to 3 times of the RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C

3.5.7 Duty Cycle

Please refer to Appendix D.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix C

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Dec. 31, 2023 ~Jan. 22, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 05, 2023	Dec. 31, 2023 ~Jan. 22, 2024	Jan. 04, 2024	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 02, 2024		Jan. 01, 2025	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	1339163	300MHz~40GHz	Oct. 11, 2023	Dec. 31, 2023 ~Jan. 22, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 02, 2024		Jan. 01, 2025	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 10, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
EXA Spectrum Analyzer	Keysight	N9010B	MY60242126	10Hz-44GHz	Oct. 10, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
Bilog Antenna	TeseQ	CBL6111D	49921	30MHz-1GHz	Apr. 09, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Apr. 08, 2024	Radiation (03CH06-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00218652	1GHz~18GHz	Apr. 06, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Apr. 05, 2024	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 08, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Jan. 07, 2024	Radiation (03CH06-KS)
SHF-EHF Horn	Com-power	AH-840	101093	18GHz~40GHz	Jan. 05, 2024		Jan. 04, 2025	Radiation (03CH06-KS)
Amplifier	SONOMA	310N	380827	9KHz ~1GHZ	Jul. 06, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Jul. 05, 2024	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 05, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Jan. 04, 2024	Radiation (03CH06-KS)
Amplifier	MITEQ	EM18G40GGA	060728	18~40GHz	Jan. 04, 2024		Jan. 03, 2025	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2082395	1Ghz-18Ghz	Jan. 05, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Jan. 04, 2024	Radiation (03CH06-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2082395	1Ghz-18Ghz	Jan. 04, 2024		Jan. 03, 2025	Radiation (03CH06-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 10, 2023	Dec. 23, 2023 ~Jan. 16, 2024	Oct. 09, 2024	Radiation (03CH06-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 23, 2023 ~Jan. 16, 2024	NCR	Radiation (03CH06-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 23, 2023 ~Jan. 16, 2024	NCR	Radiation (03CH06-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 23, 2023 ~Jan. 16, 2024	NCR	Radiation (03CH06-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	May 16, 2023	Jan. 11, 2024 ~Jan. 13, 2024	May 15, 2024	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Oct. 11, 2023	Jan. 11, 2024 ~Jan. 13, 2024	Oct. 10, 2024	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	May 16, 2023	Jan. 11, 2024 ~Jan. 13, 2024	May 15, 2024	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 11, 2023	Jan. 11, 2024 ~Jan. 13, 2024	Oct. 10, 2024	Conduction (CO01-KS)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Conducted Spurious Emission & Bandedge	**±2.26 dB**
Occupied Channel Bandwidth	**±0.1%**
Conducted Power	**±0.46 dB**
Conducted Power Spectral Density	**±0.88 dB**
Frequency	**±0.4 Hz**

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.94dB**

Uncertainty of Radiated Emission Measurement (9 KHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.32dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**6.26dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.02dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.26dB**

---------- THE END ----------

Appendix A. Conducted Test Results

Ambient Condition: 25 ℃, 45 %RH	
Test Date: 2023.12.31~2024.1.22	**Test Engineer:** Jiang Jun

DTS Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE_1M	Ant6	2402	0.67	2401.66	2402.33	0.5	PASS
	Ant3	2402	0.67	2401.66	2402.33	0.5	PASS
	Ant6	2440	0.68	2439.66	2440.34	0.5	PASS
	Ant3	2440	0.66	2439.66	2440.33	0.5	PASS
	Ant6	2480	0.68	2479.66	2480.33	0.5	PASS
	Ant3	2480	0.67	2479.66	2480.33	0.5	PASS
BLE_2M	Ant6	2402	1.14	2401.43	2402.58	0.5	PASS
	Ant3	2402	1.14	2401.44	2402.58	0.5	PASS
	Ant6	2440	1.15	2439.43	2440.58	0.5	PASS
	Ant3	2440	1.14	2439.43	2440.58	0.5	PASS
	Ant6	2480	1.15	2479.43	2480.58	0.5	PASS
	Ant3	2480	1.15	2479.43	2480.58	0.5	PASS

Test Graphs

BLE_1M_Ant6_2402



Date: 16.JAN.2024 12:35:31

BLE_1M_Ant3_2402



Date: 16.JAN.2024 12:46:52

BLE_1M_Ant6_2440



BLE_1M_Ant3_2440



BLE_1M_Ant6_2480



Date: 16.JAN.2024 12:38:00

BLE_1M_Ant3_2480



Date: 16.JAN.2024 12:49:34

BLE_2M_Ant6_2402



Date: 16.JAN.2024 12:39:22

BLE_2M_Ant3_2402



Date: 16.JAN.2024 12:50:50

BLE_2M_Ant6_2440



Date: 16.JAN.2024 12:40:39

BLE_2M_Ant3_2440



Date: 16.JAN.2024 12:52:18

BLE_2M_Ant6_2480



Date: 16.JAN.2024 12:41:41

BLE_2M_Ant3_2480



Date: 16.JAN.2024 12:53:16

Occupied Channel Bandwidth

Test Result

TestMode	Antenna	Freq(MHz)	OCB [MHz]	FL[MHz]	FH[MHz]
BLE_1M	Ant6	2402	1.019	2401.4925	2402.5115
	Ant3	2402	1.019	2401.4965	2402.5155
	Ant6	2440	1.019	2439.4925	2440.5115
	Ant3	2440	1.019	2439.4965	2440.5155
	Ant6	2480	1.019	2479.4925	2480.5115
	Ant3	2480	1.015	2479.4965	2480.5115
BLE_2M	Ant6	2402	2.002	2401.0130	2403.0150
	Ant3	2402	2.01	2401.0130	2403.0230
	Ant6	2440	2.006	2439.0130	2441.0190
	Ant3	2440	2.01	2439.0130	2441.0230
	Ant6	2480	2.006	2479.0090	2481.0150
	Ant3	2480	2.006	2479.0090	2481.0150

Test Graphs

BLE_1M_Ant6_2402



BLE_1M_Ant3_2402



BLE_1M_Ant6_2440



Date: 16.JAN.2024 12:37:04

BLE_1M_Ant3_2440



Date: 16.JAN.2024 12:48:35

BLE_1M_Ant6_2480



Date: 16.JAN.2024 12:38:06

BLE_1M_Ant3_2480



Date: 16.JAN.2024 12:49:39

BLE_2M_Ant6_2402



Date: 16.JAN.2024 12:39:28

BLE_2M_Ant3_2402



Date: 16.JAN.2024 12:50:56

BLE_2M_Ant6_2440



Date: 16.JAN.2024 12:40:45

BLE_2M_Ant3_2440



Date: 16.JAN.2024 12:52:24

BLE_2M_Ant6_2480



Date: 16.JAN.2024 12:41:47

BLE_2M_Ant3_2480



Date: 16.JAN.2024 12:53:21

Maximum conducted output power

Test Result Peak Power

TestMode	Antenna	CH.	Peak Conducted Power (dBm)	Conducted Power Limit	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit	Pass/Fail
BLE1M	Ant6	0	14.16	30.00	-6.7	7.46	36.00	Pass
		39	**14.43**	30.00	-6.7	**7.73**	36.00	Pass
		78	13.39	30.00	-6.7	6.69	36.00	Pass
BLE2M	Ant6	0	14.22	30.00	-6.7	7.52	36.00	Pass
		39	**14.53**	30.00	-6.7	**7.83**	36.00	Pass
		78	13.25	30.00	-6.7	6.55	36.00	Pass
BLE1M	Ant3	0	12.57	30.00	-5.7	6.87	36.00	Pass
		39	**13.93**	30.00	-5.7	**8.23**	36.00	Pass
		78	12.37	30.00	-5.7	6.67	36.00	Pass
BLE2M	Ant3	0	12.71	30.00	-5.7	7.01	36.00	Pass
		39	**14.07**	30.00	-5.7	**8.37**	36.00	Pass
		78	12.53	30.00	-5.7	6.83	36.00	Pass

Test Result Average Power (Reference only)

TestMode	Antenna	CH.	Duty Factor (dB)	Average Conducted Power (dBm)
BLE1M	Ant6	0	2.88	14.03
		39	2.88	14.21
		78	2.88	12.96
BLE2M	Ant6	0	4.16	14.03
		39	4.16	14.21
		78	4.16	13.07
BLE1M	Ant3	0	2.86	12.32
		39	2.86	13.82
		78	2.86	12.18
BLE2M	Ant3	0	4.16	12.32
		39	4.16	13.97
		78	4.16	12.19

Maximum power spectral density

Test Result

TestMode	Antenna	Freq(MHz)	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
BLE_1M	Ant6	2402	-2.08	≤8.00	PASS
	Ant3	2402	-3.46	≤8.00	PASS
	Ant6	2440	-1.89	≤8.00	PASS
	Ant3	2440	-2.2	≤8.00	PASS
	Ant6	2480	-3.35	≤8.00	PASS
	Ant3	2480	-3.71	≤8.00	PASS
BLE_2M	Ant6	2402	-4.74	≤8.00	PASS
	Ant3	2402	-6.2	≤8.00	PASS
	Ant6	2440	-4.63	≤8.00	PASS
	Ant3	2440	-4.88	≤8.00	PASS
	Ant6	2480	-6.07	≤8.00	PASS
	Ant3	2480	-6.39	≤8.00	PASS

Test Graphs

BLE_1M_Ant6_2402



BLE_1M_Ant3_2402



BLE_1M_Ant6_2440



Date: 16.JAN.2024 12:37:15

BLE_1M_Ant3_2440



Date: 16.JAN.2024 12:48:45

BLE_1M_Ant6_2480



Date: 16.JAN.2024 12:38:16

BLE_1M_Ant3_2480



Date: 16.JAN.2024 12:49:50

BLE_2M_Ant6_2402



Date: 16.JAN.2024 12:39:39

BLE_2M_Ant3_2402



Date: 16.JAN.2024 12:51:06

BLE_2M_Ant6_2440



Date: 16.JAN.2024 12:40:55

BLE_2M_Ant3_2440



Date: 16.JAN.2024 12:52:34

BLE_2M_Ant6_2480



Date: 16.JAN.2024 12:41:58

BLE_2M_Ant3_2480



Date: 16.JAN.2024 12:53:32

Reference level measurement

Test Result

TestMode	Antenna	Freq(MHz)	Max.Point[MHz]	Result[dBm/100KHz]
BLE_1M	Ant6	2402	2402.01	12.48
	Ant3	2402	2402.01	11.05
	Ant6	2440	2440.01	12.60
	Ant3	2440	2440.00	12.25
	Ant6	2480	2480.01	11.11
	Ant3	2480	2480.00	10.68
BLE_2M	Ant6	2402	2402.00	12.52
	Ant3	2402	2402.01	11.03
	Ant6	2440	2440.01	12.65
	Ant3	2440	2440.01	12.25
	Ant6	2480	2480.01	11.18
	Ant3	2480	2480.01	10.70

Test Graphs

BLE_1M_Ant6_2402



BLE_1M_Ant3_2402



BLE_1M_Ant6_2440



Date: 16.JAN.2024 12:37:22

BLE_1M_Ant3_2440



Date: 16.JAN.2024 12:48:53

BLE_1M_Ant6_2480



Date: 16.JAN.2024 12:38:24

BLE_1M_Ant3_2480



Date: 16.JAN.2024 12:49:57

BLE_2M_Ant6_2402



Date: 16.JAN.2024 12:39:46

BLE_2M_Ant3_2402



Date: 16.JAN.2024 12:51:14

BLE_2M_Ant6_2440



Date: 16.JAN.2024 12:41:03

BLE_2M_Ant3_2440



Date: 16.JAN.2024 12:52:42

BLE_2M_Ant6_2480



Date: 16.JAN.2024 12:42:05

BLE_2M_Ant3_2480



Date: 16.JAN.2024 12:53:39

Band edge measurements

Test Result

TestMode	Antenna	ChName	Freq(MHz)	RefLevel[dBm /100KHz]	Result[dBm /100KHz]	Limit[dBm 100KHz]	Verdict
BLE_1M	Ant6	Low	2402	12.48	-45.16	≤-7.52	PASS
	Ant3	Low	2402	11.05	-46.03	≤-8.95	PASS
	Ant6	High	2480	11.11	-47.47	≤-8.89	PASS
	Ant3	High	2480	10.68	-46.75	≤-9.32	PASS
BLE_2M	Ant6	Low	2402	12.52	-31.47	≤-7.48	PASS
	Ant3	Low	2402	11.03	-31.18	≤-8.97	PASS
	Ant6	High	2480	11.18	-46.86	≤-8.82	PASS
	Ant3	High	2480	10.70	-46.85	≤-9.3	PASS

Test Graphs

BLE_1M_Ant6_Low_2402



Date: 16.JAN.2024 12:36:09

BLE_1M_Ant3_Low_2402



Date: 16.JAN.2024 12:47:30

BLE_1M_Ant6_High_2480



Date: 16.JAN.2024 12:38:38

BLE_1M_Ant3_High_2480



Date: 16.JAN.2024 12:50:11

BLE_2M_Ant6_Low_2402



Date: 16.JAN.2024 12:40:00

BLE_2M_Ant3_Low_2402



Date: 16.JAN.2024 12:51:28

BLE_2M_Ant6_High_2480



Date: 16.JAN.2024 12:42:19

BLE_2M_Ant3_High_2480



Date: 16.JAN.2024 12:53:53

Conducted Spurious Emission

Test Result

TestMode	Antenna	Freq(MHz)	FreqRange [MHz]	RefLevel [dBm/100KHz]	Result [dBm/100KHz]	Limit [dBm/100KHz]	Verdict
BLE_1M	Ant6	2402	30~1000	12.48	-57.3	≤-7.52	PASS
			1000~26500	12.48	-51.97	≤-7.52	PASS
	Ant3	2402	30~1000	11.05	-56.51	≤-8.95	PASS
			1000~26500	11.05	-52.58	≤-8.95	PASS
	Ant6	2440	30~1000	12.60	-56.69	≤-7.4	PASS
			1000~26500	12.60	-51.66	≤-7.4	PASS
	Ant3	2440	30~1000	12.25	-57.41	≤-7.75	PASS
			1000~26500	12.25	-51.85	≤-7.75	PASS
	Ant6	2480	30~1000	11.11	-57.38	≤-8.89	PASS
			1000~26500	11.11	-52.01	≤-8.89	PASS
	Ant3	2480	30~1000	10.68	-57.51	≤-9.32	PASS
			1000~26500	10.68	-52.6	≤-9.32	PASS
BLE_2M	Ant6	2402	30~1000	12.52	-56.76	≤-7.48	PASS
			1000~26500	12.52	-52.47	≤-7.48	PASS
	Ant3	2402	30~1000	11.03	-57.5	≤-8.97	PASS
			1000~26500	11.03	-52.59	≤-8.97	PASS
	Ant6	2440	30~1000	12.65	-57.31	≤-7.35	PASS
			1000~26500	12.65	-52.24	≤-7.35	PASS
	Ant3	2440	30~1000	12.25	-57.08	≤-7.75	PASS
			1000~26500	12.25	-52.26	≤-7.75	PASS
	Ant6	2480	30~1000	11.18	-53.02	≤-8.82	PASS
			1000~26500	11.18	-52.7	≤-8.82	PASS
	Ant3	2480	30~1000	10.70	-56.03	≤-9.3	PASS
			1000~26500	10.70	-52.67	≤-9.3	PASS

Test Graphs

BLE_1M_Ant6_2402_30~1000



BLE_1M_Ant6_2402_1000~26500



BLE_1M_Ant3_2402_30~1000



Date: 16.JAN.2024 12:47:36

BLE_1M_Ant3_2402_1000~26500



Date: 16.JAN.2024 12:47:52

BLE_1M_Ant6_2440_30~1000



Date: 16.JAN.2024 12:37:28

BLE_1M_Ant6_2440_1000~26500



Date: 16.JAN.2024 12:37:43

BLE_1M_Ant3_2440_30~1000



Date: 16.JAN.2024 12:48:58

BLE_1M_Ant3_2440_1000~26500



Date: 16.JAN.2024 12:49:14

BLE_1M_Ant6_2480_30~1000



Date: 16.JAN.2024 12:38:45

BLE_1M_Ant6_2480_1000~26500



Date: 16.JAN.2024 12:39:00

BLE_1M_Ant3_2480_30~1000



Date: 16.JAN.2024 12:50:18

BLE_1M_Ant3_2480_1000~26500



Date: 16.JAN.2024 12:50:33

BLE_2M_Ant6_2402_30~1000



Date: 16.JAN.2024 12:40:07

BLE_2M_Ant6_2402_1000~26500



Date: 16.JAN.2024 12:40:22

BLE_2M_Ant3_2402_30~1000



Date: 16.JAN.2024 12:51:35

BLE_2M_Ant3_2402_1000~26500



Date: 16.JAN.2024 12:51:50

BLE_2M_Ant6_2440_30~1000



Date: 16.JAN.2024 12:41:08

BLE_2M_Ant6_2440_1000~26500



Date: 16.JAN.2024 12:41:24

BLE_2M_Ant3_2440_30~1000



Date: 16.JAN.2024 12:52:47

BLE_2M_Ant3_2440_1000~26500



Date: 16.JAN.2024 12:53:03

BLE_2M_Ant6_2480_30~1000



Date: 16.JAN.2024 12:42:26

BLE_2M_Ant6_2480_1000~26500



Date: 16.JAN.2024 12:42:41

BLE_2M_Ant3_2480_30~1000



Date: 16.JAN.2024 12:54:00

BLE_2M_Ant3_2480_1000~26500



Date: 16.JAN.2024 12:54:15

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 2023 LINE

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.186	42.65	-21.55	64.20	32.21	0.03	10.41	QP
2	*	0.186	40.05	-14.15	54.20	29.61	0.03	10.41	Average
3		0.206	40.63	-22.73	63.36	30.20	0.03	10.40	QP
4		0.206	24.93	-28.43	53.36	14.50	0.03	10.40	Average
5		0.385	35.49	-22.68	58.17	25.19	0.01	10.29	QP
6		0.385	24.59	-23.58	48.17	14.29	0.01	10.29	Average
7		0.510	31.38	-24.62	56.00	21.19	-0.03	10.22	QP
8		0.510	22.38	-23.62	46.00	12.19	-0.03	10.22	Average
9		0.822	28.82	-27.18	56.00	18.79	-0.08	10.11	QP
10		0.822	20.22	-25.78	46.00	10.19	-0.08	10.11	Average
11		1.016	31.49	-24.51	56.00	21.50	-0.10	10.09	QP
12		1.016	26.49	-19.51	46.00	16.50	-0.10	10.09	Average

Test Engineer :	Amos Zhang	**Temperature :**	25.3~26.2℃
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 2023 NEUTRAL

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.162	45.06	-20.28	65.34	34.60	0.04	10.42	QP
2	*	0.162	42.26	-13.08	55.34	31.80	0.04	10.42	Average
3		0.269	36.94	-24.22	61.16	26.61	-0.02	10.35	QP
4		0.269	29.64	-21.52	51.16	19.31	-0.02	10.35	Average
5		0.532	34.04	-21.96	56.00	23.90	-0.07	10.21	QP
6		0.532	23.94	-22.06	46.00	13.80	-0.07	10.21	Average
7		0.624	29.60	-26.40	56.00	19.50	-0.07	10.17	QP
8		0.624	24.70	-21.30	46.00	14.60	-0.07	10.17	Average
9		0.943	33.50	-22.50	56.00	23.49	-0.09	10.10	QP
10		0.943	26.60	-19.40	46.00	16.59	-0.09	10.10	Average
11		1.043	33.19	-22.81	56.00	23.20	-0.10	10.09	QP
12		1.043	24.89	-21.11	46.00	14.90	-0.10	10.09	Average

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

Appendix C. Radiated Spurious Emission Test Data

Test Engineer :	Ryan Xu	**Relative Humidity :**	41 ~ 42％
		Temperature :	22 ~ 23℃

Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	6	Bluetooth-LE_GSFK	00	2402	1Mbps	-	-
Mode 2	2400-2483.5	6	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 3	2400-2483.5	6	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 4	2400-2483.5	6	Bluetooth-LE_GSFK	00	2402	2Mbps	-	-
Mode 5	2400-2483.5	6	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 6	2400-2483.5	6	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
Mode 7	2400-2483.5	6	Bluetooth-LE_GSFK	39	2480	2Mbps	-	LF
Mode 8	2400-2483.5	3	Bluetooth-LE_GSFK	00	2402	1Mbps	-	-
Mode9	2400-2483.5	3	Bluetooth-LE_GSFK	19	2440	1Mbps	-	-
Mode 10	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	1Mbps	-	-
Mode 11	2400-2483.5	3	Bluetooth-LE_GSFK	00	2402	2Mbps	-	-
Mode 12	2400-2483.5	3	Bluetooth-LE_GSFK	19	2440	2Mbps	-	-
Mode 13	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	2Mbps	-	-
Mode 14	2400-2483.5	3	Bluetooth-LE_GSFK	39	2480	2Mbps	-	LF

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE_GSFK	00	2383.97	43.73	54.00	-10.27	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4804.00	47.06	54.00	-6.94	V	AVERAGE	Pass	Harmonic
2	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	4880.00	45.08	74.00	-28.92	H	PEAK	Pass	Harmonic
3	Bluetooth-LE_GSFK	39	2492.80	45.12	54.00	-8.88	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	39	7440.00	45.40	74.00	-28.60	V	PEAK	Pass	Harmonic
4	Bluetooth-LE_GSFK	00	2388.65	44.40	54.00	-9.60	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE_GSFK	00	4804.00	43.89	74.00	-30.11	H	PEAK	Pass	Harmonic
5	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
	Bluetooth-LE_GSFK	19	7320.00	45.24	74.00	-28.76	V	PEAK	Pass	Harmonic
6	Bluetooth-LE_GSFK	39	2483.50	48.67	54.00	-5.33	H	AVERAGE	Pass	Band Edge
6	Bluetooth-LE_GSFK	39	7440.00	45.53	74.00	-28.47	V	PEAK	Pass	Harmonic
7	Bluetooth-LE_GSFK	39	571.26	38.60	46.00	-7.40	V	PEAK	Pass	LF
8	Bluetooth-LE_GSFK	00	2385.92	43.81	54.00	-10.19	H	AVERAGE	Pass	Band Edge
8	Bluetooth-LE_GSFK	00	4804.00	43.02	74.00	-30.98	V	PEAK	Pass	Harmonic
9	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
9	Bluetooth-LE_GSFK	19	4880.00	45.87	74.00	-28.13	V	Peak	Pass	Harmonic
10	Bluetooth-LE_GSFK	39	2491.18	44.94	54.00	-9.06	V	AVERAGE	Pass	Band Edge
10	Bluetooth-LE_GSFK	39	7440.00	44.64	74.00	-29.36	V	PEAK	Pass	Harmonic
11	Bluetooth-LE_GSFK	00	2384.88	44.27	54.00	-9.73	V	AVERAGE	Pass	Band Edge
11	Bluetooth-LE_GSFK	00	4804.00	42.20	74.00	-31.80	V	PEAK	Pass	Harmonic
12	Bluetooth-LE_GSFK	19	-	-	-	-	-	-	-	Band Edge
12	Bluetooth-LE_GSFK	19	7320.00	45.32	74.00	-28.68	H	PEAK	Pass	Harmonic
13	Bluetooth-LE_GSFK	39	2483.50	49.22	54.00	-4.78	H	AVERAGE	Pass	Band Edge
13	Bluetooth-LE_GSFK	39	7440.00	46.71	74.00	-27.29	V	PEAK	Pass	Harmonic
14	Bluetooth-LE_GSFK	39	557.68	39.00	46.00	-7.00	V	PEAK	Pass	LF

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2340.81 55.03 74.00 -18.97 43.87 31.57 6.53 32.94 6.00 100 249 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 99.04 ------ ------ 87.05 32.21 6.62 32.84 6.00 100 249 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2388.65 43.72 54.00 -10.28 31.94 32.04 6.60 32.86 6.00 100 249 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 97.94 ------ ------ 85.95 32.21 6.62 32.84 6.00 100 249 AVERAGE

Mode	1	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK_CH00_2402MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2369.67 54.59 74.00 -19.41 43.13 31.78 6.57 32.89 6.00 346 284 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 99.35 ------ ------ 87.36 32.21 6.62 32.84 6.00 346 284 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2383.97 43.73 54.00 -10.27 32.03 31.98 6.59 32.87 6.00 346 284 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2402.00 98.19 ------ ------ 86.20 32.21 6.62 32.84 6.00 346 284 AVERAGE

Mode	1	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK_CH00_2402MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 44.70 74.00 -29.30 62.77 34.20 9.44 61.71 0.00 --- --- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4804.00 50.62 74.00 -23.38 68.69 34.20 9.44 61.71 0.00 331 74 PEAK 2 4804.00 47.06 54.00 -6.94 65.13 34.20 9.44 61.71 0.00 331 74 AVERAGE

Mode	2	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK_CH19_2440MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 45.08 74.00 -28.92 62.98 34.20 9.53 61.63 0.00 --- --- PEAK 2 7320.00 44.47 74.00 -29.53 57.58 35.68 11.69 60.48 0.00 --- --- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4880.00 41.14 74.00 -32.86 59.04 34.20 9.53 61.63 0.00 --- --- PEAK 2 7320.00 44.42 74.00 -29.58 57.53 35.68 11.69 60.48 0.00 --- --- PEAK

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK_CH39_2480MHz	
ANT	6	
Pol.	Horizontal	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2496.52 56.29 74.00 -17.71 43.26 32.87 6.75 32.59 6.00 160 256 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 104.32 ------ ------ 91.48 32.74 6.73 32.63 6.00 160 256 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2496.52 44.99 54.00 -9.01 31.96 32.87 6.75 32.59 6.00 160 256 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 103.32 ------ ------ 90.48 32.74 6.73 32.63 6.00 160 256 AVERAGE

Mode	3	
	Band Edge	
	2400-2483.5_Bluetooth-LE_GSFK_CH39_2480MHz	
ANT	6	
Pol.	Vertical	Fundamental
Peak	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2490.10 55.91 74.00 -18.09 42.96 32.82 6.74 32.61 6.00 365 276 PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 102.89 ------ ------ 90.05 32.74 6.73 32.63 6.00 365 276 PEAK
Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2492.80 45.12 54.00 -8.88 32.13 32.84 6.75 32.60 6.00 365 276 AVERAGE	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 2480.00 101.84 ------ ------ 89.00 32.74 6.73 32.63 6.00 365 276 AVERAGE

Mode	3	
	Harmonic	
	2400-2483.5_Bluetooth-LE_GSFK_CH39_2480MHz	
ANT	6	
Pol.	Horizontal	Vertical
Peak Avg	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 44.34 74.00 -29.66 62.11 34.18 9.61 61.56 0.00 --- --- PEAK 2 7440.00 43.86 74.00 -30.14 57.05 35.70 11.77 60.66 0.00 --- --- PEAK	 Freq Level Limit Line Margin Read Level Ant Factor Cable Loss Preamp Factor Aux Factor APos TPos Remark MHz dBuV/m dBuV/m dB dBuV dB/m dB dB dB cm deg 1 4960.00 40.75 74.00 -33.25 58.52 34.18 9.61 61.56 0.00 --- --- PEAK 2 7440.00 45.40 74.00 -28.60 58.59 35.70 11.77 60.66 0.00 --- --- PEAK