FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2429-1
FCC ID	:	IHDT56AR4
STANDARD	:	47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Feb. 05, 2024 ~ Feb. 24, 2024

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia

ACCREDITED
Cert #5145.02

Sporton International Inc. (Kunshan)
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, and Emission Designator 7
1.7 Testing Location 7
1.8 Test Software 7
1.9 Applicable Standards 8
1.10 Specification of Accessory 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**
2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration 10
2.4 Measurement Results Explanation Example 11
2.5 Frequency List of Low/Middle/High Channels 11
3 CONDUCTED TEST RESULT **12**
3.1 Measuring Instruments 12
3.2 Test Setup 12
3.3 Test Result of Conducted Test 12
3.4 Conducted Output Power and ERP/EIRP 13
3.5 Peak-to-Average Ratio 14
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 15
3.7 Conducted Band Edge 16
3.8 Conducted Spurious Emission 17
3.9 Frequency Stability 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Field Strength of Spurious Radiation Measurement 21
5 LIST OF MEASURING EQUIPMENT **22**
6 MEASUREMENT UNCERTAINTY **23**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG411904A	Rev. 01	Initial issue of report	Mar. 11, 2024
FG411904A	Rev. 02	Update Conducted power and EIRP for GSM1900, WCDMA Band II, WCDMA Band IV	Mar. 26, 2024

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	-	Report Only	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 10.95 dB at 4184.00 MHz

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2429-1
FCC ID	IHDT56AR4
IMEI Code	Conducted: 356305710036974 Radiation: 356305710030779
HW Version	DVT2
SW Version	U2UU34.8
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824 MHz ~ 849 MHz 1900: 1850MHz ~ 1910MHz **WCDMA:** Band V: 824 MHz ~ 849 MHz Band II: 1850 MHz ~ 1910 MHz Band IV: 1710 MHz ~ 1755 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869 MHz ~ 894 MHz 1900: 1930 MHz ~ 1990 MHz **WCDMA:** Band V: 869 MHz ~ 894 MHz Band II: 1930 MHz ~ 1990 MHz Band IV: 2110 MHz ~ 2155 MHz
Maximum Output Power to Antenna	**GSM/GPRS/EDGE:** 850 <Ant.0>: 32.37 dBm 1900 <Ant.1>: 29.53 dBm **WCDMA:** Band V <Ant.0>: 23.20 dBm Band II <Ant.1>: 23.20 dBm Band IV <Ant.1>: 23.18 dBm
Antenna Gain	Cellular Band <Ant.0>: -3.0 dBi PCS Band <Ant.1>: -2.5 dBi AWS Band <Ant.1>: -2.0 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK HSPA: QPSK HSPA+ : 16QAM DC-HSDPA: 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, and Emission Designator

FCC Rule	Frequency Band	Frequency Range (MHz)	Type of Modulation	Maximum ERP/EIRP (W)	Emission Designator
Part 22	GSM850 (GSM)	824.2 ~ 848.8	GMSK	0.5272	242KGXW
Part 22	GSM850 (EDGE)	824.2 ~ 848.8	8PSK	0.1368	239KG7W
Part 22	WCDMA Band V	826.4 ~ 846.6	BPSK	0.0638	4M13F9W
Part 24	GSM1900 (GSM)	1850.2 ~ 1909.8	GMSK	0.5047	244KGXW
Part 24	GSM1900 (EDGE)	1850.2 ~ 1909.8	8PSK	0.2051	250KG7W
Part 24	WCDMA Band II	1852.4 ~ 1907.6	BPSK	0.1175	4M15F9W
Part 27	WCDMA Band IV	1712.4 ~ 1752.6	BPSK	0.1312	4M15F9W

1.7 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH03-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	TH01-KS	SPORTON	Part2224_Ver5.0 200330	5.0
2.	03CH03-KS	AUDIX	E3	210616

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.10 Specification of Accessory

Accessories Information				
AC Adapter 1(US)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-681N
AC Adapter 1(EU)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-682N
AC Adapter 1(UK)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-683N
AC Adapter 1(AU)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-685N
AC Adapter 1(AR)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-686N
AC Adapter 1(BR)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-687N
AC Adapter 1(CHILE)	**Brand Name**	Motorola(Chenyang)	**Model Name**	MC-689N
AC Adapter 2(US)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-681N
AC Adapter 2(EU)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-682N
AC Adapter 2(UK)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-683N
AC Adapter 2(AU)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-685N
AC Adapter 2(AR)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-686N
AC Adapter 2(BR)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-687N
AC Adapter 2(IN)	**Brand Name**	Motorola(AOHAI)	**Model Name**	MC-684N
Battery 1	**Brand Name**	Motorola (ATL)	**Model Name**	QC50
Battery 2	**Brand Name**	Motorola (SCUD)	**Model Name**	QC50
USB Cable 1	**Brand Name**	Motorola(Saibao)	**Model Name**	SLQ-A248A
USB Cable 2	**Brand Name**	Motorola(Juwei)	**Model Name**	S928E13829
USB Cable 3	**Brand Name**	Motorola(Saibao)	**Model Name**	SLQ-A248A

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
GSM 1900	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



The EUT has been configuration operated in a manner tended to maximize its emission characteristics in a typical application.

2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820/8821	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 5.0 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 5.0 + 10 = 15.0 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99% power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Oct. 11, 2023	Feb. 23, 2024~ Feb. 24, 2024	Oct. 10, 2024	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	/	Feb. 23, 2024~ Feb. 24, 2024	/	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 06, 2023	Feb. 23, 2024~ Feb. 24, 2024	Jul. 05, 2024	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44GHz	May 15, 2023	Feb. 05, 2024	May 14, 2024	Radiation (03CH03-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 10, 2023	Feb. 05, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-1GHz	Dec. 20, 2023	Feb. 05, 2024	Dec. 19, 2024	Radiation (03CH03-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Dec. 21, 2023	Feb. 05, 2024	Dec. 20, 2024	Radiation (03CH03-KS)
SHF-EHF Horn	com-power	AH-840	101116	18GHz~40GHz	Oct. 10, 2023	Feb. 05, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	413740	30MHz ~1000MHz	Jan. 05, 2024	Feb. 05, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
Amplifier	EM	EM18G40GA	060851	18~40GHz	Jan. 05, 2024	Feb. 05, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2082394	1Ghz-18Ghz	Jan. 05, 2024	Feb. 05, 2024	Jan. 04, 2025	Radiation (03CH03-KS)
Amplifier	Keysight	83017A	MY53270319	1GHz~26.5GHz	Oct. 10, 2023	Feb. 05, 2024	Oct. 09, 2024	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Feb. 05, 2024	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Feb. 05, 2024	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Feb. 05, 2024	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required

6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Spurious Emission & Bandedge	±2.26 dB
Occupied Channel Bandwidth	±0.1%
Conducted Power	±0.46 dB
Peak to Average Ratio	±0.46 dB
Frequency Stability	±0.4 Hz

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.76dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.65dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.57dB

---------- THE END ----------

Appendix A. Test Results of Conducted Test

Test Engineer :	Smile Wang	Temperature :	24~26℃
		Relative Humidity :	50~53%

Conducted Output Power(Average power)

GSM850_Ant 0

GSM850	Burst Average Power (dBm)			ERP(W)		
TX Channel	128	189	251			
Frequency (MHz)	824.2	836.4	848.8	L	M	H
GSM 1 Tx slot	32.29	32.37	32.31	0.5176	0.5272	0.5200
GPRS 1 Tx slot	32.31	32.34	32.35	0.5200	0.5236	0.5248
GPRS 2 Tx slots	29.31	29.33	29.28	0.2606	0.2618	0.2588
GPRS 3 Tx slots	27.21	27.22	27.24	0.1607	0.1611	0.1618
GPRS 4 Tx slots	26.35	26.36	26.31	0.1318	0.1321	0.1306
EDGE 1 Tx slot	26.43	26.51	26.44	0.1343	0.1368	0.1346
EDGE 2 Tx slots	25.23	25.25	25.21	0.1019	0.1023	0.1014
EDGE 3 Tx slots	22.91	22.89	22.87	0.0597	0.0594	0.0592
EDGE 4 Tx slots	21.37	21.37	21.31	0.0419	0.0419	0.0413

GSM1900_Ant 1

GSM1900	Burst Average Power (dBm)			EIRP(W)		
TX Channel	512	661	810			
Frequency (MHz)	1850.2	1880	1909.8	L	M	H
GSM 1 Tx slot	29.47	29.52	29.53	0.4977	0.5035	0.5047
GPRS 1 Tx slot	29.26	29.26	29.21	0.4742	0.4742	0.4688
GPRS 2 Tx slots	26.91	26.96	26.88	0.2761	0.2793	0.2742
GPRS 3 Tx slots	24.71	24.73	24.67	0.1663	0.1671	0.1648
GPRS 4 Tx slots	23.90	23.93	23.88	0.1380	0.1390	0.1374
EDGE 1 Tx slot	25.60	25.62	25.57	0.2042	0.2051	0.2028
EDGE 2 Tx slots	23.17	23.16	23.14	0.1167	0.1164	0.1159
EDGE 3 Tx slots	21.44	21.47	21.38	0.0783	0.0789	0.0773
EDGE 4 Tx slots	19.02	19.09	19.03	0.0449	0.0456	0.0450

WCDMA Band V_Ant 0

Band		WCDMA V			ERP(W)		
TX Channel		4132	4182	4233			
Rx Channel		4357	4407	4458			
Frequency (MHz)		826.4	836.4	846.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.11	23.15	23.18	0.0625	0.0631	0.0635
3GPP Rel 99	RMC 12.2Kbps	23.14	23.20	23.10	0.0630	0.0638	0.0624
3GPP Rel 6	HSDPA Subtest-1	22.15	22.16	22.20	0.0501	0.0502	0.0507
3GPP Rel 6	HSDPA Subtest-2	22.06	22.07	22.12	0.0491	0.0492	0.0498
3GPP Rel 6	HSDPA Subtest-3	21.38	21.51	21.36	0.0420	0.0433	0.0418
3GPP Rel 6	HSDPA Subtest-4	21.62	21.65	21.63	0.0444	0.0447	0.0445
3GPP Rel 6	HSUPA Subtest-1	22.20	22.16	22.16	0.0507	0.0502	0.0502
3GPP Rel 6	HSUPA Subtest-2	20.06	20.01	20.05	0.0310	0.0306	0.0309
3GPP Rel 6	HSUPA Subtest-3	21.11	21.08	21.04	0.0394	0.0392	0.0388
3GPP Rel 6	HSUPA Subtest-4	20.03	20.04	20.06	0.0308	0.0308	0.0310
3GPP Rel 6	HSUPA Subtest-5	22.14	22.17	22.14	0.0500	0.0504	0.0500
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.34	19.31	19.23	0.0262	0.0261	0.0256

WCDMA Band II_Ant 1

Band		WCDMA II			EIRP(W)		
TX Channel		9262	9400	9538			
Rx Channel		9662	9800	9938			
Frequency (MHz)		1852.4	1880	1907.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.14	23.11	23.10	0.1159	0.1151	0.1148
3GPP Rel 99	RMC 12.2Kbps	23.18	23.20	23.16	0.1169	0.1175	0.1164
3GPP Rel 6	HSDPA Subtest-1	22.11	22.18	22.14	0.0914	0.0929	0.0920
3GPP Rel 6	HSDPA Subtest-2	22.12	22.01	22.14	0.0916	0.0893	0.0920
3GPP Rel 6	HSDPA Subtest-3	21.38	21.53	21.32	0.0773	0.0800	0.0762
3GPP Rel 6	HSDPA Subtest-4	21.11	21.16	21.12	0.0726	0.0735	0.0728
3GPP Rel 6	HSUPA Subtest-1	22.06	22.10	22.13	0.0904	0.0912	0.0918
3GPP Rel 6	HSUPA Subtest-2	20.05	20.03	20.06	0.0569	0.0566	0.0570
3GPP Rel 6	HSUPA Subtest-3	21.12	21.11	21.08	0.0728	0.0726	0.0721
3GPP Rel 6	HSUPA Subtest-4	20.06	20.15	20.11	0.0570	0.0582	0.0577
3GPP Rel 6	HSUPA Subtest-5	22.19	22.21	22.12	0.0931	0.0935	0.0916
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.64	19.61	19.59	0.0518	0.0514	0.0512

WCDMA Band IV_Ant 1

Band		WCDMA IV			EIRP(W)		
TX Channel		1312	1413	1513			
Rx Channel		1537	1638	1738			
Frequency (MHz)		1712.4	1732.6	1752.6	L	M	H
3GPP Rel 99	AMR 12.2Kbps	23.01	23.12	23.15	0.1262	0.1294	0.1303
3GPP Rel 99	RMC 12.2Kbps	23.13	23.18	23.11	0.1297	0.1312	0.1291
3GPP Rel 6	HSDPA Subtest-1	22.41	22.53	22.36	0.1099	0.1130	0.1086
3GPP Rel 6	HSDPA Subtest-2	22.00	22.11	22.06	0.1000	0.1026	0.1014
3GPP Rel 6	HSDPA Subtest-3	20.01	22.08	22.10	0.0632	0.1019	0.1023
3GPP Rel 6	HSDPA Subtest-4	20.64	20.65	20.61	0.0731	0.0733	0.0726
3GPP Rel 6	HSUPA Subtest-1	20.33	20.26	20.31	0.0681	0.0670	0.0678
3GPP Rel 6	HSUPA Subtest-2	21.37	21.31	21.28	0.0865	0.0853	0.0847
3GPP Rel 6	HSUPA Subtest-3	19.26	19.21	19.14	0.0532	0.0526	0.0518
3GPP Rel 6	HSUPA Subtest-4	20.15	20.16	20.15	0.0653	0.0655	0.0653
3GPP Rel 6	HSUPA Subtest-5	21.36	21.32	21.29	0.0863	0.0855	0.0849
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	18.73	18.71	18.67	0.0471	0.0469	0.0465

A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.17	3.04	PASS
Middle CH	0.17	2.99	
Highest CH	0.38	3.28	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.35	3.07	PASS
Middle CH	0.38	3.25	
Highest CH	0.41	3.16	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

26dB Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.311	0.309
Middle CH	0.316	0.314
Highest CH	0.315	0.308

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.313	0.314
Middle CH	0.317	0.314
Highest CH	0.313	0.314

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.240	0.236
Middle CH	0.242	0.239
Highest CH	0.240	0.237

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.244	0.250
Middle CH	0.242	0.247
Highest CH	0.241	0.243

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Cannel**
	

Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.71678 MHz	-46.35 dBm	-33.35 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-17.21 dBm	-4.21 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.27196 MHz	21.97 dBm	-13.03 dB

Date: 23.FEB.2024 20:52:39

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.86776 MHz	22.31 dBm	-12.69 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01497 MHz	-17.49 dBm	-4.49 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.23726 MHz	-46.89 dBm	-33.89 dB

Date: 23.FEB.2024 20:55:19

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.95355 MHz	-47.66 dBm	-34.66 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.98703 MHz	-22.37 dBm	-9.37 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.21707 MHz	15.18 dBm	-19.82 dB

Date: 23.FEB.2024 21:25:36

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.74900 MHz	15.28 dBm	-19.72 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.02096 MHz	-25.44 dBm	-12.44 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.01249 MHz	-48.04 dBm	-35.04 dB

Date: 23.FEB.2024 21:27:10

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-39.16 dBm	-26.16 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-19.87 dBm	-6.87 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85018 GHz	22.35 dBm	-12.65 dB

Date: 23.FEB.2024 21:53:55

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90987 GHz	22.63 dBm	-12.37 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-21.96 dBm	-8.96 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-38.68 dBm	-25.68 dB

Date: 23.FEB.2024 21:55:35

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84900 GHz	-39.78 dBm	-26.78 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84999 GHz	-27.86 dBm	-14.86 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85022 GHz	17.39 dBm	-17.61 dB

Date: 23.FEB.2024 22:28:49

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90980 GHz	15.96 dBm	-19.04 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-29.37 dBm	-16.37 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91102 GHz	-39.65 dBm	-26.65 dB

Date: 23.FEB.2024 22:31:54

Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	624.77011 MHz	-36.45 dBm	-23.45 dB
855.000 MHz	1.000 GHz	1.000 MHz	997.13768 MHz	-35.75 dBm	-22.75 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.59593 GHz	-34.54 dBm	-21.54 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.66079 GHz	-29.47 dBm	-16.47 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.92038 GHz	-30.77 dBm	-17.77 dB

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	759.00300 MHz	-35.36 dBm	-22.36 dB
855.000 MHz	1.000 GHz	1.000 MHz	992.78986 MHz	-34.71 dBm	-21.71 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.67254 GHz	-33.65 dBm	-20.65 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.38883 GHz	-30.10 dBm	-17.10 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00012 GHz	-29.31 dBm	-16.31 dB

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	778.74313 MHz	-35.72 dBm	-22.72 dB
855.000 MHz	1.000 GHz	1.000 MHz	984.31159 MHz	-34.94 dBm	-21.94 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.40895 GHz	-33.77 dBm	-20.77 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.82390 GHz	-30.59 dBm	-17.59 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.36858 GHz	-31.00 dBm	-18.00 dB

GSM850 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	529.22789 MHz	-36.06 dBm	-23.06 dB
855.000 MHz	1.000 GHz	1.000 MHz	921.12319 MHz	-35.21 dBm	-22.21 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.95813 GHz	-35.12 dBm	-22.12 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.78840 GHz	-30.44 dBm	-17.44 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.54156 GHz	-31.16 dBm	-18.16 dB

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	798.87806 MHz	-35.78 dBm	-22.78 dB
855.000 MHz	1.000 GHz	1.000 MHz	876.34058 MHz	-35.53 dBm	-22.53 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.98738 GHz	-34.45 dBm	-21.45 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.89576 GHz	-29.87 dBm	-16.87 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.01762 GHz	-30.84 dBm	-17.84 dB

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	745.97451 MHz	-35.57 dBm	-22.57 dB
855.000 MHz	1.000 GHz	1.000 MHz	907.50000 MHz	-34.46 dBm	-21.46 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.51269 GHz	-33.74 dBm	-20.74 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.82327 GHz	-29.17 dBm	-16.17 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.71241 GHz	-30.84 dBm	-17.84 dB

GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	912.01649 MHz	-33.66 dBm	-20.66 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.65307 GHz	-35.21 dBm	-22.21 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.65901 GHz	-33.37 dBm	-20.37 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.74328 GHz	-29.25 dBm	-16.25 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.68479 GHz	-29.36 dBm	-16.36 dB
13.600 GHz	19.100 GHz	1.000 MHz	17.69780 GHz	-25.37 dBm	-12.37 dB

Date: 23.FEB.2024 22:03:09

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	919.77261 MHz	-35.78 dBm	-22.78 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.57495 GHz	-34.03 dBm	-21.03 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.55066 GHz	-32.73 dBm	-19.73 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.68541 GHz	-29.49 dBm	-16.49 dB
7.000 GHz	13.600 GHz	1.000 MHz	10.63893 GHz	-29.17 dBm	-16.17 dB
13.600 GHz	19.100 GHz	1.000 MHz	17.70447 GHz	-24.11 dBm	-11.11 dB

Date: 23.FEB.2024 22:04:29

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	624.55522 MHz	-34.30 dBm	-21.30 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.48964 GHz	-34.84 dBm	-21.84 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.58443 GHz	-32.01 dBm	-19.01 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.03137 GHz	-29.67 dBm	-16.67 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.35040 GHz	-29.96 dBm	-16.96 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.21840 GHz	-25.05 dBm	-12.05 dB

Date: 23.FEB.2024 22:06:02

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	767.07396 MHz	-34.71 dBm	-21.71 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.57621 GHz	-34.55 dBm	-21.55 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.51351 GHz	-33.01 dBm	-20.01 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.04637 GHz	-29.41 dBm	-16.41 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.93055 GHz	-29.77 dBm	-16.77 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.01413 GHz	-24.31 dBm	-11.31 dB

Date: 23.FEB.2024 22:39:40

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	830.09245 MHz	-35.19 dBm	-22.19 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.76160 GHz	-34.96 dBm	-21.96 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.55622 GHz	-33.33 dBm	-20.33 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.86089 GHz	-28.54 dBm	-15.54 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.37195 GHz	-28.68 dBm	-15.68 dB
13.600 GHz	19.100 GHz	1.000 MHz	17.72372 GHz	-25.39 dBm	-12.39 dB

Date: 23.FEB.2024 22:40:16

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	783.55572 MHz	-35.22 dBm	-22.22 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.79369 GHz	-34.29 dBm	-21.29 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.81117 GHz	-33.51 dBm	-20.51 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.90126 GHz	-29.37 dBm	-16.37 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.39565 GHz	-29.55 dBm	-16.55 dB
13.600 GHz	19.100 GHz	1.000 MHz	17.69073 GHz	-25.18 dBm	-12.18 dB

Date: 23.FEB.2024 22:40:57

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0079	0.0076	PASS
40	Normal Voltage	0.0023	0.0093	
30	Normal Voltage	0.0031	0.0062	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0026	0.0044	
0	Normal Voltage	0.0032	0.0078	
-10	Normal Voltage	0.0047	0.0024	
-20	Normal Voltage	0.0025	0.0017	
-30	Normal Voltage	0.0021	0.0031	
20	Maximum Voltage	0.0034	0.0042	
20	Normal Voltage	0.0029	0.0012	
20	Battery End Point	0.0053	0.0037	

Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0055	0.0029	PASS
40	Normal Voltage	0.0046	0.0085	
30	Normal Voltage	0.0072	0.0079	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0078	0.0064	
0	Normal Voltage	0.0050	0.0022	
-10	Normal Voltage	0.0029	0.0057	
-20	Normal Voltage	0.0013	0.0024	
-30	Normal Voltage	0.0026	0.0072	
20	Maximum Voltage	0.0047	0.0042	
20	Normal Voltage	0.0021	0.0059	
20	Battery End Point	0.0066	0.0045	

Note:

1. Normal Voltage = 3.91V ; Battery End Point (BEP) =3.5V. ; Maximum Voltage =4.5V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.22	3.01	3.10	PASS
Middle CH	3.16	2.99	3.01	
Highest CH	3.16	3.16	3.10	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.705	4.715	4.715
Middle CH	4.705	4.725	4.715
Highest CH	4.705	4.715	4.725