

FCC TEST REPORT

Name of Sample: Mobile Cellular Phone
Model of Sample: XT2407-1
Applicant: Motorola Mobility LLC
Issue Date: 2024-05-28



ADR TEST AND CERTIFICATION CENTER
Motorola Mobility LLC, a Lenovo Company

Add: No. 19, Gao Xin 4th Road Wuhan, People's Republic of China 430205

Phone: (86)18702717862


E-mail: lucz1@motorola.com

Name of Client	Motorola Mobility LLC		
Address of Client	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA		
Trademark	Motorola	Type Name or ID	FCC ID: IHDT56AS2
Applicant No.	RF177413	Sample No.	1#: NWRE250104 2#: NWRE250106
Delivering Date	2024-04-22	Test Date	2024-04-23 to 2024-05-28
Sample Illustration	None		
Standard	47 CFR Part 2; 47 CFR Part 22; 47 CFR Part 24; 47 CFR Part 27; 47 CFR Part 90;		
Conclusion	Pass		
Remarks	N/A		

Editor: Wangzhenyu



Auditor: Hexiaolin



Approver: HuangshengLin



Matters Needing Attention

- a) The electronic report shall be valid after encryption.
- b) The paper report shall be valid after being stamped with the official seal of the company.
- c) The report is invalid without the signature of the Editor, Auditor and Approver.
- d) The test report is invalid if there is any evidence of erasure and/or falsification.
- e) If there is any dissidence for the test report, please file objection to the lab within 15 days from the date of receiving the test report.
- f) The test report is only responsible for the tested model/sample. The sample(s) presented in this report are provided by client.
- g) Context of the test report cannot be used partially or in full for publicity and/or promotional purposes without previous written approval of the lab.

Revision History

Report No.	Version	Description	Issued Date
TR-24ADRTCC7012	Rev.01	Initial issue of report	2024-05-22
TR-24ADRTCC7012	Rev.02	Update RSE report no. to FG441212-01B	2024-05-28

Catalogue

1. TEST SUMMARY	5
1.1. 5G NR BAND N5/N26.....	5
1.2. 5G NR BAND N7/N38/N41	5
1.3. EUTRA BAND 26 (814-824) & 5G NR BAND N26 (814-824)	5
1.4. 5G NR BAND N77 (3700-3980)/N78 (3700-3800)	6
2. SUMMARY OF 5G NR SPOT CHECK	7
3. MAXIMUM EFFECTIVE RADIATED (ISOTROPIC) POWER AND EMISSION DESIGNATOR.....	8
3.1. NR SYSTEM.....	8
4. GENERAL INFORMATION	10
4.1. GENERAL DESCRIPTION OF EUT	10
4.2. TEST ENVIRONMENT	10
4.3. SPECIFICATION OF ACCESSORIES	11
5. TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	11
5.1. TEST MODE FOR NR CONFIGURATION	11
5.2. TEST FREQUENCIES	12
6. DESCRIPTION OF TESTS	14
6.1. CONDUCTED OUTPUT POWER MEASUREMENT	14
6.2. EFFECTIVE (ISOTROPIC) RADIATED POWER	15
6.3. PEAK-TO-AVERAGE RATIO MEASUREMENT	15
6.4. 99% OCCUPIED BANDWIDTH & 26DB EMISSION BANDWIDTH	16
6.5. CONDUCTED BAND EDGE MEASUREMENT	16
6.6. CONDUCTED SPURIOUS EMISSION MEASUREMENT	17
7. LIST OF MEASURING EQUIPMENT	17
8. MEASUREMENT UNCERTAINTY	18
8.1. UNCERTAINTY OF CONDUCTED MEASUREMENT	18
9. APPENDIXES	18

1. Test Summary

1.1. 5G NR Band n5/n26

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Radiated Power	§22.913(a)(5)	ERP < 7W		
Peak-Average Ratio	§22.913(d)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §22.917(a)	< -13 dBm/1%*EBW, in 1 MHz bands immediately outside and adjacent to the frequency block.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §22.917(a)	< -13 dBm/100 kHz, from 9 kHz to 10th harmonics but outside authorized operating frequency ranges	Section 6 of Appendix B	Pass
Frequency Stability	§2.1055 §22.355	< ±2.5ppm	Section 7 of Appendix B	Pass

1.2. 5G NR Band n7/n38/n41

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§27.50(h) (2)	EIRP < 2W		
Peak-Average Ratio	§27.50(a)	<13 dB	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(m) (4)	For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section In addition, the attenuation factor shall not be less than 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5MHz.	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(m) (4)	< -25 dBm/MHz for outside Band Edge Range	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

1.3. EUTRA Band 26 (814-824) & 5G NR Band n26 (814-824)

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046 §90.635	Report Only	Section 1 of Appendix B	PASS
Peak-Average Ratio	---	<13 dB	Section 2 of Appendix B	PASS
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	PASS
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	PASS
26dB Emission Bandwidth		No limit		

Test Item	Rule No.	Requirements	Test Result	Verdict
Emission Mask	§2.1051 § 90.691	For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.	Section 5 of Appendix B	PASS
Conducted Spurious Emission	§2.1051 §90.691	$< 43 + 10 \log_{10}(P[\text{Watts}])$ for all out-of-band emissions	Section 6 of Appendix B	PASS
Frequency Stability	§90.213	$< \pm 2.5 \text{ ppm}$	Section 7 of Appendix B	PASS

1.4. 5G NR Band n77 (3700-3980)/n78 (3700-3800)

Test Item	Rule No.	Requirements	Test Result	Verdict
Conducted Power	§2.1046	Report Only	Section 1 of Appendix B	Pass
Effective Isotropic Radiated Power	§27.50(j) (3)	EIRP $< 1\text{W}$		
Peak-Average Ratio	§27.50(j) (4)	$< 13 \text{ dB}$	Section 2 of Appendix B	Pass
Modulation Characteristics	§2.1047	Digital modulation	Section 3 of Appendix B	Pass
Occupied Bandwidth	§2.1049	No limit	Section 4 of Appendix B	Pass
26dB Emission Bandwidth		No limit		
Conducted Band Edges	§2.1051 §27.53(l) (2)	$< -13 \text{ dBm/MHz}$	Section 5 of Appendix B	Pass
Conducted Spurious Emission	§2.1051 §27.53(l) (2)	$< -13 \text{ dBm/MHz}$	Section 6 of Appendix B	Pass
Frequency Stability	§27.54	Within authorized bands	Section 7 of Appendix B	Pass

Remark:

- Only 5G NR Bands conducted test performed and the data displayed in this report, the radiated spurious emission refer to the report (FG441212-01B).
- The maximum E(I)RP is calculated from max output power and max antenna gain, only the max E(I)RP data displayed in this report, n5/n26 for Antenna 0; n7/n38/n41 for antenna 1; n77/n78 for antenna 4.
- 5G NR Bands support SA mode for n5/n7/n26/n38/n41/n77/n78 and NSA mode for n5/n7/n38/n41/n77/n78.
- The test has been assessed on SA and NSA mode, but only the worst mode performed the whole conducted test items by referring to the max conducted power.
- The ENDC combination could be referred to the product specification.
- 5G NR n77/n78 supports HPUE mode.

2. Summary of 5G NR Spot Check

Test Item	Mode	Worst Mode Test Result		Deviation (dB)	Limit (dB)
		IHDT56AS3	IHDT56AS2		
Conducted Power	n5	22.93	22.97	0.04	3
	n7	23.59	23.68	0.09	3
	n38	23.86	23.88	0.02	3
	n41	23.91	23.82	-0.09	3

This application re-uses data collected on a similar device. The subject device of this application (Model: XT2407-1, FCC ID: IHDT56AS2) is electrically identical to the reference device (Model: XT2407-2, FCC ID: IHDT56AS3) for the portions of the circuitry corresponding to the data being re-used. Based on their similarity. The FCC Part 22, 24, 27(equipment class: PCE) referencing the original model's result and do spot check, following the FCC KDB484596 D01 Referencing Test Data v02r02.

Compared the device (Model: XT2407-1, FCC ID: IHDT56AS2) with the reference device (Model: XT2407-2, FCC ID: IHDT56AS3), according to the maximum conducted output power comparison result, therefor, band n7 was defined as the worst band and full test the conducted item to demonstrate the compliance, and the data displayed in appendix B.1.

Model difference information

The main difference between FCC ID: IHDT56AS2 and FCC ID: IHDT56AS3 is as below:

- Remove LTE B25/26 and 5G NR n2/n66.
- Add LTE B20/32/39/43 and 5G NR n20/n26/n75/n77.

Other difference and all the details of similarity and difference can be found in the confidential documents (Operational Description of Product Equality Declaration).

3. Maximum Effective Radiated (Isotropic) Power and Emission Designator

3.1. NR System

3.1.1. NR Band n7 (2500-2570)

5G NR SA (n7A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
5MHz	2502.5-2567.5	0.123595	4M50G7D	0.107647	4M53W7D
10MHz	2505.0-2565.0	0.122462	9M31G7D	0.103039	9M31W7D
15MHz	2507.5-2562.5	0.129420	14M2G7D	0.107399	14M2W7D
20MHz	2510.0-2560.0	0.129718	19M0G7D	0.107895	19M0W7D
25MHz	2512.5-2557.5	0.128825	23M8G7D	0.104954	23M8W7D
30MHz	2515.0-2555.0	0.128233	28M7G7D	0.106660	28M7W7D
40MHz	2520.0-2550.0	0.131826	38M8G7D	0.106660	38M7W7D

3.1.2. NR Band n26 (814-824)

5G NR SA (n26A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum Conducted Power (W)	Emission Designator (99% OBW)	Maximum Conducted Power (W)	Emission Designator (99% OBW)
5MHz	816.5-821.5	0.197697	4M50G7D	0.197242	4M49W7D
10MHz	819.0	0.195434	9M27G7D	0.193197	9M29W7D
15MHz	821.5	0.200909	14M1G7D	0.198153	14M1W7D
20MHz	824.0	0.203236	18M9G7D	0.199986	19M0W7D

3.1.3. NR Band n26 (824-849)

5G NR SA (n26A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum ERP (W)	Emission Designator (99% OBW)	Maximum ERP (W)	Emission Designator (99% OBW)
5MHz	826.5-846.5	0.032434	4M49G7D	0.032063	4M51W7D
10MHz	829.0-844.0	0.032063	9M27G7D	0.031769	9M29W7D
15MHz	831.5-841.5	0.032659	14M1G7D	0.032137	14M1W7D
20MHz	834.0-839.0	0.032659	18M9G7D	0.032211	18M9W7D

3.1.4. NR Band n77 (3700-3980)

5G NR SA (n77A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	3705.00-3975.00	0.372392	8M61G7D	0.370681	8M61W7D
15MHz	3707.52-3972.48	0.393550	13M6G7D	0.391742	13M7W7D
20MHz	3710.01-3969.99	0.393550	18M2G7D	0.386367	18M3W7D
30MHz	3715.02-3964.98	0.398107	27M9G7D	0.390841	27M9W7D
40MHz	3720.00-3960.00	0.399945	38M0G7D	0.396278	37M9W7D
50MHz	3725.01-3954.99	0.391742	47M5G7D	0.385478	47M6W7D
60MHz	3730.02-3949.98	0.390841	57M8G7D	0.389942	57M8W7D
70MHz	3735.00-3945.00	0.368129	67M6G7D	0.365595	67M6W7D
80MHz	3740.01-3939.99	0.363078	77M5G7D	0.363078	77M7W7D
90MHz	3745.02-3934.98	0.375837	87M4G7D	0.377572	87M6W7D
100MHz	3750.00-3930.00	0.373250	97M5G7D	0.374111	97M5W7D

3.1.5. NR Band n78 (3700-3800)

5G NR SA (n78A)		Pi/2 BPSK / QPSK		16QAM/64QAM/256QAM	
Bandwidth	Frequency Range (MHz)	Maximum EIRP (W)	Emission Designator (99% OBW)	Maximum EIRP (W)	Emission Designator (99% OBW)
10MHz	3705.00-3795.00	0.362243	8M61G7D	0.355631	8M61W7D
15MHz	3707.52-3792.48	0.363078	13M6G7D	0.363078	13M7W7D
20MHz	3710.01-3789.99	0.367282	18M2G7D	0.369828	18M2W7D
30MHz	3715.02-3784.98	0.374111	27M9G7D	0.377572	27M9W7D
40MHz	3720.00-3780.00	0.389942	37M9G7D	0.389942	37M9W7D
50MHz	3725.01-3774.99	0.353183	47M5G7D	0.352371	47M5W7D
60MHz	3730.02-3769.98	0.358922	57M8G7D	0.358922	57M8W7D
70MHz	3735.00-3765.00	0.350752	67M6G7D	0.356451	67M6W7D
80MHz	3740.01-3759.99	0.358096	77M4G7D	0.358922	77M5W7D
90MHz	3745.02-3754.98	0.364754	87M4G7D	0.362243	87M6W7D
100MHz	3750.00	0.367282	97M3G7D	0.363078	97M5W7D

4. General Information

4.1. General Description of EUT

EUT Description:	Mobile Cellular Phone
Brand Name:	Motorola
Model Name:	XT2407-1
FCC ID:	IHDT56AS2
IMEI Code:	1#: 355519300014255/355519300014263 (Conducted); 2#: 355519300014099/355519300014107 (Conducted);
Hardware Version:	DVT2
Software Version:	U3UW34.43
NR Modulation:	DFT-s-OFDM: ☒ Pi/2BPSK; ☒ QPSK; ☒ 16QAM; ☒ 64QAM; ☒ 256QAM; CP-OFDM: ☒ QPSK; ☒ 16QAM; ☒ 64QAM; ☒ 256QAM;
Sample Type:	☒ Portable Device, ☐ Module
Antenna Type:	☐ External, ☒ Integrated
Antenna Gain:	n5: -5.60dBi (Ant0); -6.38dBi (Ant1); n7: -1.36dBi (Ant0); -2.48dBi (Ant1); -0.44dBi (Ant2); n26: -5.60dBi (Ant0); -6.38dBi (Ant1); n38: -1.36dBi (Ant0); -2.48dBi (Ant1); -0.44dBi (Ant2); -4.10dBi (Ant5); n41: -1.36dBi (Ant0); -2.48dBi (Ant1); -0.44dBi (Ant2); -2.50dBi (Ant5); n77: -3.41dBi (Ant3); -0.87dBi (Ant4); -3.22dBi (Ant6); -3.64dBi (Ant9); n78: -3.41dBi (Ant3); -0.87dBi (Ant4); -3.22dBi (Ant6); -3.64dBi (Ant9);

Remark

- The information above was declared by manufacture. Please refer to the specifications or user manual for more detailed description.

4.2. Test Environment

Relative Humidity:	52.0% - 62.0%	
Atmospheric Pressure:	101.32 KPa	
Temperature:	NT (normal temperature)	25.0 °C – 27.5 °C
Voltage:	LV (Low voltage)	3.40V
	NV (Nominal voltage)	3.91V
	HV (High voltage)	4.50V

4.3. Specification of Accessories

Accessory	Brand Name	Model Name
AC Adapter 1 (US)	Motorola (Chenyang)	MC-681N
AC Adapter 2 (EU)	Motorola (Chenyang)	MC-682N
AC Adapter 3 (UK)	Motorola (Chenyang)	MC-683N
AC Adapter 4 (AU)	Motorola (Chenyang)	MC-685N
AC Adapter 5 (AR)	Motorola (Chenyang)	MC-686N
AC Adapter 6 (CHILE)	Motorola (Chenyang)	MC-689N
AC Adapter 7 (US)	Motorola (Acbel)	MC-681N
AC Adapter 8 (EU)	Motorola (Acbel)	MC-682N
AC Adapter 9 (UK)	Motorola (Acbel)	MC-683N
AC Adapter 10 (AU)	Motorola (Acbel)	MC-685N
AC Adapter 11 (AR)	Motorola (Acbel)	MC-686N
Battery 1	Motorola (SUNWODA)	QR50
Battery 2	Motorola (ATL)	QR50
USB Cable 1	Luxshare	SC18E08104
USB Cable 2	Saibao	SC18D71644

5. Test Configuration of Equipment Under Test

5.1. Test Mode for NR Configuration

Test Case	5G NR	SCS		Bandwidth	Modulation					Channel			RB	
		15KHz	30KHz		PI/2BPSK	QPSK	16QAM	64QAM	256QAM	LCH	MCH	HCH	1	Full
Effective Isotropic Radiated Power	N5 (824-849)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N7 (2500-2570)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N26 (814-824)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N26 (824-849)	●	○	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N38 (2570-2620)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N41 (2496-2690)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
	N78(3700-3800)	○	●	All Supported BW	●	●	●	●	●	●	●	●	●	●
Peak-Average Ratio	N7 (2500-2570)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N26 (814-824)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N26 (824-849)	●	○	Highest BW	●	●	○	○	○	●	●	●	○	●
	N77 (3700-3980)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●
	N78(3700-3800)	○	●	Highest BW	●	●	○	○	○	●	●	●	○	●
Modulation Characteristics	N7 (2500-2570)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N26 (814-824)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N26 (824-849)	●	○	Highest BW	●	●	●	●	●	○	●	○	○	●
	N77 (3700-3980)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
	N78(3700-3800)	○	●	Highest BW	●	●	●	●	●	○	●	○	○	●
Occupied Bandwidth &	N7 (2500-2570)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N26 (814-824)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●

26dB Emission Bandwidth	N26 (824-849)	●	○	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●
	N78(3700-3800)	○	●	All Supported BW	●	●	●	●	●	○	●	○	○	●
Conducted Band Edges	N7 (2500-2570)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N26 (814-824)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N26 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N77 (3700-3980)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●
	N78(3700-3800)	○	●	All Supported BW	●	●	○	○	○	●	○	●	●	●
Conducted Spurious Emission	N7 (2500-2570)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N26 (814-824)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N26 (824-849)	●	○	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N77 (3700-3980)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○
	N78(3700-3800)	○	●	All Supported BW	●	●	○	○	○	●	●	●	●	○
Frequency Stability	N7 (2500-2570)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N26 (814-824)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N26 (824-849)	●	○	Highest BW	○	●	○	○	○	○	●	○	○	●
	N77 (3700-3980)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●
	N78(3700-3800)	○	●	Highest BW	○	●	○	○	○	○	●	○	○	●

Remark:

- 1, the mark “●” means this configuration was chosen for testing, mark “○” means not selected, and the mark “✕” means not applicable.
- 2, All Supported BW means all supported bandwidth for selected SCS configuration.

5.2. Test Frequencies

5.2.1. 5G NR System

5.2.1.1. NR Band n5 (824-849)

5.2.1.1.1. SCS=15KHz

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	165300	826.5	167300	836.5	169300	846.5
10MHz	165800	829.0	167300	836.5	168800	844.0
15MHz	166300	831.5	167300	836.5	168300	841.5
20MHz	166800	834.0	167300	836.5	167800	839.0

5.2.1.2. NR Band n7 (2500-2570)

5.2.1.2.1. SCS=15KHz

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	500500	2502.5	507000	2535.0	513500	2567.5
10MHz	501000	2505.0	507000	2535.0	513000	2565.0
15MHz	501500	2507.5	507000	2535.0	512500	2562.5
20MHz	502000	2510.0	507000	2535.0	512000	2560.0
25MHz	502500	2512.5	507000	2535.0	511500	2557.5
30MHz	503000	2515.0	507000	2535.0	511000	2555.0
40MHz	504000	2520.0	507000	2535.0	510000	2550.0

5.2.1.3. NR Band n26 (814-824)**5.2.1.3.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	163300	816.5	163800	819.0	164300	821.5
10MHz	163800	819.0	163800	819.0	163800	819.0
15MHz	164300	821.5	164300	821.5	164300	821.5
20MHz	164800	824.0	164800	824.0	164800	824.0

5.2.1.4. NR Band n26 (824-849)**5.2.1.4.1. SCS=15KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
5MHz	165300	826.5	167300	836.5	169300	846.5
10MHz	165800	829.0	167300	836.5	168800	844.0
15MHz	166300	831.5	167300	836.5	168300	841.5
20MHz	166800	834.0	167300	836.5	167800	839.0

5.2.1.5. NR Band n38 (2570-2620)**5.2.1.5.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	515000	2575.0	519000	2595.0	523000	2615.0
15MHz	515500	2577.5	519000	2595.0	522500	2612.5
20MHz	516000	2580.0	519000	2595.0	522000	2610.0
30MHz	517000	2585.0	519000	2595.0	521000	2605.0
40MHz	518000	2590.0	519000	2595.0	520000	2600.0

5.2.1.6. NR Band n41 (2496-2690)**5.2.1.6.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
20MHz	501204	2506.02	518598	2592.99	535998	2679.99
30MHz	502200	2511.00	518598	2592.99	534996	2674.98
40MHz	503202	2516.01	518598	2592.99	534000	2670.00
50MHz	504204	2521.02	518598	2592.99	532998	2664.99
60MHz	505200	2526.00	518598	2592.99	531996	2659.98
70MHz	506202	2531.01	518598	2592.99	531000	2655.00
80MHz	507204	2536.02	518598	2592.99	529998	2649.99
90MHz	508200	2541.00	518598	2592.99	528996	2644.98
100MHz	509202	2546.01	518598	2592.99	528000	2640.00

5.2.1.7. NR Band N77 (3700-3980)**5.2.1.7.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	647000	3705.00	656000	3840.00	665000	3975.00
15MHz	647168	3707.52	656000	3840.00	664832	3972.48
20MHz	647334	3710.01	656000	3840.00	664666	3969.99
30MHz	647668	3715.02	656000	3840.00	664332	3964.98
40MHz	648000	3720.00	656000	3840.00	664000	3960.00
50MHz	648334	3725.01	656000	3840.00	663666	3954.99
60MHz	648668	3730.02	656000	3840.00	663332	3949.98
70MHz	649000	3735.00	656000	3840.00	663000	3945.00
80MHz	649334	3740.01	656000	3840.00	662666	3939.99
90MHz	649668	3745.02	656000	3840.00	662332	3934.98
100MHz	650000	3750.00	656000	3840.00	662000	3930.00

5.2.1.8. NR Band N78 (3700-3800)**5.2.1.8.1. SCS=30KHz**

Bandwidth	LCH		MCH		HCH	
	Arfcn	Freq	Arfcn	Freq	Arfcn	Freq
10MHz	647000	3705.00	650000	3750.00	653000	3795.00
15MHz	647168	3707.52	650000	3750.00	652832	3792.48
20MHz	647334	3710.01	650000	3750.00	652666	3789.99
30MHz	647668	3715.02	650000	3750.00	652332	3784.98
40MHz	648000	3720.00	650000	3750.00	652000	3780.00
50MHz	648334	3725.01	650000	3750.00	651666	3774.99
60MHz	648668	3730.02	650000	3750.00	651332	3769.98
70MHz	649000	3735.00	650000	3750.00	651000	3765.00
80MHz	649334	3740.01	650000	3750.00	650666	3759.99
90MHz	649668	3745.02	650000	3750.00	650332	3754.98
100MHz	650000	3750.00	650000	3750.00	650000	3750.00

6. Description of Tests**6.1. Conducted Output Power Measurement****6.1.1. Description of Conducted Output Power Measurement**

A base station simulator was used to establish communication with the EUT, Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

6.1.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.2.
- 2, The transmitter output port was connected to the system simulator.
- 3, Set EUT at maximum power through the system simulator.
- 4, Select lowest, Middle, Highest channels for each band and each modulation.
- 5, Record the reading power from the system simulator.

6.2. Effective (Isotropic) Radiated Power

Measurement Procedure: ANSI C63.26

Calculate power in dBm by the following formula:

ERP (dBm) = Conducted Power (dBm) + antenna gain (dBd)

EIRP (dBm) = Conducted Power (dBm) + antenna gain (dBi)

EIRP=ERP+2.15dB

6.3. Peak-to-Average Ratio Measurement

6.3.1. Description of PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13dB.

6.3.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.2.3.4(CCDF)
- 2, Refer to instrument's analyser instruction manual for details on how to use the power statistics/CCDF function.
- 3, Centre Frequency = Carrier centre frequency.
- 4, Set resolution bandwidth $\geq$ signal's occupied bandwidth.
- 5, Set the number of counts to a value that stabilizes the measured CCDF curve.
- 6, Set the measurement interval as follows:
 - 1) for continuous transmissions (>98% duty cycle), set to 1ms.
 - 2) for burst transmissions, employ an external trigger that is synchronized with the EUT burst timing sequence, or use the internal burst trigger with a trigger level that allows the burst to stabilize and set the measurement interval to a time that is less than or equal to the burst duration.
- 7, Record the maximum PAR level associated with a probability of 0.1%.

6.3.3. Alternate procedure for PAR

Measurement Procedure: 5.2.6 of ANSI C63.26

Some regulatory requirements specify a PAR limit when the output power limits are specified in terms of average power. If it becomes necessary to provide measurement data to demonstrate compliance to a PAR limit, then the appropriate procedure from those provided in 5.2.3 shall be utilized to determine the peak power (or peak PSD) and the appropriate procedure from those provided in 5.2.4 shall be used to determine the average power (or average PSD). The data from these measurements is then used in Equation (2) to determine the PAR of a narrowband CW-like signal. See 5.2.3.4 for guidance on determining the PAR of a broadband noise-like signal.

$PAR (dB) = P_{Pk} (dBm \text{ or } dBW) - P_{Avg} (dBm \text{ or } dBW)$

where

PAR peak-to-average power ratio, in dB

P_{Pk} measured peak power or peak PSD level, in dBm or dBW

P_{Avg} measured average power or average PSD level, in dBm or dBW

6.4. 99% Occupied Bandwidth & 26dB Emission Bandwidth

6.4.1. Description of 99% Occupied Bandwidth & 26dB Emission Bandwidth Measurement

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel, middle channel and high channel). The span of the analyser shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

6.4.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.4
- 2, The signal analyzer's automatic measurement capability was used to perform the 99% occupied bandwidth and the 26dB emission bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
- 3, $RBW \geq 1\% - 5\%$ of the expected OBW.
- 4, $VBW \geq 3 * RBW$
- 5, Detector=Peak
- 6, Trace Mode= Max Hold.
- 7, Sweep Time=Auto
- 8, The trace was allowed to stabilize.
- 9, If necessary, steps 2-7 were repeated after changing the RBW such that it would be within 1%-5% of the 99% occupied bandwidth observed in step 7.

6.5. Conducted Band Edge Measurement

6.5.1. Description of Conducted Band Edge Measurement

The transmitter output was connected to a calibrated coaxial cable, attenuator and spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at two frequencies (low channel and high channel).in the 1MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of 100kHz or 1% of the emission bandwidth of the fundamental emission of the transmitter may be employed. The EUT emission bandwidth is measured as the width of the signal between two points, outside of which all emissions are attenuated at least 26dB below the transmitter power. The video bandwidth of the spectrum analyser was set at thrice the resolution bandwidth. Detector Mode was set to peak or peak hold power.

6.5.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.7
- 2, Start and stop frequency were set such that the band edge would be placed in the centre of the spectrum analyzer screen.

- 3, Span was set large enough to capture all out of band emissions near the band edge.
- 4, $RBW \geq 1\%$ of the emission bandwidth (2% of the emission bandwidth for n7/n38/n41 except when 1MHz band is 2495-2496MHz);
- 5, $VBW \geq 3 * RBW$
- 6, Detector=RMS
- 7, Trace Mode=Trace Average for continuous emissions, Max Hold for pulse emissions.
- 8, Sweep Points $\geq 2 \times \text{Span}/RBW$
- 9, Sweep Time = Auto
- 10, The trace was allowed to stabilize.

6.6. Conducted Spurious Emission Measurement

6.6.1. Description of Conducted Spurious Emission Measurement

The transmitter output was connected to a calibrated coaxial cable, attenuator and Spectrum analyser, the other end of which was connected to a Base Station Simulator. The Base Station Simulator was set to force the EUT to its maximum power setting. The tests were performed at three frequencies (low channel and high channel). The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyser. The spectrum is scanned from 9KHz up to a frequency including its 10th harmonic or 40GHz, which is lower.

6.6.2. Test Procedures

- 1, The testing follows ANSI C63.26 Section 5.7
- 2, $RBW \geq 100\text{KHz}$ for emissions below 1GHz, 1MHz for emissions above 1GHz.
- 3, $VBW \geq 3 * RBW$
- 4, Detector = RMS
- 5, Trace Mode = Average.
- 6, Sweep Points $\geq 2 * \text{Span}/RBW$
- 7, Sweep Time = Auto
- 8, The trace was allowed to stabilize.

7. List of Measuring Equipment

Equipment	Model	Manufacture	Device No.	Cal Date	Cal Due
Radio Communication Analyzer	MT8000A	Anritsu	6272478367	2023-12-07	2024-12-06
	MT8821C	Anritsu	6272498303	2023-12-07	2024-12-06
Radio Communication Analyzer	E7515E	Keysight	MY59296045	2023-12-07	2024-12-06
Spectrum Analyzer (50Hz-40GHz)	FSV	R&S	101046	2023-12-07	2024-12-06
Spectrum Analyzer (50Hz-40GHz)	FSV	R&S	101334	2024-01-30	2025-01-29
Power Supply	2036	Keithley	4058748	2023-12-07	2024-12-06
Temperature Chamber	C/64/40/3	Weiss	56246017780020	2024-04-01	2025-03-31
Power Divider	-	WOKEN	0120A04051801O	NCR	
Power Divider	-	WOKEN	0120A02051801M	NCR	

Remark:

- 1, For equipment listed above that has a calibration date or calibration due date that falls within the test date range, and the equipment was used after calibrate date and before calibrate due date.
- 2, "NCR" means no calibration required.

8. Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26. All the measurement uncertainties value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be directly to specified limit to determine compliance.

8.1. Uncertainty of Conducted Measurement

Contribution	Expanded Uncertainty
Conducted Power	± 0.77
Conducted Emission	± 0.76
Channel Bandwidth	$\pm 0.08\%$

9. Appendixes

Appendix B.1	NR Band n5A (824-849)
Appendix B.2	NR Band n7A (2500-2570)
Appendix B.3	NR Band n26A (814-824)
Appendix B.4	NR Band n26A (824-849)
Appendix B.5	NR Band n77A (3700-3980)
Appendix B.6	NR Band n78A (3700-3800)

The End