



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2623-1
FCC ID : IHDT56AT1
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System
TEST DATE(S) : Oct. 12, 2025 ~ Nov. 10, 2025

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang



Approved by: Fly Liang

Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION.....	5
1.1 Applicant.....	5
1.2 Manufacturer.....	5
1.3 Product Feature of Equipment Under Test.....	5
1.4 Product Specification of Equipment Under Test.....	5
1.5 Modification of EUT	6
1.6 Specification of Accessory.....	6
1.7 Testing Location	7
1.8 Test Software.....	7
1.9 Applicable Standards.....	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....	8
2.1 Carrier Frequency Channel	8
2.2 Test Mode.....	9
2.3 Connection Diagram of Test System.....	10
2.4 Support Unit used in test configuration and system	10
2.5 EUT Operation Test Setup	10
3 TEST RESULT	11
3.1 Output Power Measurement.....	11
3.2 Radiated Band Edges and Spurious Emission Measurement	12
3.3 Antenna Requirements.....	16
4 LIST OF MEASURING EQUIPMENT.....	17
5 MEASUREMENT UNCERTAINTY.....	18
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED SPURIOUS EMISSION	
APPENDIX C. DUTY CYCLE PLOTS	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR482104-18B	Rev. 01	Initial issue of report	Nov. 21, 2025



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(b)(3)	Conducted Output Power	≤ 30dBm	Pass	-
3.2	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 15.11 dB at 41.64 MHz
3.3	15.203 & 15.247(b)	Antenna Requirement	15.203 & 15.247(b)	Pass	-

Remark: This is a variant report for XT2623-1. The change note could be the XT2623-1_Operational Description of referred to the product equality declaration which is exhibit separately. According to the differences, only the related test cases were verified from original test report (Sporton Report Number FR482104B).

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W. Merchandise Mart Plaza, Chicago IL 60654, USA

1.2 Manufacturer

Motorola Mobility LLC

222 W. Merchandise Mart Plaza, Chicago IL 60654, USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2623-1
FCC ID	IHDT56AT1
IMEI Code	Conducted: 350084460013519/350084460013527 Radiation: 350084460004674/350084460004682
HW Version	DVT2
SW Version	VVTB35.5
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	BLE 125kbps: 2.63 dBm (0.0018 W) BLE 500kbps: 2.56 dBm (0.0018 W) BLE 1Mbps: 2.60 dBm (0.0018 W) BLE 2Mbps: 2.56 dBm (0.0018 W)
Antenna Type / Gain	PIFA Antenna type with gain -4.5 dBi
Type of Modulation	Bluetooth LE : GFSK

Note:

- For BLE 1Mbps & 125Kbps & 500Kbps mode, the whole testing has assessed BLE 125Kbps mode by referring to the higher conducted power.
- BLE 2M supports the frequency range of 2404 MHz ~ 2478 MHz and does not support advertising channels (CH00, CH12 and CH39).

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(AOHAI)	Model Name	MC-201L
AC Adapter 1(EU)	Brand Name	Motorola(AOHAI)	Model Name	MC-202L
AC Adapter 1(UK)	Brand Name	Motorola(AOHAI)	Model Name	MC-203L
AC Adapter 1(IN)	Brand Name	Motorola(AOHAI)	Model Name	MC-204
AC Adapter 1(AU)	Brand Name	Motorola(AOHAI)	Model Name	MC-205L
AC Adapter 1(AR)	Brand Name	Motorola(AOHAI)	Model Name	MC-206L
AC Adapter 1(PRC)	Brand Name	Motorola(AOHAI)	Model Name	MC-208L
AC Adapter 1(CHILE)	Brand Name	Motorola(AOHAI)	Model Name	MC-209L
AC Adapter 2(US)	Brand Name	Motorola(SALCOMP)	Model Name	MC-201L
AC Adapter 2(EU)	Brand Name	Motorola(SALCOMP)	Model Name	MC-202L
AC Adapter 2(UK)	Brand Name	Motorola(SALCOMP)	Model Name	MC-203L
AC Adapter 2(AU)	Brand Name	Motorola(SALCOMP)	Model Name	MC-205L
AC Adapter 2(AR)	Brand Name	Motorola(SALCOMP)	Model Name	MC-206L
AC Adapter 2(BR)	Brand Name	Motorola(SALCOMP)	Model Name	MC-207L
AC Adapter 2(PRC)	Brand Name	Motorola(SALCOMP)	Model Name	MC-208L
AC Adapter 2(CHILE)	Brand Name	Motorola(SALCOMP)	Model Name	MC-209L
AC Adapter 3(US)	Brand Name	Motorola(CHENYANG)	Model Name	MC-201L
AC Adapter 3(EU)	Brand Name	Motorola(CHENYANG)	Model Name	MC-202L
AC Adapter 3(AR)	Brand Name	Motorola(CHENYANG)	Model Name	MC-206L
AC Adapter 3(BR)	Brand Name	Motorola(CHENYANG)	Model Name	MC-207L
Battery 1	Brand Name	Motorola(ATL)	Model Name	RL52
Battery 2	Brand Name	Motorola(COSMX)	Model Name	RL52
Battery 3	Brand Name	Motorola(SUNWODA)	Model Name	RL52
USB Cable 1	Brand Name	Motorola(Yihuaxing)	Model Name	T365-020 T365-020-01 T365-020-02
USB Cable 2	Brand Name	Motorola(WASHIN)	Model Name	HX-TL-01 HX-TL-08 HX-TL-07
USB Cable 3	Brand Name	Motorola(Juwei)	Model Name	JWUB1614-T03H JWUB1705-T03H JWUB1856-T03H
USB Cable 4	Brand Name	Motorola(I-SHENG)	Model Name	SC18D38574



1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	TH01-SZ 03CH04-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-SZ	AUDIX	E3	6.2009-8-24

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2020

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.
3. The standard of ANSI C63.10-2013 updated to ANSI C63.10-2020, the difference is not affect on test results of this device.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode


- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_BLE 125Kbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_BLE 125Kbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_BLE 125Kbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_BLE 500Kbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_BLE 500Kbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_BLE 500Kbps
	Mode 7: Bluetooth Tx CH00_2402 MHz_BLE 1Mbps
	Mode 8: Bluetooth Tx CH19_2440 MHz_BLE 1Mbps
	Mode 9: Bluetooth Tx CH39_2480 MHz_BLE 1Mbps
	Mode 10: Bluetooth Tx CH01_2404 MHz_BLE 2Mbps
	Mode 11: Bluetooth Tx CH19_2440 MHz_BLE 2Mbps
	Mode 12: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH38_2478 MHz_BLE 2Mbps
Remark: For Radiated Test Cases, The tests were performance with Adapter1, Earphone1 and USB Cable1.	

2.3 Connection Diagram of Test System

Radiated Emission:



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Earphone	N/A	N/A	N/A	N/A	N/A

2.5 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit.

3 Test Result

3.1 Output Power Measurement

3.1.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.


3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2020 clause 11.9.1.2 PKPM1 Peak power meter or ANSI C63.10-2020 clause 11.9.2.3.1 Method AVGPM method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.1.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.2 Radiated Band Edges and Spurious Emission Measurement

3.2.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.




3.2.3 Test Procedures


1. The testing follows ANSI C63.10-2020 clause 6.3, 6.5, 6.6, 11.11 and 11.12.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than peak limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1$ GHz; $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - $VBW = 10$ Hz, when duty cycle is no less than 98 percent.
 - $VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.2.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



**3.2.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.2.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.2.7 Duty Cycle

Please refer to Appendix C.

3.2.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic or 40GHz, whichever is lower)

Please refer to Appendix B.



3.3 Antenna Requirements

3.3.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.3.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.3.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Test Receiver	R&S	ESR7	101404	9kHz~7GHz	Oct. 14, 2025	Oct. 14, 2025~ Nov. 10, 2025	Oct. 13, 2026	Radiation (03CH04-SZ)
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY551502 13	10Hz~44GHz	Jul. 03, 2025	Oct. 14, 2025~ Nov. 10, 2025	Jul. 02, 2026	Radiation (03CH04-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 28, 2024	Oct. 14, 2025~ Nov. 10, 2025	Dec. 27, 2025	Radiation (03CH04-SZ)
Bilog Antenna	TeseQ	CBL6111D	41909	30MHz~1GHz	Apr. 21, 2025	Oct. 14, 2025~ Nov. 10, 2025	Apr. 20, 2026	Radiation (03CH04-SZ)
Double Ridge Guide Antenna	ETS-Lindgren	Burgeon-3117	00240057	1GHz~18GHz	Jul. 03, 2025	Oct. 14, 2025~ Nov. 10, 2025	Jul. 02, 2026	Radiation (03CH04-SZ)
Horn Antenna	SCHWARZBECK	BBHA9170	9170#679	15GHz~40GHz	Jul. 04, 2025	Oct. 14, 2025~ Nov. 10, 2025	Jul. 03, 2026	Radiation (03CH04-SZ)
LF Amplifier	EM Electronics	EM330	060773	20MHz~3GHz	Apr. 02, 2025	Oct. 14, 2025~ Nov. 10, 2025	Apr. 01, 2026	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	AMF-7D-0010 1800-30-10P-R	1943528	1GHz~18GHz	Oct. 14, 2025	Oct. 14, 2025~ Nov. 10, 2025	Oct. 13, 2026	Radiation (03CH04-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Oct. 14, 2025~ Nov. 10, 2025	Jul. 02, 2026	Radiation (03CH04-SZ)
Amplifier	Agilent Technologies	83017A	MY572801 36	500MHz~26.5G Hz	Jul. 03, 2025	Oct. 14, 2025~ Nov. 10, 2025	Jul. 02, 2026	Radiation (03CH04-SZ)
AC Power Source	APC	AFV-S-600B	F11905001 9	N/A	Oct. 14, 2025	Oct. 14, 2025~ Nov. 10, 2025	Oct. 13, 2026	Radiation (03CH04-SZ)
Turn Table	EM	EM1000	N/A	0~360 degree	NCR	Oct. 14, 2025~ Nov. 10, 2025	NCR	Radiation (03CH04-SZ)
Antenna Mast	EM	EM1000	N/A	1 m~4 m	NCR	Oct. 14, 2025~ Nov. 10, 2025	NCR	Radiation (03CH04-SZ)
Spectrum Analyzer	R&S	FSV40	101078	10Hz~40GHz	Apr. 02, 2025	Oct. 12, 2025	Apr. 01, 2026	Conducted (TH01-SZ)
Pulse Power Sensor	Anritsu	MA2411B	1339473	30MHz~40GHz	Dec. 25, 2024	Oct. 12, 2025	Dec. 24, 2025	Conducted (TH01-SZ)
Power Meter	Anritsu	ML2495A	1218010	50MHz Bandwidth	Oct. 14, 2024	Oct. 12, 2025	Oct. 13, 2025	Conducted (TH01-SZ)
Thermo meter	Anymetre	JR593	#7	- 10°C ~ 50°C 10%RH~99%RH	Apr. 03, 2025	Oct. 12, 2025	Apr. 02, 2026	Conducted (TH01-SZ)

NCR: No Calibration Required

5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Conducted Power	± 1.34 dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.1 dB
---	--------

----- THE END -----

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sam Zheng	Temperature:	21~25	°C
Test Date:	2025/10/12	Relative Humidity:	51~54	%

TEST RESULTS DATA**Peak Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	125kbps	1	0	2402	1.04	Default	30.00	-4.50	-3.46	36.00	Pass
BLE	125kbps	1	19	2440	2.63	Default	30.00	-4.50	-1.87	36.00	Pass
BLE	125kbps	1	39	2480	1.91	Default	30.00	-4.50	-2.59	36.00	Pass

TEST RESULTS DATA**Average Power Table**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	125kbps	1	0	2402	0.85	0.90	Default	30.00	-4.50	-3.60	36.00	Pass
BLE	125kbps	1	19	2440	0.85	2.40	Default	30.00	-4.50	-2.10	36.00	Pass
BLE	125kbps	1	39	2480	0.85	1.50	Default	30.00	-4.50	-3.00	36.00	Pass

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sam Zheng	Temperature:	21~25	°C
Test Date:	2025/10/12	Relative Humidity:	51~54	%

TEST RESULTS DATA											
Peak Power Table											
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	500kbps	1	0	2402	1.01	Default	30.00	-4.50	-3.49	36.00	Pass
BLE	500kbps	1	19	2440	2.56	Default	30.00	-4.50	-1.94	36.00	Pass
BLE	500kbps	1	39	2480	1.84	Default	30.00	-4.50	-2.66	36.00	Pass

TEST RESULTS DATA												
Average Power Table												
Mod.	Data Rate	Ntx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	500kbps	1	0	2402	2.49	0.70	Default	30.00	-4.50	-3.80	36.00	Pass
BLE	500kbps	1	19	2440	2.49	2.30	Default	30.00	-4.50	-2.20	36.00	Pass
BLE	500kbps	1	39	2480	2.49	1.40	Default	30.00	-4.50	-3.10	36.00	Pass

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sam Zheng	Temperature:	21~25	°C
Test Date:	2025/10/12	Relative Humidity:	51~54	%

TEST RESULTS DATA												
Peak Power Table												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail	
BLE	1Mbps	1	0	2402	1.02	Default	30.00	-4.50	-3.48	36.00	Pass	
BLE	1Mbps	1	19	2440	2.60	Default	30.00	-4.50	-1.90	36.00	Pass	
BLE	1Mbps	1	39	2480	1.90	Default	30.00	-4.50	-2.60	36.00	Pass	

TEST RESULTS DATA												
Average Power Table												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	2.17	0.80	Default	30.00	-4.50	-3.70	36.00	Pass
BLE	1Mbps	1	19	2440	2.17	2.30	Default	30.00	-4.50	-2.20	36.00	Pass
BLE	1Mbps	1	39	2480	2.17	1.40	Default	30.00	-4.50	-3.10	36.00	Pass

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Sam Zheng	Temperature:	21~25	°C
Test Date:	2025/10/12	Relative Humidity:	51~54	%

TEST RESULTS DATA											
Peak Power Table											
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE5.0	2Mbps	1	1	2404	1.01	Default	30.00	-4.50	-3.49	36.00	Pass
BLE5.0	2Mbps	1	19	2440	2.56	Default	30.00	-4.50	-1.94	36.00	Pass
BLE5.0	2Mbps	1	38	2478	1.88	Default	30.00	-4.50	-2.62	36.00	Pass

TEST RESULTS DATA												
Average Power Table												
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	Power Setting	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	1	2404	5.04	0.70	Default	30.00	-4.50	-3.80	36.00	Pass
BLE	2Mbps	1	19	2440	5.04	2.30	Default	30.00	-4.50	-2.20	36.00	Pass
BLE	2Mbps	1	38	2478	5.04	1.40	Default	30.00	-4.50	-3.10	36.00	Pass



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	Winter	Relative Humidity :	48~49%
		Temperature :	24~25℃





Radiated Spurious Emission Test Modes

Mode	Band (MHz)	Antenna	Modulation	Channel	Frequency	Data Rate	RU	Remark
Mode 1	2400-2483.5	5	Bluetooth-LE	38	2478	2Mbps	-	-
Mode 2	2400-2483.5	5	Bluetooth-LE LF	38	-	2Mbps	-	-

Summary of each worse mode

Mode	Modulation	Ch.	Freq. (MHz)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol.	Peak Avg.	Result	Remark
1	Bluetooth-LE	38	2488.74	37.96	54.00	-16.04	V	AVERAGE	Pass	Band Edge
	Bluetooth-LE	38	7434.00	43.97	74.00	-30.03	V	Peak	Pass	Harmonic
2	Bluetooth-LE LF	38	41.64	24.89	40.00	-15.11	V	Peak	Pass	LF





Mode	1																																																																																										
	Band Edge																																																																																										
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																										
ANT	5																																																																																										
Pol.	Horizontal						Fundamental																																																																																				
Peak	 Date: 2025-10-14 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.48</td><td>46.42</td><td>74.00</td><td>-27.58</td><td>42.02</td><td>32.59</td><td>5.91</td><td>34.10</td><td>366</td><td>171</td><td>PEAK</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2487.48	46.42	74.00	-27.58	42.02	32.59	5.91	34.10	366	171	PEAK	 Date: 2025-10-14 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>96.61</td><td>-----</td><td>-----</td><td>92.26</td><td>32.56</td><td>5.90</td><td>34.11</td><td>366</td><td>171</td><td>PEAK</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2478.00	96.61	-----	-----	92.26	32.56	5.90	34.11	366	171	PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark																																																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2487.48	46.42	74.00	-27.58	42.02	32.59	5.91	34.10	366	171	PEAK																																																																																
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark																																																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2478.00	96.61	-----	-----	92.26	32.56	5.90	34.11	366	171	PEAK																																																																																
Avg	 Date: 2025-10-14 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2487.70</td><td>37.69</td><td>54.00</td><td>-16.31</td><td>33.28</td><td>32.58</td><td>5.93</td><td>34.10</td><td>366</td><td>171</td><td>AVERAGE</td></tr></table>						Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2487.70	37.69	54.00	-16.31	33.28	32.58	5.93	34.10	366	171	AVERAGE	 Date: 2025-10-14 <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>2478.00</td><td>94.71</td><td>-----</td><td>-----</td><td>90.36</td><td>32.56</td><td>5.90</td><td>34.11</td><td>366</td><td>171</td><td>AVERAGE</td></tr></table>					Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg	1	2478.00	94.71	-----	-----	90.36	32.56	5.90	34.11	366	171	AVERAGE
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																			
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark																																																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2487.70	37.69	54.00	-16.31	33.28	32.58	5.93	34.10	366	171	AVERAGE																																																																																
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																																																				
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	Remark																																																																																			
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	cm	deg																																																																																		
1	2478.00	94.71	-----	-----	90.36	32.56	5.90	34.11	366	171	AVERAGE																																																																																





Mode	1																																																																	
	Band Edge																																																																	
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																	
ANT	5																																																																	
Pol.	Vertical	Fundamental																																																																
Peak	Level (dBuV/m) Date: 2025-10-14 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2478 2482.4 2486.8 2491.2 2495.6 2500 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>2484.01</td><td>45.88</td><td>74.00</td><td>-28.12</td><td>41.48</td><td>32.57</td><td>5.94 34.11 200 95 PEAK</td></tr></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2484.01	45.88	74.00	-28.12	41.48	32.57	5.94 34.11 200 95 PEAK	Level (dBuV/m) Date: 2025-10-14 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>2478.00</td><td>93.89</td><td>-----</td><td>-----</td><td>89.54</td><td>32.56</td><td>5.90 34.11 200 95 PEAK</td></tr></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2478.00	93.89	-----	-----	89.54	32.56	5.90 34.11 200 95 PEAK
	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																										
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2484.01	45.88	74.00	-28.12	41.48	32.57	5.94 34.11 200 95 PEAK																																																											
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																											
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2478.00	93.89	-----	-----	89.54	32.56	5.90 34.11 200 95 PEAK																																																											
Avg	Level (dBuV/m) Date: 2025-10-14 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 2478 2482.4 2486.8 2491.2 2495.6 2500 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>2488.74</td><td>37.96</td><td>54.00</td><td>-16.04</td><td>33.55</td><td>32.58</td><td>5.93 34.10 200 95 AVERAGE</td></tr></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2488.74	37.96	54.00	-16.04	33.55	32.58	5.93 34.10 200 95 AVERAGE	Level (dBuV/m) Date: 2025-10-14 140 122.5 105.0 87.5 70.0 52.5 35.0 17.5 0 1000 1400 1800 2200 2600 3000 Frequency (MHz) <table><tr><th>Limit</th><th>Margin</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>(dB)</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th></th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th></tr><tr><td>1</td><td>2478.00</td><td>92.06</td><td>-----</td><td>-----</td><td>87.71</td><td>32.56</td><td>5.90 34.11 200 95 AVERAGE</td></tr></table>	Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos	Freq	Level	Line	(dB)	Level	Factor	Loss	Factor	MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB	1	2478.00	92.06	-----	-----	87.71	32.56	5.90 34.11 200 95 AVERAGE
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																											
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2488.74	37.96	54.00	-16.04	33.55	32.58	5.93 34.10 200 95 AVERAGE																																																											
Limit	Margin	Read	Ant	Cable	Preamp	APos	TPos																																																											
Freq	Level	Line	(dB)	Level	Factor	Loss	Factor																																																											
MHz	dBuV/m	dBuV/m		dBuV	dB/m	dB	dB																																																											
1	2478.00	92.06	-----	-----	87.71	32.56	5.90 34.11 200 95 AVERAGE																																																											



Mode	1																																																																																																																					
	Harmonic																																																																																																																					
	2400-2483.5_Bluetooth-LE_CH38_2478MHz																																																																																																																					
ANT	5																																																																																																																					
Pol.	Horizontal						Vertical																																																																																																															
Peak Avg																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>43.57</td><td>74.00</td><td>-30.43</td><td>64.74</td><td>35.16</td><td>8.48</td><td>64.81</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7434.00</td><td>43.58</td><td>74.00</td><td>-30.42</td><td>62.28</td><td>36.10</td><td>10.17</td><td>64.97</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	43.57	74.00	-30.43	64.74	35.16	8.48	64.81	---	---	Peak	2	7434.00	43.58	74.00	-30.42	62.28	36.10	10.17	64.97	---	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Remark</th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>4956.00</td><td>43.83</td><td>74.00</td><td>-30.17</td><td>65.00</td><td>35.16</td><td>8.48</td><td>64.81</td><td>---</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>7434.00</td><td>43.97</td><td>74.00</td><td>-30.03</td><td>62.67</td><td>36.10</td><td>10.17</td><td>64.97</td><td>---</td><td>---</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	4956.00	43.83	74.00	-30.17	65.00	35.16	8.48	64.81	---	---	Peak	2	7434.00	43.97	74.00	-30.03	62.67	36.10	10.17	64.97	---	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																												
1	4956.00	43.57	74.00	-30.43	64.74	35.16	8.48	64.81	---	---	Peak																																																																																																											
2	7434.00	43.58	74.00	-30.42	62.28	36.10	10.17	64.97	---	---	Peak																																																																																																											
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Remark																																																																																																														
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																												
1	4956.00	43.83	74.00	-30.17	65.00	35.16	8.48	64.81	---	---	Peak																																																																																																											
2	7434.00	43.97	74.00	-30.03	62.67	36.10	10.17	64.97	---	---	Peak																																																																																																											



Mode	2																																																																																																																																																																																																					
	LF																																																																																																																																																																																																					
	2400-2483.5_Bluetooth-LE LF_CH38																																																																																																																																																																																																					
ANT	5																																																																																																																																																																																																					
Pol.	Horizontal					Vertical																																																																																																																																																																																																
Peak																																																																																																																																																																																																						
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>58.13</td><td>17.85</td><td>40.00</td><td>-22.15</td><td>29.03</td><td>19.76</td><td>0.76</td><td>31.70</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>139.61</td><td>23.54</td><td>43.50</td><td>-19.96</td><td>34.86</td><td>19.09</td><td>1.21</td><td>31.62</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>194.90</td><td>21.42</td><td>43.50</td><td>-22.08</td><td>34.96</td><td>16.56</td><td>1.41</td><td>31.51</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>308.39</td><td>22.07</td><td>46.00</td><td>-23.93</td><td>31.91</td><td>19.91</td><td>1.83</td><td>31.58</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>818.61</td><td>29.77</td><td>46.00</td><td>-16.23</td><td>29.50</td><td>28.37</td><td>2.98</td><td>31.08</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>959.26</td><td>30.83</td><td>46.00</td><td>-15.17</td><td>28.57</td><td>29.83</td><td>3.25</td><td>30.82</td><td>---</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	58.13	17.85	40.00	-22.15	29.03	19.76	0.76	31.70	---	Peak	2	139.61	23.54	43.50	-19.96	34.86	19.09	1.21	31.62	---	Peak	3	194.90	21.42	43.50	-22.08	34.96	16.56	1.41	31.51	---	Peak	4	308.39	22.07	46.00	-23.93	31.91	19.91	1.83	31.58	---	Peak	5	818.61	29.77	46.00	-16.23	29.50	28.37	2.98	31.08	---	Peak	6	959.26	30.83	46.00	-15.17	28.57	29.83	3.25	30.82	---	Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>APos</th><th>TPos</th><th></th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th></th><th>Remark</th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>41.64</td><td>24.89</td><td>40.00</td><td>-15.11</td><td>36.06</td><td>19.93</td><td>0.63</td><td>31.73</td><td>---</td><td>Peak</td></tr><tr><td>2</td><td>140.58</td><td>20.90</td><td>43.50</td><td>-22.60</td><td>32.17</td><td>19.14</td><td>1.21</td><td>31.62</td><td>---</td><td>Peak</td></tr><tr><td>3</td><td>313.24</td><td>19.92</td><td>46.00</td><td>-26.08</td><td>29.61</td><td>20.03</td><td>1.85</td><td>31.57</td><td>---</td><td>Peak</td></tr><tr><td>4</td><td>725.49</td><td>27.81</td><td>46.00</td><td>-18.19</td><td>28.81</td><td>27.24</td><td>2.81</td><td>31.05</td><td>---</td><td>Peak</td></tr><tr><td>5</td><td>838.01</td><td>29.68</td><td>46.00</td><td>-16.32</td><td>29.19</td><td>28.53</td><td>3.02</td><td>31.06</td><td>---</td><td>Peak</td></tr><tr><td>6</td><td>953.44</td><td>30.60</td><td>46.00</td><td>-15.40</td><td>28.40</td><td>29.80</td><td>3.24</td><td>30.84</td><td>---</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	APos	TPos		Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	41.64	24.89	40.00	-15.11	36.06	19.93	0.63	31.73	---	Peak	2	140.58	20.90	43.50	-22.60	32.17	19.14	1.21	31.62	---	Peak	3	313.24	19.92	46.00	-26.08	29.61	20.03	1.85	31.57	---	Peak	4	725.49	27.81	46.00	-18.19	28.81	27.24	2.81	31.05	---	Peak	5	838.01	29.68	46.00	-16.32	29.19	28.53	3.02	31.06	---	Peak	6	953.44	30.60	46.00	-15.40	28.40	29.80	3.24	30.84	---	Peak
		Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																																																														
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																													
1	58.13	17.85	40.00	-22.15	29.03	19.76	0.76	31.70	---	Peak																																																																																																																																																																																												
2	139.61	23.54	43.50	-19.96	34.86	19.09	1.21	31.62	---	Peak																																																																																																																																																																																												
3	194.90	21.42	43.50	-22.08	34.96	16.56	1.41	31.51	---	Peak																																																																																																																																																																																												
4	308.39	22.07	46.00	-23.93	31.91	19.91	1.83	31.58	---	Peak																																																																																																																																																																																												
5	818.61	29.77	46.00	-16.23	29.50	28.37	2.98	31.08	---	Peak																																																																																																																																																																																												
6	959.26	30.83	46.00	-15.17	28.57	29.83	3.25	30.82	---	Peak																																																																																																																																																																																												
	Limit	Read	Ant	Cable	Preamp	APos	TPos																																																																																																																																																																																															
Freq	Level	Line	Margin	Level	Factor	Loss Factor		Remark																																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																													
1	41.64	24.89	40.00	-15.11	36.06	19.93	0.63	31.73	---	Peak																																																																																																																																																																																												
2	140.58	20.90	43.50	-22.60	32.17	19.14	1.21	31.62	---	Peak																																																																																																																																																																																												
3	313.24	19.92	46.00	-26.08	29.61	20.03	1.85	31.57	---	Peak																																																																																																																																																																																												
4	725.49	27.81	46.00	-18.19	28.81	27.24	2.81	31.05	---	Peak																																																																																																																																																																																												
5	838.01	29.68	46.00	-16.32	29.19	28.53	3.02	31.06	---	Peak																																																																																																																																																																																												
6	953.44	30.60	46.00	-15.40	28.40	29.80	3.24	30.84	---	Peak																																																																																																																																																																																												

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth LE 2Mbps	57.22	1.070	0.935	1KHz

Bluetooth LE 2Mbps

