



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2603-1,XT2603-2
FCC ID : IHDT56AW1
STANDARD : 47 CFR Part 15 Subpart B
CLASSIFICATION : Certification
TEST DATE(S) : Nov. 25, 2025 ~ Nov. 26, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

**No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China**



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	8
1.6. Test Location	8
1.7. Test Software	8
1.8. Applicable Standards	9
1.9. Specification of Accessory	9
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	10
2.1. Test Mode	10
2.2. Connection Diagram of Test System	12
2.3. Support Unit used in test configuration and system	13
2.4. EUT Operation Test Setup	13
3. TEST RESULT	14
3.1. Test of AC Conducted Emission Measurement	14
3.2. Test of Radiated Emission Measurement	18
4. LIST OF MEASURING EQUIPMENT	25
5. MEASUREMENT UNCERTAINTY	26
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC591906	Rev. 01	Initial issue of report	Dec. 05, 2025

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 5.17 dB at 0.221 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 3.24 dB at 164.83 MHz for Quasi-Peak

Conformity Assessment Condition:

The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account. Please refer to each test results in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1. Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2603-1,XT2603-2
FCC ID	IHDT56AW1
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 2.4GHz 802.11ax HE20/HE40 WLAN 2.4GHz 802.11be EHT20/ EHT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/VHT160 WLAN 5GHz 802.11ax HE20/HE40/HE80/HE160 WLAN 5GHz 802.11be EHT20/EHT40/EHT80/EHT160 WLAN 6GHz 802.11a/ax HE20/HE40/HE80/HE160 WLAN 6GHz 802.11be EHT20/EHT40/EHT80/EHT160/EHT320 Bluetooth BR/EDR/LE GNSS/NFC/WPT/UWB
IMEI Code	Conduction: 350158880024015/350158880024023 for Sample 1 357665360012156/357665360012164 for Sample 2 Radiation: 350158880034352 for Sample 1 357665360012156 for Sample 2
HW Version	DVT2
SW Version	W2WV36.22
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two kinds of EUT, the sample 1(XT2603-2) is P-SIM + eSIM and the sample 2(XT2603-1) is P-SIM +P-SIM. According to the difference, we choose sample 1 to full test and the sample 2 is verified for the difference.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850MHz ~ 1910MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV : 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 7 : 2500 MHz ~ 2570 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 17 : 704 MHz ~ 716 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 38 : 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz LTE Band 42 : 3450 MHz ~ 3600 MHz LTE Band 43 : 3600 MHz ~ 3700 MHz LTE Band 48 : 3550 MHz ~ 3700 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n7 : 2500 MHz ~ 2570 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n26 : 814 MHz ~ 849 MHz 5G NR n38 : 2570 MHz ~ 2620 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n70 : 1695 MHz ~ 1710 MHz 5G NR n71 : 663 MHz ~ 698 MHz 5G NR n89 : 824 MHz ~ 849 MHz 5G NR n77 : 3700 MHz ~ 3980 MHz; 5G NR n78 : 3700 MHz ~ 3800 MHz; 802.11b/g/n/ax/be: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac/ax/be: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz 802.11a/ax/be: 5925 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz WPT: 115kHz~ 145 kHz UWB: 6489.6 MHz & 7987.2 MHz
Rx Frequency	GSM850: 869 MHz ~ 894 MHz GSM1900: 1930 MHz ~ 1990 MHz WCDMA Band II: 1930 MHz ~ 1990 MHz WCDMA Band IV : 2110 MHz ~ 2155 MHz WCDMA Band V: 869 MHz ~ 894 MHz LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz



	LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 7 : 2620 MHz ~ 2690 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 13 : 746 MHz ~ 756 MHz LTE Band 17 : 734 MHz ~ 746 MHz LTE Band 25 : 1930 MHz ~ 1995 MHz LTE Band 26 : 859 MHz ~ 894 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41 : 2496 MHz ~ 2690 MHz LTE Band 42 : 3450 MHz ~ 3600 MHz LTE Band 43 : 3600 MHz ~ 3700 MHz LTE Band 48 : 3550 MHz ~ 3700 MHz LTE Band 66 : 2110 MHz~ 2180 MHz LTE Band 71 : 617 MHz ~ 652 MHz 5G NR n2 : 1930 MHz ~ 1990 MHz 5G NR n5 : 869 MHz ~ 894 MHz 5G NR n7 : 2620 MHz ~ 2690 MHz 5G NR n25 : 1930 MHz ~ 1995 MHz 5G NR n26 : 859 MHz ~ 894 MHz 5G NR n38: 2570 MHz ~ 2620 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n66 : 2110 MHz~ 2200 MHz 5G NR n70 : 1995 MHz ~ 2020 MHz 5G NR n71 : 617 MHz ~ 652 MHz 5G NR n77 : 3700 MHz ~ 3980 MHz; 5G NR n78 : 3700 MHz ~ 3800 MHz; 802.11b/g/n/ax/be: 2400 MHz ~ 2483.5 MHz 802.11a/n/ac/ax/be: 5150 MHz ~ 5250 MHz; 5250 MHz ~ 5350 MHz; 5470 MHz ~ 5725 MHz 5725 MHz ~ 5850 MHz 802.11a/ax/be: 5925 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz NFC : 13.56 MHz GNSS : 1559 MHz ~ 1610 MHz, 1164 MHz ~ 1215 MHz WPT: 130kHz~ 135 kHz UWB: 6489.6 MHz & 7987.2 MHz
Antenna Type	WWAN : PIFA Antenna WLAN : PIFA Antenna Bluetooth : PIFA Antenna GNSS : PIFA Antenna NFC : Loop Antenna WPT : Coil Antenna UWB : IFA Antenna / slot Antenna
Type of Modulation	GSM/GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK HSPA : QPSK HSPA+ : 16QAM(16QAM not support uplink) DC-HSDPA : 64QAM LTE: QPSK / 16QAM / 64QAM / 256QAM 5G NR: DFT-s-OFDM (PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM) CP-OFDM (QPSK / 16QAM / 64QAM / 256QAM)

	802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) 802.11ax: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM) 802.11be: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM / 1024QAM / 4096QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : $\pi/4$ -DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK NFC: ASK WPT: ASK UWB: BPM-BPSK
--	--

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Test Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	CO01-KS 03CH02-KS	CN1257	314309

1.7. Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH02-KS	AUDIX	E3	6.2009-8-24a1
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.9. Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Salcomp)	Model Name	MC-901
AC Adapter 1(EU)	Brand Name	Motorola(Salcomp)	Model Name	MC-902
AC Adapter 1(UK)	Brand Name	Motorola(Salcomp)	Model Name	MC-903
AC Adapter 1(AU)	Brand Name	Motorola(Salcomp)	Model Name	MC-905
AC Adapter 1(AR)	Brand Name	Motorola(Salcomp)	Model Name	MC-906
AC Adapter 1(BR)	Brand Name	Motorola(Salcomp)	Model Name	MC-907
AC Adapter 1(CHILE)	Brand Name	Motorola(Salcomp)	Model Name	MC-909
AC Adapter 2(US)	Brand Name	Motorola(AOHAI)	Model Name	MC-901
AC Adapter 2(EU)	Brand Name	Motorola(AOHAI)	Model Name	MC-902
AC Adapter 2(UK)	Brand Name	Motorola(AOHAI)	Model Name	MC-903
AC Adapter 2(AU)	Brand Name	Motorola(AOHAI)	Model Name	MC-905
AC Adapter 2(AR)	Brand Name	Motorola(AOHAI)	Model Name	MC-906
AC Adapter 2(BR)	Brand Name	Motorola(AOHAI)	Model Name	MC-907
AC Adapter 2(CHILE)	Brand Name	Motorola(AOHAI)	Model Name	MC-909
AC Adapter 3(IN)	Brand Name	Motorola(AOHAI)	Model Name	MC-904
AC Adapter 3(IN Local)	Brand Name	Motorola(AOHAI)	Model Name	MC-904
AC Adapter 4(IN Local)	Brand Name	Motorola(Salcomp)	Model Name	MC-904
AC Adapter 4(IN)	Brand Name	Motorola(Salcomp)	Model Name	MC-904
Battery	Brand Name	Motorola (ATL)	Model Name	SR52
USB Cable 1	Brand Name	Motorola(SAIBAO)	Model Name	SC18D71644
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18E08104
USB Cable 3	Brand Name	Motorola(SAIBAO)	Model Name	SC18D86731
USB Cable 4	Brand Name	Motorola(Luxshare)	Model Name	SC18E08103
USB Cable 5	Brand Name	Motorola(SAIBAO)	Model Name	SC18E46326
USB Cable 6	Brand Name	Motorola(SAIBAO)	Model Name	SC18E59082
Magnetic Protective Cover	Brand Name	Motorola(Topwell)	Model Name	SS68E96654
Stylus	Brand Name	Motorola(Maxeye)	Model Name	XT2604-1

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.


Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM 850 Rx(Low) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Battery + UWB Idle + USB Cable 1(Charging from Adapter1) + PSIM for Sample1
	Mode 2: WCDMA 850 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + Battery + UWB Link + USB Cable 2(Charging from Adapter2) + E-SIM for Sample1
	Mode 3: LTE Band 850 Rx(High) + Bluetooth Idle + WLAN (6G) Idle + NFC On + Battery + UWB Idle + USB Cable3(Charging from Adapter3) + E-SIM for Sample1
	Mode 4: LTE Band 12 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable4(Charging from Adapter4) + E-SIM for Sample1
	Mode 5: LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable5 (Charging from Adapter2) + E-SIM for Sample1
	Mode 6: LTE Band 26 Rx(Low) + Bluetooth Idle + WLAN (6G) Idle + GNSS Rx + Battery + UWB Idle + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + E-SIM for Sample1
	Mode 7: LTE Band 12 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + E-SIM for Sample1
	Mode 8: LTE Band 71 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable 2 (Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + E-SIM for Sample1
	Mode 9: SA N5 Rx(Low) Idle + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable 3(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + E-SIM for Sample1
	Mode 10 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable 4(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + E-SIM for Sample1
	Mode 11 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable 5(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + E-SIM for Sample1
	Mode 12 : SA N26 Rx(Low) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar)+ Earphone + Battery + UWB Link + USB Cable5 (EUT Charging from Wireless charger) + Adapter 2Connect to Wireless charger + E-SIM for Sample1

AC Conducted Emission	Mode 13 SA N26 Rx(High) + Bluetooth Idle + WLAN (6G) Idle + MPEG4(Run Color Bar) + Earphone + Battery + UWB Idle + USB Cable5(Charging from Adapter2) + EUT Wireless Charging to other phones + E-SIM for Sample1 Mode 14 : SA N71 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar)+ Earphone + Battery + UWB Link + USB Cable5(Charging from Adapter2) + EUT Wireless Charging to other phones + E-SIM for Sample1 Mode 15 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable5 (Charging from Adapter2) + E-SIM for Sample2
Radiated Emissions	Mode 1: GSM 850 Rx(Low) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Battery + UWB Idle + USB Cable 1(Charging from Adapter1) + PSIM for Sample1 Mode 2: WCDMA 850 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + Camera(Front) + Battery + UWB Link + USB Cable 2(Charging from Adapter2) + E-SIM for Sample1 Mode 3: LTE Band 850 Rx(High) + Bluetooth Idle + WLAN (6G) Idle + NFC On + Battery + UWB Idle + USB Cable3(Charging from Adapter 3)+ PSIM for Sample1 Mode 4: LTE Band 12 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable4(Charging from Adapter 4) + PSIM for Sample1 Mode 5: LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable5 (Charging from Adapter4) + PSIM for Sample1 Mode 6: LTE Band 26 Rx(Low) + Bluetooth Idle + WLAN (6G) Idle + GNSS Rx + Battery + UWB Idle + USB Cable 1(Data Link with Notebook) + EUT (eMMC) USB Data Link to PC/NB + PSIM for Sample1 Mode 7: LTE Band 12 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar)+ Battery + UWB Idle + USB Cable 1(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + PSIM for Sample1 Mode 8: LTE Band 71 Rx(Middle) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable 2(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + PSIM for Sample1 Mode 9: SA N5 Rx(Low) + Bluetooth Idle + WLAN (6G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable 3 (Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + PSIM for Sample1 Mode 10 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable 4(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + PSIM for Sample1 Mode 11 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable 5(Data Link with Notebook) + PC/NB USB Data Link to EUT (eMMC) + PSIM for Sample1

Radiated Emissions	Mode 12 : SA N26 Rx(Low) + Bluetooth Idle + WLAN (6G) Idle + MPEG4(Run Color Bar) + Earphone + Battery + UWB Idle + USB Cable5 (EUT Charging from Wireless charger) + Adapter 4Connect to Wireless charger + PSIM for Sample1 Mode 13 : SA N26 Rx(High) + Bluetooth Idle + WLAN (6G) Idle + MPEG4(Run Color Bar) + Battery + UWB Idle + USB Cable5(Charging from Adapter4) + EUT Wireless Charging to other phones + PSIM for Sample1 Mode 14 : SA N71 Rx(Middle) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4(Run Color Bar) + Earphone + Battery + UWB Idle + USB Cable5(Charging from Adapter4) + EUT Wireless Charging to other phones + PSIM for Sample1 Mode 15 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + UWB Link + USB Cable5 (Charging from Adapter4) + PSIM for Sample2 Mode 16 : LTE Band 13 Rx(High) + Bluetooth Idle + WLAN (5G) Idle + MPEG4(Run Color Bar) + Battery + with shell + UWB Link + USB Cable5 (Charging from Adapter4) + PSIM for Sample1
Remark: 1. The worst case of AC is mode 5; only the test data of this mode is reported. 2. The worst case of RE is mode 5; only the test data of this mode is reported. 3. Data Link with Notebook / PC means data application transferred mode between EUT and Notebook / PC. 4. Pre-scanned Low/Middle/High channel, the worst channel was recorded in this report.	

2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded,1.8m
2.	5G NR Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded,1.8m
3.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
4.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
5.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
6.	Signal Generator	R&S	SMBV100A	258305	N/A	N/A
7.	Hard Disk	Lenovo	F310	DoC		Shielded, 1.2m
8.	SD Card	Kingston	8GB	N/A	N/A	N/A
9.	Hard disk	KINGSHARE	KSP6120G	N/A	N/A	N/A
10.	Earphone	N/A	N/A	N/A	N/A	N/A
11.	NFC Card	N/A	N/A	N/A	N/A	N/A
12.	Wireless charger	N/A	N/A	N/A	N/A	N/A

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE or 5G NR idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on camera to capture images.
3. Turn on MPEG4 function.
4. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
5. Turn on NFC function
6. Turn on UWB function

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission


Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : FCC IC-QP LISN-060105-L 24+80 LINE

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 *	0.154	56.78	-9.00	65.78	46.10	0.23	10.45	QP
2	0.154	44.28	-11.50	55.78	33.60	0.23	10.45	Average
3	0.233	38.24	-24.11	62.35	27.50	0.27	10.47	QP
4	0.233	22.24	-30.11	52.35	11.50	0.27	10.47	Average
5	0.258	39.56	-21.95	61.51	28.80	0.29	10.47	QP
6	0.258	22.96	-28.55	51.51	12.20	0.29	10.47	Average
7	0.524	37.56	-18.44	56.00	26.80	0.36	10.40	QP
8	0.524	24.36	-21.64	46.00	13.60	0.36	10.40	Average
9	15.885	37.99	-22.01	60.00	26.80	0.91	10.28	QP
10	15.885	32.39	-17.61	50.00	21.20	0.91	10.28	Average
11	20.162	39.64	-20.36	60.00	28.20	1.13	10.31	QP
12	20.162	33.74	-16.26	50.00	22.30	1.13	10.31	Average

Test Engineer :	Amos	Temperature :	25.3~26.2°C
		Relative Humidity :	38~40%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
 Condition : FCC IC-QP LISN-060105-N 24+80 NEUTRAL
 Project : (FC) 591906

	Freq	Level	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.151	60.78	-5.18	65.96	50.10	0.23	10.45	QP
2	0.151	46.88	-9.08	55.96	36.20	0.23	10.45	Average
3	0.165	45.20	-20.01	65.21	34.50	0.25	10.45	QP
4	0.165	28.20	-27.01	55.21	17.50	0.25	10.45	Average
5 *	0.221	57.62	-5.17	62.79	46.91	0.25	10.46	QP
6	0.221	36.42	-16.37	52.79	25.71	0.25	10.46	Average
7	0.317	47.38	-12.42	59.80	36.60	0.30	10.48	QP
8	0.317	22.98	-26.82	49.80	12.20	0.30	10.48	Average
9	0.532	40.64	-15.36	56.00	29.89	0.35	10.40	QP
10	0.532	25.34	-20.66	46.00	14.59	0.35	10.40	Average
11	12.852	37.12	-22.88	60.00	26.19	0.66	10.27	QP
12	12.852	31.12	-18.88	50.00	20.19	0.66	10.27	Average

Note:

- Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
- Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B Limit>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 10 meters (30M~1G) and 3 meters (1G~ 40G) from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
10. Exploratory radiated emissions testing of handheld and/or body-worn devices shall include rotation of the EUT through three orthogonal axes (X/Y/Z Plane) to determine the orientation (attitude) that maximizes the emissions.

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






3.2.5. Test Result of Radiated Emission





Test Engineer :	Yoke Si	Temperature :	23.7~24.3°C
		Relative Humidity :	47~48%
Test Distance :	3m	Polarization :	Horizontal




Site : 03CH02-KS
Condition : FCC CLASS-B 3m 3117 SN 00251694 Horizontal

	Freq	Level	Limit	Over	Read	Ant	Preamp	Cable	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	3652.0000	42.26	74.00	-31.74	68.17	33.15	65.63	6.57	---	---	Peak
2	6219.0000	38.70	74.00	-35.30	61.15	35.44	66.62	8.73	---	---	Peak
3	7928.9170	41.86	74.00	-32.14	63.78	35.67	67.87	10.28	---	---	Peak
4	9154.3330	39.80	74.00	-34.20	60.56	36.20	68.13	11.17	---	---	Peak
5	13931.330	42.35	74.00	-31.65	54.73	38.81	64.75	13.56	---	---	Peak
6	17811.580	46.03	74.00	-27.97	56.95	40.96	66.95	15.07	---	---	Peak




Test Engineer :	Yoke Si	Temperature :	23.7~24.3°C
		Relative Humidity :	47~48%
Test Distance :	10m	Polarization :	Vertical



Condition: RE 10m CBL6111D SN 63161 10.24 Vertical

	Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	
1	30.00	24.68	30.00	-5.32	31.61	25.28	0.46	32.67	---	---	Peak
2	94.51	22.37	30.00	-7.63	38.56	15.44	1.05	32.68	---	---	Peak
3	164.83	26.76	30.00	-3.24	41.87	16.16	1.40	32.67	100	206	QP
4	558.65	26.66	37.00	-10.34	30.72	26.42	2.58	33.06	---	---	Peak
5	865.41	28.45	37.00	-8.55	27.52	30.02	3.21	32.30	---	---	Peak
6	974.78	30.20	37.00	-6.80	26.66	31.49	3.39	31.34	---	---	Peak



Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz;	Apr. 16, 2025	Nov. 25, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Aug. 20, 2025	Nov. 25, 2025	Aug. 19, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Nov. 25, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 09, 2025	Nov. 25, 2025	Oct. 08, 2026	Conduction (CO01-KS)
Bilog Antenna	TESEQ	CBL6111D	63161	30MHz~1GHz	Oct. 25, 2025	Nov. 26, 2025	Oct. 24, 2026	Radiation (10CH01-KS)
Bilog Antenna	TESEQ	CBL6111D	63755	30MHz~1GHz	Oct. 25, 2025	Nov. 26, 2025	Oct. 24, 2026	Radiation (10CH01-KS)
EMI test receiver	R&S	ESR7	102630	9KHz~7GHz	Oct. 09, 2025	Nov. 26, 2025	Oct. 08, 2026	Radiation (10CH01-KS)
EMI test receive	R&S	ESR7	102631	9KHz~7GHz	Oct. 09, 2025	Nov. 26, 2025	Oct. 08, 2026	Radiation (10CH01-KS)
Amplifier	SONOMA	310N	422544	9KHz ~1GHZ	Oct. 09, 2025	Nov. 26, 2025	Oct. 08, 2026	Radiation (10CH01-KS)
Amplifier	SONOMA	310N	422545	9KHz ~1GHZ	Oct. 09, 2025	Nov. 26, 2025	Oct. 08, 2026	Radiation (10CH01-KS)
Bore-site Antenna Mast	EM	MBD-400-1	NA	1 m~4 m	NCR	Nov. 26, 2025	NCR	Radiation (10CH01-KS)
Antenna Mast	EM	MBD-400-1	NA	1 m~4 m	NCR	Nov. 26, 2025	NCR	Radiation (10CH01-KS)
Controller	EM	3000-1	NA	NA	NCR	Nov. 26, 2025	NCR	Radiation (10CH01-KS)
Turn Table	EM	T-300-1	NA	0~360 degree	NCR	Nov. 26, 2025	NCR	Radiation (10CH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55370528	10Hz-44G,MAX 30dB	Dec. 03, 2024	Nov. 26, 2025	Dec. 02, 2025	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Mar. 05, 2025	Nov. 26, 2025	Mar. 04, 2026	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 11, 2025	Nov. 26, 2025	Jan. 10, 2026	Radiation (03CH02-KS)
Amplifier	EM	EM18G40GA	060852	18~40GHz	Jan. 03, 2025	Nov. 26, 2025	Jan. 02, 2026	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Nov. 26, 2025	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Nov. 26, 2025	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Nov. 26, 2025	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required

5. Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.84dB
--	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)-03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.90dB
--	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)-03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.30dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) - 10CH01-KS(Horizontal)

Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$)	5.04dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) - 10CH01-KS(Vertical)

Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$)	5.04dB
--	--------

----- THE END -----