



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2621-3
FCC ID : IHDT56AW4
STANDARD : FCC Part 15 Subpart C §15.225
CLASSIFICATION : (DXX) Low Power Communication Device Transmitter
TEST DATE(S) : Oct. 24, 2025 ~ Nov. 24, 2025

We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.

Jason Jia

Approved by: Jason Jia



Sporton International Inc. (Kunshan)

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300
People's Republic of China



TABLE OF CONTENTS

TABLE OF CONTENTS	2
REVISION HISTORY	3
SUMMARY OF THE TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1 Applicant.....	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	5
1.6 Testing Location	6
1.7 Test Software	6
1.8 Applicable Standards.....	6
1.9 Specification of Accessory.....	7
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Descriptions of Test Mode.....	8
2.2 Connection Diagram of Test System	8
2.3 Table for Supporting Units.....	9
2.4 EUT Operation Test Setup	9
3. TEST RESULTS.....	10
3.1 AC Power Line Conducted Emissions Measurement	10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement.....	12
3.3 Frequency Stability Measurement	13
3.4 Field Strength of Fundamental Emissions and Mask Measurement.....	14
3.5 Radiated Emissions Measurement	16
3.6 Antenna Requirements.....	19
4. LIST OF MEASURING EQUIPMENT	20
5. UNCERTAINTY OF EVALUATION	21
APPENDIX A. TEST RESULTS OF CONDUCTED EMISSION TEST	
APPENDIX B. TEST RESULTS OF CONDUCTED TEST ITEMS	
B1. Test Result of 20dB Spectrum Bandwidth	
B2. Test Result of Frequency Stability	
APPENDIX C. TEST RESULTS OF RADIATED TEST ITEMS	
C1. Test Result of Field Strength of Fundamental Emissions	
C2. Results of Radiated Emissions (9 kHz~30MHz)	
C3. Results of Radiated Emissions (30MHz~1GHz)	
APPENDIX D. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR5O1022-01D	Rev. 01	Initial issue of report	Dec. 08, 2025

SUMMARY OF THE TEST RESULT

Report Section	FCC Rule	Description of Test	Result	Remark
3.1	15.207	AC Power Line Conducted Emissions	Complies	Under limit 7.12 dB at 0.175MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Complies	-
	-	99% OBW Spectrum Bandwidth	Complies	-
3.3	15.225(e)	Frequency Stability	Complies	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Complies	Max level 14.48 dB μ V/m at 13.560 MHz @30m
3.5	15.225(d) & 15.209	Radiated Spurious Emissions	Complies	Under limit 7.09 dB at 38.250MHz
3.6	15.203	Antenna Requirements	Complies	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1. General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2621-3
FCC ID	IHDT56AW4
IMEI Code	Conducted: 357452650005426 Conduction: 357452650005301 Radiation: 354137290013442/354137290013459
HW Version	DVT2
SW Version	W2WI36.28
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	13.553 ~ 13.567MHz
Channel Number	1
20dBW	2.475 KHz
99%OBW	2.098 KHz
Antenna Type	LOOP Antenna
Type of Modulation	ASK

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International Inc. (Kunshan)				
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158				
Test Site No.	Sporton Site No.			FCC Designation No.	FCC Test Firm Registration No.
	TH01-KS	03CH07-KS	CO01-KS	CN1257	314309
Test Engineer	Jacob Zhang	Moon	Amos Zhang		
Temperature	22-24°C	21~22°C	38~40°C		
Relative Humidity	53-55%	45~46%	25.3~26.2%		

1.7 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH07-KS	AUDIX	E3	210616
2.	CO01-KS	AUDIX	E3	6.2009-8-24

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart C §15.225
- ♦ ANSI C63.10-2020



1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1 US	Brand Name	Motorola(Salcomp)	Model Name	MC-331L
AC Adapter 1 EU	Brand Name	Motorola(Salcomp)	Model Name	MC-332L
AC Adapter 1 AR	Brand Name	Motorola(Salcomp)	Model Name	MC-336L
AC Adapter 1 BR	Brand Name	Motorola(Salcomp)	Model Name	MC-337L
AC Adapter 1 CHILE	Brand Name	Motorola(Salcomp)	Model Name	MC-339L
AC Adapter 2 EU	Brand Name	Motorola(Salcomp)	Model Name	MC-332
AC Adapter 3 US	Brand Name	Motorola(Chenyang)	Model Name	MC-331L
AC Adapter 3 EU	Brand Name	Motorola(Chenyang)	Model Name	MC-332L
AC Adapter 3 AR	Brand Name	Motorola(Chenyang)	Model Name	MC-336L
AC Adapter 3 BR	Brand Name	Motorola(Chenyang)	Model Name	MC-337L
AC Adapter 3 CHILE	Brand Name	Motorola(Chenyang)	Model Name	MC-339L
Battery 1	Brand Name	Motorola(ATL)	Model Name	SP52
Battery 2	Brand Name	Motorola(SWD)	Model Name	SP52
Battery 3	Brand Name	Motorola(COSMX)	Model Name	SP52
USB Cable 1	Brand Name	Motorola(WASHIN)	Model Name	HX-WT-55
USB Cable 2	Brand Name	Motorola(SAIBAO)	Model Name	SWT-A125A
USB Cable 3	Brand Name	Motorola(SAIBAO)	Model Name	SWT-A145A
USB Cable 4	Brand Name	Motorola(NAEE)	Model Name	1.1.0499
Earphone 1	Brand Name	Motorola(LYAND)	Model Name	LYM108B-76C-018
Earphone 2	Brand Name	Motorola(Juwei)	Model Name	JWEP1308-W09H

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.


The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

Pre-scanned tests, X, Y, Z in three orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: GSM 850 Idle + Bluetooth Link + WLAN Link (2.4G) + USB Cable 1(Charging from Adapter) + NFC TX
Remark: For Radiated Test Cases, The tests were performance with Adapter and USB Cable	

2.2 Connection Diagram of Test System



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Base Station	Anritus	MT8821C	N/A	N/A	Unshielded,1.8m
2.	BT Base Station	R&S	CBT	N/A	N/A	Unshielded, 1.8m
3.	WLAN AP	D-link	DIR-655	KA21R655B1	N/A	Unshielded,1.8m
4.	Notebook	Lenovo	G480	QDS-BRCM1050I	N/A	shielded cable DC O/P 1.8m , Unshielded AC I/P cable 1.8m
5.	Bluetooth Earphone	Lenovo	thinkplus-BH3	N/A	N/A	N/A
6.	SD Card	Kingston	8GB	N/A	N/A	N/A
7.	NFC Card	N/A	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.553~13.567MHz.


3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 6.9.2 for 20dB BW and 6.9.3 for 99% occupied bandwidth measurements
2. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
3. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
4. Measured the spectrum width with power higher than 20dB below carrier.
5. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2020 clause 6.8.
2. The spectrum analyzer connected via a receive antenna placed near the EUT.
3. EUT have transmitted signal and fixed channelize.
4. Set the spectrum analyzer span to view the entire emissions bandwidth.
5. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
6. The f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f)/f_c \times 10^6$ ppm and the limit is less than ± 100 ppm.
7. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225	
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.	
Freq. of Emission (MHz)	Field Strength ($\mu\text{V/m}$) at 30m	Field Strength ($\text{dB}\mu\text{V/m}$) at 30m
1.705~13.110	30	29.5
13.110~13.410	106	40.5
13.410~13.553	334	50.5
13.553~13.567	15848	84.0
13.567~13.710	334	50.5
13.710~14.010	106	40.5
14.010~30.000	30	29.5

3.4.2 Measuring Instruments


See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10 clause 6.4. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).
7. The field strength is tested at 3m distance then convert to 30m by adding distance factor $40 \cdot \log(d1/d2)$.

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

<FCC Limit>

Frequencies (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver.

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak


Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures


1. Configure the EUT according to ANSI C63.10 clause 6.5 and 6.6. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. Antenna Requirements

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Note:

1. There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.
2. Tested for radiated below 30 MHz using a loop antenna in accordance with C63.10, the antenna was positioned in three antenna orientations: parallel, perpendicular, and ground-parallel. Pre-scanned the three antenna orientations, the worst case is parallel & perpendicular polarization, and test data of two mode was reported. (Parallel: The loop antenna is placed vertical axis and aligned along the site axis; Perpendicular: The loop antenna is placed vertical axis and orthogonal to the axis; ground-parallel: The loop antenna is placed horizontal axis and parallel with the ground).

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Jul. 07, 2025	Nov. 10, 2025 ~Nov. 11, 2025	Jul. 06, 2026	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 02, 2025	Nov. 10, 2025 ~Nov. 11, 2025	Jul. 01, 2026	Conducted (TH01-KS)
MXE EMI Receiver	Keysight	N9038A	MY57290151	3Hz~8.4GHz	Jul. 02, 2025	Oct. 24, 2025 ~Nov. 24, 2025	Jul. 01, 2026	Radiation (03CH07-KS)
Active loop antenna	R&S	HFH2-Z2E	101125	9kHz~30MHz	Aug. 10, 2025	Oct. 24, 2025 ~Nov. 24, 2025	Aug. 09, 2026	Radiation (03CH07-KS)
Bilog Antenna	TESEQ	CBL 6111D	49921	30MHz~1GHz	Mar. 24, 2025	Oct. 24, 2025 ~Nov. 24, 2025	Mar 23 2026	Radiation (03CH07-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Oct. 24, 2025 ~Nov. 24, 2025	NCR	Radiation (03CH07-KS)
Turn Table	EM	EM 1000-T	N/A	0~360 degree	NCR	Oct. 24, 2025 ~Nov. 24, 2025	NCR	Radiation (03CH07-KS)
Antenna Mast	EM	EM 1000-A	N/A	1 m~4 m	NCR	Oct. 24, 2025 ~Nov. 24, 2025	NCR	Radiation (03CH07-KS)
Amplifier	SONOMA	310N	380826	9KHz~1GHz	Jul. 02, 2025	Oct. 24, 2025 ~Nov. 24, 2025	Jul. 01, 2026	Radiation (03CH07-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 16, 2025	Nov. 19, 2025 ~Nov. 24, 2025	Apr. 15, 2026	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060103	9kHz~30MHz	Jul. 3, 2025	Nov. 19, 2025 ~Nov. 24, 2025	Jul. 2, 2026	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060105	9kHz~30MHz	Dec. 24, 2024	Nov. 19, 2025 ~Nov. 24, 2025	Dec. 23, 2025	Conduction (CO01-KS)
AC Power Source	Ouhan	APW-130NYT	202201040060	AC 0V~300V,45Hz~1000Hz	Apr. 16, 2025	Nov. 19, 2025 ~Nov. 24, 2025	Apr. 15, 2026	Conduction (CO01-KS)

NCR: No Calibration Required

5. Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Measurement

Test Item	Uncertainty
Occupied Channel Bandwidth	$\pm 0.1\%$
Frequency	± 0.4 Hz

Uncertainty of AC Conducted Emission Measurement (0.15 MHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.00dB
--	--------

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	3.30dB
--	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)


Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	6.20dB
--	--------

----- THE END -----



Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Amos Zhang	Temperature :	38~40℃
Test Voltage :	120Vac / 60Hz	Relative Humidity :	25.3~26.2%
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 24+80 LINE


	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.317	47.61	-12.19	59.80	36.80	0.33	10.48	QP
2	0.317	29.61	-20.19	49.80	18.80	0.33	10.48	Average
3	0.433	48.01	-9.19	57.20	37.20	0.35	10.46	QP
4	0.433	32.41	-14.79	47.20	21.60	0.35	10.46	Average
5	0.589	47.94	-8.06	56.00	37.19	0.37	10.38	QP
6	0.589	34.34	-11.66	46.00	23.59	0.37	10.38	Average
7	0.694	47.32	-8.68	56.00	36.60	0.38	10.34	QP
8	0.694	35.22	-10.78	46.00	24.50	0.38	10.34	Average
9	0.923	43.87	-12.13	56.00	33.20	0.39	10.28	QP
10	0.923	33.27	-12.73	46.00	22.60	0.39	10.28	Average
11	1.178	43.26	-12.74	56.00	32.60	0.40	10.26	QP
12	1.178	33.16	-12.84	46.00	22.50	0.40	10.26	Average
13	1.662	43.16	-12.84	56.00	32.50	0.41	10.25	QP
14	1.662	32.46	-13.54	46.00	21.80	0.41	10.25	Average
15	2.273	42.85	-13.15	56.00	32.20	0.42	10.23	QP
16	2.273	31.25	-14.75	46.00	20.60	0.42	10.23	Average
17	2.779	43.14	-12.86	56.00	32.49	0.42	10.23	QP
18	2.779	33.24	-12.76	46.00	22.59	0.42	10.23	Average
19	4.407	42.81	-13.19	56.00	32.19	0.41	10.21	QP
20	4.407	32.21	-13.79	46.00	21.59	0.41	10.21	Average
21	11.080	43.28	-16.72	60.00	32.50	0.53	10.25	QP
22	11.080	32.68	-17.32	50.00	21.90	0.53	10.25	Average
23	13.560	56.11			45.10	0.74	10.27	QP
24 *	13.560	52.21			41.20	0.74	10.27	Average

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Amos Zhang	Temperature :	38~40℃
		Relative Humidity :	25.3~26.2%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 24+80 NEUTRAL


	Freq	Level	Over	Limit	Read	LISN	Cable	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	
			dB	dBuV	dBuV	dB	dB	
1	0.175	57.60	-7.12	64.72	46.89	0.25	10.46	QP
2	0.175	36.20	-18.52	54.72	25.49	0.25	10.46	Average
3	0.348	48.99	-10.01	59.00	38.20	0.31	10.48	QP
4	0.348	30.09	-18.91	49.00	19.30	0.31	10.48	Average
5	0.415	47.43	-10.12	57.55	36.60	0.35	10.48	QP
6	0.415	24.43	-23.12	47.55	13.60	0.35	10.48	Average
7	0.471	47.67	-8.82	56.49	36.90	0.34	10.43	QP
8	0.471	26.37	-20.12	46.49	15.60	0.34	10.43	Average
9	0.604	41.23	-14.77	56.00	30.50	0.36	10.37	QP
10	0.604	28.33	-17.67	46.00	17.60	0.36	10.37	Average
11	0.844	44.16	-11.84	56.00	33.50	0.36	10.30	QP
12	0.844	26.16	-19.84	46.00	15.50	0.36	10.30	Average
13	1.100	45.22	-10.78	56.00	34.59	0.36	10.27	QP
14	1.100	28.42	-17.58	46.00	17.79	0.36	10.27	Average
15	1.734	45.83	-10.17	56.00	35.20	0.38	10.25	QP
16	1.734	30.23	-15.77	46.00	19.60	0.38	10.25	Average
17	2.650	42.12	-13.88	56.00	31.50	0.39	10.23	QP
18	2.650	29.22	-16.78	46.00	18.60	0.39	10.23	Average
19	4.361	43.81	-12.19	56.00	33.20	0.40	10.21	QP
20	4.361	33.21	-12.79	46.00	22.60	0.40	10.21	Average
21	9.966	43.82	-16.18	60.00	33.20	0.39	10.23	QP
22	9.966	35.12	-14.88	50.00	24.50	0.39	10.23	Average
23	13.560	52.19			41.20	0.72	10.27	QP
24 *	13.560	49.19	-0.81	50.00	38.20	0.72	10.27	Average

(1) with antenna

Remark: 13.560MHz is the NFC RF fundamental signal.



Test Engineer :	Amos Zhang	Temperature :	38~40℃
		Relative Humidity :	25.3~26.2%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		




Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-L 24+80 LINE

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1 *	13.560	45.51	-14.49	60.00	34.50	0.74	10.27	QP
2	13.560	34.11	-15.89	50.00	23.10	0.74	10.27	Average

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.

Test Engineer :	Amos Zhang	Temperature :	38~40℃
		Relative Humidity :	25.3~26.2%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Site : CO01-KS
Condition : 15C RSS247-QP LISN-060105-N 24+80 NEUTRAL

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
			dB	dBuV	dBuV	dB	dB	
1	13.560	40.89	-19.11	60.00	29.90	0.72	10.27	QP
2 *	13.560	34.69	-15.31	50.00	23.70	0.72	10.27	Average

(2) With dummy load

Remark: Only the fundamental NFC signal needs to be retested per KDB 174176.



Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)



Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode		NFC Tx		Test Frequency (MHz)		13.56	
							
20dB Bandwidth (kHz)		2.475		99% OccupiedBW(kHz)		2.098	
Frequency range (MHz)		$f_L > 13.553$		13.558741		Test Result	
		$f_H < 13.567$		13.561216		Complies	

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.



B2. Test Result of Frequency Stability

Startup:

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (V)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
NV	13.55997850	-20	13.55997850
LV	13.55997850	-10	13.55997850
HV	13.55997850	0	13.55997850
		10	13.55997850
		20	13.55997850
		30	13.55997850
		40	13.55997850
		50	13.55997850
Max.Deviation (MHz)	-0.00002150	Max.Deviation (MHz)	-0.00002150
Max.Deviation (ppm)	-1.5855	Max.Deviation (ppm)	-1.5855
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS

2MIN:

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (V)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
NV	13.55998550	-20	13.55998550
LV	13.55999250	-10	13.55998550
HV	13.55998550	0	13.55998550
		10	13.55998550
		20	13.55998550
		30	13.55999250
		40	13.55998550
		50	13.55998550
Max.Deviation (MHz)	-0.00001450	Max.Deviation (MHz)	-0.00001450
Max.Deviation (ppm)	-1.0693	Max.Deviation (ppm)	-1.0693
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS



5MIN:


Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (V)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
NV	13.55998550	-20	13.55998550
LV	13.55998550	-10	13.55998550
HV	13.55998550	0	13.55998550
		10	13.55998550
		20	13.55998550
		30	13.55998550
		40	13.55998550
		50	13.55998550
Max.Deviation (MHz)	-0.00001450	Max.Deviation (MHz)	-0.00001450
Max.Deviation (ppm)	-1.0693	Max.Deviation (ppm)	-1.0693
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS


10MIN:

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability	
Voltage (V)	Measurement Frequency (MHz)	Temperature (°C)	Measurement Frequency (MHz)
NV	13.55998550	-20	13.55998550
LV	13.55998550	-10	13.55998550
HV	13.55997850	0	13.55998550
		10	13.55997850
		20	13.55997850
		30	13.55997850
		40	13.55997850
		50	13.55997850
Max.Deviation (MHz)	-0.00002150	Max.Deviation (MHz)	-0.00002150
Max.Deviation (ppm)	-1.5855	Max.Deviation (ppm)	-1.5855
Limit	FS < ±100 ppm	Limit	FS < ±100 ppm
Test Result	PASS	Test Result	PASS


Appendix C. Test Results of Radiated Test Items


C1. Results of Field Strength of Fundamental Emissions





Note:

1. The field strength is tested at 3m distance then convert to 30m by adding Distance extrapolation factor
2. $\text{Level(dB}\mu\text{V/m)} = \text{Read Level(dB}\mu\text{V)} + \text{Antenna Factor(dB/m)} + \text{Cable Loss(dB)}$
3. $\text{Over Limit(dB)} = \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$
4. $\text{Distance extrapolation factor} = 40 \log (\text{specific distance} / \text{test distance}) \text{ (dB)}$;
5. $\text{Corrected Level} = \text{Level @3m (dB}\mu\text{V/m)} - \text{distance extrapolation factor.}$

C2.Results of Radiated Spurious Emissions (9 kHz~30MHz)



Note:

1. The field strength is tested at 3m distance then convert to 300m/30m by adding Distance extrapolation factor.
2. Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);
3. $\text{Level(dB}\mu\text{V/m)} = \text{Read Level(dB}\mu\text{V)} + \text{Antenna Factor(dB/m)} + \text{Cable Loss(dB)} + \text{Aux Factor(distance factor)}$
4. $\text{Over Limit(dB)} = \text{Level(dB}\mu\text{V/m)} - \text{Limit Line(dB}\mu\text{V/m)}$


C3.Results of Radiated Spurious Emissions (30MHz~1GHz)




Test Mode : NFC Tx

Polarization :

Vertical



Site : 03CH07-KS
Condition: Part 15C 3m CBL6111D SN 44483 Vertical

	Freq	Level	Limit	Over	Read	Ant	Cable	Preamp	APos	TPos	Remark
	MHz	dBuV/m	dBuV/m	Limit	Level	Factor	Loss	Factor	cm	deg	
1	38.245	32.91	40.00	-7.09	43.41	20.97	0.59	32.06	---	---	Peak
2	53.765	30.39	40.00	-9.61	49.07	12.59	0.79	32.06	---	---	Peak
3	166.770	25.88	43.50	-17.62	40.28	15.84	1.80	32.04	---	---	Peak
4	300.145	27.83	46.00	-18.17	38.48	18.99	2.44	32.08	---	---	Peak
5	644.253	27.87	46.00	-18.13	29.29	27.27	3.57	32.26	---	---	Peak
6	877.295	29.94	46.00	-16.06	27.76	29.51	4.19	31.52	---	---	Peak