



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT2609-1, XT2609-2, XT2609-3, XT2609V
FCC ID : IHDT56AX1
STANDARD : 47 CFR Part 22, 24, 27, 90, 96
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S) : Mar. 07, 2026

We, Sporton International Inc. (ShenZhen), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (ShenZhen), the test report shall not be reproduced except in full.

Fly Liang

Approved by: Fly Liang



Sporton International Inc. (ShenZhen)

1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055

People's Republic of China



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification of Equipment Under Test	5
1.5 Modification of EUT	6
1.6 Specification of Accessory	6
1.7 Testing Location	6
1.8 Test Software	6
1.9 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Test Mode	8
2.2 Connection Diagram of Test System	8
2.3 Support Unit used in test configuration and system	9
2.4 Frequency List of Low/Middle/High Channels	9
3 RADIATED TEST ITEMS	12
3.1 Measuring Instruments	12
3.2 Test Setup	12
3.3 Test Result of Radiated Test	13
3.4 Radiated Spurious Emission	14
4 LIST OF MEASURING EQUIPMENT	16
5 MEASUREMENT UNCERTAINTY	17
APPENDIX A. TEST RESULTS OF RADIATED TEST	
APPENDIX B. TEST SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG612609K	Rev. 01	Initial issue of report	Mar. 26, 2026

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1053 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(f) §27.53(g) §27.53(h) §90.543 (e)(3) §90.543 (f)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 14) (Band 66) (Band 71)	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 7.59 dB at 7232.00 MHz
	§2.1051 §96.41	Radiated Spurious Emission (Band 48)	-40dBm/MHz		

Remark: The conducted test items of inter band CA were cover by LTE single carrier due to the CA power is reduced according to 3GPP MPR.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty"

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2609-1, XT2609-2, XT2609-3, XT2609V
FCC ID	IHDT56AX1
IMEI Code	Radiation: 357143740030330/357143740030348
EUT Stage	Identical Prototype

Remark: The different model name is different for market purpose.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 14 : 788 MHz ~ 798 MHz LTE Band 48 : 3550 MHz ~ 3700 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz
Rx Frequency	LTE Band 2 : 1930 MHz ~ 1990 MHz LTE Band 4 : 2110 MHz ~ 2155 MHz LTE Band 5 : 869 MHz ~ 894 MHz LTE Band 12 : 729 MHz ~ 746 MHz LTE Band 13 : 746 MHz ~ 756 MHz LTE Band 14 : 758 MHz ~ 768 MHz LTE Band 48 : 3550 MHz ~ 3700 MHz LTE Band 66 : 2110 MHz~ 2200 MHz LTE Band 71: 617 MHz ~ 652 MHz
Uplink CA Bands	12A-66A, 13A-66A, 14A-66A, 2A-12A, 2A-13A, 2A-14A, 2A-4A, 2A-5A, 2A-66A, 2A-48A, 2A-71A, 4A-12A, 4A-13A, 4A-5A, 5A-66A, 48A-66A
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM



1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
Battery	Brand Name	Motorola (Amperex)	Model Name	SB50
USB Cable 1	Brand Name	Motorola(CABLETECH)	Model Name	SC18E05246
USB Cable 2	Brand Name	Motorola(SAIBAO)	Model Name	SC18D86732

1.7 Testing Location

Sporton International Inc. (ShenZhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Test Firm	Sporton International Inc. (ShenZhen)		
Test Site Location	101, 1st Floor, Block B, Building 1, No. 2, Tengfeng 4th Road, Fenghuang Community, Fuyong Street, Baoan District, Shenzhen City, Guangdong Province 518103 People's Republic of China TEL: +86-755-86066985		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	03CH02-SZ	CN1256	421272

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH02-SZ	AUDIX	E3	6.2009-8-24a



1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 22, 24, 27, 90, 96
- ♦ ANSI C63.26-2015
- ♦ FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation				RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	256QAM	1	Half	Full	L	M	H
Radiated Spurious Emission	2A-48A	Worst Case													v		
	4A-13A	Worst Case													v		
	5A-66A	Worst Case													v		
	12A-66A	Worst Case													v		
	13A-66A	Worst Case													v		
	14A-66A	Worst Case													v		
	48A-66A	Worst Case													v		
Note	1. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 2. Pre-scanned harmonics for the UL CA combinations which contain the same PCC band, only the combinations with the worse test results were tested and recorded in the report.																

2.2 Connection Diagram of Test System





2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m

2.4 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3



LTE Band 5 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5

LTE Band 14 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23330	-
	Frequency	-	793	-
5	Channel	23305	23330	23355
	Frequency	790.5	793	795.5



LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560.0	3625.0	3690.0
15	Channel	55315	55990	56665
	Frequency	3557.5	3625.0	3692.5
10	Channel	55290	55990	56690
	Frequency	3555.0	3625.0	3695.0
5	Channel	55265	55990	56715
	Frequency	3552.5	3625.0	3697.5

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3

LTE Band 71 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	133222	133322	133372
	Frequency	673.0	680.5	688.0
15	Channel	133197	133297	133397
	Frequency	670.5	680.5	690.5
10	Channel	133172	133272	133422
	Frequency	668.0	678.0	693.0
5	Channel	133147	133247	133447
	Frequency	665.5	675.5	695.5


3 Radiated Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 For radiated test below 30MHz



3.2.2 For radiated test from 30MHz to 1GHz



3.2.3 For radiated test above 1GHz



3.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix A.



3.4 Radiated Spurious Emission

3.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26.

For LTE Band 2, 4, 5, 12, 66, 71

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

For LTE Band 14

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559-1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

For LTE Band 48

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. $EIRP\ (dBm) = S.G.\ Power - Tx\ Cable\ Loss + Tx\ Antenna\ Gain$
11. $ERP\ (dBm) = EIRP - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY55150213	10Hz~44GHz	Jul. 03, 2025	Mar. 07, 2026	Jul. 02, 2026	Radiation (03CH02-SZ)
Loop Antenna	R&S	HFH2-Z2E	101141	9kHz~30MHz	Dec. 25, 2025	Mar. 07, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
Bilog Antenna	TeseQ	CBL6112D	35407	30MHz-2GHz	Dec. 23, 2025	Mar. 07, 2026	Dec. 22, 2027	Radiation (03CH02-SZ)
Double Ridge Horn Antenna	ETS-Lindgren	3117	00119436	1GHz~18GHz	Jul. 04, 2025	Mar. 07, 2026	Jul. 04, 2026	Radiation (03CH02-SZ)
HF Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz	Jul. 03, 2025	Mar. 07, 2026	Jul. 03, 2026	Radiation (03CH02-SZ)
SHF-EHF Horn	com-power	AH-840	101071	18Ghz-40GHz	Apr. 03, 2025	Mar. 07, 2026	Apr. 02, 2027	Radiation (03CH02-SZ)
LF Amplifier	EM Electronics	EM330	060788	20MHz-3GHz	Dec. 25, 2025	Mar. 07, 2026	Dec. 24, 2026	Radiation (03CH02-SZ)
HF Amplifier	KEYSIGHT	83017A	MY53270105	0.5GHz~26.5Ghz	Oct. 13, 2025	Mar. 07, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
AC Power Source	Chroma	61601	616010003043	N/A	Oct. 13, 2025	Mar. 07, 2026	Oct. 12, 2026	Radiation (03CH02-SZ)
Turn Table	Chaintek	T-200	N/A	0~360 degree	NCR	Mar. 07, 2026	NCR	Radiation (03CH02-SZ)
Antenna Mast	Chaintek	MBS-400	N/A	1 m~4 m	NCR	Mar. 07, 2026	NCR	Radiation (03CH02-SZ)

NCR: No Calibration Required



5 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage $K=2$ to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.47 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.31 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.72 dB
---	---------

----- THE END -----



Appendix A. Test Results of Radiated Test

Radiated Spurious Emission

Test Engineer :	Wenbo Xiao	Temperature :	22~25°C
		Relative Humidity :	48~52%

Pre-scanned harmonic for the different antenna combinations, we choose the worst antenna mode to perform final test and record in the report.

ULCA_12A-66A (ANT0+9)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B12 BW 10MHz Middle 1RB0,QPSK	1406	-63.64	-13	-50.64	-73.72	-66.89	4.00	9.40	H
	2109	-62.42	-13	-49.42	-75.25	-65.99	4.88	10.60	H
	2812	-61.60	-13	-48.60	-76.90	-66.53	5.52	12.60	H
	1406	-64.15	-13	-51.15	-73.79	-67.40	4.00	9.40	V
	2109	-62.32	-13	-49.32	-75.10	-65.89	4.88	10.60	V
	2812	-61.73	-13	-48.73	-77.22	-66.66	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-61.85	-13	-48.85	-78.52	-68.70	5.65	12.50	H
	5208	-60.18	-13	-47.18	-81.67	-65.85	7.13	12.80	H
	6944	-56.54	-13	-43.54	-82.01	-59.94	8.40	11.80	H
	3472	-61.95	-13	-48.95	-78.64	-68.80	5.65	12.50	V
	5208	-59.99	-13	-46.99	-81.73	-65.66	7.13	12.80	V
	6944	-55.87	-13	-42.87	-81.81	-59.27	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_13A-66A (ANT1+9)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B13 BW 10MHz Middle 1RB0,QPSK	1559.5	-64.48	-42.15	-22.33	-74.03	-67.73	4.00	9.40	H
	2339.25	-61.84	-13	-48.84	-76.16	-65.41	4.88	10.60	H
	3119	-61.41	-13	-48.41	-77.89	-66.34	5.52	12.60	H
	1559.5	-64.53	-42.15	-22.38	-74.16	-67.78	4.00	9.40	V
	2339.25	-62.06	-13	-49.06	-76.38	-65.63	4.88	10.60	V
	3119	-61.19	-13	-48.19	-77.71	-66.12	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-62.22	-13	-49.22	-78.89	-69.07	5.65	12.50	H
	5208	-60.33	-13	-47.33	-81.82	-66.00	7.13	12.80	H
	6944	-56.40	-13	-43.40	-81.87	-59.80	8.40	11.80	H
	3472	-61.57	-13	-48.57	-78.26	-68.42	5.65	12.50	V
	5208	-59.61	-13	-46.61	-81.35	-65.28	7.13	12.80	V
	6944	-55.75	-13	-42.75	-81.69	-59.15	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_14A-66A (ANT1+9)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B14 BW 10MHz Middle 1RB0,QPSK	1577	-64.90	-42.15	-22.75	-74.40	-68.15	4.00	9.40	H
	2365.5	-62.33	-13	-49.33	-76.60	-65.90	4.88	10.60	H
	3154	-61.22	-13	-48.22	-77.93	-66.15	5.52	12.60	H
	1577	-64.78	-42.15	-22.63	-74.41	-68.03	4.00	9.40	V
	2365.5	-62.12	-13	-49.12	-76.38	-65.69	4.88	10.60	V
	3154	-61.39	-13	-48.39	-78.10	-66.32	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-61.51	-13	-48.51	-78.18	-68.36	5.65	12.50	H
	5208	-60.42	-13	-47.42	-81.91	-66.09	7.13	12.80	H
	6944	-56.07	-13	-43.07	-81.54	-59.47	8.40	11.80	H
	3472	-61.82	-13	-48.82	-78.51	-68.67	5.65	12.50	V
	5208	-59.98	-13	-46.98	-81.72	-65.65	7.13	12.80	V
	6944	-55.64	-13	-42.64	-81.58	-59.04	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_2A-48A (ANT9+5)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B2 BW 20MHz Middle 1RB0,QPSK	3742	-60.18	-13	-47.18	-78.27	-66.93	5.85	12.60	H
	5613	-59.10	-13	-46.10	-81.11	-64.90	7.30	13.10	H
	7484	-59.36	-13	-46.36	-53.56	-62.51	8.35	11.50	H
	3742	-60.64	-13	-47.64	-78.65	-67.39	5.85	12.60	V
	5613	-58.67	-13	-45.67	-80.87	-64.47	7.30	13.10	V
	7484	-59.43	-13	-46.43	-53.62	-62.58	8.35	11.50	V
LTE B48 BW 20MHz Middle 1RB0,QPSK	7232	-59.79	-40	-19.79	-53.46	-63.09	8.30	11.60	H
	10848	-55.98	-40	-15.98	-56.23	-57.50	10.48	12.00	H
	14464	-50.05	-40	-10.05	-56.32	-51.75	11.80	13.50	H
	7232	-59.19	-40	-19.19	-53.17	-62.49	8.30	11.60	V
	10848	-55.91	-40	-15.91	-55.79	-57.43	10.48	12.00	V
	14464	-50.54	-40	-10.54	-56.23	-52.24	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_4A-13A (ANT9+1)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B4 BW 20MHz Middle 1RB0,QPSK	3447	-55.66	-13	-42.66	-72.17	-62.51	5.65	12.50	H
	5170.5	-59.72	-13	-46.72	-81.32	-65.39	7.13	12.80	H
	6894	-56.88	-13	-43.88	-82.16	-60.28	8.40	11.80	H
	3447	-58.12	-13	-45.12	-74.67	-64.97	5.65	12.50	V
	5170.5	-59.18	-13	-46.18	-81.05	-64.85	7.13	12.80	V
	6894	-56.27	-13	-43.27	-82.03	-59.67	8.40	11.80	V
LTE B13 BW 10MHz Middle 1RB0,QPSK	1559.5	-64.35	-42.15	-22.20	-73.90	-67.60	4.00	9.40	H
	2339.25	-62.33	-13	-49.33	-76.65	-65.90	4.88	10.60	H
	3119	-61.02	-13	-48.02	-77.50	-65.95	5.52	12.60	H
	1559.5	-64.43	-42.15	-22.28	-74.06	-67.68	4.00	9.40	V
	2339.25	-62.23	-13	-49.23	-76.55	-65.80	4.88	10.60	V
	3119	-61.07	-13	-48.07	-77.59	-66.00	5.52	12.60	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



ULCA_5A-66A (ANT0+9)									
Channel	Frequency (MHz)	ERP/EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B5 BW 10MHz Middle 1RB0,QPSK	1664	-65.77	-13	-52.77	-75.33	-69.02	4.00	9.40	H
	2496	-62.97	-13	-49.97	-76.82	-66.54	4.88	10.60	H
	3328	-62.30	-13	-49.30	-78.05	-67.23	5.52	12.60	H
	1664	-65.86	-13	-52.86	-75.02	-69.11	4.00	9.40	V
	2496	-63.07	-13	-50.07	-76.88	-66.64	4.88	10.60	V
	3328	-62.73	-13	-49.73	-78.24	-67.66	5.52	12.60	V
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-59.13	-13	-46.13	-75.80	-65.98	5.65	12.50	H
	5208	-60.14	-13	-47.14	-81.63	-65.81	7.13	12.80	H
	6944	-55.77	-13	-42.77	-81.24	-59.17	8.40	11.80	H
	3472	-59.29	-13	-46.29	-75.98	-66.14	5.65	12.50	V
	5208	-59.75	-13	-46.75	-81.49	-65.42	7.13	12.80	V
	6944	-55.88	-13	-42.88	-81.82	-59.28	8.40	11.80	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

ULCA_48A-66A (ANT5+9)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
LTE B66 BW 20MHz Middle 1RB0,QPSK	3472	-57.59	-13	-44.59	-74.26	-64.44	5.65	12.50	H
	5208	-58.40	-13	-45.40	-79.89	-64.07	7.13	12.80	H
	6944	-60.41	-13	-47.41	-52.75	-63.81	8.40	11.80	H
	3472	-58.16	-13	-45.16	-74.85	-65.01	5.65	12.50	V
	5208	-57.76	-13	-44.76	-79.5	-63.43	7.13	12.80	V
	6944	-59.78	-13	-46.78	-52.59	-63.18	8.40	11.80	V
LTE B48 BW 20MHz Middle 1RB0,QPSK	7232	-47.59	-40	-7.59	-41.26	-50.89	8.30	11.60	H
	10848	-55.47	-40	-15.47	-55.72	-56.99	10.48	12.00	H
	14464	-49.68	-40	-9.68	-55.95	-51.38	11.80	13.50	H
	7232	-52.00	-40	-12.00	-45.98	-55.30	8.30	11.60	V
	10848	-55.81	-40	-15.81	-55.69	-57.33	10.48	12.00	V
	14464	-50.48	-40	-10.48	-56.17	-52.18	11.80	13.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.