




Mode	38																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11n HT20_CH157_5785MHz																																																																							
ANT	6																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	Date: 2026-06-09  Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBN:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.30</td><td>53.32</td><td>112.40</td><td>-59.08</td><td>40.32</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>101 73 Peak</td></tr><tr><td>2 5859.75</td><td>57.06</td><td>109.47</td><td>-52.41</td><td>44.07</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.12</td><td>101 73 Peak</td></tr><tr><td>3 5924.43</td><td>50.60</td><td>68.62</td><td>-18.02</td><td>37.58</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>101 73 Peak</td></tr><tr><td>4 5927.56</td><td>51.39</td><td>68.20</td><td>-16.81</td><td>38.37</td><td>34.06</td><td>12.73</td><td>34.80</td><td>1.03</td><td>101 73 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.30	53.32	112.40	-59.08	40.32	34.00	12.61	34.74	1.13	101 73 Peak	2 5859.75	57.06	109.47	-52.41	44.07	34.00	12.61	34.74	1.12	101 73 Peak	3 5924.43	50.60	68.62	-18.02	37.58	34.05	12.73	34.80	1.04	101 73 Peak	4 5927.56	51.39	68.20	-16.81	38.37	34.06	12.73	34.80	1.03	101 73 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.30	53.32	112.40	-59.08	40.32	34.00	12.61	34.74	1.13	101 73 Peak																																																															
2 5859.75	57.06	109.47	-52.41	44.07	34.00	12.61	34.74	1.12	101 73 Peak																																																															
3 5924.43	50.60	68.62	-18.02	37.58	34.05	12.73	34.80	1.04	101 73 Peak																																																															
4 5927.56	51.39	68.20	-16.81	38.37	34.06	12.73	34.80	1.03	101 73 Peak																																																															



Mode	38																																																																																																																								
	Band Edge - L																																																																																																																								
	U-NII-3_5.725-5.85_802.11n HT20_CH157_5785MHz																																																																																																																								
ANT	6																																																																																																																								
Pol.	Vertical						Fundamental																																																																																																																		
Peak	Level (dBuV/m) Date: 2026-06-09 PEAK_BE(B4)_16-24 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5621.83</td><td>51.56</td><td>68.20</td><td>-16.64</td><td>39.37</td><td>33.40</td><td>12.43</td><td>34.53</td><td>0.89</td><td>400 205 Peak</td></tr><tr><td>2 5650.14</td><td>48.18</td><td>68.30</td><td>-20.12</td><td>35.96</td><td>33.40</td><td>12.44</td><td>34.56</td><td>0.94</td><td>400 205 Peak</td></tr><tr><td>3 5706.38</td><td>51.55</td><td>106.99</td><td>-55.44</td><td>38.84</td><td>33.81</td><td>12.47</td><td>34.61</td><td>1.04</td><td>400 205 Peak</td></tr><tr><td>4 5720.07</td><td>48.44</td><td>110.95</td><td>-62.51</td><td>35.69</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>400 205 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5621.83	51.56	68.20	-16.64	39.37	33.40	12.43	34.53	0.89	400 205 Peak	2 5650.14	48.18	68.30	-20.12	35.96	33.40	12.44	34.56	0.94	400 205 Peak	3 5706.38	51.55	106.99	-55.44	38.84	33.81	12.47	34.61	1.04	400 205 Peak	4 5720.07	48.44	110.95	-62.51	35.69	33.84	12.47	34.62	1.06	400 205 Peak	Level (dBuV/m) Date: 2026-06-09 PEAK(UNII) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>104.28</td><td>-----</td><td>-----</td><td>91.32</td><td>33.96</td><td>12.50</td><td>34.67</td><td>1.17</td><td>400 205 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	104.28	-----	-----	91.32	33.96	12.50	34.67	1.17	400 205 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5621.83	51.56	68.20	-16.64	39.37	33.40	12.43	34.53	0.89	400 205 Peak																																																																																																																
2 5650.14	48.18	68.30	-20.12	35.96	33.40	12.44	34.56	0.94	400 205 Peak																																																																																																																
3 5706.38	51.55	106.99	-55.44	38.84	33.81	12.47	34.61	1.04	400 205 Peak																																																																																																																
4 5720.07	48.44	110.95	-62.51	35.69	33.84	12.47	34.62	1.06	400 205 Peak																																																																																																																
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	104.28	-----	-----	91.32	33.96	12.50	34.67	1.17	400 205 Peak																																																																																																																
Avg	Blank						Level (dBuV/m) Date: 2026-06-09 AVG_54 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5785.00</td><td>98.07</td><td>-----</td><td>-----</td><td>85.09</td><td>33.98</td><td>12.50</td><td>34.68</td><td>1.18</td><td>400 205 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor					MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5785.00	98.07	-----	-----	85.09	33.98	12.50	34.68	1.18	400 205 Average																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																				
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1 5785.00	98.07	-----	-----	85.09	33.98	12.50	34.68	1.18	400 205 Average																																																																																																																



Mode	38																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11n HT20_CH157_5785MHz																																																																							
ANT	6																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.96</td><td>48.95</td><td>110.89</td><td>-61.94</td><td>35.95</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>400 205 Peak</td></tr><tr><td>2 5874.10</td><td>50.35</td><td>105.45</td><td>-55.10</td><td>37.37</td><td>34.00</td><td>12.64</td><td>34.76</td><td>1.10</td><td>400 205 Peak</td></tr><tr><td>3 5924.43</td><td>49.97</td><td>68.62</td><td>-18.65</td><td>36.95</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>400 205 Peak</td></tr><tr><td>4 5947.36</td><td>51.92</td><td>68.20</td><td>-16.28</td><td>38.87</td><td>34.09</td><td>12.77</td><td>34.82</td><td>1.01</td><td>400 205 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5854.96	48.95	110.89	-61.94	35.95	34.00	12.61	34.74	1.13	400 205 Peak	2 5874.10	50.35	105.45	-55.10	37.37	34.00	12.64	34.76	1.10	400 205 Peak	3 5924.43	49.97	68.62	-18.65	36.95	34.05	12.73	34.80	1.04	400 205 Peak	4 5947.36	51.92	68.20	-16.28	38.87	34.09	12.77	34.82	1.01	400 205 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line Margin	Level	Factor	Loss	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																															
1 5854.96	48.95	110.89	-61.94	35.95	34.00	12.61	34.74	1.13	400 205 Peak																																																															
2 5874.10	50.35	105.45	-55.10	37.37	34.00	12.64	34.76	1.10	400 205 Peak																																																															
3 5924.43	49.97	68.62	-18.65	36.95	34.05	12.73	34.80	1.04	400 205 Peak																																																															
4 5947.36	51.92	68.20	-16.28	38.87	34.09	12.77	34.82	1.01	400 205 Peak																																																															



Mode	38																																																																																																																																																																	
	Harmonic																																																																																																																																																																	
	U-NII-3_5.725-5.85_802.11n HT20_CH157_5785MHz																																																																																																																																																																	
ANT	6																																																																																																																																																																	
Pol.	Horizontal	Vertical																																																																																																																																																																
Peak Avg	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 3856.00</td><td>52.80</td><td>74.00</td><td>-21.20</td><td>44.46</td><td>30.71</td><td>10.29</td><td>33.44</td><td>0.78</td><td>100 296 Peak</td></tr><tr><td>2 3856.00</td><td>50.63</td><td>54.00</td><td>-3.37</td><td>42.29</td><td>30.71</td><td>10.29</td><td>33.44</td><td>0.78</td><td>100 296 Average</td></tr><tr><td>3 11570.00</td><td>51.79</td><td>74.00</td><td>-22.21</td><td>33.79</td><td>39.06</td><td>17.86</td><td>40.30</td><td>1.38</td><td>140 162 Peak</td></tr><tr><td>4 11570.00</td><td>42.47</td><td>54.00</td><td>-11.53</td><td>24.47</td><td>39.06</td><td>17.86</td><td>40.30</td><td>1.38</td><td>140 162 Average</td></tr><tr><td>5 17355.00</td><td>54.28</td><td>68.20</td><td>-13.92</td><td>36.47</td><td>40.41</td><td>22.08</td><td>46.60</td><td>1.92</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 3856.00	52.80	74.00	-21.20	44.46	30.71	10.29	33.44	0.78	100 296 Peak	2 3856.00	50.63	54.00	-3.37	42.29	30.71	10.29	33.44	0.78	100 296 Average	3 11570.00	51.79	74.00	-22.21	33.79	39.06	17.86	40.30	1.38	140 162 Peak	4 11570.00	42.47	54.00	-11.53	24.47	39.06	17.86	40.30	1.38	140 162 Average	5 17355.00	54.28	68.20	-13.92	36.47	40.41	22.08	46.60	1.92	-- -- Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 3856.00</td><td>51.14</td><td>74.00</td><td>-22.86</td><td>42.80</td><td>30.71</td><td>10.29</td><td>33.44</td><td>0.78</td><td>362 254 Peak</td></tr><tr><td>2 3856.00</td><td>48.02</td><td>54.00</td><td>-5.98</td><td>39.68</td><td>30.71</td><td>10.29</td><td>33.44</td><td>0.78</td><td>362 254 Average</td></tr><tr><td>3 11570.00</td><td>55.20</td><td>74.00</td><td>-18.80</td><td>37.20</td><td>39.06</td><td>17.86</td><td>40.30</td><td>1.38</td><td>104 240 Peak</td></tr><tr><td>4 11570.00</td><td>45.78</td><td>54.00</td><td>-8.22</td><td>27.78</td><td>39.06</td><td>17.86</td><td>40.30</td><td>1.38</td><td>104 240 Average</td></tr><tr><td>5 17355.00</td><td>55.06</td><td>68.20</td><td>-13.14</td><td>37.25</td><td>40.41</td><td>22.08</td><td>46.60</td><td>1.92</td><td>-- -- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 3856.00	51.14	74.00	-22.86	42.80	30.71	10.29	33.44	0.78	362 254 Peak	2 3856.00	48.02	54.00	-5.98	39.68	30.71	10.29	33.44	0.78	362 254 Average	3 11570.00	55.20	74.00	-18.80	37.20	39.06	17.86	40.30	1.38	104 240 Peak	4 11570.00	45.78	54.00	-8.22	27.78	39.06	17.86	40.30	1.38	104 240 Average	5 17355.00	55.06	68.20	-13.14	37.25	40.41	22.08	46.60	1.92	-- -- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 3856.00	52.80	74.00	-21.20	44.46	30.71	10.29	33.44	0.78	100 296 Peak																																																																																																																																																									
2 3856.00	50.63	54.00	-3.37	42.29	30.71	10.29	33.44	0.78	100 296 Average																																																																																																																																																									
3 11570.00	51.79	74.00	-22.21	33.79	39.06	17.86	40.30	1.38	140 162 Peak																																																																																																																																																									
4 11570.00	42.47	54.00	-11.53	24.47	39.06	17.86	40.30	1.38	140 162 Average																																																																																																																																																									
5 17355.00	54.28	68.20	-13.92	36.47	40.41	22.08	46.60	1.92	-- -- Peak																																																																																																																																																									
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																									
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																									
1 3856.00	51.14	74.00	-22.86	42.80	30.71	10.29	33.44	0.78	362 254 Peak																																																																																																																																																									
2 3856.00	48.02	54.00	-5.98	39.68	30.71	10.29	33.44	0.78	362 254 Average																																																																																																																																																									
3 11570.00	55.20	74.00	-18.80	37.20	39.06	17.86	40.30	1.38	104 240 Peak																																																																																																																																																									
4 11570.00	45.78	54.00	-8.22	27.78	39.06	17.86	40.30	1.38	104 240 Average																																																																																																																																																									
5 17355.00	55.06	68.20	-13.14	37.25	40.41	22.08	46.60	1.92	-- -- Peak																																																																																																																																																									






Mode	38	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT20_CH157_5785MHz	
ANT	6	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL



Mode	39																																																																																																																							
	Band Edge																																																																																																																							
	U-NII-3_5.725-5.85_802.11n HT20_CH165_5825MHz																																																																																																																							
ANT	6																																																																																																																							
Pol.	Horizontal					Fundamental																																																																																																																		
Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.63</td><td>60.69</td><td>111.65</td><td>-50.96</td><td>47.69</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>100 67 Peak</td></tr><tr><td>2 5871.63</td><td>57.98</td><td>106.14</td><td>-48.16</td><td>44.98</td><td>34.00</td><td>12.64</td><td>34.75</td><td>1.11</td><td>100 67 Peak</td></tr><tr><td>3 5924.75</td><td>49.30</td><td>68.38</td><td>-19.08</td><td>36.28</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>100 67 Peak</td></tr><tr><td>4 5926.63</td><td>51.39</td><td>68.20</td><td>-16.81</td><td>38.37</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>100 67 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5854.63	60.69	111.65	-50.96	47.69	34.00	12.61	34.74	1.13	100 67 Peak	2 5871.63	57.98	106.14	-48.16	44.98	34.00	12.64	34.75	1.11	100 67 Peak	3 5924.75	49.30	68.38	-19.08	36.28	34.05	12.73	34.80	1.04	100 67 Peak	4 5926.63	51.39	68.20	-16.81	38.37	34.05	12.73	34.80	1.04	100 67 Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5825.00</td><td>109.04</td><td>-----</td><td>-----</td><td>96.03</td><td>34.00</td><td>12.55</td><td>34.71</td><td>1.17</td><td>100 67 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5825.00	109.04	-----	-----	96.03	34.00	12.55	34.71	1.17	100 67 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5854.63	60.69	111.65	-50.96	47.69	34.00	12.61	34.74	1.13	100 67 Peak																																																																																																															
2 5871.63	57.98	106.14	-48.16	44.98	34.00	12.64	34.75	1.11	100 67 Peak																																																																																																															
3 5924.75	49.30	68.38	-19.08	36.28	34.05	12.73	34.80	1.04	100 67 Peak																																																																																																															
4 5926.63	51.39	68.20	-16.81	38.37	34.05	12.73	34.80	1.04	100 67 Peak																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5825.00	109.04	-----	-----	96.03	34.00	12.55	34.71	1.17	100 67 Peak																																																																																																															
Avg	Blank					Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5825.00</td><td>101.20</td><td>-----</td><td>-----</td><td>88.19</td><td>34.00</td><td>12.55</td><td>34.71</td><td>1.17</td><td>100 67 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5825.00	101.20	-----	-----	88.19	34.00	12.55	34.71	1.17	100 67 Average																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5825.00	101.20	-----	-----	88.19	34.00	12.55	34.71	1.17	100 67 Average																																																																																																															





Mode	39																																																																																																																																										
	Band Edge																																																																																																																																										
	U-NII-3_5.725-5.85_802.11n HT20_CH165_5825MHz																																																																																																																																										
ANT	6																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-06-09  PEAK_BE(B4)_16-24 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5855.00</td><td>51.07</td><td>110.80</td><td>-59.73</td><td>38.07</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>396</td><td>211</td><td>Peak</td></tr><tr><td>2</td><td>5874.13</td><td>50.54</td><td>105.44</td><td>-54.90</td><td>37.56</td><td>34.00</td><td>12.64</td><td>34.76</td><td>1.10</td><td>396</td><td>211</td><td>Peak</td></tr><tr><td>3</td><td>5924.75</td><td>50.82</td><td>68.38</td><td>-17.56</td><td>37.00</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>396</td><td>211</td><td>Peak</td></tr><tr><td>4</td><td>5938.38</td><td>51.56</td><td>68.20</td><td>-16.64</td><td>38.52</td><td>34.08</td><td>12.75</td><td>34.81</td><td>1.02</td><td>396</td><td>211</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5855.00	51.07	110.80	-59.73	38.07	34.00	12.61	34.74	1.13	396	211	Peak	2	5874.13	50.54	105.44	-54.90	37.56	34.00	12.64	34.76	1.10	396	211	Peak	3	5924.75	50.82	68.38	-17.56	37.00	34.05	12.73	34.80	1.04	396	211	Peak	4	5938.38	51.56	68.20	-16.64	38.52	34.08	12.75	34.81	1.02	396	211	Peak	Level (dBuV/m) Date: 2026-06-09  PEAK(UNII) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>103.16</td><td>-----</td><td>-----</td><td>90.15</td><td>34.00</td><td>12.55</td><td>34.71</td><td>1.17</td><td>396</td><td>211</td><td>Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	103.16	-----	-----	90.15	34.00	12.55	34.71	1.17	396	211	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5855.00	51.07	110.80	-59.73	38.07	34.00	12.61	34.74	1.13	396	211	Peak																																																																																																																															
2	5874.13	50.54	105.44	-54.90	37.56	34.00	12.64	34.76	1.10	396	211	Peak																																																																																																																															
3	5924.75	50.82	68.38	-17.56	37.00	34.05	12.73	34.80	1.04	396	211	Peak																																																																																																																															
4	5938.38	51.56	68.20	-16.64	38.52	34.08	12.75	34.81	1.02	396	211	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	103.16	-----	-----	90.15	34.00	12.55	34.71	1.17	396	211	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-06-09  AVG_54 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5825.00</td><td>95.83</td><td>-----</td><td>-----</td><td>82.82</td><td>34.00</td><td>12.55</td><td>34.71</td><td>1.17</td><td>396</td><td>211</td><td>Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5825.00	95.83	-----	-----	82.82	34.00	12.55	34.71	1.17	396	211	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																						
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5825.00	95.83	-----	-----	82.82	34.00	12.55	34.71	1.17	396	211	Average																																																																																																																															



Mode	39																																																																																																																																																																																					
	Harmonic																																																																																																																																																																																					
	U-NII-3_5.725-5.85_802.11n HT20_CH165_5825MHz																																																																																																																																																																																					
ANT	6																																																																																																																																																																																					
Pol.	Horizontal	Vertical																																																																																																																																																																																				
Peak Avg	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>3880.00</td><td>54.64</td><td>74.00</td><td>-19.36</td><td>46.23</td><td>30.76</td><td>10.31</td><td>33.45</td><td>0.79</td><td>100</td><td>297 Peak</td></tr><tr><td>2</td><td>3880.00</td><td>50.34</td><td>54.00</td><td>-3.66</td><td>41.93</td><td>30.76</td><td>10.31</td><td>33.45</td><td>0.79</td><td>100</td><td>297 Average</td></tr><tr><td>3</td><td>11650.00</td><td>50.07</td><td>74.00</td><td>-23.93</td><td>32.23</td><td>38.90</td><td>17.93</td><td>40.37</td><td>1.38</td><td>111</td><td>154 Peak</td></tr><tr><td>4</td><td>11650.00</td><td>41.24</td><td>54.00</td><td>-12.76</td><td>23.40</td><td>38.90</td><td>17.93</td><td>40.37</td><td>1.38</td><td>111</td><td>154 Average</td></tr><tr><td>5</td><td>17475.00</td><td>52.92</td><td>68.20</td><td>-15.28</td><td>34.94</td><td>40.60</td><td>22.19</td><td>46.72</td><td>1.91</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	3880.00	54.64	74.00	-19.36	46.23	30.76	10.31	33.45	0.79	100	297 Peak	2	3880.00	50.34	54.00	-3.66	41.93	30.76	10.31	33.45	0.79	100	297 Average	3	11650.00	50.07	74.00	-23.93	32.23	38.90	17.93	40.37	1.38	111	154 Peak	4	11650.00	41.24	54.00	-12.76	23.40	38.90	17.93	40.37	1.38	111	154 Average	5	17475.00	52.92	68.20	-15.28	34.94	40.60	22.19	46.72	1.91	--	-- Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>3880.00</td><td>52.15</td><td>74.00</td><td>-21.85</td><td>43.74</td><td>30.76</td><td>10.31</td><td>33.45</td><td>0.79</td><td>303</td><td>254 Peak</td></tr><tr><td>2</td><td>3880.00</td><td>47.53</td><td>54.00</td><td>-6.47</td><td>39.12</td><td>30.76</td><td>10.31</td><td>33.45</td><td>0.79</td><td>303</td><td>254 Average</td></tr><tr><td>3</td><td>11650.00</td><td>50.10</td><td>74.00</td><td>-23.90</td><td>32.26</td><td>38.90</td><td>17.93</td><td>40.37</td><td>1.38</td><td>118</td><td>241 Peak</td></tr><tr><td>4</td><td>11650.00</td><td>43.23</td><td>54.00</td><td>-10.77</td><td>25.39</td><td>38.90</td><td>17.93</td><td>40.37</td><td>1.38</td><td>118</td><td>241 Average</td></tr><tr><td>5</td><td>17475.00</td><td>53.00</td><td>68.20</td><td>-15.20</td><td>35.02</td><td>40.60</td><td>22.19</td><td>46.72</td><td>1.91</td><td>--</td><td>-- Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	3880.00	52.15	74.00	-21.85	43.74	30.76	10.31	33.45	0.79	303	254 Peak	2	3880.00	47.53	54.00	-6.47	39.12	30.76	10.31	33.45	0.79	303	254 Average	3	11650.00	50.10	74.00	-23.90	32.26	38.90	17.93	40.37	1.38	118	241 Peak	4	11650.00	43.23	54.00	-10.77	25.39	38.90	17.93	40.37	1.38	118	241 Average	5	17475.00	53.00	68.20	-15.20	35.02	40.60	22.19	46.72	1.91	--	-- Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	3880.00	54.64	74.00	-19.36	46.23	30.76	10.31	33.45	0.79	100	297 Peak																																																																																																																																																																											
2	3880.00	50.34	54.00	-3.66	41.93	30.76	10.31	33.45	0.79	100	297 Average																																																																																																																																																																											
3	11650.00	50.07	74.00	-23.93	32.23	38.90	17.93	40.37	1.38	111	154 Peak																																																																																																																																																																											
4	11650.00	41.24	54.00	-12.76	23.40	38.90	17.93	40.37	1.38	111	154 Average																																																																																																																																																																											
5	17475.00	52.92	68.20	-15.28	34.94	40.60	22.19	46.72	1.91	--	-- Peak																																																																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																													
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																														
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																													
1	3880.00	52.15	74.00	-21.85	43.74	30.76	10.31	33.45	0.79	303	254 Peak																																																																																																																																																																											
2	3880.00	47.53	54.00	-6.47	39.12	30.76	10.31	33.45	0.79	303	254 Average																																																																																																																																																																											
3	11650.00	50.10	74.00	-23.90	32.26	38.90	17.93	40.37	1.38	118	241 Peak																																																																																																																																																																											
4	11650.00	43.23	54.00	-10.77	25.39	38.90	17.93	40.37	1.38	118	241 Average																																																																																																																																																																											
5	17475.00	53.00	68.20	-15.20	35.02	40.60	22.19	46.72	1.91	--	-- Peak																																																																																																																																																																											



Mode	39	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT20_CH165_5825MHz	
ANT	6	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Date: 2026-06-09  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL	Date: 2026-06-09  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL



Mode	40																																																																																																																							
	Band Edge - L																																																																																																																							
	U-NII-3_5.725-5.85_802.11n HT40_CH151_5755MHz																																																																																																																							
ANT	6																																																																																																																							
Pol.	Horizontal					Fundamental																																																																																																																		
Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5644.02</td><td>52.60</td><td>68.20</td><td>-15.60</td><td>40.38</td><td>33.40</td><td>12.44</td><td>34.55</td><td>0.93</td><td>100 61 Peak</td></tr><tr><td>2 5652.24</td><td>52.59</td><td>69.86</td><td>-17.27</td><td>40.35</td><td>33.42</td><td>12.44</td><td>34.56</td><td>0.94</td><td>100 61 Peak</td></tr><tr><td>3 5719.35</td><td>74.05</td><td>110.62</td><td>-36.57</td><td>61.30</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>100 61 Peak</td></tr><tr><td>4 5720.59</td><td>74.98</td><td>112.15</td><td>-37.17</td><td>62.23</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>100 61 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5644.02	52.60	68.20	-15.60	40.38	33.40	12.44	34.55	0.93	100 61 Peak	2 5652.24	52.59	69.86	-17.27	40.35	33.42	12.44	34.56	0.94	100 61 Peak	3 5719.35	74.05	110.62	-36.57	61.30	33.84	12.47	34.62	1.06	100 61 Peak	4 5720.59	74.98	112.15	-37.17	62.23	33.84	12.47	34.62	1.06	100 61 Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5755.00</td><td>107.96</td><td>-----</td><td>-----</td><td>95.07</td><td>33.92</td><td>12.49</td><td>34.65</td><td>1.13</td><td>100 61 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5755.00	107.96	-----	-----	95.07	33.92	12.49	34.65	1.13	100 61 Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5644.02	52.60	68.20	-15.60	40.38	33.40	12.44	34.55	0.93	100 61 Peak																																																																																																															
2 5652.24	52.59	69.86	-17.27	40.35	33.42	12.44	34.56	0.94	100 61 Peak																																																																																																															
3 5719.35	74.05	110.62	-36.57	61.30	33.84	12.47	34.62	1.06	100 61 Peak																																																																																																															
4 5720.59	74.98	112.15	-37.17	62.23	33.84	12.47	34.62	1.06	100 61 Peak																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5755.00	107.96	-----	-----	95.07	33.92	12.49	34.65	1.13	100 61 Peak																																																																																																															
Avg	Blank					Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:1.100kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5755.00</td><td>100.71</td><td>-----</td><td>-----</td><td>87.85</td><td>33.90</td><td>12.49</td><td>34.65</td><td>1.12</td><td>100 61 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5755.00	100.71	-----	-----	87.85	33.90	12.49	34.65	1.12	100 61 Average																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																															
Freq	Level	Line Margin	Level	Factor	Loss Factor	Factor																																																																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																															
1 5755.00	100.71	-----	-----	87.85	33.90	12.49	34.65	1.12	100 61 Average																																																																																																															



Mode	40																																																																															
	Band Edge - R																																																																															
	U-NII-3_5.725-5.85_802.11n HT40_CH151_5755MHz																																																																															
ANT	6																																																																															
Pol.	Horizontal					Fundamental																																																																										
Peak	Level (dBuV/m) Date: 2026-06-09 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.45</td><td>51.19</td><td>112.05</td><td>-60.86</td><td>38.19</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>100 61 Peak</td></tr><tr><td>2 5873.56</td><td>50.58</td><td>105.60</td><td>-55.02</td><td>37.60</td><td>34.00</td><td>12.64</td><td>34.76</td><td>1.10</td><td>100 61 Peak</td></tr><tr><td>3 5922.70</td><td>50.81</td><td>69.90</td><td>-19.09</td><td>37.00</td><td>34.05</td><td>12.72</td><td>34.80</td><td>1.04</td><td>100 61 Peak</td></tr><tr><td>4 5936.55</td><td>50.55</td><td>68.20</td><td>-17.65</td><td>37.52</td><td>34.07</td><td>12.75</td><td>34.81</td><td>1.02</td><td>100 61 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5854.45	51.19	112.05	-60.86	38.19	34.00	12.61	34.74	1.13	100 61 Peak	2 5873.56	50.58	105.60	-55.02	37.60	34.00	12.64	34.76	1.10	100 61 Peak	3 5922.70	50.81	69.90	-19.09	37.00	34.05	12.72	34.80	1.04	100 61 Peak	4 5936.55	50.55	68.20	-17.65	37.52	34.07	12.75	34.81	1.02	100 61 Peak	Blank				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																							
Freq	Level	Line Margin	Level	Factor	Loss	Factor																																																																										
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																							
1 5854.45	51.19	112.05	-60.86	38.19	34.00	12.61	34.74	1.13	100 61 Peak																																																																							
2 5873.56	50.58	105.60	-55.02	37.60	34.00	12.64	34.76	1.10	100 61 Peak																																																																							
3 5922.70	50.81	69.90	-19.09	37.00	34.05	12.72	34.80	1.04	100 61 Peak																																																																							
4 5936.55	50.55	68.20	-17.65	37.52	34.07	12.75	34.81	1.02	100 61 Peak																																																																							



Mode	40																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11n HT40_CH151_5755MHz																																																																																																																																										
ANT	6																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-06-09 PEAK_BE(B4)_16-24 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5619.69</td><td>50.51</td><td>68.20</td><td>-17.69</td><td>38.33</td><td>33.40</td><td>12.43</td><td>34.53</td><td>0.88</td><td>317</td><td>254</td><td>Peak</td></tr><tr><td>2</td><td>5651.00</td><td>49.98</td><td>68.94</td><td>-18.96</td><td>37.75</td><td>33.41</td><td>12.44</td><td>34.56</td><td>0.94</td><td>317</td><td>254</td><td>Peak</td></tr><tr><td>3</td><td>5716.72</td><td>67.71</td><td>109.88</td><td>-42.17</td><td>54.98</td><td>33.83</td><td>12.47</td><td>34.62</td><td>1.05</td><td>317</td><td>254</td><td>Peak</td></tr><tr><td>4</td><td>5728.28</td><td>67.40</td><td>111.44</td><td>-44.04</td><td>54.65</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>317</td><td>254</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5619.69	50.51	68.20	-17.69	38.33	33.40	12.43	34.53	0.88	317	254	Peak	2	5651.00	49.98	68.94	-18.96	37.75	33.41	12.44	34.56	0.94	317	254	Peak	3	5716.72	67.71	109.88	-42.17	54.98	33.83	12.47	34.62	1.05	317	254	Peak	4	5728.28	67.40	111.44	-44.04	54.65	33.84	12.47	34.62	1.06	317	254	Peak	Level (dBuV/m) Date: 2026-06-10 PEAK(UNII) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>100.81</td><td>-----</td><td>-----</td><td>87.95</td><td>33.90</td><td>12.49</td><td>34.65</td><td>1.12</td><td>317</td><td>254</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	100.81	-----	-----	87.95	33.90	12.49	34.65	1.12	317	254	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5619.69	50.51	68.20	-17.69	38.33	33.40	12.43	34.53	0.88	317	254	Peak																																																																																																																															
2	5651.00	49.98	68.94	-18.96	37.75	33.41	12.44	34.56	0.94	317	254	Peak																																																																																																																															
3	5716.72	67.71	109.88	-42.17	54.98	33.83	12.47	34.62	1.05	317	254	Peak																																																																																																																															
4	5728.28	67.40	111.44	-44.04	54.65	33.84	12.47	34.62	1.06	317	254	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	100.81	-----	-----	87.95	33.90	12.49	34.65	1.12	317	254	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-06-10 AVG_54 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:1.100kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5755.00</td><td>94.65</td><td>-----</td><td>-----</td><td>81.76</td><td>33.92</td><td>12.49</td><td>34.65</td><td>1.13</td><td>317</td><td>254</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5755.00	94.65	-----	-----	81.76	33.92	12.49	34.65	1.13	317	254	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5755.00	94.65	-----	-----	81.76	33.92	12.49	34.65	1.13	317	254	Average																																																																																																																															






Mode	40																																																																																																												
	Harmonic																																																																																																												
	U-NII-3_5.725-5.85_802.11n HT40_CH151_5755MHz																																																																																																												
ANT	6																																																																																																												
Pol.	Horizontal						Vertical																																																																																																						
Peak Avg																																																																																																													
	Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL						Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL																																																																																																						
<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>3838.00</td><td>52.97</td><td>74.00</td><td>-21.03</td><td>44.72</td><td>30.63</td><td>10.28</td><td>33.44</td><td>0.78</td><td>108</td><td>313</td><td>Peak</td></tr><tr><td>2</td><td>3838.00</td><td>50.64</td><td>54.00</td><td>-3.36</td><td>42.39</td><td>30.63</td><td>10.28</td><td>33.44</td><td>0.78</td><td>108</td><td>313</td><td>Average</td></tr><tr><td>3</td><td>11510.00</td><td>51.86</td><td>74.00</td><td>-22.14</td><td>33.97</td><td>38.94</td><td>17.82</td><td>40.24</td><td>1.37</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4</td><td>11510.00</td><td>42.30</td><td>54.00</td><td>-11.70</td><td>24.41</td><td>38.94</td><td>17.82</td><td>40.24</td><td>1.37</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>5</td><td>17265.00</td><td>54.08</td><td>68.20</td><td>-14.12</td><td>36.27</td><td>40.40</td><td>22.00</td><td>46.52</td><td>1.93</td><td>--</td><td>--</td><td>Peak</td></tr></table>															Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3838.00	52.97	74.00	-21.03	44.72	30.63	10.28	33.44	0.78	108	313	Peak	2	3838.00	50.64	54.00	-3.36	42.39	30.63	10.28	33.44	0.78	108	313	Average	3	11510.00	51.86	74.00	-22.14	33.97	38.94	17.82	40.24	1.37	--	--	Peak	4	11510.00	42.30	54.00	-11.70	24.41	38.94	17.82	40.24	1.37	--	--	Average	5	17265.00	54.08	68.20	-14.12	36.27	40.40	22.00	46.52	1.93	--	--	Peak
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																					
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																			
1	3838.00	52.97	74.00	-21.03	44.72	30.63	10.28	33.44	0.78	108	313	Peak																																																																																																	
2	3838.00	50.64	54.00	-3.36	42.39	30.63	10.28	33.44	0.78	108	313	Average																																																																																																	
3	11510.00	51.86	74.00	-22.14	33.97	38.94	17.82	40.24	1.37	--	--	Peak																																																																																																	
4	11510.00	42.30	54.00	-11.70	24.41	38.94	17.82	40.24	1.37	--	--	Average																																																																																																	
5	17265.00	54.08	68.20	-14.12	36.27	40.40	22.00	46.52	1.93	--	--	Peak																																																																																																	



Mode	40	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT40_CH151_5755MHz	
ANT	6	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2026-06-10 Frequency (MHz) Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL	Level (dBuV/m) Date: 2026-06-10 Frequency (MHz) Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL



Mode	41																																																																																																																																					
	Band Edge - L																																																																																																																																					
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																																																																																					
ANT	6																																																																																																																																					
Pol.	Horizontal						Fundamental																																																																																																																															
Peak	Level (dBuV/m) Date: 2026-06-10  Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5640.37</td><td>51.51</td><td>68.20</td><td>-16.69</td><td>39.30</td><td>33.40</td><td>12.44</td><td>34.55</td><td>0.92</td><td>100</td><td>74 Peak</td></tr><tr><td>2</td><td>5650.70</td><td>49.16</td><td>68.72</td><td>-19.56</td><td>36.93</td><td>33.41</td><td>12.44</td><td>34.56</td><td>0.94</td><td>100</td><td>74 Peak</td></tr><tr><td>3</td><td>5703.74</td><td>54.83</td><td>106.25</td><td>-51.42</td><td>42.12</td><td>33.81</td><td>12.47</td><td>34.60</td><td>1.03</td><td>100</td><td>74 Peak</td></tr><tr><td>4</td><td>5720.12</td><td>55.40</td><td>111.07</td><td>-55.67</td><td>42.65</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>100</td><td>74 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5640.37	51.51	68.20	-16.69	39.30	33.40	12.44	34.55	0.92	100	74 Peak	2	5650.70	49.16	68.72	-19.56	36.93	33.41	12.44	34.56	0.94	100	74 Peak	3	5703.74	54.83	106.25	-51.42	42.12	33.81	12.47	34.60	1.03	100	74 Peak	4	5720.12	55.40	111.07	-55.67	42.65	33.84	12.47	34.62	1.06	100	74 Peak	Level (dBuV/m) Date: 2026-06-10  Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>107.41</td><td>-----</td><td>-----</td><td>94.39</td><td>34.00</td><td>12.51</td><td>34.69</td><td>1.20</td><td>100</td><td>74 Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	107.41	-----	-----	94.39	34.00	12.51	34.69	1.20	100	74 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5640.37	51.51	68.20	-16.69	39.30	33.40	12.44	34.55	0.92	100	74 Peak																																																																																																																											
2	5650.70	49.16	68.72	-19.56	36.93	33.41	12.44	34.56	0.94	100	74 Peak																																																																																																																											
3	5703.74	54.83	106.25	-51.42	42.12	33.81	12.47	34.60	1.03	100	74 Peak																																																																																																																											
4	5720.12	55.40	111.07	-55.67	42.65	33.84	12.47	34.62	1.06	100	74 Peak																																																																																																																											
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																													
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5795.00	107.41	-----	-----	94.39	34.00	12.51	34.69	1.20	100	74 Peak																																																																																																																											
Avg	Blank						Level (dBuV/m) Date: 2026-06-10  Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:1.100kHz SMT:Auto <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>5795.00</td><td>100.38</td><td>-----</td><td>-----</td><td>87.37</td><td>33.99</td><td>12.51</td><td>34.68</td><td>1.19</td><td>100</td><td>74 Average</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level Factor	Loss Factor	Factor						MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5795.00	100.38	-----	-----	87.37	33.99	12.51	34.68	1.19	100	74 Average																																																																															
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line Margin	Level Factor	Loss Factor	Factor																																																																																																																																	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																												
1	5795.00	100.38	-----	-----	87.37	33.99	12.51	34.68	1.19	100	74 Average																																																																																																																											



Mode	41																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																							
ANT	6																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.52</td><td>54.09</td><td>111.89</td><td>-57.80</td><td>41.09</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>100 74 Peak</td></tr><tr><td>2 5871.11</td><td>55.90</td><td>106.29</td><td>-50.39</td><td>42.91</td><td>34.00</td><td>12.63</td><td>34.75</td><td>1.11</td><td>100 74 Peak</td></tr><tr><td>3 5924.74</td><td>49.04</td><td>68.40</td><td>-19.36</td><td>36.02</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>100 74 Peak</td></tr><tr><td>4 5943.18</td><td>51.58</td><td>68.20</td><td>-16.62</td><td>38.54</td><td>34.09</td><td>12.76</td><td>34.82</td><td>1.01</td><td>100 74 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5854.52	54.09	111.89	-57.80	41.09	34.00	12.61	34.74	1.13	100 74 Peak	2 5871.11	55.90	106.29	-50.39	42.91	34.00	12.63	34.75	1.11	100 74 Peak	3 5924.74	49.04	68.40	-19.36	36.02	34.05	12.73	34.80	1.04	100 74 Peak	4 5943.18	51.58	68.20	-16.62	38.54	34.09	12.76	34.82	1.01	100 74 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line Margin	Level	Factor	Loss	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																															
1 5854.52	54.09	111.89	-57.80	41.09	34.00	12.61	34.74	1.13	100 74 Peak																																																															
2 5871.11	55.90	106.29	-50.39	42.91	34.00	12.63	34.75	1.11	100 74 Peak																																																															
3 5924.74	49.04	68.40	-19.36	36.02	34.05	12.73	34.80	1.04	100 74 Peak																																																															
4 5943.18	51.58	68.20	-16.62	38.54	34.09	12.76	34.82	1.01	100 74 Peak																																																															



Mode	41											
	Band Edge - L											
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz											
ANT	6											
Pol.	Vertical						Fundamental					
Peak	Level (dBuV/m) Date: 2026-06-10											



Mode	41																																																																																				
	Band Edge - R																																																																																				
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																																				
ANT	6																																																																																				
Pol.	Vertical	Fundamental																																																																																			
Peak	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5854.99</td><td>48.28</td><td>110.83</td><td>-62.55</td><td>35.28</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>400</td><td>203</td><td>Peak</td></tr><tr><td>2</td><td>5874.83</td><td>50.17</td><td>105.25</td><td>-55.08</td><td>37.19</td><td>34.00</td><td>12.64</td><td>34.76</td><td>1.10</td><td>400</td><td>203</td><td>Peak</td></tr><tr><td>3</td><td>5923.50</td><td>50.42</td><td>69.31</td><td>-18.89</td><td>37.40</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>400</td><td>203</td><td>Peak</td></tr><tr><td>4</td><td>5940.08</td><td>51.20</td><td>68.20</td><td>-17.00</td><td>38.16</td><td>34.08</td><td>12.76</td><td>34.82</td><td>1.02</td><td>400</td><td>203</td><td>Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5854.99	48.28	110.83	-62.55	35.28	34.00	12.61	34.74	1.13	400	203	Peak	2	5874.83	50.17	105.25	-55.08	37.19	34.00	12.64	34.76	1.10	400	203	Peak	3	5923.50	50.42	69.31	-18.89	37.40	34.05	12.73	34.80	1.04	400	203	Peak	4	5940.08	51.20	68.20	-17.00	38.16	34.08	12.76	34.82	1.02	400	203	Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																											
1	5854.99	48.28	110.83	-62.55	35.28	34.00	12.61	34.74	1.13	400	203	Peak																																																																									
2	5874.83	50.17	105.25	-55.08	37.19	34.00	12.64	34.76	1.10	400	203	Peak																																																																									
3	5923.50	50.42	69.31	-18.89	37.40	34.05	12.73	34.80	1.04	400	203	Peak																																																																									
4	5940.08	51.20	68.20	-17.00	38.16	34.08	12.76	34.82	1.02	400	203	Peak																																																																									



Mode	41																																																																																																																																																																																																
	Harmonic																																																																																																																																																																																																
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																																																																																																																																																
ANT	6																																																																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 3862.00</td><td>52.71</td><td>74.00</td><td>-21.29</td><td>44.35</td><td>30.72</td><td>10.30</td><td>33.44</td><td>0.78</td><td>100</td><td>297</td><td>Peak</td></tr><tr><td>2 3862.00</td><td>50.82</td><td>54.00</td><td>-3.18</td><td>42.46</td><td>30.72</td><td>10.30</td><td>33.44</td><td>0.78</td><td>100</td><td>297</td><td>Average</td></tr><tr><td>3 11590.00</td><td>52.21</td><td>74.00</td><td>-21.79</td><td>34.24</td><td>39.02</td><td>17.88</td><td>40.31</td><td>1.38</td><td>--</td><td>--</td><td>Peak</td></tr><tr><td>4 11590.00</td><td>42.53</td><td>54.00</td><td>-11.47</td><td>24.56</td><td>39.02</td><td>17.88</td><td>40.31</td><td>1.38</td><td>--</td><td>--</td><td>Average</td></tr><tr><td>5 17385.00</td><td>54.86</td><td>68.20</td><td>-13.34</td><td>36.99</td><td>40.47</td><td>22.11</td><td>46.63</td><td>1.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 3862.00	52.71	74.00	-21.29	44.35	30.72	10.30	33.44	0.78	100	297	Peak	2 3862.00	50.82	54.00	-3.18	42.46	30.72	10.30	33.44	0.78	100	297	Average	3 11590.00	52.21	74.00	-21.79	34.24	39.02	17.88	40.31	1.38	--	--	Peak	4 11590.00	42.53	54.00	-11.47	24.56	39.02	17.88	40.31	1.38	--	--	Average	5 17385.00	54.86	68.20	-13.34	36.99	40.47	22.11	46.63	1.92	--	--	Peak	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 3862.00</td><td>51.10</td><td>74.00</td><td>-22.90</td><td>42.74</td><td>30.72</td><td>10.30</td><td>33.44</td><td>0.78</td><td>307</td><td>255</td><td>Peak</td></tr><tr><td>2 3862.00</td><td>48.43</td><td>54.00</td><td>-5.57</td><td>40.07</td><td>30.72</td><td>10.30</td><td>33.44</td><td>0.78</td><td>307</td><td>255</td><td>Average</td></tr><tr><td>3 11590.00</td><td>54.26</td><td>74.00</td><td>-19.74</td><td>36.29</td><td>39.02</td><td>17.88</td><td>40.31</td><td>1.38</td><td>114</td><td>240</td><td>Peak</td></tr><tr><td>4 11590.00</td><td>44.54</td><td>54.00</td><td>-9.46</td><td>26.57</td><td>39.02</td><td>17.88</td><td>40.31</td><td>1.38</td><td>114</td><td>240</td><td>Average</td></tr><tr><td>5 17385.00</td><td>54.60</td><td>68.20</td><td>-13.60</td><td>36.73</td><td>40.47</td><td>22.11</td><td>46.63</td><td>1.92</td><td>--</td><td>--</td><td>Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1 3862.00	51.10	74.00	-22.90	42.74	30.72	10.30	33.44	0.78	307	255	Peak	2 3862.00	48.43	54.00	-5.57	40.07	30.72	10.30	33.44	0.78	307	255	Average	3 11590.00	54.26	74.00	-19.74	36.29	39.02	17.88	40.31	1.38	114	240	Peak	4 11590.00	44.54	54.00	-9.46	26.57	39.02	17.88	40.31	1.38	114	240	Average	5 17385.00	54.60	68.20	-13.60	36.73	40.47	22.11	46.63	1.92	--	--	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																							
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																								
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																							
1 3862.00	52.71	74.00	-21.29	44.35	30.72	10.30	33.44	0.78	100	297	Peak																																																																																																																																																																																						
2 3862.00	50.82	54.00	-3.18	42.46	30.72	10.30	33.44	0.78	100	297	Average																																																																																																																																																																																						
3 11590.00	52.21	74.00	-21.79	34.24	39.02	17.88	40.31	1.38	--	--	Peak																																																																																																																																																																																						
4 11590.00	42.53	54.00	-11.47	24.56	39.02	17.88	40.31	1.38	--	--	Average																																																																																																																																																																																						
5 17385.00	54.86	68.20	-13.34	36.99	40.47	22.11	46.63	1.92	--	--	Peak																																																																																																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																									
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																																																																																																							
1 3862.00	51.10	74.00	-22.90	42.74	30.72	10.30	33.44	0.78	307	255	Peak																																																																																																																																																																																						
2 3862.00	48.43	54.00	-5.57	40.07	30.72	10.30	33.44	0.78	307	255	Average																																																																																																																																																																																						
3 11590.00	54.26	74.00	-19.74	36.29	39.02	17.88	40.31	1.38	114	240	Peak																																																																																																																																																																																						
4 11590.00	44.54	54.00	-9.46	26.57	39.02	17.88	40.31	1.38	114	240	Average																																																																																																																																																																																						
5 17385.00	54.60	68.20	-13.60	36.73	40.47	22.11	46.63	1.92	--	--	Peak																																																																																																																																																																																						



Mode	41	
	Harmonic	
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz	
ANT	6	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL



Mode	42																																																																																																																																				
	Band Edge - L																																																																																																																																				
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz																																																																																																																																				
ANT	6																																																																																																																																				
Pol.	Horizontal						Fundamental																																																																																																																														
Peak	Level (dBuV/m) Date: 2026-06-10 PEAK_BE(B4)_16-24 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5628.70</td><td>52.99</td><td>68.20</td><td>-15.21</td><td>40.80</td><td>33.40</td><td>12.43</td><td>34.54</td><td>0.90</td><td>100</td><td>67 Peak</td></tr><tr><td>2</td><td>5658.05</td><td>51.14</td><td>68.24</td><td>-17.10</td><td>38.92</td><td>33.40</td><td>12.44</td><td>34.56</td><td>0.94</td><td>100</td><td>67 Peak</td></tr><tr><td>3</td><td>5705.88</td><td>68.36</td><td>106.85</td><td>-38.49</td><td>55.65</td><td>33.81</td><td>12.47</td><td>34.61</td><td>1.04</td><td>100</td><td>67 Peak</td></tr><tr><td>4</td><td>5728.05</td><td>70.77</td><td>110.91</td><td>-40.14</td><td>58.02</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>100</td><td>67 Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5628.70	52.99	68.20	-15.21	40.80	33.40	12.43	34.54	0.90	100	67 Peak	2	5658.05	51.14	68.24	-17.10	38.92	33.40	12.44	34.56	0.94	100	67 Peak	3	5705.88	68.36	106.85	-38.49	55.65	33.81	12.47	34.61	1.04	100	67 Peak	4	5728.05	70.77	110.91	-40.14	58.02	33.84	12.47	34.62	1.06	100	67 Peak	Level (dBuV/m) Date: 2026-06-10 PEAK(UNII) Site : 03CH22-HY Condition: PEAK(UNII)_3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>103.72</td><td>-----</td><td>-----</td><td>90.79</td><td>33.94</td><td>12.50</td><td>34.66</td><td>1.15</td><td>100</td><td>67 Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	103.72	-----	-----	90.79	33.94	12.50	34.66	1.15	100	67 Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5628.70	52.99	68.20	-15.21	40.80	33.40	12.43	34.54	0.90	100	67 Peak																																																																																																																										
2	5658.05	51.14	68.24	-17.10	38.92	33.40	12.44	34.56	0.94	100	67 Peak																																																																																																																										
3	5705.88	68.36	106.85	-38.49	55.65	33.81	12.47	34.61	1.04	100	67 Peak																																																																																																																										
4	5728.05	70.77	110.91	-40.14	58.02	33.84	12.47	34.62	1.06	100	67 Peak																																																																																																																										
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																												
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5775.00	103.72	-----	-----	90.79	33.94	12.50	34.66	1.15	100	67 Peak																																																																																																																										
Avg	Blank						Level (dBuV/m) Date: 2026-06-10 AVG_54 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:2.200kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>96.32</td><td>-----</td><td>-----</td><td>83.39</td><td>33.94</td><td>12.50</td><td>34.66</td><td>1.15</td><td>100</td><td>67 Average</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	96.32	-----	-----	83.39	33.94	12.50	34.66	1.15	100	67 Average																																																																															
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																											
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																													
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																											
1	5775.00	96.32	-----	-----	83.39	33.94	12.50	34.66	1.15	100	67 Average																																																																																																																										




Mode	42																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz																																																																							
ANT	6																																																																							
Pol.	Horizontal	Fundamental																																																																						
Peak	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th></th><th></th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1 5854.98</td><td>63.37</td><td>110.86</td><td>-47.49</td><td>50.37</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>100 67 Peak</td></tr><tr><td>2 5870.55</td><td>63.04</td><td>106.44</td><td>-43.40</td><td>50.05</td><td>34.00</td><td>12.63</td><td>34.75</td><td>1.11</td><td>100 67 Peak</td></tr><tr><td>3 5923.75</td><td>50.88</td><td>69.12</td><td>-18.24</td><td>37.06</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>100 67 Peak</td></tr><tr><td>4 5927.25</td><td>51.01</td><td>68.20</td><td>-17.19</td><td>38.00</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.03</td><td>100 67 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line Margin	Level	Factor	Loss	Factor				MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1 5854.98	63.37	110.86	-47.49	50.37	34.00	12.61	34.74	1.13	100 67 Peak	2 5870.55	63.04	106.44	-43.40	50.05	34.00	12.63	34.75	1.11	100 67 Peak	3 5923.75	50.88	69.12	-18.24	37.06	34.05	12.73	34.80	1.04	100 67 Peak	4 5927.25	51.01	68.20	-17.19	38.00	34.05	12.73	34.80	1.03	100 67 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line Margin	Level	Factor	Loss	Factor																																																																		
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																															
1 5854.98	63.37	110.86	-47.49	50.37	34.00	12.61	34.74	1.13	100 67 Peak																																																															
2 5870.55	63.04	106.44	-43.40	50.05	34.00	12.63	34.75	1.11	100 67 Peak																																																															
3 5923.75	50.88	69.12	-18.24	37.06	34.05	12.73	34.80	1.04	100 67 Peak																																																															
4 5927.25	51.01	68.20	-17.19	38.00	34.05	12.73	34.80	1.03	100 67 Peak																																																															



Mode	42																																																																																																																																										
	Band Edge - L																																																																																																																																										
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz																																																																																																																																										
ANT	6																																																																																																																																										
Pol.	Vertical						Fundamental																																																																																																																																				
Peak	Level (dBuV/m) Date: 2026-06-10 PEAK_BE(B4)_16-24 Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5610.68</td><td>50.10</td><td>68.20</td><td>-18.10</td><td>37.93</td><td>33.40</td><td>12.42</td><td>34.52</td><td>0.87</td><td>322</td><td>258</td><td>Peak</td></tr><tr><td>2</td><td>5650.40</td><td>49.65</td><td>68.50</td><td>-18.85</td><td>37.43</td><td>33.40</td><td>12.44</td><td>34.56</td><td>0.94</td><td>322</td><td>258</td><td>Peak</td></tr><tr><td>3</td><td>5719.18</td><td>65.48</td><td>110.57</td><td>-45.09</td><td>52.73</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>322</td><td>258</td><td>Peak</td></tr><tr><td>4</td><td>5720.05</td><td>64.78</td><td>110.91</td><td>-46.13</td><td>52.03</td><td>33.84</td><td>12.47</td><td>34.62</td><td>1.06</td><td>322</td><td>258</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5610.68	50.10	68.20	-18.10	37.93	33.40	12.42	34.52	0.87	322	258	Peak	2	5650.40	49.65	68.50	-18.85	37.43	33.40	12.44	34.56	0.94	322	258	Peak	3	5719.18	65.48	110.57	-45.09	52.73	33.84	12.47	34.62	1.06	322	258	Peak	4	5720.05	64.78	110.91	-46.13	52.03	33.84	12.47	34.62	1.06	322	258	Peak	Level (dBuV/m) Date: 2026-06-10 PEAK(UNII) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>98.32</td><td>-----</td><td>-----</td><td>85.39</td><td>33.94</td><td>12.50</td><td>34.66</td><td>1.15</td><td>322</td><td>258</td><td>Peak</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	98.32	-----	-----	85.39	33.94	12.50	34.66	1.15	322	258	Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5610.68	50.10	68.20	-18.10	37.93	33.40	12.42	34.52	0.87	322	258	Peak																																																																																																																															
2	5650.40	49.65	68.50	-18.85	37.43	33.40	12.44	34.56	0.94	322	258	Peak																																																																																																																															
3	5719.18	65.48	110.57	-45.09	52.73	33.84	12.47	34.62	1.06	322	258	Peak																																																																																																																															
4	5720.05	64.78	110.91	-46.13	52.03	33.84	12.47	34.62	1.06	322	258	Peak																																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																		
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	98.32	-----	-----	85.39	33.94	12.50	34.66	1.15	322	258	Peak																																																																																																																															
Avg	Blank						Level (dBuV/m) Date: 2026-06-10 AVG_54 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL : RBW:1000.000kHz VBW:2.200kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>5775.00</td><td>91.41</td><td>-----</td><td>-----</td><td>78.48</td><td>33.94</td><td>12.50</td><td>34.66</td><td>1.15</td><td>322</td><td>258</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	5775.00	91.41	-----	-----	78.48	33.94	12.50	34.66	1.15	322	258	Average																																																																																			
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																			
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																	
1	5775.00	91.41	-----	-----	78.48	33.94	12.50	34.66	1.15	322	258	Average																																																																																																																															



Mode	42																																																																							
	Band Edge - R																																																																							
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz																																																																							
ANT	6																																																																							
Pol.	Vertical	Fundamental																																																																						
Peak	Level (dBuV/m) Date: 2026-06-10  Site : 03CH22-HY Condition: PEAK_BE(B4)_16-24 3m DRH10-E_LE2C04A18EN_260520 VERTICAL RBW:1000.000kHz VBW:3000.000kHz SMT:Auto <table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1 5854.00</td><td>59.18</td><td>111.26</td><td>-52.08</td><td>46.18</td><td>34.00</td><td>12.61</td><td>34.74</td><td>1.13</td><td>322 250 Peak</td></tr><tr><td>2 5863.38</td><td>60.03</td><td>108.45</td><td>-48.42</td><td>47.04</td><td>34.00</td><td>12.62</td><td>34.75</td><td>1.12</td><td>322 250 Peak</td></tr><tr><td>3 5924.00</td><td>49.71</td><td>68.35</td><td>-18.64</td><td>36.69</td><td>34.05</td><td>12.73</td><td>34.80</td><td>1.04</td><td>322 250 Peak</td></tr><tr><td>4 5930.23</td><td>50.58</td><td>68.20</td><td>-17.62</td><td>37.56</td><td>34.06</td><td>12.74</td><td>34.81</td><td>1.03</td><td>322 250 Peak</td></tr></table>		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1 5854.00	59.18	111.26	-52.08	46.18	34.00	12.61	34.74	1.13	322 250 Peak	2 5863.38	60.03	108.45	-48.42	47.04	34.00	12.62	34.75	1.12	322 250 Peak	3 5924.00	49.71	68.35	-18.64	36.69	34.05	12.73	34.80	1.04	322 250 Peak	4 5930.23	50.58	68.20	-17.62	37.56	34.06	12.74	34.81	1.03	322 250 Peak	Blank
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																															
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																															
1 5854.00	59.18	111.26	-52.08	46.18	34.00	12.61	34.74	1.13	322 250 Peak																																																															
2 5863.38	60.03	108.45	-48.42	47.04	34.00	12.62	34.75	1.12	322 250 Peak																																																															
3 5924.00	49.71	68.35	-18.64	36.69	34.05	12.73	34.80	1.04	322 250 Peak																																																															
4 5930.23	50.58	68.20	-17.62	37.56	34.06	12.74	34.81	1.03	322 250 Peak																																																															





Mode	42																																																																																																																																																																																																
	Harmonic																																																																																																																																																																																																
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz																																																																																																																																																																																																
ANT	6																																																																																																																																																																																																
Pol.	Horizontal						Vertical																																																																																																																																																																																										
Peak Avg	Level (dBuV/m) Date: 2026-06-10 1000 4400 7800 11200 14600 18000 Frequency (MHz) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>3850.00</td><td>53.56</td><td>74.00</td><td>-20.44</td><td>45.23</td><td>30.70</td><td>10.29</td><td>33.44</td><td>0.78</td><td>100</td><td>297 Peak</td></tr><tr><td>2</td><td>3850.00</td><td>50.29</td><td>54.00</td><td>-3.71</td><td>41.96</td><td>30.70</td><td>10.29</td><td>33.44</td><td>0.78</td><td>100</td><td>297 Average</td></tr><tr><td>3</td><td>11550.00</td><td>51.00</td><td>74.00</td><td>-22.92</td><td>33.04</td><td>39.10</td><td>17.85</td><td>40.28</td><td>1.37</td><td>100</td><td>52 Peak</td></tr><tr><td>4</td><td>11550.00</td><td>42.31</td><td>54.00</td><td>-11.69</td><td>24.27</td><td>39.10</td><td>17.85</td><td>40.28</td><td>1.37</td><td>100</td><td>52 Average</td></tr><tr><td>5</td><td>17325.00</td><td>55.04</td><td>68.20</td><td>-13.16</td><td>37.25</td><td>40.40</td><td>22.05</td><td>46.58</td><td>1.92</td><td>--</td><td>-- Peak</td></tr></tbody></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3850.00	53.56	74.00	-20.44	45.23	30.70	10.29	33.44	0.78	100	297 Peak	2	3850.00	50.29	54.00	-3.71	41.96	30.70	10.29	33.44	0.78	100	297 Average	3	11550.00	51.00	74.00	-22.92	33.04	39.10	17.85	40.28	1.37	100	52 Peak	4	11550.00	42.31	54.00	-11.69	24.27	39.10	17.85	40.28	1.37	100	52 Average	5	17325.00	55.04	68.20	-13.16	37.25	40.40	22.05	46.58	1.92	--	-- Peak	Level (dBuV/m) Date: 2026-06-10 1000 4400 7800 11200 14600 18000 Frequency (MHz) Site : 03CH22-HY Condition: PEAK(UNII) 3m DRH18-E_LE2C04A18EN_260520 VERTICAL <table><thead><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr></thead><tbody><tr><td>1</td><td>3850.00</td><td>51.74</td><td>74.00</td><td>-22.26</td><td>43.41</td><td>30.70</td><td>10.29</td><td>33.44</td><td>0.78</td><td>320</td><td>258 Peak</td></tr><tr><td>2</td><td>3850.00</td><td>47.33</td><td>54.00</td><td>-6.67</td><td>39.00</td><td>30.70</td><td>10.29</td><td>33.44</td><td>0.78</td><td>320</td><td>258 Average</td></tr><tr><td>3</td><td>11550.00</td><td>51.00</td><td>74.00</td><td>-22.40</td><td>33.56</td><td>39.10</td><td>17.85</td><td>40.28</td><td>1.37</td><td>100</td><td>240 Peak</td></tr><tr><td>4</td><td>11550.00</td><td>43.12</td><td>54.00</td><td>-10.88</td><td>25.08</td><td>39.10</td><td>17.85</td><td>40.28</td><td>1.37</td><td>100</td><td>240 Average</td></tr><tr><td>5</td><td>17325.00</td><td>54.99</td><td>68.20</td><td>-13.21</td><td>37.20</td><td>40.40</td><td>22.05</td><td>46.58</td><td>1.92</td><td>--</td><td>-- Peak</td></tr></tbody></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	3850.00	51.74	74.00	-22.26	43.41	30.70	10.29	33.44	0.78	320	258 Peak	2	3850.00	47.33	54.00	-6.67	39.00	30.70	10.29	33.44	0.78	320	258 Average	3	11550.00	51.00	74.00	-22.40	33.56	39.10	17.85	40.28	1.37	100	240 Peak	4	11550.00	43.12	54.00	-10.88	25.08	39.10	17.85	40.28	1.37	100	240 Average	5	17325.00	54.99	68.20	-13.21	37.20	40.40	22.05	46.58	1.92	--	-- Peak
		Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																							
	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																								
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																							
1	3850.00	53.56	74.00	-20.44	45.23	30.70	10.29	33.44	0.78	100	297 Peak																																																																																																																																																																																						
2	3850.00	50.29	54.00	-3.71	41.96	30.70	10.29	33.44	0.78	100	297 Average																																																																																																																																																																																						
3	11550.00	51.00	74.00	-22.92	33.04	39.10	17.85	40.28	1.37	100	52 Peak																																																																																																																																																																																						
4	11550.00	42.31	54.00	-11.69	24.27	39.10	17.85	40.28	1.37	100	52 Average																																																																																																																																																																																						
5	17325.00	55.04	68.20	-13.16	37.25	40.40	22.05	46.58	1.92	--	-- Peak																																																																																																																																																																																						
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																								
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																									
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																																																																																							
1	3850.00	51.74	74.00	-22.26	43.41	30.70	10.29	33.44	0.78	320	258 Peak																																																																																																																																																																																						
2	3850.00	47.33	54.00	-6.67	39.00	30.70	10.29	33.44	0.78	320	258 Average																																																																																																																																																																																						
3	11550.00	51.00	74.00	-22.40	33.56	39.10	17.85	40.28	1.37	100	240 Peak																																																																																																																																																																																						
4	11550.00	43.12	54.00	-10.88	25.08	39.10	17.85	40.28	1.37	100	240 Average																																																																																																																																																																																						
5	17325.00	54.99	68.20	-13.21	37.20	40.40	22.05	46.58	1.92	--	-- Peak																																																																																																																																																																																						





Mode	42	
	Harmonic	
	U-NII-3_5.725-5.85_802.11ac VHT80_CH155_5775MHz	
ANT	6	
Pol.	Horizontal	Vertical
10.6G ~18G Avg	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 HORIZONTAL	Level (dBuV/m) Date: 2026-06-10 Site : 03CH22-HY Condition: AVG_54 3m DRH18-E_LE2C04A18EN_260520 VERTICAL



Mode	44																																																																																																																																																																																												
	LF																																																																																																																																																																																												
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																																																																																																																																												
ANT	6																																																																																																																																																																																												
Pol.	Horizontal					Vertical																																																																																																																																																																																							
QPI Peak																																																																																																																																																																																													
	Site : 03CH22-HY Condition: QP 3m Bilog_63304_251126 HORIZONTAL					Site : 03CH22-HY Condition: QP 3m Bilog_63304_251126 VERTICAL																																																																																																																																																																																							
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>87.23</td><td>26.33</td><td>40.00</td><td>-13.67</td><td>43.03</td><td>14.30</td><td>1.50</td><td>32.56</td><td>0.06 -- -- Peak</td></tr><tr><td>2</td><td>98.14</td><td>29.25</td><td>43.50</td><td>-14.25</td><td>45.59</td><td>14.62</td><td>1.53</td><td>32.55</td><td>0.06 -- -- Peak</td></tr><tr><td>3</td><td>272.58</td><td>23.04</td><td>46.00</td><td>-22.96</td><td>34.06</td><td>18.69</td><td>2.72</td><td>32.51</td><td>0.08 -- -- Peak</td></tr><tr><td>4</td><td>345.25</td><td>28.64</td><td>46.00</td><td>-17.36</td><td>37.74</td><td>20.28</td><td>3.08</td><td>32.54</td><td>0.08 -- -- Peak</td></tr><tr><td>5</td><td>741.98</td><td>38.88</td><td>46.00</td><td>-7.12</td><td>38.83</td><td>27.91</td><td>4.49</td><td>32.52</td><td>0.17 -- -- Peak</td></tr><tr><td>6</td><td>951.58</td><td>33.14</td><td>46.00</td><td>-12.86</td><td>28.34</td><td>30.67</td><td>5.10</td><td>31.20</td><td>0.23 -- -- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	87.23	26.33	40.00	-13.67	43.03	14.30	1.50	32.56	0.06 -- -- Peak	2	98.14	29.25	43.50	-14.25	45.59	14.62	1.53	32.55	0.06 -- -- Peak	3	272.58	23.04	46.00	-22.96	34.06	18.69	2.72	32.51	0.08 -- -- Peak	4	345.25	28.64	46.00	-17.36	37.74	20.28	3.08	32.54	0.08 -- -- Peak	5	741.98	38.88	46.00	-7.12	38.83	27.91	4.49	32.52	0.17 -- -- Peak	6	951.58	33.14	46.00	-12.86	28.34	30.67	5.10	31.20	0.23 -- -- Peak	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm deg</th></tr><tr><td>1</td><td>32.91</td><td>30.58</td><td>40.00</td><td>-9.42</td><td>39.29</td><td>22.95</td><td>0.88</td><td>32.57</td><td>0.03 100 51 QP</td></tr><tr><td>2</td><td>88.20</td><td>31.05</td><td>43.50</td><td>-12.45</td><td>47.65</td><td>14.38</td><td>1.51</td><td>32.55</td><td>0.06 -- -- Peak</td></tr><tr><td>3</td><td>269.59</td><td>21.79</td><td>46.00</td><td>-24.21</td><td>32.56</td><td>18.96</td><td>2.70</td><td>32.51</td><td>0.08 -- -- Peak</td></tr><tr><td>4</td><td>341.37</td><td>28.87</td><td>46.00</td><td>-17.13</td><td>38.16</td><td>20.11</td><td>3.06</td><td>32.54</td><td>0.08 -- -- Peak</td></tr><tr><td>5</td><td>741.98</td><td>38.13</td><td>46.00</td><td>-7.87</td><td>38.08</td><td>27.91</td><td>4.49</td><td>32.52</td><td>0.17 -- -- Peak</td></tr><tr><td>6</td><td>957.32</td><td>32.89</td><td>46.00</td><td>-13.11</td><td>27.79</td><td>30.89</td><td>5.11</td><td>31.14</td><td>0.24 -- -- Peak</td></tr></table>						Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor		MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg	1	32.91	30.58	40.00	-9.42	39.29	22.95	0.88	32.57	0.03 100 51 QP	2	88.20	31.05	43.50	-12.45	47.65	14.38	1.51	32.55	0.06 -- -- Peak	3	269.59	21.79	46.00	-24.21	32.56	18.96	2.70	32.51	0.08 -- -- Peak	4	341.37	28.87	46.00	-17.13	38.16	20.11	3.06	32.54	0.08 -- -- Peak	5	741.98	38.13	46.00	-7.87	38.08	27.91	4.49	32.52	0.17 -- -- Peak	6	957.32	32.89	46.00	-13.11	27.79	30.89	5.11	31.14
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																				
1	87.23	26.33	40.00	-13.67	43.03	14.30	1.50	32.56	0.06 -- -- Peak																																																																																																																																																																																				
2	98.14	29.25	43.50	-14.25	45.59	14.62	1.53	32.55	0.06 -- -- Peak																																																																																																																																																																																				
3	272.58	23.04	46.00	-22.96	34.06	18.69	2.72	32.51	0.08 -- -- Peak																																																																																																																																																																																				
4	345.25	28.64	46.00	-17.36	37.74	20.28	3.08	32.54	0.08 -- -- Peak																																																																																																																																																																																				
5	741.98	38.88	46.00	-7.12	38.83	27.91	4.49	32.52	0.17 -- -- Peak																																																																																																																																																																																				
6	951.58	33.14	46.00	-12.86	28.34	30.67	5.10	31.20	0.23 -- -- Peak																																																																																																																																																																																				
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																																																																																				
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																																																																																					
MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm deg																																																																																																																																																																																				
1	32.91	30.58	40.00	-9.42	39.29	22.95	0.88	32.57	0.03 100 51 QP																																																																																																																																																																																				
2	88.20	31.05	43.50	-12.45	47.65	14.38	1.51	32.55	0.06 -- -- Peak																																																																																																																																																																																				
3	269.59	21.79	46.00	-24.21	32.56	18.96	2.70	32.51	0.08 -- -- Peak																																																																																																																																																																																				
4	341.37	28.87	46.00	-17.13	38.16	20.11	3.06	32.54	0.08 -- -- Peak																																																																																																																																																																																				
5	741.98	38.13	46.00	-7.87	38.08	27.91	4.49	32.52	0.17 -- -- Peak																																																																																																																																																																																				
6	957.32	32.89	46.00	-13.11	27.79	30.89	5.11	31.14	0.24 -- -- Peak																																																																																																																																																																																				



Mode	46																																																																																																																									
	SHF																																																																																																																									
	U-NII-3_5.725-5.85_802.11n HT40_CH159_5795MHz																																																																																																																									
ANT	6																																																																																																																									
Pol.	Horizontal						Vertical																																																																																																																			
Peak																																																																																																																										
	Site : 03CH22-HY Condition: PEAK(UNII) 1m BBHA9170_1225_250702 HORIZONTAL						Site : 03CH22-HY Condition: PEAK(UNII) 1m BBHA9170_1225_250702 VERTICAL																																																																																																																			
	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>39534.99</td><td>50.47</td><td>74.00</td><td>-23.53</td><td>41.48</td><td>46.00</td><td>34.56</td><td>62.03</td><td>-9.54</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>39534.99</td><td>40.50</td><td>54.00</td><td>-13.50</td><td>31.51</td><td>46.00</td><td>34.56</td><td>62.03</td><td>-9.54</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg	1	39534.99	50.47	74.00	-23.53	41.48	46.00	34.56	62.03	-9.54	--	PEAK	2	39534.99	40.50	54.00	-13.50	31.51	46.00	34.56	62.03	-9.54	--	Average	<table><tr><th></th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line</th><th>Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr><tr><td>1</td><td>39088.25</td><td>48.72</td><td>74.00</td><td>-25.28</td><td>40.66</td><td>45.17</td><td>34.74</td><td>62.31</td><td>-9.54</td><td>--</td><td>PEAK</td></tr><tr><td>2</td><td>39088.25</td><td>38.94</td><td>54.00</td><td>-15.06</td><td>30.88</td><td>45.17</td><td>34.74</td><td>62.31</td><td>-9.54</td><td>--</td><td>Average</td></tr></table>							Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark	Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor			MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg	1	39088.25	48.72	74.00	-25.28	40.66	45.17	34.74	62.31	-9.54	--	PEAK	2	39088.25	38.94	54.00	-15.06	30.88	45.17	34.74	62.31	-9.54	--
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	cm	deg																																																																																																																
1	39534.99	50.47	74.00	-23.53	41.48	46.00	34.56	62.03	-9.54	--	PEAK																																																																																																															
2	39534.99	40.50	54.00	-13.50	31.51	46.00	34.56	62.03	-9.54	--	Average																																																																																																															
	Limit	Read	Ant	Cable	Preamp	Aux	APos	TPos	Remark																																																																																																																	
Freq	Level	Line	Margin	Level	Factor	Loss	Factor	Factor																																																																																																																		
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB/m	dB	dB	dB	cm	deg																																																																																																															
1	39088.25	48.72	74.00	-25.28	40.66	45.17	34.74	62.31	-9.54	--	PEAK																																																																																																															
2	39088.25	38.94	54.00	-15.06	30.88	45.17	34.74	62.31	-9.54	--	Average																																																																																																															



Appendix D. Duty Cycle Plots

Band	Duty Cycle (%)	T(us)	1/T(kHz)	VBW Setting
802.11a	98.10	-	-	10Hz
5GHz 802.11n HT20	98.62	-	-	10Hz
5GHz 802.11n HT40	96.34	948	1.05	1.1KHz
5GHz 802.11ac VHT80	92.80	464	2.16	2.2kHz

