Portable Cellular Phone SAR Test Report

Test Report #:	18936-1F
Date of Report:	12-Sep-2006
Date of Test:	29-Aug-2006 thorough 08-Sep-2006
FCC ID #:	**IHDT56GB1**
Generic Name:	**MQ4-4411H31**
Laboratory:	Motorola Mobile Devices Business Product Safety & Compliance Laboratory 11th Floor, Hibrand Living Hall, 215, Yangae-Dong, Seocho-Gu, Seoul, South Korea, 137-130
Report Author:	Jon Park Senior Staff Engineer

Accreditation:

This laboratory is accredited to ISO/IEC 17025-1999 to perform the following tests:

Tests:	Procedures:
Electromagnetic Specific Absorption Rate	ANSI / IEEE C95.1-1992, 1999 (SAR) IEEE C95.3-1991 IEEE 1528, IEC 62209-1 FCC OET Bulletin 65 (*including Supplements A, B, C*) Australian Communications Authority Radio Communications (Electromagnetic Radiation – Human Exposure) Standard 2003 CENELEC EN 50361 (2001)
Simulated Tissue Preparation	WI-0247
RF Power Measurement	WI-1847

On the following products or types of products:
Wireless Communications Devices (Examples): Two Way Radios; Portable Phones (including Cellular, Licensed Non-Broadcast and PCS); Low Frequency Readers; and Pagers

A2LA certificate #1651-02

Statement of Compliance:

Motorola declares under its sole responsibility that the portable cellular telephone model to which this declaration relates, is in conformity with the appropriate General Population/Uncontrolled RF exposure standards, recommendations and guidelines (FCC 47 CFR §2.1093) as well as with CENELEC en50360:2001 and ANSI / IEEE C95.1. It also declares that the product was tested in accordance with CENELEC en50361:2001, IEEE 1528, as well as other appropriate measurement standards, guidelines and recommended practices. Any deviations from these standards, guidelines and recommended practices are noted below:

(none)

©Motorola, Inc. 2006
This test report shall not be reproduced except in full, without written approval of the laboratory.

The results and statements contained herein relate only to the items tested. The names of individuals involved may be mentioned only in connection with the statements or results from this report.

Motorola encourages all feedback, both positive and negative, on this test report.

Table of Contents

1. Introduction **2**

2. Description of the Device Under Test **2**

2.1 Antenna description *2*

2.2 Device description *2*

3. Test Equipment Used **3**

3.1 Dosimetric System *3*

3.2 Additional Equipment *3*

4. Electrical parameters of the tissue simulating liquid **4**

5. System Accuracy Verification **5**

6. Test Results **6**

6.1 Head Adjacent Test Results *6*

6.2 Body Worn Test Results *11*

References **15**

Appendix 1: SAR distribution comparison for system accuracy verification **16**

Appendix 2: SAR distribution plots for Phantom Head Adjacent Use **17**

Appendix 3: SAR distribution plots for Body Worn Configuration **18**

Appendix 4: Probe Calibration Certificate **19**

Appendix 5: Measurement Uncertainty Budget **20**

Appendix 6: Photographs of the device under test **22**

Appendix 7: Dipole Characterization Certificate **26**

1. Introduction

The Motorola Mobile Devices Business Product Safety Laboratory has performed measurements of the maximum potential exposure to the user of the portable cellular phone covered by this test report. The Specific Absorption Rate (SAR) of this product was measured. The portable cellular phone was tested in accordance with [1], [4] and [5]. The SAR values measured for the portable cellular phone are below the maximum recommended levels of 1.6 W/kg in a 1g average set in [3] and 2.0W/kg in a 10g average set in [2].

2. Description of the Device Under Test

2.1 Antenna description

Type	Internal Antenna	
Location	Bottom of the transceiver	
Dimensions	Length	40.2 mm
	Width	6.95 mm
Configuration	FJA	

2.2 Device description

Serial number	**TA489002DI**													
Mode(s) of Operation	GSM 850	GSM 900	GSM 1800	GSM 1900	GPRS 850	GPRS 900	GPRS 1800	GPRS 1900	EDGE 850	EDGE 900	EDGE 1800	EDGE 1900	Blue Tooth	WiFi 802.11 b
Modulation Mode(s)	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	GMSK	8PSK	8PSK	8PSK	8PSK	GFSK	FDMS
Maximum Output Power Setting	33.50 dBm	33.50 dBm	31.00 dBm	31.00 dBm	33.50 dBm	33.50 dBm	31.00 dBm	31.00 dBm	28.00 dBm	28.00 dBm	27.00 dBm	27.00 dBm	4.00 dBm	15.00 dBm
Duty Cycle	1:8	1:8	1:8	1:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	2:8	1:1	1:1
Transmitting Frequency Rang(s)	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2 – 1909.8 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2 – 1909.8 MHz	824.2-848.8 MHz	880.2-914.8 MHz	1710.2-1784.8 MHz	1850.2-1909.8 MHz	2400 - 2483.5 MHz	2412 – 2472 Mhz
Production Unit or Identical Prototype (47 CFR §2..908)	Identical Prototype													
Device Category	Portable													
RF Exposure Limits	General Population / Uncontrolled													

3. Test Equipment Used

3.1 Dosimetric System

The Motorola Mobile Devices Business Product Safety & Compliance Laboratory utilizes a Dosimetric Assessment System (Dasy4™ v4.7) manufactured by Schmid & Partner Engineering AG (SPEAG™), of Zurich Switzerland. All the SAR measurements are taken within a shielded enclosure. The overall 10g RSS uncertainty of the measurement system is ±10.8% (K=1) with an expanded uncertainty of ±21.6% (K=2). The overall 1g RSS uncertainty of the measurement system is ±11.1% (K=1) with an expanded uncertainty of ±22.2% (K=2). The measurement uncertainty budget is given in Appendix 6. Per IEEE 1528, this uncertainty budget is applicable to the SAR range of 0.4W/kg to 10W/kg.

The list of calibrated equipment used for the measurements is shown in the following table.

Description	Serial Number	Cal Due Date
DASY4™ DAE V1	385	21-Mar-2007
E-Field Probe ETDV6	1501	23-Mar-2007
Dipole Validation Kit, DV900V2	077	22-May-2007
S.A.M. Phantom used for 800/900MHz	TP-1155	
Dipole Validation Kit, DV1800V2	280tr	
S.A.M. Phantom used for 1800/1900/2450MHz	TP-1086	
Dipole Validation Kit, DV2450V2	767	22-May-2007

3.2 Additional Equipment

Description	Serial Number	Cal Due Date
Signal Generator HP8648C	3847A04630	02-Mar-2007
Power Meter E4419B	US39250623	24-May-2007
Power Sensor #1 - 8481A	3318A86935	23-May-2007
Power Sensor #2 - 8481A	US37296472	23-May-2007
Network Analyzer HP8753ES	US39172714	07-Mar-2007
Dielectric Probe Kit HP85070C	US99360207	

4. Electrical parameters of the tissue simulating liquid

Prior to conducting SAR measurements, the relative permittivity, ε_r, and the conductivity, σ, of the tissue simulating liquids were measured with a HP85070 Dielectric Probe Kit These values, along with the temperature of the simulated tissue are shown in the table below. The recommended limits for permittivity and conductivity are also shown. A mass density of ρ=1g/cm3 was entered into the system in all the cases. It can be seen that the measured parameters are within tolerance of the recommended limits specified in [1] and [5].

f (MHz)	Tissue type	Limits / Measured	Dielectric Parameters		
			ε_r	σ (S/m)	Temp (°C)
835	Head	**Measured,** 04-Sep-2006	42.2	0.91	20.3
		Measured, 08-Sep-2006	41.5	0.91	21.2
		Recommended Limits	41.5 ±5%	0.90 ±5%	18-25
	Body	**Measured,** 29-Aug-2006	54.5	0.95	21.3
		Recommended Limits	55.2 ±5%	0.97 ±5%	18-25
1880	Head	**Measured,** 31-Aug-2006	39.3	1.43	20.5
		Recommended Limits	40.0 ±5%	1.40 ±5%	18-25
	Body	**Measured,** 31-Aug-2006	50.9	1.57	21.5
		Recommended Limits	53.3 ±5%	1.52 ±5%	18-25
2450	Head	**Measured,** 06-Sep-2006	37.6	1.87	20.9
		Recommended Limits	39.2 ±5%	1.80 ±5%	18-25
	Body	**Measured,** 07-Sep-2006	52.9	2.03	21.0
		Recommended Limits	52.7 ±5%	1.95 ±5%	18-25

The list of ingredients and the percent composition used for the tissue simulates are indicated in the table below.

Ingredient	835MHz / 900 MHz Head	835MHz / 900 MHz Body	1800MHz / 1900 MHz Head	1800 MHz / 1900 MHz Body	2450MHz Head	2450 MHz Body
Sugar	57	44.9	--	--	--	--
DGBE	--	--	47	30.8	--	30
Diacetin	--	--	--	--	51	
Water	40.45	53.06	52.62	68.8	48.75	70
Salt	1.45	0.94	0.38	0.4	0.15	--
HEC	1	1	--	--	--	--
Bact.	0.1	0.1	--	--	0.1	--

5. System Accuracy Verification

A system accuracy verification of the DASY4™ was performed using the measurement equipment listed in Section 3.1. The daily system accuracy verification occurs within the flat section of the SAM phantom.

A SAR measurement was performed to verify the measured SAR was within ±10% from the target SAR indicated in Section 8.3.7 Reference SAR Values in [5] or Appendix 7 for the 900Mhz and 2450Mhz target reference SAR value. These tests were done at 900MHz, 1800MHz, and 2450Mhz. These frequencies are within ±10% of the compliance test mid-band frequency as required in [1] and [5]. The test was conducted on the same days as the measurement of the DUT. Recommended limits for permittivity and conductivity, specified in [5], are shown in the table below. The obtained results from the system accuracy verification are also displayed in the table below. SAR values are normalized to 1W forward power delivered to the dipole. It is seen that the system is operating within its specification, as the results are within acceptable tolerance of the reference values. The distributions of SAR compare well with those of the reference measurements (see Appendix 1). The tissue stimulant depth was verified to be 15.0cm ±0.5cm. Z-axis scans showing the SAR penetration are also included in Appendix 1.

f (MHz)	Description	SAR (W/kg), 1gram	Dielectric Parameters		Ambient Temp (°C)	Tissue Temp (°C)
			ε_r	σ (S/m)		
900	**Measured,** 29-Aug-2006	10.93	40.7	0.96	20.9	21.4
	Measured, 04-Sep-2006	10.9	41.5	0.97	20.7	21.5
	Measured, 08-Sep-2006	11.08	40.8	0.97	20.8	21.2
	Recommended Limits	11.3	41.5 ±5%	0.97 ±5%	18-25	18-25
1800	**Measured,** 31-Aug-2006	36.18	39.1	1.35	21.5	20.9
	Recommended Limits	38.1	40.0 ±5%	1.4 ±5%	18-25	18-25
2450	**Measured,** 05-Sep-2006	53.00	37.6	1.87	21.2	21.1
	Measured, 06-Sep-2006	55.30	38.1	1.87	21.2	20.9
	Recommended Limits	58.0	39.2 ±5%	1.80 ±5%	18-25	18-25

The following probe conversion factors were used on the E-Field probe(s) used for the system accuracy verification measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1501	900	6.02	8 of 9
		1810	4.86	8 of 9
		2450	4.10	8 of 9

6. Test Results

The test sample was operated using an actual transmission through a base station simulator. The base station simulator was setup to the proper channel, transmitter power level and transmit mode of operation. The phone was tested in the configurations stipulated in [1], [4] and [5]. The phone was positioned into these configurations using the device holder supplied with the DASY4™ SAR measurement system The measured dielectric constant of the material used for the device holder is less than 2.9 and the loss tangent is less than 0.02 (± 30%) at 850MHz. The default settings for the "coarse" and "cube" scans were chosen and used for measurements. The grid spacing of the course scan was set to 15cm as shown in the SAR plots included in Appendix 2 and 3. Please refer to the DASY manual for additional information on SAR scanning procedures and algorithms used.

The Cellular Phone model covered by this report has the following battery options:
Model #SNN5744A - 1000mAH Battery
Model #SNN5766A – 810mAH Battery

The battery with the highest capacity is the Model#SNN5744A 1000mAH Battery. This battery was used to do most of the SAR testing. The phone was placed in the SAR measurement system with a fully charged battery. The configuration that resulted in the highest SAR values were tested using the other batteries listed above.

6.1 Head Adjacent Test Results

The SAR results shown in tables 1 through 6 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output powers, the temperature of the simulated tissue after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is New SAR = Old SAR * 10^(-drift/10). The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. Note that 800MHz digital mode SAR measurements were performed in accordance with [4].

The left head and right head SAR contour distributions are similar. Because of this similarity, the cheek/touch and 15° tilt test conditions with the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 2. All other test conditions measured lower SAR values than those included in Appendix 2.

The SAR measurements were performed using the SAM phantoms listed in section 3.1. Since the same phantoms and simulated tissue were used for the system accuracy verification and the device SAR measurements, the Z-axis scans included in Appendix 1 are applicable for verification of simulated tissue depth to be 15.0cm ±0.5cm.

The following probe conversion factors were used on the E-Field probe(s) used for the head adjacent measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1501	900	6.02	8 of 9
		1810	4.86	8 of 9
		2450	4.10	8 of 9

Left Head Cheek Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	21.4	0.01	0.276	0.28	0.388	0.39
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	20.8	-0.08	0.144	0.15	0.217	0.22
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	20.6	0.20	0.0216	0.02	0.0371	0.04
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.30		0.43
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.17		026

Table 1: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

Right Head Cheek Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	**21.2**	**-0.04**	**0.315**	**0.32**	**0.463**	**0.47**
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	**20.5**	**0.03**	**0.15**	**0.15**	**0.239**	**0.24**
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	**20.9**	**-0.04**	**0.0187**	**0.02**	**0.0358**	**0.04**
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.34		**0.51**
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.17		**0.28**

Table 2: SAR measurement results at the highest possible output power, measured in a head cheek position against the ICNIRP and ANSI SAR Limit.

The Highest Head Cheek Position with SNN5766A Battery								
f **(MHz)**	**Description**	**Conducted Output Power (dBm)**	**Temp (°C)**	**Drift (dB)**	***10g SAR value***		***1g SAR value***	
					Measured (W/kg)	**Extrapolated (W/kg)**	**Measured (W/kg)**	**Extrapolated (W/kg)**
GSM 850MHz	**Channel 128**	33.50						
	Channel 190	33.50	20.9	-0.08	0.30	0.31	0.438	0.45
	Channel 251	33.51						
GSM 1900MHz	**Channel 512**	30.97						
	Channel 661	30.92	20.7	0.00	0.127	0.13	0.198	0.20
	Channel 810	30.98						
WiFi 2450MHz	**Channel 1**	15.00						
	Channel 6	15.00	20.5	-0.44	0.0181	0.02	0.0342	0.04
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.33		0.49
GSM 1900MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.15		0.24

Table 3: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

Left Head 15° Tilt Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	21.4	0.00	0.14	0.14	0.183	0.18
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	**21.7**	**0.04**	**0.0436**	**0.04**	**0.07**	**0.07**
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	**21.1**	**-0.14**	**0.00578**	**0.01**	**0.0109**	**0.01**
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.15		0.19
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.05		**0.08**

Table 4: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

Right Head 15° Tilt Position								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	21.4	0.00	0.151	0.15	0.197	0.20
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	20.5	0.06	0.0312	0.03	0.0515	0.05
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	20.6	-0.37	0.00144	0.00	0.00592	0.01
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.15		0.21
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.03		0.06

Table 5: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

The Highest Head 15° Tilt Position with SNN5766A Battery								
f **(MHz)**	**Description**	**Conducted Output Power (dBm)**	**Temp (°C)**	**Drift (dB)**	***10g SAR value***		***1g SAR value***	
					Measured (W/kg)	**Extrapolated (W/kg)**	**Measured (W/kg)**	**Extrapolated (W/kg)**
GSM 850MHz	**Channel 128**	33.50						
	Channel 190	33.50	**20.3**	**0.00**	**0.168**	**0.17**	**0.22**	**0.22**
	Channel 251	33.51						
GSM 1900MHz	**Channel 512**	30.97						
	Channel 661	30.92	20.9	-0.04	0.0431	0.04	0.0689	0.07
	Channel 810	30.98						
WiFi 2450MHz	**Channel 1**	15.00						
	Channel 6	15.00	21.4	0.10	0.00412	0.00	0.0148	0.01
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.17		**0.23**
GSM 1900MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.04		0.08

Table 6: SAR measurement results at the highest possible output power, measured in a head 15° Tilt position against the ICNIRP and ANSI SAR Limit.

6.2 Body Worn Test Results

The SAR results shown in tables 7 through 12 are maximum SAR values averaged over 1 gram of phantom tissue, to demonstrate compliance to [3] and also over 10 grams of phantom tissue, to demonstrate compliance to the [6]. Also shown are the measured conducted output powers, the temperature of the test facility during the test, the temperature of the tissue simulate after the test, the measured drift and the extrapolated SAR. The exact method of extrapolation is New SAR = Old SAR * 10^(-drift/10). The SAR reported at the end of the measurement process by the DASY4™ measurement system can be scaled up by the measured drift to determine the SAR at the beginning of the measurement process. This is the most conservative SAR because it corresponds to the average output power at the beginning of the SAR test. This extrapolation has been done because when the DUT is operating properly it may exhibit a slump in radiated power and SAR over time. This is verified by measuring the SAR drift after the test. Note that 800MHz digital mode SAR measurements were performed in accordance with [4].

The test conditions that produced the highest SAR values in each band are indicated as bold numbers in the following tables and are included in Appendix 3. All other test conditions measured lower SAR values than those included in Appendix 3.

A “flat” phantom was for the body-worn tests. This “flat” phantom is made out of 1” thick natural High Density Polyethylene with a thickness at the bottom equal to 2.0mm. It measures 52.7cm(long) x 26.7cm(wide) x 21.2cm(tall). The measured dielectric constant of the material used is less than 2.3 and the loss tangent is less than 0.0046 all the way up to 2.184GHz.

The tissue stimulant depth was verified to be 15.0cm ±0.5cm. The same device holder described in section 6 was used for positioning the phone. The functional accessories were divided into two categories, the ones with metal components and the ones with non-metal components. For non-metallic component accessories’, testing was performed on the accessory that displayed the closest proximity to the flat phantom. Each metallic component accessory, if any, was checked for uniqueness of metal component so that each is tested with the device. If multiple accessories shared an identical metal component, only the accessory that dictates the closest spacing to the body was tested. In addition to accessory testing, the cellular phone was tested with the front and back of the phone facing the phantom. For voice mode operation, the phone was placed as a distance of 15mm from the phantom. For data mode operation, the phone was placed as a distance of 25mm from the phantom. The cellular phone was tested with a headset connected to the device for all body-worn SAR measurements.

There are no Body-Worn Accessories available for this phone at the time of testing hence the device was tested per the supplement C testing guidelines for devices that do not have body worn accessories. The phone was placed a maximum of 25mm away from a flat phantom per the supplement C standard guidelines to perform SAR measurement.

The following probe conversion factors were used on the E-Field probe(s) used for the body worn measurements:

Description	Serial Number	f (MHz)	Conversion Factor	Cal Cert pg #
E-Field Probe ET3DV6	SN1501	900	5.64	8 of 9
		1810	4.36	8 of 9
		2450	3.73	8 of 9

Body-Worn; Front of Phone 15mm from Phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	21.4	-0.01	0.0625	0.06	0.0842	0.08
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	21.6	0.00	0.042	0.04	0.0643	0.06
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	20.2	-0.09	0.00019	0.00	0.00063	0.00
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.06		0.08
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.04		0.06

Table 7: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

Body-Worn; Back of Phone 15mm from Phantom								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	21.4	-0.02	0.143	0.14	0.202	0.20
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	**21.5**	**-0.03**	**0.108**	**0.11**	**0.166**	**0.17**
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	**21.0**	**-0.20**	**0.00854**	**0.01**	**0.0214**	**0.02**
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.15		0.22
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.12		**0.19**

Table 8: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

Body-Worn; Back of Phone 15mm from Phantom with Enabled Bluetooth								
f **(MHz)**	**Description**	**Conducted Output Power (dBm)**	**Temp (°C)**	**Drift (dB)**	***10g SAR value***		***1g SAR value***	
					Measured (W/kg)	**Extrapolated (W/kg)**	**Measured (W/kg)**	**Extrapolated (W/kg)**
GSM 850MHz	**Channel 128**	33.50						
	Channel 190	33.50	**21.3**	**-0.04**	**0.144**	**0.15**	**0.203**	**0.20**
	Channel 251	33.51						
GSM 1900MHz	**Channel 512**	30.97						
	Channel 661	30.92	21.2	-0.07	0.101	0.10	0.156	0.16
	Channel 810	30.98						
WiFi 2450MHz	**Channel 1**	15.00						
	Channel 6	15.00	21.0	-0.20	0.00854	0.01	0.0214	0.02
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.16		**0.22**
GSM 1900MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.11		0.18

Table 9: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

Body-Worn; Back of Phone 25mm from Phantom with GPRS Class10 mode								
f **(MHz)**	**Description**	**Conducted Output Power (dBm)**	**Temp (°C)**	**Drift (dB)**	***10g SAR value***		***1g SAR value***	
					Measured (W/kg)	**Extrapolated (W/kg)**	**Measured (W/kg)**	**Extrapolated (W/kg)**
GSM 850MHz	**Channel 128**	33.50						
	Channel 190	33.50	21.2	0.00	0.125	0.13	0.17	0.17
	Channel 251	33.51						
GSM 1900MHz	**Channel 512**	30.97						
	Channel 661	30.92	21.0	0.01	0.0735	0.07	0.112	0.11
	Channel 810	30.98						
WiFi 2450MHz	**Channel 1**	15.00						
	Channel 6	15.00	21.0	-0.40	0.00319	0.00	0.00651	0.01
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.13		0.18
GSM 1900MHz & WiFi 2450MHz	**Summation of extrapolated SAR values**	**N/A**						
						0.07		0.12

Table 10: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

Body-Worn; Back of Phone 25mm from Phantom with EDGE Class10 mode								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	28.02						
	Channel 190	28.00	21.2	0.03	0.0812	0.08	0.111	0.11
	Channel 251	28.01						
GSM 1900MHz	Channel 512	26.93						
	Channel 661	27.04	20.3	-0.10	0.0256	0.03	0.0391	0.04
	Channel 810	27.03						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	21.0	-0.40	0.00319	0.00	0.00651	0.01
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.08		0.12
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.03		0.05

Table 11: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

The Highest Body-Worn position with SNN5766A Battery								
f (MHz)	Description	Conducted Output Power (dBm)	Temp (°C)	Drift (dB)	*10g SAR value*		*1g SAR value*	
					Measured (W/kg)	Extrapolated (W/kg)	Measured (W/kg)	Extrapolated (W/kg)
GSM 850MHz	Channel 128	33.50						
	Channel 190	33.50	20.8	-0.11	0.141	0.14	0.199	0.20
	Channel 251	33.51						
GSM 1900MHz	Channel 512	30.97						
	Channel 661	30.92	21.1	-0.01	0.108	0.11	0.169	0.17
	Channel 810	30.98						
WiFi 2450MHz	Channel 1	15.00						
	Channel 6	15.00	20.1	-0.43	0.00681	0.01	0.0198	0.02
	Channel 11	15.00						
GSM 850MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.15		0.22
GSM 1900MHz & WiFi 2450MHz	Summation of extrapolated SAR values	N/A						
						0.12		0.19

Table 12: SAR measurement results at the highest possible output power, measured in a body-worn position against the ICNIRP and ANSI SAR Limit.

References

[1] CENELEC, en50361:2001 “Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300MHz – 3GHz)”

[2] CENELEC, en50360:2001 “Product standard to demonstrate the compliance of mobile phones with the basic restrictions related to human exposure to electromagnetic fields (300MHz – 3GHz)”.

[3] ANSI / IEEE, C95.1 1999 Edition “IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300GHz”

[4] FCC OET Bulletin 65 Supplement C 01-01

[5] IEEE 1528 2003 Edition “IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques”

[6] ICNIRP Guidelines “Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz)”

Appendix 1

SAR distribution comparison for the system accuracy verification

Date/Time: 8/29/2006 7:14:48 AM

Test Laboratory: Motorola 20060829 900MHz Good -3.3%

Procedure Notes: 200MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200 mW
Sim.Temp@meas = 21.52C Sim.Temp@SPC = 21.4C Room Temp @ SPC = 20.9C
Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 900 MHz; σ = 0.96 mho/m; ε_r = 40.7; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(6.02, 6.02, 6.02); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 2.21 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.5 V/m; Power Drift = 0.056 dB
Peak SAR (extrapolated) = 3.32 W/kg
SAR(1 g) = 2.23 mW/g; SAR(10 g) = 1.44 mW/g
Maximum value of SAR (measured) = 2.42 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.5 V/m; Power Drift = 0.056 dB
Peak SAR (extrapolated) = 3.18 W/kg
SAR(1 g) = 2.14 mW/g; SAR(10 g) = 1.39 mW/g
Maximum value of SAR (measured) = 2.30 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 2.45 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
2.5
2.0
1.5
1.0
0.5
0.0
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16
m

Date/Time: 9/4/2006 7:01:39 AM

Test Laboratory: Motorola 200600904 900MHz Good -3.5%

Procedure Notes: 900 MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200 mW
Sim.Temp@meas = 21.97C Sim.Temp@SPC = 21.5C Room Temp @ SPC = 20.7C
Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 900 MHz; σ = 0.97 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(6.02, 6.02, 6.02); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 2.20 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.2 V/m; Power Drift = 0.020 dB
Peak SAR (extrapolated) = 3.33 W/kg
SAR(1 g) = 2.23 mW/g; SAR(10 g) = 1.44 mW/g
Maximum value of SAR (measured) = 2.42 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.2 V/m; Power Drift = 0.020 dB
Peak SAR (extrapolated) = 3.16 W/kg
SAR(1 g) = 2.13 mW/g; SAR(10 g) = 1.39 mW/g
Maximum value of SAR (measured) = 2.28 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 2.44 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
2.5
2.0
1.5
1.0
0.5
0.0
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16
m

Date/Time: 9/8/2006 7:18:30 AM

Test Laboratory: Motorola 200600908 900MHz Good -2.0%

Procedure Notes: 900 MHz System Performance Check / Dipole Sn# 077 PM1 Power = 200 mW
Sim.Temp@meas = 21.65C Sim.Temp@SPC = 21.2C Room Temp @ SPC = 20.8C
Communication System: CW - Dipole; Frequency: 900 MHz; Channel Number: 4; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 900 MHz; σ = 0.97 mho/m; ε_r = 40.8; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(6.02, 6.02, 6.02); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 2.25 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.5 V/m; Power Drift = 0.018 dB
Peak SAR (extrapolated) = 3.38 W/kg
SAR(1 g) = 2.26 mW/g; SAR(10 g) = 1.45 mW/g
Maximum value of SAR (measured) = 2.46 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 51.5 V/m; Power Drift = 0.018 dB
Peak SAR (extrapolated) = 3.23 W/kg
SAR(1 g) = 2.17 mW/g; SAR(10 g) = 1.41 mW/g
Maximum value of SAR (measured) = 2.34 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 2.48 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
2.5
2.0
1.5
1.0
0.5
0.0
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16
m

Date/Time: 8/31/2006 2:19:30 PM

Test Laboratory: Motorola 20060831 1800MHz Good -5.1%

Procedure Notes: 1800 MHz System Performance Check / Dipole Sn# 280tr PM1 Power = 200 mW
Sim.Temp@meas = 21.07C Sim.Temp@SPC = 20.9C Room Temp @ SPC = 21.5C
Communication System: CW - Dipole; Frequency: 1800 MHz; Channel Number: 8; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 1800 MHz; σ = 1.35 mho/m; ε_r = 39.1; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.86, 4.86, 4.86); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 6.53 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 80.2 V/m; Power Drift = 0.039 dB
Peak SAR (extrapolated) = 12.6 W/kg
SAR(1 g) = 7.36 mW/g; SAR(10 g) = 3.92 mW/g
Maximum value of SAR (measured) = 8.30 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 80.2 V/m; Power Drift = 0.039 dB
Peak SAR (extrapolated) = 12.1 W/kg
SAR(1 g) = 7.11 mW/g; SAR(10 g) = 3.81 mW/g
Maximum value of SAR (measured) = 8.03 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 8.25 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
0
1
2
3
4
5
6
7
8
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16
m

Date/Time: 9/5/2006 8:53:02 PM

Test Laboratory: Motorola 200600905 2450MHz Good -8.6%

Procedure Notes: 2450 MHz System Performance Check / Dipole Sn# 767 PM1 Power = 200 mW
Sim.Temp@meas = 21.32C Sim.Temp@SPC = 21.1C Room Temp @ SPC = 21.2C
Communication System: CW - Dipole; Frequency: 2450 MHz; Channel Number: 11; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 2450 MHz; σ = 1.87 mho/m; ε_r = 37.6; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.1, 4.1, 4.1); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 7.89 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 84.0 V/m; Power Drift = 0.060 dB
Peak SAR (extrapolated) = 23.6 W/kg
SAR(1 g) = 10.8 mW/g; SAR(10 g) = 5 mW/g
Maximum value of SAR (measured) = 12.1 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 84.0 V/m; Power Drift = 0.060 dB
Peak SAR (extrapolated) = 22.5 W/kg
SAR(1 g) = 10.4 mW/g; SAR(10 g) = 4.86 mW/g
Maximum value of SAR (measured) = 11.6 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 12.3 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
0
1
2
3
4
5
6
7
8
9
10
11
12
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16
m

Date/Time: 9/6/2006 8:47:34 PM

Test Laboratory: Motorola 200600906 2450MHz Good -4.6%

Procedure Notes: 2450 MHz System Performance Check / Dipole Sn# 767 PM1 Power = 198 mW
Sim.Temp@meas = 21.28C Sim.Temp@SPC = 20.9C Room Temp @ SPC = 21.2C
Communication System: CW - Dipole; Frequency: 2450 MHz; Channel Number: 11; Duty Cycle: 1:1
Medium: VALIDATION Only; Medium parameters used: f = 2450 MHz; σ = 1.87 mho/m; ε_r = 38.1; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.1, 4.1, 4.1); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Daily SPC Check/Dipole Area Scan (4x9x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 10.1 mW/g

Daily SPC Check/0-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 85.5 V/m; Power Drift = 0.096 dB
Peak SAR (extrapolated) = 24.9 W/kg
SAR(1 g) = 11.2 mW/g; SAR(10 g) = 5.09 mW/g
Maximum value of SAR (measured) = 12.2 mW/g

Daily SPC Check/90-Degree 5x5x7 Cube (5x5x7)/Cube 0:
Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 85.5 V/m; Power Drift = 0.096 dB
Peak SAR (extrapolated) = 23.4 W/kg
SAR(1 g) = 10.7 mW/g; SAR(10 g) = 4.95 mW/g
Maximum value of SAR (measured) = 11.9 mW/g

Daily SPC Check/Z-Axis Retraction (1x1x31):
Measurement grid: dx=20mm, dy=20mm, dz=5mm
Maximum value of SAR (measured) = 12.4 mW/g




SAR(x,y,z,f0)
SAR; Z-Axis Retraction:Value Along Z, X=0, Y=0
mW/g
m
0
1
2
3
4
5
6
7
8
9
10
11
12
13
0.00
0.02
0.04
0.06
0.08
0.10
0.12
0.14
0.16

Appendix 2

SAR distribution plots for Phantom Head Adjacent Use

Date/Time: 9/8/2006 3:49:53 PM

Test Laboratory: Motorola GSM850 Cheek

TA489002DI;
Procedure Notes: Pwr Step: 05(OTA) Antenna Position: Internal
Battery Model #: SNN5744A DEVICE POSITION (cheek or rotated): Cheek
Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8
Medium: Low Freq Head; Medium parameters used: f = 835 MHz; σ = 0.91 mho/m; ε_r = 41.5; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(6.02, 6.02, 6.02); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Right Head Template/Area Scan - Normal (10mm) (10x25x1):
Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 0.486 mW/g

Right Head Template/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 22.9 V/m; Power Drift = -0.045 dB
Peak SAR (extrapolated) = 0.743 W/kg
SAR(1 g) = 0.463 mW/g; SAR(10 g) = 0.315 mW/g
Maximum value of SAR (measured) = 0.510 mW/g



Date/Time: 9/4/2006 3:40:16 PM

Test Laboratory: Motorola GSM850 Tilt

TA489002DI;

Procedure Notes: Pwr Step: 05(OTA) Antenna Position: Internal

Battery Model #: SNN5766A DEVICE POSITION (cheek or rotated): Rotated

Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8

Medium: Low Freq Head; Medium parameters used: f = 835 MHz; σ = 0.91 mho/m; ε_r = 42.2; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(6.02, 6.02, 6.02); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Sugar SAM; Type: SAM; Serial: TP-1155;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Right Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.230 mW/g

Right Head Template/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 16.2 V/m; Power Drift = -0.001 dB

Peak SAR (extrapolated) = 0.268 W/kg

SAR(1 g) = 0.220 mW/g; SAR(10 g) = 0.168 mW/g

Maximum value of SAR (measured) = 0.231 mW/g



Date/Time: 8/31/2006 10:04:53 AM

Test Laboratory: Motorola GSM1900 Cheek

TA489002DI;
Procedure Notes: Pwr Step: 00(OTA) Antenna Position: Internal
Battery Model #: SNN5744A DEVICE POSITION (cheek or rotated): Cheek
Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8
Medium: Regular Glycol Head; Medium parameters used: f = 1880 MHz; σ = 1.43 mho/m; ε_r = 39.3; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.86, 4.86, 4.86); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Right Head Template/Area Scan - Normal (15mm) (7x17x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.252 mW/g

Right Head Template/Zoom Scan - to correct max outside (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 12.7 V/m; Power Drift = 0.026 dB
Peak SAR (extrapolated) = 0.349 W/kg
SAR(1 g) = 0.239 mW/g; SAR(10 g) = 0.150 mW/g
Maximum value of SAR (measured) = 0.260 mW/g



Date/Time: 8/31/2006 9:35:38 AM

Test Laboratory: Motorola GSM1900 Tilt

TA489002DI;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: Internal

Battery Model #: SNN5744A DEVICE POSITION (cheek or rotated): Rotated

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Head; Medium parameters used: f = 1880 MHz; σ = 1.43 mho/m; ε_r = 39.3; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.86, 4.86, 4.86); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.069 mW/g

Left Head Template/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 7.55 V/m; Power Drift = 0.045 dB

Peak SAR (extrapolated) = 0.101 W/kg

SAR(1 g) = 0.070 mW/g; SAR(10 g) = 0.044 mW/g

Maximum value of SAR (measured) = 0.076 mW/g



Date/Time: 9/6/2006 9:08:00 AM

Test Laboratory: Motorola WiFi 2450 Cheek

TA489002DI;
Procedure Notes: Pwr Step: Test Mode Antenna Position: Internal
Battery Model #: SNN5744A DEVICE POSITION (cheek or rotated): Cheek
Communication System: Wi-Fi 2450; Frequency: 2437 MHz; Channel Number: 6; Duty Cycle: 1:1
Medium: 2450 Glycol Head; Medium parameters used: f = 2450 MHz; σ = 1.87 mho/m; ε_r = 37.6; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.1, 4.1, 4.1); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Right Head Template/Area Scan - Normal (15mm) (7x17x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.038 mW/g

Right Head Template/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 4.78 V/m; Power Drift = -0.037 dB
Peak SAR (extrapolated) = 0.069 W/kg
SAR(1 g) = 0.036 mW/g; SAR(10 g) = 0.019 mW/g
Maximum value of SAR (measured) = 0.041 mW/g



Date/Time: 9/6/2006 8:40:37 AM

Test Laboratory: Motorola WiFi2450 Tilt

TA489002DI;

Procedure Notes: Pwr Step: Test Mode Antenna Position: Internal

Battery Model #: SNN5744A DEVICE POSITION (cheek or rotated): Rotated

Communication System: Wi-Fi 2450; Frequency: 2437 MHz; Channel Number: 6; Duty Cycle: 1:1

Medium: 2450 Glycol Head; Medium parameters used: f = 2450 MHz; σ = 1.87 mho/m; ε_r = 37.6; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.1, 4.1, 4.1); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_Glycol SAM; Type: SAM; Serial: TP-1086;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Left Head Template/Area Scan - Normal (15mm) (7x17x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.012 mW/g

Left Head Template/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.44 V/m; Power Drift = -0.135 dB

Peak SAR (extrapolated) = 0.018 W/kg

SAR(1 g) = 0.011 mW/g; SAR(10 g) = 0.00578 mW/g



Appendix 3

SAR distribution plots for Body Worn Configuration

Date/Time: 8/29/2006 8:47:17 AM

Test Laboratory: Motorola GSM850 Body Worn

TA489002DI;
Procedure Notes: Pwr Step: 05(OTA) Antenna Position: Internal
Battery Model #: SNN5744A Device Position: Back of phone 15mm away from Flat Phantom (Enabled Bluetooth)
Communication System: GSM 850; Frequency: 836.6 MHz; Channel Number: 190; Duty Cycle: 1:8
Medium: Low Freq Body; Medium parameters used: f = 835 MHz; σ = 0.95 mho/m; ε_r = 54.5; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(5.64, 5.64, 5.64); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Section 1, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1):
Measurement grid: dx=15mm, dy=15mm
Maximum value of SAR (measured) = 0.208 mW/g

Amy Twin Phone Template/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 14.9 V/m; Power Drift = -0.041 dB
Peak SAR (extrapolated) = 0.264 W/kg
SAR(1 g) = 0.203 mW/g; SAR(10 g) = 0.144 mW/g
Maximum value of SAR (measured) = 0.218 mW/g



Date/Time: 8/31/2006 1:10:19 PM

Test Laboratory: Motorola GSM1900 Body Worn

TA489002DI;

Procedure Notes: Pwr Step: 00(OTA) Antenna Position: Internal

Battery Model #: SNN5744A Device Position: Back of phone 15mm away from flat phantom

Communication System: GSM 1900; Frequency: 1880 MHz; Channel Number: 661; Duty Cycle: 1:8

Medium: Regular Glycol Body; Medium parameters used: f = 1880 MHz; σ = 1.57 mho/m; ε_r = 50.9; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(4.36, 4.36, 4.36); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Section 2, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Amy Twin Phone Template/Area Scan - Normal Body (15mm) (13x7x1):

Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (measured) = 0.178 mW/g

Amy Twin Phone Template/Zoom Scan (7x7x7)/Cube 0:

Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 11.0 V/m; Power Drift = -0.025 dB

Peak SAR (extrapolated) = 0.256 W/kg

SAR(1 g) = 0.166 mW/g; SAR(10 g) = 0.108 mW/g

Maximum value of SAR (measured) = 0.177 mW/g



Date/Time: 9/7/2006 9:08:34 AM

Test Laboratory: Motorola WiFi2450 Body Worn

TA489002DI;
Procedure Notes: Pwr Step: Test mode Antenna Position: Internal
Battery Model #: SNN5744A Device position: Back of phone 15mm away from Flat phantom
Communication System: Wi-Fi 2450; Frequency: 2437 MHz; Channel Number: 6; Duty Cycle: 1:1
Medium: 2450 Glycol Body; Medium parameters used: f = 2450 MHz; σ = 2.03 mho/m; ε_r = 52.9; ρ = 1000 kg/m^3

DASY4 Configuration:

- Probe: ET3DV6R - SN1501; ConvF(3.73, 3.73, 3.73); Calibrated: 3/23/2006
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn385; Calibrated: 3/21/2006
- Phantom: PCS10_ Section 2, Amy Twin, Rev2 (23-June-04); Type: Amy Twin Flat; Serial: n/a;
- Measurement SW: DASY4, V4.7 Build 44; Postprocessing SW: SEMCAD, V1.8 Build 160

Amy Twin Phone Template/Area Scan - Normal Body (10mm) (19x10x1):
Measurement grid: dx=10mm, dy=10mm
Maximum value of SAR (measured) = 0.022 mW/g

Amy Twin Phone Template/Zoom Scan (7x7x7)/Cube 0:
Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.73 V/m; Power Drift = -0.203 dB
Peak SAR (extrapolated) = 0.074 W/kg
SAR(1 g) = 0.021 mW/g; SAR(10 g) = 0.00854 mW/g
Maximum value of SAR (measured) = 0.023 mW/g



Appendix 4

Probe Calibration Certificate

Calibration Laboratory of
Schmid & Partner
Engineering AG
Zeughausstrasse 43, 8004 Zurich, Switzerland

S Schweizerischer Kalibrierdienst
C Service suisse d'étalonnage
Servizio svizzero di taratura
S Swiss Calibration Service

Accredited by the Swiss Federal Office of Metrology and Accreditation
The Swiss Accreditation Service is one of the signatories to the EA Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client Motorola Korea

Certificate No: ET3-1501_Mar06

CALIBRATION CERTIFICATE

Object	ET3DV6R - SN:1501
Calibration procedure(s)	QA CAL-01.v5 Calibration procedure for dosimetric E-field probes
Calibration date:	March 23, 2006
Condition of the calibrated item	In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Calibrated by, Certificate No.)	Scheduled Calibration
Power meter E4419B	GB41293874	3-May-05 (METAS, No. 251-00466)	May-06
Power sensor E4412A	MY41495277	3-May-05 (METAS, No. 251-00466)	May-06
Power sensor E4412A	MY41498087	3-May-05 (METAS, No. 251-00466)	May-06
Reference 3 dB Attenuator	SN: S5054 (3c)	11-Aug-05 (METAS, No. 251-00499)	Aug-06
Reference 20 dB Attenuator	SN: S5086 (20b)	3-May-05 (METAS, No. 251-00467)	May-06
Reference 30 dB Attenuator	SN: S5129 (30b)	11-Aug-05 (METAS, No. 251-00500)	Aug-06
Reference Probe ES3DV2	SN: 3013	2-Jan-06 (SPEAG, No. ES3-3013_Jan06)	Jan-07
DAE4	SN: 654	2-Feb-06 (SPEAG, No. DAE4-654_Feb06)	Feb-07

Secondary Standards	ID #	Check Date (in house)	Scheduled Check
RF generator HP 8648C	US3642U01700	4-Aug-99 (SPEAG, in house check Nov-05)	In house check: Nov-07
Network Analyzer HP 8753E	US37390585	18-Oct-01 (SPEAG, in house check Nov-05)	In house check: Nov 06

	Name	Function	Signature
Calibrated by:	Katja Pokovic	Technical Manager	
Approved by:	Niels Kuster	Quality Manager	

Issued: March 23, 2006

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.

Glossary:

TSL	tissue simulating liquid
NORMx,y,z	sensitivity in free space
ConF	sensitivity in TSL / NORMx,y,z
DCP	diode compression point
Polarization φ	φ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis

Calibration is Performed According to the Following Standards:

a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
b) CENELEC EN 50361, "Basic standard for the measurement of Specific Absorption Rate related to human exposure to electromagnetic fields from mobile phones (300 MHz - 3 GHz), July 2001

Methods Applied and Interpretation of Parameters:

- *NORMx,y,z:* Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORMx,y,z are only intermediate values, i.e., the uncertainties of NORMx,y,z does not effect the E^2-field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORMx,y,z * frequency_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z:* DCP are numerical linearization parameters assessed based on the data of power sweep (no uncertainty required). DCP does not depend on frequency nor media.
- *ConvF and Boundary Effect Parameters:* Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORMx,y,z * ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- *Spherical isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

Probe ET3DV6R

SN:1501

Manufactured:	September 21, 1999
Last calibrated:	March 21, 2005
Recalibrated:	March 23, 2006

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

DASY - Parameters of Probe: ET3DV6R SN:1501

Sensitivity in Free Space[A]

NormX	**2.17** ± 10.1%	$\mu V/(V/m)^2$	DCP X	**96** mV
NormY	**2.18** ± 10.1%	$\mu V/(V/m)^2$	DCP Y	**96** mV
NormZ	**2.24** ± 10.1%	$\mu V/(V/m)^2$	DCP Z	**96** mV

Diode Compression[B]

Sensitivity in Tissue Simulating Liquid (Conversion Factors)

Please see Page 8.

Boundary Effect

TSL **900 MHz** **Typical SAR gradient: 5 % per mm**

Sensor Center to Phantom Surface Distance		**3.7 mm**	**4.7 mm**
SAR_{be} [%]	Without Correction Algorithm	8.5	4.6
SAR_{be} [%]	With Correction Algorithm	0.1	0.1

TSL **1810 MHz** **Typical SAR gradient: 10 % per mm**

Sensor Center to Phantom Surface Distance		**3.7 mm**	**4.7 mm**
SAR_{be} [%]	Without Correction Algorithm	7.3	4.1
SAR_{be} [%]	With Correction Algorithm	0.2	0.4

Sensor Offset

Probe Tip to Sensor Center **2.7** mm

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

[A] The uncertainties of NormX,Y,Z do not affect the E^2-field uncertainty inside TSL (see Page 8).

[B] Numerical linearization parameter: uncertainty not required.

Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field: ± 6.3% (k=2)

Receiving Pattern (ϕ), ϑ = 0°







Uncertainty of Axial Isotropy Assessment: ± 0.5% (k=2)

Dynamic Range f(SAR_{head})

(Waveguide R22, f = 1800 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment





f [MHz]	Validity [MHz][c]	TSL	Permittivity	Conductivity	Alpha	Depth	ConvF Uncertainty
900	± 50 / ± 100	Head	41.5 ± 5%	0.97 ± 5%	0.56	1.88	6.02 ± 11.0% (k=2)
1810	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.50	2.49	4.86 ± 11.0% (k=2)
1950	± 50 / ± 100	Head	40.0 ± 5%	1.40 ± 5%	0.50	2.60	4.65 ± 11.0% (k=2)
2450	± 50 / ± 100	Head	39.2 ± 5%	1.80 ± 5%	0.59	2.29	4.10 ± 11.8% (k=2)
900	± 50 / ± 100	Body	55.0 ± 5%	1.05 ± 5%	0.50	2.05	5.64 ± 11.0% (k=2)
1810	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.63	2.41	4.36 ± 11.0% (k=2)
1950	± 50 / ± 100	Body	53.3 ± 5%	1.52 ± 5%	0.75	2.15	4.19 ± 11.0% (k=2)
2450	± 50 / ± 100	Body	52.7 ± 5%	1.95 ± 5%	0.54	2.21	3.73 ± 11.8% (k=2)

[c] The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

Deviation from Isotropy in HSL

Error (ϕ, ϑ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment: ± 2.6% (k=2)

Appendix 5

Measurement Uncertainty Budget

a	*b*	*c*	*d*	*e = f(d,k)*	*f*	*g*	*h = c x f / e*	*i = c x g / e*	*k*
Uncertainty Component	**IEEE 1528 section**	**Tol. (± %)**	**Prob Dist**	**Div.**	**c_i (1 g)**	**c_i (10 g)**	**1 g u_i (±%)**	**10 g u_i (±%)**	**v_i**
Measurement System									
Probe Calibration	E.2.1	5.9	N	1.00	1	1	5.9	5.9	∞
Axial Isotropy	E.2.2	4.7	R	1.73	0.707	0.707	1.9	1.9	∞
Hemispherical Isotropy	E.2.2	9.6	R	1.73	0.707	0.707	3.9	3.9	∞
Boundary Effect	E.2.3	1.0	R	1.73	1	1	0.6	0.6	∞
Linearity	E.2.4	4.7	R	1.73	1	1	2.7	2.7	∞
System Detection Limits	E.2.5	1.0	R	1.73	1	1	0.6	0.6	∞
Readout Electronics	E.2.6	0.3	N	1.00	1	1	0.3	0.3	∞
Response Time	E.2.7	1.1	R	1.73	1	1	0.6	0.6	∞
Integration Time	E.2.8	1.1	R	1.73	1	1	0.6	0.6	∞
RF Ambient Conditions - Noise	E.6.1	3.0	R	1.73	1	1	1.7	1.7	∞
RF Ambient Conditions - Reflections	E.6.1	0.0	R	1.73	1	1	0.0	0.0	∞
Probe Positioner Mech. Tolerance	E.6.2	0.4	R	1.73	1	1	0.2	0.2	∞
Probe Positioning w.r.t Phantom	E.6.3	1.4	R	1.73	1	1	0.8	0.8	∞
Max. SAR Evaluation (ext., int., avg.)	E.5	3.4	R	1.73	1	1	2.0	2.0	∞
Test sample Related									
Test Sample Positioning	E.4.2	3.2	N	1.00	1	1	3.2	3.2	29
Device Holder Uncertainty	E.4.1	4.0	N	1.00	1	1	4.0	4.0	8
SAR drift	6.6.2	5.0	R	1.73	1	1	2.9	2.9	∞
Phantom and Tissue Parameters									
Phantom Uncertainty	E.3.1	4.0	R	1.73	1	1	2.3	2.3	∞
Liquid Conductivity (target)	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity (measurement)	E.3.3	3.3	N	1.00	0.64	0.43	2.1	1.4	∞
Liquid Permittivity (target)	E.3.2	5.0	R	1.73	0.6	0.49	1.7	1.4	∞
Liquid Permittivity (measurement)	E.3.3	1.9	N	1.00	0.6	0.49	1.1	0.9	∞
Combined Standard Uncertainty			RSS				11.1	10.8	411
Expanded Uncertainty (95% CONFIDENCE LEVEL)			*k*=2				22.2	21.6	

Appendix 6

Photographs of the device under test

Figure 1. Front of Phone

Figure 2. Phone Open

Figure 3. Back of Phone

Figure 4. Phone Against the Flat Phantom

Figure 5. Phone Against the Head Phantom (Cheek Touch)

Figure 6. Phone Against the Head Phantom (15°Tilt)

Appendix 7

Dipole Characterization Certificate

Certification of System Performance Check Targets
Based on WI-0396

-Historical Data-

	900MHz	
IEEE1528 Target:	10.8	**(W/kg)**
Measurement Uncertainty (k=1):	9.0%	
Measurement Period:	*3-June-05 to 10-May-06*	
# of tests performed:	1571	
Grand Average:	11.3	**(W/kg)**
% Delta (Average - IEEE1528 Target)	4.3%	
Is % Delta <= Expanded Measurement Uncertainty (k=2)?	**Yes**	
Accept/Reject Average as new system performance check target?	**ACCEPT**	
	Applies to Dipole SN's: **55, 69, 77, 78, 79, 80, 91, 92, 93, 94, 95, 96, 97**	

-New System Performance Check Targets- per WI-0396
(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
900MHz	**11.3**	41.5 ± 5%	0.97 ± 5%

= =

-Approvals-

Submitted by: Marge Kaunas   Date: 12-May-06

Signed: [signature]

Comments: Spreadsheet detailing referenced historical measurements is available upon request.

Approved by: Mark Douglas   **Date:** 22-May-06

Signed: [signature]

Comments:

= =

Certification of System Performance Check Targets
Based on WI-0396

-Historical Data-

	2450MHz	
IEEE1528 Target:	52.4	**(W/kg)**
Measurement Uncertainty (k=1):	9.0%	
Measurement Period:	*3-June-05 to 10-May-06*	
# of tests performed:	64	
Grand Average:	58.0	**(W/kg)**
% Delta (Average - IEEE1528 Target)	10.6%	
Is % Delta <= Expanded Measurement Uncertainty (k=2)?	**Yes**	
Accept/Reject Average as new system performance check target?	**ACCEPT**	
	Applies to Dipole SN's: 740, 766, 767	

-New System Performance Check Targets- per WI-0396
(based on analysis of historical data)

Frequency	SAR Target (W/kg)	Permittivity	Conductivity (S/m)
2450MHz	**58.0**	39.2 ± 5%	1.80 ± 5%

-Approvals-

Submitted by: Marge Kaunas — Date: 12-May-06

Signed: Marge Kaunas

Comments: Spreadsheet detailing referenced historical measurements is available upon request.

Approved by: Mark Douglas — **Date:** 22-May-06

Signed: Mark Douglas

Comments: