Variant FCC Test Report

APPLICANT	:	Motorola Mobility, Inc.
EQUIPMENT	:	GSM / EGPRS Mobile Phone
BRAND NAME	:	Motorola
MODEL NAME	:	EX119
GPPD NUMBER	:	3049
FCC ID	:	IHDT56MK2
STANDARD	:	FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION	:	Certification

This is a variant report which is only valid together with the original test report. The product was received on Mar. 29, 2011 and completely tested on Apr. 10, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:

Roy Wu / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1. GENERAL DESCRIPTION **5**

1.1. Applicant 5
1.2. Manufacturer 5
1.3. Feature of Equipment Under Test 5
1.4. Test Site 6
1.5. Applied Standards 6
1.6. Ancillary Equipment List 6

2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST **7**

2.1. Test Mode 7
2.2. Connection Diagram of Test System 8
2.3. Test Software 8

3. TEST RESULT **9**

3.1. Test of AC Conducted Emission Measurement 9
3.2. Test of Radiated Emission Measurement 13

4. LIST OF MEASURING EQUIPMENT **17**

5. UNCERTAINTY OF EVALUATION **18**

APPENDIX A. PRODUCT EQUALITY DECLARATION

APPENDIX B. ORIGINAL REPORT

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC132917-02	Rev. 01	This is a variant report for adding one more sample which can be referred to appendix A for product equality declaration. All the test cases were performed on Sample 1 in original report which can be referred to Sporton Report No. FC132917A as appendix B. Based on original report, only the worst cases of radiated emission and conducted emission with Sample 2 were verified.	Apr. 20, 2011

SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.107	7.2.2	AC Conducted Emission	< 15.107 limits < RSS-Gen table 2 limits	PASS	Under limit 13.2 dB at 0.19 MHz
3.2	15.109	7.2.3.2	Radiated Emission	< 15.109 limits or < RSS-Gen table 1 limits (Section 6)	PASS	Under limit 6.24 dB at 341.30 MHz

1. General Description

1.1. Applicant

Motorola Mobility, Inc.
No. 1, Wang Jing East Road, Chao Yang District Beijing, China 100102

1.2. Manufacturer

Arima Communications Corp.
6F., No. 866, Jhongjheng Rd., Jhonghe Dist., New Taipei City 23586, Taiwan

1.3. Feature of Equipment Under Test

Product Feature & Specification	
Equipment	GSM / EGPRS Mobile Phone
Brand Name	Motorola
Model Name	EX119
FCC ID	IHDT56MK2
EUT Configuration	Sample 1 : EUT with Single SIM Card (EX118) Sample 2 : EUT with Dual SIM Card (EX119)
Tx Frequency Range	GSM850 : 824 MHz ~ 849 MHz GSM1900 : 1850 MHz ~ 1910 MHz Bluetooth : 2400 MHz ~ 2483.5 MHz WLAN : 2400 MHz ~ 2483.5 MHz
Rx Frequency Range	GSM850 : 869 MHz ~ 894 MHz GSM1900 : 1930 MHz ~ 1990 MHz Bluetooth : 2400 MHz ~ 2483.5 MHz WLAN : 2400 MHz ~ 2483.5 MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN/Bluetooth : PIFA Antenna
HW Version	P2
SW Version	Sample 1 : BREA_G_07.0C.00R_S_WIFI Sample 2 : BREA_G_07.0C.00R_D_WIFI
Type of Modulation	GSM / GPRS : GMSK EDGE : 8PSK Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π/4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK 802.11b : DSSS (BPSK / QPSK / CCK) 802.11g : OFDM (BPSK / QPSK / 16QAM / 64QAM)
EUT Stage	Production Unit

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4. Test Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07HY	722060/4086B-1

1.5. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2003
- IC RSS-Gen Issue 3

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

1.6. Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
4.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	LCD Monitor	Lenovo	6135-AB1	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m
6.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
7.	iPod	Apple	A1199	FCC DoC	Shielded, 1.0 m	N/A

2. Test Configuration of Equipment Under Test

2.1. Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

The following tables are showing the test modes as the worst cases and recorded in this report.

Item	EUT Configuration	Test Condition	
		EMI AC	EMI RE
1.	Charging Mode (EUT with notebook)	☒	☒

Abbreviations:

- EMI AC: AC conducted emissions
- EMI RE: EUT radiated emissions

Test Items	EUT Configure Mode	Function Type
AC Conducted Emission	1	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2
Radiated Emissions	1	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2

2.2. Connection Diagram of Test System



2.3. Test Software

The EUT was in GSM idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and execute the program, "winthrax", installed in notebook for active sync files transfer with EUT via USB cable.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.1.4 Test Setup



3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	**Temperature :**	20~22℃
Test Engineer :	Novic Chiang	**Relative Humidity :**	40~42%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	44.8	Off	L1	19.4	20.8	65.6
0.198000	50.5	Off	L1	19.4	13.2	63.7
0.270000	44.1	Off	L1	19.4	17.0	61.1
0.334000	39.6	Off	L1	19.4	19.8	59.4
0.398000	34.8	Off	L1	19.4	23.1	57.9
1.270000	30.9	Off	L1	19.4	25.1	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	18.1	Off	L1	19.4	37.5	55.6
0.198000	38.2	Off	L1	19.4	15.5	53.7
0.270000	32.2	Off	L1	19.4	18.9	51.1
0.334000	28.0	Off	L1	19.4	21.4	49.4
0.398000	22.6	Off	L1	19.4	25.3	47.9
1.270000	29.5	Off	L1	19.4	16.5	46.0

Test Mode :	Mode 1	**Temperature :**	20~22℃
Test Engineer :	Novic Chiang	**Relative Humidity :**	40~42%
Test Voltage :	120Vac / 60Hz	**Phase :**	Neutral
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	44.7	Off	N	19.4	20.9	65.6
0.198000	48.8	Off	N	19.4	14.9	63.7
0.262000	42.3	Off	N	19.4	19.1	61.4
0.334000	38.2	Off	N	19.4	21.2	59.4
0.470000	30.3	Off	N	19.4	26.2	56.5
1.406000	30.1	Off	N	19.5	25.9	56.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	17.4	Off	N	19.4	38.2	55.6
0.198000	36.6	Off	N	19.4	17.1	53.7
0.262000	32.2	Off	N	19.4	19.2	51.4
0.334000	28.1	Off	N	19.4	21.3	49.4
0.470000	22.0	Off	N	19.4	24.5	46.5
1.406000	27.5	Off	N	19.5	18.5	46.0

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments

See list of measuring instruments of this test report.

3.2.3. Test Procedures

1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the quasi-peak method and reported
8. Emission level (dBuV/m) = 20 log Emission level (uV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission



3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 1	**Temperature :**	23~26°C
Test Engineer :	Wii Chang	**Relative Humidity :**	54~60%
Test Distance :	3m	**Polarization :**	Horizontal
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2		
Remark :	#7 is System Simulator signal which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B HF_ANT_100624 HORIZONTAL
Project : FD 132917-02
Power : From System
Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	85.62	18.96	-21.04	40.00	41.64	7.95	0.91	31.54	---	---	Peak
2	126.66	23.07	-20.43	43.50	41.94	11.57	1.14	31.57	---	---	Peak
3	217.65	31.01	-14.99	46.00	50.73	10.34	1.40	31.46	---	---	Peak
4 @	341.30	39.76	-6.24	46.00	54.40	14.75	1.90	31.30	110	215	Peak
5	397.30	36.52	-9.48	46.00	49.07	16.50	2.14	31.19	---	---	Peak
6	666.10	33.82	-12.18	46.00	41.29	20.51	2.87	30.85	---	---	Peak
7 @	881.70	39.99			43.97	23.42	3.31	30.71	---	---	Peak
8	7436.00	41.61	-32.39	74.00	54.34	35.34	10.12	58.19	---	---	Peak

Test Mode :	Mode 1	**Temperature :**	23~26°C
Test Engineer :	Wii Chang	**Relative Humidity :**	54~60%
Test Distance :	3m	**Polarization :**	Vertical
Function Type :	GSM850 Idle + Bluetooth Idle + WLAN Idle + Earphone + USB Cable (Link with Notebook) for Sample 2		
Remark :	#7 is System Simulator signal which can be ignored.		



Site : 03CH07-HY
Condition : FCC CLASS-B HF_ANT_100624 VERTICAL
Project : FD 132917-02
Power : From System
Mode : Mode 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1	43.77	29.66	-10.34	40.00	49.39	11.13	0.64	31.50	100	215	Peak
2	93.18	23.20	-20.30	43.50	44.75	9.01	0.96	31.53	---	---	Peak
3	227.10	27.54	-18.46	46.00	46.50	11.02	1.46	31.45	---	---	Peak
4	330.10	30.95	-15.05	46.00	46.02	14.39	1.85	31.31	---	---	Peak
5	397.30	29.96	-16.04	46.00	42.51	16.50	2.14	31.19	---	---	Peak
6	663.30	31.58	-14.42	46.00	39.09	20.48	2.87	30.86	---	---	Peak
7 @	881.70	39.68			43.66	23.42	3.31	30.71	---	---	Peak
8	7470.00	41.61	-32.39	74.00	54.36	35.31	10.14	58.20	---	---	Peak

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9KHz – 30MHz	Dec. 03, 2010	Dec. 02, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9KHz – 30MHz	Dec. 01, 2010	Nov. 30, 2011	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32 dB.GAIN	Mar. 29, 2011	Mar. 28, 2012	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/001	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH07-HY)
System Simulator	R&S	CMU200	117591	N/A	Oct. 18, 2010	Oct. 17, 2011	-

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty Uc(y)	**1.13**		
Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.26**		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty Uc(y)	**1.27**		
Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.54**		

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR Γ1 = 0.197 Antenna VSWR Γ2 = 0.194 Uncertainty = 20Log(1-Γ1*Γ2)	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty Uc(y)	**2.36**				
Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.72**				

Appendix A. Product Equality Declaration

Arima Communications Corp.
6F., No.866, Jhongjheng Rd.,
Jhonghe Dist., New Taipei
City 23586, Taiwan.
http://www.arimacomm.com.tw

Date: 2011/4/11

GSM/GPRS Mobile phone

Subject: Product Equality Declaration

(Declaration of equality of a product variant with a previously assessed original product. To be signed in the name of the company that is responsible for the product variant.)

We, **Arima Communications Corp.** declare on our sole responsibility for the product of EX119(model name) as below:

The difference between EX119 and EX118 is:

- EX118:single sim wifi
- EX119:dual sim wifi

Except Listings above, the others are the same as previous version.

Should you have any questions or comments regarding this matter, please have my best attention.

Sincerely yours,

Signature

Michael Lu / Manager (Date: Apr 11, 2011)
Company: Arima Communications Corp.
Address: 6F., No.866, Jhongjheng Rd., Jhonghe Dist., New Taipei City 23586, Taiwan.
Tel.: +886-2-8227-7755 ; Fax: +886-2-8227-5533

Copyright © Arima Communications Corporation All Rights Reserved.

Page 1 of 1

Appendix B. Original Report

Please refer to Sporton report number FC132917A as below.