

**SAR COMPLIANCE EVALUATION REPORT****Applicant Name:**

Motorola Mobility, Inc.
8000 West Sunrise Blvd.
Plantation, FL 33322
United States

Date of Testing:

05/26/11 - 06/22/11, 08/22/11

Test Site/Location:

PCTEST Lab, Columbia, MD, USA

Test Report Serial No.:

0Y1105170871-R6.IHD

FCC ID:

IHDT56MP1

APPLICANT:

MOTOROLA MOBILITY, INC.

EUT Type:**Application Type:****FCC Rule Part(s):****Tx Frequency:****Conducted Power:****Max. SAR Measurement:****Test Device Serial No.:**

Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN Certification

CFR §2.1093; FCC/OET Bulletin 65 Supplement C [June 2001]

817.90 - 823.10 MHz - Cellular CDMA- FCC Rule Part 90S

824.70 - 848.31 MHz - Cellular CDMA-FCC Rule Part 22H

1851.25 - 1908.75 MHz - PCS CDMA-FCC Rule Part 24E

2412 - 2462 MHz WLAN - FCC Rule Part 15C

25.02 dBm Cell. CDMA - FCC Rule Part 90S

25.25 dBm Cell. CDMA - FCC Rule Part 22H

24.45 dBm PCS CDMA - FCC Rule Part 24E

18.58 dBm 2.4 GHz WLAN - FCC Rule Part 15C

0.93 W/kg Cell. CDMA - FCC Rule Part 90S Head SAR

0.67 W/kg Cell. CDMA - FCC Rule Part 90S Body-Worn SAR

1.25 W/kg Cell. CDMA - FCC Rule Part 90S Hotspot Body

1.02 W/kg Cell. CDMA - FCC Rule Part 22H Head SAR

0.73 W/kg Cell. CDMA - FCC Rule Part 22H Body-Worn SAR

1.37 W/kg Cell. CDMA - FCC Rule Part 22H Hotspot Body SAR

1.06 W/kg PCS CDMA - FCC Rule Part 24E Head SAR

0.44 W/kg PCS CDMA - FCC Rule Part 24E Body-Worn SAR

0.73 W/kg PCS CDMA - FCC Rule Part 24E Hotspot Body SAR

0.32 W/kg 2.4 GHz WLAN - FCC Rule Part 15C Head SAR

0.01 W/kg 2.4 GHz WLAN - FCC Rule Part 15C Body-Worn SAR

0.06 W/kg 2.4 GHz WLAN - FCC Rule Part 15C Hotspot Body SAR

Pre-Production [S/N: Unit A, Unit C, Unit E, Unit X, Unit Y]

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001), IEEE 1528-2003 and in applicable Industry Canada Radio Standards Specifications (RSS); for North American frequency bands only.

Note: This revised Test Report (S/N: 0Y1105170871-R6.IHD) supersedes and replaces the previously issued test report on the same subject EUT for the same type of testing as indicated. Please discard or destroy the previously issued test report(s) and dispose of it accordingly.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.



Randy Ortanez
President



FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 1 of 45

T A B L E O F C O N T E N T S

1	INTRODUCTION	3
2	TEST SITE LOCATION	4
3	SAR MEASUREMENT SETUP	5
4	DASY E-FIELD PROBE SYSTEM	7
5	PROBE CALIBRATION PROCESS	8
6	PHANTOM AND EQUIVALENT TISSUES.....	9
7	DOSIMETRIC ASSESSMENT & PHANTOM SPECS.....	10
8	DEFINITION OF REFERENCE POINTS	11
9	TEST CONFIGURATION POSITIONS	12
10	FCC RF EXPOSURE LIMITS.....	15
11	FCC 3G MEASUREMENT PROCEDURES.....	16
12	SAR TESTING WITH IEEE 802.11 TRANSMITTERS.....	18
13	MEASURED RF CONDUCTED POWERS	19
14	FCC PERSONAL WIRELESS ROUTER CONFIGURATIONS.....	25
15	SYSTEM VERIFICATION.....	27
16	SAR DATA SUMMARY	29
17	FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS.....	38
18	EQUIPMENT LIST.....	41
19	MEASUREMENT UNCERTAINTIES	42
20	CONCLUSION.....	43
21	REFERENCES	44

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 2 of 45

1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices. [1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz [3] and Health Canada RF Exposure Guidelines Safety Code 6 [24]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [4] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density (ρ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{dt} \left(\frac{dU}{dm} \right) = \frac{d}{dt} \left(\frac{dU}{\rho dv} \right)$$

Figure 1-1
SAR Mathematical Equation

SAR is expressed in units of Watts per Kilogram (W/kg).

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- σ = conductivity of the tissue-simulating material (S/m)
- ρ = mass density of the tissue-simulating material (kg/m^3)
- E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 3 of 45

2 TEST SITE LOCATION

2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC.

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.



Figure 2-1

Map of the Greater Baltimore and Metropolitan Washington, D.C. area

2.2 Test Facility / Accreditations:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing-Aid Compatibility (HAC), Battery Safety, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and all Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS and CDMA, and EvDO mobile phones.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO Data, CDMA 1xRTT Data

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 4 of 45

3 SAR MEASUREMENT SETUP

3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of a high precision robotics system (Staubli), robot controller, desktop computer, near-field probe, probe alignment sensor, and the SAM phantom containing the head or body equivalent material. The robot is a six-axis industrial robot, performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, A/D conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal from the DAE and transfers data to the PC card.

3.3 System Electronics




Figure 3-1
SAR Measurement System Setup

The DAE consists of a highly sensitive electrometer-grade auto-zeroing preamplifier, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 5 of 45

3.4 Automated Test System Specifications

Test Software: SPEAG DASY4 version 4.7 Measurement Software
Robot: Stäubli Unimation Corp. Robot RX60L
Repeatability: 0.02 mm
No. of Axes: 6

Data Acquisition Electronic System (DAE)

Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic
Software: SEMCAD software
Connecting Lines: Optical Downlink for data and status info
Optical upload for commands and clock

PC Interface Card

Function: Link to DAE
16-bit A/D converter for surface detection system
Two Serial & Ethernet link to robotics
Direct emergency stop output for robot

Phantom

Type: SAM Twin Phantom (V4.0)
Shell Material: Composite
Thickness: 2.0 ± 0.2 mm



Figure 3-2
SAR Measurement System

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 6 of 45

4.1 Probe Measurement System



**Figure 4-1
SAR System**

The SAR measurements were conducted with the dosimetric probe designed in the classical triangular configuration (see Figure 4-3) and optimized for dosimetric evaluation [9]. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach and looks for the

maximum using a 2nd order curve fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

4.2 Probe Specifications

Model(s):	ES3DV2, ES3DV3, EX3DV4
Frequency	10 MHz – 6.0 GHz (EX3DV4)
Range:	10 MHz – 4 GHz (ES3DV3, ES3DV2)
Calibration:	In head and body simulating, tissue at Frequencies from 300 up to 6000MHz
Linearity:	± 0.2 dB (30 MHz to 6 GHz) for EX3DV4 ± 0.2 dB (30 MHz to 4 GHz) for ES3DV3, ES3DV2
Dynamic Range:	10 mW/kg – 100 W/kg
Probe Length:	330 mm
Probe Tip Length:	20 mm
Body Diameter:	12 mm
Tip Diameter:	2.5 mm (3.9mm for ES3DV3)
Tip-Center:	1 mm (2.0 mm for ES3DV3)
Application:	SAR Dosimetry Testing Compliance tests of mobile phones Dosimetry in strong gradient fields



**Figure 4-2
Near-Field Probe**



**Figure 4-3
Triangular Probe
Configuration**

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 7 of 45

5

PROBE CALIBRATION PROCESS

5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe Amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm²) using an RF Signal generator, TEM cell, and RF Power Meter.

5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm².

5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated head tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$SAR = C \frac{\Delta T}{\Delta t}$$

where:

Δt = exposure time (30 seconds),
 C = heat capacity of tissue (brain or muscle),
 ΔT = temperature increase due to RF exposure.

$$SAR = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

σ = simulated tissue conductivity,
 ρ = Tissue density (1.25 g/cm³ for brain tissue)

SAR is proportional to $\Delta T/\Delta t$, the initial rate of tissue heating, before thermal diffusion takes place. The electric field in the simulated tissue can be used to estimate SAR by equating the thermally derived SAR to that with the E- field component.




Figure 5-1 E-Field and Temperature measurements at 900MHz [9]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [9]

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 8 of 45

6 PHANTOM AND EQUIVALENT TISSUES

6.1 SAM Phantoms



Figure 6-1
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a table. The shape of the shell is based on data from an anatomical study designed to represent the 90th percentile of the population [12][13]. The phantom enables the dosimetric evaluation of SAR for both left and right handed handset usage, as well as body-worn usage using the flat phantom region. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. The shell phantom has a 2mm shell thickness (except the ear region where shell thickness increases to 6 mm).

6.2 Tissue Simulating Mixture Characterization




Figure 6-2
SAM Phantom with
Simulating Tissue

Table 6-1
Composition of the Tissue Equivalent Matter

Frequency (MHz)	835	835	1900	1900	2450	2450
Tissue	Head	Body	Head	Body	Head	Body
Ingredients (% by weight)						
Bactericide	0.1	0.1				
DGBE			44.92	29.44	7.99	26.7
HEC	1	1				
NaCl	1.45	0.94	0.18	0.39	0.16	0.1
Sucrose	57	44.9				
Triton X-100					19.97	
Water	40.45	53.06	54.9	70.17	71.88	73.2

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 9 of 45

7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR distribution at the exposed side of the head was measured at a distance no greater than 5.0 mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
2. The point SAR measurement was taken at the maximum SAR region determined from Step 1 to enable the monitoring of SAR fluctuations/drifts during testing the 1 gram cube. This fixed point was measured and used as a reference value.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see references or the DASY manual for more details):
 - a. The data was extrapolated to the surface of the outer-shell of the phantom. The combined distance extrapolated was the combined distance from the center of the dipoles 2.7mm away from the tip of the probe housing plus the 1.2 mm distance between the surface and the lowest measuring point. The extrapolation was based on a least-squares algorithm. A polynomial of the fourth order was calculated through the points in the z-axis (normal to the phantom shell).
 - b. After the maximum interpolated values were calculated between the points in the cube, the SAR was averaged over the spatial volume (1g or 10g) using a 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions). The volume was then integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were obtained through interpolation, in order to calculate the averaged SAR.
 - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 2, was re-measured after the zoom scan was complete. If the value deviated by more than 5%, the evaluation was repeated.




Figure 7-1
Sample SAR Area Scan

7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimize reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15 cm.



Figure 7-2
SAM Twin Phantom Shell

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 10 of 45

8

DEFINITION OF REFERENCE POINTS

8.1 EAR REFERENCE POINT

Figure 8-1 shows the front, back and side views of the SAM Twin Phantom. The point “M” is the reference point for the center of the mouth, “LE” is the left ear reference point (ERP), and “RE” is the right ERP. The ERP is 15mm posterior to the entrance to the ear canal (EEC) along the B-M line (Back-Mouth), as shown in Figure 8-1. The plane passing through the two ear canals and M is defined as the Reference Plane. The line N-F (Neck-Front) is perpendicular to the reference plane and passing through the RE (or LE) is called the Reference Pivoting Line (see Figure 8-2). Line B-M is perpendicular to the N-F line. Both N-F and B-M lines are marked on the external phantom shell to facilitate handset positioning [5].




Figure 8-1
Close-Up Side view
of ERP

8.2 HANDSET REFERENCE POINTS

Two imaginary lines on the handset were established: the vertical centerline and the horizontal line. The test device was placed in a normal operating position with the “test device reference point” located along the “vertical centerline” on the front of the device aligned to the “ear reference point” (See Figure 8-3). The “test device reference point” was then located at the same level as the center of the ear reference point. The test device was positioned so that the “vertical centerline” was bisecting the front surface of the handset at it’s top and bottom edges, positioning the “ear reference point” on the outer surface of the both the left and right head phantoms on the ear reference point.



Figure 8-2
Front, back and side view of SAM Twin Phantom




Figure 8-3
Handset Vertical Center & Horizontal Line Reference Points

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 11 of 45

9 TEST CONFIGURATION POSITIONS

9.1 Device Holder

The DASY device holder has been made out of low-loss POM material having the following dielectric parameters: relative permittivity $\epsilon = 3$ and loss tangent $\delta = 0.02$.

9.2 Positioning for Cheek/Touch

1. The test device was positioned with the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9-1), such that the plane defined by the vertical center line and the horizontal line of the phone is approximately parallel to the sagittal plane of the phantom.




Figure 9-1 Front, Side and Top View of Cheek/Touch Position

2. The handset was translated towards the phantom along the line passing through RE & LE until the handset touches the ear.
3. While maintaining the handset in this plane, the handset was rotated around the LE-RE line until the vertical centerline was in the plane normal to MB-NF including the line MB (reference plane).
4. The phone was then rotated around the vertical centerline until the phone (horizontal line) was symmetrical with respect to the line NF.
5. While maintaining the vertical centerline in the reference plane, keeping point A on the line passing through RE and LE, and maintaining the phone contact with the ear, the handset was rotated about the line NF until any point on the handset made contact with a phantom point below the ear (cheek) (See Figure 9-2).

9.3 Positioning for Ear / 15° Tilt

With the test device aligned in the “Cheek/Touch Position”:

1. While maintaining the orientation of the phone, the phone was retracted parallel to the reference plane far enough to enable a rotation of the phone by 15 degree.
2. The phone was then rotated around the horizontal line by 15 degree.
3. While maintaining the orientation of the phone, the phone was moved parallel to the reference plane until any part of the phone touches the head. (In this position, point A was located on the line RE-LE). The tilted position is obtained when the contact is on the pinna. If the contact was at any location other than the pinna, the angle of the phone would then be reduced. The tilted position was obtained when any part of the phone was in contact of the ear as well as a second part of the phone was in contact with the head (see Figure 9-2).

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 12 of 45




Figure 9-2 Front, Side and Top View of Ear/15° Tilt Position




Figure 9-3
Side view w/ relevant markings



Figure 9-4 Body SAR Sample Photo
(Not Actual EUT)

9.4 SAR Evaluations near the Mouth/Jaw Regions of the SAM Phantom

Antennas located near the bottom of a phone may require SAR measurements around the mouth and jaw regions of the SAM head phantom. This typically applies to clam-shell style phones that are generally longer in the unfolded normal use positions or to certain older style long rectangular phones. It has been known for some time that there are SAR measurement difficulties in these regions of the SAM phantom. SAR probes are calibrated in tissue equivalent liquids with sufficient separation between the probe sensors and nearby physical boundaries to ensure scattering does not affect probe calibration. When the probe tip is moved into tight regions with multiple boundaries surrounding its sensors, probe calibration and measurement accuracy can become questionable. In addition, these measurement locations often require a probe to be tilted at steep angles, where it may no longer comply with calibration requirements and measurement protocols, or satisfy the required measurement uncertainty. In some situations it is not feasible to tilt the probe or rotate the phantom, as suggested by measurement standards, to conduct these measurements.




Figure 9-5
SAR Scans near the Jaw/Mouth

In order to ensure there is sufficient conservativeness for ensuring compliance until practical solutions are available, additional measurement considerations are necessary to address these technical difficulties. When measurements are required near the mouth, nose, jaw or similar tight regions of the SAM phantom,

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 13 of 45

area or zoom scans are often unable to fully enclose the peak SAR location as required by IEEE 1528 and Supplement C, due to probe orientation and positioning difficulties. Even when limited measurements are possible, the test results could be questionable due to probe calibration and measurement uncertainty issues. Under these circumstances, the following procedures apply, adopted from the FCC guidance on SAR handsets document publication 648474. The SAR required in these regions of SAM should be measured using a flat phantom. **Rectangular shaped phones** should be positioned with its bottom edge positioned from the flat phantom with the same distance provided by the cheek touching position using SAM. The ear reference point (ERP, as defined for SAM) of the phone should be positioned ½ cm from the flat phantom shell. **Clam-shell phones** should be positioned with the hinge against a smooth edge of the flat phantom where the upper half of the phone is unfolded and extended beyond the phantom side wall. The lower half of the phone is secured in the test device holder at a fixed distance below the flat phantom determined by the minimum separation along the lower edge of the phone in the cheek touching position using SAM. Any case with substantial variation in separation distance along the lower edge of a clam shell is discussed with the FCC for best-to-use methodology.

The flat phantom data should allow test results to be compared uniformly across measurement systems, until suitable solutions are available in measurement standards to address certain probe calibration and positioning issues, due to implementation differences between horizontal and upright SAM configurations. These flat phantom procedures are only applicable for stand-alone SAR evaluation in tight regions of the SAM phantom, where measurement is not feasible or test results can be questionable due to probe calibration and accessibility issues. Details on device positioning and photos showing how separation distances are determined are included in the SAR report Photographs. SAR for other regions of the head must be evaluated using SAM; therefore, a phone with antennas at different locations may require flat and SAM phantom evaluation for the different antennas.

9.5 Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9-4). A device with a headset output is tested with a headset connected to the device.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in head fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 14 of 45

10 FCC RF EXPOSURE LIMITS

10.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

10.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Table 10-1
SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6

HUMAN EXPOSURE LIMITS		
	UNCONTROLLED ENVIRONMENT <i>General Population</i> (W/kg) or (mW/g)	CONTROLLED ENVIRONMENT <i>Occupational</i> (W/kg) or (mW/g)
SPATIAL PEAK SAR Brain	1.6	8.0
SPATIAL AVERAGE SAR Whole Body	0.08	0.4
SPATIAL PEAK SAR Hands, Feet, Ankles, Wrists	4.0	20

1. The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
2. The Spatial Average value of the SAR averaged over the whole body.
3. The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 15 of 45

11 FCC 3G MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital average power.

11.1 Procedures Used to Establish RF Signal for SAR

The following procedures are according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007..

The device was placed into a simulated call using a base station simulator in a RF shielded chamber. Establishing connections in this manner ensure a consistent means for testing SAR and are recommended for evaluating SAR [4]. Devices under test were evaluated prior to testing, with a fully charged battery and were configured to operate at maximum output power. In order to verify that the device was tested throughout the SAR test at maximum output power, the SAR measurement system measures a "point SAR" at an arbitrary reference point at the start and end of the 1 gram SAR evaluation, to assess for any power drifts during the evaluation. Any power drifts of greater than 5% were repeated.

11.2 SAR Measurement Conditions for CDMA2000

The following procedures were performed according to FCC KDB Publication 941225 D01 "SAR Measurement Procedures for 3G Devices" v02, October 2007.

11.2.1 Output Power Verification

See 3GPP2 C.S0011/TIA-98-E as recommended by "SAR Measurement Procedures for 3G Devices" v02, October 2007. Maximum output power is verified on the High, Middle and Low channels according to procedures in section 4.4.5.2 of 3GPP2 C.S0011/TIA-98-E. SO55 tests were measured with power control bits in the "All Up" condition.

1. If the mobile station (MS) supports Reverse TCH RC 1 and Forward TCH RC 1, set up a call using Fundamental Channel Test Mode 1 (RC=1/1) with 9600 bps data rate only.
2. Under RC1, C.S0011 Table 4.4.5.2-1, Table 11-1 parameters were applied.
3. If the MS supports the RC 3 Reverse FCH, RC3 Reverse SCH₀ and demodulation of RC 3,4, or 5, set up a call using Supplemental Channel Test Mode 3 (RC 3/3) with 9600 bps Fundamental Channel and 9600 bps SCH₀ data rate.
4. Under RC3, C.S0011 Table 4.4.5.2-2, Table 11-2 was applied.
5. FCHs were configured at full rate for maximum SAR with "All Up" power control bits.

Table 11-1
Parameters for Max. Power for RC1

Parameter	Units	Value
$\overline{I_{or}}$	dBm/1.23 MHz	-104
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

Table 11-2
Parameters for Max. Power for RC3

Parameter	Units	Value
$\overline{I_{or}}$	dBm/1.23 MHz	-86
$\frac{Pilot E_c}{I_{or}}$	dB	-7
$\frac{Traffic E_c}{I_{or}}$	dB	-7.4

11.2.2 Head SAR Measurements

SAR for head exposure configurations is measured in RC3 with the DUT configured to transmit at full rate using Loopback Service Option SO55. SAR for RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1 using the exposure configuration that results in the highest SAR for that channel in RC3.

FCC ID: IHDT56MP1	 PCTEST Engineering Laboratory, Inc.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 16 of 45

11.2.3 Body SAR Measurements

SAR for body exposure configurations is measured in RC3 with the DUT configured to transmit at full rate on FCH with all other code channels disabled using TDSO / SO32. SAR for multiple code channels (FCH + SCH_n) is not required when the maximum average output of each RF channel is less than ¼ dB higher than that measured with FCH only. Otherwise, SAR is measured on the maximum output channel (FCH + SCH_n) with FCH at full rate and SCH₀ enabled at 9600 bps using the exposure configuration that results in the highest SAR for that channel with FCH only. When multiple code channels are enabled, the DUT output may shift by more than 0.5 dB and lead to higher SAR drifts and SCH dropouts. Body SAR was measured using TDSO / SO32 with power control bits in the “All Up”

Body SAR in RC1 is not required when the maximum average output of each channel is less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel in RC1; with Loopback Service Option SO55, at full rate, using the body exposure configuration that results in the highest SAR for that channel in RC3.

11.2.4 Handsets with EVDO

For handsets with Ev-Do capabilities, when the maximum average output of each channel in Rev. 0 is less than ¼ dB higher than that measured in RC3 (1x RTT), body SAR for EV-DO is not required. Otherwise, SAR for Rev. 0 is measured on the maximum output channel at 153.6 kbps using the body exposure configuration that results in the highest SAR for that channel in RC3. SAR for Rev. A is not required when the maximum average output of each channel is less than that measured in Rev. 0 or less than ¼ dB higher than that measured in RC3. Otherwise, SAR is measured on the maximum output channel for Rev. A using a Reverse Data Channel payload size of 4096 bits and a Termination Target of 16 slots defined for Subtype 2 Physical Layer configurations. A Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots would be configured in the downlink for both Rev. 0 and Rev. A.

11.2.5 Body SAR Measurements for EVDO Hotspot

Hotspot Body SAR is measured using Subtype 0/1 Physical Layer configurations for Rev. 0. SAR for Subtype 2 Physical layer configurations is not required for Rev. A when the maximum average output of each RF channels is less than that measured in Subtype 0/1 Physical layer configurations. Otherwise, SAR is measured on the maximum output channel for Rev. A using the exposure configuration that results in the highest SAR for the RF channels in Rev. 0. The AT is tested with a Reverse Data Channel rate of 153.6 kbps in Subtype 0/1 Physical Layer configurations; and a Reverse Data Channel payload size of 4096 bits and Termination Target of 16 slots in Subtype 2 Physical Layer configurations. Both FTAP and FETAP are configured with a Forward Traffic Channel data rate corresponding to the 2-slot version of 307.2 kbps with the ACK Channel transmitting in all slots. AT power control should be in “All Bits Up” conditions for TAP/ETAP.

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 17 of 45

12 SAR TESTING WITH IEEE 802.11 TRANSMITTERS

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

12.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.

12.2 Frequency Channel Configurations [27]

802.11 b/g/n operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11g/n mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

Table 12-1
802.11 Test Channels per FCC Requirements

Mode	GHz	Channel	Turbo Channel	"Default Test Channels"			
				§15.247		UNII	
				802.11b	802.11g		
802.11 b/g	2.412	1		✓	▽		
	2.437	6	6	✓	▽		
	2.462	11		✓	▽		
802.11a	5.18	36	42 (5.21 GHz)			✓	
	5.20	40					*
	5.22	44					*
	5.24	48	50 (5.25 GHz)			✓	
	5.26	52				✓	
	5.28	56	58 (5.29 GHz)				*
	5.30	60					*
	5.32	64				✓	
	5.500	100	Unknown				*
	5.520	104				✓	
	5.540	108					*
	5.560	112					*
	5.580	116				✓	
	5.600	120					*
	5.620	124				✓	
	5.640	128					*
	5.660	132					*
	5.680	136				✓	
	5.700	140					*
UNII or §15.247	5.745	149		✓		✓	
	5.765	153	152 (5.76 GHz)		*		*
	5.785	157		✓			*
	5.805	161	160 (5.80 GHz)		*	✓	
	§15.247	5.825	165	✓			

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 18 of 45

13 MEASURED RF CONDUCTED POWERS

The maximum conducted power of all modes and bands were measured.

This device additionally uses power reduction for CDMA and WLAN modes. Therefore, additional power measurements were included with power reduction.

13.1 CDMA Conducted Powers

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	820.1	25.09	24.94	24.92	25.01	24.95	24.83
	1013	824.7	24.83	24.69	24.61	24.69	24.79	24.70
	384	835.52	24.92	24.89	24.80	24.72	24.71	24.61
	777	848.31	25.00	24.97	24.97	24.88	24.72	24.69
PCS	25	1851.25	24.35	24.19	24.29	24.13	24.34	24.33
	600	1880	24.40	24.33	24.33	24.26	24.45	24.46
	1175	1908.75	24.39	24.36	24.38	24.28	24.43	24.50

Note: RC1 is only applicable for IS-95 compatibility.

Note: It was confirmed with the manufacturer that the device used for SAR testing with the measured output powers was not overdriven to non-linear operations.

Hardware modifications were not required to be made on the devices in order to obtain reduced output power devices and power measurements, which represented the reduced power levels as would be implemented in Hotspot Mode.

Per KDB Publication 941225 D01:

1. Head SAR was tested with SO55 RC3. SO55 RC1 was not required since the average output power was not more than 0.25 dB than the SO55 RC3 powers. Head SAR was additionally evaluated in the worst case configuration with EVDO Rev. A to cover possible 3rd party applications that support VoIP.
2. Body-Worn SAR was tested with TDSO32 FCH. EVDO and TDSO32 FCH+SCH SAR tests were not required since the average output power was not more than 0.25 dB higher than the TDSO32 FCH powers.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 19 of 45

13.2 CDMA Conducted Powers with Power Reduction

When Hotspot Mode is activated by the end-user, PCS CDMA modes are reduced in output power. See Section 13.7 for more details.

Band	Channel	Frequency	SO55 [dBm]	SO55 [dBm]	TDSO SO32 [dBm]	TDSO SO32 [dBm]	1x EvDO Rev. 0 [dBm]	1x EvDO Rev. A [dBm]
	F-RC	MHz	RC1	RC3	FCH+SCH	FCH	(RTAP)	(RETAP)
Cellular	564	820.1	25.03	24.91	25.00	25.02	24.82	25.00
	1013	824.7	25.24	25.06	25.25	25.25	25.08	25.00
	384	835.52	25.29	25.05	25.23	25.22	25.00	24.97
	777	848.31	25.07	25.00	25.05	25.07	24.90	24.81
PCS	25	1851.25	18.23	17.97	18.01	18.18	18.10	18.18
	600	1880	18.14	17.99	18.09	18.17	18.21	18.14
	1175	1908.75	18.00	18.00	18.00	18.03	18.15	18.05

Note: RC1 is only applicable for IS-95 compatibility.

Note: It was confirmed with the manufacturer that the device used for SAR testing with the measured output powers was not overdriven to non-linear operations.

Note:

1. Per KDB Publication 941225 D01, Hotspot SAR was tested with EVDO Rev 0. EVDO Rev A and TDSO32 SAR tests were not required since the average output power was not more than 0.25 dB higher than the EVDO Rev. 0 powers.



Figure 13-1
Power Measurement Setup

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 20 of 45

13.3 Standalone 2.4 GHz WLAN powers

Table 13-1
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1	18.49	18.43	18.36	18.41
802.11b	2437	6	18.52	18.52	18.50	18.49
802.11b	2462	11	18.58	18.52	18.49	18.50

Table 13-2
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	17.13	17.18	16.73	16.72	14.78	14.65	13.01	13.02
802.11g	2437	6	17.22	17.28	16.86	16.87	14.86	14.69	13.15	13.23
802.11g	2462	11	17.22	17.29	16.87	16.86	14.85	14.72	13.33	13.21

Table 13-3
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11n (800ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	2412	1	16.64	16.63	16.76	14.75	14.76	13.11	13.15	12.34
802.11n	2437	6	16.73	16.85	16.81	14.82	14.85	13.16	13.21	12.40
802.11n	2462	11	16.72	16.81	16.88	14.81	14.80	13.17	13.21	12.31

Mode	Freq [MHz]	Channel	2.4GHz 802.11n (400ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			7.2	14.4	21.7	28.9	43.3	57.8	65.0	72.2
802.11n	2412	1	16.64	16.82	16.75	14.73	14.74	13.15	13.06	12.23
802.11n	2437	6	16.76	16.86	16.83	14.96	14.81	13.18	13.14	12.34
802.11n	2462	11	16.76	16.75	16.84	14.84	14.83	13.18	13.20	12.21

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.

Bold face configurations represent configurations tested for SAR.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 21 of 45

13.4 2.4 GHz WLAN powers with CDMA Transmission

When CDMA Voice is transmitting simultaneously with WLAN, WLAN powers are reduced by 10 dB. See Section 13.6 for more details.

Table 13-4
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1	8.32	8.34	8.31	8.30
802.11b	2437	6	8.46	8.43	8.46	8.45
802.11b	2462	11	8.39	8.45	8.52	8.51

Table 13-5
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	8.05	8.13	8.14	8.19	8.20	8.19	8.21	8.20
802.11g	2437	6	8.23	8.29	8.41	8.39	8.24	8.23	8.25	8.28
802.11g	2462	11	8.38	8.35	8.36	8.35	8.34	8.33	8.36	8.35

Table 13-6
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11n (800ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	2412	1	7.95	7.98	8.06	8.07	8.07	7.98	7.98	8.22
802.11n	2437	6	8.03	8.21	8.22	8.16	8.17	8.09	8.12	8.23
802.11n	2462	11	7.96	8.08	8.05	8.06	8.06	8.11	7.99	8.11
Mode	Freq [MHz]	Channel	2.4GHz 802.11n (400ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			7.2	14.4	21.7	28.9	43.3	57.8	65.0	72.2
802.11n	2412	1	7.93	8.23	8.33	8.28	8.28	8.23	8.21	8.35
802.11n	2437	6	8.05	8.13	8.13	8.07	8.18	8.14	8.00	8.24
802.11n	2462	11	8.06	8.16	8.19	8.10	8.18	8.17	8.15	8.27

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.

Bold face configurations represent configurations tested for simultaneous transmission purposes for CDMA and WLAN.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 22 of 45

13.5 2.4 GHz WLAN powers with Mobile Hotspot

When mobile hotspot is activated, WLAN powers are reduced by 3 dB. See Section 13.7 for more information.

Table 13-7
IEEE 802.11b Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11b Conducted Power [dBm]			
			Data Rate [Mbps]			
			1	2	5.5	11
802.11b	2412	1	15.30	15.44	15.43	15.42
802.11b	2437	6	15.48	15.43	15.48	15.47
802.11b	2462	11	15.42	15.41	15.40	15.50

Table 13-8
IEEE 802.11g Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11g Conducted Power [dBm]							
			Data Rate [Mbps]							
			6	9	12	18	24	36	48	54
802.11g	2412	1	15.22	15.32	15.33	15.32	14.83	14.71	13.25	13.15
802.11g	2437	6	15.28	15.33	15.35	15.33	14.72	14.83	13.25	13.25
802.11g	2462	11	15.25	15.43	15.33	15.32	14.83	14.83	13.22	13.14

Table 13-9
IEEE 802.11n Average RF Power

Mode	Freq [MHz]	Channel	2.4GHz 802.11n (800ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			6.5	13.0	19.5	26.0	39.0	52.0	58.5	65.0
802.11n	2412	1	15.08	15.16	15.16	14.71	14.70	13.04	13.07	12.14
802.11n	2437	6	15.13	15.30	15.27	14.68	14.67	13.13	13.15	12.16
802.11n	2462	11	15.11	15.13	15.22	14.64	14.76	13.10	13.11	12.17

Mode	Freq [MHz]	Channel	2.4GHz 802.11n (400ns) Conducted Power [dBm]							
			Data Rate [Mbps]							
			7.2	14.4	21.7	28.9	43.3	57.8	65.0	72.2
802.11n	2412	1	15.04	15.04	15.12	14.77	14.63	13.08	13.08	12.15
802.11n	2437	6	15.17	15.30	15.31	14.73	14.72	13.24	13.12	12.31
802.11n	2462	11	15.13	15.12	15.23	14.66	14.75	13.12	13.00	12.20

Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.

Bold face configurations represent configurations tested for WLAN SAR in a hotspot condition.



Figure 13-2
Power Measurement Setup

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 23 of 45

13.6 Power Reduction Under Head and Body-Worn Accessory Conditions

When CDMA Voice and WLAN are transmitting simultaneously, WLAN powers are reduced.

Two samples with software-only NV (non-volatile) item changes were provided by the manufacturer with the reduced power for WIFI enabled via manufacturer's software in order to evaluate the SAR with the handset that reflects limited output powers with simultaneous CDMA voice and WLAN transmission scenario (Unit A and Unit X). The reduced powers were confirmed via conducted power measurements at the RF port. Detailed description of the simultaneous CDMA and WIFI power reduction implementation is included in the operational description.

Mode	Power Reduction [dB]
Cell. CDMA - FCC Rule Part 90S	0
Cell. CDMA - FCC Rule Part 22H	0
PCS CDMA - FCC Rule Part 24E	0
WLAN	10

13.7 Mobile Hotspot Scenario

This device utilizes power reduction under portable hotspot conditions for SAR compliance. There is a 7 dB power reduction for PCS CDMA. There is no power reduction for Cellular Band CDMA. There is an additional 3 dB power reduction for WLAN.

Additional samples were provided by the manufacturer programmed with software-only NV (non-volatile) item changes to evaluate the SAR with reduced power under Mobile Hotspot conditions (Unit E and Unit Y). The reduced powers were confirmed via conducted power measurements at the RF port. Detailed description of the Hotspot power reduction implementation is included in the operational description.

Mode	Power Reduction [dB]
Cell. CDMA - FCC Rule Part 90S	0
Cell. CDMA - FCC Rule Part 22H	0
PCS CDMA - FCC Rule Part 24E	7
WLAN	3

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 24 of 45

14 FCC PERSONAL WIRELESS ROUTER CONFIGURATIONS

14.1 Personal Wireless Router Considerations

Some battery-operated handsets have the capability to transmit and receive internet connectivity through simultaneous transmission of WIFI in conjunction with a separate licensed transmitter. The FCC has provided guidance in KDB Publication 941225 D06 where SAR test considerations are based on a composite test separation distance of 10 mm from the edges, front and back of the device with antennas 2.5 cm or closer to the edge of the device, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

14.2 SAR Test Setup for Personal Wireless Router Features

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions. Therefore, SAR must be evaluated for each frequency transmission and mode separately and summed with the WIFI transmitter according to KDB 648474 publication procedures. Therefore, the measurements were performed for each standalone transmitter for the required exposure conditions. The "Portable Hotspot" feature on the handset was NOT activated, to ensure the SAR measurements were valid within a single transmission frequency.

14.3 Power Reduction for Portable Hotspot Mode

There is CDMA and WLAN power reduction for this model when mobile hotspot is activated. See Section 13.7 for details.

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 25 of 45

14.4 SAR Test Configurations

Table 14-1
Mobile Hotspot Sides for SAR Testing

Mobile Hotspot Sides for SAR Testing						
Mode	Back	Front	Top	Bottom	Right	Left
Cell. CDMA - FCC Rule Part 90S	Yes	Yes	No	Yes	Yes	Yes
Cell. CDMA - FCC Rule Part 22H	Yes	Yes	No	Yes	Yes	Yes
PCS CDMA - FCC Rule Part 24E	Yes	Yes	No	Yes	Yes	Yes
2.4 GHz WLAN - FCC Rule Part 15C	Yes	Yes	No	Yes	Yes	No




Figure 14-1 Identification of Sides for SAR Testing (Back View)

Note: Per FCC KDB Publication 941225 D06, the edges with antennas within 2.5 cm are required to be evaluated for SAR. See Figure 14-1 for distances of the actual device.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 26 of 45

15 SYSTEM VERIFICATION

15.1 Tissue Verification

Table 15-1
Measured Tissue Properties

Calibrated for Tests Performed on:	Tissue Type	Measured Frequency (MHz)	Measured Conductivity, σ (S/m)	Measured Dielectric Constant, ϵ	TARGET Conductivity, σ (S/m)	TARGET Dielectric Constant, ϵ	% dev σ	% dev ϵ
06/21/2011	835H	820	0.881	42.55	0.898	41.571	-1.89%	2.36%
		835	0.922	42.19	0.900	41.500	2.44%	1.66%
		850	0.942	42.34	0.916	41.500	2.84%	2.02%
08/22/2011	835H	820	0.880	42.86	0.898	41.571	-2.00%	3.10%
		835	0.902	42.59	0.900	41.500	0.22%	2.63%
		850	0.912	42.32	0.916	41.500	-0.44%	1.98%
06/20/2011	835B	820	0.880	42.86	0.898	41.571	-2.00%	3.10%
		835	0.902	42.59	0.900	41.500	0.22%	2.63%
		850	0.912	42.32	0.916	41.500	-0.44%	1.98%
06/21/2011	1900H	1850	1.390	40.18	1.400	40.000	-0.71%	0.45%
		1880	1.412	40.16	1.400	40.000	0.86%	0.40%
		1910	1.446	39.99	1.400	40.000	3.29%	-0.02%
08/22/2011	1900H	1850	1.389	40.08	1.400	40.000	-0.79%	0.20%
		1880	1.424	40.25	1.400	40.000	1.71%	0.63%
		1910	1.428	40.08	1.400	40.000	2.00%	0.20%
06/22/2011	1900B	1850	1.501	51.48	1.520	53.300	-1.25%	-3.41%
		1880	1.501	51.40	1.520	53.300	-1.25%	-3.56%
		1910	1.529	51.08	1.520	53.300	0.59%	-4.17%
05/26/2011	2450H	2401	1.813	38.95	1.758	39.298	3.13%	-0.89%
		2450	1.879	38.77	1.800	39.200	4.39%	-1.10%
		2499	1.922	38.56	1.852	39.135	3.78%	-1.47%
06/01/2011	2450H	2401	1.755	39.53	1.758	39.298	-0.17%	0.59%
		2450	1.791	39.36	1.800	39.200	-0.50%	0.41%
		2499	1.852	39.06	1.852	39.135	0.00%	-0.19%
06/01/2011	2450B	2401	1.952	50.91	1.903	52.765	2.57%	-3.52%
		2450	2.030	50.77	1.950	52.700	4.10%	-3.66%
		2499	2.086	50.46	2.019	52.638	3.32%	-4.14%
06/07/2011	2450B	2401	1.902	51.20	1.903	52.765	-0.05%	-2.97%
		2450	1.975	50.95	1.950	52.700	1.28%	-3.32%
		2499	2.041	50.80	2.019	52.638	1.09%	-3.49%

Note: KDB Publication 450824 was ensured to be applied for probe calibration frequencies greater than or equal to 50 MHz of the DUT frequencies.

The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies (per IEEE 1528 6.6.1.2). The SAR test plots may slightly differ from the table above since the DASY software rounds to three significant digits.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 27 of 45

15.2 Measurement Procedure for Tissue verification

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity , for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r'\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where Y is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively, $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$, ω is the angular frequency, and $j = \sqrt{-1}$.

15.3 Test System Verification

Prior to assessment, the system is verified to $\pm 10\%$ of the manufacturer SAR measurement on the reference dipole at the time of calibration.

Table 15-2
System Verification Results

System Verification TARGET & MEASURED										
Date:	Amb. Temp (°C)	Liquid Temp (°C)	Input Power (W)	Tissue Frequency (MHz)	Dipole SN	Tissue Type	Measured SAR _{1g} (W/kg)	1 W Target SAR _{1g} (W/kg)	1 W Normalized SAR _{1g} (W/kg)	Deviation (%)
06/21/2011	23.2	22.1	0.100	835	4d047	Head	0.975	9.530	9.750	2.31%
08/22/2011	23.3	22.0	0.250	835	4d047	Head	2.48	9.530	9.920	4.09%
06/20/2011	23.5	22.2	0.100	835	4d047	Body	0.997	9.850	9.970	1.22%
06/21/2011	24.2	22.7	0.040	1900	502	Head	1.6	40.200	40.000	-0.50%
08/22/2011	23.6	22.5	0.040	1900	502	Head	1.57	40.200	39.250	-2.36%
06/22/2011	24.1	22.6	0.040	1900	502	Body	1.63	41.100	40.750	-0.85%
05/26/2011	23.4	22.4	0.0158	2450	797	Head	0.91	53.300	57.595	8.06%
06/01/2011	24.1	22.2	0.0158	2450	797	Head	0.87	53.300	55.063	3.31%
06/01/2011	23.9	22.3	0.0158	2450	797	Body	0.864	52.300	54.684	4.56%
06/07/2011	24.9	23.0	0.0158	2450	797	Body	0.804	52.300	50.886	-2.70%




Figure 15-1
System Verification Setup Diagram



Figure 15-2
System Verification Setup Photo

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 28 of 45

16 SAR DATA SUMMARY

Table 16-1
Cell. CDMA - FCC Rule Part 90S Head SAR Results

MEASUREMENT RESULTS										
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Serial Number	SAR (1g)
MHz	Ch.									(W/kg)
820.10	564	90S	Cell.CDMA	RC3/SO55	24.94	0.04	Right	Touch	Unit X	0.927
820.10	564	90S	Cell.CDMA	EVDO Rev. A	25.00	-0.06	Right	Touch	Unit X	0.838
820.10	564	90S	Cell.CDMA	RC3/SO55	24.94	0.01	Right	Tilt	Unit X	0.642
820.10	564	90S	Cell.CDMA	RC3/SO55	24.94	0.07	Left	Touch	Unit X	0.888
820.10	564	90S	Cell.CDMA	RC3/SO55	24.94	0.02	Left	Tilt	Unit X	0.522
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. CDMA2000 mode was tested under RC3/SO55 per KDB Publication 941225 D01.
7. Per FCC KDB Publication 447498 6)c), only one channel is required since the transmission band is from 817.90 – 823.10 MHz.
8. EVDO Rev.A was tested in the worst case configuration to cover potential 3rd party VoIP applications installed by the end user.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 29 of 45

Table 16-2
Cell. CDMA - FCC Rule Part 22H Head SAR Results

MEASUREMENT RESULTS										
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Serial Number	SAR (1g)
MHz	Ch.									(W/kg)
824.70	1013	22H	Cell. CDMA	RC3/SO55	24.69	-0.01	Right	Touch	Unit X	0.821
836.52	384	22H	Cell. CDMA	RC3/SO55	24.89	-0.03	Right	Touch	Unit X	1.020
848.31	777	22H	Cell. CDMA	RC3/SO55	24.97	0.08	Right	Touch	Unit X	1.000
836.52	384	22H	Cell. CDMA	EVDO Rev. A	24.61	0.00	Right	Touch	Unit X	0.865
836.52	384	22H	Cell. CDMA	RC3/SO55	24.89	0.09	Right	Tilt	Unit X	0.684
824.70	1013	22H	Cell. CDMA	RC3/SO55	24.69	0.02	Left	Touch	Unit X	0.753
836.52	384	22H	Cell. CDMA	RC3/SO55	24.89	0.06	Left	Touch	Unit X	0.930
848.31	777	22H	Cell. CDMA	RC3/SO55	24.97	0.02	Left	Touch	Unit X	0.934
836.52	384	22H	Cell. CDMA	RC3/SO55	24.89	-0.01	Left	Tilt	Unit X	0.571
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. CDMA2000 mode was tested under RC3/SO55 per KDB Publication 941225 D01.
8. EVDO Rev.A was tested in the worst case configuration to cover potential 3rd party VoIP applications installed by the end user.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 30 of 45

Table 16-3
PCS CDMA - FCC Rule Part 24E Head SAR Results

MEASUREMENT RESULTS										
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Side	Test Position	Serial Number	SAR (1g)
MHz	Ch.									(W/kg)
1851.25	25	24E	PCS CDMA	RC3/SO55	24.19	-0.01	Right	Mouth-Jaw	Unit X	1.010
1880.00	600	24E	PCS CDMA	RC3/SO55	24.33	-0.01	Right	Mouth-Jaw	Unit X	0.864
1908.75	1175	24E	PCS CDMA	RC3/SO55	24.36	-0.05	Right	Mouth-Jaw	Unit X	0.974
1880.00	600	24E	PCS CDMA	RC3/SO55	24.33	0.00	Right	Tilt	Unit X	0.358
1851.25	25	24E	PCS CDMA	RC3/SO55	24.19	0.02	Left	Touch	Unit X	1.060
1880.00	600	24E	PCS CDMA	RC3/SO55	24.33	0.03	Left	Touch	Unit X	0.908
1908.75	1175	24E	PCS CDMA	RC3/SO55	24.36	-0.03	Left	Touch	Unit X	1.020
1851.25	25	24E	PCS CDMA	EVDO Rev. A	24.46	0.05	Left	Touch	Unit X	0.963
1880.00	600	24E	PCS CDMA	RC3/SO55	24.33	0.00	Left	Tilt	Unit X	0.354
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration (left, right, cheek/touch, tilt/ear, extended and retracted) is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
7. CDMA2000 mode was tested under RC3/SO55 per KDB Publication 941225 D01.
8. Due to the antenna position in the EUT, the SAR peak locations for the right touch configuration were unable to be captured due to the phantom restrictions. Hence, mouth-jaw test procedures were applied as described in FCC KDB publication 648474 replacing right touch. Please see Section 9.4 for more information.
9. EVDO Rev.A was tested in the worst case configuration to cover potential 3rd party VoIP applications installed by the end user.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 31 of 45

Table 16-4
2.4 GHz WLAN - FCC Rule Part 15C Head SAR Results

MEASUREMENT RESULTS											
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Side	Test Position	Serial Number	Data Rate (Mbps)	SAR (1g)
MHz	Ch.										(W/kg)
2462	11	IEEE 802.11b	DSSS	18.58	-0.01	0	Right	Touch	Unit C	1	0.321
2462	11	IEEE 802.11b	DSSS	18.58	0.08	0	Right	Tilt	Unit C	1	0.048
2462	11	IEEE 802.11b	DSSS	18.58	0.04	0	Left	Touch	Unit C	1	0.091
2462	11	IEEE 802.11b	DSSS	18.58	0.09	0	Left	Tilt	Unit C	1	0.058
2437	6	IEEE 802.11b	DSSS	8.46	0.01	10	Right	Touch	Unit A	1	0.025
2437	6	IEEE 802.11b	DSSS	8.46	0.03	10	Right	Tilt	Unit A	1	0.013
2437	6	IEEE 802.11b	DSSS	8.46	0.08	10	Left	Touch	Unit A	1	0.017
2437	6	IEEE 802.11b	DSSS	8.46	0.08	10	Left	Tilt	Unit A	1	0.012
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Head 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth was at least 15.0 cm.
6. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
7. WLAN transmission was verified using a spectrum analyzer.
8. Maximum power WLAN was tested to cover standalone transmission for VoIP services.
9. Reduced Power WLAN (-10 dB) was tested for simultaneous transmission purposes to address the CDMA Voice + WLAN scenario (see Section 13.6)

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN	Page 32 of 45	

**Table 16-5
Body-Worn SAR Results**

MEASUREMENT RESULTS											
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Power Drift [dB]	Spacing	Serial Number	Side	SAR (1g)
MHz	Ch.										(W/kg)
820.10	564	90S	Cell. CDMA	TDSO32	25.01	0.00	N/A	2.5 cm	Unit X	back	0.668
836.52	384	22H	Cell. CDMA	TDSO32	24.72	0.02	N/A	2.5 cm	Unit X	back	0.732
1880.00	600	24E	PCS CDMA	TDSO32	24.26	0.00	N/A	2.5 cm	Unit X	back	0.439
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population								Body 1.6 W/kg (mW/g) averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
5. Liquid tissue depth was at least 15.0 cm.
6. A separation distance of 25 mm is chosen because Motorola has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
7. Body-Worn SAR was tested under RC3/SO32 with FCH only since FCH+SCH modes are not greater than 0.25 dB of the FCH only mode per KDB Publication 941225 D01.
8. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438 for Part 22H and 24E, if the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
9. Per FCC KDB Publication 447498 6)c), only one channel is required for Part 90S since the transmission band is from 817.90 – 823.10 MHz.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 33 of 45

Table 16-6
Cell. CDMA Hotspot SAR Results

MEASUREMENT RESULTS											
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	Side	SAR (1g)
MHz	Ch.										(W/kg)
820.10	564	90S	Cell.CDMA	EVDO	24.82	0.06	0	1.0 cm	Unit Y	back	1.250
820.10	564	90S	Cell.CDMA	EVDO	24.82	-0.01	0	1.0 cm	Unit Y	front	1.040
820.10	564	90S	Cell.CDMA	EVDO	24.82	-0.06	0	1.0 cm	Unit Y	bottom	0.045
820.10	564	90S	Cell.CDMA	EVDO	24.82	0.02	0	1.0 cm	Unit Y	right	0.833
820.10	564	90S	Cell.CDMA	EVDO	24.82	-0.09	0	1.0 cm	Unit Y	left	0.778
824.70	1013	22H	Cell.CDMA	EVDO	25.08	-0.02	0	1.0 cm	Unit Y	back	1.180
836.52	384	22H	Cell.CDMA	EVDO	25.00	0.01	0	1.0 cm	Unit Y	back	1.370
848.31	777	22H	Cell.CDMA	EVDO	24.90	0.01	0	1.0 cm	Unit Y	back	1.300
824.70	1013	22H	Cell.CDMA	EVDO	25.08	-0.04	0	1.0 cm	Unit Y	front	1.020
836.52	384	22H	Cell.CDMA	EVDO	25.00	-0.03	0	1.0 cm	Unit Y	front	1.020
848.31	777	22H	Cell.CDMA	EVDO	24.90	-0.07	0	1.0 cm	Unit Y	front	1.070
836.52	384	22H	Cell.CDMA	EVDO	25.00	0.06	0	1.0 cm	Unit Y	bottom	0.051
824.70	1013	22H	Cell.CDMA	EVDO	25.08	0.00	0	1.0 cm	Unit Y	right	0.857
836.52	384	22H	Cell.CDMA	EVDO	25.00	0.06	0	1.0 cm	Unit Y	right	0.949
848.31	777	22H	Cell.CDMA	EVDO	24.90	-0.10	0	1.0 cm	Unit Y	right	0.905
824.70	1013	22H	Cell.CDMA	EVDO	25.08	0.05	0	1.0 cm	Unit Y	left	0.752
836.52	384	22H	Cell.CDMA	EVDO	25.00	0.03	0	1.0 cm	Unit Y	left	0.855
848.31	777	22H	Cell.CDMA	EVDO	24.90	-0.10	0	1.0 cm	Unit Y	left	0.741
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body			
Spatial Peak								1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population								averaged over 1 gram			

Notes:

- The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
- All modes of operation were investigated, and worst-case results are reported.
- Tissue parameters and temperatures are listed on the SAR plots.
- Batteries are fully charged for all readings. Standard battery (BP7X) was used.
- Liquid tissue depth was at least 15.0 cm.
- Device was tested using a fixed spacing.
- CDMA Hotspot Body SAR was tested under EVDO Rev. 0 per FCC 3G Guidance (See Section 11.2.5) per FCC KDB Publication 941225 D01. EVDO Rev A and TDS032 SAR tests were not required since the average output power was not more than 0.25 dB higher than the EVDO Rev. 0 powers.
- Justification for reduced test configurations for Part 22H: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
- Top Edge was not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 guidance (see Section 14.4).
- SAR evaluation requires a single frequency of measurement for valid measurements using the SAR probe and tissue calibrated which are calibrated for specific limited frequency ranges. Therefore, during SAR evaluation it was ensured that the WIFI transmission was disabled by the manufacturer to assess the standalone SAR to be evaluated for SAR. WIFI SAR was separately evaluated to account for the WIFI SAR for portable hotspot exposure conditions (See Section 14).
- Per FCC KDB Publication 447498 6)c), only one channel is required for Part 90S since the transmission band is from 817.90 – 823.10 MHz.
- There is no power reduction for Cell. CDMA transmission in hotspot mode.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN	Page 34 of 45	

Table 16-7
PCS Hotspot SAR Results

MEASUREMENT RESULTS											
FREQUENCY		FCC Rule Part	Mode/Band	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	Side	SAR (1g)
MHz	Ch.										(W/kg)
1880.00	600	24E	PCS. CDMA	EVDO	18.21	0.00	7.0	1.0 cm	Unit Y	back	0.624
1880.00	600	24E	PCS. CDMA	EVDO	18.21	0.01	7.0	1.0 cm	Unit Y	front	0.417
1880.00	600	24E	PCS. CDMA	EVDO	18.21	-0.09	7.0	1.0 cm	Unit Y	bottom	0.730
1880.00	600	24E	PCS. CDMA	EVDO	18.21	0.04	7.0	1.0 cm	Unit Y	right	0.024
1880.00	600	24E	PCS. CDMA	EVDO	18.21	0.00	7.0	1.0 cm	Unit Y	left	0.087
ANSI / IEEE C95.1 1992 - SAFETY LIMIT								Body			
Spatial Peak								1.6 W/kg (mW/g)			
Uncontrolled Exposure/General Population								averaged over 1 gram			

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001]
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
5. Liquid tissue depth was at least 15.0 cm.
6. Device was tested using a fixed spacing.
7. CDMA Hotspot Body SAR was tested under EVDO Rev. 0 per FCC 3G Guidance (See Section 11.2.5) per FCC KDB Publication 941225 D01. EVDO Rev A and TDSO32 SAR tests were not required since the average output power was not more than 0.25 dB higher than the EVDO Rev. 0 powers.
8. Justification for reduced test configurations: Per FCC/OET Bulletin 65 Supplement C (June 2001) and Public Notice DA-02-1438, if the SAR measured at the middle channel for each test configuration is at least 3.0 dB lower than the SAR limit, testing at the high and low channels is optional for such test configuration(s).
9. Top Edge was not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 guidance (see Section 14.4).
10. SAR evaluation requires a single frequency of measurement for valid measurements using the SAR probe and tissue calibrated which are calibrated for specific limited frequency ranges. Therefore, during SAR evaluation it was ensured that the WIFI transmission was disabled by the manufacturer to assess the standalone SAR to be evaluated for SAR. WIFI SAR was separately evaluated to account for the WIFI SAR for portable hotspot exposure conditions (See Section 14).
11. PCS powers are reduced in mobile hotspot mode. See Section 13.7 for more information.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN	Page 35 of 45	

Table 16-8
2.4 GHz WLAN Body-Worn SAR Results

MEASUREMENT RESULTS											
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.										(W/kg)
2462	11	IEEE 802.11b	DSSS	18.58	0.06	0	2.5 cm	Unit C	1	back	0.014
2437	6	IEEE 802.11b	DSSS	8.46	0.06	10	2.5 cm	Unit A	1	back	0.0001
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is was at least 15.0 cm.
6. A separation distance of 25 mm is chosen because Motorola has determined that it supports the types of body-worn accessories available in the marketplace to users for this handset.
7. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
8. WLAN transmission was verified using a spectrum analyzer.
9. Maximum power WLAN was tested to cover standalone transmission for VoIP services.
10. Reduced Power WLAN (-10 dB) was tested for simultaneous transmission purposes to address the CDMA Voice + WLAN scenario (see Section 13.6).

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 36 of 45

Table 16-9
Hotspot 2.4 GHz Body SAR Results

MEASUREMENT RESULTS											
FREQUENCY		Mode	Service	Conducted Power [dBm]	Power Drift [dB]	Power Reduction [dB]	Spacing	Serial Number	Data Rate (Mbps)	Side	SAR (1g)
MHz	Ch.										(W/kg)
2437	6	IEEE 802.11b	DSSS	15.48	0.01	3	1.0 cm	Unit E	1	back	0.056
2437	6	IEEE 802.11b	DSSS	15.48	0.06	3	1.0 cm	Unit E	1	front	0.045
2437	6	IEEE 802.11b	DSSS	15.48	0.06	3	1.0 cm	Unit E	1	bottom	0.032
2437	6	IEEE 802.11b	DSSS	15.48	0.00	3	1.0 cm	Unit E	1	right	0.056
ANSI / IEEE C95.1 1992 - SAFETY LIMIT Spatial Peak Uncontrolled Exposure/General Population							Body 1.6 W/kg (mW/g) averaged over 1 gram				

Notes:

1. The test data reported are the worst-case SAR value with the position set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [June 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Batteries are fully charged for all readings. Standard battery (BP7X) was used.
4. Tissue parameters and temperatures are listed on the SAR plots.
5. Liquid tissue depth is was at least 15.0 cm.
6. Device was tested using a fixed spacing.
7. Justification for reduced test configurations for WIFI channels per KDB Publication 248227 and April 2010 FCC/TCB Meeting Notes: Highest average RF output power channel for the lowest data rate were selected for SAR evaluation. Other IEEE 802.11 modes (including 802.11g/n) were not investigated since the average output powers were not greater than 0.25 dB than that of the corresponding channel in the lowest data rate IEEE 802.11b mode.
8. WLAN transmission was verified using a spectrum analyzer.
9. Top and Left Edges were not tested since the antenna distance from the edge was greater than 2.5 cm per FCC KDB Publication 941225 D06 (see Section 14.4).
10. WLAN powers are reduced in mobile hotspot mode. See Section 13.7 for more information.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 37 of 45

17 FCC MULTI-TX AND ANTENNA SAR CONSIDERATIONS

17.1 Introduction

The following procedures adopted from “FCC SAR Considerations for Cell Phones with Multiple Transmitters” FCC KDB Publication 648474 are applicable to handsets with built-in unlicensed transmitters such as 802.11a/b/g and Bluetooth devices which may simultaneously transmit with the licensed transmitter.

17.2 FCC Power Tables & Conditions

	2.45	5.15 - 5.35	5.47 - 5.85	GHz
P_{Ref}	12	6	5	mW
Device output power should be rounded to the nearest mW to compare with values specified in this table.				

Figure 17-1
Output Power Thresholds for Unlicensed Transmitters

	Individual Transmitter	Simultaneous Transmission
Licensed Transmitters	<u>Routine evaluation required</u>	SAR not required: <u>Unlicensed only</u> - when stand-alone 1-g SAR is not required and antenna is ≥ 5 cm from other antennas Licensed & Unlicensed - when the sum of the 1-g SAR is < 1.6 W/kg for all simultaneous transmitting antennas - when SAR to peak location separation ratio of simultaneous transmitting antenna pair is < 0.3
Unlicensed Transmitters	When there is no simultaneous transmission – - output ≤ 60/f: SAR not required - output > 60/f: stand-alone SAR required When there is simultaneous transmission – <u>Stand-alone SAR not required when</u> - output $\leq 2 \cdot P_{Ref}$ and antenna is ≥ 5.0 cm from other antennas - output $\leq P_{Ref}$ and antenna is ≥ 2.5 cm from other antennas - output $\leq P_{Ref}$ and antenna is < 2.5 cm from other antennas, each with either output power $\leq P_{Ref}$ or 1-g SAR < 1.2 W/kg <u>Otherwise stand-alone SAR is required</u> When stand-alone SAR is required - test SAR on highest output channel for each wireless mode and exposure condition - if SAR for highest output channel is $> 50\%$ of SAR limit, evaluate all channels according to normal procedures	SAR required: Licensed & Unlicensed antenna pairs with SAR to peak location separation ratio ≥ 0.3; test is only required for the configuration that results in the highest SAR in stand-alone configuration for each wireless mode and exposure condition Note: simultaneous transmission exposure conditions for head and body can be different for different style phones; therefore, different test requirements may apply

Figure 17-2
SAR Evaluation Requirements for Multiple Transmitter Handsets

17.3 Multiple Antenna/Transmission Information

The separation between the main antenna and the Bluetooth and WLAN antennas is 13.44 mm. RF Conducted Power of Bluetooth Tx is 11.858 mW. RF Conducted Power of WLAN is 72.11 mW.

Bluetooth can transmit simultaneously with the CDMA/EVDO Main antenna but cannot transmit simultaneously with the WLAN antenna (same RF path).

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 38 of 45

17.4 Simultaneous Transmission Analysis

Based on the output power, antenna separation distance and the Body SAR of the dominant transmitter, a stand-alone Bluetooth SAR test is not required while for WLAN it is required.

Table 17-1
Simultaneous Transmission Scenario (Held to Ear)

Simult Tx	Configuration	Cell. CDMA - FCC Rule Part 90S SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)	Simult Tx	Configuration	Cell. CDMA - FCC Rule Part 22H SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	0.927	0.025	0.952	Head SAR	Right Cheek	1.020	0.025	1.045
	Right Tilt	0.642	0.013	0.655		Right Tilt	0.684	0.013	0.697
	Left Cheek	0.888	0.017	0.905		Left Cheek	0.934	0.017	0.951
	Left Tilt	0.522	0.012	0.534		Left Tilt	0.571	0.012	0.583

Simult Tx	Configuration	PCS CDMA - FCC Rule Part 24E SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Head SAR	Right Cheek	1.010	0.025	1.035
	Right Tilt	0.358	0.013	0.371
	Left Cheek	1.060	0.017	1.077
	Left Tilt	0.354	0.012	0.366

Note:

1. This simultaneous transmission scenario represents a held-to-ear voice call with WLAN data.
2. WLAN is reduced by 10 dB when transmitting simultaneously with a voice call. See Section 13.6 for more details.

Table 17-2
Simultaneous Transmission Scenario (Body-Worn at 2.5 cm)

Configuration	Mode	2G/3G SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Back Side	Cell. CDMA - FCC Rule Part 90S	0.668	0.000	0.668
Back Side	Cell. CDMA - FCC Rule Part 22H	0.732	0.000	0.732
Back Side	PCS CDMA - FCC Rule Part 24E	0.439	0.000	0.439

Note:

1. This simultaneous transmission scenario represents a body-worn voice call with WLAN data.
2. WLAN is reduced by 10 dB when transmitting simultaneously with a voice call. See Section 13.6 for more details.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 39 of 45

Table 17-3
Simultaneous Transmission Scenario (Hotspot)

Simult Tx	Configuration	Cell. CDMA - FCC Rule Part 90S SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	1.250	0.056	1.306
	Front	1.040	0.045	1.085
	Top	-	-	0.000
	Bottom	0.045	0.032	0.077
	Right	0.833	0.056	0.889
	Left	0.778	-	0.778
Simult Tx	Configuration	Cell. CDMA - FCC Rule Part 22H SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	1.370	0.056	1.426
	Front	1.070	0.045	1.115
	Top	-	-	0.000
	Bottom	0.051	0.032	0.083
	Right	0.949	0.056	1.005
	Left	0.855	-	0.855
Simult Tx	Configuration	PCS CDMA - FCC Rule Part 24E SAR (W/kg)	WIFI SAR (W/kg)	Σ SAR (W/kg)
Body SAR	Back	0.624	0.056	0.680
	Front	0.417	0.045	0.462
	Top	-	-	0.000
	Bottom	0.730	0.032	0.762
	Right	0.024	0.056	0.080
	Left	0.087	-	0.087

Note:

1. Per FCC KDB Publication 941225 D06, the edges with antennas more than 2.5 cm are not required to be evaluated for SAR (“-”).
2. This simultaneous transmission scenario represents mobile hotspot transmissions.
3. PCS CDMA band reduces by 7 dB and WLAN reduces by 3 dB when hotspot power reduction is enabled. See Section 13.7 for more details.

17.5 Simultaneous Transmission Conclusion

The above numerical summed SAR was below the SAR limit. Therefore, the above analysis is sufficient to determine that simultaneous transmission cases will not exceed the SAR limit. Therefore, no volumetric SAR summation is required per FCC KDB Publication 648474.

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN	Page 40 of 45	

18 EQUIPMENT LIST

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	85070B	Dielectric Probe Kit	8/22/2010	Annual	8/22/2011	US33020316
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/13/2010	Annual	10/13/2011	3613A00315
Agilent	8753E	(30kHz-6GHz) Network Analyzer	4/21/2011	Annual	4/21/2012	JP38020182
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46110872
Agilent	E5515C	Wireless Communications Test Set	10/8/2010	Annual	10/8/2011	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	4/8/2011	Annual	4/8/2012	MY45470194
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/11/2010	Annual	10/11/2011	1833460
Gigatronics	8651A	Universal Power Meter	10/11/2010	Annual	10/11/2011	8650319
Rohde & Schwarz	CMU200	Base Station Simulator	11/11/2010	Annual	11/11/2011	836371/0079
Rohde & Schwarz	CMU200	Base Station Simulator	6/1/2011	Annual	6/1/2012	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	4/19/2011	Annual	4/19/2012	107826
Rohde & Schwarz	NRVD	Dual Channel Power Meter	4/8/2011	Biennial	4/8/2013	101695
SPEAG	D1765V2	1765 MHz SAR Dipole	6/16/2011	Annual	6/16/2012	1008
SPEAG	D1900V2	1900 MHz SAR Dipole	2/17/2011	Annual	2/17/2012	502
SPEAG	D1900V2	1900 MHz SAR Dipole	8/18/2009	Biennial	8/18/2011	5d080
SPEAG	D2450V2	2450 MHz SAR Dipole	8/27/2009	Biennial	8/27/2011	719
SPEAG	D2450V2	2450 MHz SAR Dipole	2/8/2011	Annual	2/8/2012	797
SPEAG	D2600V2	2600 MHz SAR Dipole	4/15/2011	Annual	4/15/2012	1004
SPEAG	D5GHzV2	5 GHz SAR Dipole	8/19/2009	Biennial	8/19/2011	1007
SPEAG	D5GHzV2	5 GHz SAR Dipole	2/11/2011	Annual	2/11/2012	1057
SPEAG	D835V2	835 MHz SAR Dipole	2/9/2011	Annual	2/9/2012	4d047
SPEAG	D835V2	835 MHz SAR Dipole	8/24/2009	Biennial	8/24/2011	4d026
SPEAG	DAE3	Dasy Data Acquisition Electronics	11/18/2010	Annual	11/18/2011	455
SPEAG	DAE4	Dasy Data Acquisition Electronics	3/17/2011	Annual	3/17/2012	704
SPEAG	DAE4	Dasy Data Acquisition Electronics	4/20/2011	Annual	4/20/2012	665
SPEAG	DAE4	Dasy Data Acquisition Electronics	2/21/2011	Annual	2/21/2012	649
SPEAG	ES3DV2	SAR Probe	9/21/2010	Annual	9/21/2011	3022
SPEAG	EX3DV4	SAR Probe	8/19/2010	Annual	8/19/2011	3561
SPEAG	EX3DV4	SAR Probe	2/14/2011	Annual	2/14/2012	3550
SPEAG	DAE4	Dasy Data Acquisition Electronics	5/19/2011	Annual	5/19/2012	859
SPEAG	D750V3	750 MHz Dipole	2/14/2011	Annual	2/14/2012	1003
SPEAG	ES3DV3	SAR Probe	3/24/2011	Annual	3/24/2012	3213
SPEAG	ES3DV3	SAR Probe	4/18/2011	Annual	4/18/2012	3209
Rohde & Schwarz	SMIQ03B	Signal Generator	4/6/2011	Annual	4/6/2012	DE27259
SPEAG	D1640V2	1640 MHz Dipole	8/17/2010	Annual	8/17/2011	321
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	8/30/2010	Annual	8/30/2011	100976
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5318
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5442
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1190013
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	98150041
Agilent	8648D	Signal Generator	4/5/2011	Annual	4/5/2012	3629U00687
Anritsu	ML2438A	Power Meter	2/7/2011	Annual	2/7/2012	1070030
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5821
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	8013
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	5605
Anritsu	MA2481A	Power Sensor	2/7/2011	Annual	2/7/2012	2400
Agilent	E5515C	Wireless Communications Test Set	8/13/2010	Annual	8/13/2011	GB43304447
Agilent	E5515C	Wireless Communications Tester	4/21/2011	Annual	4/21/2012	US41140256
Amplifier Research	551G4	5W, 800MHz-4.2GHz	N/A			21910
Mini-Circuits	BW-N20W5+	DC to 18 GHz Precision Fixed 20 dB Attenuator	N/A			N/A
Agilent	E5515C	Wireless Communications Test Set	2/8/2011	Annual	2/8/2012	GB45360985
SPEAG	D3700V2	3700 MHz SAR Dipole	2/16/2011	Annual	2/16/2012	1002
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	3/11/2011	Annual	3/11/2012	103962
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331322
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331323
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331330
Control Company	61220-416	Long-Stem Thermometer	2/15/2011	Biennial	2/15/2013	111331332
Control Company	61220-416	Long-Stem Thermometer	3/16/2011	Biennial	3/16/2013	111391601
SPEAG	ES3DV3	SAR Probe	4/8/2011	Annual	4/8/2012	3258
SPEAG	D1750V2	1750 MHz SAR Dipole	5/24/2011	Annual	5/24/2012	1051
MiniCircuits	SLP-2400+	Low Pass Filter	N/A			R8979500903
MiniCircuits	NLP-1.9+	Low Pass Filter	N/A			N/A
Narda	4772-3	Attenuator (3dB)	N/A			9406
Narda	BW-S3W2	Attenuator (3dB)	N/A			120

All equipment used was confirmed to be calibrated for all days used for testing.

FCC ID: IHD756MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 41 of 45

19 MEASUREMENT UNCERTAINTIES

Applicable for 750 – 3000 MHz.

a	b	c	d	e= f(d,k)	f	g	h = c x f/e	i = c x g/e	k
Uncertainty Component	IEEE 1528 Sec.	Tol. (± %)	Prob. Dist.	Div.	c _i 1gm	c _i 10 gms	1gm u _i (± %)	10gms u _i (± %)	v _i
Measurement System									
Probe Calibration	E.2.1	6.0	N	1	1.0	1.0	6.0	6.0	∞
Axial Isotropy	E.2.2	0.25	N	1	0.7	0.7	0.2	0.2	∞
Hemishperical Isotropy	E.2.2	1.3	N	1	1.0	1.0	1.3	1.3	∞
Boundary Effect	E.2.3	0.4	N	1	1.0	1.0	0.4	0.4	∞
Linearity	E.2.4	0.3	N	1	1.0	1.0	0.3	0.3	∞
System Detection Limits	E.2.5	5.1	N	1	1.0	1.0	5.1	5.1	∞
Readout Electronics	E.2.6	1.0	N	1	1.0	1.0	1.0	1.0	∞
Response Time	E.2.7	0.8	R	1.73	1.0	1.0	0.5	0.5	∞
Integration Time	E.2.8	2.6	R	1.73	1.0	1.0	1.5	1.5	∞
RF Ambient Conditions	E.6.1	3.0	R	1.73	1.0	1.0	1.7	1.7	∞
Probe Positioner Mechanical Tolerance	E.6.2	0.4	R	1.73	1.0	1.0	0.2	0.2	∞
Probe Positioning w/ respect to Phantom	E.6.3	2.9	R	1.73	1.0	1.0	1.7	1.7	∞
Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation	E.5	1.0	R	1.73	1.0	1.0	0.6	0.6	∞
Test Sample Related									
Test Sample Positioning	E.4.2	6.0	N	1	1.0	1.0	6.0	6.0	287
Device Holder Uncertainty	E.4.1	3.32	R	1.73	1.0	1.0	1.9	1.9	∞
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	1.73	1.0	1.0	2.9	2.9	∞
Phantom & Tissue Parameters									
Phantom Uncertainty (Shape & Thickness tolerances)	E.3.1	4.0	R	1.73	1.0	1.0	2.3	2.3	∞
Liquid Conductivity - deviation from target values	E.3.2	5.0	R	1.73	0.64	0.43	1.8	1.2	∞
Liquid Conductivity - measurement uncertainty	E.3.3	3.8	N	1	0.64	0.43	2.4	1.6	6
Liquid Permittivity - deviation from target values	E.3.2	5.0	R	1.73	0.60	0.49	1.7	1.4	∞
Liquid Permittivity - measurement uncertainty	E.3.3	4.5	N	1	0.60	0.49	2.7	2.2	6
Combined Standard Uncertainty (k=1)							RSS	12.1	11.7
Expanded Uncertainty (95% CONFIDENCE LEVEL)							k=2	24.2	23.5
									299

The above measurement uncertainties are according to IEEE Std. 1528-2003

FCC ID: IHDT56MP1	 PCTEST ENGINEERING LABORATORY, INC.	SAR COMPLIANCE REPORT	 MOTOROLA	Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN	Page 42 of 45	

20 CONCLUSION

20.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Industry Canada, with respect to all parameters subject to this test. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: 0Y1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 43 of 45

21 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, June 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.
- [16] W. Gander, Computermathematik, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Recipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 44 of 45

- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 4, March 2010.
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Measurement Procedures for 3G Devices KDB Publication 941225
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB Publication 248227
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB Publication 648474
- [29] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, KDB Publication 450824
- [30] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, KDB Publication 616217
- [31] FCC SAR Measurement Requirements for 3 – 6 GHz, KDB Publication 865664
- [32] FCC Mobile Portable RF Exposure Procedure, KDB Publication 447498
- [33] FCC SAR Procedures for Dongle Transmitters, KDB Publication 447498
- [34] Anexo à Resolução No. 533, de 10 de Setembro de 2009.
- [35] FCC SAR Test Considerations for LTE Handsets and Data Modems, KDB Publication 941225.
- [36] IEC 62209-2, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 2: Procedure to determine the specific absorption rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz), Mar. 2010.
- [37] FCC D06 Hot Spot SAR v01, KDB Publication 941225.

FCC ID: IHDT56MP1		SAR COMPLIANCE REPORT		Reviewed by: Quality Manager
Filename: OY1105170871-R6.IHD	Test Dates: 05/26/11 - 06/22/11, 08/22/11	EUT Type: Cellular/PCS CDMA/EVDO Phone with Bluetooth and WLAN		Page 45 of 45