



FCC RF Test Report

APPLICANT : Motorola Mobility, LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : 4602
FCC ID : IHDT56UB1
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : (DTS) Digital Transmission System

The product was received on May 01, 2015 and testing was completed on Jun. 15, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1 Applicant	5
1.2 Manufacturer	5
1.3 Product Feature of Equipment Under Test	5
1.4 Product Specification subjective to this standard	6
1.5 Modification of EUT	6
1.6 Testing Location	6
1.7 Applicable Standards	7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	8
2.1 Carrier Frequency Channel	8
2.2 Pre-Scanned RF Power	9
2.3 Test Mode	10
2.4 Connection Diagram of Test System	11
2.5 Support Unit used in test configuration and system	13
2.6 EUT Operation Test Setup	13
2.7 Measurement Results Explanation Example	14
3 TEST RESULT	15
3.1 6dB Bandwidth Measurement	15
3.2 Output Power Measurement	17
3.3 Power Spectral Density Measurement	18
3.4 Conducted Band Edges and Spurious Emission Measurement	20
3.5 Radiated Band Edges and Spurious Emission Measurement	30
3.6 AC Conducted Emission Measurement	34
3.7 Antenna Requirements	44
4 LIST OF MEASURING EQUIPMENT	45
5 UNCERTAINTY OF EVALUATION	46
APPENDIX A. CONDUCTED TEST RESULTS	
APPENDIX B. RADIATED TEST RESULTS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR550147C	Rev. 01	Initial issue of report	Jul. 01, 2015



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	$\geq 0.5\text{MHz}$	Pass	-
3.2	15.247(b)	Power Output Measurement	$\leq 30\text{dBm}$	Pass	-
3.3	15.247(e)	Power Spectral Density	$\leq 8\text{dBm}/3\text{kHz}$	Pass	-
3.4	15.247(d)	Conducted Band Edges	$\leq 20\text{dBc}$	Pass	-
		Conducted Spurious Emission		Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 0.83 dB at 2483.960 MHz
3.6	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 8.10 dB at 2.862 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.2 Manufacturer

Motorola Mobility, LLC

222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	4602
FCC ID	IHDT56UB1
IMEI Code	990006240086388 (for AC Conducted Emission) 990006240060151 (for Radiated Spurious Emission)
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/NFC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth 2.1 EDR Bluetooth 4.1 - LE
HW Version	P2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
AC Adapter 1	Brand Name : Motorola
	Model Name : SPN5791A
AC Adapter 2	Brand Name : Motorola
	Model Name : SPN5865A
Battery	Brand Name : Motorola
	Model Name : FL40
USB Cable	Brand Name : Motorola
	Model Name : SKN6461A
Earphone	Brand Name : Motorola
	Model Name : 89719N

1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to Antenna	802.11b : 23.41 dBm (0.2193 W) 802.11g : 23.56 dBm (0.2270 W) 802.11n HT20 : 23.55 dBm (0.2265 W)
Antenna Type	Fixed, stamped metal Antenna type (The antenna peak gain of EUT is less than 6 dBi)
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	Sporton Site No.		
	TH02-HY	CO05-HY	03CH07-HY

Note: The test site complies with ANSI C63.4 2009 requirement.



1.7 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
- ♦ ANSI C63.10-2009

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. FCC permits the use of the 1.5 meter table as an alternative in C63.10-2013 through inquiry tracking number 961829.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The final configuration from all the combinations and the worst-case data rates were investigated by measuring the maximum power across all the data rates and modulation modes under section 2.2.

Based on the worst configuration found above, the RF power setting is set individually to meet FCC compliance limit for the final conducted and radiated tests shown in section 2.3.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437	-	-

2.2 Pre-Scanned RF Power

Preliminary tests were performed in different data rate and data rate associated with the highest power were chosen for full test shown in the following tables.

Channel	Frequency	2.4GHz 802.11b RF Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412MHz	22.63	22.59	22.61	22.44
CH 06	2437MHz	22.62	22.61	22.60	22.61
CH 11	2462MHz	23.41	22.33	22.37	22.36

Channel	Frequency	2.4GHz 802.11b Average Power (dBm)			
		DSSS Data Rate			
		1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
CH 01	2412MHz	20.34	20.21	20.32	20.23
CH 06	2437MHz	20.12	20.11	20.09	20.07
CH 11	2462MHz	20.17	20.15	20.15	20.09

Channel	Frequency	2.4GHz 802.11g RF Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412MHz	23.52	23.44	23.42	23.47	23.42	23.32	22.78	22.67
CH 06	2437MHz	23.56	23.47	23.55	23.44	23.54	23.34	23.15	22.94
CH 11	2462MHz	22.87	22.74	22.76	22.78	22.82	22.71	22.62	22.48

Channel	Frequency	2.4GHz 802.11g Average Power (dBm)							
		OFDM Data Rate							
		6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
CH 01	2412MHz	17.31	17.27	17.25	17.29	17.25	16.53	15.41	15.01
CH 06	2437MHz	17.34	17.19	17.29	17.29	17.26	16.51	15.49	14.79
CH 11	2462MHz	16.10	16.00	16.05	16.08	16.03	15.97	14.99	14.37

Channel	Frequency	2.4GHz 802.11n HT20 RF Power (dBm)							
		OFDM Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412MHz	23.39	23.26	23.27	23.31	23.29	22.83	22.33	21.78
CH 06	2437MHz	23.55	23.42	23.32	23.45	23.50	23.16	22.85	22.33
CH 11	2462MHz	23.01	22.86	22.91	22.94	22.96	22.73	22.53	22.13

Channel	Frequency	2.4GHz 802.11n HT20 Average Power (dBm)							
		OFDM Data Rate							
		MCS0	MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7
CH 01	2412MHz	17.09	16.89	16.81	16.82	16.78	15.21	13.96	13.03
CH 06	2437MHz	16.97	16.94	16.95	16.77	16.96	15.49	14.24	13.22
CH 11	2462MHz	16.13	16.08	16.06	16.09	15.93	14.81	13.88	12.74

2.3 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates from the power table described in section 2.2.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0

Test Cases	
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 1) + MP3
	Mode 2: GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3
Remark: The worst case of conducted emission is mode 2; only the test data of it was reported.	


2.4 Connection Diagram of Test System

<WLAN Tx Mode>


<EUT Standalone>



<For Adapter 1>




<For Adapter 2>




<AC Conducted Emission Mode>

<For Adapter 1>



<For Adapter 2>



2.5 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
3.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	Mobile Cellular Phone	Motorola	4602	IHDT56UB1	N/A	N/A
6.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.6 EUT Operation Test Setup

For WLAN function, programmed RF utility, "QRCT" installed in the EUT provide functions like channel selection and power level for continuous transmitting and receiving signals.



2.7 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned}\text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)}\end{aligned}$$

3 Test Result

3.1 6dB Bandwidth Measurement

3.1.1 Limit of 6dB Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures


1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Occupied Bandwidth

Please refer to Appendix A of this test report.



3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting Antenna of directional gain greater than 6dBi are used the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the Antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the Antenna exceeds 6dBi.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v03r03.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A of this test report.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A of this test report.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.


3.3.4 Test Setup





3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A of this test report.



3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement and radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a).


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.


3.4.4 Test Setup





3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Luffy Lin and AC Chang






Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11b Channel 06

100kHz PSD reference Level




Date: 24.MAY.2015 03:35:06

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 03:36:49

Spurious Emission 2GHz~25GHz




Date: 24.MAY.2015 03:35:46



Test Mode :	802.11b	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11b Channel 11

100kHz PSD reference Level




Date: 24.MAY.2015 03:42:03

High Channel Plot




Date: 24.MAY.2015 03:42:32

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 03:43:16

Spurious Emission 2GHz~25GHz




Date: 24.MAY.2015 03:43:34



Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11g Channel 01

100kHz PSD reference Level




Date: 15.JUN.2015 21:20:44

Low Channel Plot




Date: 15.JUN.2015 21:21:04

Spurious Emission 30MHz~3GHz



Date: 1.JUN.2015 22:56:27


Spurious Emission 2GHz~25GHz




Date: 1.JUN.2015 22:56:45




Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Luffy Lin and AC Chang

WLAN 802.11g Channel 06**100kHz PSD reference Level**

Date: 24.MAY.2015 05:08:01

Spurious Emission 30MHz~3GHz

Date: 24.MAY.2015 05:09:17

Spurious Emission 2GHz~25GHz


Date: 24.MAY.2015 05:09:35



Test Mode :	802.11g	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11g Channel 11

100kHz PSD reference Level




Date: 24.MAY.2015 05:13:12

High Channel Plot




Date: 24.MAY.2015 05:13:31

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 05:13:59

Spurious Emission 2GHz~25GHz




Date: 24.MAY.2015 05:14:17



Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Low	Relative Humidity :	45~54%
Test Channel :	01	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11n HT20 Channel 01

100kHz PSD reference Level




Date: 24.MAY.2015 05:24:00

Low Channel Plot




Date: 24.MAY.2015 05:24:20

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 05:24:41

Spurious Emission 2GHz~25GHz




Date: 24.MAY.2015 05:24:59



Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz Mid	Relative Humidity :	45~54%
Test Channel :	06	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11n HT20 Channel 06

100kHz PSD reference Level




Date: 24.MAY.2015 05:28:08

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 05:28:32

Spurious Emission 2GHz~25GHz




Date: 24.MAY.2015 05:28:50



Test Mode :	802.11n HT20	Temperature :	21~26°C
Test Band :	2.4GHz High	Relative Humidity :	45~54%
Test Channel :	11	Test Engineer :	Luffy Lin and AC Chang


WLAN 802.11n HT20 Channel 11

100kHz PSD reference Level




Date: 24.MAY.2015 05:32:30

High Channel Plot




Date: 24.MAY.2015 05:33:46

Spurious Emission 30MHz~3GHz



Date: 24.MAY.2015 05:34:14

Spurious Emission 2GHz~25GHz



Date: 24.MAY.2015 05:34:32

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v03r03.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
7. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW=100 kHz for $f < 1 \text{ GHz}$; VBW $\geq$ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3MHz for $f \geq 1 \text{ GHz}$ for peak measurement.


For average measurement:

 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


Band	Duty Cycle(%)	T(μ s)	1/T(kHz)	VBW Setting
802.11b	97.63	8240.00	0.12	300Hz
802.11g	87.34	1380.00	0.72	1kHz
2.4GHz 802.11n HT20	86.30	1260.00	0.79	1kHz

3.5.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dB μ V)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission


Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		



Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.382000	42.4	Off	L1	19.5	15.8	58.2
0.614000	35.7	Off	L1	19.5	20.3	56.0
0.798000	37.7	Off	L1	19.5	18.3	56.0
0.982000	38.4	Off	L1	19.6	17.6	56.0
1.110000	39.4	Off	L1	19.5	16.6	56.0
1.246000	40.2	Off	L1	19.6	15.8	56.0
1.382000	39.8	Off	L1	19.6	16.2	56.0
1.550000	39.0	Off	L1	19.5	17.0	56.0
1.718000	38.6	Off	L1	19.6	17.4	56.0
1.966000	37.4	Off	L1	19.6	18.6	56.0
2.502000	42.5	Off	L1	19.7	13.5	56.0
2.646000	44.2	Off	L1	19.7	11.8	56.0
2.734000	45.8	Off	L1	19.7	10.2	56.0
2.862000	47.1	Off	L1	19.7	8.9	56.0
2.918000	46.9	Off	L1	19.7	9.1	56.0
2.990000	46.1	Off	L1	19.7	9.9	56.0

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		


Final Result : Quasi-Peak


Frequency (MHz)	Quasi-Peak (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
3.198000	44.1	Off	L1	19.7	11.9	56.0
3.326000	39.9	Off	L1	19.8	16.1	56.0
3.582000	38.7	Off	L1	19.7	17.3	56.0
4.342000	41.4	Off	L1	19.7	14.6	56.0
4.518000	42.7	Off	L1	19.8	13.3	56.0
4.742000	42.3	Off	L1	19.7	13.7	56.0
5.862000	41.5	Off	L1	19.7	18.5	60.0
7.206000	40.8	Off	L1	19.8	19.2	60.0
8.782000	40.4	Off	L1	19.8	19.6	60.0
10.190000	42.7	Off	L1	19.8	17.3	60.0

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
0.382000	31.0	Off	L1	19.5	17.2	48.2
0.614000	27.6	Off	L1	19.5	18.4	46.0
0.798000	27.2	Off	L1	19.5	18.8	46.0
0.982000	26.3	Off	L1	19.6	19.7	46.0
1.110000	28.1	Off	L1	19.5	17.9	46.0
1.246000	29.6	Off	L1	19.6	16.4	46.0
1.382000	28.8	Off	L1	19.6	17.2	46.0
1.550000	28.2	Off	L1	19.5	17.8	46.0
1.718000	29.7	Off	L1	19.6	16.3	46.0
1.966000	29.0	Off	L1	19.6	17.0	46.0
2.502000	33.6	Off	L1	19.7	12.4	46.0
2.646000	35.3	Off	L1	19.7	10.7	46.0
2.734000	36.7	Off	L1	19.7	9.3	46.0
2.862000	37.9	Off	L1	19.7	8.1	46.0
2.918000	36.6	Off	L1	19.7	9.4	46.0
2.990000	36.6	Off	L1	19.7	9.4	46.0


Test Mode :	Mode 1	Temperature :	21~23℃
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		


Final Result : Average

Frequency (MHz)	Average (dBμV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμV)
3.198000	35.3	Off	L1	19.7	10.7	46.0
3.326000	32.3	Off	L1	19.8	13.7	46.0
3.582000	26.0	Off	L1	19.7	20.0	46.0
4.342000	32.7	Off	L1	19.7	13.3	46.0
4.518000	33.4	Off	L1	19.8	12.6	46.0
4.742000	32.6	Off	L1	19.7	13.4	46.0
5.862000	31.9	Off	L1	19.7	18.1	50.0
7.206000	29.1	Off	L1	19.8	20.9	50.0
8.782000	29.7	Off	L1	19.8	20.3	50.0
10.190000	33.5	Off	L1	19.8	16.5	50.0




Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		

**Final Result : Quasi-Peak**


Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	36.9	Off	N	19.5	28.7	65.6
0.438000	38.6	Off	N	19.5	18.5	57.1
0.566000	37.0	Off	N	19.4	19.0	56.0
0.958000	39.6	Off	N	19.6	16.4	56.0
1.086000	39.2	Off	N	19.5	16.8	56.0
1.310000	39.0	Off	N	19.6	17.0	56.0
1.486000	40.3	Off	N	19.6	15.7	56.0
1.646000	39.6	Off	N	19.6	16.4	56.0
1.886000	38.8	Off	N	19.5	17.2	56.0
2.462000	40.9	Off	N	19.7	15.1	56.0
2.630000	43.7	Off	N	19.7	12.3	56.0
2.782000	45.7	Off	N	19.7	10.3	56.0
2.934000	46.8	Off	N	19.7	9.2	56.0

Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		


Final Result : Quasi-Peak

Frequency (MHz)	Quasi-Peak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
3.046000	44.8	Off	N	19.7	11.2	56.0
3.158000	45.2	Off	N	19.7	10.8	56.0
3.310000	40.7	Off	N	19.8	15.3	56.0
3.566000	36.4	Off	N	19.7	19.6	56.0
4.030000	35.6	Off	N	19.7	20.4	56.0
4.238000	39.0	Off	N	19.7	17.0	56.0
4.390000	40.4	Off	N	19.7	15.6	56.0
4.670000	41.3	Off	N	19.7	14.7	56.0
4.982000	39.9	Off	N	19.8	16.1	56.0
5.702000	39.6	Off	N	19.7	20.4	60.0
7.574000	39.0	Off	N	19.8	21.0	60.0
8.334000	38.9	Off	N	19.8	21.1	60.0
9.054000	39.9	Off	N	19.9	20.1	60.0
9.950000	42.3	Off	N	19.9	17.7	60.0


Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		


Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.158000	21.1	Off	N	19.5	34.5	55.6
0.438000	26.7	Off	N	19.5	20.4	47.1
0.566000	25.6	Off	N	19.4	20.4	46.0
0.958000	27.2	Off	N	19.6	18.8	46.0
1.086000	27.8	Off	N	19.5	18.2	46.0
1.310000	28.1	Off	N	19.6	17.9	46.0
1.486000	29.9	Off	N	19.6	16.1	46.0
1.646000	29.2	Off	N	19.6	16.8	46.0
1.886000	28.5	Off	N	19.5	17.5	46.0
2.462000	31.2	Off	N	19.7	14.8	46.0
2.630000	34.4	Off	N	19.7	11.6	46.0
2.782000	35.0	Off	N	19.7	11.0	46.0
2.934000	35.9	Off	N	19.7	10.1	46.0



Test Mode :	Mode 1	Temperature :	21~23°C
Test Engineer :	Eric Jeng	Relative Humidity :	59~61%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + Earphone + USB Cable (Charging from Adapter 2) + MP3		



Final Result : Average

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
3.046000	36.1	Off	N	19.7	9.9	46.0
3.158000	34.3	Off	N	19.7	11.7	46.0
3.310000	30.0	Off	N	19.8	16.0	46.0
3.566000	26.0	Off	N	19.7	20.0	46.0
4.030000	27.1	Off	N	19.7	18.9	46.0
4.238000	30.0	Off	N	19.7	16.0	46.0
4.390000	31.4	Off	N	19.7	14.6	46.0
4.670000	31.4	Off	N	19.7	14.6	46.0
4.982000	29.1	Off	N	19.8	16.9	46.0
5.702000	30.8	Off	N	19.7	19.2	50.0
7.574000	29.4	Off	N	19.8	20.6	50.0
8.334000	28.7	Off	N	19.8	21.3	50.0
9.054000	30.3	Off	N	19.9	19.7	50.0
9.950000	34.1	Off	N	19.9	15.9	50.0



3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Power Meter	Anritsu	ML2495A	1036004	300MHz~40GHz z	Aug. 09, 2014	May 10, 2015 ~ Jun. 15, 2015	Aug. 08, 2015	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	1027253	300MHz~40GHz z	Aug. 11, 2014	May 10, 2015 ~ Jun. 15, 2015	Aug. 10, 2015	Conducted (TH02-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Oct. 17, 2014	May 10, 2015 ~ Jun. 15, 2015	Oct. 16, 2015	Conducted (TH02-HY)
EMI Test Receiver	Rohde & Schwarz	ESCS 30	100356	9kHz ~ 2.75GHz	Dec. 01, 2014	May 16, 2015 ~ Jun. 09, 2015	Nov. 30, 2015	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 02, 2014	May 16, 2015 ~ Jun. 09, 2015	Dec. 01, 2015	Conduction (CO05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	May 16, 2015 ~ Jun. 09, 2015	N/A	Conduction (CO05-HY)
Bilog Antenna	Schaffner	CBL6111C	2726	30MHz ~ 1GHz	Sep. 27, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Sep. 26, 2015	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Aug. 18, 2015	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 30, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Aug. 29, 2015	Radiation (03CH07-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 03, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Nov. 02, 2015	Radiation (03CH07-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590075	1GHz ~ 18GHz	Apr. 20, 2015	Jun. 09, 2015 ~ Jun. 11, 2015	Apr. 19, 2016	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1000MHz z	Mar. 12, 2015	Jun. 09, 2015 ~ Jun. 11, 2015	Mar. 11, 2016	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Oct. 21, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Oct. 20, 2015	Radiation (03CH07-HY)
Signal Analyzer	Rohde & Schwarz	FSV 30	101749	10Hz~30GHz	Mar. 10, 2015	Jun. 09, 2015 ~ Jun. 11, 2015	Mar. 09, 2016	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Jun. 09, 2015 ~ Jun. 11, 2015	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 degree	N/A	Jun. 09, 2015 ~ Jun. 11, 2015	N/A	Radiation (03CH07-HY)
Preamplifier	MITEQ	JS44-180040 00-33-8P	1840917	18GHz ~ 40GHz	Jun. 02, 2015	Jun. 09, 2015 ~ Jun. 11, 2015	Jun. 01, 2016	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9 kHz~30 MHz	Jul. 28, 2014	Jun. 09, 2015 ~ Jun. 11, 2015	Jul. 27, 2015	Radiation (03CH07-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.26
---	------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2
---	-----



Appendix A. Conducted Test Results

A1 - DTS Part

Test Engineer:	Luffy Lin and AC Chang	Temperature:	24~26	°C
Test Date:	2015/05/10 ~ 2015/06/15	Relative Humidity:	45~49	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band								
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
11b	1Mbps	1	1	2412		8.56	0.50	Pass
11b	1Mbps	1	6	2437		9.10	0.50	Pass
11b	1Mbps	1	11	2462		9.04	0.50	Pass
11g	6Mbps	1	1	2412		16.40	0.50	Pass
11g	6Mbps	1	6	2437		16.40	0.50	Pass
11g	6Mbps	1	11	2462		16.38	0.50	Pass
HT20	MCS0	1	1	2412		17.62	0.50	Pass
HT20	MCS0	1	6	2437		17.60	0.50	Pass
HT20	MCS0	1	11	2462		17.64	0.50	Pass

TEST RESULTS DATA
Peak Power Table

2.4GHz Band										
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
11b	1Mbps	1	1	2412	22.63	30.00	-2.30	20.33	36.00	Pass
11b	1Mbps	1	6	2437	22.62	30.00	-2.30	20.32	36.00	Pass
11b	1Mbps	1	11	2462	23.41	30.00	-2.30	21.11	36.00	Pass
11g	6Mbps	1	1	2412	23.52	30.00	-2.30	21.22	36.00	Pass
11g	6Mbps	1	6	2437	23.56	30.00	-2.30	21.26	36.00	Pass
11g	6Mbps	1	11	2462	22.87	30.00	-2.30	20.57	36.00	Pass
HT20	MCS0	1	1	2412	23.39	30.00	-2.30	21.09	36.00	Pass
HT20	MCS0	1	6	2437	23.55	30.00	-2.30	21.25	36.00	Pass
HT20	MCS0	1	11	2462	23.01	30.00	-2.30	20.71	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

2.4GHz Band						
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
11b	1Mbps	1	1	2412	0.10	20.34
11b	1Mbps	1	6	2437	0.10	20.12
11b	1Mbps	1	11	2462	0.10	20.17
11g	6Mbps	1	1	2412	0.59	17.31
11g	6Mbps	1	6	2437	0.59	17.34
11g	6Mbps	1	11	2462	0.59	16.10
HT20	MCS0	1	1	2412	0.64	17.09
HT20	MCS0	1	6	2437	0.64	16.97
HT20	MCS0	1	11	2462	0.64	16.13

TEST RESULTS DATA
Peak Power Density

2.4GHz Band								
Mod.	Data Rate	NTx	CH.	Freq. (MHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
11b	1Mbps	1	1	2412	-2.51	-2.30	8.00	Pass
11b	1Mbps	1	6	2437	-2.45	-2.30	8.00	Pass
11b	1Mbps	1	11	2462	-2.03	-2.30	8.00	Pass
11g	6Mbps	1	1	2412	-8.70	-2.30	8.00	Pass
11g	6Mbps	1	6	2437	-8.26	-2.30	8.00	Pass
11g	6Mbps	1	11	2462	-7.76	-2.30	8.00	Pass
HT20	MCS0	1	1	2412	-8.48	-2.30	8.00	Pass
HT20	MCS0	1	6	2437	-7.74	-2.30	8.00	Pass
HT20	MCS0	1	11	2462	-8.60	-2.30	8.00	Pass



Appendix B. Radiated Spurious Emission

Test Engineer :	Nick Yu, Ken Wu, and James Chiu	Temperature :	22~23°C
		Relative Humidity :	58~62%

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)(Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2378.13	58.71	-15.29	74	53.14	32.16	7.68	34.27	200	12	P	H
		2389.83	45.29	-8.71	54	39.66	32.18	7.75	34.3	200	12	A	H
	*	2412	104.6	-	-	98.95	32.2	7.75	34.3	200	12	P	H
	*	2412	100.91	-	-	95.26	32.2	7.75	34.3	200	12	A	H
													H
													H
		2340.87	58.94	-15.06	74	53.4	32.11	7.68	34.25	112	297	P	V
		2332.77	45.08	-8.92	54	39.61	32.09	7.6	34.22	112	297	A	V
	*	2412	102.62	-	-	96.97	32.2	7.75	34.3	112	297	P	V
	*	2412	99	-	-	93.35	32.2	7.75	34.3	112	297	A	V
													V
													V
802.11b CH 06 2437MHz		2366.07	58.95	-15.05	74	53.41	32.13	7.68	34.27	183	150	P	H
		2387.94	45.07	-8.93	54	39.41	32.18	7.75	34.27	183	150	A	H
	*	2437	105.14	-	-	99.42	32.24	7.83	34.35	183	150	P	H
	*	2437	102.41	-	-	96.69	32.24	7.83	34.35	183	150	A	H
		2485.52	60.15	-13.85	74	54.39	32.28	7.91	34.43	183	150	P	H
		2484.64	46.24	-7.76	54	40.48	32.28	7.91	34.43	183	150	A	H
		2330.43	58.7	-15.3	74	53.23	32.09	7.6	34.22	100	296	P	V
		2374.8	45.09	-8.91	54	39.52	32.16	7.68	34.27	100	296	A	V
	*	2437	104.73	-	-	99.01	32.24	7.83	34.35	100	296	P	V
	*	2437	101.02	-	-	95.3	32.24	7.83	34.35	100	296	A	V
		2498.24	59.63	-14.37	74	53.9	32.3	7.91	34.48	100	296	P	V
		2484.44	46.06	-7.94	54	40.3	32.28	7.91	34.43	100	296	A	V



802.11b CH 11 2462MHz	*	2462	105.92	-	-	100.14	32.26	7.91	34.39	200	59	P	H
	*	2462	102.21	-	-	96.43	32.26	7.91	34.39	200	59	A	H
		2488.08	61.18	-12.82	74	55.4	32.3	7.91	34.43	200	59	P	H
		2487.28	50.77	-3.23	54	45.01	32.28	7.91	34.43	200	59	A	H
													H
													H
	*	2462	102.6	-	-	96.82	32.26	7.91	34.39	100	299	P	V
	*	2462	98.84	-	-	93.06	32.26	7.91	34.39	100	299	A	V
		2487.16	61.2	-12.8	74	55.44	32.28	7.91	34.43	100	299	P	V
		2486.76	50.45	-3.55	54	44.69	32.28	7.91	34.43	100	299	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	47.09	-26.91	74	61.31	34.26	11.16	59.64	100	0	P	H
													H
													H
													H
		4824	48.27	-25.73	74	62.49	34.26	11.16	59.64	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4872	47.84	-26.16	74	61.9	34.3	11.21	59.57	100	0	P	H
		7311	45.43	-28.57	74	53.22	35.6	15.08	58.47	100	0	P	H
													H
													H
		4872	46.43	-27.57	74	60.49	34.3	11.21	59.57	100	0	P	V
		7311	46.93	-27.07	74	54.72	35.6	15.08	58.47	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4926	45.35	-28.65	74	59.24	34.34	11.27	59.5	100	0	P	H
		7386	43.71	-30.29	74	51.55	35.6	15.14	58.58	100	0	P	H
													H
													H
		4926	45.46	-28.54	74	59.35	34.34	11.27	59.5	100	0	P	V
		7386	43.73	-30.27	74	51.57	35.6	15.14	58.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		2389.65	59.3	-14.7	74	53.64	32.18	7.75	34.27	200	12	P	H
		2389.92	46.13	-7.87	54	40.5	32.18	7.75	34.3	200	12	A	H
	*	2412	103.67	-	-	98.02	32.2	7.75	34.3	200	12	P	H
	*	2412	92.51	-	-	86.86	32.2	7.75	34.3	200	12	A	H
													H
													H
		2389.65	59.52	-14.48	74	53.86	32.18	7.75	34.27	104	298	P	V
		2312.34	45.46	-8.54	54	39.98	32.07	7.6	34.19	104	298	A	V
	*	2412	102.18	-	-	96.53	32.2	7.75	34.3	104	298	P	V
	*	2412	91.4	-	-	85.75	32.2	7.75	34.3	104	298	A	V
													V
													V
802.11g CH 06 2437MHz		2374.98	59.22	-14.78	74	53.65	32.16	7.68	34.27	141	153	P	H
		2347.26	45.39	-8.61	54	39.85	32.11	7.68	34.25	141	153	A	H
	*	2437	105.84	-	-	100.12	32.24	7.83	34.35	141	153	P	H
	*	2437	95.26	-	-	89.54	32.24	7.83	34.35	141	153	A	H
		2484.84	59.45	-14.55	74	53.69	32.28	7.91	34.43	141	153	P	H
		2484.52	46.15	-7.85	54	40.39	32.28	7.91	34.43	141	153	A	H
		2333.85	58.85	-15.15	74	53.38	32.09	7.6	34.22	100	297	P	V
		2364.63	45.44	-8.56	54	39.9	32.13	7.68	34.27	100	297	A	V
	*	2437	105.66	-	-	99.94	32.24	7.83	34.35	100	297	P	V
	*	2437	95.17	-	-	89.45	32.24	7.83	34.35	100	297	A	V
		2491.2	58.77	-15.23	74	52.99	32.3	7.91	34.43	100	297	P	V
		2484.6	45.98	-8.02	54	40.22	32.28	7.91	34.43	100	297	A	V



802.11g CH 11 2462MHz	*	2462	105.67	-	-	99.89	32.26	7.91	34.39	202	40	P	H
	*	2462	95.46	-	-	89.68	32.26	7.91	34.39	202	40	A	H
		2484.24	69.96	-4.04	74	64.2	32.28	7.91	34.43	202	40	P	H
		2483.52	52.21	-1.79	54	46.45	32.28	7.91	34.43	202	40	A	H
													H
													H
	*	2462	100.28	-	-	94.5	32.26	7.91	34.39	387	127	P	V
	*	2462	90.24	-	-	84.46	32.26	7.91	34.39	387	127	A	V
		2483.52	65.45	-8.55	74	59.69	32.28	7.91	34.43	387	127	P	V
		2483.52	48.58	-5.42	54	42.82	32.28	7.91	34.43	387	127	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	41.62	-32.38	74	55.84	34.26	11.16	59.64	100	0	P	H
													H
													H
													H
		4824	42.27	-31.73	74	56.49	34.26	11.16	59.64	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4872	42.8	-31.2	74	56.86	34.3	11.21	59.57	100	0	P	H
		7311	44.23	-29.77	74	52.02	35.6	15.08	58.47	100	0	P	H
													H
													H
		4872	42.08	-31.92	74	56.14	34.3	11.21	59.57	100	0	P	V
		7311	43.87	-30.13	74	51.66	35.6	15.08	58.47	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4926	42.06	-31.94	74	55.95	34.34	11.27	59.5	100	0	P	H
		7386	43.13	-30.87	74	50.97	35.6	15.14	58.58	100	0	P	H
													H
													H
		4924	41.29	-32.71	74	55.18	34.34	11.27	59.5	100	0	P	V
		7386	43	-31	74	50.84	35.6	15.14	58.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		2389.83	65.46	-8.54	74	59.83	32.18	7.75	34.3	186	34	P	H
		2390	49.12	-4.88	54	43.49	32.18	7.75	34.3	186	34	A	H
	*	2412	103.82	-	-	98.17	32.2	7.75	34.3	186	34	P	H
	*	2412	93.64	-	-	87.99	32.2	7.75	34.3	186	34	A	H
													H
													H
		2389.74	65.8	-8.2	74	60.14	32.18	7.75	34.27	104	296	P	V
		2390	48.28	-5.72	54	42.65	32.18	7.75	34.3	104	296	A	V
	*	2412	103.64	-	-	97.99	32.2	7.75	34.3	104	296	P	V
	*	2412	92.7	-	-	87.05	32.2	7.75	34.3	104	296	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2388.84	59.43	-14.57	74	53.77	32.18	7.75	34.27	100	140	P	H
		2349.24	45.51	-8.49	54	39.97	32.11	7.68	34.25	100	140	A	H
	*	2437	105.25	-	-	99.53	32.24	7.83	34.35	100	140	P	H
	*	2437	94.44	-	-	88.72	32.24	7.83	34.35	100	140	A	H
		2483.56	61.37	-12.63	74	55.61	32.28	7.91	34.43	100	140	P	H
		2483.52	46	-8	54	40.24	32.28	7.91	34.43	100	140	A	H
		2342.31	59.13	-14.87	74	53.59	32.11	7.68	34.25	114	290	P	V
		2311.98	45.59	-8.41	54	40.11	32.07	7.6	34.19	114	290	A	V
	*	2437	103.17	-	-	97.45	32.24	7.83	34.35	114	290	P	V
	*	2437	92.88	-	-	87.16	32.24	7.83	34.35	114	290	A	V
		2484.32	59.32	-14.68	74	53.56	32.28	7.91	34.43	114	290	P	V
		2483.8	46.09	-7.91	54	40.33	32.28	7.91	34.43	114	290	A	V



802.11n HT20 CH 11 2462MHz	*	2462	104.58	-	-	98.8	32.26	7.91	34.39	203	39	P	H
	*	2462	93.8	-	-	88.02	32.26	7.91	34.39	203	39	A	H
		2483.8	71.71	-2.29	74	65.95	32.28	7.91	34.43	203	39	P	H
		2483.56	52.89	-1.11	54	47.13	32.28	7.91	34.43	203	39	A	H
													H
													H
	*	2462	101.87	-	-	96.09	32.26	7.91	34.39	388	118	P	V
	*	2462	90.85	-	-	85.07	32.26	7.91	34.39	388	118	A	V
		2483.8	67.32	-6.68	74	61.56	32.28	7.91	34.43	388	118	P	V
		2483.56	50.58	-3.42	54	44.82	32.28	7.91	34.43	388	118	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	44	-30	74	58.22	34.26	11.16	59.64	100	0	P	H
													H
													H
													H
		4824	42.7	-31.3	74	56.92	34.26	11.16	59.64	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4872	41.46	-32.54	74	55.52	34.3	11.21	59.57	100	0	P	H
		7311	44.49	-29.51	74	52.28	35.6	15.08	58.47	100	0	P	H
													H
													H
		4874	41.49	-32.51	74	55.55	34.3	11.21	59.57	100	0	P	V
		7311	44.52	-29.48	74	52.31	35.6	15.08	58.47	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	41.75	-32.25	74	55.64	34.34	11.27	59.5	100	0	P	H
		7386	44.05	-29.95	74	51.89	35.6	15.14	58.58	100	0	P	H
													H
													H
		4924	41.28	-32.72	74	55.17	34.34	11.27	59.5	100	0	P	V
		7386	44.39	-29.61	74	52.23	35.6	15.14	58.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11g (LF) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11g LF		31.08	27.8	-12.2	40	39.21	18.28	1.77	31.46	100	296	P	H
		38.91	26.85	-13.15	40	41.86	14.44	1.77	31.22	-	-	P	H
		104.25	28.04	-15.46	43.5	46.3	10.5	2.38	31.14	-	-	P	H
		384	20.56	-25.44	46	32.76	15.26	3.52	30.98	-	-	P	H
		690.6	25.01	-20.99	46	30.57	20.51	4.35	30.42	-	-	P	H
		950.3	28.97	-17.03	46	30	24.43	4.94	30.4	-	-	P	H
													H
													H
													H
													H
													H
		30.54	36.17	-3.83	40	47.58	18.28	1.77	31.46	188	52	P	V
		35.13	34.07	-5.93	40	47.4	16.2	1.77	31.3	-	-	P	V
		96.96	29.23	-14.27	43.5	48.59	9.68	2.06	31.1	-	-	P	V
		556.2	23.55	-22.45	46	30.39	19.92	4.01	30.77	-	-	P	V
		744.5	26.51	-19.49	46	30.28	22.15	4.48	30.4	-	-	P	V
		986	30.39	-23.61	54	30.74	24.87	5.03	30.25	-	-	P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF) (Standalone)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		31.35	28.02	-11.98	40	39.39	18.28	1.77	31.42	100	286	P	H
		105.6	27.63	-15.87	43.5	45.85	10.56	2.38	31.16	-	-	P	H
		151.23	25.55	-17.95	43.5	43.27	10.78	2.61	31.11	-	-	P	H
		628.3	23.84	-22.16	46	29.8	20.36	4.22	30.54	-	-	P	H
		835.5	27.7	-18.3	46	30.37	23	4.7	30.37	-	-	P	H
		998.6	30.4	-23.6	54	30.95	24.62	5.03	30.2	-	-	P	H
													H
													H
													H
													H
													H
													H
		31.08	36.02	-3.98	40	47.43	18.28	1.77	31.46	311	50	P	V
		33.51	35.08	-4.92	40	47.93	16.72	1.77	31.34	-	-	P	V
		98.31	28.73	-14.77	43.5	47.85	9.92	2.06	31.1	-	-	P	V
		414.8	21.53	-24.47	46	32.38	16.45	3.52	30.82	-	-	P	V
		738.9	26.98	-19.02	46	30.79	22.18	4.41	30.4	-	-	P	V
		923	28.59	-17.41	46	30.05	24.09	4.8	30.35	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m) (with adapter1)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 11 2462MHz	*	2462	103.77	-	-	97.99	32.26	7.91	34.39	140	36	P	H
	*	2462	93.25	-	-	87.47	32.26	7.91	34.39	140	36	A	H
		2483.96	73.17	-0.83	74	67.41	32.28	7.91	34.43	140	36	P	H
		2483.6	52.9	-1.1	54	47.14	32.28	7.91	34.43	140	36	A	H
													H
													H
	*	2462	100.52	-	-	94.74	32.26	7.91	34.39	100	336	P	V
	*	2462	90.08	-	-	84.3	32.26	7.91	34.39	100	336	A	V
		2484.24	65.84	-8.16	74	60.08	32.28	7.91	34.43	100	336	P	V
		2483.6	49.76	-4.24	54	44	32.28	7.91	34.43	100	336	A	V
													V
													V
Remark	1. No other spurious found. 2. II results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m) (with adapter1)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 11 2462MHz		4924	41.75	-32.25	74	55.64	34.34	11.27	59.5	100	0	P	H
		7386	44.05	-29.95	74	51.89	35.6	15.14	58.58	100	0	P	H
													H
													H
		4924	41.28	-32.72	74	55.17	34.34	11.27	59.5	100	0	P	V
		7386	44.39	-29.61	74	52.23	35.6	15.14	58.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF) (with adapter1)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		76.98	21.82	-18.18	40	44.09	6.87	2.06	31.2	-	-	P	H
		207.66	23.03	-20.47	43.5	42.27	9.17	2.69	31.1	-	-	P	H
		254.91	23.77	-22.23	46	38.61	13.2	2.96	31	-	-	P	H
		364.4	22.44	-23.56	46	35.34	14.79	3.39	31.08	-	-	P	H
		649.3	26.58	-19.42	46	32.46	20.4	4.22	30.5	-	-	P	H
		881	29.1	-16.9	46	31.88	22.9	4.66	30.34	113	212	P	H
													H
													H
													H
													H
													H
													H
		82.38	22.96	-17.04	40	44.61	7.44	2.06	31.15	-	-	P	V
		195.51	17.98	-25.52	43.5	37.41	8.98	2.69	31.1	-	-	P	V
		275.7	22.23	-23.77	46	37.17	12.85	3.16	30.95	-	-	P	V
		377	20.12	-25.88	46	32.7	15.04	3.39	31.01	-	-	P	V
		694.1	26.47	-19.53	46	31.98	20.55	4.35	30.41	-	-	P	V
		889.4	29.49	-16.51	46	32.25	22.9	4.66	30.32	100	56	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m) (with adapter2)

802.11n HT20 CH 11 2462MHz	*	2462	103.56	-	-	97.78	32.26	7.91	34.39	158	25	P	H
	*	2462	92.97	-	-	87.19	32.26	7.91	34.39	158	25	A	H
		2483.52	71.17	-2.83	74	65.41	32.28	7.91	34.43	158	25	P	H
		2483.64	52.31	-1.69	54	46.55	32.28	7.91	34.43	158	25	A	H
													H
													H
	*	2462	100.93	-	-	95.15	32.26	7.91	34.39	100	240	P	V
	*	2462	90.35	-	-	84.57	32.26	7.91	34.39	100	240	A	V
		2484.2	68.69	-5.31	74	62.93	32.28	7.91	34.43	100	240	P	V
		2483.56	51.7	-2.3	54	45.94	32.28	7.91	34.43	100	240	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

15C 2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m) (with adapter2)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preampl	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 11 2462MHz		4924	41.68	-32.32	74	55.57	34.34	11.27	59.5	100	0	P	H
		7386	45.07	-28.93	74	52.91	35.6	15.14	58.58	100	0	P	H
													H
													H
		4924	42.06	-31.94	74	55.95	34.34	11.27	59.5	100	0	P	V
		7386	44.74	-29.26	74	52.58	35.6	15.14	58.58	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



15C Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF) (with adapter2)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		101.55	33.33	-10.17	43.5	51.63	10.44	2.38	31.12	-	-	P	H
		154.2	36.29	-7.21	43.5	54.11	10.72	2.61	31.15	148	322	P	H
		204.96	32.62	-10.88	43.5	51.88	9.15	2.69	31.1	-	-	P	H
		442.1	23.11	-22.89	46	33.13	17.06	3.63	30.71	-	-	P	H
		644.4	24.65	-21.35	46	30.54	20.4	4.22	30.51	-	-	P	H
		920.9	28.91	-17.09	46	30.45	24	4.8	30.34	-	-	P	H
													H
													H
													H
													H
													H
													H
		41.34	36.57	-3.43	40	53.4	12.6	1.77	31.2	255	60	P	V
		100.74	34.07	-9.43	43.5	52.38	10.42	2.38	31.11	-	-	P	V
		204.96	31.6	-11.9	43.5	50.86	9.15	2.69	31.1	-	-	P	V
		625.5	24.04	-21.96	46	30.06	20.31	4.22	30.55	-	-	P	V
		801.9	27.32	-18.68	46	30.96	22.04	4.62	30.3	-	-	P	V
		981.8	30.04	-23.96	54	30.32	24.96	5.03	30.27	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency per 15.209(c).
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.