FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	10715, 10716
FCC ID	:	IHDT56WC4
STANDARD	:	FCC 47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Jan. 19, 2017 and testing was completed on Mar. 11, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager

Sporton International (KunShan) INC.

No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China

TABLE OF CONTENTS

1 GENERAL DESCRIPTION 5

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Specification of Accessory 7
1.8 Testing Location 8
1.9 Applicable Standards 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST 9

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration 10
2.4 Measurement Results Explanation Example 10

3 CONDUCTED TEST RESULT 11

3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power and ERP/EIRP 12
3.5 Peak-to-Average Ratio 13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 14
3.7 Conducted Band Edge 15
3.8 Conducted Spurious Emission 16
3.9 Frequency Stability 17

4 RADIATED TEST ITEMS 18

4.1 Measuring Instruments 18
4.2 Test Setup 18
4.3 Test Result of Radiated Test 18
4.4 Field Strength of Spurious Radiation Measurement 19

5 LIST OF MEASURING EQUIPMENT 20

6 UNCERTAINTY OF EVALUATION 21

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG711916A	Rev. 01	Initial issue of report	Apr. 01, 2017

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(2)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b) §27.53(g)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 31.18 dB at 2508.000 MHz

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	10715, 10716
FCC ID	IHDT56WC4
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/HSPA+/DC-HSDPA/LTE/ WLAN2.4GHz 802.11b/g/n HT20/ Bluetooth v3.0+EDR Bluetooth v4.0 LE/Bluetooth v4.1 LE/Bluetooth v4.2 LE
IMEI Code	Conducted: 355640080004009 Radiation: 355639080021294/355639080021302
HW Version	WKGMA1A4-3
SW Version	woods- userdebug 7.0 NMA25.27 314 intcfg,test-keys
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for SIM slot, sample 1(model name: 10715) is dual SIM slot, sample 2(model name: 10716) is single SIM slot. According to the difference, the sample 1 to perform full test.
3. After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose dual SIM1 card to perform all tests.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz **WCDMA:** Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz **WCDMA:** Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	**GSM/GPRS/EDGE:** 850: 32.72 dBm 1900: 29.99 dBm **WCDMA:** Band V: 23.59 dBm Band II: 23.59 dBm Band IV: 23.57 dBm
Antenna Type	PIFA Antenna
Antenna Gain	Cellular Band: -0.4 dBi PCS Band: 1.4 dBi AWS Band: -0.4 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: BPSK (Uplink) HSDPA/DC-HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink) HSPA+: 16QAM DC-HSDPA: 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22H	GSM850 GSM	GMSK	1.040	0.0096 ppm	244KGXW
Part 22H	GSM850 EDGE class 8	8PSK	0.270	0.0395 ppm	251KG7W
Part 22H	WCDMA Band V RMC 12.2Kbps	BPSK	0.127	0.0239 ppm	4M21F9W
Part 24E	GSM1900 GSM	GMSK	1.377	0.0191 ppm	243KGXW
Part 24E	GSM1900 EDGE class 8	8PSK	0.508	0.0218 ppm	247KG7W
Part 24E	WCDMA Band II RMC 12.2Kbps	BPSK	0.316	0.0064 ppm	4M21F9W
Part 27L	WCDMA Band IV RMC 12.2Kbps	BPSK	0.207	0.0139 ppm	4M21F9W

1.7 Specification of Accessory

Specification of Accessory				
AC Adapter	**Brand Name**	Motorola (Salom)	**Model Name**	SSW-2865BR SPN5933A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5.0Vdc, 2000mA		
Battery 1	**Brand Name**	Motorola (ATL)	**Model Name**	GK40
	Power Rating	3.8Vdc,2685/2800mAh (Min/Typ)	**Type**	Li-ion
Battery 2	**Brand Name**	Motorola (Sunwoda)	**Model Name**	GK40
	Power Rating	3.8Vdc,2685/2800mAh (Min/Typ)	**Type**	Li-ion
Earphone	**Brand Name**	Motorola (Cosonic)	**Model Name**	SH38C16617
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
USB Cable	**Brand Name**	Motorola (Sai Bao)	**Model Name**	SYD-A017A
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

1.8 Testing Location

Test Site	Sporton International (KunShan) INC.		
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	**Sporton Site No.**		**FCC Registration No.**
	TH01-KS	03CH02-KS 03CH03-KS	418269 306251

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 10th harmonic for GSM850 and WCDMA Band V.
2. 30 MHz to 10th harmonic for WCDMA Band IV.
3. 30 MHz to 10th harmonic for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.6 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.6 + 10 = 14.6 (dB)

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.

Record the maximum PAPR level associated with a probability of 0.1%.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)
   =P(W) - [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 9kHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

= P(W) - [43 + 10log(P)] (dB)

= [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

= -13dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C steps up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at 20±5° C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

    = P(W) - [43 + 10log(P)] (dB)

    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)

    = -13dBm.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Feb. 23, 2017~ Mar. 09, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 13, 2016	Feb. 23, 2017~ Mar. 09, 2017	Oct. 12, 2017	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 22, 2016	Mar. 11, 2017	Apr. 21, 2017	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Aug. 20, 2016	Mar. 11, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Mar. 11, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 15, 2017	Mar. 11, 2017	Feb. 14, 2018	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	Apr. 22, 2016	Mar. 11, 2017	Apr. 21, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1~26.5GHz Gain 30dB	Oct. 13, 2016	Mar. 11, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35 -HG	1887435	18~40GHz	Oct. 13, 2016	Mar. 11, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Mar. 11, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Mar. 11, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Mar. 11, 2017	NCR	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 22, 2016	Mar. 11, 2017	Apr. 21, 2017	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 16, 2016	Mar. 11, 2017	Apr. 15, 2017	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 16, 2016	Mar. 11, 2017	Apr. 15, 2017	Radiation (03CH03-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 15, 2017	Mar. 11, 2017	Feb. 14, 2018	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 09, 2016	Mar. 11, 2017	Aug. 08, 2017	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 13, 2016	Mar. 11, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
Amplifier	MITEQ	TTA1840-35 -HG	1887435	18GHz~40GHz	Oct. 13, 2016	Mar. 11, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Mar. 11, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Mar. 11, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Mar. 11, 2017	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.2dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz) for 03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.7dB

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz) for 03CH02-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.3dB

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz) for 03CH03-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.8dB

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz) for 03CH03-KS

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.3dB

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.71	32.72	32.70	29.90	29.95	29.99
GPRS class 8	32.69	32.70	32.69	29.88	29.93	29.98
GPRS class 10	31.91	31.93	31.94	29.05	29.11	29.17
GPRS class 11	29.82	29.84	29.82	26.98	27.04	27.10
GPRS class 12	28.47	28.43	28.47	25.70	25.77	25.82
EGPRS class 8	26.87	26.83	26.81	25.62	25.66	25.57
EGPRS class 10	25.94	25.81	25.82	24.61	24.62	24.57
EGPRS class 11	23.91	23.84	23.85	22.56	22.60	22.56
EGPRS class 12	22.61	22.59	22.60	21.46	21.53	21.46

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.34	23.44	23.58	23.42	23.57	23.46	23.45	23.42	23.56
RMC 12.2K	23.36	23.46	23.59	23.43	23.59	23.47	23.46	23.43	23.57
HSDPA Subtest-1	22.17	22.30	22.46	22.24	22.48	22.30	22.42	22.36	22.49
HSDPA Subtest-2	22.19	22.35	22.55	22.24	22.47	21.98	22.47	22.39	22.48
HSDPA Subtest-3	21.73	21.87	22.01	21.75	22.03	21.88	21.98	21.94	22.02
HSDPA Subtest-4	21.70	21.85	21.98	21.73	22.01	21.84	21.95	21.91	21.97
DC-HSDPA Subtest-1	22.01	22.10	22.18	22.05	22.29	22.1	22.19	22.16	22.30
DC-HSDPA Subtest-2	22.03	22.11	22.20	22.07	22.26	22.09	22.23	22.19	22.31
DC-HSDPA Subtest-3	21.54	21.64	21.70	21.70	21.81	21.75	21.68	21.64	21.75
DC-HSDPA Subtest-4	21.52	21.61	21.67	21.60	21.79	21.62	21.64	21.60	21.72
HSUPA Subtest-1	20.25	20.34	20.52	20.24	20.43	20.33	20.44	20.37	20.48
HSUPA Subtest-2	20.22	20.29	20.49	20.22	20.43	20.30	20.48	20.36	20.47
HSUPA Subtest-3	21.20	21.36	21.53	21.25	21.46	21.32	21.45	21.37	21.51
HSUPA Subtest-4	19.65	19.82	19.94	19.69	19.94	19.82	19.89	19.83	19.99
HSUPA Subtest-5	22.20	22.30	22.50	22.20	22.40	22.30	22.40	22.40	22.40
HSPA+ (16QAM) Subtest-1	19.51	19.70	19.76	19.54	19.77	19.72	19.70	19.63	19.79

ERP/EIRP

GSM850 (G_T - L_C= -0.40dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.71	32.72	32.70
Conducted Power (Watts)	1.866	1.871	1.862
ERP(dBm)	30.16	30.17	30.15
ERP(Watts)	1.038	1.040	1.035

EDGE850 (G_T - L_C= -0.40dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	26.87	26.83	26.81
Conducted Power (Watts)	0.486	0.482	0.480
ERP(dBm)	24.32	24.28	24.26
ERP(Watts)	0.270	0.268	0.267

GSM1900 (G_T - L_C= 1.40dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	29.90	29.95	29.99
Conducted Power (Watts)	0.977	0.989	0.998
EIRP(dBm)	31.30	31.35	31.39
EIRP(Watts)	1.349	1.365	1.377

EDGE1900 (G_T - L_C= 1.40dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	25.62	25.66	25.57
Conducted Power (Watts)	0.365	0.368	0.361
EIRP(dBm)	27.02	27.06	26.97
EIRP(Watts)	0.504	0.508	0.498

WCDMA Band V (G_T - $L_{C=}$ -0.40dB)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.4	846.6
Conducted Power (dBm)	23.36	23.46	23.59
Conducted Power (Watts)	0.217	0.222	0.229
ERP(dBm)	20.81	20.91	21.04
ERP(Watts)	0.121	0.123	0.127

WCDMA Band II (G_T - $L_{C=}$ 1.40dB)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Conducted Power (dBm)	23.43	23.59	23.47
Conducted Power (Watts)	0.220	0.229	0.222
EIRP(dBm)	24.83	24.99	24.87
EIRP(Watts)	0.304	0.316	0.307

WCDMA Band IV (G_T - $L_{C=}$ -0.40dB)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	23.46	23.43	23.57
Conducted Power (Watts)	0.222	0.220	0.228
EIRP(dBm)	23.06	23.03	23.17
EIRP(Watts)	0.202	0.201	0.207

Peak-to-Average Ratio

Mode	GSM850(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.07	PASS
Middle CH	0.12	3.07	
Highest CH	0.12	3.07	

Mode	GSM1900(dB)		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.36	PASS
Middle CH	0.14	3.42	
Highest CH	0.12	3.25	

Mode	WCDMA Band V(dB)	WCDMA Band II(dB)	WCDMA Band IV(dB)	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.87	2.87	2.93	PASS
Middle CH	2.96	2.93	2.93	
Highest CH	2.75	2.67	2.75	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)	
Lowest Channel	
	
Middle Channel	
	
Highest Channel	
	

26dB Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.315	0.314
Middle CH	0.317	0.313
Highest CH	0.315	0.317

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.314	0.313
Middle CH	0.312	0.312
Highest CH	0.315	0.317

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.87	4.86	4.86
Middle CH	4.87	4.86	4.85
Highest CH	4.87	4.87	4.86

GSM850 (GSM)

Lowest Channel



Lowest Channel



Middle Channel



Middle Channel



Highest Channel



Highest Channel



GSM1900 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)	
Lowest Channel	
	
Middle Channel	
	
Highest Channel	
	

Occupied Bandwidth

Mode	GSM850(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.244	0.247
Middle CH	0.242	0.251
Highest CH	0.243	0.248

Mode	GSM1900(MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.243	0.247
Middle CH	0.240	0.247
Highest CH	0.243	0.244

Mode	WCDMA Band V(MHz)	WCDMA Band II(MHz)	WCDMA Band IV(MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.21	4.21	4.21
Middle CH	4.20	4.21	4.20
Highest CH	4.20	4.20	4.20

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)

Lowest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Middle Channel



Highest Channel



Highest Channel



WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)	
Lowest Channel	
	
Middle Channel	
	
Highest Channel	
	

Conducted Band Edge

GSM850 (GSM)	
Lowest Band Edge	**Highest Band Edge**





GSM850 (EDGE class 8)	
Lowest Band Edge	**Highest Band Edge**





GSM1900 (GSM)	
Lowest Band Edge	**Highest Band Edge**



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-40.01 dBm	-27.01 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-17.81 dBm	-4.81 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85027 GHz	21.48 dBm	-13.52 dB

Date: 23.FEB.2017 03:52:57



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90987 GHz	22.72 dBm	-12.28 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-20.84 dBm	-7.84 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91104 GHz	-39.89 dBm	-26.89 dB

Date: 23.FEB.2017 03:54:48

GSM1900 (EDGE class 8)	
Lowest Band Edge	**Highest Band Edge**
	

Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84897 GHz	-40.83 dBm	-27.83 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84997 GHz	-29.70 dBm	-16.70 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85017 GHz	15.42 dBm	-19.58 dB

Date: 23.FEB.2017 04:20:45

Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90982 GHz	14.85 dBm	-20.15 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91001 GHz	-29.74 dBm	-16.74 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91102 GHz	-40.99 dBm	-27.99 dB

Date: 23.FEB.2017 04:22:22

WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.98651 MHz	-36.45 dBm	-23.45 dB
823.000 MHz	824.000 MHz	50.000 kHz	823.99900 MHz	-17.99 dBm	-4.99 dB
824.000 MHz	829.000 MHz	100.000 kHz	824.92158 MHz	7.16 dBm	-27.84 dB

Date: 23.FEB.2017 02:19:57

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
844.000 MHz	849.000 MHz	100.000 kHz	845.74575 MHz	7.75 dBm	-27.25 dB
849.000 MHz	850.000 MHz	50.000 kHz	849.00100 MHz	-18.43 dBm	-5.43 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.03247 MHz	-35.17 dBm	-22.17 dB

Date: 23.FEB.2017 02:22:50

WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84869 GHz	-21.84 dBm	-8.84 dB
1.849 GHz	1.850 GHz	50.000 kHz	1.85000 GHz	-18.02 dBm	-5.02 dB
1.850 GHz	1.855 GHz	100.000 kHz	1.85102 GHz	7.53 dBm	-27.47 dB

Date: 23.FEB.2017 01:58:15

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.905 GHz	1.910 GHz	100.000 kHz	1.90619 GHz	7.56 dBm	-27.44 dB
1.910 GHz	1.911 GHz	50.000 kHz	1.91000 GHz	-19.35 dBm	-6.35 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91123 GHz	-23.45 dBm	-10.45 dB

Date: 23.FEB.2017 02:01:07

WCDMA Band IV (RMC 12.2Kbps)	
Lowest Band Edge	**Highest Band Edge**



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.705 GHz	1.709 GHz	1.000 MHz	1.70860 GHz	-22.11 dBm	-9.11 dB
1.709 GHz	1.710 GHz	50.000 kHz	1.71000 GHz	-17.75 dBm	-4.75 dB
1.710 GHz	1.715 GHz	100.000 kHz	1.71097 GHz	7.91 dBm	-27.09 dB

Date: 23.FEB.2017 01:27:28



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.750 GHz	1.755 GHz	100.000 kHz	1.75110 GHz	8.02 dBm	-26.98 dB
1.755 GHz	1.756 GHz	50.000 kHz	1.75500 GHz	-18.73 dBm	-5.73 dB
1.756 GHz	1.760 GHz	1.000 MHz	1.75622 GHz	-22.65 dBm	-9.65 dB

Date: 23.FEB.2017 01:30:18

Conducted Spurious Emission

Note: Below 1MHz fail points are Spectrum Analyzer signal which can be ignored.

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	46.47001 kHz*	-2.87 dBm*	10.13 dB*
30.000 MHz	1.000 GHz	1.000 MHz	787.43378 MHz	-36.73 dBm	-23.73 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.65856 GHz	-38.73 dBm	-25.73 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.38753 GHz	-36.63 dBm	-23.63 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.67229 GHz	-32.59 dBm	-19.59 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.31804 GHz	-32.33 dBm	-19.33 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.79233 GHz	-28.78 dBm	-15.78 dB

Date: 1.MAR.2017 18:44:14

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	106.42204 kHz*	-2.75 dBm*	10.25 dB*
30.000 MHz	1.000 GHz	1.000 MHz	796.64418 MHz	-37.70 dBm	-24.70 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.76329 GHz	-38.13 dBm	-25.13 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.68925 GHz	-36.76 dBm	-23.76 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.62380 GHz	-33.29 dBm	-20.29 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.31144 GHz	-32.64 dBm	-19.64 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.32722 GHz	-29.36 dBm	-16.36 dB

Date: 1.MAR.2017 18:50:03

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	61.45802 kHz*	0.64 dBm*	13.64 dB*
30.000 MHz	1.000 GHz	1.000 MHz	868.87306 MHz	-36.78 dBm	-23.78 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.71810 GHz	-38.39 dBm	-25.39 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.67108 GHz	-36.44 dBm	-23.44 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.38333 GHz	-32.36 dBm	-19.36 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.42175 GHz	-32.24 dBm	-19.24 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.89432 GHz	-29.01 dBm	-16.01 dB

Date: 1.MAR.2017 18:45:22

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	121.41004 kHz*	0.14 dBm*	13.14 dB*
30.000 MHz	1.000 GHz	1.000 MHz	704.05547 MHz	-37.22 dBm	-24.22 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.78271 GHz	-38.31 dBm	-25.31 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.60748 GHz	-35.79 dBm	-22.79 dB
3.000 GHz	7.000 GHz	1.000 MHz	4.93001 GHz	-33.02 dBm	-20.02 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.74418 GHz	-31.86 dBm	-18.86 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.93124 GHz	-29.37 dBm	-16.37 dB

Date: 1.MAR.2017 18:50:38

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	106.42204 kHz*	-0.64 dBm*	12.36 dB*
30.000 MHz	1.000 GHz	1.000 MHz	962.43128 MHz	-36.92 dBm	-23.92 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.63069 GHz	-37.44 dBm	-24.44 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.29789 GHz	-35.49 dBm	-22.49 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.50931 GHz	-31.53 dBm	-18.53 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.22123 GHz	-32.75 dBm	-19.75 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.94892 GHz	-29.08 dBm	-16.08 dB

Date: 1.MAR.2017 18:45:49

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	91.43403 kHz*	-2.61 dBm*	10.39 dB*
30.000 MHz	1.000 GHz	1.000 MHz	981.33683 MHz	-36.19 dBm	-23.19 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.10789 GHz	-37.69 dBm	-24.69 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.91450 GHz	-36.74 dBm	-23.74 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.67629 GHz	-32.78 dBm	-19.78 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.40478 GHz	-32.54 dBm	-19.54 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.37789 GHz	-28.84 dBm	-15.84 dB

Date: 1.MAR.2017 18:51:04

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	100.000 kHz	16.49400 kHz*	-1.30 dBm*	11.70 dB*
30.000 MHz	820.000 MHz	1.000 MHz	819.80260 MHz	-35.30 dBm	-22.30 dB
855.000 MHz	1.000 GHz	1.000 MHz	965.76087 MHz	-37.59 dBm	-24.59 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.71641 GHz	-37.53 dBm	-24.53 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.61442 GHz	-32.64 dBm	-19.64 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.53518 GHz	-34.70 dBm	-21.70 dB

Date: 1.MAR.2017 18:08:25

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	100.000 kHz	16.49400 kHz*	-0.71 dBm*	12.29 dB*
30.000 MHz	820.000 MHz	1.000 MHz	137.19891 MHz	-37.51 dBm	-24.51 dB
855.000 MHz	1.000 GHz	1.000 MHz	931.55797 MHz	-38.13 dBm	-25.13 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.60242 GHz	-37.18 dBm	-24.18 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.21685 GHz	-33.19 dBm	-20.19 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.68466 GHz	-35.09 dBm	-22.09 dB

Date: 1.MAR.2017 18:09:04

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	100.000 kHz	16.49400 kHz*	-1.27 dBm*	11.73 dB*
30.000 MHz	820.000 MHz	1.000 MHz	732.94603 MHz	-37.90 dBm	-24.90 dB
855.000 MHz	1.000 GHz	1.000 MHz	855.10870 MHz	-36.58 dBm	-23.58 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.95988 GHz	-37.01 dBm	-24.01 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.62680 GHz	-33.37 dBm	-20.37 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.07762 GHz	-35.13 dBm	-22.13 dB

Date: 1.MAR.2017 18:09:38

WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	106.42204 kHz*	-2.60 dBm*	10.40 dB*
30.000 MHz	1.000 GHz	1.000 MHz	976.48926 MHz	-36.89 dBm	-23.89 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.84394 GHz	-30.27 dBm	-17.27 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.97891 GHz	-35.41 dBm	-22.41 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.95776 GHz	-32.73 dBm	-19.73 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.29871 GHz	-32.96 dBm	-19.96 dB
13.600 GHz	19.100 GHz	1.000 MHz	17.06888 GHz	-29.60 dBm	-16.60 dB

Date: 1.MAR.2017 18:25:49

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	76.44603 kHz*	0.29 dBm*	13.29 dB*
30.000 MHz	1.000 GHz	1.000 MHz	391.38681 MHz	-36.45 dBm	-23.45 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.84268 GHz	-37.68 dBm	-24.68 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.99763 GHz	-35.84 dBm	-22.84 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.75578 GHz	-32.71 dBm	-19.71 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.76068 GHz	-32.97 dBm	-19.97 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.93910 GHz	-29.44 dBm	-16.44 dB

Date: 1.MAR.2017 18:27:08

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
9.000 kHz	30.000 MHz	1.000 MHz	61.45802 kHz*	-2.54 dBm*	10.46 dB*
30.000 MHz	1.000 GHz	1.000 MHz	790.82709 MHz	-37.20 dBm	-24.20 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.73499 GHz	-37.78 dBm	-24.78 dB
1.915 GHz	3.000 GHz	1.000 MHz	1.91561 GHz	-30.78 dBm	-17.78 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.70979 GHz	-32.28 dBm	-19.28 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.86486 GHz	-32.75 dBm	-19.75 dB
13.600 GHz	19.100 GHz	1.000 MHz	18.69637 GHz	-29.84 dBm	-16.84 dB

Date: 1.MAR.2017 18:27:36

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0036	0.0287	PASS
40	Normal Voltage	0.0024	0.0024	
30	Normal Voltage	0.0084	0.0359	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0048	0.0191	
0	Normal Voltage	0.0048	0.0263	
-10	Normal Voltage	0.0072	0.0347	
-20	Normal Voltage	0.0012	0.0395	
-30	Normal Voltage	0.0036	0.0323	
20	Maximum Voltage	0.0000	0.0347	
20	Normal Voltage	0.0096	0.0311	
20	Battery End Point	0.0072	0.0215	

Note: Normal Voltage = 3.8V. ；Battery End Point (BEP) = 3.5 V.；Maximum Voltage =4.4 V

Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0043	0.0181	PASS
40	Normal Voltage	0.0005	0.0191	
30	Normal Voltage	0.0191	0.0053	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0027	0.0165	
0	Normal Voltage	0.0016	0.0027	
-10	Normal Voltage	0.0154	0.0197	
-20	Normal Voltage	0.0000	0.0021	
-30	Normal Voltage	0.0149	0.0218	
20	Maximum Voltage	0.0138	0.0181	
20	Normal Voltage	0.0128	0.0122	
20	Battery End Point	0.0048	0.0186	

Note:

1. Normal Voltage = 3.8V. ；Battery End Point (BEP) = 3.5 V.；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0012	PASS
40	Normal Voltage	0.0191	
30	Normal Voltage	0.0179	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0060	
0	Normal Voltage	0.0239	
-10	Normal Voltage	0.0215	
-20	Normal Voltage	0.0036	
-30	Normal Voltage	0.0155	
20	Maximum Voltage	0.0048	
20	Normal Voltage	0.0203	
20	Battery End Point	0.0143	

Note: Normal Voltage = 3.8V. ；Battery End Point (BEP) = 3.5 V.；Maximum Voltage =4.4 V

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0048	PASS
40	Normal Voltage	0.0037	
30	Normal Voltage	0.0032	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0011	
0	Normal Voltage	0.0043	
-10	Normal Voltage	0.0021	
-20	Normal Voltage	0.0064	
-30	Normal Voltage	0.0027	
20	Maximum Voltage	0.0053	
20	Normal Voltage	0.0032	
20	Battery End Point	0.0016	

Note:

1. Normal Voltage = 3.8V. ；Battery End Point (BEP) = 3.5 V.；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0121	PASS
40	Normal Voltage	0.0139	
30	Normal Voltage	0.0023	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0092	
0	Normal Voltage	0.0063	
-10	Normal Voltage	0.0029	
-20	Normal Voltage	0.0052	
-30	Normal Voltage	0.0017	
20	Maximum Voltage	0.0087	
20	Normal Voltage	0.0012	
20	Battery End Point	0.0081	

Note:

1. Normal Voltage = 3.8V. ；Battery End Point (BEP) = 3.5 V.；Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

For Battery 1

GSM850 (GSM)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-45.13	-13	-32.13	-51.20	-47.45	1.33	5.80	H
	2508	-44.18	-13	-31.18	-55.91	-47.35	1.58	6.90	H
	3348	-67.39	-13	-54.39	-76.60	-70.89	1.85	7.50	H
	1672	-52.06	-13	-39.06	-56.67	-54.38	1.33	5.80	V
	2508	-48.66	-13	-35.66	-58.51	-51.83	1.58	6.90	V
	3348	-67.06	-13	-54.06	-76.08	-70.56	1.85	7.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-62.48	-13	-49.48	-65.08	-64.80	1.33	5.80	H
	2508	-55.63	-13	-42.63	-64.98	-58.80	1.58	6.90	H
	3348	-67.41	-13	-54.41	-76.62	-70.91	1.85	7.50	H
	1672	-67.01	-13	-54.01	-68.88	-69.33	1.33	5.80	V
	2508	-57.36	-13	-44.36	-65.33	-60.53	1.58	6.90	V
	3348	-68.30	-13	-55.30	-77.32	-71.80	1.85	7.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-69.09	-13	-56.09	-72.60	-74.08	1.88	6.87	H
	5640	-64.58	-13	-51.58	-72.77	-71.88	2.38	9.68	H
	7520	-61.94	-13	-48.94	-73.97	-71.01	2.74	11.81	H
	3760	-67.90	-13	-54.90	-71.69	-72.89	1.88	6.87	V
	5640	-64.82	-13	-51.82	-73.39	-72.12	2.38	9.68	V
	7520	-63.43	-13	-50.43	-74.14	-72.50	2.74	11.81	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (EDGE class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-68.14	-13	-55.14	-71.65	-73.13	1.88	6.87	H
	5640	-65.32	-13	-52.32	-73.51	-72.62	2.38	9.68	H
	7520	-61.93	-13	-48.93	-73.96	-71.00	2.74	11.81	H
	3760	-67.60	-13	-54.60	-71.39	-72.59	1.88	6.87	V
	5640	-65.55	-13	-52.55	-74.12	-72.85	2.38	9.68	V
	7520	-64.19	-13	-51.19	-74.9	-73.26	2.74	11.81	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-67.92	-13	-54.92	-70.52	-70.24	1.33	5.80	H
	2512	-55.99	-13	-42.99	-65.34	-59.16	1.58	6.90	H
	3342	-61.77	-13	-48.77	-70.98	-65.27	1.85	7.50	H
	1672	-69.31	-13	-56.31	-71.18	-71.63	1.33	5.80	V
	2512	-56.79	-13	-43.79	-64.76	-59.96	1.58	6.90	V
	3342	-64.06	-13	-51.06	-73.08	-67.56	1.85	7.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3760	-69.02	-13	-56.02	-72.53	-74.01	1.88	6.87	H
	5640	-64.87	-13	-51.87	-73.06	-72.17	2.38	9.68	H
	7520	-60.98	-13	-47.98	-73.01	-70.05	2.74	11.81	H
	3760	-68.86	-13	-55.86	-72.65	-73.85	1.88	6.87	V
	5640	-64.28	-13	-51.28	-72.85	-71.58	2.38	9.68	V
	7520	-63.63	-13	-50.63	-74.34	-72.70	2.74	11.81	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-64.21	-13	-51.21	-71.00	-69.10	1.81	6.70	H
	5196	-56.06	-13	-43.06	-68.74	-62.96	2.23	9.13	H
	6930	-59.84	-13	-46.84	-75.02	-67.90	2.60	10.66	H
	3465	-65.25	-13	-52.25	-70.45	-70.14	1.81	6.70	V
	5199	-56.98	-13	-43.98	-70.53	-63.88	2.23	9.13	V
	6930	-59.89	-13	-46.89	-74.94	-67.95	2.6	10.66	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

For Battery 2

GSM850 (GSM)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-50.33	-13	-37.33	-55.56	-52.65	1.33	5.80	H
	2508	-45.41	-13	-32.41	-56.87	-48.58	1.58	6.90	H
	3348	-67.13	-13	-54.13	-76.34	-70.63	1.85	7.50	H
	1672	-55.65	-13	-42.65	-59.33	-57.97	1.33	5.80	V
	2508	-53.02	-13	-40.02	-61.18	-56.19	1.58	6.90	V
	3348	-67.64	-13	-54.64	-76.66	-71.14	1.85	7.50	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-68.66	-13	-55.66	-72.17	-73.65	1.88	6.87	H
	5640	-64.36	-13	-51.36	-72.55	-71.66	2.38	9.68	H
	7521	-62.50	-13	-49.50	-74.53	-71.57	2.74	11.81	H
	3759	-68.61	-13	-55.61	-72.4	-73.60	1.88	6.87	V
	5640	-64.27	-13	-51.27	-72.84	-71.57	2.38	9.68	V
	7521	-62.77	-13	-49.77	-73.48	-71.84	2.74	11.81	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV(RMC 12.2Kbps)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-64.01	-13	-51.01	-70.80	-68.90	1.81	6.70	H
	5199	-58.75	-13	-45.75	-71.43	-65.65	2.23	9.13	H
	6930	-59.25	-13	-46.25	-74.43	-67.31	2.60	10.66	H
	3465	-66.08	-13	-53.08	-71.28	-70.97	1.81	6.70	V
	5199	-57.52	-13	-44.52	-71.07	-64.42	2.23	9.13	V
	6930	-59.05	-13	-46.05	-74.1	-67.11	2.6	10.66	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.