



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
PRODUCT ID : 10644
FCC ID : IHDT56WD1
STANDARD : FCC Part 15 Subpart E §15.407
CLASSIFICATION : (NII) Unlicensed National Information Infrastructure

The product was received on Mar. 27, 2017 and testing was completed on May 15, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.

James Huang

Prepared by: James Huang / Manager



Approved by: Jones Tsai / Manager



Sporton International (KunShan) INC.

No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China



TABLE OF CONTENTS

1	GENERAL DESCRIPTION	5
1.1	Applicant	5
1.2	Manufacturer	5
1.3	Product Feature of Equipment Under Test.....	5
1.4	Product Specification of Equipment Under Test.....	6
1.5	Specification of Accessory.....	7
1.6	Modification of EUT	7
1.7	Testing Location	8
1.8	Applicable Standards.....	8
2	TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1	Carrier Frequency Channel	9
2.2	Test Mode.....	11
2.3	Connection Diagram of Test System.....	13
2.4	Support Unit used in test configuration and system	14
2.5	EUT Operation Test Setup	14
2.6	Measurement Results Explanation Example.....	15
3	TEST RESULT	16
3.1	26dB & 99% Occupied Bandwidth Measurement	16
3.2	Maximum Conducted Output Power Measurement	19
3.3	Power Spectral Density Measurement	23
3.4	Unwanted Radiated Emission Measurement	26
3.5	AC Conducted Emission Measurement.....	32
3.6	Frequency Stability Measurement.....	36
3.7	Automatically Discontinue Transmission	37
3.8	Antenna Requirements	38
4	LIST OF MEASURING EQUIPMENTS.....	39
5	UNCERTAINTY OF EVALUATION	40
APPENDIX A. CONDUCTED TEST RESULTS		
APPENDIX B. RADIATED SPURIOUS EMISSION		
APPENDIX C. DUTY CYCLE PLOTS		
APPENDIX D. SETUP PHOTOGRAPHS		



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR732707D	Rev. 01	Initial issue of report	May 24, 2017
FR732707D	Rev. 02	Update the report for revising HW version	May 27, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	2.1049 15.403(i)	26dB & 99% Bandwidth	-	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	FCC ≤ 24 dBm (depend on band)	Pass	-
3.3	15.407(a)	Power Spectral Density	FCC ≤ 11 dBm (depend on band)	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b) 15.209(a)	Pass	Under limit 3.26 dB at 5350.300 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 10.84 dB at 0.630 MHz
3.6	15.407(g)	Frequency Stability	Within Operation Band	Pass	-
3.7	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.8	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Product ID	10644
FCC ID	IHDT56WD1
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/ WCDMA/HSPA/DC-HSDPA HSPA+(16QAM uplink is not supported)/LTE WLAN2.4GHz 802.11b/g/n HT20 WLAN5GHz 802.11a/n HT20/HT40 Bluetooth v3.0+EDR/ Bluetooth v4.0 LE/ Bluetooth v4.1 LE/ Bluetooth v4.2 LE
IMEI Code	Conducted: 355668080019974 Radiation: 355668080033629 Conduction: 355668080020477
HW Version	DVT1
SW Version	NPR26.7
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	5180 MHz ~ 5240 MHz 5260 MHz ~ 5320 MHz 5500 MHz ~ 5720 MHz
Maximum Output Power to Antenna	<5180 MHz ~ 5240 MHz> 802.11a : 16.25 dBm / 0.0422 W 802.11n HT20 : 16.14 dBm / 0.0411 W 802.11n HT40 : 15.03 dBm / 0.0318 W <5260 MHz ~ 5320 MHz> 802.11a : 16.26 dBm / 0.0423 W 802.11n HT20 : 16.21 dBm / 0.0418 W 802.11n HT40 : 15.01 dBm / 0.0317 W <5500 MHz ~ 5720 MHz > 802.11a : 15.55 dBm / 0.0359 W 802.11n HT20 : 15.54 dBm / 0.0358 W 802.11n HT40 : 14.80 dBm / 0.0302 W
Maximum Output Power to Antenna for Straddle Channel	802.11a : 14.51 dBm / 0.0282 W 802.11n HT20 : 14.59 dBm / 0.0288 W 802.11n HT40 : 15.26 dBm / 0.0336 W
99% Occupied Bandwidth	<5180 MHz ~ 5240 MHz> 802.11a : 19.63 MHz 802.11n HT20 : 20.18 MHz 802.11n HT40 : 36.96 MHz <5260 MHz ~ 5320 MHz> 802.11a : 19.73 MHz 802.11n HT20 : 20.43 MHz 802.11n HT40 : 37.06 MHz <5500 MHz ~ 5720 MHz > 802.11a : 20.08 MHz 802.11n HT20 : 21.58 MHz 802.11n HT40 : 37.96 MHz
99% Occupied Bandwidth for Straddle Channel	802.11a : 18.78 MHz 802.11n HT20 : 19.83 MHz 802.11n HT40 : 37.36 MHz
Antenna Gain / Gain	<5180 MHz ~ 5240 MHz > IFA Antenna with gain 0.10 dBi <5260 MHz ~ 5320 MHz > IFA Antenna with gain 0.10 dBi <5500 MHz ~ 5720 MHz > IFA Antenna with gain -0.10 dBi
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)

1.5 Specification of Accessory

Specification of Accessory				
AC Adapter 1	Brand Name	Motorola (Acbel)	Model Name	C-P35 SPN5945A
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5.2 Vdc, 2000mA		
AC Adapter 2	Brand Name	Motorola (Salom)	Model Name	SSW-2919UMTJ C-P35 SPN5945A
	Power Rating	I/P: 100-240 Vac, 300mA, O/P: 5.2 Vdc, 2000mA		
Battery	Brand Name	Motorola (Amperex)	Model Name	HE50
	Power Rating	3.8Vdc, 5000mAh	Type	Li-ion
USB Cable	Brand Name	Motorola	Model Name	SKN6462A
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

1.6 Modification of EUT

No modifications are made to the EUT during all test items.



1.7 Testing Location

Test Site	Sporton International (KunShan) INC.			
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958			
Test Site No.	Sporton Site No.			FCC Registration No.
	TH01-KS	03CH02-KS	CO01-KS	418269

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conducted emission (150 kHz to 30 MHz) and radiated emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (X plane) were recorded in this report.

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5180-5240 MHz Band 1 (U-NII-1)	36	5180	44	5220
	38*	5190	46*	5230
	40	5200	48	5240
	-	-	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5260-5320 MHz Band 2 (U-NII-2A)	52	5260	60	5300
	54*	5270	62*	5310
	56	5280	64	5320
	-	-	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5500-5700 MHz Band 3 (U-NII-2C)	100	5500	112	5560
	102*	5510	116	5580
	104	5520	132	5660
	-	-	134*	5670
	108	5540	136	5680
	110*	5550	140	5700



Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
TDWR Channel	120	5600	126*	5630
	-	-	128	5640
	124	5620	-	-

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
Straddle Channel	-	-	144	5720
	142*	5710	-	-

Note: The above Frequency and Channel in "*" were 802.11n HT40.

2.2 Test Mode

Final test mode of conducted test items and radiated spurious emissions are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

AC Conducted Emission	Mode 1 : GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 1) + Earphone
	Mode 2 : GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 2) + Earphone
Remark: The worst case of conducted emission is mode 2; only the test data of it was reported.	




Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5720MHz
		802.11a	802.11a	802.11a
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140
Straddle		-	-	144

Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5720MHz
		802.11n HT20	802.11n HT20	802.11n HT20
L	Low	36	52	100
M	Middle	44	60	116
H	High	48	64	140
Straddle		-	-	144

Ch. #		Band I : 5180-5240 MHz	Band II : 5260-5320 MHz	Band III : 5500-5720MHz
		802.11n HT40	802.11n HT40	802.11n HT40
L	Low	38	54	102
M	Middle	-	-	110
H	High	46	62	134
Straddle		-	-	142


2.3 Connection Diagram of Test System

<WLAN5GHz 802.11a/n HT20 Tx Mode>



<WLAN5GHz 802.11n HT40 Tx Mode>



<AC Conducted Emission Mode>


2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	LINKSYS	WRT600N	Q87-WRT600NV11	N/A	Unshielded, 1.8 m
3.	Notebook	Lenovo	G480	PRC4	N/A	AC I/P: Unshielded, 1.8 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
5.	SD Card	Kingston	4GB	N/A	N/A	N/A
6.	Earphone	Lenovo	LH102	N/A	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the Notebook under large package sizes transmission.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 6.8 dB.

Offset (dB) = RF cable loss(dB).

= 6.8 (dB)

3 Test Result

3.1 26dB & 99% Occupied Bandwidth Measurement

3.1.1 Description of 26dB & 99% Occupied Bandwidth

This section is for reporting purpose only.

There is no restriction limits for bandwidth.

For Straddle Channel, U-NII procedures and limits were applied for operations in the frequency band in accordance with FCC KDB 644545 D03.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures



1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04. Section C) Emission bandwidth
2. Set RBW = approximately 1% of the emission bandwidth.
3. Set the VBW > RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1%.
7. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1MHz and set the Video bandwidth (VBW) $\geq 3 * RBW$.
8. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of 26dB & 99% Occupied Bandwidth Plots

Please refer to Appendix A.



Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum conducted output power over the frequency band of operation shall not exceed 250 mW.

For the 5.25–5.725 GHz bands, the maximum conducted output power over the frequency bands of operation shall not exceed the lesser of 250 mW or $11 \text{ dBm} + 10 \log B$, where B is the 26 dB emission bandwidth in megahertz.

For Straddle Channel, U-NII procedures and limits were applied for operations in the frequency band in accordance with FCC KDB 644545 D03.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Note that U-NII-2 band, devices with a maximum e.i.r.p. greater than 500 mW shall implement TPC in order to have the capability to operate at least 6 dB below the maximum permitted e.i.r.p. of 1 W.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Method PM (Measurement using an RF average power meter):


1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, $10 \log(1/x)$, where x is the duty cycle.

For straddle channel, the testing follows Method SA-3 (RMS detection with max hold) of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.


Compute power by integrating the spectrum across the 99% occupied bandwidth of the signal using the instrument's band power measurement function.

3.2.4 Test Setup

For normal channel:



For straddle channel:






3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.







3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

<FCC 14-30 CFR 15.407>

For mobile and portable client devices in the 5.15–5.25 GHz band, the maximum power spectral density shall not exceed 11dBm in any 1 megahertz band.

For the 5.25–5.725 GHz bands, the maximum power spectral density shall not exceed 11 dBm in any 1 megahertz band.

For Straddle Channel, U-NII procedures and limits were applied for operations in the frequency band in accordance with FCC KDB 644545 D03.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.


Section F) Maximum power spectral density.

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).


1. The testing follows Method SA-2 of FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.
 - Measure the duty cycle.
 - Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 1 MHz.
 - Set VBW $\geq$ 3 MHz.
 - Number of points in sweep $\geq$ 2 Span / RBW.
 - Sweep time = auto.
 - Detector = RMS
 - Trace average at least 100 traces in power averaging mode.
 - Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6$ dB if the duty cycle is 25 percent.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.



Note: Average Power Density (dB) = Measured value+ Duty Factor

3.4 Unwanted Radiated Emission Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

- (1) For transmitters operating in the 5150-5250 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27dBm/MHz.

For transmitters operating in the 5250-5350 MHz band: all emissions outside of the 5150-5350 MHz band shall not exceed an EIRP of -27 dBm/MHz. Devices operating in the 5250-5350 MHz band that generate emissions in the 5150-5250 MHz band must meet all applicable technical requirements for operation in the 5150-5250 MHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5150-5250 MHz band.

For transmitters operating in the 5470-5725MHz band: all emissions outside of the 5470-5725MHz band shall not exceed an EIRP of -27 dBm/MHz.

- (2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$



EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D01 v01r04 G)2)c)

- (i) Section 15.407(b)(1) to (b)(3) specify the unwanted emission limits for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.³
- (ii) Section 15.407(b)(4) specifies the unwanted emission limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are in terms of a Peak detector. An alternative to the band emissions mask is specified in Section 15.407(b)(4)(ii). The alternative limits are based on the highest antenna gain specified in the filing. There are also marketing and importation restrictions for the devices using the alternative limit.⁴

Note 3: An out-of-band emission that complies with both the average and peak limits of Section 15.209 is not required to satisfy the -27 dBm/MHz peak emission limit.

Note 4: Only devices with antenna gains of 10 dBi or less may be approved using the emission limits specified in Section 15.247(d) till March 2, 2018; all other devices operating in this band must use the mask specified in Section 15.407(b)(4)(i).

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v01r04.

Section G) Unwanted emissions measurement.

(1) Procedure for Unwanted Emissions Measurements Below 1000MHz

- RBW = 120 kHz
- VBW = 300 kHz
- Detector = Peak
- Trace mode = max hold

(2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz

- RBW = 1 MHz
- VBW $\geq$ 3 MHz
- Detector = Peak
- Sweep time = auto
- Trace mode = max hold


(3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz

- RBW = 1 MHz
- VBW = 10 Hz, when duty cycle is no less than 98 percent.
- VBW $\geq$ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.4.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

3.4.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.4.7 Duty Cycle

Please refer to Appendix C.

3.4.8 Test Result of Radiated Spurious Emissions (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 2) + Earphone		




Site : CO01-KS
Condition : FCC PART 15E LISN-L-161017-060103 LINE

mode : Mode 2
IMEI : 355668080020477

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.155	44.51	-21.23	65.74	33.60	0.52	10.39	QP
2	0.155	32.71	-23.03	55.74	21.80	0.52	10.39	Average
3	0.185	42.29	-21.95	64.24	31.60	0.34	10.35	QP
4	0.185	30.59	-23.65	54.24	19.90	0.34	10.35	Average
5	0.226	36.18	-26.43	62.61	25.60	0.27	10.31	QP
6	0.226	26.18	-26.43	52.61	15.60	0.27	10.31	Average
7	0.433	32.37	-24.83	57.20	21.90	0.27	10.20	QP
8	0.433	24.27	-22.93	47.20	13.80	0.27	10.20	Average
9	0.611	36.04	-19.96	56.00	25.60	0.26	10.18	QP
10	0.611	30.74	-15.26	46.00	20.30	0.26	10.18	Average
11	0.668	39.03	-16.97	56.00	28.60	0.25	10.18	QP
12 *	0.668	33.33	-12.67	46.00	22.90	0.25	10.18	Average



Test Mode :	Mode 2	Temperature :	22~24℃
Test Engineer :	Eligah Wang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	GSM850 Idle + Bluetooth Link + WLAN Link (5G) + USB Cable (Charging from Adapter 2) + Earphone		



Site : CO01-KS
Condition : FCC PART 15E LISN-N-161017-060103 NEUTRAL

mode : Mode 2
IMEI : 355668080020477

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.150	41.33	-24.67	66.00	30.60	0.34	10.39	QP
2	0.150	36.03	-19.97	56.00	25.30	0.34	10.39	Average
3	0.191	38.27	-25.71	63.98	27.60	0.33	10.34	QP
4	0.191	27.97	-26.01	53.98	17.30	0.33	10.34	Average
5	0.459	33.17	-23.54	56.71	22.60	0.38	10.19	QP
6	0.459	25.87	-20.84	46.71	15.30	0.38	10.19	Average
7	0.585	40.46	-15.54	56.00	29.90	0.38	10.18	QP
8	0.585	34.86	-11.14	46.00	24.30	0.38	10.18	Average
9	0.630	42.16	-13.84	56.00	31.60	0.38	10.18	QP
10 *	0.630	35.16	-10.84	46.00	24.60	0.38	10.18	Average
11	0.665	37.26	-18.74	56.00	26.70	0.38	10.18	QP
12	0.665	27.86	-18.14	46.00	17.30	0.38	10.18	Average

3.6 Frequency Stability Measurement

3.6.1 Limit of Frequency Stability

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emission is maintained within the band of operation under all conditions of normal operation as specified in the user's manual.


3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures

1. To ensure emission at the band edge is maintained within the authorized band, those values shall be measured by radiation emissions at upper and lower frequency points, and finally compensated by frequency deviation as procedures below.
2. The EUT was operated at the maximum output power, and connected to the spectrum analyzer, which is set to maximum hold function and peak detector. The peak value of the power envelope was measured and noted. The upper and lower frequency points were respectively measured relatively 10dB lower than the measured peak value.
3. The frequency deviation was calculated by adding the upper frequency point and the lower frequency point divided by two. Those detailed values of frequency deviation are provided in table below.

3.6.4 Test Setup



3.6.5 Test Result of Frequency Stability

Please refer to Appendix A.

The frequency band 5180-5240MHz which was verified by testing against other standard is less than 20 ppm which is sufficient to maintain the signal within the 5150-5250MHz band.



3.7 Automatically Discontinue Transmission

3.7.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.7.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.7.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.



3.8 Antenna Requirements

3.8.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.8.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.8.3 Antenna Gain

The antenna gain is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.



4 List of Measuring Equipments

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Apr. 11, 2017~ May 01, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Pulse Power Sensor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 19, 2017	Apr. 11, 2017~ May 01, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 19, 2017	Apr. 11, 2017~ May 01, 2017	Jan. 18, 2018	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 13, 2016	Apr. 11, 2017~ May 01, 2017	Oct. 13, 2017	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz; Max 30dBm	Aug. 09, 2016	Apr. 11, 2017~ May 15, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 22, 2016	Apr. 11, 2017~ May 15, 2017	Apr. 21, 2017	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz, MAX 30dB	Apr. 18, 2017		Apr. 17, 2018	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 23, 2016	Apr. 11, 2017~ May 15, 2017	Nov. 22, 2017	Radiation (03CH01-KS)
Bilog Antenna	TeseQ	CBL6112D	37879	30MHz~2GHz	Aug. 20, 2016	Apr. 11, 2017~ May 15, 2017	Aug. 19, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 22, 2016	Apr. 11, 2017~ May 15, 2017	Oct. 21, 2017	Radiation (03CH02-KS)
High Gain Amplifier	MITEQ	AMF-7D-0010 1800-30-10P	1943529	1GHz~18GHz	Jan. 19, 2017	Apr. 11, 2017~ May 15, 2017	Jan. 18, 2018	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 15, 2017	Apr. 11, 2017~ May 15, 2017	Feb. 14, 2018	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 09, 2016	Apr. 11, 2017~ May 15, 2017	Aug. 08, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1GHz~26.5GHz	Oct. 13, 2016	Apr. 11, 2017~ May 15, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18GHz~40GHz	Oct. 13, 2016	Apr. 11, 2017~ May 15, 2017	Oct. 12, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	6160100024 73	N/A	NCR	Apr. 11, 2017~ May 15, 2017	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Apr. 11, 2017~ May 15, 2017	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Apr. 11, 2017~ May 15, 2017	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESC17	100768	9kHz~7GHz	Apr. 29, 2016	Apr. 11, 2017~ Apr. 23, 2017	Apr. 28, 2017	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2016	Apr. 11, 2017~ Apr. 23, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2016	Apr. 11, 2017~ Apr. 23, 2017	Oct. 12, 2017	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 13, 2016	Apr. 11, 2017~ Apr. 23, 2017	Oct. 12, 2017	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2dB
--	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.7dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.3dB
--	-------



Appendix A. Conducted Test Results

Report Number : FR732707D

Test Engineer:	Silent Hai	Temperature:	21~25	°C
Test Date:	2017/4/11~2017/5/1	Relative Humidity:	51~55	%

TEST RESULTS DATA
26dB and 99% OBW

Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)		
11a	6Mbps	1	36	5180	18.78	24.43	-	22.74		
11a	6Mbps	1	44	5220	19.63	28.62	-	22.93		
11a	6Mbps	1	48	5240	19.58	33.32	-	22.92		
HT20	MCS0	1	36	5180	19.43	24.28	-	22.88		
HT20	MCS0	1	44	5220	19.93	34.87	-	23.00		
HT20	MCS0	1	48	5240	20.18	34.42	-	23.01		
HT40	MCS0	1	38	5190	36.66	44.24	-	23.01		
HT40	MCS0	1	46	5230	36.96	46.57	-	23.01		

TEST RESULTS DATA
Average Power Table

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	36	5180	0.60	14.17	24.00	0.10		Pass
11a	6Mbps	1	44	5220	0.60	15.99	24.00	0.10		Pass
11a	6Mbps	1	48	5240	0.60	16.25	24.00	0.10		Pass
HT20	MCS0	1	36	5180	0.63	14.12	24.00	0.10		Pass
HT20	MCS0	1	44	5220	0.63	16.00	24.00	0.10		Pass
HT20	MCS0	1	48	5240	0.63	16.14	24.00	0.10		Pass
HT40	MCS0	1	38	5190	0.65	8.48	24.00	0.10		Pass
HT40	MCS0	1	46	5230	0.65	15.03	24.00	0.10		Pass

TEST RESULTS DATA
Power Spectral Density

FCC Band I										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)	-	Pass/Fail
11a	6Mbps	1	36	5180	0.60	3.90	11.00	0.10		Pass
11a	6Mbps	1	44	5220	0.60	5.33	11.00	0.10		Pass
11a	6Mbps	1	48	5240	0.60	5.70	11.00	0.10		Pass
HT20	MCS0	1	36	5180	0.63	3.24	11.00	0.10		Pass
HT20	MCS0	1	44	5220	0.63	5.02	11.00	0.10		Pass
HT20	MCS0	1	48	5240	0.63	5.42	11.00	0.10		Pass
HT40	MCS0	1	38	5190	0.65	-5.14	11.00	0.10		Pass
HT40	MCS0	1	46	5230	0.65	1.26	11.00	0.10		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	52	5260	19.73	31.77	23.95	29.95	23.98	
11a	6M bps	1	60	5300	19.43	33.67	23.88	29.88	23.98	
11a	6M bps	1	64	5320	19.58	30.02	23.92	29.92	23.98	
HT20	MCS 0	1	52	5260	20.28	32.87	23.98	30.00	23.98	
HT20	MCS 0	1	60	5300	20.43	34.57	23.98	30.00	23.98	
HT20	MCS 0	1	64	5320	20.18	30.42	23.98	30.00	23.98	
HT40	MCS 0	1	54	5270	37.06	46.57	23.98	30.00	23.98	
HT40	MCS 0	1	62	5310	36.56	44.60	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table

FCC Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	52	5260	0.60	15.95	23.98	0.10	26.99	Pass
11a	6M bps	1	60	5300	0.60	16.26	23.98	0.10	26.99	Pass
11a	6M bps	1	64	5320	0.60	15.01	23.98	0.10	26.99	Pass
HT20	MCS 0	1	52	5260	0.63	15.88	23.98	0.10	26.99	Pass
HT20	MCS 0	1	60	5300	0.63	16.21	23.98	0.10	26.99	Pass
HT20	MCS 0	1	64	5320	0.63	14.94	23.98	0.10	26.99	Pass
HT40	MCS 0	1	54	5270	0.65	15.01	23.98	0.10	26.99	Pass
HT40	MCS 0	1	62	5310	0.65	10.44	23.98	0.10	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band II										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	52	5260	0.60	5.49	11.00	0.10		Pass
11a	6M bps	1	60	5300	0.60	5.52	11.00	0.10		Pass
11a	6M bps	1	64	5320	0.60	4.30	11.00	0.10		Pass
HT20	MCS 0	1	52	5260	0.63	5.07	11.00	0.10		Pass
HT20	MCS 0	1	60	5300	0.63	5.22	11.00	0.10		Pass
HT20	MCS 0	1	64	5320	0.63	4.07	11.00	0.10		Pass
HT40	MCS 0	1	54	5270	0.65	1.19	11.00	0.10		Pass
HT40	MCS 0	1	62	5310	0.65	-3.10	11.00	0.10		Pass

TEST RESULTS DATA
26dB and 99% OBW

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6M bps	1	100	5500	19.18	26.22	23.83	29.83	23.98	
11a	6M bps	1	116	5580	20.08	33.52	23.98	30.00	23.98	
11a	6M bps	1	140	5700	18.43	23.33	23.66	29.66	23.98	
HT20	MCS 0	1	100	5500	19.68	27.77	23.94	29.94	23.98	
HT20	MCS 0	1	116	5580	21.58	36.66	23.98	30.00	23.98	
HT20	MCS 0	1	140	5700	19.18	23.98	23.83	29.83	23.98	
HT40	MCS 0	1	102	5510	36.86	45.67	23.98	30.00	23.98	
HT40	MCS 0	1	110	5550	37.46	49.54	23.98	30.00	23.98	
HT40	MCS 0	1	134	5670	37.96	54.04	23.98	30.00	23.98	

TEST RESULTS DATA
Average Power Table

FCC Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)	EIRP Power Limit (dBm)	Pass/Fail
11a	6M bps	1	100	5500	0.60	14.41	23.98	-0.10	26.99	Pass
11a	6M bps	1	116	5580	0.60	15.55	23.98	-0.10	26.99	Pass
11a	6M bps	1	140	5700	0.60	11.08	23.98	-0.10	26.99	Pass
HT20	MCS 0	1	100	5500	0.63	14.44	23.98	-0.10	26.99	Pass
HT20	MCS 0	1	116	5580	0.63	15.54	23.98	-0.10	26.99	Pass
HT20	MCS 0	1	140	5700	0.63	11.14	23.98	-0.10	26.99	Pass
HT40	MCS 0	1	102	5510	0.65	9.54	23.98	-0.10	26.99	Pass
HT40	MCS 0	1	110	5550	0.65	14.80	23.98	-0.10	26.99	Pass
HT40	MCS 0	1	134	5670	0.65	14.24	23.98	-0.10	26.99	Pass

TEST RESULTS DATA
Power Spectral Density

Band III										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6M bps	1	100	5500	0.60	3.84	11.00	-0.10		Pass
11a	6M bps	1	116	5580	0.60	5.06	11.00	-0.10		Pass
11a	6M bps	1	140	5700	0.60	0.54	11.00	-0.10		Pass
HT20	MCS 0	1	100	5500	0.63	3.95	11.00	-0.10		Pass
HT20	MCS 0	1	116	5580	0.63	5.10	11.00	-0.10		Pass
HT20	MCS 0	1	140	5700	0.63	0.06	11.00	-0.10		Pass
HT40	MCS 0	1	102	5510	0.65	-3.72	11.00	-0.10		Pass
HT40	MCS 0	1	110	5550	0.65	1.39	11.00	-0.10		Pass
HT40	MCS 0	1	134	5670	0.65	0.60	11.00	-0.10		Pass

TEST RESULTS DATA
26dB and 99% OBW

Straddle Channel										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26dB Emission Bandwidth (MHz)	IC 99% Bandwidth Power Limit (dBm)	IC 99% Bandwidth EIRP Limit (dBm)	FCC 26dB Bandwidth Power Limit (dBm)	Note
11a	6Mbps	1	144	5720	18.78	24.83	-	-	-	
				NII-2C	14.4905	17.837	22.61	28.61	23.51	
				NII-3	4.2907	6.988	30.00	36.02	-	
HT20	MCS0	1	144	5720	19.83	24.53	-	-	-	
				NII-2C	15.0899	17.537	22.79	28.79	23.44	
				NII-3	4.7403	6.988	30.00	36.02	-	
HT40	MCS0	1	142	5710	37.36	54.58	-	-	-	
				NII-2C	33.8811	43.771	23.98	30.00	23.98	
				NII-3	3.4815	10.804	30.00	36.02	-	

TEST RESULTS DATA
Average Power Table

FCC Straddle Channel										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6Mbps	1	144	5720	0.60	14.51	-	-0.10		Pass
				NII-2C	0.60	13.58	23.51	-0.10		Pass
				NII-3	0.60	7.34	30.00	-0.10		Pass
HT20	MCS0	1	144	5720	0.63	14.59	-	-0.10		Pass
				NII-2C	0.63	13.55	23.44	-0.10		Pass
				NII-3	0.63	7.89	30.00	-0.10		Pass
HT40	MCS0	1	142	5710	0.65	15.26	-	-0.10		Pass
				NII-2C	0.65	14.97	23.98	-0.10		Pass
				NII-3	0.65	3.36	30.00	-0.10		Pass

TEST RESULTS DATA
Power Spectral Density

Straddle Channel										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Power Density (dBm/MHz)	Average PSD Limit (dBm/MHz)	DG (dBi)		Pass/Fail
11a	6Mbps	1	144	NII-2C	0.60	4.03	11.00	-0.10		Pass
				NII-3	0.60	4.03	30.00	-0.10		Pass
HT20	MCS0	1	144	NII-2C	0.63	4.16	11.00	-0.10		Pass
				NII-3	0.63	4.16	30.00	-0.10		Pass
HT40	MCS0	1	142	NII-2C	0.65	1.64	11.00	-0.10		Pass
				NII-3	0.65	1.64	30.00	-0.10		Pass

TEST RESULTS DATA
Frequency Stability

Band I										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	36	5180	5179.925	-0.075	-14.48	50	3.8	
11a	6Mbps	1	36	5180	5179.975	-0.025	-4.83	-30	3.8	
11a	6Mbps	1	36	5180	5179.900	-0.100	-19.31	25	4.4	
11a	6Mbps	1	36	5180	5179.925	-0.075	-14.48	25	3.4	
11a	6Mbps	1	36	5180	5179.925	-0.075	-14.48	25	3.8	

Band II										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	52	5260	5259.925	-0.075	-14.26	50	3.8	
11a	6Mbps	1	52	5260	5259.950	-0.050	-9.51	-30	3.8	
11a	6Mbps	1	52	5260	5259.950	-0.050	-9.51	25	4.4	
11a	6Mbps	1	52	5260	5259.925	-0.075	-14.26	25	3.4	
11a	6Mbps	1	52	5260	5259.950	-0.050	-9.51	25	3.8	

Band III										
Mod.	Data Rate	N _{TX}	CH.	Freq. (MHz)	Center Frequency (MHz)	Frequency Deviation (MHz)	Frequency Stability (ppm)	Temperature (°C)	Voltage (V)	Note
11a	6Mbps	1	100	5500	5499.950	-0.050	-9.09	50	3.8	
11a	6Mbps	1	100	5500	5499.950	-0.050	-9.09	-30	3.8	
11a	6Mbps	1	100	5500	5499.950	-0.050	-9.09	25	4.4	
11a	6Mbps	1	100	5500	5499.950	-0.050	-9.09	25	3.4	
11a	6Mbps	1	100	5500	5499.950	-0.050	-9.09	25	3.8	



Appendix B. Radiated Spurious Emission

Band 1 - 5150~5250MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 36 5180MHz		5149.76	62.66	-11.34	74	55.09	31.06	7.02	30.51	126	225	P	H
		5150	47.52	-6.48	54	41.56	31.06	7.02	32.12	126	225	A	H
	*	5174	105.09	-	-	97.62	31	7.06	30.59	126	225	P	H
	*	5174	97.46	-	-	89.99	31	7.06	30.59	126	225	A	H
		5149.6	58.08	-15.92	74	50.51	31.06	7.02	30.51	321	263	P	V
		5149.92	45	-9	54	37.43	31.06	7.02	30.51	321	263	A	V
	*	5186	102.38	-	-	94.91	31	7.06	30.59	321	263	P	V
	*	5186	94.64	-	-	87.17	31	7.06	30.59	321	263	A	V
802.11a CH 44 5220MHz		5123.52	49.46	-24.54	74	41.83	31.09	7	30.46	289	215	P	H
		5131.04	40.11	-13.89	54	32.48	31.09	7	30.46	289	215	A	H
	*	5222	104.71	-	-	97.27	30.94	7.11	30.61	289	215	P	H
	*	5222	97.33	-	-	89.89	30.94	7.11	30.61	289	215	A	H
		5393.16	46.89	-27.11	74	39.25	30.65	7.34	30.35	289	215	P	H
		5354.64	38.27	-15.73	54	30.66	30.71	7.3	30.4	289	215	A	H
		5134.56	49.65	-24.35	74	42.02	31.09	7	30.46	294	209	P	V
		5126.88	39.99	-14.01	54	32.36	31.09	7	30.46	294	209	A	V
	*	5214	102.71	-	-	95.27	30.94	7.11	30.61	294	209	P	V
	*	5214	95.88	-	-	88.44	30.94	7.11	30.61	294	209	A	V
		5379.66	47.85	-26.15	74	40.21	30.65	7.34	30.35	294	209	P	V
		5396.58	38.21	-15.79	54	30.54	30.62	7.37	30.32	294	209	A	V



802.11a CH 48 5240MHz		5395.86	47.41	-26.59	74	39.74	30.62	7.37	30.32	123	229	P	H
		5351.76	38.32	-15.68	54	30.71	30.71	7.3	30.4	123	229	A	H
	*	5246	106.51	-	-	99.03	30.88	7.16	30.56	123	229	P	H
	*	5246	98.28	-	-	90.8	30.88	7.16	30.56	123	229	A	H
		5378.4	47.47	-26.53	74	39.83	30.65	7.34	30.35	299	261	P	V
		5385.06	38.28	-15.72	54	30.64	30.65	7.34	30.35	299	261	A	V
	*	5244	104.86	-	-	97.38	30.88	7.16	30.56	299	261	P	V
	*	5244	97.12	-	-	89.64	30.88	7.16	30.56	299	261	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		10360	39.07	-34.93	74	55.5	37.49	9.9	63.82	150	316	P	H
CH 36		10360	40.63	-33.37	74	57.06	37.49	9.9	63.82	150	0	P	V
5180MHz													
802.11a		10440	41.91	-32.09	74	58.09	37.62	9.94	63.74	150	360	P	H
CH 44		10440	40.79	-33.21	74	56.97	37.62	9.94	63.74	150	360	P	V
5220MHz													
802.11a		10480	40.63	-33.37	74	56.64	37.71	9.97	63.69	150	360	P	H
CH 48		10480	42.28	-31.72	74	58.29	37.71	9.97	63.69	150	360	P	V
5240MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		5147.84	60.74	-13.26	74	54.78	31.06	7.02	32.12	105	251	P	H
		5150	47.32	-6.68	54	41.36	31.06	7.02	32.12	105	251	A	H
	*	5186	101.79	-	-	95.86	31	7.06	32.13	105	251	P	H
	*	5186	94.5	-	-	88.57	31	7.06	32.13	105	251	A	H
		5147.84	56.13	-17.87	74	50.17	31.06	7.02	32.12	354	98	P	V
		5150	43.58	-10.42	54	37.62	31.06	7.02	32.12	354	98	A	V
	*	5174	98.41	-	-	92.48	31	7.06	32.13	354	98	P	V
	*	5174	90.66	-	-	84.73	31	7.06	32.13	354	98	A	V
802.11n HT20 CH 44 5220MHz		5149.12	48.25	-25.75	74	42.29	31.06	7.02	32.12	122	250	P	H
		5128.8	38.92	-15.08	54	32.95	31.09	7	32.12	122	250	A	H
	*	5216	102.68	-	-	96.76	30.94	7.11	32.13	122	250	P	H
	*	5216	94.97	-	-	89.05	30.94	7.11	32.13	122	250	A	H
		5354.1	45.49	-28.51	74	39.63	30.71	7.3	32.15	122	250	P	H
		5356.8	36.73	-17.27	54	30.87	30.71	7.3	32.15	122	250	A	H
		5110.72	48.51	-25.49	74	42.53	31.12	6.98	32.12	364	101	P	V
		5131.04	38.49	-15.51	54	32.52	31.09	7	32.12	364	101	A	V
	*	5212	98.11	-	-	92.19	30.94	7.11	32.13	364	101	P	V
	*	5212	90.88	-	-	84.96	30.94	7.11	32.13	364	101	A	V
		5388.66	45.68	-28.32	74	39.85	30.65	7.34	32.16	364	101	P	V
		5350.14	36.61	-17.39	54	30.75	30.71	7.3	32.15	364	101	A	V



802.11n HT20 CH 48 5240MHz		5385.6	46.61	-27.39	74	40.78	30.65	7.34	32.16	142	251	P	H
		5378.58	36.87	-17.13	54	31.04	30.65	7.34	32.16	142	251	A	H
	*	5244	103.27	-	-	97.37	30.88	7.16	32.14	142	251	P	H
	*	5244	95.48	-	-	89.58	30.88	7.16	32.14	142	251	A	H
		5351.4	45.7	-28.3	74	39.84	30.71	7.3	32.15	361	101	P	V
		5360.4	36.69	-17.31	54	30.83	30.71	7.3	32.15	361	101	A	V
	*	5246	99.37	-	-	93.47	30.88	7.16	32.14	361	101	P	V
	*	5246	91.76	-	-	85.86	30.88	7.16	32.14	361	101	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 36 5180MHz		10360	38.64	-35.36	74	55.07	37.49	9.9	63.82	135	281	P	H
		10360	40.62	-33.38	74	57.05	37.49	9.9	63.82	135	0	P	V
802.11n HT20 CH 44 5220MHz		10440	38.96	-35.04	74	55.14	37.62	9.94	63.74	135	236	P	H
		10440	40.45	-33.55	74	56.63	37.62	9.94	63.74	135	65	P	V
802.11n HT20 CH 48 5240MHz		10480	40.41	-33.59	74	56.42	37.71	9.97	63.69	135	58	P	H
		10480	39.32	-34.68	74	55.33	37.71	9.97	63.69	135	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		5147.04	57.57	-16.43	74	51.61	31.06	7.02	32.12	270	235	P	H
		5150	47.2	-6.8	54	41.24	31.06	7.02	32.12	270	235	A	H
	*	5200	95.96	-	-	90.03	30.97	7.09	32.13	270	235	P	H
	*	5200	88.02	-	-	82.09	30.97	7.09	32.13	270	235	A	H
		5365.08	45.53	-28.47	74	39.69	30.68	7.32	32.16	270	235	P	H
		5355	36.82	-17.18	54	30.96	30.71	7.3	32.15	270	235	A	H
		5149.92	52.04	-21.96	74	46.08	31.06	7.02	32.12	340	143	P	V
		5150	42.03	-11.97	54	36.07	31.06	7.02	32.12	340	143	A	V
	*	5202	92.25	-	-	86.32	30.97	7.09	32.13	340	143	P	V
	*	5202	84.18	-	-	78.25	30.97	7.09	32.13	340	143	A	V
		5379.84	45.64	-28.36	74	39.81	30.65	7.34	32.16	340	143	P	V
		5390.28	36.67	-17.33	54	30.84	30.65	7.34	32.16	340	143	A	V
802.11n HT40 CH 46 5230MHz		5139.04	52.3	-21.7	74	46.33	31.09	7	32.12	282	233	P	H
		5150	41.73	-12.27	54	35.77	31.06	7.02	32.12	282	233	A	H
	*	5244	102.57	-	-	96.67	30.88	7.16	32.14	282	233	P	H
	*	5244	94.78	-	-	88.88	30.88	7.16	32.14	282	233	A	H
		5369.94	47.15	-26.85	74	41.31	30.68	7.32	32.16	282	233	P	H
		5362.56	37.34	-16.66	54	31.5	30.68	7.32	32.16	282	233	A	H
		5122.4	49.21	-24.79	74	43.23	31.12	6.98	32.12	336	141	P	V
		5127.2	39.63	-14.37	54	33.66	31.09	7	32.12	336	141	A	V
	*	5244	97.48	-	-	91.58	30.88	7.16	32.14	336	141	P	V
	*	5244	90.11	-	-	84.21	30.88	7.16	32.14	336	141	A	V
		5370.48	46	-28	74	40.16	30.68	7.32	32.16	336	141	P	V
		5390.82	36.87	-17.13	54	31.04	30.65	7.34	32.16	336	141	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 38 5190MHz		10380	39.07	-34.93	74	55.44	37.52	9.91	63.8	100	360	P	H
		10380	39.32	-34.68	74	55.69	37.52	9.91	63.8	100	360	P	V
802.11n HT40 CH 46 5230MHz		10460	41.39	-32.61	74	57.51	37.65	9.95	63.72	100	360	P	H
		10460	40.21	-33.79	74	56.33	37.65	9.95	63.72	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 1 5150~5250MHz

Band 2 - 5250~5350MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 52 5260MHz		5125.12	50.16	-23.84	74	42.53	31.09	7	30.46	300	216	P	H
		5105.92	40.04	-13.96	54	32.36	31.12	6.98	30.42	300	216	A	H
	*	5266	106.15	-	-	98.65	30.85	7.18	30.53	300	216	P	H
	*	5266	98.34	-	-	90.84	30.85	7.18	30.53	300	216	A	H
		5124.96	51.22	-22.78	74	43.59	31.09	7	30.46	295	261	P	V
		5102.08	40.03	-13.97	54	32.3	31.15	6.95	30.37	295	261	A	V
	*	5254	104.77	-	-	97.29	30.88	7.16	30.56	295	261	P	V
	*	5254	96.91	-	-	89.43	30.88	7.16	30.56	295	261	A	V
802.11a CH 60 5300MHz		5101.6	50.05	-23.95	74	42.32	31.15	6.95	30.37	115	271	P	H
		5100.8	40.09	-13.91	54	32.36	31.15	6.95	30.37	115	271	A	H
	*	5296	107.26	-	-	99.72	30.79	7.23	30.48	115	271	P	H
	*	5296	99.95	-	-	92.41	30.79	7.23	30.48	115	271	A	H
		5355.8	56.95	-17.05	74	49.34	30.71	7.3	30.4	115	271	P	H
	!	5352.2	48.57	-5.43	54	40.96	30.71	7.3	30.4	115	271	A	H
		5116.32	49.07	-24.93	74	41.39	31.12	6.98	30.42	300	260	P	V
		5103.68	40.11	-13.89	54	32.38	31.15	6.95	30.37	300	260	A	V
	*	5306	105.37	-	-	97.83	30.79	7.23	30.48	300	260	P	V
	*	5306	97.08	-	-	89.54	30.79	7.23	30.48	300	260	A	V
		5352.5	51.85	-22.15	74	44.24	30.71	7.3	30.4	300	260	P	V
		5352.1	44.51	-9.49	54	36.9	30.71	7.3	30.4	300	260	A	V



802.11a CH 64 5320MHz	*	5324	106.96	-	-	99.4	30.76	7.25	30.45	100	270	P	H
	*	5324	99.44	-	-	91.88	30.76	7.25	30.45	100	270	A	H
		5353.2	66.6	-7.4	74	58.99	30.71	7.3	30.4	100	270	P	H
	!	5350.3	50.74	-3.26	54	43.13	30.71	7.3	30.4	100	270	A	H
	*	5314	104.77	-	-	97.21	30.76	7.25	30.45	309	263	P	V
	*	5314	96.99	-	-	89.43	30.76	7.25	30.45	309	263	A	V
		5353.4	59.82	-14.18	74	52.21	30.71	7.3	30.4	309	263	P	V
	!	5350.4	49.48	-4.52	54	41.87	30.71	7.3	30.4	309	263	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		10520	41.85	-32.15	74	57.72	37.78	10	63.65	150	360	P	H
CH 52 5260MHz		10520	42.16	-31.84	74	58.03	37.78	10	63.65	150	0	P	V
802.11a		10600	41.5	-32.5	74	57.07	37.93	10.05	63.55	150	0	P	H
CH 60 5300MHz		10600	40.73	-33.27	74	56.3	37.93	10.05	63.55	150	2	P	V
802.11a		10640	41.36	-32.64	74	56.81	38	10.07	63.52	150	0	P	H
CH 64 5320MHz		10640	40.28	-33.72	74	55.73	38	10.07	63.52	150	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 52 5260MHz		5139.2	48.35	-25.65	74	42.38	31.09	7	32.12	145	249	P	H
		5117.92	38.72	-15.28	54	32.74	31.12	6.98	32.12	145	249	A	H
	*	5268	103.8	-	-	97.91	30.85	7.18	32.14	145	249	P	H
	*	5268	95.7	-	-	89.81	30.85	7.18	32.14	145	249	A	H
		5115.52	48.44	-25.56	74	42.46	31.12	6.98	32.12	363	101	P	V
		5133.12	38.7	-15.3	54	32.73	31.09	7	32.12	363	101	A	V
	*	5254	99.86	-	-	93.96	30.88	7.16	32.14	363	101	P	V
	*	5254	91.96	-	-	86.06	30.88	7.16	32.14	363	101	A	V
802.11n HT20 CH 60 5300MHz		5110.24	47.68	-26.32	74	41.7	31.12	6.98	32.12	355	208	P	H
		5110.4	38.77	-15.23	54	32.79	31.12	6.98	32.12	355	208	A	H
	*	5306	104.75	-	-	98.88	30.79	7.23	32.15	355	208	P	H
	*	5306	97.28	-	-	91.41	30.79	7.23	32.15	355	208	A	H
		5351.9	54.86	-19.14	74	49	30.71	7.3	32.15	355	208	P	H
		5351.8	45.92	-8.08	54	40.06	30.71	7.3	32.15	355	208	A	H
		5116.96	47.39	-26.61	74	41.41	31.12	6.98	32.12	374	101	P	V
		5101.6	38.56	-15.44	54	32.57	31.15	6.95	32.11	374	101	A	V
	*	5304	98.73	-	-	92.86	30.79	7.23	32.15	374	101	P	V
	*	5304	91.09	-	-	85.22	30.79	7.23	32.15	374	101	A	V
		5351.9	47.77	-26.23	74	41.91	30.71	7.3	32.15	374	101	P	V
		5351.9	40.39	-13.61	54	34.53	30.71	7.3	32.15	374	101	A	V



802.11n HT20 CH 64 5320MHz	*	5314	104.34	-	-	98.48	30.76	7.25	32.15	352	211	P	H
	*	5314	96.74	-	-	90.88	30.76	7.25	32.15	352	211	A	H
		5351.8	67.73	-6.27	74	61.87	30.71	7.3	32.15	352	211	P	H
	!	5350.8	48.95	-5.05	54	43.09	30.71	7.3	32.15	352	211	A	H
	*	5328	98.55	-	-	92.69	30.74	7.27	32.15	369	102	P	V
	*	5328	90.82	-	-	84.96	30.74	7.27	32.15	369	102	A	V
		5350.2	56.55	-17.45	74	50.69	30.71	7.3	32.15	369	102	P	V
		5350	44.07	-9.93	54	38.21	30.71	7.3	32.15	369	102	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 52 5260MHz		10520	40	-34	74	55.87	37.78	10	63.65	135	26	P	H
		10520	40.53	-33.47	74	56.4	37.78	10	63.65	135	338	P	V
802.11n HT20 CH 60 5300MHz		10600	40.85	-33.15	74	56.42	37.93	10.05	63.55	135	213	P	H
		10600	40.2	-33.8	74	55.77	37.93	10.05	63.55	135	360	P	V
802.11n HT20 CH 64 5320MHz		10640	41.37	-32.63	74	56.82	38	10.07	63.52	135	360	P	H
		10640	40.43	-33.57	74	55.88	38	10.07	63.52	135	105	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 54 5270MHz		5143.04	48.14	-25.86	74	42.18	31.06	7.02	32.12	295	235	P	H
		5128.32	38.73	-15.27	54	32.76	31.09	7	32.12	295	235	A	H
	*	5278	102.51	-	-	96.63	30.82	7.2	32.14	295	235	P	H
	*	5278	94.64	-	-	88.76	30.82	7.2	32.14	295	235	A	H
		5361.8	51.28	-22.72	74	45.44	30.68	7.32	32.16	295	235	P	H
		5350	41.63	-12.37	54	35.77	30.71	7.3	32.15	295	235	A	H
		5132.96	47.62	-26.38	74	41.65	31.09	7	32.12	349	143	P	V
		5108.8	38.74	-15.26	54	32.76	31.12	6.98	32.12	349	143	A	V
	*	5286	96.64	-	-	90.76	30.82	7.2	32.14	349	143	P	V
	*	5286	89.5	-	-	83.62	30.82	7.2	32.14	349	143	A	V
		5351.6	47.69	-26.31	74	41.83	30.71	7.3	32.15	349	143	P	V
		5350.8	38.19	-15.81	54	32.33	30.71	7.3	32.15	349	143	A	V
802.11n HT40 CH 62 5310MHz		5115.36	48.32	-25.68	74	42.34	31.12	6.98	32.12	100	235	P	H
		5102.4	38.79	-15.21	54	32.8	31.15	6.95	32.11	100	235	A	H
	*	5298	97.82	-	-	91.95	30.79	7.23	32.15	100	235	P	H
	*	5298	90.25	-	-	84.38	30.79	7.23	32.15	100	235	A	H
		5352.3	59.97	-14.03	74	54.11	30.71	7.3	32.15	100	235	P	H
	!	5350	50.44	-3.56	54	44.58	30.71	7.3	32.15	100	235	A	H
		5116.16	47.76	-26.24	74	41.78	31.12	6.98	32.12	382	168	P	V
		5102.88	38.52	-15.48	54	32.53	31.15	6.95	32.11	382	168	A	V
	*	5320	92.99	-	-	87.13	30.76	7.25	32.15	382	168	P	V
	*	5320	85.36	-	-	79.5	30.76	7.25	32.15	382	168	A	V
		5350.3	53.64	-20.36	74	47.78	30.71	7.3	32.15	382	168	P	V
		5350.2	44.89	-9.11	54	39.03	30.71	7.3	32.15	382	168	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 54 5270MHz		10540	39.24	-34.76	74	55.05	37.81	10.01	63.63	100	360	P	H
		10540	41.77	-32.23	74	57.58	37.81	10.01	63.63	100	360	P	V
802.11n HT40 CH 62 5310MHz		10620	41.27	-32.73	74	56.79	37.96	10.06	63.54	100	360	P	H
		10620	40.75	-33.25	74	56.27	37.96	10.06	63.54	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 2 5250~5350MHz

Band 3 - 5470~5725MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 100 5500MHz		5469.36	63.21	-10.79	74	55.76	30.5	7.37	30.42	126	271	P	H
	!	5469.52	50.01	-3.99	54	42.56	30.5	7.37	30.42	126	271	A	H
	*	5508	106.48	-	-	99.14	30.44	7.37	30.47	126	271	P	H
	*	5508	99.52	-	-	92.18	30.44	7.37	30.47	126	271	A	H
		5469.84	58.57	-15.43	74	51.12	30.5	7.37	30.42	299	263	P	V
		5470	46.89	-7.11	54	39.44	30.5	7.37	30.42	299	263	A	V
	*	5496	102.59	-	-	95.19	30.47	7.37	30.44	299	263	P	V
	*	5496	95.47	-	-	88.07	30.47	7.37	30.44	299	263	A	V
802.11a CH 116 5580MHz		5428.72	47.66	-26.34	74	40.1	30.56	7.37	30.37	100	215	P	H
		5394.16	39.24	-14.76	54	31.6	30.65	7.34	30.35	100	215	A	H
	*	5574	105.99	-	-	98.87	30.32	7.36	30.56	100	215	P	H
	*	5574	98.28	-	-	91.16	30.32	7.36	30.56	100	215	A	H
		5753.16	49.72	-24.28	74	41.4	31.17	7.56	30.41	100	215	P	H
		5764.44	39.96	-14.04	54	31.64	31.17	7.56	30.41	100	215	A	H
		5434.32	47.61	-26.39	74	40.05	30.56	7.37	30.37	263	264	P	V
		5391.44	38.64	-15.36	54	31	30.65	7.34	30.35	263	264	A	V
	*	5576	101.79	-	-	94.67	30.32	7.36	30.56	263	264	P	V
	*	5576	94.04	-	-	86.92	30.32	7.36	30.56	263	264	A	V
		5738.04	48.14	-25.86	74	40	31.03	7.54	30.43	263	264	P	V
		5764.12	39.63	-14.37	54	31.31	31.17	7.56	30.41	263	264	A	V



802.11a CH 140 5700MHz	*	5694	101.86	-	-	94.27	30.62	7.47	30.5	100	214	P	H
	*	5694	93.34	-	-	85.75	30.62	7.47	30.5	100	214	A	H
		5725.08	57.35	-16.65	74	49.39	30.89	7.52	30.45	100	214	P	H
		5725	45.21	-8.79	54	37.25	30.89	7.52	30.45	100	214	A	H
	*	5706	98.58	-	-	90.82	30.75	7.49	30.48	300	285	P	V
	*	5706	89.75	-	-	81.99	30.75	7.49	30.48	300	285	A	V
		5725.08	53.76	-20.24	74	45.8	30.89	7.52	30.45	300	285	P	V
		5725	43.12	-10.88	54	35.16	30.89	7.52	30.45	300	285	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 100 5500MHz		11000	42.29	-31.71	74	56.44	38.66	10.31	63.12	150	340	P	H
		11000	42.93	-31.07	74	57.08	38.66	10.31	63.12	150	0	P	V
802.11a CH 116 5580MHz		11160	42.55	-31.45	74	56.1	38.97	10.42	62.94	150	360	P	H
		11160	42.4	-31.6	74	55.95	38.97	10.42	62.94	150	81	P	V
802.11a CH 140 5700MHz		11400	44.72	-29.28	74	57.41	39.41	10.57	62.67	150	272	P	H
		11400	44.32	-29.68	74	57.01	39.41	10.57	62.67	150	319	P	V
Remark		1. No other spurious found. 2. All results are PASS against Peak and Average limit line.											



Band 3 - 5470~5725MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		5469.68	58.93	-15.07	74	51.48	30.5	7.37	30.42	189	257	P	H
		5470	50.14	-3.86	54	42.69	30.5	7.37	30.42	189	257	A	H
	*	5496	104.77	-	-	99.11	30.47	7.37	32.18	189	257	P	H
	*	5496	96.9	-	-	91.24	30.47	7.37	32.18	189	257	A	H
		5460.88	53.22	-20.78	74	45.71	30.53	7.37	30.39	302	237	P	V
		5470	44.15	-9.85	54	36.7	30.5	7.37	30.42	302	237	A	V
	*	5496	98.81	-	-	91.41	30.47	7.37	30.44	302	237	P	V
	*	5496	91.59	-	-	84.19	30.47	7.37	30.44	302	237	A	V
802.11n HT20 CH 116 5580MHz		5388.24	46.73	-27.27	74	40.9	30.65	7.34	32.16	113	262	P	H
		5393.2	37.72	-16.28	54	31.89	30.65	7.34	32.16	113	262	A	H
	*	5582	104.26	-	-	98.8	30.29	7.36	32.19	113	262	P	H
	*	5582	97.28	-	-	91.82	30.29	7.36	32.19	113	262	A	H
		5739.88	47.93	-26.07	74	41.84	31.03	7.54	32.48	113	262	P	H
		5753	37.99	-16.01	54	31.78	31.17	7.56	32.52	113	262	A	H
		5465.84	45.95	-28.05	74	40.25	30.5	7.37	32.17	382	171	P	V
		5459.6	37.31	-16.69	54	31.58	30.53	7.37	32.17	382	171	A	V
	*	5574	99.99	-	-	94.5	30.32	7.36	32.19	382	171	P	V
	*	5574	92.34	-	-	86.85	30.32	7.36	32.19	382	171	A	V
		5752.2	47.15	-26.85	74	40.94	31.17	7.56	32.52	382	171	P	V
		5754.6	37.9	-16.1	54	31.69	31.17	7.56	32.52	382	171	A	V



802.11n HT20 CH 140 5700MHz	*	5704	100.06	-	-	94.2	30.75	7.49	32.38	100	260	P	H
	*	5704	91.49	-	-	85.63	30.75	7.49	32.38	100	260	A	H
		5726.04	57.37	-16.63	74	51.39	30.89	7.52	32.43	100	260	P	H
		5725	45.35	-8.65	54	39.37	30.89	7.52	32.43	100	260	A	H
	*	5696	94.29	-	-	88.54	30.62	7.47	32.34	364	171	P	V
	*	5696	85.23	-	-	79.48	30.62	7.47	32.34	364	171	A	V
		5728.44	51.14	-22.86	74	45.16	30.89	7.52	32.43	364	171	P	V
		5725	40.85	-13.15	54	34.87	30.89	7.52	32.43	364	171	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 100 5500MHz		11000	40.43	-33.57	74	54.58	38.66	10.31	63.12	135	304	P	H
		11000	40.85	-33.15	74	55	38.66	10.31	63.12	135	7	P	V
802.11n HT20 CH 116 5580MHz		11160	40.73	-33.27	74	54.28	38.97	10.42	62.94	135	290	P	H
		11160	42.12	-31.88	74	55.67	38.97	10.42	62.94	135	87	P	V
802.11n HT20 CH 140 5700MHz		11400	43.72	-30.28	74	56.41	39.41	10.57	62.67	135	360	P	H
		11400	43.79	-30.21	74	56.48	39.41	10.57	62.67	135	117	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 102 5510MHz		5469.2	59.32	-14.68	74	53.62	30.5	7.37	32.17	100	323	P	H
	!	5469.84	48.56	-5.44	54	42.86	30.5	7.37	32.17	100	323	A	H
	*	5498	94.16	-	-	88.53	30.44	7.37	32.18	100	323	P	H
	*	5498	86.92	-	-	81.29	30.44	7.37	32.18	100	323	A	H
		5751.64	46.87	-27.13	74	40.66	31.17	7.56	32.52	100	323	P	H
		5749.88	37.87	-16.13	54	31.78	31.03	7.54	32.48	100	323	A	H
		5467.6	56.72	-17.28	74	51.02	30.5	7.37	32.17	378	166	P	V
		5469.04	45.5	-8.5	54	39.8	30.5	7.37	32.17	378	166	A	V
	*	5502	90.36	-	-	84.73	30.44	7.37	32.18	378	166	P	V
	*	5502	83.6	-	-	77.97	30.44	7.37	32.18	378	166	A	V
		5733.4	46.73	-27.27	74	40.75	30.89	7.52	32.43	378	166	P	V
		5763.16	37.71	-16.29	54	31.5	31.17	7.56	32.52	378	166	A	V
802.11n HT40 CH 110 5550MHz		5468.24	50.9	-23.1	74	45.2	30.5	7.37	32.17	100	253	P	H
		5469.36	40.44	-13.56	54	34.74	30.5	7.37	32.17	100	253	A	H
	*	5542	98.51	-	-	92.95	30.38	7.36	32.18	100	253	P	H
	*	5542	91.07	-	-	85.51	30.38	7.36	32.18	100	253	A	H
		5758.76	46.79	-27.21	74	40.58	31.17	7.56	32.52	100	253	P	H
		5749	38	-16	54	31.91	31.03	7.54	32.48	100	253	A	H
		5460.56	47.01	-26.99	74	41.28	30.53	7.37	32.17	301	165	P	V
		5468.08	38.7	-15.3	54	33	30.5	7.37	32.17	301	165	A	V
	*	5542	94.26	-	-	88.7	30.38	7.36	32.18	301	165	P	V
	*	5542	86.98	-	-	81.42	30.38	7.36	32.18	301	165	A	V
		5755.64	47.13	-26.87	74	40.92	31.17	7.56	32.52	301	165	P	V
		5754.44	37.87	-16.13	54	31.66	31.17	7.56	32.52	301	165	A	V



802.11n HT40 CH 134 5670MHz		5433.04	46.42	-27.58	74	40.66	30.56	7.37	32.17	100	258	P	H
		5464.56	37.29	-16.71	54	31.59	30.5	7.37	32.17	100	258	A	H
	*	5666	98.68	-	-	93.16	30.34	7.43	32.25	100	258	P	H
	*	5666	90.64	-	-	85.12	30.34	7.43	32.25	100	258	A	H
		5731	56.66	-17.34	74	50.68	30.89	7.52	32.43	100	258	P	H
		5725	45.28	-8.72	54	39.3	30.89	7.52	32.43	100	258	A	H
		5433.84	46.34	-27.66	74	40.58	30.56	7.37	32.17	359	154	P	V
		5469.52	36.98	-17.02	54	31.28	30.5	7.37	32.17	359	154	A	V
	*	5662	94.03	-	-	88.51	30.34	7.43	32.25	359	154	P	V
	*	5662	85.94	-	-	80.42	30.34	7.43	32.25	359	154	A	V
		5726.84	49.78	-24.22	74	43.8	30.89	7.52	32.43	359	154	P	V
		5727.88	40.02	-13.98	54	34.04	30.89	7.52	32.43	359	154	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - 5470~5725MHz
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 102 5510MHz		11020	41.8	-32.2	74	55.89	38.69	10.32	63.1	100	360	P	H
		11020	41.99	-32.01	74	56.08	38.69	10.32	63.1	100	360	P	V
802.11n HT40 CH 110 5550MHz		11100	41.94	-32.06	74	55.74	38.84	10.37	63.01	100	360	P	H
		11100	43.84	-30.16	74	57.64	38.84	10.37	63.01	100	360	P	V
802.11n HT40 CH 134 5670MHz		11340	43.24	-30.76	74	56.17	39.29	10.53	62.75	100	360	P	H
		11340	42.5	-31.5	74	55.43	39.29	10.53	62.75	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 144 5720MHz	*	5716	102.2	-	-	96.34	30.75	7.49	32.38	109	252	P	H
	*	5716	93.57	-	-	87.71	30.75	7.49	32.38	109	252	A	H
	*	5716	96.77	-	-	90.91	30.75	7.49	32.38	299	154	P	V
	*	5716	88.34	-	-	82.48	30.75	7.49	32.38	299	154	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a		11440	44.08	-29.92	74	56.66	39.47	10.59	62.64	100	360	P	H
CH 144 5720MHz		11440	44.11	-29.89	74	56.69	39.47	10.59	62.64	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n	*	5724	102.23	-	-	96.25	30.89	7.52	32.43	100	259	P	H
HT20	*	5724	93.43	-	-	87.45	30.89	7.52	32.43	100	259	A	H
CH 144	*	5726	96.57	-	-	90.59	30.89	7.52	32.43	314	132	P	V
5720MHz	*	5726	87.91	-	-	81.93	30.89	7.52	32.43	314	132	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		11440	43.4	-30.6	74	55.98	39.47	10.59	62.64	100	360	P	H
HT20													V
CH 144		11440	43.24	-30.76	74	55.82	39.47	10.59	62.64	100	360	P	
5720MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n	*	5698	99.67	-	-	93.92	30.62	7.47	32.34	100	256	P	H
HT40	*	5698	91.24	-	-	85.49	30.62	7.47	32.34	100	256	A	H
CH 142	*	5716	94.16	-	-	88.3	30.75	7.49	32.38	298	154	P	V
5710MHz	*	5716	85.43	-	-	79.57	30.75	7.49	32.38	298	154	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 3 - Straddle Channel
WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n		11420	44.07	-29.93	74	56.7	39.44	10.58	62.65	100	360	P	H
HT40													V
CH 142		11420	42.46	-31.54	74	55.09	39.44	10.58	62.65	100	360	P	
5710MHz													
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Emission below 1GHz

WIFI 802.11a (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a LF		33.88	28.28	-11.72	40	35.2	24.06	0.04	31.02	100	98	P	H
		116.33	26.62	-16.88	43.5	39.13	17.64	0.62	30.77	-	-	P	H
		158.04	24.55	-18.95	43.5	36.88	17.05	1.55	30.93	-	-	P	H
		303.54	21.83	-24.17	46	31.35	19.72	2.26	31.5	-	-	P	H
		639.16	27.28	-18.72	46	28.93	26.13	3.01	30.79	-	-	P	H
		975.75	32.5	-21.5	54	30.18	30.62	3.1	31.4	-	-	P	H
		33.88	32.03	-7.97	40	38.95	24.06	0.04	31.02	100	164	P	V
		71.71	24.36	-15.64	40	41.04	13.94	0.78	31.4	-	-	P	V
		139.61	23.54	-19.96	43.5	36.09	17.41	0.9	30.86	-	-	P	V
		148.34	23.45	-20.05	43.5	36.03	17.32	0.99	30.89	-	-	P	V
		163.86	23.56	-19.94	43.5	36.07	16.86	1.58	30.95	-	-	P	V
		514.03	25.76	-20.24	46	30.11	24.29	2.93	31.57	-	-	P	V
Remark		1. No other spurious found. 2. All results are PASS against limit line.											



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	P eak or A verage
H/V	H orizontal or V ertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 01													
2412MHz		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)


= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix C. Duty Cycle Plots


Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.04	1.362	0.734	1kHz
802.11n HT20	86.52	1.274	0.785	1kHz
802.11n HT40	86.12	1.232	0.812	1kHz

802.11a






802.11n HT20



Date: 11.APR.2017 23:26:50

802.11n HT40



Date: 11.APR.2017 23:35:43