



FCC RF Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
Product ID : 10745, 10746
FCC ID : IHDT56WH4
STANDARD : FCC 47 CFR Part 2, and 90(S)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Mar. 17, 2017 and testing was completed on Apr. 26, 2017. We, Sporton International (KunShan) INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA / EIA-603-D-2010 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (KunShan) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



Sporton International (KunShan) INC.

No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China



TABLE OF CONTENTS

REVISION HISTORY.....	3
SUMMARY OF TEST RESULT	4
1 GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Feature of Equipment Under Test.....	5
1.4. Product Specification of Equipment Under Test	6
1.5. Modification of EUT	6
1.6. Specification of Accessory	6
1.7. Maximum Frequency Tolerance, Emission Designator and Conducted Power.....	7
1.8. Testing Site.....	8
1.9. Applied Standards	8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System	10
2.3 Support Unit used in test configuration and system.....	10
2.4 Measurement Results Explanation Example	10
2.5 Frequency List of Low/Middle/High Channels.....	11
3 TEST RESULT	12
3.1 Conducted Output Power Measurement.....	12
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	13
3.3 Emissions Mask Measurement	14
3.4 Emissions Mask – Out Of Band Emissions Measurement.....	16
3.5 Field Strength of Spurious Radiation Measurement	18
3.6 Frequency Stability Measurement.....	20
4 LIST OF MEASURING EQUIPMENT	22
5 UNCERTAINTY OF EVALUATION	23
APPENDIX A. TEST RESULTS OF CONDUCTED TEST	
APPENDIX B. TEST RESULTS OF RADIATED TEST	
APPENDIX C. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW731705	Rev. 01	Initial issue of report	May 31, 2017



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	$< 50 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	$< 43 + 10 \log_{10}(P[\text{Watts}])$	PASS	Under limit 42.92 dB at 2456.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	$< 2.5 \text{ ppm}$	PASS	-



1 General Description

1.1. Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Feature of Equipment Under Test

Product Feature & Specification	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Product ID	10745, 10746
FCC ID	IHDT56WH4
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/HSPA+ (16QAM uplink is not supported)/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth v3.0 + EDR/ Bluetooth v4.0 LE/Bluetooth v4.1 LE
IMEI Code	Conducted: 355654080026813/355654080026821 Radiation: 355654080029734/355654080029742
HW Version	DVT2
SW Version	sanders_n-userdebug 7.1.1 NPS26.85 1826 intcfg.test-keys
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, sample 1 (model name: 10745) is dual SIM slot and sample 2 (model name: 10746) is single SIM slot. According to the difference, we choose sample 1 to perform full test.

1.4. Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	LTE Band 26 : 814.7 ~ 823.3 MHz
Rx Frequency	LTE Band 26 : 859.7 ~ 868.3 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	23.48 dBm
Antenna Type	PIFA Antenna
Type of Modulation	QPSK / 16QAM

Remark: This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).

1.5. Modification of EUT

No modifications are made to the EUT during all test items.

1.6. Specification of Accessory

Specification of Accessory				
AC Adapter	Brand Name	Motorola (Salom)	Model Name	SC-22
	Power Rating	I/P: 100 - 240 Vac, 500 mA, O/P: 5/9/12 Vdc, 3000/1600/1200 mA		
Battery	Brand Name	Motorola (ATL)	Model Name	HG30
	Power Rating	3.8Vdc, 3000mAh	Type	Li-ion, ATL404296
Earphone	Brand Name	Motorola(JuWei)	Model Name	JWEP0998-W09R
	Signal Line Type	1.23 meter, non-shielded cable, without ferrite core		
USB Cable	Brand Name	Motorola (hetong)	Model Name	HT-SJX-17030102
	Signal Line Type	1.02 meter, shielded cable, without ferrite core		

1.7. Maximum Frequency Tolerance, Emission Designator and Conducted Power

FCC Rule	System	Type of Modulation	BW	Frequency Tolerance (ppm)	Emission Designator	Maximum Conducted power(W)
Part 90S	LTE Band 26	QPSK	1.4 MHz	-	1M10G7D	0.2046
Part 90S	LTE Band 26	16QAM	1.4 MHz	-	1M10W7D	0.1626
Part 90S	LTE Band 26	QPSK	3 MHz	-	2M73G7D	0.2042
Part 90S	LTE Band 26	16QAM	3 MHz	-	2M74W7D	0.1592
Part 90S	LTE Band 26	QPSK	5 MHz	-	4M50G7D	0.2018
Part 90S	LTE Band 26	16QAM	5 MHz	-	4M49W7D	0.1622
Part 90S	LTE Band 26	QPSK	10 MHz	0.0077 ppm	8M97G7D	0.1923
Part 90S	LTE Band 26	16QAM	10 MHz	-	9M05W7D	0.1574
Part 90S	LTE Band 26	QPSK	15 MHz	-	13M4G7D	0.2228
Part 90S	LTE Band 26	16QAM	15 MHz	-	13M5W7D	0.1734

1.8. Testing Site

Test Site	Sporton International (KunShan) INC.		
Test Site Location	No.3-2, Pingxiang Road, Kunshan Development Zone, Jiangsu, China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH03-KS	306251

Note: The test site complies with ANSI C63.4 2014 requirement.

1.9. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA / EIA-603-D-2010
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test


2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 10th harmonic.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v			v	v	v
Frequency Stability	26				v		-	v				v		v	
Radiated Spurious Emission	26	v	v	v	v		-	v		v				v	
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GWINSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss

Following shows an offset computation example with cable loss 4.5 dB

$$\begin{aligned}
 \text{Offset (dB)} &= \text{RF cable loss (dB)}. \\
 &= 4.5 \text{ (dB)}
 \end{aligned}$$



2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.


3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.


3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $116 \log_{10}(f/6.1)$ decibels or $50 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least $43 + 10 \log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.


3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor $10 \log (1\% \text{ of OBW/measured RBW})(\text{dB})$ was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least $43 + 10 \log (P)$ dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its 10^{th} harmonic.


3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)
= $P(W) - [43 + 10\log(P)]$ (dB)
= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)
= -13dBm.

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least $43 + 10 \log (P)$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log_{10}(P[\text{Watts}])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures


1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. $\text{EIRP (dBm)} = \text{S.G. Power} - \text{Tx Cable Loss} + \text{Tx Antenna Gain}$
11. $\text{ERP (dBm)} = \text{EIRP} - 2.15$
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from $43 + 10 \log(P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log(P)] \text{ (dB)}$
 $= [30 + 10 \log(P)] \text{ (dBm)} - [43 + 10 \log(P)] \text{ (dB)}$
 $= -13 \text{ dBm}.$

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.


3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at $20\pm 5^{\circ}\text{C}$ and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.



4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 09, 2016	Apr. 18, 2017	Aug. 08, 2017	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 13, 2016	Apr. 18, 2017	Oct. 12, 2017	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz~44GHz	Apr. 18, 2017	Apr. 26, 2017	Apr. 17, 2018	Radiation (03CH03-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 22, 2017	Apr. 26, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1356	1GHz~18GHz	Apr. 22, 2017	Apr. 26, 2017	Apr. 21, 2018	Radiation (03CH03-KS)
Amplifier	SONOMA	310N	187289	9kHz~1GHz	Aug. 09, 2016	Apr. 26, 2017	Aug. 08, 2017	Radiation (03CH03-KS)
Amplifier	Agilent	8449B	3008A02370	1GHz~26.5GHz	Oct. 13, 2016	Apr. 26, 2017	Oct. 12, 2017	Radiation (03CH03-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Apr. 26, 2017	NCR	Radiation (03CH03-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Apr. 26, 2017	NCR	Radiation (03CH03-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Apr. 26, 2017	NCR	Radiation (03CH03-KS)

NCR: No Calibration Required



5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.8dB
---	-------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.3dB
---	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	23.34	-	-
15	1	37		23.48		
15	1	74		23.33		
15	36	0		22.51		
15	36	20		22.46		
15	36	39		22.44		
15	75	0		22.47		
15	1	0	16-QAM	22.39		
15	1	37		22.36		
15	1	74		22.18		
15	36	0		21.43		
15	36	20		21.43		
15	36	39		21.43		
15	75	0		21.49		



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK		22.84	
10	1	25			22.65	
10	1	49			22.63	
10	25	0			21.87	
10	25	12			21.88	
10	25	25			21.91	
10	50	0			21.84	
10	1	0	16-QAM		21.69	
10	1	25			21.97	
10	1	49			21.79	
10	25	0			21.02	
10	25	12			20.97	
10	25	25			21.07	
10	50	0			20.98	
5	1	0	QPSK	22.79	22.78	22.85
5	1	12		22.86	23.00	23.05
5	1	24		22.64	22.91	22.49
5	12	0		21.83	21.75	21.95
5	12	7		21.77	21.80	21.99
5	12	13		21.76	21.93	21.91
5	25	0		21.85	21.83	21.92
5	1	0	16-QAM	21.53	21.55	21.68
5	1	12		21.62	22.03	22.10
5	1	24		21.60	21.74	21.53
5	12	0		20.75	20.66	20.77
5	12	7		21.03	20.64	20.74
5	12	13		21.09	20.79	20.76
5	25	0		20.93	20.98	20.77



LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.90	22.86	22.84
3	1	8		22.98	23.02	23.10
3	1	14		22.75	22.84	22.87
3	8	0		21.97	21.87	21.88
3	8	4		21.89	21.95	21.97
3	8	7		21.89	21.95	21.88
3	15	0		21.81	21.75	21.92
3	1	0	16-QAM	21.52	21.50	21.63
3	1	8		21.62	22.02	21.63
3	1	14		21.61	21.86	21.75
3	8	0		20.93	20.95	20.97
3	8	4		20.99	20.84	20.94
3	8	7		20.86	20.95	21.07
3	15	0		20.60	20.58	20.77
1.4	1	0	QPSK	22.69	22.77	22.72
1.4	1	3		22.80	22.84	22.89
1.4	1	5		22.63	22.65	22.65
1.4	3	0		22.84	22.89	23.11
1.4	3	1		22.93	22.99	23.02
1.4	3	3		22.92	22.86	23.01
1.4	6	0		21.81	21.82	21.87
1.4	1	0	16-QAM	21.65	21.65	21.75
1.4	1	3		21.72	21.72	21.74
1.4	1	5		21.63	21.66	21.62
1.4	3	0		21.94	21.80	21.79
1.4	3	1		22.11	21.81	21.81
1.4	3	3		21.97	21.84	21.89
1.4	6	0		20.85	20.71	20.88


**26dB Bandwidth**

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.256	1.27	3.039	3.027	4.915	4.895	-	-	14.505	14.505	-	-
Middle CH	1.25	1.281	2.997	2.979	4.795	4.955	9.75	9.77	-	-	-	-
Highest CH	1.292	1.267	3.009	3.021	4.905	4.925	-	-	-	-	-	-




LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Date: 18 APR 2017 04:08:27

Lowest Channel / 1.4MHz / 16QAM




Date: 18 APR 2017 04:08:50

Middle Channel / 1.4MHz / QPSK




Date: 18 APR 2017 04:08:33

Middle Channel / 1.4MHz / 16QAM




Date: 18 APR 2017 04:08:14

Highest Channel / 1.4MHz / QPSK




Date: 18 APR 2017 04:08:55


Highest Channel / 1.4MHz / 16QAM




Date: 18 APR 2017 04:10:17

LTE Band 26
Lowest Channel / 3MHz / QPSK



Date: 18 APR 2017 04:11:01

Lowest Channel / 3MHz / 16QAM



Date: 18 APR 2017 04:10:40

Middle Channel / 3MHz / QPSK



Date: 18 APR 2017 04:11:26

Middle Channel / 3MHz / 16QAM








Date: 18 APR 2017 04:11:55

Highest Channel / 3MHz / QPSK


Date: 18 APR 2017 04:12:46

Highest Channel / 3MHz / 16QAM



Date: 18 APR 2017 04:12:16

LTE Band 26
Lowest Channel / 5MHz / QPSK

Lowest Channel / 5MHz / 16QAM

Middle Channel / 5MHz / QPSK

Middle Channel / 5MHz / 16QAM

Highest Channel / 5MHz / QPSK

Highest Channel / 5MHz / 16QAM





LTE Band 26


Middle Channel / 10MHz / QPSK




Middle Channel / 10MHz / 16QAM



Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM




**Occupied Bandwidth**

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.1	2.71	2.72	4.48	4.48	-	-	13.37	13.49	-	-
Middle CH	1.1	1.09	2.73	2.74	4.48	4.49	8.97	9.05	-	-	-	-
Highest CH	1.1	1.09	2.71	2.73	4.5	4.49	-	-	-	-	-	-




LTE Band 26


Lowest Channel / 1.4MHz / QPSK




Lowest Channel / 1.4MHz / 16QAM




Middle Channel / 1.4MHz / QPSK




Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK




Highest Channel / 1.4MHz / 16QAM






LTE Band 26


Lowest Channel / 3MHz / QPSK




Lowest Channel / 3MHz / 16QAM




Middle Channel / 3MHz / QPSK




Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK




Highest Channel / 3MHz / 16QAM






LTE Band 26


Lowest Channel / 5MHz / QPSK




Lowest Channel / 5MHz / 16QAM




Middle Channel / 5MHz / QPSK




Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK




Highest Channel / 5MHz / 16QAM






LTE Band 26

Middle Channel / 10MHz / QPSK



Date: 18 APR 2017 04:16:49


Middle Channel / 10MHz / 16QAM



Date: 18 APR 2017 04:16:26


LTE Band 26

Lowest Channel / 15MHz / QPSK




Date: 18 APR 2017 04:17:15


Lowest Channel / 15MHz / 16QAM




Date: 18 APR 2017 04:17:36

**Conducted Band Edge****LTE Band 26 / 1.4MHz / QPSK****Lowest Band Edge / 1RB**


Date: 18 APR 2017 01:48:51

Highest Band Edge / 1RB

Date: 18 APR 2017 01:49:32

Lowest Band Edge / Full RB

Date: 18 APR 2017 01:48:04


Highest Band Edge / Full RB

Date: 18 APR 2017 01:50:43




LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 18 APR 2017 01:47:29

Highest Band Edge / 1 RB




Date: 18 APR 2017 01:49:58

Lowest Band Edge / Full RB



Date: 18 APR 2017 01:47:50

Highest Band Edge / Full RB




Date: 18 APR 2017 01:50:25




LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB




Date: 18 APR 2017 02:41:08

Highest Band Edge / 1 RB




Date: 18 APR 2017 02:45:15

Lowest Band Edge / Full RB



Date: 18 APR 2017 02:42:04

Highest Band Edge / Full RB




Date: 18 APR 2017 02:43:08




LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 18 APR 2017 02:41:31

Highest Band Edge / 1 RB




Date: 18 APR 2017 02:43:57

Lowest Band Edge / Full RB



Date: 18 APR 2017 02:41:49

Highest Band Edge / Full RB




Date: 18 APR 2017 02:43:32




LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB




Date: 18 APR 2017 02:46:35


Highest Band Edge / 1 RB



Date: 18 APR 2017 02:50:33



Date: 18 APR 2017 02:47:48




Date: 18 APR 2017 02:48:55




LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB




Date: 18 APR 2017 02:46:58


Highest Band Edge / 1 RB



Date: 18 APR 2017 02:50:03



Date: 18 APR 2017 02:47:32




Date: 18 APR 2017 02:49:36




LTE Band 26 / 10MHz / QPSK

Lowest Band Edge / 1 RB




Date: 18 APR 2017 02:52:05

Highest Band Edge / 1 RB



Date: 18 APR 2017 02:53:36




Date: 18 APR 2017 02:53:58




LTE Band 26 / 10MHz / 16QAM

Lowest Band Edge / 1 RB




Date: 18 APR 2017 02:52:33

Highest Band Edge / 1 RB



Date: 18 APR 2017 02:53:09




Date: 18 APR 2017 02:54:24




LTE Band 26 / 15MHz QPSK

Lowest Band Edge / 1 RB




Lowest Band Edge / Full RB




LTE Band 26 / 15MHz 16QAM

Lowest Band Edge / 1 RB



Lowest Band Edge / Full RB






Conducted Spurious Emission


LTE Band 26 / 1.4MHz

Lowest Channel / QPSK




Date: 18.APR.2017 04:01:16

Lowest Channel / 16QAM




Date: 18.APR.2017 04:01:47

Middle Channel / QPSK



Date: 18.APR.2017 04:02:57

Middle Channel / 16QAM




Date: 18.APR.2017 04:02:23




LTE Band 26 / 1.4MHz

Highest Channel / QPSK



Date: 18.APR.2017 04:04:02


Highest Channel / 16QAM



Date: 18.APR.2017 04:04:45


LTE Band 26 / 3MHz

Lowest Channel / QPSK



Date: 18.APR.2017 03:57:24

Lowest Channel / 16QAM




Date: 18.APR.2017 03:56:55




LTE Band 26 / 3MHz

Middle Channel / QPSK




Date: 18.APR.2017 03:55:16

Middle Channel / 16QAM




Date: 18.APR.2017 03:55:56

Highest Channel / QPSK



Date: 18.APR.2017 03:57:57

Highest Channel / 16QAM




Date: 18.APR.2017 03:58:25




LTE Band 26 / 5MHz

Lowest Channel / QPSK




Date: 18.APR.2017 03:50:58

Lowest Channel / 16QAM




Date: 18.APR.2017 03:51:26

Middle Channel / QPSK



Date: 18.APR.2017 03:50:10

Middle Channel / 16QAM




Date: 18.APR.2017 03:49:32




LTE Band 26 / 5MHz

Highest Channel / QPSK



Date: 18.APR.2017 03:52:14


Highest Channel / 16QAM



Date: 18.APR.2017 03:52:42


LTE Band 26 / 10MHz

Middle Channel / QPSK



Date: 18.APR.2017 03:53:37

Middle Channel / 16QAM




Date: 18.APR.2017 03:54:01




LTE Band 26 / 15MHz

Lowest Channel / QPSK



Date: 18.APR.2017 03:42:36

Lowest Channel / 16QAM



Date: 18.APR.2017 03:43:20

Frequency Stability

Test Conditions		LTE Band 26 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	2.5ppm
		Deviation (ppm)	Result
50	Normal Voltage	0.0049	PASS
40	Normal Voltage	0.0063	
30	Normal Voltage	0.0053	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0013	
0	Normal Voltage	0.0046	
-10	Normal Voltage	0.0068	
-20	Normal Voltage	0.0060	
-30	Normal Voltage	0.0016	
20	Maximum Voltage	0.0077	
20	Normal Voltage	0.0002	
20	Battery End Point	0.0070	

Note:

1. Normal Voltage =3.8 V. ; Battery End Point (BEP) =3.6 V. ; Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.



Appendix B. Test Results of Radiated Test

LTE Band 26 / 1.4MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1636	-65.15	-13	-52.15	-63.78	-67.01	1.19	5.20	H
	2456	-55.92	-13	-42.92	-58.91	-58.14	1.53	5.90	H
	3273	-66.49	-13	-53.49	-70.44	-69.28	1.76	6.70	H
	1636	-65.46	-13	-52.46	-63.42	-67.32	1.19	5.20	V
	2456	-63.08	-13	-50.08	-65.06	-65.30	1.53	5.90	V
	3273	-68.85	-13	-55.85	-72.17	-71.64	1.76	6.70	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 3MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1634	-67.10	-13	-54.10	-65.73	-68.96	1.19	5.20	H
	2454	-65.50	-13	-52.50	-68.49	-67.72	1.53	5.90	H
	3270	-67.10	-13	-54.10	-71.05	-69.89	1.76	6.70	H
	1634	-64.37	-13	-51.37	-62.33	-66.23	1.19	5.20	V
	2454	-67.16	-13	-54.16	-69.14	-69.38	1.53	5.90	V
	3270	-69.45	-13	-56.45	-72.77	-72.24	1.76	6.70	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



LTE Band 26 / 5MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1634	-66.07	-13	-53.07	-64.70	-67.93	1.19	5.20	H
	2450	-64.86	-13	-51.86	-67.85	-67.08	1.53	5.90	H
	3267	-66.52	-13	-53.52	-70.47	-69.31	1.76	6.70	H
	1634	-64.94	-13	-51.94	-62.9	-66.80	1.19	5.20	V
	2450	-65.19	-13	-52.19	-67.17	-67.41	1.53	5.90	V
	3267	-67.70	-13	-54.70	-71.02	-70.49	1.76	6.70	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

LTE Band 26 / 10MHz / QPSK / RB Size 1 Offset 0									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1628	-64.37	-13	-51.37	-63.00	-66.23	1.19	5.20	H
	2444	-66.17	-13	-53.17	-69.16	-68.39	1.53	5.90	H
	3258	-66.39	-13	-53.39	-70.34	-69.18	1.76	6.70	H
	1628	-64.77	-13	-51.77	-62.73	-66.63	1.19	5.20	V
	2444	-66.45	-13	-53.45	-68.43	-68.67	1.53	5.90	V
	3258	-68.55	-13	-55.55	-71.87	-71.34	1.76	6.70	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.