

FCC SAR Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT1922-1
FCC ID : IHDT56XB6
STANDARD : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures and had been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.



Approved by: Mark Qu / Manager



Sporton International (Kunshan) Inc.
No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China



Table of Contents

1. Statement of Compliance	4
2. Administration Data	5
3. Guidance Applied	5
4. Equipment Under Test (EUT) Information	6
4.1 General Information	6
4.2 Specification of Accessory	7
4.3 General LTE SAR Test and Reporting Considerations	8
5. Re-use of Measured Data	10
5.1 Introduction Section	10
5.2 Difference Section	10
5.3 Spot Check Verification Data Section	11
5.4 Reference detail Section	11
6. RF Exposure Limits	12
6.1 Uncontrolled Environment	12
6.2 Controlled Environment	12
7. Specific Absorption Rate (SAR)	13
7.1 Introduction	13
7.2 SAR Definition	13
8. System Description and Setup	14
8.1 E-Field Probe	15
8.2 Data Acquisition Electronics (DAE)	15
8.3 Phantom	16
8.4 Device Holder	17
9. Measurement Procedures	18
9.1 Spatial Peak SAR Evaluation	18
9.2 Power Reference Measurement	19
9.3 Area Scan	19
9.4 Zoom Scan	20
9.5 Volume Scan Procedures	20
9.6 Power Drift Monitoring	20
10. Test Equipment List	21
11. System Verification	22
11.1 Tissue Simulating Liquids	22
11.2 Tissue Verification	23
11.3 System Performance Check Results	24
12. RF Exposure Positions	25
12.1 Ear and handset reference point	25
12.2 Definition of the cheek position	26
12.3 Definition of the tilt position	27
12.4 Body Worn Accessory	28
12.5 Product Specific 10g SAR Exposure	28
12.6 Wireless Router	29
13. Conducted RF Output Power (Unit: dBm)	30
14. Antenna Location	43
15. SAR Test Results	44
15.1 Head SAR	46
15.2 Hotspot SAR	47
15.3 Body Worn Accessory SAR	49
15.4 Product specific 10g SAR	50
15.5 Repeated SAR Measurement	51
16. Simultaneous Transmission Analysis	52
16.1 Head Exposure Conditions	53
16.2 Hotspot Exposure Conditions	54
16.3 Body-Worn Accessory Exposure Conditions	56
16.4 SPLSR Evaluation and Analysis	57
17. Uncertainty Assessment	58
18. References	59
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	
Appendix E. Reference Report	

Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA7D0507-01	Rev. 01	Initial issue of report	Feb. 01, 2018

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for **Motorola Mobility LLC, Mobile Cellular Phone, XT1922-1**, are as follows.

<1g SAR>:

Equipment Class	Frequency Band		Highest SAR Summary			Highest Simultaneous Transmission 1g SAR (W/kg)
			Head (Separation 0mm)	Hotspot (Separation 5mm)	Body-worn (Separation 5mm)	
			1g SAR (W/kg)			
Licensed	GSM	GSM850	0.28	0.74	0.74	1.56
		GSM1900	0.12	1.18	1.18	
	WCDMA	Band V	0.40	0.84	0.84	
		Band II	0.21	1.10	1.10	
	LTE	Band 5	0.41	0.88	0.88	
		Band 7	0.39	0.71	0.71	
		Band 26	0.26	0.68	0.68	
		Band 38	0.31	1.19	1.19	
		Band 41	0.18	1.07	1.07	
DTS	WLAN	2.4GHz WLAN	1.11	0.49	0.49	1.56
DSS	Bluetooth	2.4GHz Bluetooth		<0.10	<0.10	1.28
Date of Testing:			2017/12/20 ~ 2017/12/26			

<10g SAR>:

Equipment Class	Frequency Band		Highest SAR Summary
			Product Specific 10g SAR (W/kg) (Gap 0mm)
Licensed	GSM	GSM1900	3.34
	WCDMA	Band II	3.60
	LTE	Band 7	3.30
		Band 38	1.96
		Band 41	1.54

This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

2. Administration Data

Testing Laboratory	
Test Site	Sporton International (Kunshan) Inc.
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL : +86-512-57900158 FAX : +86-512-57900958

Applicant	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

Manufacturer	
Company Name	Motorola Mobility LLC
Address	222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

3. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

4. Equipment Under Test (EUT) Information

4.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1922-1
FCC ID	IHDT56XB6
IMEI Code	SIM1: 351859090026695 SIM2: 351859090026703
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2537.5 MHz ~ 2652.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA HSPA+ (16QAM uplink is not supported) LTE: QPSK, 16QAM WLAN 2.4GHz : 802.11b/g/n HT20 Bluetooth v3.0+EDR, Bluetooth v4.0 LE, Bluetooth v4.1 LE, Bluetooth v4.2 LE
HW Version	DVT1B
SW Version	fastboot_aljeter_oem_userdebug_8.0.0_OPP27.38_1080_intcfg-test-keys
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark: 802.11n-HT40 is not supported in 2.4GHz WLAN. - This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation. - This device 2.4GHz WLAN support hotspot operation and Bluetooth support tethering applications. - This device does not support DTM operation and supports GRPS/EGPRS mode up to multi-slot class 12. - When the phone is in talking mode and receiver worked, all WWAN powers are full power. - When the phone is in talking mode and receiver worked, then power reduction will be implemented immediately in WLAN 2.4GHz. - When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900, WCDMA band II and LTE band 7/38/41. - The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device. When front or back body worn condition is detected, GSM1900, WCDMA band II, and LTE band 7/38/41 reduced power will be active. (P-sensor can't work at detecting presence of the user's body at the four edges of the device.) - This device hotspot reduced power and P-sensor reduced power level are the same. So only show one reduced power level for hotspot reduced power and P-sensor reduced power for this application. - P-sensor can detect handheld state, for bottom side of product specific 10g SAR condition, WCDMA band II reduced power will be active. - There are two different types of EUT. They are dual SIM card mobile and single SIM card mobile. The others are the same including circuit design, PCB board, structure and all components. It is special to declare. After pre-scan two types of EUT, we found test result of the sample that dual SIM was the worst, so we chose dual SIM card mobile to perform all test. - For dual SIM card mobile has two SIM slots and supports dual SIM dual standby. The WWAN radio transmission will be enabled by either one SIM at a time (single active). After pre-scan two SIM cards power, we found test result of the SIM1 was the worse, so we chose SIM1 slot to perform all tests.	

4.2 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola (Salom)	Model Name	SC-22 SPN5970A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(EU)	Brand Name	Motorola (Salom)	Model Name	SC-23 SPN5971A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(UK)	Brand Name	Motorola (Salom)	Model Name	SC-24 SPN5972A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(IN)	Brand Name	Motorola (Salom)	Model Name	SC-25 SPN5973A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(AU)	Brand Name	Motorola (Salom)	Model Name	SC-26 SPN5974A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(AR)	Brand Name	Motorola (Salom)	Model Name	SC-27 SPN5975A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(BR)	Brand Name	Motorola (Salom)	Model Name	SC-28 SPN5976A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 1(BR)	Brand Name	Motorola (Salom)	Model Name	SC-28 SPN5997A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(US)	Brand Name	Motorola (Chenyang)	Model Name	SC-22 SPN5993A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(EU)	Brand Name	Motorola (Chenyang)	Model Name	SC-23 SPN5989A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(UK)	Brand Name	Motorola (Chenyang)	Model Name	SC-24 SPN5990A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(IN)	Brand Name	Motorola (Chenyang)	Model Name	SC-25 SPN5991A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(AU)	Brand Name	Motorola (Chenyang)	Model Name	SC-26 SPN5988A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
AC Adapter 2(AR)	Brand Name	Motorola (Chenyang)	Model Name	SC-27 SPN5992A
	Power Rating	I/P: 100-240 Vac, 500mA, O/P: 5Vdc,3000mA or 9Vdc,1600mA or 12Vdc,1200mA		
Battery	Brand Name	Lenovo (SCUD)	Model Name	BL270
	Power Rating	3.85/4.4Vdc,4000mAh	Type	Li-ion
Earphone	Brand Name	Motorola(NEW LEADER)	Model Name	NLD-EM307E-02SF
	Signal Line Type	1.2 meter, non-shielded cable, without ferrite core		
USB Cable	Brand Name	Motorola (Saibao)	Model Name	SLQ-A077A
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

4.3 General LTE SAR Test and Reporting Considerations

Summarized necessary items addressed in KDB 941225 D05 v02r05								
FCC ID	IHDT56XB6							
Equipment Name	Mobile Cellular Phone							
Operating Frequency Range of each LTE transmission band	LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2537.5 MHz ~ 2652.5 MHz							
Channel Bandwidth	LTE Band 5:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 7: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz							
Uplink Modulations Used	QPSK / 16QAM							
LTE Voice / Data requirements	Voice and Data							
LTE Release Version	R9, Cat4							
CA Support	Not Supported							
LTE MPR permanently built-in by design	Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
	Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
		1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
	QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
	16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
	16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
	64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
	64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM	≥ 1						≤ 5	
LTE A-MPR	In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration	A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Power reduction applied to satisfy SAR compliance	Yes 1. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of LTE band 7/38/41. 2. The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device. When front or back body worn condition is detected LTE band 7/38/41 reduced power will be active. (P-sensor can't work at detecting presence of the user's body at the four edges of the device.)							

Transmission (H, M, L) channel numbers and frequencies in each LTE band										
LTE Band 5										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	20407	824.7	20415	825.5	20425	826.5	20450		829	
M	20525	836.5	20525	836.5	20525	836.5	20525		836.5	
H	20643	848.3	20635	847.5	20625	846.5	20600		844	
LTE Band 7										
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	20775	2502.5	20800	2505	20825	2507.5	20850		2510	
M	21100	2535	21100	2535	21100	2535	21100		2535	
H	21425	2567.5	21400	2565	21375	2562.5	21350		2560	
LTE Band 26										
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5
LTE Band 38										
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	37775	2572.5	37800	2575	37825	2577.5	37850		2580	
M	38000	2595	38000	2595	38000	2595	38000		2595	
H	38225	2617.5	38200	2615	38175	2612.5	38150		2610	
LTE Band 41										
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz			
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)		
L	40065	2537.5	40090	2540	40115	2542.5	40140		2545	
LM	40385	2569.5	40390	2570	40395	2570.5	40400		2571	
HM	40705	2601.5	40690	2600	40685	2599.5	40670		2598	
H	41215	2652.5	41190	2650	41165	2647.5	41140		2645	

5. Re-use of Measured Data

5.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT1922-1, FCC ID: IHDT56XB6) is electrically identical to the reference device (Model: XT1922-5, XT1922-4, FCC ID: IHDT56XB5) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 178919 D01.

5.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration "PED" file.

The re-used RF data includes the following bands provided in Appendix E (Sporton SAR Report No. FA7D0507 for the reference device Model: XT1922-5, XT1922-4, FCC ID: IHDT56XB5):

- GSM850/1900
- WCDMA Band V/II
- LTE Band 5/7
- WLAN/Bluetooth

LTE Band 26/38/41 full SAR test, spot check for WWAN (except for LTE Band 26/38/41) and BT/WLAN are performed to ensure that SAR measurement for both devices are the same. So, the original SAR value can represent this application.

5.3 Spot Check Verification Data Section

Band	BW (MHz)	Modulation	RB Size	RB offset	Mode	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Original model (FCC ID: IHDT56XB5)				Spot check model (FCC ID: IHDT56XB6)				Deviation
											Average Power (dBm)	Tune-Up Limit (dBm)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	Average Power (dBm)	Tune-Up Limit (dBm)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)	
WLAN2.4GHz	-	-	-	-	802.11b 1Mbps	Left Cheek	-	Reduced	11	2462	17.13	17.50	0.998	1.114	17.13	17.50	1.040	1.161	4.22%
GSM850	-	-	-	-	GPRS 1 Tx slot	Back	5	Full	128	824.2	32.78	33.50	0.626	0.739	32.78	33.50	0.540	0.637	-13.80%
GSM1900	-	-	-	-	GPRS 2 Tx slots	Back	5	Reduced	661	1880	21.67	22.50	0.972	1.177	21.67	22.50	0.839	1.016	-13.68%
WCDMA Band V	-	-	-	-	RMC12.2Kbps	Back	5	Full	4182	836.4	23.22	24.00	0.699	0.837	23.22	24.00	0.679	0.813	-2.87%
WCDMA Band II	-	-	-	-	RMC12.2Kbps	Back	5	Reduced	9400	1880	16.82	17.50	0.941	1.100	16.82	17.50	0.961	1.124	2.18%
LTE Band 5	10M	QPSK	1	25	-	Back	5	Full	20525	836.5	23.45	24.00	0.777	0.882	23.45	24.00	0.803	0.911	3.29%
LTE Band 7	20M	QPSK	50	50	-	Front	5	Reduced	21100	2535	19.89	20.50	0.620	0.713	19.89	20.50	0.700	0.806	13.04%
Bluetooth	-	-	-	-	1Mbps	Top Side	5	Full	39	2441	11.34	11.50	0.081	0.091	11.34	11.50	0.075	0.085	-17.58%

Note: In the table above, all the deviation of SAR test results are compliant with uncertainty budget.

5.4 Reference detail Section

Reference FCC ID	Folder Test/RF Exposure	Report Title/Section
IHDT56XB5	RF Exposure(FA7D0507)	All sections applicable

6. RF Exposure Limits

6.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

6.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

7. Specific Absorption Rate (SAR)

7.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

7.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

8. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

8.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

8.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

8.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

8.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

9. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

9.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

9.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

9.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

9.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm $2 - 3$ GHz: ≤ 5 mm*	$3 - 4$ GHz: ≤ 5 mm* $4 - 6$ GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	$3 - 4$ GHz: ≤ 4 mm $4 - 5$ GHz: ≤ 3 mm $5 - 6$ GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	$3 - 4$ GHz: ≤ 3 mm $4 - 5$ GHz: ≤ 2.5 mm $5 - 6$ GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	$3 - 4$ GHz: ≥ 28 mm $4 - 5$ GHz: ≥ 25 mm $5 - 6$ GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

9.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

9.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.



10. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d151	2017/3/20	2018/3/19
SPEAG	2600MHz System Validation Kit	D2600V2	1112	2017/9/18	2018/9/17
SPEAG	Data Acquisition Electronics	DAE4	1210	2017/5/25	2018/5/24
SPEAG	Dosimetric E-Field Probe	EX3DV4	3857	2017/5/26	2018/5/25
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1542	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1644	NCR	NCR
SPEAG	SAM Twin Phantom	QD 000 P40 CB	TP-1164	NCR	NCR
SPEAG	Phone Positioner	N/A	N/A	NCR	NCR
Anritsu	Radio communication analyzer	MT8820C	6201563814	2017/1/19	2018/1/18
Agilent	ENA Series Network Analyzer	E5071C	MY46111157	2017/4/18	2018/4/17
SPEAG	DAK Kit	DAK3.5	1146	2017/7/18	2018/7/17
R&S	Signal Generator	SMR40	100455	2017/1/19	2018/1/18
Anritsu	Power Meter	ML2495A	1419002	2017/5/15	2018/5/14
Anritsu	Power Sensor	MA2411B	1339124	2017/5/15	2018/5/14
Anritsu	Power Meter	ML2495A	1218006	2017/10/6	2018/10/5
Anritsu	Power Sensor	MA2411B	1207363	2017/10/6	2018/10/5
WISEWIND	Hygrometer	WISEWIND 0905	0905	2017/4/20	2018/4/19
JM	DIGITAC THERMOMETER	JM222	AA1207166	2017/4/19	2018/4/18
R&S	CBT BLUETOOTH TESTER	CBT	100783	2017/8/8	2018/8/7
EXA	Spectrum Analyzer	N9010A	MY55150244	2017/4/18	2018/4/17
ARRA	Power Divider	A3200-2	N/A	Note	
MCL	Attenuation1	BW-S10W5+	N/A	Note	
MCL	Attenuation2	BW-S10W5+	N/A	Note	
MCL	Attenuation3	BW-S10W5+	N/A	Note	
AR	Amplifier	5S1G4	333096	Note	
mini-circuits	Amplifier	ZVE-3W-83+	162601250	Note	
Agilent	Dual Directional Coupler	778D	50422	Note	
PASTERNAK	Dual Directional Coupler	PE2214-10	N/A	Note	

Note:

Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

11. System Verification

11.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1Photo of Liquid Height for Head SAR




Fig 10.2 Photo of Liquid Height for Body SAR

11.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. ($^{\circ}\text{C}$)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	Head	22.6	0.908	41.897	0.90	41.50	0.89	0.96	± 5	2017/12/26
2600	Head	22.6	2.052	38.095	1.96	39.00	4.69	-2.32	± 5	2017/12/20
835	Body	22.8	0.978	54.809	0.97	55.20	0.82	-0.71	± 5	2017/12/24
2600	Body	22.7	2.198	52.262	2.16	52.50	1.76	-0.45	± 5	2017/12/23

11.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

<1g SAR>:

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2017/12/26	835	Head	250	4d151	3857	1210	2.40	9.73	9.60	-1.34
2017/12/20	2600	Head	250	1112	3857	1210	14.30	56.40	57.20	1.42
2017/12/24	835	Body	250	4d151	3857	1210	2.49	9.72	9.96	2.47
2017/12/23	2600	Body	250	1112	3857	1210	14.40	55.00	57.60	4.73

<10g SAR>:

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2017/12/23	2600	Body	250	1112	3857	1210	6.46	24.40	25.84	5.90




Fig 8.3.1 System Performance Check Setup

Fig 8.3.2 Setup Photo

12. RF Exposure Positions

12.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2. The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

12.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

12.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15° .
3. Rotate the handset around the horizontal line by 15° .
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

12.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

12.5 Product Specific 10g SAR Exposure

For smart phones with a display diagonal dimension $> 15.0 \text{ cm}$ or an overall diagonal dimension $> 16.0 \text{ cm}$ that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at $\leq 25 \text{ mm}$ from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR $> 1.2 \text{ W/kg}$.



12.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets (L x W $\geq$ 9 cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

13. Conducted RF Output Power (Unit: dBm)

<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B26 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

<Full Power Mode>
<LTE Band 26>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26765	26865	26965	24	0
Frequency (MHz)				821.5	831.5	841.5		
15	QPSK	1	0	23.10	23.11	23.16		
15	QPSK	1	37	23.28	23.04	23.44	23	1
15	QPSK	1	74	23.22	23.20	23.21		
15	QPSK	36	0	22.40	22.32	22.41		
15	QPSK	36	20	22.31	22.31	22.22	23	1
15	QPSK	36	39	22.36	22.37	22.26		
15	QPSK	75	0	22.36	22.24	22.37		
15	16QAM	1	0	21.74	21.81	21.86	23	1
15	16QAM	1	37	22.02	21.89	22.07		
15	16QAM	1	74	21.91	21.81	21.88		
15	16QAM	36	0	21.26	21.24	21.29	22	2
15	16QAM	36	20	21.33	21.21	21.23		
15	16QAM	36	39	21.28	21.20	21.16		
15	16QAM	75	0	21.38	21.25	21.31	24	0
Channel				26740	26865	26990		
Frequency (MHz)				819	831.5	844		
10	QPSK	1	0	23.02	23.14	23.24	24	0
10	QPSK	1	25	23.40	23.06	23.35		
10	QPSK	1	49	23.16	23.26	23.16		
10	QPSK	25	0	22.39	22.24	22.35	23	1
10	QPSK	25	12	22.47	22.35	22.34		
10	QPSK	25	25	22.41	22.34	22.24		
10	QPSK	50	0	22.37	22.27	22.25	23	1
10	16QAM	1	0	21.74	21.85	21.60		
10	16QAM	1	25	22.05	21.77	22.09		
10	16QAM	1	49	22.02	21.76	21.76	22	2
10	16QAM	25	0	21.20	21.13	21.48		
10	16QAM	25	12	21.39	21.15	21.36		
10	16QAM	25	25	21.29	21.13	21.15	22	2
10	16QAM	50	0	21.29	21.26	21.28		



Channel				26715	26865	27015	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				816.5	831.5	846.5		
5	QPSK	1	0	23.01	23.12	23.13	24	0
5	QPSK	1	12	23.00	23.21	23.05		
5	QPSK	1	24	23.21	23.06	22.79		
5	QPSK	12	0	22.27	22.17	22.32	23	1
5	QPSK	12	7	22.32	22.30	22.25		
5	QPSK	12	13	22.35	22.30	22.30		
5	QPSK	25	0	22.34	22.30	22.22		
5	16QAM	1	0	22.26	21.59	22.44	23	1
5	16QAM	1	12	21.94	21.85	22.39		
5	16QAM	1	24	21.74	21.52	21.71		
5	16QAM	12	0	21.09	21.09	21.36	22	2
5	16QAM	12	7	21.14	21.13	21.39		
5	16QAM	12	13	21.38	21.01	21.22		
5	16QAM	25	0	21.26	21.24	21.16		
Channel				26705	26865	27025	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				815.5	831.5	847.5		
3	QPSK	1	0	23.01	23.27	23.40	24	0
3	QPSK	1	8	23.14	23.43	23.39		
3	QPSK	1	14	23.28	23.18	22.96		
3	QPSK	8	0	22.29	22.22	22.51	23	1
3	QPSK	8	4	22.29	22.32	22.25		
3	QPSK	8	7	22.36	22.29	22.24		
3	QPSK	15	0	22.32	22.24	22.28		
3	16QAM	1	0	22.55	21.72	22.35	23	1
3	16QAM	1	8	22.62	22.25	22.05		
3	16QAM	1	14	22.67	22.36	21.71		
3	16QAM	8	0	21.26	21.29	21.38	22	2
3	16QAM	8	4	21.36	21.34	21.35		
3	16QAM	8	7	21.44	21.39	21.25		
3	16QAM	15	0	21.26	21.39	21.24		
Channel				26697	26865	27033	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				814.7	831.5	848.3		
1.4	QPSK	1	0	22.81	22.98	23.35	24	0
1.4	QPSK	1	3	22.92	23.17	23.29		
1.4	QPSK	1	5	22.87	23.12	22.95		
1.4	QPSK	3	0	23.10	23.19	23.40		
1.4	QPSK	3	1	23.33	23.25	23.35		
1.4	QPSK	3	3	23.21	23.26	23.29		
1.4	QPSK	6	0	22.15	22.16	22.24	23	1
1.4	16QAM	1	0	21.67	22.04	21.75	23	1
1.4	16QAM	1	3	21.78	22.29	21.85		
1.4	16QAM	1	5	21.79	21.70	21.93		
1.4	16QAM	3	0	21.86	22.17	22.27		
1.4	16QAM	3	1	22.15	22.23	22.54		
1.4	16QAM	3	3	22.15	22.23	22.36		
1.4	16QAM	6	0	21.23	21.08	21.26	22	2

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- “special subframe S” contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$		
8	$24144 \cdot T_s$			-	-	-
9	$13168 \cdot T_s$			-	-	-

Special subframe (30720·T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.167)/5 = 63.3\%$
- for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.143)/5 = 62.9\%$
- For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

<Full Power Mode>
<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150	24	0
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	22.81	22.91	22.86		
20	QPSK	1	49	23.21	22.99	22.87	23	1
20	QPSK	1	99	22.85	22.77	22.83		
20	QPSK	50	0	22.20	22.09	21.90		
20	QPSK	50	24	22.09	22.02	21.88	23	1
20	QPSK	50	50	21.99	21.85	21.81		
20	QPSK	100	0	22.01	21.92	21.84		
20	16QAM	1	0	21.64	21.50	21.60	23	1
20	16QAM	1	49	21.91	21.59	21.67		
20	16QAM	1	99	21.66	21.35	21.56		
20	16QAM	50	0	21.02	20.75	20.65	22	2
20	16QAM	50	24	21.09	20.72	20.66		
20	16QAM	50	50	21.06	20.83	20.57		
20	16QAM	100	0	20.99	20.79	20.70	22	2
Channel				37825	38000	38175		
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	22.87	22.77	22.86	24	0
15	QPSK	1	37	23.18	22.78	22.88		
15	QPSK	1	74	22.87	22.67	23.03		
15	QPSK	36	0	22.06	21.95	21.95	23	1
15	QPSK	36	20	22.16	22.08	21.91		
15	QPSK	36	39	22.08	21.98	21.98		
15	QPSK	75	0	22.01	21.91	22.01	23	1
15	16QAM	1	0	21.62	21.77	21.87		
15	16QAM	1	37	22.01	21.78	21.68		
15	16QAM	1	74	21.70	21.70	21.87	22	2
15	16QAM	36	0	20.96	20.73	20.65		
15	16QAM	36	20	21.06	20.81	20.71		
15	16QAM	36	39	21.01	20.73	20.81	22	2
15	16QAM	75	0	20.97	20.88	20.97		

Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	22.88	22.78	22.72	24	0
10	QPSK	1	25	22.85	22.83	22.87		
10	QPSK	1	49	22.99	22.77	23.01		
10	QPSK	25	0	21.99	21.94	21.86	23	1
10	QPSK	25	12	22.02	21.96	21.81		
10	QPSK	25	25	22.04	21.97	21.93		
10	QPSK	50	0	22.11	22.04	21.93		
10	16QAM	1	0	21.71	21.38	21.73	23	1
10	16QAM	1	25	21.79	21.64	21.77		
10	16QAM	1	49	21.88	21.57	21.78		
10	16QAM	25	0	21.16	21.10	20.72	22	2
10	16QAM	25	12	21.09	21.06	20.68		
10	16QAM	25	25	21.01	21.04	20.81		
10	16QAM	50	0	20.97	20.71	20.70		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	22.76	22.69	22.79	24	0
5	QPSK	1	12	23.05	22.79	22.72		
5	QPSK	1	24	22.89	22.50	22.86		
5	QPSK	12	0	21.89	21.85	21.83	23	1
5	QPSK	12	7	21.86	21.85	21.78		
5	QPSK	12	13	22.00	21.86	22.06		
5	QPSK	25	0	22.00	21.88	21.96		
5	16QAM	1	0	21.46	21.77	21.34	23	1
5	16QAM	1	12	21.87	21.69	21.42		
5	16QAM	1	24	21.87	21.66	21.72		
5	16QAM	12	0	20.80	20.76	20.74	22	2
5	16QAM	12	7	20.98	20.75	20.79		
5	16QAM	12	13	20.76	20.77	20.87		
5	16QAM	25	0	21.13	20.99	20.91		

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	23.16	23.05	22.99	22.91	24	0
20	QPSK	1	49	23.30	23.26	23.17	23.08		
20	QPSK	1	99	22.89	22.94	22.86	22.85		
20	QPSK	50	0	22.32	22.20	22.16	22.07	23	1
20	QPSK	50	24	22.18	22.15	22.09	21.95		
20	QPSK	50	50	22.03	22.09	22.15	21.92		
20	QPSK	100	0	22.18	22.09	22.18	22.03	23	1
20	16QAM	1	0	22.14	21.78	21.60	21.96		
20	16QAM	1	49	22.05	22.01	21.87	21.95		
20	16QAM	1	99	21.49	21.87	21.44	21.73	22	2
20	16QAM	50	0	21.37	20.83	21.06	21.10		
20	16QAM	50	24	21.22	21.16	21.14	20.84		
20	16QAM	50	50	21.09	21.05	21.09	20.90	22	2
20	16QAM	100	0	21.14	21.04	21.03	20.92		
Channel				40115	40395	40685	41165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5		
15	QPSK	1	0	23.27	23.18	22.85	23.04	24	0
15	QPSK	1	37	23.28	23.22	23.21	22.97		
15	QPSK	1	74	23.10	23.09	22.92	22.87		
15	QPSK	36	0	22.27	22.13	22.15	22.06	23	1
15	QPSK	36	20	22.05	22.21	22.12	21.91		
15	QPSK	36	39	22.13	22.15	22.10	21.96		
15	QPSK	75	0	22.29	22.05	22.07	22.06	23	1
15	16QAM	1	0	22.48	21.66	21.74	22.03		
15	16QAM	1	37	22.00	21.81	21.88	21.81		
15	16QAM	1	74	21.99	21.98	21.61	21.91	22	2
15	16QAM	36	0	21.14	21.13	21.04	20.99		
15	16QAM	36	20	21.04	21.10	21.02	20.99		
15	16QAM	36	39	21.12	21.08	21.01	21.09	22	2
15	16QAM	75	0	21.15	21.10	21.01	21.05		



Channel				40090	40390	40690	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2540	2570	2600	2650		
10	QPSK	1	0	23.19	23.12	22.87	22.93	24	0
10	QPSK	1	25	23.23	23.21	23.11	22.97		
10	QPSK	1	49	23.05	23.02	22.90	22.90		
10	QPSK	25	0	22.34	22.09	22.14	22.05	23	1
10	QPSK	25	12	22.13	22.15	22.13	21.91		
10	QPSK	25	25	22.22	22.23	22.18	21.95		
10	QPSK	50	0	22.29	22.11	22.20	22.05		
10	16QAM	1	0	21.85	22.02	21.86	21.80	23	1
10	16QAM	1	25	21.97	21.94	21.91	21.73		
10	16QAM	1	49	21.89	21.63	21.68	21.77		
10	16QAM	25	0	21.20	21.15	20.98	20.95	22	2
10	16QAM	25	12	21.08	21.10	21.00	20.81		
10	16QAM	25	25	21.08	21.28	20.92	20.95		
10	16QAM	50	0	21.23	20.95	21.06	20.90		
Channel				40065	40385	40705	41215	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5		
5	QPSK	1	0	23.06	23.12	22.91	22.84	24	0
5	QPSK	1	12	23.10	23.07	22.93	23.00		
5	QPSK	1	24	23.02	23.07	22.87	22.83		
5	QPSK	12	0	22.32	22.08	22.06	21.88	23	1
5	QPSK	12	7	22.20	22.14	21.97	21.93		
5	QPSK	12	13	22.12	22.06	22.06	21.89		
5	QPSK	25	0	22.28	22.19	22.04	21.94		
5	16QAM	1	0	21.88	21.59	21.97	21.75	23	1
5	16QAM	1	12	21.72	21.81	21.62	21.77		
5	16QAM	1	24	21.90	21.59	21.82	21.68		
5	16QAM	12	0	21.13	21.10	20.96	20.92	22	2
5	16QAM	12	7	21.02	21.10	20.98	20.92		
5	16QAM	12	13	21.02	21.04	20.91	20.79		
5	16QAM	25	0	21.15	21.13	20.85	21.14		

<Reduced Power Mode for Hotspot On/P-Sensor On>

<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150	22	0
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	21.73	21.68	21.67		
20	QPSK	1	49	21.82	21.80	21.68	22	0
20	QPSK	1	99	21.56	21.49	21.62		
20	QPSK	50	0	21.86	21.78	21.72		
20	QPSK	50	24	21.82	21.74	21.69	22	0
20	QPSK	50	50	21.65	21.56	21.62		
20	QPSK	100	0	21.76	21.75	21.66		
20	16QAM	1	0	21.61	21.45	21.59	22	0
20	16QAM	1	49	21.70	21.60	21.27		
20	16QAM	1	99	21.44	21.30	21.43		
20	16QAM	50	0	21.05	21.03	20.86	22	0
20	16QAM	50	24	21.11	20.80	20.85		
20	16QAM	50	50	21.02	21.03	20.86		
20	16QAM	100	0	20.93	20.86	20.81	22	0
Channel				37825	38000	38175		
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	21.64	21.74	21.85	22	0
15	QPSK	1	37	21.60	21.86	21.77		
15	QPSK	1	74	21.71	21.46	21.84		
15	QPSK	36	0	21.64	21.67	21.65	22	0
15	QPSK	36	20	21.85	21.75	21.60		
15	QPSK	36	39	21.86	21.65	21.66		
15	QPSK	75	0	21.81	21.66	21.70	22	0
15	16QAM	1	0	21.61	21.31	21.75		
15	16QAM	1	37	21.77	21.52	21.57		
15	16QAM	1	74	21.45	21.24	21.65	22	0
15	16QAM	36	0	20.96	20.86	20.92		
15	16QAM	36	20	21.15	20.87	20.88		
15	16QAM	36	39	21.09	20.88	20.97	22	0
15	16QAM	75	0	20.96	20.91	21.04		


Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	21.63	21.51	21.58	22	0
10	QPSK	1	25	21.63	21.69	21.74		
10	QPSK	1	49	21.92	21.53	21.79		
10	QPSK	25	0	21.87	21.86	21.73	22	0
10	QPSK	25	12	21.86	21.89	21.67		
10	QPSK	25	25	21.82	21.82	21.78		
10	QPSK	50	0	21.87	21.88	21.70		
10	16QAM	1	0	21.44	21.32	21.20	22	0
10	16QAM	1	25	21.57	21.57	21.43		
10	16QAM	1	49	21.58	21.32	21.25		
10	16QAM	25	0	21.18	21.20	20.78	22	0
10	16QAM	25	12	21.11	20.96	20.82		
10	16QAM	25	25	20.97	20.88	20.84		
10	16QAM	50	0	20.99	21.04	20.96		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	21.64	21.51	21.62	22	0
5	QPSK	1	12	21.69	21.72	21.67		
5	QPSK	1	24	21.57	21.54	21.60		
5	QPSK	12	0	21.64	21.78	21.66	22	0
5	QPSK	12	7	21.72	21.75	21.70		
5	QPSK	12	13	21.80	21.66	21.89		
5	QPSK	25	0	21.76	21.78	21.87		
5	16QAM	1	0	21.61	21.57	21.16	22	0
5	16QAM	1	12	21.73	21.58	21.34		
5	16QAM	1	24	21.62	21.46	21.31		
5	16QAM	12	0	20.96	20.85	20.77	22	0
5	16QAM	12	7	20.92	20.87	20.90		
5	16QAM	12	13	21.07	20.77	20.98		
5	16QAM	25	0	21.42	20.84	21.13		

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	20.17	20.00	20.04	19.99	21	0
20	QPSK	1	49	20.14	20.16	20.24	20.30		
20	QPSK	1	99	19.83	20.10	20.01	19.93		
20	QPSK	50	0	20.12	20.03	20.20	20.27	21	0
20	QPSK	50	24	20.18	20.23	20.12	19.98		
20	QPSK	50	50	20.03	20.08	20.20	20.01		
20	QPSK	100	0	20.12	20.09	20.09	20.13	21	0
20	16QAM	1	0	19.77	19.63	19.57	19.65		
20	16QAM	1	49	19.93	19.87	20.01	19.91		
20	16QAM	1	99	19.80	19.60	19.80	19.56	21	0
20	16QAM	50	0	20.13	19.97	20.09	19.88		
20	16QAM	50	24	20.05	20.14	20.19	19.84		
20	16QAM	50	50	20.06	20.03	20.17	19.90	21	0
20	16QAM	100	0	20.07	20.14	20.17	20.00		
Channel				40115	40395	40685	41165		
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5		
15	QPSK	1	0	20.16	20.02	19.95	20.07	21	0
15	QPSK	1	37	20.23	20.20	20.26	20.19		
15	QPSK	1	74	19.94	19.94	19.88	19.87		
15	QPSK	36	0	20.24	20.09	20.04	20.03	21	0
15	QPSK	36	20	20.04	20.16	20.19	20.06		
15	QPSK	36	39	19.96	20.17	20.23	20.09		
15	QPSK	75	0	20.18	20.08	20.13	19.98	21	0
15	16QAM	1	0	20.38	20.03	19.87	19.93		
15	16QAM	1	37	19.78	20.14	20.05	19.84		
15	16QAM	1	74	19.64	19.97	19.79	19.88	21	0
15	16QAM	36	0	20.29	19.89	19.88	20.00		
15	16QAM	36	20	19.99	20.10	19.97	19.89		
15	16QAM	36	39	19.95	20.07	19.98	19.92	21	0
15	16QAM	75	0	20.06	20.11	20.07	19.95		

Channel				40090	40390	40690	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2540	2570	2600	2650		
10	QPSK	1	0	20.07	19.95	19.97	19.90	21	0
10	QPSK	1	25	20.14	20.26	19.99	19.96		
10	QPSK	1	49	19.94	20.00	19.75	19.82		
10	QPSK	25	0	20.23	20.06	20.15	20.01	21	0
10	QPSK	25	12	20.18	20.11	20.23	19.91		
10	QPSK	25	25	19.95	20.15	20.10	19.91		
10	QPSK	50	0	20.08	20.04	20.10	19.83		
10	16QAM	1	0	20.01	19.88	19.83	19.93	21	0
10	16QAM	1	25	19.92	19.98	19.89	19.84		
10	16QAM	1	49	19.58	19.87	19.43	19.71		
10	16QAM	25	0	20.07	20.19	20.06	19.98	21	0
10	16QAM	25	12	20.13	20.43	20.28	20.01		
10	16QAM	25	25	20.00	20.30	20.20	20.29		
10	16QAM	50	0	20.04	19.99	19.90	20.02		
Channel				40065	40385	40705	41215	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5		
5	QPSK	1	0	19.96	19.98	19.94	19.89	21	0
5	QPSK	1	12	20.03	20.05	20.04	19.92		
5	QPSK	1	24	19.81	20.05	19.74	19.76		
5	QPSK	12	0	20.20	19.96	19.91	19.95	21	0
5	QPSK	12	7	20.06	20.09	20.08	19.75		
5	QPSK	12	13	19.98	20.04	20.06	19.81		
5	QPSK	25	0	20.09	20.06	19.99	19.93		
5	16QAM	1	0	19.94	19.89	19.84	19.78	21	0
5	16QAM	1	12	20.00	20.03	19.90	19.69		
5	16QAM	1	24	19.83	19.88	19.59	19.61		
5	16QAM	12	0	20.02	19.99	19.96	19.98	21	0
5	16QAM	12	7	19.97	20.03	19.98	19.80		
5	16QAM	12	13	19.96	20.08	19.93	19.83		
5	16QAM	25	0	19.99	20.10	19.87	20.10		

14. Antenna Location



Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	>25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN Main	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	Yes	No

General Note:

Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge.



15. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - c. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix 63.3%/62.9% = 1.006 is applied to scale-up the measured SAR result.
The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required when the measured SAR is ≥ 0.8 W/kg. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. Per KDB 648474 D04v01r03, when the reported SAR for a body-worn accessory measured without a headset connected to the handset is ≤ 1.2 W/kg, SAR testing with a headset connected to the handset is not required.
5. When the phone is in talking mode and receiver worked, all WWAN powers are full power.
6. When the phone is in talking mode and receiver worked, then power reduction will be implemented immediately in WLAN 2.4GHz.
7. When hotspot mode is enabled, power reduction will be activated to limit the maximum power of GSM1900, WCDMA band II and LTE band 7/38/41.
8. The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device. When front or back body worn condition is detected, GSM1900, WCDMA band II, and LTE band 7/38/41 reduced power will be active. (P-sensor can't work at detecting presence of the user's body at the four edges of the device.)
9. This device hotspot reduced power and P-sensor reduced power level are the same. So only show one reduced power level for hotspot reduced power and P-sensor reduced power for this application.
10. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold
 - a. When hotspot is not worked, GSM1900, WCDMA Band II/IV, LTE Band 4/2/7 product specific 10g SAR is required.
 - b. When 10-g product specific 10g SAR is considered, SAR thresholds is specified in the procedures for SAR test reduction and exclusion should be multiplied by 2.5.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B26 / B38 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.

**15.1 Head SAR****<FDD LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
01	LTE Band 26	15M	QPSK	1	37	Right Cheek	Full	26865	831.5	23.04	24.00	1.247	0.03	0.205	0.256
	LTE Band 26	15M	QPSK	36	0	Right Cheek	Full	26865	831.5	22.32	23.00	1.169	0.01	0.156	0.182
	LTE Band 26	15M	QPSK	1	37	Right Tilted	Full	26865	831.5	23.04	24.00	1.247	0.11	0.114	0.142
	LTE Band 26	15M	QPSK	36	0	Right Tilted	Full	26865	831.5	22.32	23.00	1.169	0.14	0.083	0.097
	LTE Band 26	15M	QPSK	1	37	Left Cheek	Full	26865	831.5	23.04	24.00	1.247	0.08	0.199	0.248
	LTE Band 26	15M	QPSK	36	0	Left Cheek	Full	26865	831.5	22.32	23.00	1.169	0.1	0.149	0.174
	LTE Band 26	15M	QPSK	1	37	Left Tilted	Full	26865	831.5	23.04	24.00	1.247	0.03	0.108	0.135
	LTE Band 26	15M	QPSK	36	0	Left Tilted	Full	26865	831.5	22.32	23.00	1.169	0.04	0.075	0.088

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Right Cheek	Full	38000	2595	22.99	24.00	1.262	62.9	1.006	0.05	0.143	0.182
	LTE Band 38	20M	QPSK	50	0	Right Cheek	Full	38000	2595	22.09	23.00	1.233	62.9	1.006	0.13	0.094	0.117
	LTE Band 38	20M	QPSK	1	49	Right Tilted	Full	38000	2595	22.99	24.00	1.262	62.9	1.006	-0.13	0.111	0.141
	LTE Band 38	20M	QPSK	50	0	Right Tilted	Full	38000	2595	22.09	23.00	1.233	62.9	1.006	0.12	0.071	0.088
02	LTE Band 38	20M	QPSK	1	49	Left Cheek	Full	38000	2595	22.99	24.00	1.262	62.9	1.006	0.17	0.240	0.305
	LTE Band 38	20M	QPSK	50	0	Left Cheek	Full	38000	2595	22.09	23.00	1.233	62.9	1.006	0.04	0.152	0.189
	LTE Band 38	20M	QPSK	1	49	Left Tilted	Full	38000	2595	22.99	24.00	1.262	62.9	1.006	-0.08	0.111	0.141
	LTE Band 38	20M	QPSK	50	0	Left Tilted	Full	38000	2595	22.09	23.00	1.233	62.9	1.006	0.14	0.075	0.093
	LTE Band 41	20M	QPSK	1	49	Right Cheek	Full	40140	2545	23.30	24.00	1.175	62.9	1.006	0.05	0.102	0.121
	LTE Band 41	20M	QPSK	50	0	Right Cheek	Full	40140	2545	22.32	23.00	1.169	62.9	1.006	0.1	0.066	0.078
	LTE Band 41	20M	QPSK	1	49	Right Tilted	Full	40140	2545	23.30	24.00	1.175	62.9	1.006	0.11	0.067	0.079
	LTE Band 41	20M	QPSK	50	0	Right Tilted	Full	40140	2545	22.32	23.00	1.169	62.9	1.006	0.14	0.046	0.054
03	LTE Band 41	20M	QPSK	1	49	Left Cheek	Full	40140	2545	23.30	24.00	1.175	62.9	1.006	0.01	0.149	0.176
	LTE Band 41	20M	QPSK	50	0	Left Cheek	Full	40140	2545	22.32	23.00	1.169	62.9	1.006	0.08	0.099	0.116
	LTE Band 41	20M	QPSK	1	49	Left Tilted	Full	40140	2545	23.30	24.00	1.175	62.9	1.006	0.03	0.082	0.097
	LTE Band 41	20M	QPSK	50	0	Left Tilted	Full	40140	2545	22.32	23.00	1.169	62.9	1.006	0.03	0.046	0.054

15.2 Hotspot SAR

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 26	15M	QPSK	1	37	Front	5	Full	26865	831.5	23.04	24.00	1.247	0.12	0.373	0.465
	LTE Band 26	15M	QPSK	36	0	Front	5	Full	26865	831.5	22.32	23.00	1.169	0.08	0.274	0.320
04	LTE Band 26	15M	QPSK	1	37	Back	5	Full	26865	831.5	23.04	24.00	1.247	0.11	0.547	0.682
	LTE Band 26	15M	QPSK	36	0	Back	5	Full	26865	831.5	22.32	23.00	1.169	0.01	0.425	0.497
	LTE Band 26	15M	QPSK	1	37	Left Side	5	Full	26865	831.5	23.04	24.00	1.247	0.01	0.323	0.403
	LTE Band 26	15M	QPSK	36	0	Left Side	5	Full	26865	831.5	22.32	23.00	1.169	0.08	0.241	0.282
	LTE Band 26	15M	QPSK	1	37	Right Side	5	Full	26865	831.5	23.04	24.00	1.247	0.17	0.313	0.390
	LTE Band 26	15M	QPSK	36	0	Right Side	5	Full	26865	831.5	22.32	23.00	1.169	0.04	0.227	0.265
	LTE Band 26	15M	QPSK	1	37	Bottom Side	5	Full	26865	831.5	23.04	24.00	1.247	0.01	0.121	0.151
	LTE Band 26	15M	QPSK	36	0	Bottom Side	5	Full	26865	831.5	22.32	23.00	1.169	0.17	0.092	0.108



<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
05	LTE Band 38	20M	QPSK	1	49	Front	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.04	1.110	1.169
	LTE Band 38	20M	QPSK	50	0	Front	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.11	1.070	1.132
	LTE Band 38	20M	QPSK	100	0	Front	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	0.05	1.120	1.193
	LTE Band 38	20M	QPSK	1	49	Back	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.06	1.010	1.064
	LTE Band 38	20M	QPSK	50	0	Back	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.19	1.080	1.143
	LTE Band 38	20M	QPSK	100	0	Back	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	0.15	1.090	1.162
	LTE Band 38	20M	QPSK	1	49	Left Side	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	-0.16	0.367	0.387
	LTE Band 38	20M	QPSK	50	0	Left Side	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.05	0.371	0.393
	LTE Band 38	20M	QPSK	1	49	Right Side	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.03	0.361	0.380
	LTE Band 38	20M	QPSK	50	0	Right Side	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	0.05	0.347	0.367
06	LTE Band 38	20M	QPSK	1	49	Bottom Side	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	-0.09	0.663	0.698
	LTE Band 38	20M	QPSK	50	0	Bottom Side	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.14	0.633	0.670
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.08	0.906	1.071
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40140	2545	20.14	21.00	1.219	62.9	1.006	0.07	0.467	0.573
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40400	2571	20.16	21.00	1.213	62.9	1.006	0.02	0.585	0.714
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40670	2598	20.24	21.00	1.191	62.9	1.006	0.08	0.737	0.883
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.07	0.871	1.037
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40140	2545	20.12	21.00	1.225	62.9	1.006	0.03	0.446	0.549
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40400	2571	20.03	21.00	1.250	62.9	1.006	0.07	0.569	0.716
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40670	2598	20.20	21.00	1.202	62.9	1.006	0.12	0.683	0.826
	LTE Band 41	20M	QPSK	100	0	Front	5	Reduced	41140	2645	20.13	21.00	1.222	62.9	1.006	0.07	0.870	1.069
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.09	0.855	1.011
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40140	2545	20.14	21.00	1.219	62.9	1.006	0.02	0.382	0.468
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40400	2571	20.16	21.00	1.213	62.9	1.006	0.09	0.504	0.615
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40670	2598	20.24	21.00	1.191	62.9	1.006	0.18	0.652	0.781
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.15	0.809	0.963
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40140	2545	20.12	21.00	1.225	62.9	1.006	0.11	0.366	0.451
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40400	2571	20.03	21.00	1.250	62.9	1.006	0.06	0.466	0.586
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40670	2598	20.20	21.00	1.202	62.9	1.006	0.16	0.649	0.785
	LTE Band 41	20M	QPSK	100	0	Back	5	Reduced	41140	2645	20.13	21.00	1.222	62.9	1.006	0.04	0.822	1.010
	LTE Band 41	20M	QPSK	1	49	Left Side	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	-0.07	0.273	0.323
	LTE Band 41	20M	QPSK	50	0	Left Side	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	-0.01	0.269	0.320
	LTE Band 41	20M	QPSK	1	49	Right Side	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	-0.12	0.278	0.329
	LTE Band 41	20M	QPSK	50	0	Right Side	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	-0.1	0.266	0.317
	LTE Band 41	20M	QPSK	1	49	Bottom Side	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.05	0.504	0.596
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.13	0.489	0.582

**15.3 Body Worn Accessory SAR****<FDD LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 26	15M	QPSK	1	37	Front	5	Full	26865	831.5	23.04	24.00	1.247	0.12	0.373	0.465
	LTE Band 26	15M	QPSK	36	0	Front	5	Full	26865	831.5	22.32	23.00	1.169	0.08	0.274	0.320
07	LTE Band 26	15M	QPSK	1	37	Back	5	Full	26865	831.5	23.04	24.00	1.247	0.11	0.547	0.682
	LTE Band 26	15M	QPSK	36	0	Back	5	Full	26865	831.5	22.32	23.00	1.169	0.01	0.425	0.497

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Front	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.04	1.110	1.169
	LTE Band 38	20M	QPSK	50	0	Front	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.11	1.070	1.132
08	LTE Band 38	20M	QPSK	100	0	Front	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	0.05	1.120	1.193
	LTE Band 38	20M	QPSK	1	49	Back	5	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.06	1.010	1.064
	LTE Band 38	20M	QPSK	50	0	Back	5	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	-0.19	1.080	1.143
	LTE Band 38	20M	QPSK	100	0	Back	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	0.15	1.090	1.162
09	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.08	0.906	1.071
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40140	2545	20.14	21.00	1.219	62.9	1.006	0.07	0.467	0.573
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40400	2571	20.16	21.00	1.213	62.9	1.006	0.02	0.585	0.714
	LTE Band 41	20M	QPSK	1	49	Front	5	Reduced	40670	2598	20.24	21.00	1.191	62.9	1.006	0.08	0.737	0.883
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.07	0.871	1.037
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40140	2545	20.12	21.00	1.225	62.9	1.006	0.03	0.446	0.549
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40400	2571	20.03	21.00	1.250	62.9	1.006	0.07	0.569	0.716
	LTE Band 41	20M	QPSK	50	0	Front	5	Reduced	40670	2598	20.20	21.00	1.202	62.9	1.006	0.12	0.683	0.826
	LTE Band 41	20M	QPSK	100	0	Front	5	Reduced	41140	2645	20.13	21.00	1.222	62.9	1.006	0.07	0.870	1.069
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.09	0.855	1.011
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40140	2545	20.14	21.00	1.219	62.9	1.006	0.02	0.382	0.468
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40400	2571	20.16	21.00	1.213	62.9	1.006	0.09	0.504	0.615
	LTE Band 41	20M	QPSK	1	49	Back	5	Reduced	40670	2598	20.24	21.00	1.191	62.9	1.006	0.18	0.652	0.781
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.15	0.809	0.963
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40140	2545	20.12	21.00	1.225	62.9	1.006	0.11	0.366	0.451
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40400	2571	20.03	21.00	1.250	62.9	1.006	0.06	0.466	0.586
	LTE Band 41	20M	QPSK	50	0	Back	5	Reduced	40670	2598	20.20	21.00	1.202	62.9	1.006	0.16	0.649	0.785
	LTE Band 41	20M	QPSK	100	0	Back	5	Reduced	41140	2645	20.13	21.00	1.222	62.9	1.006	0.04	0.822	1.010

**15.4 Product specific 10g SAR****<TDD LTE SAR>**

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 38	20M	QPSK	1	49	Front	0	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.14	1.060	1.117
	LTE Band 38	20M	QPSK	50	0	Front	0	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	0.01	1.050	1.111
	LTE Band 38	20M	QPSK	1	49	Back	0	Reduced	38000	2595	21.80	22.00	1.047	62.9	1.006	0.09	1.820	1.917
10	LTE Band 38	20M	QPSK	50	0	Back	0	Reduced	38000	2595	21.78	22.00	1.052	62.9	1.006	0.07	1.850	1.958
	LTE Band 41	20M	QPSK	1	49	Front	0	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.03	0.814	0.962
	LTE Band 41	20M	QPSK	50	0	Front	0	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.12	0.768	0.914
11	LTE Band 41	20M	QPSK	1	49	Back	0	Reduced	41140	2645	20.30	21.00	1.175	62.9	1.006	0.13	1.300	1.537
	LTE Band 41	20M	QPSK	50	0	Back	0	Reduced	41140	2645	20.27	21.00	1.183	62.9	1.006	0.14	1.210	1.440

15.5 Repeated SAR Measurement

No.	Band	BW (MHz)	Modulation	RB Size	RB Offset	Test Position	Gap (mm)	Power Mode	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	LTE Band 38	20M	QPSK	100	0	Front	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	0.05	1.120	1	1.193
2nd	LTE Band 38	20M	QPSK	100	0	Front	5	Reduced	38000	2595	21.75	22.00	1.059	62.9	1.006	-0.01	1.100	1.018	1.172

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. The ratio is the difference in percentage between original and repeated *measured SAR*.
4. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

16. Simultaneous Transmission Analysis

No.	Simultaneous Transmission Configurations	Mobile Cellular Phone		
		Head	Body-worn	Hotspot
1.	GSM Voice + WLAN2.4GHz	Yes	Yes	
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes
5.	GSM Voice + Bluetooth		Yes	
6.	GPRS/EDGE + Bluetooth		Yes	Yes
7.	WCDMA+ Bluetooth		Yes	Yes
8.	LTE + Bluetooth		Yes	Yes

General Note:

1. This device supports VoIP in GPRS, EGPRS, WCDMA and LTE (e.g. for 3rd-party VoIP), LTE supports VoLTE operation.
2. EUT will choose each GSM, WCDMA, and LTE according to the network signal condition; therefore, they will not operate simultaneously at any moment.
3. This device WLAN 2.4GHz supports hotspot operation and Bluetooth support tethering applications.
4. WLAN 2.4GHz and Bluetooth share the same antenna so can't transmit simultaneously.
5. All licensed modes share the same antenna part and cannot transmit simultaneously.
6. Chose the worst zoom scan SAR of WLAN correspondingly for co-located with WWAN analysis.
7. The reported SAR summation is calculated based on the same configuration and test position.
8. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\min. \text{ separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.

16.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	1+2 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	
			1g SAR (W/kg)	1g SAR (W/kg)	
GSM	GSM850	Right Cheek	0.233	0.519	0.75
		Right Tilted	0.138	1.114	1.25
		Left Cheek	0.280	1.114	1.39
		Left Tilted	0.163	0.777	0.94
	GSM1900	Right Cheek	0.116	0.519	0.64
		Right Tilted	0.038	1.114	1.15
		Left Cheek	0.059	1.114	1.17
		Left Tilted	0.031	0.777	0.81
WCDMA	Band V	Right Cheek	0.388	0.519	0.91
		Right Tilted	0.237	1.114	1.35
		Left Cheek	0.397	1.114	1.51
		Left Tilted	0.231	0.777	1.01
	Band II	Right Cheek	0.208	0.519	0.73
		Right Tilted	0.063	1.114	1.18
		Left Cheek	0.117	1.114	1.23
		Left Tilted	0.064	0.777	0.84
LTE	Band 5	Right Cheek	0.387	0.519	0.91
		Right Tilted	0.212	1.114	1.33
		Left Cheek	0.409	1.114	1.52
		Left Tilted	0.229	0.777	1.01
	Band 7	Right Cheek	0.205	0.519	0.72
		Right Tilted	0.169	1.114	1.28
		Left Cheek	0.385	1.114	1.50
		Left Tilted	0.194	0.777	0.97
	Band 26	Right Cheek	0.256	0.519	0.78
		Right Tilted	0.142	1.114	1.26
		Left Cheek	0.248	1.114	1.36
		Left Tilted	0.135	0.777	0.91
	Band 38	Right Cheek	0.182	0.519	0.70
		Right Tilted	0.141	1.114	1.26
		Left Cheek	0.305	1.114	1.42
		Left Tilted	0.141	0.777	0.92
	Band 41	Right Cheek	0.121	0.519	0.64
		Right Tilted	0.079	1.114	1.19
		Left Cheek	0.176	1.114	1.29
		Left Tilted	0.097	0.777	0.87

16.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)				
GSM	GSM850	Front	0.493	0.490	0.087	0.98	0.58		
		Back	0.739	0.359	0.076	1.10	0.82		
		Left Side	0.492			0.49	0.49		
		Right Side	0.459	0.490	0.062	0.95	0.52		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.156			0.16	0.16		
	GSM1900	Front	0.527	0.490	0.087	1.02	0.61		
		Back	1.177	0.359	0.076	1.54	1.25		
		Left Side	0.033			0.03	0.03		
		Right Side	0.043	0.490	0.062	0.53	0.11		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	1.069			1.07	1.07		
WCDMA	Band V	Front	0.689	0.490	0.087	1.18	0.78		
		Back	0.837	0.359	0.076	1.20	0.91		
		Left Side	0.712			0.71	0.71		
		Right Side	0.665	0.490	0.062	1.16	0.73		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.190			0.19	0.19		
	Band II	Front	0.496	0.490	0.087	0.99	0.58		
		Back	1.100	0.359	0.076	1.46	1.18		
		Left Side	0.033			0.03	0.03		
		Right Side	0.050	0.490	0.062	0.54	0.11		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	1.058			1.06	1.06		

WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	Bluetooth				
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)				
LTE	Band 5	Front	0.701	0.490	0.087	1.19	0.79		
		Back	0.882	0.359	0.076	1.24	0.96		
		Left Side	0.684			0.68	0.68		
		Right Side	0.637	0.490	0.062	1.13	0.70		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.207			0.21	0.21		
	Band 7	Front	0.713	0.490	0.087	1.20	0.80		
		Back	0.604	0.359	0.076	0.96	0.68		
		Left Side	0.287			0.29	0.29		
		Right Side	0.238	0.490	0.062	0.73	0.30		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.555			0.56	0.56		
	Band 26	Front	0.465	0.490	0.087	0.96	0.55		
		Back	0.682	0.359	0.076	1.04	0.76		
		Left Side	0.403			0.40	0.40		
		Right Side	0.390	0.490	0.062	0.88	0.45		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.151			0.15	0.15		
	Band 38	Front	1.193	0.490	0.087	1.68	1.28	0.02	#01
		Back	1.162	0.359	0.076	1.52	1.24		
		Left Side	0.393			0.39	0.39		
		Right Side	0.380	0.490	0.062	0.87	0.44		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.698			0.70	0.70		
	Band 41	Front	1.071	0.490	0.087	1.56	1.16		
		Back	1.011	0.359	0.076	1.37	1.09		
		Left Side	0.323			0.32	0.32		
		Right Side	0.329	0.490	0.062	0.82	0.39		
		Top Side		0.405	0.091	0.41	0.09		
		Bottom Side	0.596			0.60	0.60		

16.3 Body-Worn Accessory Exposure Conditions


WWAN Band		Exposure Position	1	2	3	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	Bluetooth				
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)				
GSM	GSM850	Front	0.493	0.490	0.087	0.98	0.58		
		Back	0.739	0.359	0.076	1.10	0.82		
	GSM1900	Front	0.527	0.490	0.087	1.02	0.61		
		Back	1.177	0.359	0.076	1.54	1.25		
WCDMA	Band V	Front	0.689	0.490	0.087	1.18	0.78		
		Back	0.837	0.359	0.076	1.20	0.91		
	Band II	Front	0.496	0.490	0.087	0.99	0.58		
		Back	1.100	0.359	0.076	1.46	1.18		
LTE	Band 5	Front	0.701	0.490	0.087	1.19	0.79		
		Back	0.882	0.359	0.076	1.24	0.96		
	Band 7	Front	0.713	0.490	0.087	1.20	0.80		
		Back	0.604	0.359	0.076	0.96	0.68		
	Band 26	Front	0.465	0.490	0.087	0.96	0.55		
		Back	0.682	0.359	0.076	1.04	0.76		
	Band 38	Front	1.193	0.490	0.087	1.68	1.28	0.02	#01
		Back	1.162	0.359	0.076	1.52	1.24		
	Band 41	Front	1.071	0.490	0.087	1.56	1.16		
		Back	1.011	0.359	0.076	1.37	1.09		

16.4 SPLSR Evaluation and Analysis

General Note:

- When standalone SAR is measured for both antennas in the pair, the peak location separation distance is computed by the square root of $[(x_1-x_2)^2 + (y_1-y_2)^2 + (z_1-z_2)^2]$, where (x_1, y_1, z_1) and (x_2, y_2, z_2) are the coordinates in the area scans or extrapolated peak SAR locations in the zoom scans, as appropriate.
- $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.

Case #01	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (cm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE Band 38	Front	1.193	5	7.58	-0.08	0.37	144.9	1.68	0.02	Not required
	WLAN2.4GHz		0.490	5	-6.7	2.36	0.4				



Test Engineer: Nick Hu



17. Uncertainty Assessment

Pre KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

18. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [11] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [12] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.



Appendix A. Plots of System Performance Check

The plots are shown as follows.

System Check_Head_835MHz**DUT: D835V2 - SN:4d151**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: HSL_850 Medium parameters used: $f = 835$ MHz; $\sigma = 0.908$ S/m; $\epsilon_r = 41.897$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.73, 9.73, 9.73); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM3; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.04 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 54.41 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 3.49 W/kg

SAR(1 g) = 2.4 W/kg; SAR(10 g) = 1.58 W/kg

Maximum value of SAR (measured) = 3.02 W/kg



0 dB = 3.02 W/kg = 4.80 dBW/kg

System Check_Head_2600MHz**DUT: D2600V2 - SN:1112**

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: HSL_2600 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.052$ S/m; $\epsilon_r = 38.095$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.62, 7.62, 7.62); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM2; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 22.1 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 85.47 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 32.0 W/kg

SAR(1 g) = 14.3 W/kg; SAR(10 g) = 6.2 W/kg

Maximum value of SAR (measured) = 22.8 W/kg



0 dB = 22.8 W/kg = 13.58 dBW/kg

System Check_Body_835MHz**DUT: D835V2 - SN:4d151**

Communication System: UID 0, CW (0); Frequency: 835 MHz; Duty Cycle: 1:1

Medium: MSL_850 Medium parameters used: $f = 835$ MHz; $\sigma = 0.978$ S/m; $\epsilon_r = 54.809$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.72, 9.72, 9.72); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (61x61x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 3.13 W/kg


Pin=250mW/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 52.23 V/m; Power Drift = -0.10 dB

Peak SAR (extrapolated) = 3.67 W/kg

SAR(1 g) = 2.49 W/kg; SAR(10 g) = 1.65 W/kg

Maximum value of SAR (measured) = 3.14 W/kg



0 dB = 3.14 W/kg = 4.97 dBW/kg

System Check_Body_2600MHz**DUT: D2600V2 - SN:1112**

Communication System: UID 0, CW (0); Frequency: 2600 MHz; Duty Cycle: 1:1

Medium: MSL_2600 Medium parameters used: $f = 2600$ MHz; $\sigma = 2.198$ S/m; $\epsilon_r = 52.262$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.3 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Pin=250mW/Area Scan (81x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 21.7 W/kg


Pin=250mW/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.43 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 28.7 W/kg

SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.46 W/kg

Maximum value of SAR (measured) = 21.7W/kg



0 dB = 21.7 W/kg = 13.36 dBW/kg



Appendix B. Plots of High SAR Measurement

The plots are shown as follows.

01_LTE Band 26_15M_QPSK_1RB_37Offset_Right Cheek_0mm_Ch26865

Communication System: UID 0, FDD_LTE (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: HSL_850 Medium parameters used: $f = 831.5$ MHz; $\sigma = 0.905$ S/m; ϵ_r

$= 41.943$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.73, 9.73, 9.73); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM3; Type: SAM; Serial: TP-1542
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch26865/Area Scan (71x121x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm

Maximum value of SAR (interpolated) = 0.244 W/kg



Ch26865/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm

Reference Value = 4.519 V/m; Power Drift = 0.03 dB

Peak SAR (extrapolated) = 0.267 W/kg

SAR(1 g) = 0.205 W/kg; SAR(10 g) = 0.156 W/kg

Maximum value of SAR (measured) = 0.234 W/kg



0 dB = 0.234 W/kg = -6.31 dBW/kg

02_LTE Band 38_20M_QPSK_1RB_49Offset_Left Cheek_0mm_Ch38000

Communication System: UID 0, TDD_LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59
Medium: HSL_2600 Medium parameters used: $f = 2595$ MHz; $\sigma = 2.046$ S/m; $\epsilon_r =$

38.112; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.62, 7.62, 7.62); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM2; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch38000/Area Scan (81x141x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.345 W/kg


Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 3.381 V/m; Power Drift = 0.17 dB

Peak SAR (extrapolated) = 0.466 W/kg

SAR(1 g) = 0.240 W/kg; SAR(10 g) = 0.124 W/kg

Maximum value of SAR (measured) = 0.350 W/kg



0 dB = 0.350 W/kg = -4.56 dBW/kg

03_LTE Band 41_20M_QPSK_1RB_49Offset_Left Cheek_0mm_Ch40140

Communication System: UID 0, TDD_LTE (0); Frequency: 2545 MHz; Duty Cycle: 1:1.59

Medium: HSL_2600 Medium parameters used: $f = 2545$ MHz; $\sigma = 1.986$ S/m; $\epsilon_r = 38.294$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.4 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.62, 7.62, 7.62); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM2; Type: SAM; Serial: TP-1644
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch40140/Area Scan (81x141x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.214 W/kg



Ch40140/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.932 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 0.285 W/kg

SAR(1 g) = 0.149 W/kg; SAR(10 g) = 0.079 W/kg

Maximum value of SAR (measured) = 0.214 W/kg



0 dB = 0.214 W/kg = -6.70 dBW/kg

04_LTE Band 26_15M_QPSK_1RB_37Offset_Back_5mm_Ch26865

Communication System: UID 0, FDD_LTE (0); Frequency: 831.5 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 831.5$ MHz; $\sigma = 0.975$ S/m; $\epsilon_r = 54.859$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.72, 9.72, 9.72); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch26865/Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.784 W/kg


Ch26865/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.07 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.894 W/kg

SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.346 W/kg

Maximum value of SAR (measured) = 0.703 W/kg



05_LTE Band 38_20M_QPSK_100RB_0Offset_Front_5mm_Ch38000

Communication System: UID 0, TDD_LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2595$ MHz; $\sigma = 2.192$ S/m; $\epsilon_r = 52.277$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch38000/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.53 W/kg

Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.714 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.60 W/kg

SAR(1 g) = 1.120 W/kg; SAR(10 g) = 0.482 W/kg

Maximum value of SAR (measured) = 1.83 W/kg



Ch38000/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.714 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.31 W/kg

SAR(1 g) = 0.763 W/kg; SAR(10 g) = 0.370 W/kg

Maximum value of SAR (measured) = 1.63 W/kg



0 dB = 1.63 W/kg = 2.12 dBW/kg

06_LTE Band 41_20M_QPSK_1RB_49Offset_Front_5mm_Ch41140

Communication System: UID 0, TDD_LTE (0); Frequency: 2645 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2645$ MHz; $\sigma = 2.261$ S/m; $\epsilon_r = 52.078$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch41140/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.34 W/kg



Ch41140/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.479 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.13 W/kg

SAR(1 g) = 0.906 W/kg; SAR(10 g) = 0.389 W/kg

Maximum value of SAR (measured) = 1.49 W/kg



0 dB = 1.49 W/kg = 1.73 dBW/kg

07_LTE Band 26_15M_QPSK_1RB_37Offset_Back_5mm_Ch26865

Communication System: UID 0, FDD_LTE (0); Frequency: 831.5 MHz; Duty Cycle: 1:1
Medium: MSL_850 Medium parameters used: $f = 831.5$ MHz; $\sigma = 0.975$ S/m; $\epsilon_r = 54.859$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(9.72, 9.72, 9.72); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch26865/Area Scan (121x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 0.784 W/kg


Ch26865/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.07 V/m; Power Drift = 0.11 dB

Peak SAR (extrapolated) = 0.894 W/kg

SAR(1 g) = 0.547 W/kg; SAR(10 g) = 0.346 W/kg

Maximum value of SAR (measured) = 0.703 W/kg



08_LTE Band 38_20M_QPSK_100RB_0Offset_Front_5mm_Ch38000

Communication System: UID 0, TDD_LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2595$ MHz; $\sigma = 2.192$ S/m; $\epsilon_r = 52.277$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch38000/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.53 W/kg

Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.714 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.60 W/kg

SAR(1 g) = 1.120 W/kg; SAR(10 g) = 0.482 W/kg

Maximum value of SAR (measured) = 1.83 W/kg


Ch38000/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 5.714 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 2.31 W/kg

SAR(1 g) = 0.763 W/kg; SAR(10 g) = 0.370 W/kg

Maximum value of SAR (measured) = 1.63 W/kg



0 dB = 1.63 W/kg = 2.12 dBW/kg

09_LTE Band 41_20M_QPSK_1RB_49Offset_Front_5mm_Ch41140

Communication System: UID 0, TDD_LTE (0); Frequency: 2645 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2645$ MHz; $\sigma = 2.261$ S/m; $\epsilon_r = 52.078$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch41140/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.34 W/kg


Ch41140/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 4.479 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 2.13 W/kg

SAR(1 g) = 0.906 W/kg; SAR(10 g) = 0.389 W/kg

Maximum value of SAR (measured) = 1.49 W/kg



0 dB = 1.49 W/kg = 1.73 dBW/kg

10_LTE Band 38_20M_QPSK_50RB_0Offset_Back_0mm_Ch38000

Communication System: UID 0, TDD_LTE (0); Frequency: 2595 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2595$ MHz; $\sigma = 2.192$ S/m; $\epsilon_r = 52.277$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch38000/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 9.45 W/kg


Ch38000/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.851 V/m; Power Drift = 0.07 dB

Peak SAR (extrapolated) = 17.7 W/kg

SAR(1 g) = 5.73 W/kg; SAR(10 g) = 1.850 W/kg

Maximum value of SAR (measured) = 9.69 W/kg



0 dB = 9.69 W/kg = 9.86 dBW/kg

11_LTE Band 41_20M_QPSK_1RB_49Offset_Back_0mm_Ch41140

Communication System: UID 0, TDD_LTE (0); Frequency: 2645 MHz; Duty Cycle: 1:1.59

Medium: MSL_2600 Medium parameters used: $f = 2645$ MHz; $\sigma = 2.261$ S/m; $\epsilon_r = 52.078$; $\rho = 1000$

kg/m³

Ambient Temperature : 23.3 °C; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: EX3DV4 - SN3857; ConvF(7.59, 7.59, 7.59); Calibrated: 2017.5.26;
- Sensor-Surface: 2mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1210; Calibrated: 2017.5.25
- Phantom: SAM1; Type: SAM; Serial: TP-1164
- Measurement SW: DASY52, Version 52.8 (8); SEMCAD X Version 14.6.10 (7331)

Ch41140/Area Scan (151x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 6.22 W/kg


Ch41140/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 2.350 V/m; Power Drift = 0.13 dB

Peak SAR (extrapolated) = 11.9 W/kg

SAR(1 g) = 4.08 W/kg; SAR(10 g) = 1.300 W/kg

Maximum value of SAR (measured) = 8.01 W/kg



0 dB = 8.01 W/kg = 9.04 dBW/kg



Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client

Sporton_XA

Certificate No: **Z17-97038**

CALIBRATION CERTIFICATE

Object

D835V2 - SN: 4d151

Calibration Procedure(s)

FD-Z11-003-01

Calibration Procedures for dipole validation kits

Calibration date:

March 20, 2017

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	101919	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Power sensor NRP-Z91	101547	27-Jun-16 (CTTL, No.J16X04777)	Jun-17
Reference Probe EX3DV4	SN 3617	23-Jan-17(SPEAG,No.EX3-3617_Jan17)	Jan-18
DAE4	SN 777	22-Aug-16(CTTL-SPEAG,No.Z16-97138)	Aug-17
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	13-Jan-17 (CTTL, No.J17X00286)	Jan-18
Network Analyzer E5071C	MY46110673	13-Jan-17 (CTTL, No.J17X00285)	Jan-18

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Qi Dianyuan	SAR Project Leader	
Approved by:	Lu Bingsong	Deputy Director of the laboratory	

Issued: March 24, 2017

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) For hand-held devices used in close proximity to the ear (frequency range of 300MHz to 3GHz)", February 2005
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.8.8.1258
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	41.0 $\pm$ 6 %	0.89 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.41 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	9.73 mW / g $\pm$ 20.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.57 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	6.33 mW / g $\pm$ 20.4 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	55.6 $\pm$ 6 %	0.96 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.41 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	9.72 mW / g $\pm$ 20.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.60 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	6.44 mW / g $\pm$ 20.4 % (k=2)