FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT1921-6, XT1921-1
FCC ID	:	IHDT56XC1
STANDARD	:	FCC 47 CFR Part 2, and 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 20, 2017 and testing was completed on Jan. 29, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI / TIA-603-E and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager

Testing Laboratory
1190

SPORTON INTERNATIONAL INC.
No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum Frequency Tolerance and Emission Designator 6
1.7 Testing Site 7
1.8 Applied Standards 7

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**

2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 10

3 TEST RESULT **11**

3.1 Conducted Output Power Measurement 11
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement 12
3.3 Emissions Mask Measurement 13
3.4 Emissions Mask – Out Of Band Emissions Measurement 15
3.5 Field Strength of Spurious Radiation Measurement 16
3.6 Frequency Stability Measurement 18

4 LIST OF MEASURING EQUIPMENT **20**

5 UNCERTAINTY OF EVALUATION **21**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG7D2018-03E	Rev. 01	Initial issue of report	Mar. 02, 2018

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< $50+10\log_{10}$(P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< $43+10\log_{10}$(P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 30.94 dB at 2464.000 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W. Merchandise Mart Plaza, Chicago IL 60654, USA

1.2 Manufacturer

Motorola Mobility LLC
222 W. Merchandise Mart Plaza, Chicago IL 60654, USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1921-6, XT1921-1
FCC ID	IHDT56XC1
IMEI Code	351838090014992 (for Radiation) 351838090015965 (for Conducted)
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/FM/GNSS WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 Bluetooth BR/EDR/LE
HW Version	DVT1B
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Accessory List	
AC Adapter 1	Brand Name : Motorola
	Model Name : C-P35
AC Adapter 2	Brand Name : Motorola
	Model Name : SSW-2919UMTJ C-P35 SPN5945A
AC Adapter 3	Brand Name : Motorola
	Model Name : C-P56
AC Adapter 4	Brand Name : Motorola
	Model Name : C-P56
Battery	Brand Name : Motorola
	Model Name : GK40
USB Cable	Brand Name : Saibao
	Model Name : SWT-A083A

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814.7 ~ 823.3 MHz
Rx Frequency	859.7 ~ 868.3 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	23.40 dBm
Antenna Type / Gain	PIFA Antenna and Coupling type (LDS) Antenna with -0.105 dBi
Type of Modulation	QPSK / 16QAM

Remark: This test report recorded only product characteristics and test results of PCS Licensed Transmitter Held to Ear (PCE).

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Frequency Tolerance and Emission Designator

LTE Band 26	QPSK		16QAM	
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)
1.4	1M10G7D	-	1M10W7D	-
3	2M72G7D	-	2M72W7D	-
5	4M50G7D	-	4M49W7D	-
10	9M09G7D	0.0028	9M01W7D	-
15	13M4G7D	0.0029	13M5W7D	-

1.7 Testing Site

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	**Sporton Site No.**
	TH05-HY

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd Rd. Guishan Dist, Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH13-HY

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR Part 2, 90
- ANSI / TIA-603-E
- FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02
- Interim Guidance for Equipment Authorization of Devices with Channel Bandwidths Combined Across Two Contiguous Service Rule Allocations OET/Lab/EACB, June 6, 2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v			v	v	v
Frequency Stability	26				v	v	-	v				v		v	
E.R.P.	26					v	-	v	v	v			v		
Radiated Spurious Emission	26	Worst Case											v		
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies. 4. All the radiated test cases were performed with Adapter 1.														

2.2 Connection Diagram of Test System

<EUT Standalone>



<EUT with Accessories>



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a)

(a) Out-of-band emission requirement shall apply only to the "outer" channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log_{10}(f/6.1) decibels or 50 + 10 Log_{10}(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log_{10}(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5° C and connected with the base station.
2. The power supply voltage to the EUT was varied from BEP to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
LTE Base Station	Anritsu	MT8820C	6201432821	GSM/GPRS /WCDMA/LTE	Oct. 13, 2017	Jan. 03, 2018~ Jan. 29, 2018	Oct. 12, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 07, 2017	Jan. 03, 2018~ Jan. 29, 2018	Nov. 06, 2018	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV30	100895	9kHz~30GHz	Apr. 25, 2017	Jan. 03, 2018~ Jan. 29, 2018	Apr. 24, 2018	Conducted (TH05-HY)
Temperature Chamber	ESPEC	SH-641	92013720	-30℃~70℃	Aug. 28, 2017	Jan. 03, 2018~ Jan. 29, 2018	Aug. 27, 2018	Conducted (TH05-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL890001	1V~20V 0.5A~5A	Oct. 06, 2017	Jan. 03, 2018~ Jan. 29, 2018	Oct. 05, 2018	Conducted (TH05-HY)
Coupler	Warison	1-18GHz 20dB 25WSMA Directional Coupler	#B	1G~18GHz	Feb. 20, 2017	Jan. 03, 2018~ Jan. 29, 2018	Feb. 19, 2018	Conducted (TH05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 18, 2017	Jan. 17, 2018~ Jan. 22, 2018	Jul. 17, 2018	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0 602	30MHz~1GHz	Oct. 14, 2017	Jan. 17, 2018~ Jan. 22, 2018	Oct. 13, 2018	Radiation (03CH13-HY)
Amplifier	Sonoma-Instrument	310 N	187282	9KHz~1GHz	Dec. 21, 2016	Jan. 17, 2018~ Jan. 22, 2018	Dec. 20, 2018	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1241	1GHz ~ 18GHz	Jun. 15, 2017	Jan. 17, 2018~ Jan. 22, 2018	Jun. 14, 2018	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-00101 800-30-10P	1590074	1GHz~18GHz	May 22, 2017	Jan. 17, 2018~ Jan. 22, 2018	May 21, 2018	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY55370526	10Hz~44GHz	Mar. 15, 2017	Jan. 17, 2018~ Jan. 22, 2018	Mar. 14, 2018	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1m~4m	N/A	Jan. 17, 2018~ Jan. 22, 2018	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jan. 17, 2018~ Jan. 22, 2018	N/A	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170251	18GHz- 40GHz	Nov. 10, 2017	Jan. 17, 2018~ Jan. 22, 2018	Nov. 09, 2018	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Jan. 17, 2018~ Jan. 22, 2018	Nov. 26, 2018	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1522	1G~18GHz	Mar. 17, 2017	Jan. 17, 2018~ Jan. 22, 2018	Mar. 16, 2018	Radiation (03CH13-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May 22, 2017	Jan. 17, 2018~ Jan. 22, 2018	May 21, 2018	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz ~ 26.5GHz	Dec. 05, 2017	Jan. 17, 2018~ Jan. 22, 2018	Dec. 04, 2018	Radiation (03CH13-HY)

5 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.07

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.48

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.92

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	22.95	-	-
15	1	37		**23.40**	-	-
15	1	74		22.81	-	-
15	36	0		22.25	-	-
15	36	20		22.20	-	-
15	36	39		22.10	-	-
15	75	0		22.32	-	-
15	1	0	16-QAM	22.01	-	-
15	1	37		21.99	-	-
15	1	74		21.65	-	-
15	36	0		21.30	-	-
15	36	20		21.30	-	-
15	36	39		21.25	-	-
15	75	0		21.28	-	-
10	1	0	QPSK	-	22.99	-
10	1	25		-	23.33	-
10	1	49		-	23.15	-
10	25	0		-	22.51	-
10	25	12		-	22.23	-
10	25	25		-	22.04	-
10	50	0		-	22.21	-
10	1	0	16-QAM	-	21.69	-
10	1	25		-	21.82	-
10	1	49		-	21.47	-
10	25	0		-	21.10	-
10	25	12		-	21.23	-
10	25	25		-	21.16	-
10	50	0		-	21.20	-

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
5	1	0	QPSK	22.93	22.95	22.61
5	1	12		23.32	23.24	22.90
5	1	24		22.82	23.01	22.62
5	12	0		22.26	22.16	22.81
5	12	7		22.21	22.17	21.92
5	12	13		22.18	22.18	21.77
5	25	0		22.15	22.18	21.82
5	1	0	16-QAM	21.55	22.06	21.54
5	1	12		22.00	22.18	21.60
5	1	24		21.82	21.45	21.26
5	12	0		21.26	20.99	20.81
5	12	7		21.10	21.22	20.91
5	12	13		21.11	21.20	20.79
5	25	0		21.24	21.15	20.81
3	1	0	QPSK	22.98	22.82	22.91
3	1	8		23.00	22.92	22.71
3	1	14		22.81	23.10	22.50
3	8	0		22.34	22.10	22.10
3	8	4		22.22	22.16	21.89
3	8	7		22.34	22.16	21.95
3	15	0		22.16	22.12	22.04
3	1	0	16-QAM	21.95	21.84	21.31
3	1	8		21.75	21.74	21.29
3	1	14		21.67	22.30	21.38
3	8	0		21.30	21.30	20.99
3	8	4		21.31	21.21	20.74
3	8	7		21.32	21.35	20.81
3	15	0		21.28	21.20	20.80

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
1.4	1	0	QPSK	23.10	23.04	22.80
1.4	1	3		23.18	23.21	22.72
1.4	1	5		23.00	22.96	22.74
1.4	3	0		23.12	23.18	23.09
1.4	3	1		23.27	23.29	22.99
1.4	3	3		23.22	23.24	22.81
1.4	6	0		22.30	22.16	21.81
1.4	1	0	16-QAM	21.74	21.65	21.50
1.4	1	3		22.18	21.68	21.60
1.4	1	5		22.20	21.65	21.35
1.4	3	0		22.16	22.04	21.80
1.4	3	1		22.30	22.46	21.80
1.4	3	3		22.18	22.03	21.69
1.4	6	0		21.09	20.99	20.64

LTE Band 26_Part 90S

Peak-to-Average Ratio

Mode	LTE Band 26 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.39	4.84	4.55	5.68	
Highest CH	-	-	-	-	

LTE Band 26 / 10MHz / QPSK

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 26 / 10MHz / 16QAM

Middle Channel / 1RB



Middle Channel / Full RB



26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.27	1.26	2.99	2.99	4.92	4.88	-	-	14.57	14.42	-	-
Middle CH	1.27	1.26	2.95	3.06	4.91	4.95	9.83	9.81	-	-	-	-
Highest CH	1.27	1.28	3.03	3.00	4.99	4.94	-	-	-	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel /3MHz / 16QAM



Highest Channel /3MHz / QPSK



Highest Channel /3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.10	1.10	2.71	2.70	4.49	4.49	-	-	13.43	13.46	-	-
Middle CH	1.10	1.09	2.72	2.72	4.50	4.49	9.09	9.01	-	-	-	-
Highest CH	1.09	1.10	2.72	2.70	4.49	4.49	-	-	-	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 26

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



Conducted Band Edge

LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.12 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-17.81 dBm	-40.93 dB	-4.81 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-21.18 dBm	-44.30 dB	-0.18 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-50.36 dBm	-73.48 dB	-29.36 dB
737.500 kHz	3.000 MHz	100.000 kHz	816.01618 MHz	-42.60 dBm	-65.72 dB	-29.60 dB

Date: 6.JAN.2018 20:30:05

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 23.14 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	821.87940 MHz	-38.44 dBm	-61.58 dB	-25.44 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-49.07 dBm	-72.21 dB	-28.07 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-21.25 dBm	-44.39 dB	-0.25 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-16.57 dBm	-39.71 dB	-3.57 dB

Date: 6.JAN.2018 20:31:22

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 22.05 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.94945 MHz	-21.87 dBm	-43.92 dB	-8.87 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-25.44 dBm	-47.49 dB	-4.44 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-25.83 dBm	-47.88 dB	-4.83 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44185 MHz	-21.07 dBm	-43.12 dB	-8.07 dB

Date: 6.JAN.2018 16:34:56

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.87 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55815 MHz	-22.43 dBm	-44.30 dB	-9.43 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-26.58 dBm	-48.44 dB	-5.58 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-27.16 dBm	-49.02 dB	-6.16 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.05925 MHz	-22.83 dBm	-44.70 dB	-9.83 dB

Date: 6.JAN.2018 16:39:29

LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.57 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.95815 MHz	-17.85 dBm	-39.42 dB	-4.85 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-21.43 dBm	-43.00 dB	-0.43 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-50.52 dBm	-72.09 dB	-29.52 dB
737.500 kHz	3.000 MHz	100.000 kHz	816.08579 MHz	-43.87 dBm	-65.44 dB	-30.87 dB

Date: 6.JAN.2018 16:33:48

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.30 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.02733 MHz	-43.24 dBm	-64.54 dB	-30.24 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-51.35 dBm	-72.65 dB	-30.35 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-22.22 dBm	-43.52 dB	-1.22 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.05055 MHz	-17.99 dBm	-39.29 dB	-4.99 dB

Date: 6.JAN.2018 16:38:21

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.92 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	813.94075 MHz	-25.11 dBm	-46.03 dB	-12.11 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	813.99531 MHz	-27.53 dBm	-48.45 dB	-6.53 dB
700.000 kHz	737.500 kHz	30.000 kHz	815.40469 MHz	-27.95 dBm	-48.86 dB	-6.95 dB
737.500 kHz	3.000 MHz	100.000 kHz	815.44185 MHz	-22.60 dBm	-43.51 dB	-9.60 dB

Date: 6.JAN.2018 16:36:05

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.99 dBm Tx Bandwidth 1.400 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-737.500 kHz	100.000 kHz	822.55815 MHz	-23.91 dBm	-44.91 dB	-10.91 dB
-737.500 kHz	-700.000 kHz	30.000 kHz	822.59531 MHz	-27.94 dBm	-48.93 dB	-6.94 dB
700.000 kHz	737.500 kHz	30.000 kHz	824.00469 MHz	-28.06 dBm	-49.05 dB	-7.06 dB
737.500 kHz	3.000 MHz	100.000 kHz	824.04185 MHz	-22.61 dBm	-43.60 dB	-9.61 dB

Date: 6.JAN.2018 16:40:37

LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-14.38 dBm	-37.16 dB	-1.38 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-21.05 dBm	-43.83 dB	-0.05 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-53.63 dBm	-76.40 dB	-32.63 dB
1.538 MHz	5.000 MHz	100.000 kHz	819.26132 MHz	-40.01 dBm	-62.78 dB	-27.01 dB

Date: 6.JAN.2018 16:41:46

Highest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	818.65175 MHz	-37.51 dBm	-60.37 dB	-24.51 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-52.89 dBm	-75.74 dB	-31.89 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-21.02 dBm	-43.88 dB	-0.02 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-16.24 dBm	-39.09 dB	-3.24 dB

Date: 6.JAN.2018 20:32:13

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-24.55 dBm	-46.66 dB	-11.55 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-28.60 dBm	-50.71 dB	-7.60 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-28.46 dBm	-50.57 dB	-7.46 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04474 MHz	-23.91 dBm	-46.02 dB	-10.91 dB

Date: 6.JAN.2018 16:44:02

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-25.53 dBm	-47.50 dB	-12.53 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-29.11 dBm	-51.08 dB	-8.11 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-29.52 dBm	-51.48 dB	-8.52 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-24.11 dBm	-46.07 dB	-11.11 dB

Date: 6.JAN.2018 16:48:36

LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.36 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.95526 MHz	-17.39 dBm	-38.76 dB	-4.39 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-22.64 dBm	-44.01 dB	-1.64 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-55.18 dBm	-76.54 dB	-34.18 dB
1.538 MHz	5.000 MHz	100.000 kHz	818.05887 MHz	-43.71 dBm	-65.07 dB	-30.71 dB

Date: 6.JAN.2018 16:42:54

Highest Band Edge /1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.46 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	818.66624 MHz	-42.49 dBm	-63.95 dB	-29.49 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-54.76 dBm	-76.22 dB	-33.76 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-22.85 dBm	-44.31 dB	-1.85 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-17.61 dBm	-39.07 dB	-4.61 dB

Date: 6.JAN.2018 16:47:27

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.80 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	813.94077 MHz	-27.19 dBm	-47.98 dB	-14.19 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99063 MHz	-31.28 dBm	-52.07 dB	-10.28 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00937 MHz	-30.53 dBm	-51.32 dB	-9.53 dB
1.538 MHz	5.000 MHz	100.000 kHz	817.04474 MHz	-25.35 dBm	-46.14 dB	-12.35 dB

Date: 6.JAN.2018 16:45:11

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.86 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-1.538 MHz	100.000 kHz	820.95526 MHz	-27.45 dBm	-48.30 dB	-14.45 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99063 MHz	-30.71 dBm	-51.56 dB	-9.71 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00937 MHz	-30.65 dBm	-51.50 dB	-9.65 dB
1.538 MHz	5.000 MHz	100.000 kHz	824.04474 MHz	-27.02 dBm	-47.87 dB	-14.02 dB

Date: 6.JAN.2018 16:49:44

LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-20.61 dBm	-43.24 dB	-7.61 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-25.09 dBm	-47.71 dB	-4.09 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-58.59 dBm	-81.21 dB	-37.59 dB
2.538 MHz	7.500 MHz	100.000 kHz	822.98791 MHz	-38.59 dBm	-61.22 dB	-25.59 dB

Date: 6.JAN.2018 16:50:52

Highest Band Edge / 1 RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	815.01209 MHz	-36.17 dBm	-58.99 dB	-23.17 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-57.26 dBm	-80.09 dB	-36.26 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-25.21 dBm	-48.03 dB	-4.21 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-23.09 dBm	-45.92 dB	-10.09 dB

Date: 6.JAN.2018 16:55:25

Lowest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-27.65 dBm	-49.66 dB	-14.65 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-31.94 dBm	-53.94 dB	-10.94 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-31.88 dBm	-53.88 dB	-10.88 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.04838 MHz	-26.77 dBm	-48.77 dB	-13.77 dB

Date: 6.JAN.2018 16:53:09

Highest Band Edge / Full RB



Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95162 MHz	-27.31 dBm	-49.21 dB	-14.31 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-32.18 dBm	-54.07 dB	-11.18 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-32.88 dBm	-54.77 dB	-11.88 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-27.78 dBm	-49.67 dB	-14.78 dB

Date: 6.JAN.2018 16:57:41

LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 21.02 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-24.29 dBm	-45.30 dB	-11.29 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-25.89 dBm	-46.90 dB	-4.89 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-59.43 dBm	-80.44 dB	-38.43 dB
2.538 MHz	7.500 MHz	100.000 kHz	822.96615 MHz	-43.00 dBm	-64.02 dB	-30.00 dB

Date: 6.JAN.2018 16:52:01

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.69 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	815.07738 MHz	-40.23 dBm	-60.92 dB	-27.23 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-58.93 dBm	-79.62 dB	-37.93 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-26.88 dBm	-47.56 dB	-5.88 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-21.74 dBm	-42.43 dB	-8.74 dB

Date: 6.JAN.2018 16:56:33

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.84 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	813.95162 MHz	-30.38 dBm	-51.22 dB	-17.38 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	813.98125 MHz	-34.25 dBm	-55.09 dB	-13.25 dB
2.500 MHz	2.538 MHz	30.000 kHz	819.01875 MHz	-33.94 dBm	-54.78 dB	-12.94 dB
2.538 MHz	7.500 MHz	100.000 kHz	819.04838 MHz	-28.85 dBm	-49.69 dB	-15.85 dB

Date: 6.JAN.2018 16:54:17

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.04 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-7.500 MHz	-2.538 MHz	100.000 kHz	818.95162 MHz	-28.91 dBm	-49.95 dB	-15.91 dB
-2.538 MHz	-2.500 MHz	30.000 kHz	818.98125 MHz	-33.86 dBm	-54.91 dB	-12.86 dB
2.500 MHz	2.538 MHz	30.000 kHz	824.01875 MHz	-34.11 dBm	-55.16 dB	-13.11 dB
2.538 MHz	7.500 MHz	100.000 kHz	824.04838 MHz	-27.98 dBm	-49.03 dB	-14.98 dB

Date: 6.JAN.2018 16:58:49

LTE Band 26 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Band Edge / Full RB



LTE Band 26 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Highest Band Edge / 1 RB



Band Edge / Full RB



LTE Band 26 / 15MHz QPSK

Lowest Band Edge / 1 RB



Lowest Band Edge / Full RB



LTE Band 26 / 15MHz 16QAM

Lowest Band Edge / 1 RB



Lowest Band Edge / Full RB



Conducted Spurious Emission

LTE Band 26 / 1.4MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	723.26199 MHz	-57.89 dBm	-44.89 dB
836.500 MHz	1.000 GHz	100.000 kHz	969.37438 MHz	-56.86 dBm	-43.86 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44339 GHz	-45.40 dBm	-32.40 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.96875 GHz	-41.48 dBm	-28.48 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.04974 GHz	-43.31 dBm	-30.31 dB

Date: 6.JAN.2018 17:58:04

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	219.17729 MHz	-57.83 dBm	-44.83 dB
836.500 MHz	1.000 GHz	100.000 kHz	981.78796 MHz	-56.76 dBm	-43.76 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44289 GHz	-46.68 dBm	-33.68 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98825 GHz	-41.20 dBm	-28.20 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.03374 GHz	-43.40 dBm	-30.40 dB

Date: 6.JAN.2018 17:58:57

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	328.99713 MHz	-57.69 dBm	-44.69 dB
836.500 MHz	1.000 GHz	100.000 kHz	995.99825 MHz	-56.90 dBm	-43.90 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45589 GHz	-46.05 dBm	-33.05 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99825 GHz	-41.41 dBm	-28.41 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.09773 GHz	-43.44 dBm	-30.44 dB

Date: 6.JAN.2018 17:59:50

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	746.93341 MHz	-57.90 dBm	-44.90 dB
836.500 MHz	1.000 GHz	100.000 kHz	986.19805 MHz	-56.75 dBm	-43.75 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45589 GHz	-46.66 dBm	-33.66 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99725 GHz	-41.39 dBm	-28.39 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.31267 GHz	-43.36 dBm	-30.36 dB

Date: 6.JAN.2018 18:00:43

LTE Band 26 / 1.4MHz

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	216.46089 MHz	-57.88 dBm	-44.88 dB
836.500 MHz	1.000 GHz	100.000 kHz	984.07468 MHz	-56.93 dBm	-43.93 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.46888 GHz	-44.94 dBm	-31.94 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99325 GHz	-41.51 dBm	-28.51 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.04624 GHz	-43.11 dBm	-30.11 dB

Date: 6.JAN.2018 18:01:35

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	673.20277 MHz	-57.90 dBm	-44.90 dB
836.500 MHz	1.000 GHz	100.000 kHz	982.27797 MHz	-56.81 dBm	-43.81 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.46888 GHz	-46.01 dBm	-33.01 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99625 GHz	-41.21 dBm	-28.21 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.08173 GHz	-43.49 dBm	-30.49 dB

Date: 6.JAN.2018 18:02:28

LTE Band 26 / 3MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	237.02786 MHz	-57.88 dBm	-44.88 dB
836.500 MHz	1.000 GHz	100.000 kHz	974.11114 MHz	-56.76 dBm	-43.76 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44289 GHz	-45.26 dBm	-32.26 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98725 GHz	-41.49 dBm	-28.49 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.07173 GHz	-43.42 dBm	-30.42 dB

Date: 6.JAN.2018 18:03:21

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	218.40117 MHz	-57.77 dBm	-44.77 dB
836.500 MHz	1.000 GHz	100.000 kHz	975.90784 MHz	-56.87 dBm	-43.87 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44289 GHz	-46.48 dBm	-33.48 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99175 GHz	-41.23 dBm	-28.23 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.03574 GHz	-43.42 dBm	-30.42 dB

Date: 6.JAN.2018 18:04:14

LTE Band 26 / 3MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	212.96839 MHz	-57.76 dBm	-44.76 dB
836.500 MHz	1.000 GHz	100.000 kHz	994.03821 MHz	-56.58 dBm	-43.58 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45339 GHz	-45.61 dBm	-32.61 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.83927 GHz	-41.18 dBm	-28.18 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00525 GHz	-43.17 dBm	-30.17 dB

Date: 6.JAN.2018 18:05:07

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	336.37019 MHz	-57.92 dBm	-44.92 dB
836.500 MHz	1.000 GHz	100.000 kHz	987.99476 MHz	-56.71 dBm	-43.71 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.99975 GHz	-46.68 dBm	-33.68 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.97875 GHz	-41.37 dBm	-28.37 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.08223 GHz	-43.42 dBm	-30.42 dB

Date: 6.JAN.2018 18:06:00

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	224.61007 MHz	-57.83 dBm	-44.83 dB
836.500 MHz	1.000 GHz	100.000 kHz	966.59765 MHz	-56.90 dBm	-43.90 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.64309 GHz	-46.09 dBm	-33.09 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99975 GHz	-41.42 dBm	-28.42 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.03774 GHz	-43.34 dBm	-30.34 dB

Date: 6.JAN.2018 18:06:53

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	340.25075 MHz	-57.94 dBm	-44.94 dB
836.500 MHz	1.000 GHz	100.000 kHz	995.01823 MHz	-56.92 dBm	-43.92 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.46388 GHz	-45.72 dBm	-32.72 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98975 GHz	-41.45 dBm	-28.45 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.09923 GHz	-43.44 dBm	-30.44 dB

Date: 6.JAN.2018 18:07:46

LTE Band 26 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	530.39818 MHz	-57.75 dBm	-44.75 dB
836.500 MHz	1.000 GHz	100.000 kHz	972.64111 MHz	-56.91 dBm	-43.91 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44339 GHz	-45.72 dBm	-32.72 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98975 GHz	-41.51 dBm	-28.51 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.09623 GHz	-43.48 dBm	-30.48 dB

Date: 6.JAN.2018 18:08:38

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	222.28173 MHz	-57.86 dBm	-44.86 dB
836.500 MHz	1.000 GHz	100.000 kHz	991.42483 MHz	-56.67 dBm	-43.67 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44289 GHz	-46.52 dBm	-33.52 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.82677 GHz	-41.48 dBm	-28.48 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.07273 GHz	-43.35 dBm	-30.35 dB

Date: 6.JAN.2018 18:09:31

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	340.63881 MHz	-57.93 dBm	-44.93 dB
836.500 MHz	1.000 GHz	100.000 kHz	972.31444 MHz	-56.88 dBm	-43.88 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.63409 GHz	-45.32 dBm	-32.32 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99325 GHz	-41.24 dBm	-28.24 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.28918 GHz	-43.45 dBm	-30.45 dB

Date: 6.JAN.2018 18:10:24

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	226.55035 MHz	-57.63 dBm	-44.63 dB
836.500 MHz	1.000 GHz	100.000 kHz	947.48726 MHz	-56.94 dBm	-43.94 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45089 GHz	-46.32 dBm	-33.32 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99125 GHz	-41.51 dBm	-28.51 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.98825 GHz	-43.44 dBm	-30.44 dB

Date: 6.JAN.2018 18:11:17

LTE Band 26 / 5MHz

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	722.09783 MHz	-57.96 dBm	-44.96 dB
836.500 MHz	1.000 GHz	100.000 kHz	984.89136 MHz	-56.72 dBm	-43.72 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45839 GHz	-45.48 dBm	-32.48 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98675 GHz	-41.44 dBm	-28.44 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.03624 GHz	-43.48 dBm	-30.48 dB

Date: 6.JAN.2018 18:12:10

Highest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	327.05685 MHz	-57.85 dBm	-44.85 dB
836.500 MHz	1.000 GHz	100.000 kHz	963.98427 MHz	-56.70 dBm	-43.70 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.45839 GHz	-46.35 dBm	-33.35 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98925 GHz	-41.54 dBm	-28.54 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.00975 GHz	-43.49 dBm	-30.49 dB

Date: 6.JAN.2018 18:13:03

LTE Band 26 / 10MHz

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	811.000 MHz	100.000 kHz	810.41454 MHz	-53.60 dBm	-40.60 dB
827.000 MHz	1.000 GHz	100.000 kHz	832.27123 MHz	-45.76 dBm	-32.76 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44389 GHz	-45.94 dBm	-32.94 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99375 GHz	-41.34 dBm	-28.34 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.09773 GHz	-43.57 dBm	-30.57 dB

Date: 6.JAN.2018 17:41:20

Middle Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	811.000 MHz	100.000 kHz	810.80485 MHz	-55.40 dBm	-42.40 dB
827.000 MHz	1.000 GHz	100.000 kHz	832.27123 MHz	-46.28 dBm	-33.28 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44389 GHz	-46.19 dBm	-33.19 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.99625 GHz	-41.41 dBm	-28.41 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.04174 GHz	-43.39 dBm	-30.39 dB

Date: 6.JAN.2018 17:42:13

LTE Band 26 / 15MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	231.20702 MHz	-57.70 dBm	-44.70 dB
836.500 MHz	1.000 GHz	100.000 kHz	841.48177 MHz	-43.91 dBm	-30.91 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.63009 GHz	-45.47 dBm	-32.47 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.98625 GHz	-41.54 dBm	-28.54 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.94526 GHz	-43.34 dBm	-30.34 dB

Date: 6.JAN.2018 18:18:42

Lowest Channel / 16QAM



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	806.500 MHz	100.000 kHz	342.57909 MHz	-57.73 dBm	-44.73 dB
836.500 MHz	1.000 GHz	100.000 kHz	841.48177 MHz	-44.28 dBm	-31.28 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.44489 GHz	-46.29 dBm	-33.29 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.97925 GHz	-41.40 dBm	-28.40 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.09273 GHz	-43.40 dBm	-30.40 dB

Date: 6.JAN.2018 18:19:35

Frequency Stability

Test Conditions		LTE Band 26 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 10MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0012	PASS
40	Normal Voltage	0.0028	
30	Normal Voltage	0.0015	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0016	
0	Normal Voltage	0.0023	
-10	Normal Voltage	0.0001	
-20	Normal Voltage	0.0010	
-30	Normal Voltage	0.0021	
20	Maximum Voltage	0.0015	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0016	

Note:

1. Normal Voltage =3.8 V.；Battery End Point (BEP) =3.5 V.；Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Test Conditions		LTE Band 26 (QPSK) / Low Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 15MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0004	PASS
40	Normal Voltage	0.0005	
30	Normal Voltage	0.0016	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0029	
0	Normal Voltage	0.0002	
-10	Normal Voltage	0.0021	
-20	Normal Voltage	0.0009	
-30	Normal Voltage	0.0001	
20	Maximum Voltage	0.0002	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0019	

Note:

1. Normal Voltage =3.8 V.；Battery End Point (BEP) =3.5 V.；Maximum Voltage =4.4 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of ERP and Radiated Test

ERP

LTE Band 26 / 15MHz (Channel 26765)							
Channel	Mode	RB		Conducted		ERP	
		Size	Offset	Power (dBm)	Power (Watts)	ERP(dBm)	ERP(W)
Lowest	QPSK	1	37	23.40	0.22	23.30	0.21
Middle		-	-	-	-	-	-
Highest		-	-	-	-	-	-
Lowest	16QAM	1	0	22.01	0.16	21.91	0.16
Middle		-	-	-	-	-	-
Highest		-	-	-	-	-	-
Limit	ERP < 7W			Result		PASS	

Radiated Spurious Emission

Part90S LTE Band 26

LTE Band 26 / 15MHz / QPSK									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1640	-54.34	-13	-41.34	-65.31	-56.12	0.97	4.91	H
	2464	-43.94	-13	-30.94	-57.45	-45.8	1.28	5.29	H
	3280	-57.13	-13	-44.13	-73.69	-60.48	1.54	7.03	H
									H
									H
									H
									H
	1640	-58.23	-13	-45.23	-69.19	-60.01	0.97	4.91	V
	2464	-47.78	-13	-34.78	-61.29	-49.64	1.28	5.29	V
	3280	-57.14	-13	-44.14	-73.7	-60.49	1.54	7.03	V
									V
									V
									V
									V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.