FCC RADIO TEST REPORT

FCC ID	:	**IHDT56XM1**
Equipment	:	**Mobile Cellular Phone**
Brand Name	:	**Motorola**
Model Name	:	**XT2000-1**
Applicant	:	**Motorola Mobility, LLC** **222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States**
Manufacturer	:	**Motorola Mobility, LLC** **222 W Merchandise Mart Plaza, Suite 1800, Chicago, IL 60654, United States**
Standard	:	**FCC Part 15 Subpart C §15.225**

The product was received on Jan. 24, 2019 and testing was started from Feb. 13, 2019 and completed on Feb. 21, 2019. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Jones Tsai

Approved by: Jones Tsai

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**
Summary of Test Result **4**
1. General Description **5**
1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 6
1.3 Modification of EUT 6
1.4 Testing Location 6
1.5 Applicable Standards 6
2. Test Configuration of Equipment Under Test **7**
2.1 Descriptions of Test Mode 7
2.2 Connection Diagram of Test System 8
2.3 Table for Supporting Units 9
2.4 EUT Operation Test Setup 9
3. Test Results **10**
3.1 AC Power Line Conducted Emissions Measurement 10
3.2 20dB and 99% OBW Spectrum Bandwidth Measurement 12
3.3 Frequency Stability Measurement 13
3.4 Field Strength of Fundamental Emissions and Mask Measurement 14
3.5 Radiated Emissions Measurement 16
3.6 Antenna Requirements 19
4. List of Measuring Equipment **20**
5. Uncertainty of Evaluation **21**
Appendix A. Test Results of Conducted Emission Test
Appendix B. Test Results of Conducted Test Items
B1. Test Result of 20dB Spectrum Bandwidth
B2. Test Result of Frequency Stability
Appendix C. Test Results of Radiated Test Items
C1. Test Result of Field Strength of Fundamental Emissions
C2. Results of Radiated Emissions (9 kHz~30MHz)
C3. Results of Radiated Emissions (30MHz~1GHz)

History of this test report

Report No.	Version	Description	Issued Date
FR912419D	01	Initial issue of report	Mar. 25, 2019
FR912419D	02	Remove watermark.	Mar. 29, 2019

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.207	AC Power Line Conducted Emissions	Pass	Under limit 6.99 dB at 13.560MHz
3.2	15.215(c)	20dB Spectrum Bandwidth	Pass	-
	2.1049	99% OBW Spectrum Bandwidth	Reporting only	-
3.3	15.225(e)	Frequency Stability	Pass	-
3.4	15.225(a)(b)(c)	Field Strength of Fundamental Emissions	Pass	Max level 57.07 dBµV/m at 13.560 MHz
3.5	15.225(d) 15.209	Radiated Spurious Emissions	Pass	Under limit 6.35 dB at 40.800MHz
3.6	15.203	Antenna Requirements	Pass	-

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Wii Chang

Report Producer: Natasha Hsieh

1. General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2000-1
FCC ID	IHDT56XM1
IMEI Code	**Conducted :** IMEI: 355573090013670 **Conduction :** IMEI: 355573090013654 **Radiation :** IMEI: 355573090013522
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/GNSS/NFC WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT3
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Accessory List	
AC Adapter	Brand Name : Motorola
	Model Name : SA18C45883
	Manufacturer : Salom
Battery 1	Brand Name : Motorola
	Model Name : KV40
	Manufacturer : Amperex
Battery 2	Brand Name : Motorola
	Model Name : KV30
	Manufacturer : Amperex
Headset Jack Adaptor	Brand Name : Motorola
	Model Name : SC18C45885
	Manufacturer : Luxshare
USB-C Data Cable	Brand Name : Motorola
	Model Name : SC18C45884
	Manufacturer : Luxshare
USB-C Headset 2	Brand Name : Motorola
	Model Name : SH38C48284
	Manufacturer : Grandsun

Supported Unit Used in Test Configuration and System	
USB-C Headset 1	Brand Name : Google
	Model Name : G019A
	Manufacturer : Grandsun

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency	13.56MHz
Channel Number	1
20dBW	2.66 KHz
99%OBW	2.24 KHz
Antenna Type	Internal Fixed with flex pattern Antenna
Type of Modulation	ASK

Remark: The above EUT's information was declared by manufacturer.

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978		
Test Site No.	**Sporton Site No.**		
	TH03-HY	CO05-HY	03CH07-HY
Test Engineer	George Chen	Eric Jeng	Stan Hsieh
Temperature	22~24°C	22~25°C	23~24°C
Relative Humidity	53~55%	52~55%	51~53%

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW1190

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.225
- FCC KDB 414788 D01 Radiated Test Site v01r01
- ANSI C63.10-2013

2. Test Configuration of Equipment Under Test

2.1 Descriptions of Test Mode

Investigation has been done on all the possible configurations.

The following table is a list of the test modes shown in this test report.

Test Items	
AC Power Line Conducted Emissions	Field Strength of Fundamental Emissions
20dB Spectrum Bandwidth	Frequency Stability
Radiated Emissions 9kHz~30MHz	Radiated Emissions 30MHz~1GHz

The EUT pre-scanned in three NFC type, A, B, V. The worst type (type B) was recorded in this report. Pre-scanned tests, X, Y, Z, Open Mode and Close Mode in five orthogonal panels to determine the final configuration (Y plane as worst plane) from all possible combinations.

Test Cases	
AC Conducted Emission	Mode 1: NFC Tx + Bluetooth Link + WLAN (2.4GHz) Link + USB-C Data Cable (Charging from Adapter) for Open Mode Mode 2: NFC Tx + Bluetooth Link + WLAN (2.4GHz) Link + USB-C Data Cable (Charging from Adapter) for Close Mode
Remark: 1. The worst case of conducted emission is mode 2; only the test data of it was reported. 2. All the radiation test items were performed with USB-C Headset 1.	

2.2 Connection Diagram of Test System

<AC Conducted Emissions>



<For Fundamental Emissions and Mask and Radiated Emissions Measurement>



2.3 Table for Supporting Units

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
2.	Notebook	DELL	Latitude E6320	FCC DoC/ Contains FCC ID: QDS-BRCM1054	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
3.	Bluetooth Earphone	lenovo	LBH 301	FCC DoC	N/A	N/A
4.	NFC Card	N/A	N/A	N/A	N/A	N/A

2.4 EUT Operation Test Setup

The EUT was programmed to be in continuously transmitting mode.

The ancillary equipment, NFC card, is used to make the EUT (NFC) continuously transmit at 13.56MHz and is placed around 0 cm gap to the EUT.

3. Test Results

3.1 AC Power Line Conducted Emissions Measurement

3.1.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBμV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4 Test setup



3.1.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2 20dB and 99% OBW Spectrum Bandwidth Measurement

3.2.1 Limit

Intentional radiators must be designed to ensure that the 20dB and 99% emission bandwidth in the specific band 13.56MHz.

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT in peak Max hold mode.
2. The resolution bandwidth of 1 kHz and the video bandwidth of 3 kHz were used.
3. Measured the spectrum width with power higher than 20dB below carrier.
4. Measured the 99% OBW.

3.2.4 Test Setup



3.2.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.3 Frequency Stability Measurement

3.3.1 Limit

The frequency tolerance of the carrier signal shall be maintained within +/- 0.01% (100ppm) of the operating frequency over a temperature variation of -20 degrees to +50 degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. The spectrum analyzer connected via a receive antenna placed near the EUT.
2. EUT have transmitted signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire emissions bandwidth.
4. Set RBW = 1 kHz, VBW = 3 kHz with peak detector and maxhold settings.
5. The fc is declaring of channel frequency. Then the frequency error formula is (fc-f)/fc × 10^6 ppm and the limit is less than ±100ppm.
6. Extreme temperature rule is -20°C~50°C.

3.3.4 Test Setup



3.3.5 Test Result of Conducted Test Items

Please refer to Appendix B.

3.4 Field Strength of Fundamental Emissions and Mask Measurement

3.4.1 Limit

Rules and specifications	FCC CFR 47 Part 15 section 15.225			
Description	Compliance with the spectrum mask is tested with RBW set to 9kHz.			
Freq. of Emission (MHz)	Field Strength (μV/m) at 30m	Field Strength (dBμV/m) at 30m	Field Strength (dBμV/m) at 10m	Field Strength (dBμV/m) at 3m
1.705~13.110	30	29.5	48.58	69.5
13.110~13.410	106	40.5	59.58	80.5
13.410~13.553	334	50.5	69.58	90.5
13.553~13.567	15848	84.0	103.08	124.0
13.567~13.710	334	50.5	69.58	90.5
13.710~14.010	106	40.5	59.58	80.5
14.010~30.000	30	29.5	48.58	69.5

3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the loop receiving antenna mounted antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the receiving antenna was fixed at one meter above ground to find the maximum emissions field strength.
4. For Fundamental emissions, use the receiver to measure QP reading.
5. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
6. Compliance with the spectrum mask is tested with RBW set to 9kHz.
   Note: Emission level (dBμV/m) = 20 log Emission level (μV/m).

3.4.4 Test Setup

For radiated emissions below 30MHz



3.4.5 Test Result of Field Strength of Fundamental Emissions and Mask

Please refer to Appendix C.

3.5 Radiated Emissions Measurement

3.5.1 Limit

The field strength of any emissions which appear outside of 13.110 ~14.010MHz band shall not exceed the general radiated emissions limits.

Frequencies (MHz)	Field Strength (μV/m)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Measuring Instrument Setting

The following table is the setting of receiver:

Receiver Parameter	Setting
Attenuation	Auto
Frequency Range: 9kHz~150kHz	RBW 200Hz for QP
Frequency Range: 150kHz~30MHz	RBW 9kHz for QP
Frequency Range: 30MHz~1000MHz	RBW 120kHz for Peak

Note: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz and 110-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

3.5.4 Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
7. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver.

3.5.5 Test Setup

For radiated emissions below 30MHz



For radiated emissions above 30MHz



3.5.6 Test Result of Radiated Emissions Measurement

Please refer to Appendix C.

Remark: There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.6 Antenna Requirements

3.6.1 Standard Applicable

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited.

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	AC POWER	AFC-500W	F104070011	50Hz~60Hz	Mar. 21, 2018	Feb. 19, 2019	Mar. 20, 2019	Conducted (TH03-HY)
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 06, 2018	Feb. 19, 2019	Mar. 05, 2019	Conducted (TH03-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 29, 2018	Feb. 19, 2019	Jun. 28, 2019	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30℃ ~70℃	Dec. 06, 2017	Feb. 19, 2019	Dec. 05, 2019	Conducted (TH03-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Feb. 17, 2019	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Nov. 12, 2018	Feb. 17, 2019	Nov. 11, 2019	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 06, 2018	Feb. 17, 2019	Mar. 05, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 14, 2018	Feb. 17, 2019	Nov. 13, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 09, 2018	Feb. 17, 2019	Nov. 08, 2019	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Feb. 17, 2019	N/A	Conduction (CO05-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Sep. 14, 2018	Feb. 17, 2019	Sep. 13, 2019	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Nov. 08, 2018	Feb. 17, 2019	Nov. 07, 2019	Conduction (CO05-HY)
EMI Test Receiver	Agilent	N9038A(MXE)	MY53290053	20Hz to 26.5GHz	Jan. 23, 2019	Feb. 13, 2019~ Feb. 21, 2019	Jan. 22, 2020	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1GHz	May 21, 2018	Feb. 13, 2019~ Feb. 21, 2019	May 20, 2019	Radiation (03CH07-HY)
Filter	Wainwright	WHK20/1000C7/40SS	SN3	20M High Pass	Nov. 02, 2018	Feb. 13, 2019~ Feb. 21, 2019	Nov. 01, 2019	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Feb. 13, 2019~ Feb. 21, 2019	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF780208368	Control Ant Mast	N/A	Feb. 13, 2019~ Feb. 21, 2019	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Feb. 13, 2019~ Feb. 21, 2019	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 Degree	N/A	Feb. 13, 2019~ Feb. 21, 2019	N/A	Radiation (03CH07-HY)
Software	Audix	E3 6.2009-8-24	80504004656H	N/A	N/A	Feb. 13, 2019~ Feb. 21, 2019	N/A	Radiation (03CH07-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 13, 2018	Feb. 13, 2019~ Feb. 21, 2019	Oct. 12, 2019	Radiation (03CH07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 07, 2019	Feb. 13, 2019~ Feb. 21, 2019	Jan. 06, 2020	Radiation (03CH07-HY)
Hygrometer	Testo	608-H2	41410070	N/A	Oct. 22, 2018	Feb. 13, 2019~ Feb. 21, 2019	Oct. 21, 2019	Radiation (03CH07-HY)

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.20

Uncertainty of Radiated Emission Measurement (9 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	3.40

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.70

Appendix A. Test Results of Conducted Emission Test

Test Engineer :	Eric Jeng	**Temperature :**	22~25℃
		Relative Humidity :	52~55%

EUT Information

Report NO :	912419
Test Mode :	Mode 2
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.165750	---	26.42	55.17	28.75	L1	OFF	19.5
0.165750	34.45	---	65.17	30.72	L1	OFF	19.5
0.195000	---	25.45	53.82	28.37	L1	OFF	19.5
0.195000	32.03	---	63.82	31.79	L1	OFF	19.5
0.620250	---	24.50	46.00	21.50	L1	OFF	19.6
0.620250	30.30	---	56.00	25.70	L1	OFF	19.6
2.017500	---	25.74	46.00	20.26	L1	OFF	19.6
2.017500	31.97	---	56.00	24.03	L1	OFF	19.6
8.070000	---	25.68	50.00	24.32	L1	OFF	19.8
8.070000	33.20	---	60.00	26.80	L1	OFF	19.8
13.560000	---	43.01	50.00	6.99	L1	OFF	20.0
13.560000	45.01	---	60.00	14.99	L1	OFF	20.0
16.345500	---	25.30	50.00	24.70	L1	OFF	20.1
16.345500	33.10	---	60.00	26.90	L1	OFF	20.1

EUT Information

Report NO :	912419
Test Mode :	Mode 2
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	26.70	55.40	28.70	N	OFF	19.5
0.161250	34.69	---	65.40	30.71	N	OFF	19.5
0.636000	---	24.66	46.00	21.34	N	OFF	19.6
0.636000	28.14	---	56.00	27.86	N	OFF	19.6
2.067000	---	24.80	46.00	21.20	N	OFF	19.4
2.067000	28.88	---	56.00	27.12	N	OFF	19.4
2.438250	---	24.48	46.00	21.52	N	OFF	19.6
2.438250	27.56	---	56.00	28.44	N	OFF	19.6
4.812000	---	25.12	46.00	20.88	N	OFF	19.7
4.812000	26.57	---	56.00	29.43	N	OFF	19.7
13.562250	---	40.66	50.00	9.34	N	OFF	20.1
13.562250	41.61	---	60.00	18.39	N	OFF	20.1
16.336500	---	27.01	50.00	22.99	N	OFF	20.2
16.336500	36.54	---	60.00	23.46	N	OFF	20.2

Appendix B. Test Results of Conducted Test Items

B1. Test Result of 20dB Spectrum Bandwidth

Test mode	NFC Tx	Test Frequency (MHz)	13.56
			
20dB Bandwidth (kHz)	2.660	**99% OccupiedBW(kHz)**	2.240
Frequency range (MHz)	**f_L > 13.553**	13.55858	**Test Result**
	f_H < 13.567	13.56124	**Complies**

Remark: Because the measured signal is CW adjusting the RBW per C63.10 would not be practical since measured bandwidth will always follow the RBW and the result will be approximately twice the RBW.

B2. Test Result of Frequency Stability

B3. Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
120	13.559900	**-20**	**0**	13.559890
102	13.559900		**2**	13.559900
138	13.559890		**5**	13.559900
			10	13.559880
		-10	**0**	13.559880
			2	13.559890
			5	13.559880
			10	13.559880
		0	**0**	13.559880
			2	13.559880
			5	13.559870
			10	13.559890
		10	**0**	13.559880
			2	13.559880
			5	13.559890
			10	13.559890
		20	**0**	13.559910
			2	13.559900
			5	13.559890
			10	13.559880
		30	**0**	13.559890
			2	13.559880
			5	13.559890
			10	13.559880
		40	**0**	13.559870
			2	13.559890
			5	13.559880
			10	13.559890

Voltage vs. Frequency Stability		Temperature vs. Frequency Stability		
Voltage (Vac)	Measurement Frequency (MHz)	Temperature (℃)	Time	Measurement Frequency (MHz)
		50	0	13.559880
			2	13.559880
			5	13.559880
			10	13.559880
Max.Deviation (MHz)	-0.000110	Max.Deviation (MHz)		-0.000130
Max.Deviation (ppm)	-8.1121	Max.Deviation (ppm)		-9.5870
Limit	FS < ±100 ppm	Limit		FS < ±100 ppm
Test Result	PASS	Test Result		PASS

Appendix C. Test Results of Radiated Test Items

C1. Test Result of Field Strength of Fundamental Emissions

Test Mode :	NFC Tx for Open Mode	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP-ANT(H)100488 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 912419
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	53.98	-70.02	124.00	32.53	21.02	0.43	100	0	QP



Site : 03CH07-HY
Condition : 15.225 3m LOOP-ANT(V)100488 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 912419
Mode : 1

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	51.06	-72.94	124.00	29.61	21.02	0.43	100	260	QP

Test Mode :	NFC Tx for Close Mode	Test Frequency (MHz)	13.56



Site : 03CH07-HY
Condition : 15.225 3m LOOP-ANT(H)100488 HORIZONTAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 912419
Mode : 2

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	57.07	-66.93	124.00	35.62	21.02	0.43	---	---	QP



Site : 03CH07-HY
Condition : 15.225 3m LOOP-ANT(V)100488 VERTICAL
: RBW:9.000KHz VBW:9.000KHz SWT:Auto
Project : 912419
Mode : 2

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	cm	deg	
1	13.56	54.33	-69.67	124.00	32.88	21.02	0.43	100	282	QP

C2. Results of Radiated Spurious Emissions (9 kHz~30MHz)

Test Mode :	NFC Tx for Open Mode	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.009	47.93	-80.59	128.52	27.8	19.7	0.43	-	-	Average
0.06597	47.33	-63.89	111.22	27.1	19.8	0.43	-	-	Average
0.09282	47.44	-60.81	108.25	27.41	19.6	0.43	-	-	QP
0.12656	44.11	-61.45	105.56	24.11	19.57	0.43	-	-	Average
0.15	44.17	-59.91	104.08	24.2	19.54	0.43	-	-	Average
0.49	44.82	-28.98	73.8	25.09	19.3	0.43	100	0	QP
11.768	36.83	-32.67	69.5	15.54	20.86	0.43	-	-	QP
13.56	53.98	-15.52	69.5	32.53	21.02	0.43	-	-	QP
22.075	38.43	-31.07	69.5	15.59	21.64	1.2	-	-	QP
29.695	39.33	-30.17	69.5	16.34	21.79	1.2	-	-	QP

Test Mode :	NFC Tx for Open Mode	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.01063	46.28	-80.79	127.07	26.15	19.7	0.43	-	-	Average
0.06159	44	-67.81	111.81	23.77	19.8	0.43	-	-	Average
0.09134	45.56	-62.83	108.39	25.53	19.6	0.43	-	-	QP
0.1284	45.37	-60.06	105.43	25.37	19.57	0.43	-	-	Average
0.15	42.34	-61.74	104.08	22.37	19.54	0.43	-	-	Average
0.49	42.26	-31.54	73.8	22.53	19.3	0.43	-	-	QP
8.176	49.64	-19.86	69.5	28.77	20.44	0.43	100	0	QP
13.56	51.06	-18.44	69.5	29.61	21.02	0.43	-	-	QP
23.713	39.33	-30.17	69.5	16.46	21.67	1.2	-	-	QP
29.985	39.65	-29.85	69.5	16.65	21.8	1.2	-	-	QP

Note:

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
4. Limit line = specific limits (dBµV) + distance extrapolation factor.

Test Mode :	NFC Tx for Close Mode	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.00936	46.75	-81.43	128.18	26.62	19.7	0.43	-	-	Average
0.06417	47.8	-63.66	111.46	27.57	19.8	0.43	-	-	Average
0.09538	47.22	-60.8	108.02	27.19	19.6	0.43	-	-	QP
0.11	43.46	-63.32	106.78	23.43	19.6	0.43	-	-	Average
0.15544	44.88	-58.89	103.77	24.91	19.54	0.43	-	-	Average
0.49751	44.23	-29.44	73.67	24.5	19.3	0.43	100	0	QP
11.16	37.66	-31.84	69.5	16.42	20.81	0.43	-	-	QP
13.56	57.07	-12.43	69.5	35.62	21.02	0.43	-	-	QP
22.237	38.62	-30.88	69.5	15.78	21.64	1.2	-	-	QP
29.275	39.56	-29.94	69.5	16.57	21.79	1.2	-	-	QP

Test Mode :	NFC Tx for Close Mode	Polarization :	Vertical



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
0.009	46.2	-82.32	128.52	26.07	19.7	0.43	-	-	Average
0.06093	46.18	-65.73	111.91	25.95	19.8	0.43	-	-	Average
0.09008	44.43	-64.08	108.51	24.4	19.6	0.43	-	-	QP
0.11868	42.56	-63.56	106.12	22.56	19.57	0.43	-	-	Average
0.15204	46.26	-57.71	103.97	26.29	19.54	0.43	-	-	Average
0.50502	41.91	-31.63	73.54	22.17	19.31	0.43	-	-	QP
8.096	51.51	-17.99	69.5	30.64	20.44	0.43	100	0	QP
13.56	54.33	-15.17	69.5	32.88	21.02	0.43	-	-	QP
16.765	38.58	-30.92	69.5	16.84	21.31	0.43	-	-	QP
25.385	39.46	-30.04	69.5	16.55	21.71	1.2	-	-	QP

Note:

1. 13.56 MHz is fundamental signal which can be ignored.
2. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB);
4. Limit line = specific limits (dBµV) + distance extrapolation factor.

C3. Results of Radiated Spurious Emissions (30MHz~1GHz)

Test Mode :	NFC Tx for Open Mode	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.54	23.12	-16.88	40	28.01	24.09	1.2	30.18	-	-	Peak
97.23	27.76	-15.74	43.5	40.84	15.45	1.55	30.08	-	-	Peak
216.84	29.92	-16.08	46	42.44	15.26	2.18	29.96	-	-	Peak
776.7	30.8	-15.2	46	28.07	27.96	4.18	29.41	-	-	Peak
868.4	32.18	-13.82	46	27.66	28.98	4.58	29.04	-	-	Peak
953.8	33.49	-12.51	46	26.78	30.54	4.71	28.54	100	0	Peak

Test Mode :	NFC Tx for Open Mode	Polarization :	Vertical



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
30.27	31.57	-8.43	40	35.95	24.6	1.2	30.18	-	-	Peak
35.67	32.2	-7.8	40	39.66	21.51	1.2	30.17	100	0	Peak
49.17	28.69	-11.31	40	42.98	14.66	1.2	30.15	-	-	Peak
769.7	30.87	-15.13	46	28.22	27.91	4.18	29.44	-	-	Peak
863.5	31.7	-14.3	46	27.17	29.01	4.58	29.06	-	-	Peak
957.3	33.19	-12.81	46	26.24	30.75	4.71	28.51	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.

Test Mode :	NFC Tx for Close Mode	Polarization :	Horizontal



Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
40.8	28.18	-11.82	40	38.34	18.81	1.2	30.17	-	-	Peak
54.3	26.25	-13.75	40	42.52	12.67	1.2	30.14	-	-	Peak
95.07	34.17	-9.33	43.5	47.5	15.21	1.55	30.09	100	0	Peak
762.7	30.54	-15.46	46	27.97	27.85	4.18	29.46	-	-	Peak
848.8	31.53	-14.47	46	27.48	28.73	4.45	29.13	-	-	Peak
957.3	33.67	-12.33	46	26.72	30.75	4.71	28.51	-	-	Peak

Test Mode :	NFC Tx for Close Mode	Polarization :	Vertical



Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
35.94	32.44	-7.56	40	39.9	21.51	1.2	30.17	-	-	Peak
40.8	33.65	-6.35	40	43.81	18.81	1.2	30.17	100	0	Peak
49.98	30.46	-9.54	40	45.16	14.25	1.2	30.15	-	-	Peak
773.9	30.6	-15.4	46	27.9	27.94	4.18	29.42	-	-	Peak
880.3	31.81	-14.19	46	27.33	28.89	4.58	28.99	-	-	Peak
959.4	33.71	-12.29	46	26.65	30.85	4.71	28.5	-	-	Peak

Note:

1. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
2. Emission level (dBμV/m) = 20 log Emission level (μV/m).
3. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor= Level.

———THE END———