



FCC SAR TEST REPORT

FCC ID : IHDT56XN3
Equipment : Mobile Cellular Phone
Brand Name : Motorola
Applicant : Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA
Manufacturer : Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA
Standard : FCC 47 CFR Part 2 (2.1093)
ANSI/IEEE C95.1-1992
IEEE 1528-2013

The product was received on Sep. 17, 2018 and testing was started from Sep. 19, 2018 and completed on Oct. 12, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this variant report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.



Approved by: Cona Huang / Deputy Manager

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

1. Statement of Compliance	4
2. Guidance Applied.....	4
3. Equipment Under Test (EUT) Information.....	5
3.1 General Information	5
3.2 General LTE SAR Test and Reporting Considerations	8
3.1 Proximity Sensor Triggering Test.....	10
4. RF Exposure Limits.....	14
4.1 Uncontrolled Environment.....	14
4.2 Controlled Environment.....	14
5. Specific Absorption Rate (SAR).....	15
5.1 Introduction	15
5.2 SAR Definition.....	15
6. System Description and Setup	16
6.1 E-Field Probe	17
6.2 Data Acquisition Electronics (DAE)	17
6.3 Phantom.....	18
6.4 Device Holder.....	19
7. Measurement Procedures	20
7.1 Spatial Peak SAR Evaluation.....	20
7.2 Power Reference Measurement.....	21
7.3 Area Scan	21
7.4 Zoom Scan.....	22
7.5 Volume Scan Procedures.....	22
7.6 Power Drift Monitoring.....	22
8. Test Equipment List.....	23
9. System Verification	24
9.1 Tissue Simulating Liquids.....	24
9.2 Tissue Verification	25
9.3 System Performance Check Results.....	26
10. RF Exposure Positions	28
10.1 Ear and handset reference point.....	28
10.2 Definition of the cheek position	29
10.3 Definition of the tilt position	30
10.4 Body Worn Accessory	30
10.5 Product Specific	31
10.6 Wireless Router.....	31
11. Conducted RF Output Power (Unit: dBm).....	32
12. Antenna Location	103
13. SAR Test Results	104
13.1 Head SAR	106
13.2 Hotspot SAR	109
13.3 Body Worn Accessory SAR.....	113
13.4 Product Specific SAR.....	116
13.5 Repeated SAR Measurement	118
14. Simultaneous Transmission Analysis.....	119
14.1 Head Exposure Conditions	120
14.2 Hotspot Exposure Conditions.....	121
14.3 Body-Worn Accessory Exposure Conditions	123
14.4 Product Specific Exposure Conditions	124
14.5 SPLSR Evaluation and Analysis.....	126
15. Supplemental tuner tests results.....	138
15.1 Supplemental Head SAR results.....	138
15.2 Supplemental Body SAR results	139
16. Uncertainty Assessment	140
17. References.....	140
Appendix A. Plots of System Performance Check	
Appendix B. Plots of High SAR Measurement	
Appendix C. DASY Calibration Certificate	
Appendix D. Test Setup Photos	

History of this test report

Report No.	Version	Description	Issued Date
FA890437-01	01	Initial issue of report	Oct. 24, 2018

1. Statement of Compliance

The maximum results of Specific Absorption Rate (SAR) found during testing for Motorola Mobility LLC, Mobile Cellular Phone, are as follows.

Equipment Class	Frequency Band	Highest SAR Summary				Highest Simultaneous Transmission 1g SAR (W/kg)
		Head (Separation 0mm)	Body-worn (Separation 5mm)	Hotspot (Separation 5mm)	Product Specific (Separation 0mm)	
		1g SAR (W/kg)			10g SAR (W/kg)	
Licensed	GSM850	0.40	1.42	1.42	3.32	1.59
	GSM1900	0.07	1.38	1.38	3.12	
	WCDMA II	0.11	1.40	1.40	3.07	
	WCDMA IV	0.12	1.28	1.28	3.46	
	WCDMA V	0.38	1.41	1.41	2.15	
	LTE Band 2	0.12	1.39	1.41	3.36	
	LTE Band 4	0.13	1.30	1.30	2.55	
	LTE Band 7	0.31	1.21	1.21	3.10	
	LTE Band 5 / 26	0.34	1.18	1.18		
	LTE Band 38 / 41	0.19	1.07	1.07	1.92	
DTS	2.4GHz WLAN	1.18	1.13	1.13		1.59
NII	5GHz WLAN	1.15	1.12	1.12	1.42	1.55
DSS	Bluetooth	0.17	0.16	0.16		1.59
Date of Testing:		2018/9/19 ~ 2018/10/12				

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test. This device is in compliance with Specific Absorption Rate (SAR) for general population/uncontrolled exposure limits (1.6 W/kg for Partial-Body 1g SAR, 4.0 W/kg for Product Specific 10g SAR) specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2013 and FCC KDB publications.

Reviewed by: Jason Wang

Report Producer: Wan Liu

2. Guidance Applied

The Specific Absorption Rate (SAR) testing specification, method, and procedure for this device is in accordance with the following standards:

- FCC 47 CFR Part 2 (2.1093)
- ANSI/IEEE C95.1-1992
- IEEE 1528-2013
- FCC KDB 865664 D01 SAR Measurement 100 MHz to 6 GHz v01r04
- FCC KDB 865664 D02 SAR Reporting v01r02
- FCC KDB 447498 D01 General RF Exposure Guidance v06
- FCC KDB 648474 D04 SAR Evaluation Considerations for Wireless Handsets v01r03
- FCC KDB 248227 D01 802.11 Wi-Fi SAR v02r02
- FCC KDB 941225 D01 3G SAR Procedures v03r01
- FCC KDB 941225 D05 SAR for LTE Devices v02r05
- FCC KDB 941225 D05A Rel.10 LTE SAR Test Guidance v01r02
- FCC KDB 941225 D06 Hotspot Mode SAR v02r01

3. Equipment Under Test (EUT) Information

3.1 General Information

Product Feature & Specification	
Equipment Name	Mobile Cellular Phone
Brand Name	Motorola
FCC ID	IHDT56XN3
IMEI Code	SIM1: 355575090010390 SIM2: 355575090010408
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz WCDMA Band IV: 1712.4 MHz ~ 1752.6 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2537.5 MHz ~ 2652.5 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz WLAN 5.2GHz Band: 5180 MHz ~ 5240 MHz WLAN 5.3GHz Band: 5260 MHz ~ 5320 MHz WLAN 5.5GHz Band: 5500 MHz ~ 5700 MHz WLAN 5.8GHz Band: 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM WLAN 2.4GHz : 802.11b/g/n/ac HT20/VHT20 WLAN 5GHz : 802.11a/n/ac HT20/HT40/VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE NFC:ASK
HW Version	DVT1B
SW Version	PPW29.56
GSM / (E)GPRS Transfer mode	Class B – EUT cannot support Packet Switched and Circuit Switched Network simultaneously but can automatically switch between Packet and Circuit Switched Network.
EUT Stage	Identical Prototype
Remark:	
- The device has two SIM slots and supports Dual SIM Dual Standby. The WWAN radio transmission will be enabled by either one SIM at a time (Single active). - This device WLAN 2.4GHz / 5.2GHz / 5.8GHz supports Hotspot operation and Bluetooth support tethering applications. - This device implements antenna tuning techniques for several WWAN (cellular) operating modes and frequencies for the purpose of improving antenna efficiency over a broad range of frequencies. Specifically, this technique is employed in the WCDMA and LTE modes but not supports GSM 850/1900 and LTE B7 / B38 / B41. In this report SAR was measured according to the normally required SAR configurations with the tuner active and worst tune state (auto tune) was used for SAR testing. The detail descriptions of the antenna tuner are included in the operational description and supplemental data for additional information on section15. - When operating in a call in talk position at the head, the device utilizes the At-Head power table. When operating in a body-worn condition, with proximity of the user's body at the front or back of the device, the device operates in the Body-Worn power table. If neither the At-Head or Body-Worn condition is detected, but the device is operating in WiFi Hotspot mode, the device utilizes the Hotspot power table. When operating in any other radiated condition, the device uses the Default power table. - The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device. The control logic is such that, when this front or back body-worn condition is detected and the device is	

operating in a mode where on-body operation may be expected, the conducted power is applied in the Body-Worn power table. In this condition (user's body detected at front or back face of the device), the Body-Worn power table is applied regardless whether or not the Wi-Fi hotspot mode is active.

6. Note that the Body-Worn Reduced power tables and detection schemes described above are sufficient to assure that body-worn SAR limits are met, regardless whether the Wi-Fi hotspot feature is active or not. However, because FCC has an additional specific test definition and limit for Wi-Fi hotspot mode operation, the additional Hotspot power table is applied if hand-held operation is indicated (i.e., not At-Head or Body-Worn) when the Wi-Fi hotspot feature is active. This ensures the 4 edges of the device comply with the letter of the Wi-Fi Hotspot requirement.
7. The device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna (if that antenna may require reduced power relative the Default power table in order to meet extremity SAR limits). The control logic is such that, if the Body-Worn, At-Head or WiFi Hotspot conditions are not detected, but tissue (as a finger or hand, for example) is detected near the transmitting antenna, the Handheld Reduced power table will be applied
8. Reduced power for different RF exposure conditions:
9. Head: If audio is present at the earpiece, the device will reduce output powers on the WLAN transmitter for held-to-ear and detail descriptions of the power reduction mechanism are included in the operational description.
10. Body worn: The device employs proximity sensors that detect the presence of the user's body at the front or back faces of the device, when operating in near-body condition by end user, the device will reduced maximum output powers on the GSM850, GSM1900, WCDMA B2 / B4/ B5, LTE B2 / B4 / B7 / B38 / B41 and 5GHz WLAN and detail descriptions of the power reduction mechanism are included in the operational description.
11. Hotspot: When the mobile hotspot session is turn on by end user, the device will reduced output powers on the GSM850, GSM1900, WCDMA B2 / B4 / B5 LTE B2 / B4 / B7 / B38 / B41 and 5GHz WLAN and detail descriptions of the power reduction mechanism are included in the operational description.
12. Handheld: The device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna, the device will reduced output powers on the GSM 850, WCDMA B2 / B4 and LTE B2 / B4 / B7 transmitter and detail descriptions of the power reduction mechanism are included in the operational description.

<Maximum power for each bands and exposure conditions>

TX. freq.	Default	Head		Body Worn		Hotspot		Product Specific	
	max. tune up limit (dBm)	max. tune up limit(dBm)	power reduction (dB)	max. tune up limit(dBm)	power reduction (dB)	max. tune up limit(dBm)	power reduction (dB)	max. tune up limit(dBm)	power reduction (dB)
GSM850 GSM 1 Tx slot	33.50	33.50		33.00	0.50	33.00	0.50	33.00	0.50
GSM850 GPRS 1 Tx slot	33.50	33.50		33.00	0.50	33.00	0.50	33.00	0.50
GSM850 GPRS 2 Tx slots	30.50	30.50		30.00	0.50	30.00	0.50	30.00	0.50
GSM850 GPRS 3 Tx slots	28.75	28.75		28.00	0.75	28.00	0.75	28.00	0.75
GSM850 GPRS 4 Tx slots	27.50	27.50		25.00	2.50	25.00	2.50	25.00	2.50
GSM850 EDGE 1 Tx slot	28.00	28.00		26.50	1.50	26.50	1.50	26.50	1.50
GSM850 EDGE 2 Tx slots	28.00	28.00		26.50	1.50	26.50	1.50	26.50	1.50
GSM850 EDGE 3 Tx slots	26.25	26.25		25.50	0.75	25.50	0.75	25.50	0.75
GSM850 EDGE 4 Tx slots	25.00	25.00		24.50	0.50	24.50	0.50	24.50	0.50
GSM1900 GSM 1 Tx slot	30.50	30.50		26.50	4.00	25.00	5.50	30.50	
GSM1900 GPRS 1 Tx slot	30.50	30.50		26.50	4.00	25.00	5.50	30.50	
GSM1900 GPRS 2 Tx slots	27.50	27.50		23.00	4.50	21.00	6.50	27.50	
GSM1900 GPRS 3 Tx slots	25.75	25.75		20.50	5.25	20.25	5.50	25.75	
GSM1900 GPRS 4 Tx slots	24.50	24.50		19.50	5.00	18.00	6.50	24.50	
GSM1900 EDGE 1 Tx slot	27.00	27.00		23.00	4.00	21.50	5.50	27.00	
GSM1900 EDGE 2 Tx slots	27.00	27.00		23.00	4.00	21.50	5.50	27.00	
GSM1900 EDGE 3 Tx slots	25.25	25.25		21.25	4.00	19.75	5.50	25.25	
GSM1900 EDGE 4 Tx slots	24.00	24.00		20.00	4.00	18.50	5.50	24.00	
WCDMA II	24.00	24.00		17.50	6.50	15.50	8.50	20.50	3.50
WCDMA IV	24.00	24.00		18.00	6.00	16.00	8.00	21.00	3.00
WCDMA V	25.00	25.00		24.50	0.50	24.50	0.50	25.00	
LTE B2	24.00	24.00		17.50	6.50	16.00	8.00	21.50	2.50
LTE B4	24.00	24.00		17.00	7.00	15.00	9.00	20.00	4.00
LTE B5	24.00	24.00		24.00		24.00		24.00	
LTE B7	24.00	24.00		20.50	3.50	20.50	3.50	23.00	1.00
LTE B26	24.00	24.00		24.00		24.00		24.00	
LTE B38	24.00	24.00		23.50	0.50	23.50	0.50	24.00	
LTE B41	24.00	24.00		23.50	0.50	23.50	0.50	24.00	
2.4GHz WLAN 802.11b	20.00	20.00		20.00		20.00		20.00	
2.4GHz WLAN 802.11g	18.00	18.00		18.00		18.00		18.00	
2.4GHz WLAN 802.11n-HT20	18.00	18.00		18.00		18.00		18.00	
2.4GHz WLAN 802.11ac-VHT20	18.00	18.00		18.00		18.00		18.00	
5GHz WLAN 802.11a	18.00	15.50	2.50	17.00	1.00	17.00	1.00	18.00	
5GHz WLAN 802.11n-HT20	18.00	16.00	2.00	17.00	1.00	17.00	1.00	18.00	
5GHz WLAN 802.11n-HT40	18.00	15.50	2.50	17.00	1.00	17.00	1.00	18.00	
5GHz WLAN 802.11ac-VHT20	18.00	16.00	2.00	17.00	1.00	17.00	1.00	18.00	
5GHz WLAN 802.11ac-VHT40	18.00	15.50	2.50	17.00	1.00	17.00	1.00	18.00	
5GHz WLAN 802.11ac-VHT80	17.00	17.00		16.50	0.50	16.50	0.50	17.00	
BT	13.00	13.00		13.00		13.00		13.00	

3.2 General LTE SAR Test and Reporting Considerations


Summarized necessary items addressed in KDB 941225 D05 v02r05									
FCC ID		IHDT56XN3							
Equipment Name		Mobile Cellular Phone							
Operating Frequency Range of each LTE transmission band		LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 26: 814.7 MHz ~ 848.3 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz							
Channel Bandwidth		LTE Band 02:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 04:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz, 20MHz LTE Band 05:1.4MHz, 3MHz, 5MHz, 10MHz LTE Band 07: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 26:1.4MHz, 3MHz, 5MHz, 10MHz, 15MHz LTE Band 38: 5MHz, 10MHz, 15MHz, 20MHz LTE Band 41: 5MHz, 10MHz, 15MHz, 20MHz							
uplink modulations used		QPSK / 16QAM / 64QAM							
LTE Voice / Data requirements		Voice and Data.							
LTE MPR permanently built-in by design		Table 6.2.3-1: Maximum Power Reduction (MPR) for Power Class 1, 2 and 3							
		Modulation	Channel bandwidth / Transmission bandwidth (N _{RB})						MPR (dB)
			1.4 MHz	3.0 MHz	5 MHz	10 MHz	15 MHz	20 MHz	
		QPSK	> 5	> 4	> 8	> 12	> 16	> 18	≤ 1
		16 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 1
		16 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 2
		64 QAM	≤ 5	≤ 4	≤ 8	≤ 12	≤ 16	≤ 18	≤ 2
		64 QAM	> 5	> 4	> 8	> 12	> 16	> 18	≤ 3
256 QAM		≥ 1						≤ 5	
LTE A-MPR		In the base station simulator configuration, Network Setting value is set to NS_01 to disable A-MPR during SAR testing and the LTE SAR tests was transmitting on all TTI frames (Maximum TTI)							
Spectrum plots for RB configuration		A properly configured base station simulator was used for the SAR and power measurement; therefore, spectrum plots for each RB allocation and offset configuration are not included in the SAR report.							
Power reduction applied to satisfy SAR compliance		Yes, when operating in hotspot mode that LTE B2 / B4 / B7 / B38 / B41 power reduction applied to satisfy SAR compliance.							
LTE Carrier Aggregation Combinations		Intra-Band possible combinations and the detail power measurement please referred to section 11.							
LTE Carrier Aggregation Information	Additional	This device supports maximum of 2 carriers in the downlink. Additional following LTE Release features are not supported: Relay, HetNet, Enhanced MIMO, eICI, WiFi Offloading, MDH, eMBMA, Cross-Carrier Scheduling, Enhanced SC-FDMA.							

Transmission (H, M, L) channel numbers and frequencies in each LTE band												
LTE Band 2												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	18607	1850.7	18615	1851.5	18625	1852.5	18650	1855	18675	1857.5	18700	1860
M	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880	18900	1880
H	19193	1909.3	19185	1908.5	19175	1907.5	19150	1905	19125	1902.5	19100	1900
LTE Band 4												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	19957	1710.7	19965	1711.5	19975	1712.5	20000	1715	20025	1717.5	20050	1720
M	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5	20175	1732.5
H	20393	1754.3	20385	1753.5	20375	1752.5	20350	1750	20325	1747.5	20300	1745
LTE Band 5												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20407	824.7	20415	825.5	20425	826.5	20450	829	20450	829	20450	829
M	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5	20525	836.5
H	20643	848.3	20635	847.5	20625	846.5	20600	844	20600	844	20600	844
LTE Band 7												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	20775	2502.5	20800	2505	20825	2507.5	20850	2510	20850	2510	20850	2510
M	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535	21100	2535
H	21425	2567.5	21400	2565	21375	2562.5	21350	2560	21350	2560	21350	2560
LTE Band 26												
	Bandwidth 1.4 MHz		Bandwidth 3 MHz		Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	26697	814.7	26705	815.5	26715	816.5	26740	819	26765	821.5	26765	821.5
M	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5	26865	831.5
H	27033	848.3	27025	847.5	27015	846.5	26990	844	26965	841.5	26965	841.5
LTE Band 38												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	37775	2572.5	37800	2575	37825	2577.5	37850	2580	37850	2580	37850	2580
M	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595	38000	2595
H	38225	2617.5	38200	2615	38175	2612.5	38150	2610	38150	2610	38150	2610
LTE Band 41												
	Bandwidth 5 MHz		Bandwidth 10 MHz		Bandwidth 15 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz		Bandwidth 20 MHz	
	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)	Ch. #	Freq. (MHz)
L	40065	2537.5	40090	2540	40115	2542.5	40140	2545	40140	2545	40140	2545
L	40385	2569.5	40390	2570	40395	2570.5	40400	2571	40400	2571	40400	2571
M	40705	2601.5	40690	2600	40685	2599.5	40670	2598	40670	2598	40670	2598
H	41215	2652.5	41190	2650	41165	2647.5	41140	2645	41140	2645	41140	2645

3.1 Proximity Sensor Triggering Test



<Proximity Sensor Triggering Distance>:



1. Proximity sensor triggering distance testing was performed according to the procedures outlined in KDB 616217 D04 section 6.2, and EUT moving further away from the flat phantom and EUT moving toward the flat phantom were both assessed and the tissue-equivalent medium for highest frequency (2600MHz) and lowest (835MHz) frequency was used for proximity sensor triggering testing.
2. Capacitive proximity sensors placed coincident with antenna elements at the top and bottom ends of the phone are utilized to determine when the device comes in proximity of the user's body at the front or back of the device.
3. The output power will reduce to body worn power level when top and bottom sensor pad be detected.
4. The sensors used to detect the proximity of the user's body (Body-Worn condition) at the front or back surface of the device use a detection threshold distance. The data shown in the sections below shows the distance(s).
5. The device additionally employs proximity sensors that detect the presence of tissue near the currently active transmit antenna (if that antenna may require reduced power relative the Default power table in order to meet extremity SAR limits). The control logic is such that, if the Body-Worn, At-Head or WiFi Hotspot conditions are not detected, but tissue (as a finger or hand, for example) is detected near the transmitting antenna, the Handheld Reduced power table will be applied
6. When the sensor is active, the device will reduced maximum output powers on the GSM850/1900, WCDMA B2 / B4 / B5 and LTE B2 / B4 / B7 / B38 / B41 transmitter.





Proximity Sensor Trigger Distance (mm)						
Position	Front		Back		Bottom Side	
Position	Moving towards	Moving away	Moving towards	Moving away	Moving towards	Moving away
Minimum	12	12	16	16	17	17

<Sensor triggers distance V.S Measure power>







4. RF Exposure Limits

4.1 Uncontrolled Environment

Uncontrolled Environments are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

4.2 Controlled Environment

Controlled Environments are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. The exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

Limits for Occupational/Controlled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.4	8.0	20.0

Limits for General Population/Uncontrolled Exposure (W/kg)

Whole-Body	Partial-Body	Hands, Wrists, Feet and Ankles
0.08	1.6	4.0

1. Whole-Body SAR is averaged over the entire body, partial-body SAR is averaged over any 1gram of tissue defined as a tissue volume in the shape of a cube. SAR for hands, wrists, feet and ankles is averaged over any 10 grams of tissue defined as a tissue volume in the shape of a cube.

5. Specific Absorption Rate (SAR)

5.1 Introduction

SAR is related to the rate at which energy is absorbed per unit mass in an object exposed to a radio field. The SAR distribution in a biological body is complicated and is usually carried out by experimental techniques or numerical modeling. The standard recommends limits for two tiers of groups, occupational/controlled and general population/uncontrolled, based on a person's awareness and ability to exercise control over his or her exposure. In general, occupational/controlled exposure limits are higher than the limits for general population/uncontrolled.

5.2 SAR Definition

The SAR definition is the time derivative (rate) of the incremental energy (dW) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dv) of a given density (ρ). The equation description is as below:

$$SAR = \frac{d}{dt} \left(\frac{dW}{dm} \right) = \frac{d}{dt} \left(\frac{dW}{\rho dv} \right)$$


SAR is expressed in units of Watts per kilogram (W/kg)

$$SAR = \frac{\sigma |E|^2}{\rho}$$

Where: σ is the conductivity of the tissue, ρ is the mass density of the tissue and E is the RMS electrical field strength.

6. System Description and Setup

The DASY system used for performing compliance tests consists of the following items:



- A standard high precision 6-axis robot with controller, teach pendant and software. An arm extension for accommodating the data acquisition electronics (DAE).
- An isotropic Field probe optimized and calibrated for the targeted measurement.
- A data acquisition electronics (DAE) which performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. The unit is battery powered with standard or rechargeable batteries. The signal is optically transmitted to the EOC.
- The Electro-optical converter (EOC) performs the conversion from optical to electrical signals for the digital communication to the DAE. To use optical surface detection, a special version of the EOC is required. The EOC signal is transmitted to the measurement server.
- The function of the measurement server is to perform the time critical tasks such as signal filtering, control of the robot operation and fast movement interrupts.
- The Light Beam used is for probe alignment. This improves the (absolute) accuracy of the probe positioning.
- A computer running WinXP or Win7 and the DASY5 software.
- Remote control and teach pendant as well as additional circuitry for robot safety such as warning lamps, etc.
- The phantom, the device holder and other accessories according to the targeted measurement.

6.1 E-Field Probe

The SAR measurement is conducted with the dosimetric probe (manufactured by SPEAG). The probe is specially designed and calibrated for use in liquid with high permittivity. The dosimetric probe has special calibration in liquid at different frequency. This probe has a built in optical surface detection system to prevent from collision with phantom.

<ES3DV3 Probe>

Construction	Symmetric design with triangular core Interleaved sensors Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – 4 GHz; Linearity: ± 0.2 dB (30 MHz – 4 GHz)	
Directivity	± 0.2 dB in TSL (rotation around probe axis) ± 0.3 dB in TSL (rotation normal to probe axis)	
Dynamic Range	5 μ W/g – >100 mW/g; Linearity: ± 0.2 dB	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 3.9 mm (body: 12 mm) Distance from probe tip to dipole centers: 3.0 mm	

<EX3DV4 Probe>

Construction	Symmetric design with triangular core Built-in shielding against static charges PEEK enclosure material (resistant to organic solvents, e.g., DGBE)	
Frequency	10 MHz – >6 GHz Linearity: ± 0.2 dB (30 MHz – 6 GHz)	
Directivity	± 0.3 dB in TSL (rotation around probe axis) ± 0.5 dB in TSL (rotation normal to probe axis)	
Dynamic Range	10 μ W/g – >100 mW/g Linearity: ± 0.2 dB (noise: typically <1 μ W/g)	
Dimensions	Overall length: 337 mm (tip: 20 mm) Tip diameter: 2.5 mm (body: 12 mm) Typical distance from probe tip to dipole centers: 1 mm	

6.2 Data Acquisition Electronics (DAE)

The data acquisition electronics (DAE) consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the measurement server is accomplished through an optical downlink for data and status information as well as an optical uplink for commands and the clock.

The input impedance of the DAE is 200 MOhm; the inputs are symmetrical and floating. Common mode rejection is above 80 dB.



Fig 5.1 Photo of DAE

6.3 Phantom

<SAM Twin Phantom>

Shell Thickness	2 ± 0.2 mm; Center ear point: 6 ± 0.2 mm	
Filling Volume	Approx. 25 liters	
Dimensions	Length: 1000 mm; Width: 500 mm; Height: adjustable feet	
Measurement Areas	Left Hand, Right Hand, Flat Phantom	

The bottom plate contains three pair of bolts for locking the device holder. The device holder positions are adjusted to the standard measurement positions in the three sections. A white cover is provided to tap the phantom during off-periods to prevent water evaporation and changes in the liquid parameters. On the phantom top, three reference markers are provided to identify the phantom position with respect to the robot.

<ELI Phantom>

Shell Thickness	2 ± 0.2 mm (sagging: <1%)	
Filling Volume	Approx. 30 liters	
Dimensions	Major ellipse axis: 600 mm Minor axis: 400 mm	

The ELI phantom is intended for compliance testing of handheld and body-mounted wireless devices in the frequency range of 30 MHz to 6 GHz. ELI4 is fully compatible with standard and all known tissue simulating liquids.

6.4 Device Holder

<Mounting Device for Hand-Held Transmitter>

In combination with the Twin SAM V5.0/V5.0c or ELI phantoms, the Mounting Device for Hand-Held Transmitters enables rotation of the mounted transmitter device to specified spherical coordinates. At the heads, the rotation axis is at the ear opening. Transmitter devices can be easily and accurately positioned according to IEC 62209-1, IEEE 1528, FCC, or other specifications. The device holder can be locked for positioning at different phantom sections (left head, right head, flat). And upgrade kit to Mounting Device to enable easy mounting of wider devices like big smart-phones, e-books, small tablets, etc. It holds devices with width up to 140 mm.



Mounting Device for Hand-Held Transmitters



Mounting Device Adaptor for Wide-Phones

<Mounting Device for Laptops and other Body-Worn Transmitters>

The extension is lightweight and made of POM, acrylic glass and foam. It fits easily on the upper part of the mounting device in place of the phone positioned. The extension is fully compatible with the SAM Twin and ELI phantoms.



Mounting Device for Laptops

7. Measurement Procedures

The measurement procedures are as follows:

<Conducted power measurement>

- (a) For WWAN power measurement, use base station simulator to configure EUT WWAN transmission in conducted connection with RF cable, at maximum power in each supported wireless interface and frequency band.
- (b) Read the WWAN RF power level from the base station simulator.
- (c) For WLAN/BT power measurement, use engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power in each supported wireless interface and frequency band
- (d) Connect EUT RF port through RF cable to the power meter, and measure WLAN/BT output power

<SAR measurement>

- (a) Use base station simulator to configure EUT WWAN transmission in radiated connection, and engineering software to configure EUT WLAN/BT continuously transmission, at maximum RF power, in the highest power channel.
- (b) Place the EUT in the positions as Appendix D demonstrates.
- (c) Set scan area, grid size and other setting on the DASY software.
- (d) Measure SAR results for the highest power channel on each testing position.
- (e) Find out the largest SAR result on these testing positions of each band
- (f) Measure SAR results for other channels in worst SAR testing position if the reported SAR of highest power channel is larger than 0.8 W/kg

According to the test standard, the recommended procedure for assessing the peak spatial-average SAR value consists of the following steps:

- (a) Power reference measurement
- (b) Area scan
- (c) Zoom scan
- (d) Power drift measurement

7.1 Spatial Peak SAR Evaluation

The procedure for spatial peak SAR evaluation has been implemented according to the test standard. It can be conducted for 1g and 10g, as well as for user-specific masses. The DASY software includes all numerical procedures necessary to evaluate the spatial peak SAR value.

The base for the evaluation is a "cube" measurement. The measured volume must include the 1g and 10g cubes with the highest averaged SAR values. For that purpose, the center of the measured volume is aligned to the interpolated peak SAR value of a previously performed area scan.

The entire evaluation of the spatial peak values is performed within the post-processing engine (SEMCAD). The system always gives the maximum values for the 1g and 10g cubes. The algorithm to find the cube with highest averaged SAR is divided into the following stages:

- (a) Extraction of the measured data (grid and values) from the Zoom Scan
- (b) Calculation of the SAR value at every measurement point based on all stored data (A/D values and measurement parameters)
- (c) Generation of a high-resolution mesh within the measured volume
- (d) Interpolation of all measured values from the measurement grid to the high-resolution grid
- (e) Extrapolation of the entire 3-D field distribution to the phantom surface over the distance from sensor to surface
- (f) Calculation of the averaged SAR within masses of 1g and 10g

7.2 Power Reference Measurement

The Power Reference Measurement and Power Drift Measurements are for monitoring the power drift of the device under test in the batch process. The minimum distance of probe sensors to surface determines the closest measurement point to phantom surface. This distance cannot be smaller than the distance of sensor calibration points to probe tip as defined in the probe properties.

7.3 Area Scan

The area scan is used as a fast scan in two dimensions to find the area of high field values, before doing a fine measurement around the hot spot. The sophisticated interpolation routines implemented in DASY software can find the maximum found in the scanned area, within a range of the global maximum. The range (in dB0) is specified in the standards for compliance testing. For example, a 2 dB range is required in IEEE standard 1528 and IEC 62209 standards, whereby 3 dB is a requirement when compliance is assessed in accordance with the ARIB standard (Japan), if only one zoom scan follows the area scan, then only the absolute maximum will be taken as reference. For cases where multiple maximums are detected, the number of zoom scans has to be increased accordingly.

Area scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

	≤ 3 GHz	> 3 GHz
Maximum distance from closest measurement point (geometric center of probe sensors) to phantom surface	5 ± 1 mm	$\frac{1}{2} \cdot \delta \cdot \ln(2) \pm 0.5$ mm
Maximum probe angle from probe axis to phantom surface normal at the measurement location	$30^\circ \pm 1^\circ$	$20^\circ \pm 1^\circ$
Maximum area scan spatial resolution: Δx_{Area} , Δy_{Area}	≤ 2 GHz: ≤ 15 mm $2 - 3$ GHz: ≤ 12 mm	$3 - 4$ GHz: ≤ 12 mm $4 - 6$ GHz: ≤ 10 mm
	When the x or y dimension of the test device, in the measurement plane orientation, is smaller than the above, the measurement resolution must be $\leq$ the corresponding x or y dimension of the test device with at least one measurement point on the test device.	

7.4 Zoom Scan

Zoom scans are used to assess the peak spatial SAR values within a cubic averaging volume containing 1 gram and 10 gram of simulated tissue. The zoom scan measures points (refer to table below) within a cube whose base faces are centered on the maxima found in a preceding area scan job within the same procedure. When the measurement is done, the zoom scan evaluates the averaged SAR for 1 gram and 10 gram and displays these values next to the job's label.

Zoom scan parameters extracted from FCC KDB 865664 D01v01r04 SAR measurement 100 MHz to 6 GHz.

			≤ 3 GHz	> 3 GHz
Maximum zoom scan spatial resolution: $\Delta x_{\text{Zoom}}, \Delta y_{\text{Zoom}}$			≤ 2 GHz: ≤ 8 mm 2 – 3 GHz: ≤ 5 mm*	3 – 4 GHz: ≤ 5 mm* 4 – 6 GHz: ≤ 4 mm*
Maximum zoom scan spatial resolution, normal to phantom surface	uniform grid: $\Delta z_{\text{Zoom}}(n)$		≤ 5 mm	3 – 4 GHz: ≤ 4 mm 4 – 5 GHz: ≤ 3 mm 5 – 6 GHz: ≤ 2 mm
	graded grid	$\Delta z_{\text{Zoom}}(1)$: between 1 st two points closest to phantom surface	≤ 4 mm	3 – 4 GHz: ≤ 3 mm 4 – 5 GHz: ≤ 2.5 mm 5 – 6 GHz: ≤ 2 mm
		$\Delta z_{\text{Zoom}}(n>1)$: between subsequent points	$\leq 1.5 \cdot \Delta z_{\text{Zoom}}(n-1)$	
Minimum zoom scan volume	x, y, z		≥ 30 mm	3 – 4 GHz: ≥ 28 mm 4 – 5 GHz: ≥ 25 mm 5 – 6 GHz: ≥ 22 mm
Note: δ is the penetration depth of a plane-wave at normal incidence to the tissue medium; see draft standard IEEE P1528-2011 for details.				
* When zoom scan is required and the <i>reported</i> SAR from the <i>area scan based 1-g SAR estimation</i> procedures of KDB 447498 is ≤ 1.4 W/kg, ≤ 8 mm, ≤ 7 mm and ≤ 5 mm zoom scan resolution may be applied, respectively, for 2 GHz to 3 GHz, 3 GHz to 4 GHz and 4 GHz to 6 GHz.				

7.5 Volume Scan Procedures

The volume scan is used to assess overlapping SAR distributions for antennas transmitting in different frequency bands. It is equivalent to an oversized zoom scan used in standalone measurements. The measurement volume will be used to enclose all the simultaneous transmitting antennas. For antennas transmitting simultaneously in different frequency bands, the volume scan is measured separately in each frequency band. In order to sum correctly to compute the 1g aggregate SAR, the EUT remain in the same test position for all measurements and all volume scan use the same spatial resolution and grid spacing. When all volume scan were completed, the software, SEMCAD postprocessor can combine and subsequently superpose these measurement data to calculating the multiband SAR.

7.6 Power Drift Monitoring

All SAR testing is under the EUT install full charged battery and transmit maximum output power. In DASy measurement software, the power reference measurement and power drift measurement procedures are used for monitoring the power drift of EUT during SAR test. Both these procedures measure the field at a specified reference position before and after the SAR testing. The software will calculate the field difference in dB. If the power drifts more than 5%, the SAR will be retested.

8. Test Equipment List

Manufacturer	Name of Equipment	Type/Model	Serial Number	Calibration	
				Last Cal.	Due Date
SPEAG	835MHz System Validation Kit	D835V2	4d167	Feb. 27, 2018	Feb. 26, 2019
SPEAG	1750MHz System Validation Kit	D1750V2	1068	Nov. 15, 2017	Nov. 14, 2018
SPEAG	1900MHz System Validation Kit	D1900V2	5d185	Feb. 28, 2018	Feb. 27, 2019
SPEAG	2450MHz System Validation Kit	D2450V2	736	Aug. 31, 2018	Sep. 30, 2019
SPEAG	2600MHz System Validation Kit	D2600V2	1078	Mar. 01, 2018	Feb. 28, 2019
SPEAG	5GHz System Validation Kit	D5GHzV2	1040	Jun. 28, 2018	Jun. 27, 2019
SPEAG	5GHz System Validation Kit	D5GHzV2	1203	Dec. 14, 2017	Dec. 13, 2018
SPEAG	Data Acquisition Electronics	DAE4	1424	Jan. 18, 2018	Jan. 17, 2019
SPEAG	Data Acquisition Electronics	DAE3	495	May. 24, 2018	May. 23, 2019
SPEAG	Data Acquisition Electronics	DAE4	1399	Nov. 16, 2017	Nov. 15, 2018
SPEAG	Data Acquisition Electronics	DAE3	577	Sep. 19, 2018	Sep. 18, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	3976	Jan. 23, 2018	Jan. 22, 2019
SPEAG	Dosimetric E-Field Probe	ES3DV3	3169	May. 28, 2018	May. 27, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	7306	Jul. 26, 2018	Jul. 25, 2019
SPEAG	Dosimetric E-Field Probe	EX3DV4	7375	Dec. 18, 2017	Dec. 17, 2018
RCPTWN	Thermometer	HTC-1	TM685-1	Mar. 16, 2018	Mar. 15, 2019
RCPTWN	Thermometer	HTC-1	TM281-1	Mar. 16, 2018	Mar. 15, 2019
RCPTWN	Thermometer	HTC-1	TM560-1	Mar. 16, 2018	Mar. 15, 2019
Gencom	Thermometer	TE1	TM225-1	Mar. 16, 2018	Mar. 15, 2019
Anritsu	Radio Communication Analyzer	MT8821C	6201341950	Apr. 17, 2018	Apr. 16, 2019
Agilent	Wireless Communication Test Set	E5515C	MY50266977	May. 21, 2018	May. 20, 2019
R&S	BT Base Station	CBT	100815	Feb. 05, 2018	Feb. 04, 2019
SPEAG	Device Holder	N/A	N/A	N/A	N/A
Anritsu	Signal Generator	MG3710A	6201502524	Dec. 07, 2017	Dec. 06, 2018
Agilent	ENA Network Analyzer	E5071C	MY46316648	Jan. 17, 2018	Jan. 16, 2019
SPEAG	Dielectric Probe Kit	DAK-3.5	1146	Jul. 24, 2018	Jul. 23, 2019
LINE SEIKI	Digital Thermometer	DTM3000-spezial	2942	Dec. 08, 2017	Dec. 07, 2018
Anritsu	Power Meter	ML2495A	1419002	May. 18, 2018	May. 17, 2019
Anritsu	Power Sensor	MA2411B	1339124	May. 18, 2018	May. 17, 2019
Anritsu	Power Meter	ML2495A	1240001	Sep. 13, 2018	Sep. 12, 2019
Anritsu	Power Sensor	MA2411B	1207349	Sep. 13, 2018	Sep. 12, 2019
Agilent	Spectrum Analyzer	E4408B	MY44211028	Aug. 28, 2018	Aug. 27, 2019
Anritsu	Spectrum Analyzer	MS2830A	6201396378	Jun. 23, 2018	Jun. 22, 2019
Mini-Circuits	Power Amplifier	ZVE-8G+	6382	Aug. 09, 2018	Aug. 08, 2019
Mini-Circuits	Power Amplifier	ZHL-42W+	15542	Aug. 09, 2018	Aug. 08, 2019
ATM	Dual Directional Coupler	C122H-10	P610410z-02	Note 1	
Woken	Attenuator 1	WK0602-XX	N/A	Note 1	
PE	Attenuator 2	PE7005-10	N/A	Note 1	
PE	Attenuator 3	PE7005- 3	N/A	Note 1	

General Note:

- Prior to system verification and validation, the path loss from the signal generator to the system check source and the power meter, which includes the amplifier, cable, attenuator and directional coupler, was measured by the network analyzer. The reading of the power meter was offset by the path loss difference between the path to the power meter and the path to the system check source to monitor the actual power level fed to the system check source.

9. System Verification

9.1 Tissue Simulating Liquids

For the measurement of the field distribution inside the SAM phantom with DASY, the phantom must be filled with around 25 liters of homogeneous body tissue simulating liquid. For head SAR testing, the liquid height from the ear reference point (ERP) of the phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.1. For body SAR testing, the liquid height from the center of the flat phantom to the liquid top surface is larger than 15 cm, which is shown in Fig. 10.2.




Fig 10.1 Photo of Liquid Height for Head SAR



Fig 10.2 Photo of Liquid Height for Body SAR

9.2 Tissue Verification

The following tissue formulations are provided for reference only as some of the parameters have not been thoroughly verified. The composition of ingredients may be modified accordingly to achieve the desired target tissue parameters required for routine SAR evaluation.

Frequency (MHz)	Water (%)	Sugar (%)	Cellulose (%)	Salt (%)	Preventol (%)	DGBE (%)	Conductivity (σ)	Permittivity (ϵ_r)
For Head								
750	41.1	57.0	0.2	1.4	0.2	0	0.89	41.9
835	40.3	57.9	0.2	1.4	0.2	0	0.90	41.5
900	40.3	57.9	0.2	1.4	0.2	0	0.97	41.5
1800, 1900, 2000	55.2	0	0	0.3	0	44.5	1.40	40.0
2450	55.0	0	0	0	0	45.0	1.80	39.2
2600	54.8	0	0	0.1	0	45.1	1.96	39.0
For Body								
750	51.7	47.2	0	0.9	0.1	0	0.96	55.5
835	50.8	48.2	0	0.9	0.1	0	0.97	55.2
900	50.8	48.2	0	0.9	0.1	0	1.05	55.0
1800, 1900, 2000	70.2	0	0	0.4	0	29.4	1.52	53.3
2450	68.6	0	0	0	0	31.4	1.95	52.7
2600	68.1	0	0	0.1	0	31.8	2.16	52.5

Simulating Liquid for 5GHz, Manufactured by SPEAG

Ingredients	(% by weight)
Water	64~78%
Mineral oil	11~18%
Emulsifiers	9~15%
Additives and Salt	2~3%

<Tissue Dielectric Parameter Check Results>

Frequency (MHz)	Tissue Type	Liquid Temp. (°C)	Conductivity (σ)	Permittivity (ϵ_r)	Conductivity Target (σ)	Permittivity Target (ϵ_r)	Delta (σ) (%)	Delta (ϵ_r) (%)	Limit (%)	Date
835	HSL	22.6	0.896	41.879	0.90	41.50	-0.44	0.91	±5	2018/9/21
835	HSL	22.5	0.873	41.092	0.90	41.50	-3.00	-0.98	±5	2018/10/8
835	MSL	22.7	0.982	55.748	0.97	55.20	1.24	0.99	±5	2018/9/21
835	MSL	22.5	0.983	57.093	0.97	55.20	1.34	3.43	±5	2018/10/5
1750	HSL	22.4	1.410	40.018	1.37	40.10	2.92	-0.20	±5	2018/9/19
1750	MSL	22.6	1.454	55.160	1.49	53.40	-2.42	3.30	±5	2018/10/3
1750	MSL	22.3	1.463	55.350	1.49	53.40	-1.81	3.65	±5	2018/10/4
1900	HSL	22.6	1.452	39.397	1.40	40.00	3.71	-1.51	±5	2018/9/20
1900	MSL	22.6	1.556	55.543	1.52	53.30	2.37	4.21	±5	2018/10/3
1900	MSL	22.3	1.551	51.650	1.52	53.30	2.04	-3.10	±5	2018/10/4
2450	HSL	22.8	1.784	40.649	1.80	39.20	-0.89	3.70	±5	2018/10/12
2450	MSL	22.6	1.988	54.052	1.95	52.70	1.95	2.57	±5	2018/10/11
2600	HSL	22.5	1.964	38.996	1.96	39.00	0.20	-0.01	±5	2018/9/20
2600	MSL	22.6	2.201	51.811	2.16	52.50	1.90	-1.31	±5	2018/10/5
2600	MSL	22.8	2.183	51.688	2.16	52.50	1.06	-1.55	±5	2018/10/8
2600	MSL	22.6	2.188	53.515	2.16	52.50	1.30	1.93	±5	2018/10/11
5250	MSL	22.6	5.440	46.883	5.36	48.95	1.49	-4.22	±5	2018/10/11
5300	HSL	22.2	4.865	36.161	4.76	35.90	2.21	0.73	±5	2018/10/12
5600	HSL	22.2	5.169	35.734	5.07	35.50	1.95	0.66	±5	2018/10/12
5600	MSL	22.6	5.892	46.262	5.77	48.50	2.11	-4.61	±5	2018/10/11
5750	MSL	22.6	6.098	46.020	5.94	48.28	2.66	-4.68	±5	2018/10/11
5800	HSL	22.2	5.383	35.473	5.27	35.30	2.14	0.49	±5	2018/10/12

9.3 System Performance Check Results

Comparing to the original SAR value provided by SPEAG, the verification data should be within its specification of 10 %. Below table shows the target SAR and measured SAR after normalized to 1W input power. The table below indicates the system performance check can meet the variation criterion and the plots can be referred to Appendix A of this report.

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 1g SAR (W/kg)	Targeted 1g SAR (W/kg)	Normalized 1g SAR (W/kg)	Deviation (%)
2018/9/21	835	HSL	250	D835V2-4d167	ES3DV3 - SN3169	DAE3 Sn495	2.31	9.26	9.24	-0.22
2018/10/8	835	HSL	250	D835V2-4d167	EX3DV4 - SN7306	DAE4 Sn1399	2.38	9.26	9.52	2.81
2018/9/21	835	MSL	250	D835V2-4d167	EX3DV4 - SN3976	DAE4 Sn1424	2.54	9.62	10.16	5.61
2018/10/5	835	MSL	250	D835V2-4d167	EX3DV4 - SN7306	DAE4 Sn1399	2.58	9.62	10.32	7.28
2018/9/19	1750	HSL	250	D1750V2-1068	ES3DV3 - SN3169	DAE3 Sn495	9.00	36.70	36	-1.91
2018/10/3	1750	MSL	250	D1750V2-1068	EX3DV4 - SN7306	DAE4 Sn1399	9.24	37.20	36.96	-0.65
2018/10/4	1750	MSL	250	D1750V2-1068	EX3DV4 - SN7306	DAE4 Sn1399	9.30	37.20	37.2	0.00
2018/9/20	1900	HSL	250	D1900V4-5d185	ES3DV3 - SN3169	DAE3 Sn495	10.10	39.30	40.4	2.80
2018/10/3	1900	MSL	250	D1900V4-5d185	EX3DV4 - SN7306	DAE4 Sn1399	10.70	39.90	42.8	7.27
2018/10/4	1900	MSL	250	D1900V4-5d185	EX3DV4 - SN7306	DAE4 Sn1399	10.30	39.90	41.2	3.26
2018/10/12	2450	HSL	250	D2450V2-736	EX3DV4 - SN7306	DAE3 Sn577	12.60	52.70	50.4	-4.36
2018/10/11	2450	MSL	250	D2450V2-736	EX3DV4 - SN7306	DAE4 Sn1399	13.90	51.50	55.6	7.96
2018/9/20	2600	HSL	250	D2600V2-1078	ES3DV3 - SN3169	DAE3 Sn495	13.30	56.50	53.2	-5.84
2018/10/5	2600	MSL	250	D2600V2-1078	EX3DV4 - SN7306	DAE4 Sn1399	13.90	54.10	55.6	2.77
2018/10/8	2600	MSL	250	D2600V2-1078	EX3DV4 - SN7306	DAE4 Sn1399	13.80	54.10	55.2	2.03
2018/10/11	2600	MSL	250	D2600V2-1078	EX3DV4 - SN7306	DAE4 Sn1399	13.80	54.10	55.2	2.03
2018/10/11	5250	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	7.94	77.50	79.4	2.45
2018/10/12	5250	HSL	100	D5GHzV2-1040	EX3DV4 - SN7375	DAE3 Sn577	8.23	82.20	82.3	0.12
2018/10/12	5600	HSL	100	D5GHzV2-1040	EX3DV4 - SN7375	DAE3 Sn577	8.36	85.30	83.6	-1.99
2018/10/11	5600	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	8.56	79.30	85.6	7.94
2018/10/11	5750	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	7.79	76.80	77.9	1.43
2018/10/12	5750	HSL	100	D5GHzV2-1040	EX3DV4 - SN7375	DAE3 Sn577	8.18	80.60	81.8	1.49

Date	Frequency (MHz)	Tissue Type	Input Power (mW)	Dipole S/N	Probe S/N	DAE S/N	Measured 10g SAR (W/kg)	Targeted 10g SAR (W/kg)	Normalized 10g SAR (W/kg)	Deviation (%)
2018/10/5	835	MSL	250	D835V2-4d167	EX3DV4 - SN7306	DAE4 Sn1399	1.70	6.27	6.8	8.45
2018/10/4	1750	MSL	250	D1750V2-1068	EX3DV4 - SN7306	DAE4 Sn1399	5.03	19.70	20.12	2.13
2018/10/4	1900	MSL	250	D1900V4-5d185	EX3DV4 - SN7306	DAE4 Sn1399	5.37	20.80	21.48	3.27
2018/10/8	2600	MSL	250	D2600V2-1078	EX3DV4 - SN7306	DAE4 Sn1399	6.16	24.10	24.64	2.24
2018/10/11	2600	MSL	250	D2600V2-1078	EX3DV4 - SN7306	DAE4 Sn1399	6.18	24.10	24.72	2.57
2018/10/11	5250	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	2.24	21.50	22.4	4.19
2018/10/11	5600	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	2.39	22.10	23.9	8.14
2018/10/11	5750	MSL	100	D5GHzV2-1203	EX3DV4 - SN7306	DAE4 Sn1399	2.19	21.30	21.9	2.82




Fig 8.3.1 System Performance Check Setup



Fig 8.3.2 Setup Photo

10. RF Exposure Positions

10.1 Ear and handset reference point

Figure 9.1.1 shows the front, back, and side views of the SAM phantom. The center-of-mouth reference point is labeled "M," the left ear reference point (ERP) is marked "LE," and the right ERP is marked "RE." Each ERP is 15 mm along the B-M (back-mouth) line behind the entrance-to-ear-canal (EEC) point, as shown in Figure 9.1.2. The Reference Plane is defined as passing through the two ear reference points and point M. The line N-F (neck-front), also called the reference pivoting line, is normal to the Reference Plane and perpendicular to both a line passing through RE and LE and the B-M line (see Figure 9.1.3). Both N-F and B-M lines should be marked on the exterior of the phantom shell to facilitate handset positioning. Posterior to the N-F line the ear shape is a flat surface with 6 mm thickness at each ERP, and forward of the N-F line the ear is truncated, as illustrated in Figure 9.1.2. The ear truncation is introduced to preclude the ear lobe from interfering with handset tilt, which could lead to unstable positioning at the cheek.




Fig 9.1.1 Front, back, and side views of SAM twin phantom




Fig 9.1.2 Close-up side view of phantom showing the ear region.




Fig 9.1.3 Side view of the phantom showing relevant markings and seven cross-sectional plane locations

10.2 Definition of the cheek position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. Define two imaginary lines on the handset—the vertical centerline and the horizontal line. The vertical centerline passes through two points on the front side of the handset—the midpoint of the width w_t of the handset at the level of the acoustic output (point A in Figure 9.2.1 and Figure 9.2.2), and the midpoint of the width w_b of the bottom of the handset (point B). The horizontal line is perpendicular to the vertical centerline and passes through the center of the acoustic output (see Figure 9.2.1). The two lines intersect at point A. Note that for many handsets, point A coincides with the center of the acoustic output; however, the acoustic output may be located elsewhere on the horizontal line. Also note that the vertical centerline is not necessarily parallel to the front face of the handset (see Figure 9.2.2), especially for clamshell handsets, handsets with flip covers, and other irregularly-shaped handsets.
3. Position the handset close to the surface of the phantom such that point A is on the (virtual) extension of the line passing through points RE and LE on the phantom (see Figure 9.2.3), such that the plane defined by the vertical centerline and the horizontal line of the handset is approximately parallel to the sagittal plane of the phantom.
4. Translate the handset towards the phantom along the line passing through RE and LE until handset point A touches the pinna at the ERP.
5. While maintaining the handset in this plane, rotate it around the LE-RE line until the vertical centerline is in the plane normal to the plane containing B-M and N-F lines, i.e., the Reference Plane.
6. Rotate the handset around the vertical centerline until the handset (horizontal line) is parallel to the N-F line.
7. While maintaining the vertical centerline in the Reference Plane, keeping point A on the line passing through RE and LE, and maintaining the handset contact with the pinna, rotate the handset about the N-F line until any point on the handset is in contact with a phantom point below the pinna on the cheek. See Figure 9.2.3. The actual rotation angles should be documented in the test report.




Fig 9.2.1 Handset vertical and horizontal reference lines—"fixed case"




Fig 9.2.2 Handset vertical and horizontal reference lines—"clam-shell case"




Fig 9.2.3 cheek or touch position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which establish the Reference Plane for handset positioning, are indicated.

10.3 Definition of the tilt position

1. Ready the handset for talk operation, if necessary. For example, for handsets with a cover piece (flip cover), open the cover. If the handset can transmit with the cover closed, both configurations must be tested.
2. While maintaining the orientation of the handset, move the handset away from the pinna along the line passing through RE and LE far enough to allow a rotation of the handset away from the cheek by 15°.
3. Rotate the handset around the horizontal line by 15°.
4. While maintaining the orientation of the handset, move the handset towards the phantom on the line passing through RE and LE until any part of the handset touches the ear. The tilt position is obtained when the contact point is on the pinna. See Figure 9.3.1. If contact occurs at any location other than the pinna, e.g., the antenna at the back of the phantom head, the angle of the handset should be reduced. In this case, the tilt position is obtained if any point on the handset is in contact with the pinna and a second point




Fig 9.3.1 Tilt position. The reference points for the right ear (RE), left ear (LE), and mouth (M), which define the Reference Plane for handset positioning, are indicated.

10.4 Body Worn Accessory

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9.4). Per KDB648474 D04v01r03, body-worn accessory exposure is typically related to voice mode operations when handsets are carried in body-worn accessories. The body-worn accessory procedures in FCC KDB 447498 D01v06 should be used to test for body-worn accessory SAR compliance, without a headset connected to it. This enables the test results for such configuration to be compatible with that required for hotspot mode when the body-worn accessory test separation distance is greater than or equal to that required for hotspot mode, when applicable. When the reported SAR for body-worn accessory, measured without a headset connected to the handset is $> 1.2 \text{ W/kg}$, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a handset attached to the handset.

Accessories for body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are test with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.




Fig 9.4 Body Worn Position

10.5 Product Specific

For smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm that provide similar mobile web access and multimedia support found in mini-tablets or UMPC mini-tablets that support voice calls next to the ear, According to KDB648474 D04v01r03, the following phablet procedures should be applied to evaluate SAR compliance for each applicable wireless modes and frequency band. Devices marketed as phablets, regardless of form factors and operating characteristics must be tested as a phablet to determine SAR compliance

1. The normally required head and body-worn accessory SAR test procedures for handsets, including hotspot mode, must be applied.
2. The UMPC mini-tablet procedures must also be applied to test the SAR of all surfaces and edges with an antenna located at ≤ 25 mm from that surface or edge, in direct contact with a flat phantom, for 10-g extremity SAR according to the body-equivalent tissue dielectric parameters in KDB 865664 to address interactive hand use exposure conditions.⁶ The UMPC mini-tablet 1-g SAR at 5 mm is not required. When hotspot mode applies, 10-g extremity SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg.

10.6 Wireless Router

Some battery-operated handsets have the capability to transmit and receive user through simultaneous transmission of WIFI simultaneously with a separate licensed transmitter. The FCC has provided guidance in FCC KDB Publication 941225 D06 v02r01 where SAR test considerations for handsets ($L \times W \geq 9$ cm x 5 cm) are based on a composite test separation distance of 10mm from the front, back and edges of the device containing transmitting antennas within 2.5cm of their edges, determined from general mixed use conditions for this type of devices. Since the hotspot SAR results may overlap with the body-worn accessory SAR requirements, the more conservative configurations can be considered, thus excluding some body-worn accessory SAR tests.

When the user enables the personal wireless router functions for the handset, actual operations include simultaneous transmission of both the WIFI transmitter and another licensed transmitter. Both transmitters often do not transmit at the same transmitting frequency and thus cannot be evaluated for SAR under actual use conditions due to the limitations of the SAR assessment probes. Therefore, SAR must be evaluated for each frequency transmission and mode separately and spatially summed with the WIFI transmitter according to FCC KDB Publication 447498 D01v06 publication procedures. The "Portable Hotspot" feature on the handset was NOT activated during SAR assessments, to ensure the SAR measurements were evaluated for a single transmission frequency RF signal at a time.

11. Conducted RF Output Power (Unit: dBm)

<GSM Conducted Power>

General Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. For Head SAR Test, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode. For Hotspot, Body-worn, Product Specific SAR Test, the GPRS (2Tx slots) for GSM850 and GPRS (1Tx slots) for GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode
3. Power reduction which is triggered by hotspot mode is implemented in GSM1900 band, for hotspot mode SAR testing EUT was set in reduced power mode and GPRS 1 Tx slot due to its highest frame-average power.

<Default Power Mode>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	31.74	32.42	33.01	33.50	22.74	23.42	24.01	24.50
GPRS 1 Tx slot	31.79	32.50	33.05	33.50	22.79	23.50	24.05	24.50
GPRS 2 Tx slots	28.50	28.92	29.40	30.50	22.50	22.82	23.30	24.50
GPRS 3 Tx slots	26.75	26.75	27.08	28.75	22.49	22.49	22.82	24.49
GPRS 4 Tx slots	25.50	25.55	25.60	27.50	22.50	22.55	22.60	24.50
EDGE 1 Tx slot	26.13	26.10	26.05	28.00	17.13	17.10	17.05	19.00
EDGE 2 Tx slots	26.18	26.02	26.05	28.00	20.18	20.02	20.05	22.00
EDGE 3 Tx slots	24.74	24.58	24.50	26.25	20.48	20.32	20.24	21.99
EDGE 4 Tx slots	23.22	23.11	23.08	25.00	20.22	20.11	20.08	22.00

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot	30.34	30.28	30.15	30.50	21.34	21.28	21.15	21.50
GPRS 1 Tx slot	30.35	30.30	30.17	30.50	21.35	21.30	21.17	21.50
GPRS 2 Tx slots	26.85	26.61	26.38	27.50	20.85	20.61	20.38	21.50
GPRS 3 Tx slots	24.73	24.45	24.18	25.75	20.47	20.19	19.92	21.49
GPRS 4 Tx slots	23.36	23.06	22.77	24.50	20.36	20.06	19.77	21.50
EDGE 1 Tx slot	25.51	25.54	25.40	27.00	16.51	16.54	16.40	18.00
EDGE 2 Tx slots	25.87	25.73	25.58	27.00	19.87	19.73	19.58	21.00
EDGE 3 Tx slots	24.43	24.13	24.00	25.25	20.17	19.87	19.74	20.99
EDGE 4 Tx slots	22.96	22.77	22.70	24.00	19.96	19.77	19.70	21.00

<Near-body Power Mode>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	32.48	32.41	32.14	33.00	23.48	23.41	23.14	24.00
GPRS 1 Tx slot	32.66	32.35	32.19	33.00	23.66	23.35	23.19	24.00
GPRS 2 Tx slots	28.50	28.92	29.40	30.00	22.50	22.92	23.40	24.00
GPRS 3 Tx slots	26.56	26.20	26.33	28.00	22.30	21.94	22.07	23.74
GPRS 4 Tx slots	24.39	24.42	24.36	25.00	21.39	21.42	21.36	22.00
EDGE 1 Tx slot	25.10	25.03	25.23	26.50	16.10	16.03	16.23	17.50
EDGE 2 Tx slots	24.98	24.93	24.78	26.50	18.98	18.93	18.78	20.50
EDGE 3 Tx slots	23.98	24.02	24.09	25.50	19.72	19.76	19.83	21.24
EDGE 4 Tx slots	22.74	23.04	22.94	24.50	19.74	20.04	19.94	21.50

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot	26.42	26.29	26.29	26.50	17.42	17.29	17.29	17.50
GPRS 1 Tx slot	26.44	26.38	26.27	26.50	17.44	17.38	17.27	17.50
GPRS 2 Tx slots	21.99	22.14	21.95	23.00	15.99	16.14	15.95	17.00
GPRS 3 Tx slots	19.77	19.67	19.72	20.50	15.51	15.41	15.46	16.24
GPRS 4 Tx slots	18.76	18.79	18.71	19.50	15.76	15.79	15.71	16.50
EDGE 1 Tx slot	22.69	22.69	22.69	23.00	13.69	13.69	13.69	14.00
EDGE 2 Tx slots	22.69	22.63	22.46	23.00	16.69	16.63	16.46	17.00
EDGE 3 Tx slots	20.72	20.32	20.44	21.25	16.46	16.06	16.18	16.99
EDGE 4 Tx slots	19.32	19.43	19.23	20.00	16.32	16.43	16.23	17.00

<Hotspot Power Mode>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	32.46	32.16	32.21	33.00	23.46	23.16	23.21	24.00
GPRS 1 Tx slot	32.39	32.38	32.19	33.00	23.39	23.38	23.19	24.00
GPRS 2 Tx slots	28.50	28.92	29.40	30.00	22.50	22.92	23.40	24.00
GPRS 3 Tx slots	26.49	26.44	26.30	28.00	22.23	22.18	22.04	23.74
GPRS 4 Tx slots	24.36	24.46	24.34	25.00	21.36	21.46	21.34	22.00
EDGE 1 Tx slot	25.23	25.16	25.11	26.50	16.23	16.16	16.11	17.50
EDGE 2 Tx slots	24.83	24.73	24.96	26.50	18.83	18.73	18.96	20.50
EDGE 3 Tx slots	24.20	23.87	24.07	25.50	19.94	19.61	19.81	21.24
EDGE 4 Tx slots	22.82	22.97	22.84	24.50	19.82	19.97	19.84	21.50

GSM1900	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	512	661	810		512	661	810	
Frequency (MHz)	1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot	24.07	23.91	23.98	25.00	15.07	14.91	14.98	16.00
GPRS 1 Tx slot	24.04	23.97	23.99	25.00	15.04	14.97	14.99	16.00
GPRS 2 Tx slots	20.77	20.68	20.66	21.00	14.77	14.68	14.66	15.00
GPRS 3 Tx slots	18.98	18.99	18.72	20.25	14.72	14.73	14.46	15.99
GPRS 4 Tx slots	17.95	18.00	17.91	18.00	14.95	15.00	14.91	15.00
EDGE 1 Tx slot	20.14	20.12	20.06	21.50	11.14	11.12	11.06	12.50
EDGE 2 Tx slots	20.47	20.38	20.39	21.50	14.47	14.38	14.39	15.50
EDGE 3 Tx slots	18.50	18.50	18.53	19.75	14.24	14.24	14.27	15.49
EDGE 4 Tx slots	17.32	17.14	17.15	18.50	14.32	14.14	14.15	15.50

<Product Specific Power Mode>

GSM850	Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel	128	189	251		128	189	251	
Frequency (MHz)	824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot	32.48	32.41	32.14	33.00	23.48	23.41	23.14	24.00
GPRS 1 Tx slot	32.66	32.35	32.19	33.00	23.66	23.35	23.19	24.00
GPRS 2 Tx slots	28.50	28.92	29.40	30.00	22.50	22.92	23.40	24.00
GPRS 3 Tx slots	26.56	26.20	26.33	28.00	22.30	21.94	22.07	23.74
GPRS 4 Tx slots	24.39	24.42	24.36	25.00	21.39	21.42	21.36	22.00
EDGE 1 Tx slot	25.10	25.03	25.23	26.50	16.10	16.03	16.23	17.50
EDGE 2 Tx slots	24.98	24.93	24.78	26.50	18.98	18.93	18.78	20.50
EDGE 3 Tx slots	23.98	24.02	24.09	25.50	19.72	19.76	19.83	21.24
EDGE 4 Tx slots	22.74	23.04	22.94	24.50	19.74	20.04	19.94	21.50

<WCDMA Conducted Power>

1. The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification.
2. The procedures in KDB 941225 D01v03r01 are applied for 3GPP Rel. 6 HSPA to configure the device in the required sub-test mode(s) to determine SAR test exclusion.
3. For DC-HSDPA, the device was configured according to the H-Set 12, Fixed Reference Channel (FRC) configuration in Table C.8.1.12 of 3GPP TS 34.121-1, with the primary and the secondary serving HS-DSCH Cell enabled during the power measurement.

A summary of these settings are illustrated below:

HSDPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set Gain Factors (β_c and β_d) and parameters were set according to each
 - ii. Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - iii. Set RMC 12.2Kbps + HSDPA mode.
 - iv. Set Cell Power = -86 dBm
 - v. Set HS-DSCH Configuration Type to FRC (H-set 1, QPSK)
 - vi. Select HSDPA Uplink Parameters
 - vii. Set Delta ACK, Delta NACK and Delta CQI = 8
 - viii. Set Ack-Nack Repetition Factor to 3
 - ix. Set CQI Feedback Cycle (k) to 4 ms
 - x. Set CQI Repetition Factor to 2
 - xi. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

Table C.10.1.4: β values for transmitter characteristics tests with HS-DPCCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{hs} (Note 1, Note 2)	CM (dB) (Note 3)	MPR (dB) (Note 3)
1	2/15	15/15	64	2/15	4/15	0.0	0.0
2	12/15 (Note 4)	15/15 (Note 4)	64	12/15 (Note 4)	24/15	1.0	0.0
3	15/15	8/15	64	15/8	30/15	1.5	0.5
4	15/15	4/15	64	15/4	30/15	1.5	0.5
Note 1: Δ_{ACK}, Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. Note 2: For the HS-DPCCH power mask requirement test in clause 5.2C, 5.7A, and the Error Vector Magnitude (EVM) with HS-DPCCH test in clause 5.13.1A, and HSDPA EVM with phase discontinuity in clause 5.13.1AA, Δ_{ACK} and $\Delta_{NACK} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$, and $\Delta_{CQI} = 24/15$ with $\beta_{hs} = 24/15 * \beta_c$. Note 3: CM = 1 for $\beta_c/\beta_d = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCCH, DPCCH and HS-DPCCH the MPR is based on the relative CM difference. This is applicable for only UEs that support HSDPA in release 6 and later releases. Note 4: For subtest 2 the β_c/β_d ratio of 12/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 11/15$ and $\beta_d = 15/15$.							

Setup Configuration

HSUPA Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration.
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting * :
 - i. Call Configs = 5.2B, 5.9B, 5.10B, and 5.13.2B with QPSK
 - ii. Set the Gain Factors (β_c and β_d) and parameters (AG Index) were set according to each specific sub-test in the following table, C11.1.3, quoted from the TS 34.121
 - iii. Set Cell Power = -86 dBm
 - iv. Set Channel Type = 12.2k + HSPA
 - v. Set UE Target Power
 - vi. Power Ctrl Mode= Alternating bits
 - vii. Set and observe the E-TFCI
 - viii. Confirm that E-TFCI is equal to the target E-TFCI of 75 for sub-test 1, and other subtest's E-TFCI
- d. The transmitted maximum output power was recorded.

Table C.11.1.3: β values for transmitter characteristics tests with HS-DPCCH and E-DCH

Sub-test	β_c	β_d	β_d (SF)	β_c/β_d	β_{HS} (Note 1)	β_{ec}	β_{ed} (Note 4) (Note 5)	β_{ed} (SF)	β_{ed} (Codes)	CM (dB) (Note 2)	MPR (dB) (Note 2) (Note 6)	AG Index (Note 5)	E-TFCI
1	11/15 (Note 3)	15/15 (Note 3)	64	11/15 (Note 3)	22/15	209/25	1309/225	4	1	1.0	0.0	20	75
2	6/15	15/15	64	6/15	12/15	12/15	94/75	4	1	3.0	2.0	12	67
3	15/15	9/15	64	15/9	30/15	30/15	β_{ed1} : 47/15 β_{ed2} : 47/15	4	2	2.0	1.0	15	92
4	2/15	15/15	64	2/15	4/15	2/15	56/75	4	1	3.0	2.0	17	71
5	15/15	0	-	-	5/15	5/15	47/15	4	1	1.0	0.0	12	67

Note 1: For sub-test 1 to 4, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 30/15$ with $\beta_{hs} = 30/15 * \beta_c$. For sub-test 5, Δ_{ACK} , Δ_{NACK} and $\Delta_{CQI} = 5/15$ with $\beta_{hs} = 5/15 * \beta_c$.

Note 2: CM = 1 for $\beta_d/\beta_c = 12/15$, $\beta_{hs}/\beta_c = 24/15$. For all other combinations of DPDCH, DPCCH, HS-DPCCH, E-DPDCH and E-DPCCH the MPR is based on the relative CM difference.

Note 3: For subtest 1 the β_c/β_d ratio of 11/15 for the TFC during the measurement period (TF1, TF0) is achieved by setting the signalled gain factors for the reference TFC (TF1, TF1) to $\beta_c = 10/15$ and $\beta_d = 15/15$.

Note 4: In case of testing by UE using E-DPDCH Physical Layer category 1, Sub-test 3 is omitted according to TS25.306 Table 5.1g.

Note 5: β_{ed} can not be set directly; it is set by Absolute Grant Value.

Note 6: For subtests 2, 3 and 4, UE may perform E-DPDCH power scaling at max power which could results in slightly smaller MPR values.

Setup Configuration


DC-HSDPA 3GPP release 8 Setup Configuration:

- a. The EUT was connected to Base Station Agilent E5515C referred to the Setup Configuration below
- b. The RF path losses were compensated into the measurements.
- c. A call was established between EUT and Base Station with following setting:
 - i. Set RMC 12.2Kbps + HSDPA mode.
 - ii. Set Cell Power = -25 dBm
 - iii. Set HS-DSCH Configuration Type to FRC (H-set 12, QPSK)
 - iv. Select HSDPA Uplink Parameters
 - v. Set Gain Factors (β_c and β_d) and parameters were set according to each Specific sub-test in the following table, C10.1.4, quoted from the TS 34.121
 - a). Subtest 1: $\beta_c/\beta_d=2/15$
 - b). Subtest 2: $\beta_c/\beta_d=12/15$
 - c). Subtest 3: $\beta_c/\beta_d=15/8$
 - d). Subtest 4: $\beta_c/\beta_d=15/4$
 - vi. Set Delta ACK, Delta NACK and Delta CQI = 8
 - vii. Set Ack-Nack Repetition Factor to 3
 - viii. Set CQI Feedback Cycle (k) to 4 ms
 - ix. Set CQI Repetition Cycle to 2
 - x. Power Ctrl Mode = All Up bits
- d. The transmitted maximum output power was recorded.

The following tests were conducted according to the test requirements outlines in 3GPP TS 34.121 specification. A summary of these settings are illustrated below:

C.8.1.12 Fixed Reference Channel Definition H-Set 12
Table C.8.1.12: Fixed Reference Channel H-Set 12

Parameter	Unit	Value
Nominal Avg. Inf. Bit Rate	kbps	60
Inter-TTI Distance	TTI's	1
Number of HARQ Processes	Processes	6
Information Bit Payload (N_{INF})	Bits	120
Number Code Blocks	Blocks	1
Binary Channel Bits Per TTI	Bits	960
Total Available SML's in UE	SML's	19200
Number of SML's per HARQ Proc.	SML's	3200
Coding Rate		0.15
Number of Physical Channel Codes	Codes	1
Modulation		QPSK
Note 1: The RMC is intended to be used for DC-HSDPA mode and both cells shall transmit with identical parameters as listed in the table.		
Note 2: Maximum number of transmission is limited to 1, i.e., retransmission is not allowed. The redundancy and constellation version 0 shall be used.		


Figure C.8.19: Coding rate for Fixed reference Channel H-Set 12 (QPSK)
Setup Configuration

<WCDMA Conducted Power>
General Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

<Default Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	22.77	22.94	22.91	24.00	22.80	23.01	23.02	24.00	23.83	23.92	23.82	25.00
3GPP Rel 99	RMC 12.2Kbps	22.78	22.96	22.92	24.00	22.81	23.03	23.04	24.00	23.85	23.94	23.89	25.00
3GPP Rel 6	HSDPA Subtest-1	21.86	21.97	21.93	23.00	21.87	21.97	22.06	23.00	22.88	22.92	22.64	24.00
3GPP Rel 6	HSDPA Subtest-2	21.85	21.91	21.96	23.00	21.88	21.94	22.05	23.00	22.87	22.92	22.63	24.00
3GPP Rel 6	HSDPA Subtest-3	21.32	21.43	21.42	22.50	21.40	21.45	21.55	22.50	22.44	22.44	22.15	23.50
3GPP Rel 6	HSDPA Subtest-4	21.35	21.45	21.44	22.50	21.40	21.48	21.52	22.50	22.33	22.42	22.14	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	21.47	21.56	21.55	23.00	21.53	21.62	21.65	23.00	22.45	22.53	22.29	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	21.43	21.50	21.53	23.00	21.48	21.53	21.59	23.00	22.43	22.47	22.20	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	20.97	20.87	21.03	22.50	20.98	21.01	21.09	22.50	21.97	21.87	21.67	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	20.98	20.85	21.00	22.50	20.97	20.99	21.07	22.50	21.95	21.85	21.60	23.50
3GPP Rel 6	HSUPA Subtest-1	21.08	21.24	21.37	23.00	21.03	21.14	21.31	23.00	22.16	22.13	21.88	24.00
3GPP Rel 6	HSUPA Subtest-2	19.06	19.24	19.37	21.00	19.06	19.14	19.31	21.00	20.21	20.15	19.90	22.00
3GPP Rel 6	HSUPA Subtest-3	20.08	20.22	20.37	22.00	19.98	20.14	20.31	22.00	21.16	21.16	20.90	23.00
3GPP Rel 6	HSUPA Subtest-4	19.04	19.27	19.36	21.00	19.04	19.18	19.25	21.00	20.16	20.14	19.85	22.00
3GPP Rel 6	HSUPA Subtest-5	21.07	21.20	21.35	23.00	20.99	21.10	21.30	23.00	22.14	22.10	21.85	24.00

<Near-body Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	16.10	16.21	16.32	17.50	16.55	16.62	16.80	18.00	23.20	23.21	23.03	24.50
3GPP Rel 99	RMC 12.2Kbps	16.11	16.25	16.37	17.50	16.56	16.66	16.85	18.00	23.22	23.22	23.04	24.50
3GPP Rel 6	HSDPA Subtest-1	15.60	15.37	15.47	16.50	15.87	15.82	15.79	17.00	22.30	22.22	22.24	23.50
3GPP Rel 6	HSDPA Subtest-2	15.47	15.51	15.43	16.50	15.77	15.82	15.79	17.00	22.50	22.27	22.37	22.50
3GPP Rel 6	HSDPA Subtest-3	15.17	15.04	14.98	16.00	15.20	15.31	15.24	16.50	21.93	21.83	21.77	22.00
3GPP Rel 6	HSDPA Subtest-4	15.05	14.97	14.97	16.00	15.30	15.36	15.19	16.50	21.91	21.71	21.84	22.00
3GPP Rel 8	DC-HSDPA Subtest-1	15.59	15.36	15.46	16.50	15.72	15.76	15.76	17.00	22.41	22.27	22.11	23.50
3GPP Rel 8	DC-HSDPA Subtest-2	15.55	15.44	15.51	16.50	15.67	15.81	15.77	17.00	22.25	22.29	22.10	23.50
3GPP Rel 8	DC-HSDPA Subtest-3	14.92	14.83	14.94	16.00	15.24	15.19	15.15	16.50	21.80	21.83	21.69	23.00
3GPP Rel 8	DC-HSDPA Subtest-4	14.89	14.81	14.84	16.00	15.26	15.25	15.25	16.50	21.89	21.70	21.82	23.00
3GPP Rel 6	HSUPA Subtest-1	15.19	15.03	15.11	16.50	15.51	15.50	15.39	17.00	22.24	22.17	22.30	23.50
3GPP Rel 6	HSUPA Subtest-2	13.61	13.44	13.50	14.50	13.70	13.80	13.68	15.00	20.37	20.16	20.23	21.50
3GPP Rel 6	HSUPA Subtest-3	14.11	14.08	14.24	15.50	14.47	14.37	14.42	16.00	20.94	20.88	20.95	22.50
3GPP Rel 6	HSUPA Subtest-4	13.20	13.22	13.24	14.50	13.52	13.57	13.36	15.00	20.46	20.21	20.10	21.50
3GPP Rel 6	HSUPA Subtest-5	15.22	15.26	15.12	16.50	15.48	15.40	15.50	17.00	22.39	22.31	22.30	23.50

<Hotspot Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513		4132	4182	4233	
Rx Channel		9662	9800	9938		1537	1638	1738		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2Kbps	14.08	14.21	14.32	15.50	14.54	14.65	14.80	16.00	23.20	23.21	23.03	24.50
3GPP Rel 99	RMC 12.2Kbps	14.10	14.23	14.33	15.50	14.55	14.69	14.84	16.00	23.22	23.22	23.04	24.50
3GPP Rel 6	HSDPA Subtest-1	13.26	13.18	13.23	14.50	13.85	13.75	13.75	15.00	22.30	22.22	22.24	23.50
3GPP Rel 6	HSDPA Subtest-2	13.43	13.23	13.30	14.50	13.77	13.72	13.82	15.00	22.50	22.27	22.37	23.50
3GPP Rel 6	HSDPA Subtest-3	12.89	12.76	12.84	14.00	13.20	13.30	13.31	14.50	21.93	21.83	21.77	23.00
3GPP Rel 6	HSDPA Subtest-4	12.82	12.73	12.79	14.00	13.41	13.40	13.26	14.50	21.91	21.71	21.84	23.00
3GPP Rel 8	DC-HSDPA Subtest-1	13.32	13.22	13.24	14.50	13.80	13.83	13.81	15.00	22.41	22.27	22.11	23.50
3GPP Rel 8	DC-HSDPA Subtest-2	13.22	13.12	13.35	14.50	13.64	13.87	13.80	15.00	22.25	22.29	22.10	23.50
3GPP Rel 8	DC-HSDPA Subtest-3	12.74	12.61	12.79	14.00	13.25	13.34	13.29	14.50	21.80	21.83	21.69	23.00
3GPP Rel 8	DC-HSDPA Subtest-4	12.85	12.64	12.63	14.00	13.19	13.30	13.13	14.50	21.89	21.70	21.82	23.00
3GPP Rel 6	HSUPA Subtest-1	12.97	12.85	12.95	14.50	13.38	13.43	13.39	15.00	22.24	22.17	22.30	23.50
3GPP Rel 6	HSUPA Subtest-2	11.36	11.27	11.38	12.50	11.70	11.84	11.65	13.00	20.37	20.16	20.23	21.50
3GPP Rel 6	HSUPA Subtest-3	12.04	11.90	11.89	13.50	12.34	12.52	12.41	14.00	20.94	20.88	20.95	22.50
3GPP Rel 6	HSUPA Subtest-4	11.09	10.98	10.94	12.50	11.54	11.38	11.46	13.00	20.46	20.21	20.10	21.50
3GPP Rel 6	HSUPA Subtest-5	12.95	12.94	12.91	14.50	13.46	13.39	13.47	15.00	22.39	22.31	22.30	23.50


<Product Specific Power Mode>

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA IV			Tune-up Limit (dBm)
TX Channel		9262	9400	9538		1312	1413	1513	
Rx Channel		9662	9800	9938		1537	1638	1738	
Frequency (MHz)		1852.4	1880	1907.6		1712.4	1732.6	1752.6	
3GPP Rel 99	AMR 12.2Kbps	20.10	20.25	20.32	20.50	19.05	19.15	19.30	21.00
3GPP Rel 99	RMC 12.2Kbps	20.12	20.25	20.37	20.50	19.07	19.19	19.33	21.00
3GPP Rel 6	HSDPA Subtest-1	18.89	19.32	18.90	19.50	18.22	18.29	18.16	20.00
3GPP Rel 6	HSDPA Subtest-2	18.91	18.91	18.71	19.50	18.23	18.24	18.32	20.00
3GPP Rel 6	HSDPA Subtest-3	18.37	18.34	18.32	19.00	17.84	17.72	17.83	19.50
3GPP Rel 6	HSDPA Subtest-4	18.33	18.37	18.39	19.00	17.97	17.91	17.84	19.50
3GPP Rel 8	DC-HSDPA Subtest-1	18.74	18.77	18.76	19.50	18.27	18.22	18.26	20.00
3GPP Rel 8	DC-HSDPA Subtest-2	18.74	18.76	18.77	19.50	18.27	18.17	18.23	20.00
3GPP Rel 8	DC-HSDPA Subtest-3	18.27	18.20	18.25	19.00	17.74	17.86	17.77	19.50
3GPP Rel 8	DC-HSDPA Subtest-4	18.38	18.30	18.15	19.00	17.70	17.67	17.69	19.50
3GPP Rel 6	HSUPA Subtest-1	18.44	18.44	18.38	19.50	18.02	18.03	18.02	20.00
3GPP Rel 6	HSUPA Subtest-2	16.68	16.79	16.88	17.50	16.14	16.30	16.20	18.00
3GPP Rel 6	HSUPA Subtest-3	17.59	17.43	17.45	18.50	17.05	17.07	17.06	19.00
3GPP Rel 6	HSUPA Subtest-4	16.51	16.45	16.43	17.50	16.05	16.07	16.05	18.00
3GPP Rel 6	HSUPA Subtest-5	18.45	18.57	18.61	19.50	18.03	18.01	18.08	20.00


<LTE Conducted Power>

General Note:

1. Anritsu MT8820C base station simulator was used to setup the connection with EUT; the frequency band, channel bandwidth, RB allocation configuration, modulation type are set in the base station simulator to configure EUT transmitting at maximum power and at different configurations which are requested to be reported to FCC, for conducted power measurement and SAR testing.
2. Per KDB 941225 D05v02r05, when a properly configured base station simulator is used for the SAR and power measurements, spectrum plots for each RB allocation and offset configuration is not required.
3. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
4. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
5. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
6. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
7. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $>$ not $\frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
8. For LTE B4 / B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
9. LTE band 5 / 38 SAR test was covered by Band 26 / 41; according to April 2015 TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. the maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion
 - b. the channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band
10. According to 2017 TCB workshop, for 64 QAM and 16 QAM should be verified by checking the signal constellation with a call box to avoid incorrect maximum power levels due to MPR and other requirements associated with signal modulation, and the following figure is taken from the "Fundamental Measurement >> Modulation Analysis >> constellation" mode of the device connect to the MT8821C base station, therefore, the device 64QAM and 16QAM signal modulation are correct.



64QAM



16QAM

Default Power Mode

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	22.38	22.70	22.73	24.00	0
20	QPSK	1	49	22.46	22.69	22.65		
20	QPSK	1	99	22.50	22.69	22.66		
20	QPSK	50	0	21.51	21.77	21.69	23.00	1
20	QPSK	50	24	21.52	21.81	21.70		
20	QPSK	50	50	21.57	21.71	21.66		
20	QPSK	100	0	21.48	21.74	21.75	23.00	1
20	16QAM	1	0	21.68	22.03	21.94		
20	16QAM	1	49	21.81	22.14	21.97		
20	16QAM	1	99	21.89	22.01	21.87	22.00	2
20	16QAM	50	0	20.61	20.86	20.76		
20	16QAM	50	24	20.63	20.89	20.82		
20	16QAM	50	50	20.64	20.86	20.77	22.00	2
20	16QAM	100	0	20.55	20.83	20.80		
20	64QAM	1	0	21.57	20.95	20.88		
20	64QAM	1	49	21.65	20.94	20.92	22.00	2
20	64QAM	1	99	21.71	20.99	20.86		
20	64QAM	50	0	20.58	19.90	19.80	21.00	3
20	64QAM	50	24	19.66	19.94	19.83		
20	64QAM	50	50	19.64	19.86	19.78		
20	64QAM	100	0	19.64	19.90	19.78		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	22.43	22.60	22.54	24.00	0
15	QPSK	1	37	22.50	22.68	22.58		
15	QPSK	1	74	22.43	22.63	22.53		
15	QPSK	36	0	21.56	21.74	21.56	23.00	1
15	QPSK	36	20	21.63	21.77	21.58		
15	QPSK	36	39	21.56	21.71	21.61		
15	QPSK	75	0	21.59	21.72	21.56	23.00	1
15	16QAM	1	0	21.74	21.94	21.89		
15	16QAM	1	37	21.82	22.10	21.95		
15	16QAM	1	74	21.77	21.91	21.69	22.00	2
15	16QAM	36	0	20.67	20.84	20.66		
15	16QAM	36	20	20.68	20.86	20.71		
15	16QAM	36	39	20.62	20.81	20.73	22.00	2
15	16QAM	75	0	20.65	20.84	20.67		
15	64QAM	1	0	20.75	20.96	20.83		
15	64QAM	1	37	20.80	21.04	20.90	22.00	2
15	64QAM	1	74	20.77	20.87	20.91		
15	64QAM	36	0	19.73	19.92	19.77		
15	64QAM	36	20	19.78	19.94	19.75	21.00	3
15	64QAM	36	39	19.71	19.86	19.77		
15	64QAM	75	0	19.71	19.87	19.69		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	22.29	22.62	22.38	24.00	0
10	QPSK	1	25	22.19	22.54	22.43		
10	QPSK	1	49	22.29	22.53	22.40		
10	QPSK	25	0	21.24	21.58	21.40	23.00	1
10	QPSK	25	12	21.35	21.58	21.49		
10	QPSK	25	25	21.31	21.56	21.47		
10	QPSK	50	0	21.35	21.57	21.39		
10	16QAM	1	0	21.66	22.03	21.83	23.00	1
10	16QAM	1	25	21.57	21.92	21.82		
10	16QAM	1	49	21.68	21.92	21.61		
10	16QAM	25	0	20.36	20.70	20.55	22.00	2
10	16QAM	25	12	20.46	20.71	20.64		
10	16QAM	25	25	20.41	20.68	20.56		
10	16QAM	50	0	20.46	20.67	20.50		
10	64QAM	1	0	20.57	20.89	20.64	22.00	2
10	64QAM	1	25	20.48	20.80	20.71		
10	64QAM	1	49	20.60	20.91	20.52		
10	64QAM	25	0	19.36	19.73	19.55	21.00	3
10	64QAM	25	12	19.48	19.75	19.65		
10	64QAM	25	25	19.46	19.69	19.58		
10	64QAM	50	0	19.46	19.73	19.54		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	22.16	22.50	22.40	24.00	0
5	QPSK	1	12	22.15	22.51	22.40		
5	QPSK	1	24	22.12	22.48	22.38		
5	QPSK	12	0	21.22	21.59	21.46	23.00	1
5	QPSK	12	7	21.23	21.60	21.49		
5	QPSK	12	13	21.19	21.54	21.46		
5	QPSK	25	0	21.18	21.53	21.45		
5	16QAM	1	0	21.50	21.85	21.74	23.00	1
5	16QAM	1	12	21.53	21.91	21.70		
5	16QAM	1	24	21.48	21.84	21.56		
5	16QAM	12	0	20.33	20.67	20.54	22.00	2
5	16QAM	12	7	20.33	20.68	20.59		
5	16QAM	12	13	20.30	20.67	20.50		
5	16QAM	25	0	20.28	20.63	20.56		
5	64QAM	1	0	20.44	20.79	20.67	22.00	2
5	64QAM	1	12	20.47	20.78	20.81		
5	64QAM	1	24	20.39	20.75	20.50		
5	64QAM	12	0	19.38	19.74	19.61	21.00	3
5	64QAM	12	7	19.42	19.78	19.63		
5	64QAM	12	13	19.39	19.70	19.56		
5	64QAM	25	0	19.33	19.67	19.58		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	22.13	22.49	22.39	24.00	0
3	QPSK	1	8	22.14	22.51	22.37		
3	QPSK	1	14	22.10	22.46	22.35		
3	QPSK	8	0	21.18	21.54	21.45	23.00	1
3	QPSK	8	4	21.22	21.57	21.47		
3	QPSK	8	7	21.19	21.53	21.40		
3	QPSK	15	0	21.18	21.55	21.46		
3	16QAM	1	0	21.48	21.81	21.65	23.00	1
3	16QAM	1	8	21.50	21.86	21.64		
3	16QAM	1	14	21.47	21.82	21.55		
3	16QAM	8	0	20.34	20.70		22.00	2
3	16QAM	8	4	20.39	20.75	20.55		
3	16QAM	8	7	20.33	20.69	20.50		
3	16QAM	15	0	20.30	20.65	20.52		
3	64QAM	1	0	20.39	20.75	20.60	22.00	2
3	64QAM	1	8	20.43	20.80	20.57		
3	64QAM	1	14	20.38	20.73	20.50		
3	64QAM	8	0	19.37	19.73	19.59	21.00	3
3	64QAM	8	4	19.38	19.76	19.58		
3	64QAM	8	7	19.35	19.73	19.57		
3	64QAM	15	0	19.33	19.69	19.54		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	22.10	22.42	22.29	24.00	0
1.4	QPSK	1	3	22.13	22.48	22.42		
1.4	QPSK	1	5	22.04	22.41	22.32		
1.4	QPSK	3	0	22.11	22.47	22.33		
1.4	QPSK	3	1	22.17	22.52	22.40		
1.4	QPSK	3	3	22.11	22.45	22.35		
1.4	QPSK	6	0	21.12	21.48	21.40	23.00	1
1.4	16QAM	1	0	21.42	21.78	21.50	23.00	1
1.4	16QAM	1	3	21.52	21.88	21.54		
1.4	16QAM	1	5	21.44	21.79	21.47		
1.4	16QAM	3	0	21.20	21.55	21.33		
1.4	16QAM	3	1	21.28	21.58	21.37		
1.4	16QAM	3	3	21.20	21.54	21.32		
1.4	16QAM	6	0	20.29	20.65	20.49	22.00	2
1.4	64QAM	1	0	20.40	20.71	20.52	22.00	2
1.4	64QAM	1	3	20.44	20.76	20.53		
1.4	64QAM	1	5	20.36	20.70	20.47		
1.4	64QAM	3	0	20.38	20.70	20.51		
1.4	64QAM	3	1	20.41	20.77	20.55		
1.4	64QAM	3	3	20.35	20.70	20.50		
1.4	64QAM	6	0	19.23	19.57	19.45	21.00	3

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	22.56	22.77	22.63	24.00	0
20	QPSK	1	49	22.54	22.76	22.71		
20	QPSK	1	99	22.55	22.67	22.61		
20	QPSK	50	0	21.59	21.78	21.65	23.00	1
20	QPSK	50	24	21.72	21.82	21.65		
20	QPSK	50	50	21.64	21.74	21.66		
20	QPSK	100	0	21.78	21.76	21.61		
20	16QAM	1	0	21.96	22.14	22.07	23.00	1
20	16QAM	1	49	21.98	22.20	22.10		
20	16QAM	1	99	22.06	21.98	21.98		
20	16QAM	50	0	20.79	20.92	20.77	22.00	2
20	16QAM	50	24	20.90	20.90	20.78		
20	16QAM	50	50	20.85	20.87	20.79		
20	16QAM	100	0	20.85	20.87	20.74		
20	64QAM	1	0	20.94	21.13	20.93	22.00	2
20	64QAM	1	49	20.97	21.05	21.02		
20	64QAM	1	99	21.00	20.89	20.98		
20	64QAM	50	0	19.80	19.96	19.79	21.00	3
20	64QAM	50	24	19.94	19.95	19.80		
20	64QAM	50	50	19.91	19.87	19.83		
20	64QAM	100	0	19.91	19.91	19.77		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	22.62	22.72	22.66	24.00	0
15	QPSK	1	37	22.59	22.70	22.73		
15	QPSK	1	74	22.68	22.64	22.68		
15	QPSK	36	0	21.64	21.81	21.71	23.00	1
15	QPSK	36	20	21.66	21.82	21.81		
15	QPSK	36	39	21.75	21.76	21.75		
15	QPSK	75	0	21.70	21.74	21.69		
15	16QAM	1	0	21.94	22.04	22.02	23.00	1
15	16QAM	1	37	22.00	22.09	21.95		
15	16QAM	1	74	22.04	22.04	22.02		
15	16QAM	36	0	20.78	20.87	20.75	22.00	2
15	16QAM	36	20	20.78	20.91	20.93		
15	16QAM	36	39	20.86	20.87	20.86		
15	16QAM	75	0	20.84	20.89	20.76		
15	64QAM	1	0	20.87	21.13	21.02	22.00	2
15	64QAM	1	37	20.94	21.07	21.05		
15	64QAM	1	74	21.03	21.03	20.90		
15	64QAM	36	0	19.83	19.92	19.87	21.00	3
15	64QAM	36	20	19.86	19.99	19.97		
15	64QAM	36	39	19.95	19.92	19.91		
15	64QAM	75	0	19.88	19.92	19.80		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	22.54	22.66	22.71	24.00	0
10	QPSK	1	25	22.57	22.66	22.69		
10	QPSK	1	49	22.43	22.59	22.61		
10	QPSK	25	0	21.60	21.67	21.67	23.00	1
10	QPSK	25	12	21.62	21.69	21.73		
10	QPSK	25	25	21.57	21.65	21.67		
10	QPSK	50	0	21.58	21.65	21.69	23.00	1
10	16QAM	1	0	21.82	22.02	21.97		
10	16QAM	1	25	21.90	22.02	22.02		
10	16QAM	1	49	21.81	22.00	22.01	22.00	2
10	16QAM	25	0	20.70	20.80	20.82		
10	16QAM	25	12	20.69	20.80	20.84		
10	16QAM	25	25	20.69	20.78	20.82	22.00	2
10	16QAM	50	0	20.68	20.82	20.79		
10	64QAM	1	0	20.81	20.96	21.05		
10	64QAM	1	25	20.80	20.94	21.05	22.00	2
10	64QAM	1	49	20.75	20.97	20.97		
10	64QAM	25	0	19.76	19.88	19.86		
10	64QAM	25	12	19.72	19.83	19.86	21.00	3
10	64QAM	25	25	19.71	19.81	19.83		
10	64QAM	50	0	19.76	19.80	19.83		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	22.52	22.57	22.61	24.00	0
5	QPSK	1	12	22.49	22.55	22.58		
5	QPSK	1	24	22.47	22.52	22.51		
5	QPSK	12	0	21.55	21.60	21.63	23.00	1
5	QPSK	12	7	21.59	21.66	21.68		
5	QPSK	12	13	21.53	21.65	21.63		
5	QPSK	25	0	21.51	21.59	21.64	23.00	1
5	16QAM	1	0	21.71	21.92	21.94		
5	16QAM	1	12	21.80	21.92	21.92		
5	16QAM	1	24	21.75	21.97	21.90	22.00	2
5	16QAM	12	0	20.64	20.77	20.74		
5	16QAM	12	7	20.72	20.84	20.75		
5	16QAM	12	13	20.66	20.74	20.74	22.00	2
5	16QAM	25	0	20.68	20.76	20.72		
5	64QAM	1	0	20.79	20.98	20.93		
5	64QAM	1	12	20.82	20.87	20.89	22.00	2
5	64QAM	1	24	20.77	20.88	20.88		
5	64QAM	12	0	19.72	19.76	19.83		
5	64QAM	12	7	19.77	19.85	19.82	21.00	3
5	64QAM	12	13	19.69	19.80	19.81		
5	64QAM	25	0	19.65	19.74	19.73		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	22.48	22.53	22.57	24.00	0
3	QPSK	1	8	22.45	22.51	22.54		
3	QPSK	1	14	22.43	22.48	22.47		
3	QPSK	8	0	21.51	21.56	21.59	23.00	1
3	QPSK	8	4	21.55	21.62	21.64		
3	QPSK	8	7	21.49	21.61	21.59		
3	QPSK	15	0	21.47	21.55	21.60		
3	16QAM	1	0	21.67	21.88	21.90	23.00	1
3	16QAM	1	8	21.76	21.88	21.88		
3	16QAM	1	14	21.71	21.93	21.86		
3	16QAM	8	0	20.60	20.73	20.70	22.00	2
3	16QAM	8	4	20.68	20.80	20.71		
3	16QAM	8	7	20.62	20.70	20.70		
3	16QAM	15	0	20.64	20.72	20.68		
3	64QAM	1	0	20.75	20.94	20.89	22.00	2
3	64QAM	1	8	20.78	20.83	20.85		
3	64QAM	1	14	20.73	20.84	20.84		
3	64QAM	8	0	19.68	19.72	19.79	21.00	3
3	64QAM	8	4	19.73	19.81	19.78		
3	64QAM	8	7	19.65	19.76	19.77		
3	64QAM	15	0	19.61	19.70	19.69		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	22.62	22.60	22.59	24.00	0
1.4	QPSK	1	3	22.71	22.62	22.69		
1.4	QPSK	1	5	22.59	22.61	22.75		
1.4	QPSK	3	0	22.72	22.66	22.70		
1.4	QPSK	3	1	22.71	22.70	22.70		
1.4	QPSK	3	3	22.69	22.75	22.67		
1.4	QPSK	6	0	21.71	21.77	21.77	23.00	1
1.4	16QAM	1	0	21.96	22.15	22.12	23.00	1
1.4	16QAM	1	3	22.00	22.19	22.19		
1.4	16QAM	1	5	22.00	22.14	22.03		
1.4	16QAM	3	0	21.79	21.92	21.86		
1.4	16QAM	3	1	21.81	21.93	21.89		
1.4	16QAM	3	3	21.73	21.91	21.87		
1.4	16QAM	6	0	20.89	20.97	20.94	22.00	2
1.4	64QAM	1	0	20.45	20.76	20.57	22.00	2
1.4	64QAM	1	3	20.49	20.81	20.58		
1.4	64QAM	1	5	20.41	20.75	20.52		
1.4	64QAM	3	0	20.43	20.75	20.56		
1.4	64QAM	3	1	20.46	20.82	20.60		
1.4	64QAM	3	3	20.40	20.75	20.55		
1.4	64QAM	6	0	19.28	19.62	19.50	21.00	3

<LTE Band 5>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20450	20525	20600		
Frequency (MHz)				829	836.5	844		
10	QPSK	1	0	22.72	22.71	22.62	24.00	0
10	QPSK	1	25	22.64	22.66	22.58		
10	QPSK	1	49	22.62	22.55	22.51		
10	QPSK	25	0	21.66	21.70	21.65	23.00	1
10	QPSK	25	12	21.77	21.71	21.65		
10	QPSK	25	25	21.71	21.63	21.59		
10	QPSK	50	0	21.76	21.65	21.61		
10	16QAM	1	0	22.04	22.08	21.98	23.00	1
10	16QAM	1	25	21.97	22.02	21.97		
10	16QAM	1	49	21.99	21.95	21.85		
10	16QAM	25	0	20.78	20.81	20.76	22.00	2
10	16QAM	25	12	20.90	20.83	20.75		
10	16QAM	25	25	20.85	20.74	20.72		
10	16QAM	50	0	20.89	20.77	20.72		
10	64QAM	1	0	20.95	20.97	20.96	22.00	2
10	64QAM	1	25	20.93	20.93	20.86		
10	64QAM	1	49	20.95	20.85	20.76		
10	64QAM	25	0	19.78	19.83	19.77	21.00	3
10	64QAM	25	12	19.92	19.86	19.78		
10	64QAM	25	25	19.83	19.76	19.70		
10	64QAM	50	0	19.88	19.80	19.76		
Channel				20425	20525	20625	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				826.5	836.5	846.5		
5	QPSK	1	0	22.69	22.70	22.65	24.00	0
5	QPSK	1	12	22.70	22.69	22.57		
5	QPSK	1	24	22.69	22.66	22.56		
5	QPSK	12	0	21.58	21.72	21.65	23.00	1
5	QPSK	12	7	21.75	21.75	21.67		
5	QPSK	12	13	21.73	21.71	21.65		
5	QPSK	25	0	21.73	21.72	21.62		
5	16QAM	1	0	22.10	22.08	21.96	23.00	1
5	16QAM	1	12	22.05	22.13	21.92		
5	16QAM	1	24	21.99	21.92	21.92		
5	16QAM	12	0	20.85	20.88	20.79	22.00	2
5	16QAM	12	7	20.92	20.90	20.81		
5	16QAM	12	13	20.86	20.87	20.77		
5	16QAM	25	0	20.83	20.84	20.77		
5	64QAM	1	0	20.99	20.97	20.94	22.00	2
5	64QAM	1	12	20.94	21.00	20.91		
5	64QAM	1	24	20.89	20.90	20.93		
5	64QAM	12	0	19.88	19.83	19.90	21.00	3
5	64QAM	12	7	19.98	19.85	20.00		
5	64QAM	12	13	19.83	19.81	20.01		
5	64QAM	25	0	19.97	19.99	19.89		

Channel				20415	20525	20635	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				825.5	836.5	847.5		
3	QPSK	1	0	22.70	22.69	22.63	24.00	0
3	QPSK	1	8	22.68	22.68	22.63		
3	QPSK	1	14	22.65	22.64	22.55		
3	QPSK	8	0	21.76	21.76	21.67	23.00	1
3	QPSK	8	4	21.76	21.79	21.65		
3	QPSK	8	7	21.70	21.73	21.64		
3	QPSK	15	0	21.72	21.72	21.62		
3	16QAM	1	0	22.12	22.05	22.02	23.00	1
3	16QAM	1	8	22.05	22.05	22.03		
3	16QAM	1	14	21.95	21.97	21.97		
3	16QAM	8	0	20.88	20.84	20.76	22.00	2
3	16QAM	8	4	20.87	20.83	20.82		
3	16QAM	8	7	20.82	20.85	20.75		
3	16QAM	15	0	20.86	20.80	20.74		
3	64QAM	1	0	21.03	21.00	20.94	22.00	2
3	64QAM	1	8	20.99	20.94	20.86		
3	64QAM	1	14	20.96	20.86	20.87		
3	64QAM	8	0	19.93	19.90	19.84	21.00	3
3	64QAM	8	4	19.96	19.95	19.84		
3	64QAM	8	7	19.87	19.86	19.80		
3	64QAM	15	0	19.87	19.85	19.76		
Channel				20407	20525	20643	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				824.7	836.5	848.3		
1.4	QPSK	1	0	22.64	22.63	22.51	24.00	0
1.4	QPSK	1	3	22.71	22.66	22.62		
1.4	QPSK	1	5	22.61	22.61	22.47		
1.4	QPSK	3	0	22.70	22.65	22.57		
1.4	QPSK	3	1	22.71	22.70	22.60		
1.4	QPSK	3	3	22.68	22.63	22.55		
1.4	QPSK	6	0	21.68	21.65	21.58	23.00	1
1.4	16QAM	1	0	22.05	22.04	21.91	23.00	1
1.4	16QAM	1	3	22.09	22.06	21.91		
1.4	16QAM	1	5	21.94	22.02	21.79		
1.4	16QAM	3	0	21.78	21.74	21.63		
1.4	16QAM	3	1	21.79	21.81	21.68		
1.4	16QAM	3	3	21.76	21.74	21.60		
1.4	16QAM	6	0	20.90	20.82	20.70	22.00	2
1.4	64QAM	1	0	20.88	20.72	20.81	22.00	2
1.4	64QAM	1	3	20.79	20.71	20.80		
1.4	64QAM	1	5	20.22	20.49	20.56		
1.4	64QAM	3	0	20.46	20.85	20.57		
1.4	64QAM	3	1	20.33	20.43	20.40		
1.4	64QAM	3	3	20.29	20.45	20.37		
1.4	64QAM	6	0	19.99	20.00	20.00	21.00	3

<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	23.04	22.95	22.98	24.00	0
20	QPSK	1	49	23.02	22.93	22.85		
20	QPSK	1	99	23.03	22.90	22.78		
20	QPSK	50	0	22.09	22.02	21.97	23.00	1
20	QPSK	50	24	22.13	21.99	21.99		
20	QPSK	50	50	22.10	21.95	21.90		
20	QPSK	100	0	22.09	22.00	21.94		
20	16QAM	1	0	22.25	22.24	22.31	23.00	1
20	16QAM	1	49	22.29	22.20	22.14		
20	16QAM	1	99	22.39	22.18	22.14		
20	16QAM	50	0	21.16	21.10	21.10	22.00	2
20	16QAM	50	24	21.19	21.09	21.01		
20	16QAM	50	50	21.23	21.07	20.97		
20	16QAM	100	0	21.18	21.08	20.98		
20	64QAM	1	0	21.32	21.23	21.21	22.00	2
20	64QAM	1	49	21.28	21.16	21.08		
20	64QAM	1	99	21.22	21.14	21.03		
20	64QAM	50	0	20.18	20.09	20.10	21.00	3
20	64QAM	50	24	20.19	20.13	20.04		
20	64QAM	50	50	20.24	20.03	20.06		
20	64QAM	100	0	20.22	20.06	20.01		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	22.95	22.96	22.91	24.00	0
15	QPSK	1	37	22.95	22.89	22.84		
15	QPSK	1	74	22.98	22.87	22.76		
15	QPSK	36	0	22.06	21.97	21.94	23.00	1
15	QPSK	36	20	22.08	21.95	21.93		
15	QPSK	36	39	22.02	21.91	21.84		
15	QPSK	75	0	22.04	21.95	21.90		
15	16QAM	1	0	22.31	22.23	22.14	23.00	1
15	16QAM	1	37	22.24	22.19	22.14		
15	16QAM	1	74	22.31	22.24	22.03		
15	16QAM	36	0	21.14	21.06	20.98	22.00	2
15	16QAM	36	20	21.15	21.05	21.01		
15	16QAM	36	39	21.10	21.01	20.92		
15	16QAM	75	0	21.13	21.02	21.01		
15	64QAM	1	0	21.99	21.25	21.09	22.00	2
15	64QAM	1	37	21.98	21.18	21.06		
15	64QAM	1	74	22.00	21.16	21.05		
15	64QAM	36	0	20.17	20.06	20.02	21.00	3
15	64QAM	36	20	20.22	20.09	20.02		
15	64QAM	36	39	20.15	20.02	19.98		
15	64QAM	75	0	20.16	20.07	19.98		

Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	22.98	22.91	22.88	24.00	0
10	QPSK	1	25	22.96	22.91	22.84		
10	QPSK	1	49	23.00	22.88	22.77		
10	QPSK	25	0	22.05	21.96	21.89	23.00	1
10	QPSK	25	12	22.06	21.94	21.88		
10	QPSK	25	25	22.03	21.91	21.86		
10	QPSK	50	0	22.03	21.94	21.88		
10	16QAM	1	0	22.34	22.19	22.19	23.00	1
10	16QAM	1	25	22.26	22.17	22.09		
10	16QAM	1	49	22.31	22.17	22.09		
10	16QAM	25	0	21.13	21.05	20.99	22.00	2
10	16QAM	25	12	21.18	21.07	20.99		
10	16QAM	25	25	21.11	21.02	20.97		
10	16QAM	50	0	21.13	21.04	20.98		
10	64QAM	1	0	21.18	21.16	21.03	22.00	2
10	64QAM	1	25	21.08	21.14	20.95		
10	64QAM	1	49	21.11	21.25	20.96		
10	64QAM	25	0	20.13	20.05	20.00	21.00	3
10	64QAM	25	12	20.19	20.03	19.99		
10	64QAM	25	25	20.20	20.10	19.98		
10	64QAM	50	0	20.12	20.09	19.99		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	22.98	22.92	22.88	24.00	0
5	QPSK	1	12	22.99	22.88	22.87		
5	QPSK	1	24	23.01	22.89	22.83		
5	QPSK	12	0	22.00	21.90	21.94	23.00	1
5	QPSK	12	7	22.09	21.97	21.93		
5	QPSK	12	13	22.00	21.94	21.84		
5	QPSK	25	0	22.04	21.93	21.90		
5	16QAM	1	0	22.28	22.28	22.14	23.00	1
5	16QAM	1	12	22.29	22.18	22.14		
5	16QAM	1	24	22.26	22.17	22.03		
5	16QAM	12	0	21.12	21.03	20.98	22.00	2
5	16QAM	12	7	21.12	21.00	21.01		
5	16QAM	12	13	21.16	21.02	20.92		
5	16QAM	25	0	21.11	21.03	21.01		
5	64QAM	1	0	21.99	21.23	21.09	22.00	2
5	64QAM	1	12	21.98	21.16	21.06		
5	64QAM	1	24	22.00	21.14	21.05		
5	64QAM	12	0	20.17	20.09	20.02	21.00	3
5	64QAM	12	7	20.22	20.13	20.02		
5	64QAM	12	13	20.15	20.03	19.98		
5	64QAM	25	0	20.16	20.06	19.98		

<LTE Band 26>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				26765	26865	26965	24.00	0
Frequency (MHz)				821.5	831.5	841.5		
15	QPSK	1	0	22.82	22.74	22.68		
15	QPSK	1	37	22.80	22.71	22.57	23.00	1
15	QPSK	1	74	22.80	22.60	22.50		
15	QPSK	36	0	21.84	21.79	21.65		
15	QPSK	36	20	21.82	21.76	21.65		
15	QPSK	36	39	21.86	21.70	21.56	23.00	1
15	QPSK	75	0	21.81	21.72	21.61		
15	16QAM	1	0	22.19	22.07	22.09		
15	16QAM	1	37	22.17	22.09	21.95		
15	16QAM	1	74	22.14	21.99	21.90	22.00	2
15	16QAM	36	0	20.96	20.88	20.74		
15	16QAM	36	20	20.93	20.87	20.75		
15	16QAM	36	39	20.98	20.80	20.65		
15	16QAM	75	0	20.92	20.83	20.74	22.00	2
15	64QAM	1	0	21.10	21.05	20.98		
15	64QAM	1	37	21.04	21.03	20.90		
15	64QAM	1	74	21.09	20.91	20.81		
15	64QAM	36	0	20.00	19.92	19.80	21.00	3
15	64QAM	36	20	19.97	19.89	19.78		
15	64QAM	36	39	20.02	19.83	19.69		
15	64QAM	75	0	19.94	19.82	19.73		
Channel				26740	26865	26990	24.00	0
Frequency (MHz)				819	831.5	844		
10	QPSK	1	0	22.75	22.65	22.67		
10	QPSK	1	25	22.67	22.75	22.63	23.00	1
10	QPSK	1	49	22.68	22.67	22.56		
10	QPSK	25	0	21.76	21.79	21.62		
10	QPSK	25	12	21.81	21.75	21.63		
10	QPSK	25	25	21.77	21.72	21.59	23.00	1
10	QPSK	50	0	21.80	21.73	21.65		
10	16QAM	1	0	22.13	22.05	22.00		
10	16QAM	1	25	21.97	22.07	21.98		
10	16QAM	1	49	22.08	22.03	21.87	22.00	2
10	16QAM	25	0	20.81	20.91	20.78		
10	16QAM	25	12	20.94	20.86	20.75		
10	16QAM	25	25	20.86	20.84	20.71		
10	16QAM	50	0	20.94	20.84	20.77	22.00	2
10	64QAM	1	0	21.07	21.00	20.95		
10	64QAM	1	25	20.95	21.08	20.92		
10	64QAM	1	49	20.96	21.00	20.84		
10	64QAM	25	0	19.86	19.92	19.74	21.00	3
10	64QAM	25	12	19.98	19.87	19.79		
10	64QAM	25	25	19.88	19.87	19.74		
10	64QAM	50	0	19.92	19.88	19.78		

Channel				26715	26865	27015	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				816.5	831.5	846.5		
5	QPSK	1	0	22.74	22.67	22.78	24.00	0
5	QPSK	1	12	22.70	22.58	22.77		
5	QPSK	1	24	22.63	22.57	22.74		
5	QPSK	12	0	21.58	21.59	21.79	23.00	1
5	QPSK	12	7	21.90	21.63	21.82		
5	QPSK	12	13	21.76	21.63	21.78		
5	QPSK	25	0	21.74	21.59	21.78		
5	16QAM	1	0	21.86	21.93	22.09	23.00	1
5	16QAM	1	12	21.91	21.97	22.15		
5	16QAM	1	24	22.00	21.84	22.11		
5	16QAM	12	0	20.99	20.77	20.91	22.00	2
5	16QAM	12	7	20.88	20.79	20.97		
5	16QAM	12	13	20.89	20.76	20.94		
5	16QAM	25	0	20.91	20.70	20.85		
5	64QAM	1	0	20.93	20.94	21.03	22.00	2
5	64QAM	1	12	20.86	20.84	21.00		
5	64QAM	1	24	20.91	20.83	20.95		
5	64QAM	12	0	19.97	19.84	19.92	21.00	3
5	64QAM	12	7	19.90	19.74	19.90		
5	64QAM	12	13	19.96	19.73	19.86		
5	64QAM	25	0	19.95	19.67	19.85		
Channel				26705	26865	27025	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				815.5	831.5	847.5		
3	QPSK	1	0	22.74	22.77	22.63	24.00	0
3	QPSK	1	8	22.71	22.72	22.58		
3	QPSK	1	14	22.66	22.70	22.56		
3	QPSK	8	0	21.74	21.77	21.63	23.00	1
3	QPSK	8	4	21.75	21.80	21.66		
3	QPSK	8	7	21.71	21.73	21.59		
3	QPSK	15	0	21.72	21.78	21.64		
3	16QAM	1	0	22.06	22.10	21.96	23.00	1
3	16QAM	1	8	22.13	22.02	21.88		
3	16QAM	1	14	22.08	22.04	21.90		
3	16QAM	8	0	20.89	20.93	20.79	22.00	2
3	16QAM	8	4	20.86	20.90	20.76		
3	16QAM	8	7	20.83	20.84	20.70		
3	16QAM	15	0	20.83	20.87	20.73		
3	64QAM	1	0	21.02	21.03	20.89	22.00	2
3	64QAM	1	8	21.02	21.03	20.89		
3	64QAM	1	14	20.93	20.93	20.79		
3	64QAM	8	0	19.89	19.96	19.82	21.00	3
3	64QAM	8	4	19.93	19.93	19.79		
3	64QAM	8	7	19.88	19.91	19.77		
3	64QAM	15	0	19.84	19.89	19.75		

Channel				26697	26865	27033	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				814.7	831.5	848.3		
1.4	QPSK	1	0	22.64	22.68	22.52	24.00	0
1.4	QPSK	1	3	22.71	22.77	22.57		
1.4	QPSK	1	5	22.62	22.66	22.52		
1.4	QPSK	3	0	22.70	22.72	22.52		
1.4	QPSK	3	1	22.73	22.76	22.60		
1.4	QPSK	3	3	22.66	22.72	22.56		
1.4	QPSK	6	0	21.67	21.71	21.54	23.00	1
1.4	16QAM	1	0	21.99	22.06	21.81	23.00	1
1.4	16QAM	1	3	22.06	22.09	21.99		
1.4	16QAM	1	5	22.00	22.02	21.87		
1.4	16QAM	3	0	21.82	21.82	21.66		
1.4	16QAM	3	1	21.86	21.84	21.76		
1.4	16QAM	3	3	21.79	21.77	21.71		
1.4	16QAM	6	0	20.88	20.89	20.70	22.00	2
1.4	64QAM	1	0	21.00	21.06	21.20	22.00	2
1.4	64QAM	1	3	21.03	21.13	21.09		
1.4	64QAM	1	5	20.13	20.33	20.25		
1.4	64QAM	3	0	20.22	20.31	20.19		
1.4	64QAM	3	1	20.10	20.00	20.03		
1.4	64QAM	3	3	20.11	20.01	20.07		
1.4	64QAM	6	0	19.79	19.90	19.87	21.00	3

Near-body Power Mode

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	16.26	16.47	16.46	17.50	0
20	QPSK	1	49	16.04	16.28	16.27		
20	QPSK	1	99	16.11	16.38	16.27		
20	QPSK	50	0	16.09	16.27	16.32	17.50	0
20	QPSK	50	24	16.08	16.31	16.29		
20	QPSK	50	50	16.13	16.26	16.26		
20	QPSK	100	0	16.06	16.25	16.27	17.50	0
20	16QAM	1	0	16.30	16.53	16.68		
20	16QAM	1	49	16.47	16.69	16.64		
20	16QAM	1	99	16.44	16.31	16.32	17.50	0
20	16QAM	50	0	16.21	16.40	16.41		
20	16QAM	50	24	16.20	16.46	16.39		
20	16QAM	50	50	16.24	16.39	16.39	17.50	0
20	16QAM	100	0	16.15	16.38	16.39		
20	64QAM	1	0	16.20	16.39	16.53		
20	64QAM	1	49	16.28	16.48	16.48	17.50	0
20	64QAM	1	99	16.38	16.61	16.48		
20	64QAM	50	0	16.18	16.40	16.40		
20	64QAM	50	24	16.21	16.44	16.42	17.50	0
20	64QAM	50	50	16.26	16.38	16.38		
20	64QAM	100	0	16.16	16.39	16.41		
Channel				18675	18900	19125		
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	16.24	16.46	16.46	17.50	0
15	QPSK	1	37	15.94	16.27	16.24		
15	QPSK	1	74	16.07	16.29	16.22		
15	QPSK	36	0	16.01	16.19	16.31	17.50	0
15	QPSK	36	20	15.99	16.28	16.20		
15	QPSK	36	39	16.11	16.16	16.19		
15	QPSK	75	0	15.97	16.16	16.23	17.50	0
15	16QAM	1	0	16.24	16.51	16.64		
15	16QAM	1	37	16.46	16.64	16.63		
15	16QAM	1	74	16.39	16.25	16.29	17.50	0
15	16QAM	36	0	16.16	16.31	16.37		
15	16QAM	36	20	16.10	16.41	16.38		
15	16QAM	36	39	16.19	16.29	16.37	17.50	0
15	16QAM	75	0	16.15	16.37	16.37		
15	64QAM	1	0	16.18	16.33	16.46		
15	64QAM	1	37	16.22	16.41	16.46	17.50	0
15	64QAM	1	74	16.31	16.53	16.40		
15	64QAM	36	0	16.13	16.32	16.31		
15	64QAM	36	20	16.14	16.41	16.35	17.50	0
15	64QAM	36	39	16.24	16.35	16.30		
15	64QAM	75	0	16.10	16.37	16.34		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	16.25	16.40	16.37	17.50	0
10	QPSK	1	25	16.00	16.26	16.19		
10	QPSK	1	49	16.08	16.32	16.20		
10	QPSK	25	0	16.00	16.21	16.31	17.50	0
10	QPSK	25	12	16.01	16.24	16.24		
10	QPSK	25	25	16.05	16.23	16.25		
10	QPSK	50	0	16.05	16.20	16.24		
10	16QAM	1	0	16.26	16.50	16.65	17.50	0
10	16QAM	1	25	16.43	16.64	16.58		
10	16QAM	1	49	16.40	16.27	16.26		
10	16QAM	25	0	16.15	16.38	16.34	17.50	0
10	16QAM	25	12	16.15	16.36	16.34		
10	16QAM	25	25	16.21	16.30	16.29		
10	16QAM	50	0	16.13	16.36	16.33		
10	64QAM	1	0	16.11	16.38	16.52	17.50	0
10	64QAM	1	25	16.24	16.46	16.42		
10	64QAM	1	49	16.30	16.57	16.44		
10	64QAM	25	0	16.10	16.35	16.34	17.50	0
10	64QAM	25	12	16.19	16.41	16.39		
10	64QAM	25	25	16.21	16.35	16.32		
10	64QAM	50	0	16.14	16.36	16.32		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	16.18	16.46	16.45	17.50	0
5	QPSK	1	12	15.97	16.26	16.24		
5	QPSK	1	24	16.04	16.33	16.24		
5	QPSK	12	0	16.00	16.18	16.26	17.50	0
5	QPSK	12	7	16.03	16.28	16.27		
5	QPSK	12	13	16.10	16.20	16.18		
5	QPSK	25	0	15.99	16.17	16.18		
5	16QAM	1	0	16.23	16.44	16.67	17.50	0
5	16QAM	1	12	16.45	16.65	16.59		
5	16QAM	1	24	16.38	16.24	16.29		
5	16QAM	12	0	16.14	16.33	16.35	17.50	0
5	16QAM	12	7	16.20	16.45	16.38		
5	16QAM	12	13	16.19	16.32	16.33		
5	16QAM	25	0	16.07	16.36	16.31		
5	64QAM	1	0	16.14	16.37	16.43	17.50	0
5	64QAM	1	12	16.18	16.46	16.40		
5	64QAM	1	24	16.28	16.52	16.47		
5	64QAM	12	0	16.14	16.33	16.31	17.50	0
5	64QAM	12	7	16.14	16.43	16.41		
5	64QAM	12	13	16.20	16.32	16.33		
5	64QAM	25	0	16.09	16.38	16.36		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	16.20	16.41	16.40	17.50	0
3	QPSK	1	8	16.02	16.26	16.23		
3	QPSK	1	14	16.04	16.29	16.23		
3	QPSK	8	0	16.06	16.23	16.22	17.50	0
3	QPSK	8	4	15.99	16.31	16.24		
3	QPSK	8	7	16.05	16.22	16.22		
3	QPSK	15	0	15.97	16.18	16.26		
3	16QAM	1	0	16.28	16.49	16.63	17.50	0
3	16QAM	1	8	16.44	16.67	16.61		
3	16QAM	1	14	16.34	16.29	16.30		
3	16QAM	8	0	16.14	16.36	16.41	17.50	0
3	16QAM	8	4	16.14	16.38	16.36		
3	16QAM	8	7	16.14	16.36	16.38		
3	16QAM	15	0	16.11	16.29	16.37		
3	64QAM	1	0	16.16	16.38	16.46	17.50	0
3	64QAM	1	8	16.23	16.45	16.39		
3	64QAM	1	14	16.29	16.52	16.48		
3	64QAM	8	0	16.09	16.37	16.36	17.50	0
3	64QAM	8	4	16.19	16.43	16.38		
3	64QAM	8	7	16.22	16.37	16.33		
3	64QAM	15	0	16.13	16.36	16.31		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	16.20	16.38	16.41	17.50	0
1.4	QPSK	1	3	15.96	16.23	16.21		
1.4	QPSK	1	5	16.04	16.37	16.26		
1.4	QPSK	3	0	16.07	16.25	16.22		
1.4	QPSK	3	1	16.04	16.25	16.22		
1.4	QPSK	3	3	16.08	16.26	16.24		
1.4	QPSK	6	0	16.05	16.16	16.25	17.50	0
1.4	16QAM	1	0	16.23	16.45	16.60	17.50	0
1.4	16QAM	1	3	16.42	16.62	16.55		
1.4	16QAM	1	5	16.36	16.22	16.31		
1.4	16QAM	3	0	16.13	16.36	16.39		
1.4	16QAM	3	1	16.15	16.37	16.34		
1.4	16QAM	3	3	16.24	16.30	16.32		
1.4	16QAM	6	0	16.09	16.34	16.35	17.50	0
1.4	64QAM	1	0	16.11	16.32	16.50	17.50	0
1.4	64QAM	1	3	16.22	16.39	16.43		
1.4	64QAM	1	5	16.36	16.58	16.48		
1.4	64QAM	3	0	16.11	16.31	16.36		
1.4	64QAM	3	1	16.13	16.37	16.38		
1.4	64QAM	3	3	16.24	16.36	16.33		
1.4	64QAM	6	0	16.12	16.35	16.38	17.50	0

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300	17.00	0
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	16.08	16.21	16.13		
20	QPSK	1	49	15.61	15.79	15.84	17.00	0
20	QPSK	1	99	15.67	15.74	15.75		
20	QPSK	50	0	15.66	15.83	15.76		
20	QPSK	50	24	15.74	15.78	15.76	17.00	0
20	QPSK	50	50	15.72	15.77	15.82		
20	QPSK	100	0	15.76	15.77	15.78		
20	16QAM	1	0	16.08	16.13	16.22	17.00	0
20	16QAM	1	49	16.03	16.19	16.21		
20	16QAM	1	99	16.02	16.16	16.18		
20	16QAM	50	0	15.79	15.94	15.89	17.00	0
20	16QAM	50	24	15.90	15.95	15.93		
20	16QAM	50	50	15.83	15.91	15.95		
20	16QAM	100	0	15.86	15.93	15.89	17.00	0
20	64QAM	1	0	16.00	16.10	15.99		
20	64QAM	1	49	15.98	16.14	16.14		
20	64QAM	1	99	15.95	16.06	16.00	17.00	0
20	64QAM	50	0	15.83	15.95	15.94		
20	64QAM	50	24	15.92	15.95	15.94		
20	64QAM	50	50	15.85	15.89	15.96	17.00	0
20	64QAM	100	0	15.88	15.92	15.90		
Channel				20025	20175	20325	17.00	0
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	16.02	16.14	16.10		
15	QPSK	1	37	15.52	15.72	15.83	17.00	0
15	QPSK	1	74	15.59	15.72	15.68		
15	QPSK	36	0	15.66	15.79	15.71		
15	QPSK	36	20	15.65	15.70	15.67	17.00	0
15	QPSK	36	39	15.67	15.71	15.82		
15	QPSK	75	0	15.73	15.73	15.73		
15	16QAM	1	0	16.03	16.10	16.17	17.00	0
15	16QAM	1	37	16.02	16.16	16.20		
15	16QAM	1	74	15.99	16.13	16.09		
15	16QAM	36	0	15.74	15.90	15.84	17.00	0
15	16QAM	36	20	15.88	15.86	15.87		
15	16QAM	36	39	15.80	15.85	15.93		
15	16QAM	75	0	15.85	15.91	15.82	17.00	0
15	64QAM	1	0	15.94	16.07	15.94		
15	64QAM	1	37	15.88	16.10	16.06		
15	64QAM	1	74	15.87	16.05	15.95	17.00	0
15	64QAM	36	0	15.79	15.87	15.91		
15	64QAM	36	20	15.84	15.90	15.85		
15	64QAM	36	39	15.80	15.85	15.92	17.00	0
15	64QAM	75	0	15.85	15.92	15.88		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	16.07	16.20	16.13	17.00	0
10	QPSK	1	25	15.59	15.77	15.84		
10	QPSK	1	49	15.57	15.67	15.74		
10	QPSK	25	0	15.59	15.77	15.69	17.00	0
10	QPSK	25	12	15.67	15.69	15.69		
10	QPSK	25	25	15.69	15.71	15.73		
10	QPSK	50	0	15.67	15.69	15.73		
10	16QAM	1	0	16.01	16.11	16.20	17.00	0
10	16QAM	1	25	15.98	16.16	16.19		
10	16QAM	1	49	15.99	16.09	16.10		
10	16QAM	25	0	15.72	15.89	15.83	17.00	0
10	16QAM	25	12	15.81	15.88	15.88		
10	16QAM	25	25	15.74	15.86	15.92		
10	16QAM	50	0	15.80	15.91	15.83		
10	64QAM	1	0	15.92	16.09	15.97	17.00	0
10	64QAM	1	25	15.92	16.09	16.05		
10	64QAM	1	49	15.87	16.04	15.90		
10	64QAM	25	0	15.74	15.94	15.90	17.00	0
10	64QAM	25	12	15.83	15.87	15.89		
10	64QAM	25	25	15.75	15.88	15.93		
10	64QAM	50	0	15.82	15.87	15.80		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	16.06	16.13	16.09	17.00	0
5	QPSK	1	12	15.56	15.69	15.78		
5	QPSK	1	24	15.58	15.66	15.74		
5	QPSK	12	0	15.58	15.78	15.67	17.00	0
5	QPSK	12	7	15.71	15.78	15.74		
5	QPSK	12	13	15.67	15.74	15.74		
5	QPSK	25	0	15.73	15.70	15.78		
5	16QAM	1	0	16.02	16.12	16.15	17.00	0
5	16QAM	1	12	15.93	16.19	16.15		
5	16QAM	1	24	16.01	16.10	16.14		
5	16QAM	12	0	15.70	15.86	15.87	17.00	0
5	16QAM	12	7	15.87	15.86	15.93		
5	16QAM	12	13	15.80	15.87	15.85		
5	16QAM	25	0	15.76	15.91	15.83		
5	64QAM	1	0	15.99	16.08	15.90	17.00	0
5	64QAM	1	12	15.92	16.09	16.13		
5	64QAM	1	24	15.92	16.03	15.99		
5	64QAM	12	0	15.79	15.89	15.91	17.00	0
5	64QAM	12	7	15.91	15.87	15.89		
5	64QAM	12	13	15.82	15.84	15.95		
5	64QAM	25	0	15.80	15.83	15.84		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	16.07	16.16	16.03	17.00	0
3	QPSK	1	8	15.52	15.75	15.82		
3	QPSK	1	14	15.59	15.67	15.67		
3	QPSK	8	0	15.65	15.77	15.70	17.00	0
3	QPSK	8	4	15.71	15.76	15.71		
3	QPSK	8	7	15.63	15.73	15.80		
3	QPSK	15	0	15.68	15.72	15.68		
3	16QAM	1	0	16.06	16.05	16.17	17.00	0
3	16QAM	1	8	16.00	16.18	16.19		
3	16QAM	1	14	15.98	16.06	16.17		
3	16QAM	8	0	15.77	15.91	15.83	17.00	0
3	16QAM	8	4	15.84	15.91	15.86		
3	16QAM	8	7	15.76	15.88	15.87		
3	16QAM	15	0	15.85	15.87	15.84		
3	64QAM	1	0	15.97	16.07	15.97	17.00	0
3	64QAM	1	8	15.92	16.11	16.08		
3	64QAM	1	14	15.92	15.99	16.00		
3	64QAM	8	0	15.77	15.88	15.91	17.00	0
3	64QAM	8	4	15.83	15.93	15.92		
3	64QAM	8	7	15.77	15.82	15.95		
3	64QAM	15	0	15.82	15.89	15.82		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	16.05	16.18	16.06	17.00	0
1.4	QPSK	1	3	15.61	15.73	15.76		
1.4	QPSK	1	5	15.65	15.65	15.65		
1.4	QPSK	3	0	15.61	15.81	15.73		
1.4	QPSK	3	1	15.67	15.68	15.69		
1.4	QPSK	3	3	15.62	15.68	15.81		
1.4	QPSK	6	0	15.73	15.73	15.75	17.00	0
1.4	16QAM	1	0	16.00	16.06	16.21	17.00	0
1.4	16QAM	1	3	16.02	16.09	16.18		
1.4	16QAM	1	5	16.00	16.10	16.16		
1.4	16QAM	3	0	15.76	15.88	15.84		
1.4	16QAM	3	1	15.80	15.93	15.91		
1.4	16QAM	3	3	15.78	15.87	15.88		
1.4	16QAM	6	0	15.80	15.84	15.81	17.00	0
1.4	64QAM	1	0	15.96	16.03	15.98	17.00	0
1.4	64QAM	1	3	15.93	16.05	16.05		
1.4	64QAM	1	5	15.88	16.05	15.90		
1.4	64QAM	3	0	15.79	15.94	15.88		
1.4	64QAM	3	1	15.84	15.89	15.85		
1.4	64QAM	3	3	15.85	15.81	15.93		
1.4	64QAM	6	0	15.88	15.83	15.88	17.00	0

<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	19.64	19.39	19.53	20.50	0
20	QPSK	1	49	19.68	19.41	19.56		
20	QPSK	1	99	19.59	19.40	19.52		
20	QPSK	50	0	19.79	19.51	19.63	20.50	0
20	QPSK	50	24	19.77	19.50	19.62		
20	QPSK	50	50	19.70	19.50	19.57		
20	QPSK	100	0	19.70	19.50	19.60		
20	16QAM	1	0	20.04	19.86	19.83	20.50	0
20	16QAM	1	49	20.01	19.79	19.86		
20	16QAM	1	99	19.89	19.79	19.88		
20	16QAM	50	0	19.85	19.58	19.68	20.50	0
20	16QAM	50	24	19.82	19.56	19.71		
20	16QAM	50	50	19.78	19.55	19.66		
20	16QAM	100	0	19.78	19.55	19.68		
20	64QAM	1	0	19.65	19.72	19.84	20.50	0
20	64QAM	1	49	19.97	19.74	19.79		
20	64QAM	1	99	19.85	19.68	19.78		
20	64QAM	50	0	19.89	19.61	19.70	20.50	0
20	64QAM	50	24	19.87	19.59	19.70		
20	64QAM	50	50	19.79	19.60	19.69		
20	64QAM	100	0	19.81	19.60	19.70		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	19.59	19.30	19.51	20.50	0
15	QPSK	1	37	19.63	19.40	19.54		
15	QPSK	1	74	19.49	19.35	19.43		
15	QPSK	36	0	19.71	19.48	19.62	20.50	0
15	QPSK	36	20	19.72	19.45	19.56		
15	QPSK	36	39	19.67	19.43	19.55		
15	QPSK	75	0	19.61	19.48	19.56		
15	16QAM	1	0	19.97	19.78	19.79	20.50	0
15	16QAM	1	37	19.96	19.79	19.78		
15	16QAM	1	74	19.82	19.71	19.86		
15	16QAM	36	0	19.85	19.48	19.65	20.50	0
15	16QAM	36	20	19.82	19.48	19.66		
15	16QAM	36	39	19.69	19.46	19.60		
15	16QAM	75	0	19.74	19.51	19.62		
15	64QAM	1	0	19.60	19.66	19.77	20.50	0
15	64QAM	1	37	19.92	19.73	19.71		
15	64QAM	1	74	19.75	19.61	19.73		
15	64QAM	36	0	19.81	19.60	19.67	20.50	0
15	64QAM	36	20	19.78	19.56	19.68		
15	64QAM	36	39	19.75	19.50	19.68		
15	64QAM	75	0	19.80	19.55	19.61		

Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	19.58	19.37	19.50	20.50	0
10	QPSK	1	25	19.62	19.40	19.49		
10	QPSK	1	49	19.54	19.39	19.44		
10	QPSK	25	0	19.71	19.44	19.56	20.50	0
10	QPSK	25	12	19.75	19.47	19.61		
10	QPSK	25	25	19.68	19.44	19.51		
10	QPSK	50	0	19.65	19.42	19.54		
10	16QAM	1	0	20.00	19.77	19.77	20.50	0
10	16QAM	1	25	19.92	19.70	19.81		
10	16QAM	1	49	19.80	19.74	19.82		
10	16QAM	25	0	19.76	19.58	19.68	20.50	0
10	16QAM	25	12	19.74	19.53	19.63		
10	16QAM	25	25	19.75	19.49	19.59		
10	16QAM	50	0	19.75	19.47	19.63		
10	64QAM	1	0	19.57	19.71	19.82	20.50	0
10	64QAM	1	25	19.89	19.72	19.77		
10	64QAM	1	49	19.79	19.58	19.77		
10	64QAM	25	0	19.86	19.56	19.67	20.50	0
10	64QAM	25	12	19.82	19.55	19.61		
10	64QAM	25	25	19.79	19.53	19.61		
10	64QAM	50	0	19.77	19.58	19.67		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	19.64	19.34	19.46	20.50	0
5	QPSK	1	12	19.60	19.40	19.52		
5	QPSK	1	24	19.51	19.35	19.45		
5	QPSK	12	0	19.74	19.44	19.57	20.50	0
5	QPSK	12	7	19.71	19.46	19.52		
5	QPSK	12	13	19.63	19.44	19.48		
5	QPSK	25	0	19.66	19.44	19.54		
5	16QAM	1	0	19.95	19.78	19.76	20.50	0
5	16QAM	1	12	19.96	19.73	19.77		
5	16QAM	1	24	19.87	19.71	19.85		
5	16QAM	12	0	19.80	19.54	19.66	20.50	0
5	16QAM	12	7	19.73	19.54	19.62		
5	16QAM	12	13	19.75	19.54	19.56		
5	16QAM	25	0	19.77	19.51	19.60		
5	64QAM	1	0	19.64	19.68	19.81	20.50	0
5	64QAM	1	12	19.94	19.67	19.78		
5	64QAM	1	24	19.83	19.58	19.78		
5	64QAM	12	0	19.81	19.57	19.65	20.50	0
5	64QAM	12	7	19.79	19.53	19.65		
5	64QAM	12	13	19.78	19.57	19.61		
5	64QAM	25	0	19.74	19.59	19.63		

Hotspot Power Mode

<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	14.82	15.09	15.14	16.00	0
20	QPSK	1	49	14.74	14.98	14.97		
20	QPSK	1	99	14.81	15.08	14.97		
20	QPSK	50	0	14.85	15.01	15.02	16.00	0
20	QPSK	50	24	14.78	15.00	14.99		
20	QPSK	50	50	14.83	14.96	14.96		
20	QPSK	100	0	14.76	14.95	14.97		
20	16QAM	1	0	15.00	15.23	15.38	16.00	0
20	16QAM	1	49	15.17	15.39	15.34		
20	16QAM	1	99	15.14	15.41	15.41		
20	16QAM	50	0	14.91	15.10	15.11	16.00	0
20	16QAM	50	24	14.90	15.16	15.09		
20	16QAM	50	50	14.94	15.09	15.09		
20	16QAM	100	0	14.85	15.08	15.09		
20	64QAM	1	0	14.90	15.09	15.23	16.00	0
20	64QAM	1	49	14.98	15.18	15.18		
20	64QAM	1	99	15.08	15.31	15.18		
20	64QAM	50	0	14.88	15.10	15.10	16.00	0
20	64QAM	50	24	14.91	15.14	15.12		
20	64QAM	50	50	14.96	15.08	15.08		
20	64QAM	100	0	14.86	15.09	15.11		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	14.81	15.00	15.09	16.00	0
15	QPSK	1	37	14.69	14.89	14.96		
15	QPSK	1	74	14.72	14.99	14.95		
15	QPSK	36	0	14.78	14.94	14.95	16.00	0
15	QPSK	36	20	14.72	14.90	14.97		
15	QPSK	36	39	14.79	14.92	14.86		
15	QPSK	75	0	14.74	14.92	14.93		
15	16QAM	1	0	15.00	15.14	15.36	16.00	0
15	16QAM	1	37	15.13	15.31	15.26		
15	16QAM	1	74	15.09	15.38	15.31		
15	16QAM	36	0	14.89	15.02	15.06	16.00	0
15	16QAM	36	20	14.84	15.12	15.05		
15	16QAM	36	39	14.85	15.05	14.99		
15	16QAM	75	0	14.78	15.03	15.03		
15	64QAM	1	0	14.89	15.00	15.15	16.00	0
15	64QAM	1	37	14.89	15.12	15.13		
15	64QAM	1	74	15.06	15.25	15.13		
15	64QAM	36	0	14.79	15.09	15.06	16.00	0
15	64QAM	36	20	14.83	15.14	15.09		
15	64QAM	36	39	14.91	15.01	15.08		
15	64QAM	75	0	14.85	14.99	15.10		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	14.81	15.00	15.14	16.00	0
10	QPSK	1	25	14.73	14.96	14.94		
10	QPSK	1	49	14.78	14.98	14.97		
10	QPSK	25	0	14.79	14.94	15.02	16.00	0
10	QPSK	25	12	14.73	14.98	14.98		
10	QPSK	25	25	14.79	14.93	14.96		
10	QPSK	50	0	14.75	14.94	14.87		
10	16QAM	1	0	14.93	15.16	15.30	16.00	0
10	16QAM	1	25	15.16	15.30	15.31		
10	16QAM	1	49	15.12	15.35	15.31		
10	16QAM	25	0	14.91	15.04	15.09	16.00	0
10	16QAM	25	12	14.84	15.10	15.00		
10	16QAM	25	25	14.91	15.03	15.00		
10	16QAM	50	0	14.79	14.99	15.01		
10	64QAM	1	0	14.84	15.05	15.15	16.00	0
10	64QAM	1	25	14.92	15.08	15.16		
10	64QAM	1	49	15.06	15.25	15.11		
10	64QAM	25	0	14.83	15.07	15.05	16.00	0
10	64QAM	25	12	14.86	15.08	15.11		
10	64QAM	25	25	14.95	15.03	15.04		
10	64QAM	50	0	14.79	15.02	15.08		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	14.76	15.04	15.11	16.00	0
5	QPSK	1	12	14.66	14.94	14.94		
5	QPSK	1	24	14.77	15.07	14.94		
5	QPSK	12	0	14.84	14.96	14.96	16.00	0
5	QPSK	12	7	14.74	14.92	14.95		
5	QPSK	12	13	14.83	14.92	14.95		
5	QPSK	25	0	14.72	14.93	14.92		
5	16QAM	1	0	14.96	15.19	15.35	16.00	0
5	16QAM	1	12	15.16	15.32	15.34		
5	16QAM	1	24	15.12	15.39	15.36		
5	16QAM	12	0	14.88	15.05	15.08	16.00	0
5	16QAM	12	7	14.83	15.07	15.04		
5	16QAM	12	13	14.87	15.07	15.02		
5	16QAM	25	0	14.84	15.00	15.05		
5	64QAM	1	0	14.84	15.03	15.23	16.00	0
5	64QAM	1	12	14.91	15.15	15.10		
5	64QAM	1	24	15.00	15.29	15.11		
5	64QAM	12	0	14.78	15.06	15.00	16.00	0
5	64QAM	12	7	14.87	15.10	15.03		
5	64QAM	12	13	14.93	15.04	15.01		
5	64QAM	25	0	14.80	14.99	15.02		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	14.80	15.02	15.14	16.00	0
3	QPSK	1	8	14.72	14.90	14.90		
3	QPSK	1	14	14.80	15.03	14.93		
3	QPSK	8	0	14.79	14.95	14.95	16.00	0
3	QPSK	8	4	14.77	14.95	14.96		
3	QPSK	8	7	14.73	14.92	14.93		
3	QPSK	15	0	14.67	14.93	14.88		
3	16QAM	1	0	14.92	15.15	15.36	16.00	0
3	16QAM	1	8	15.10	15.39	15.31		
3	16QAM	1	14	15.09	15.33	15.34		
3	16QAM	8	0	14.82	15.07	15.08	16.00	0
3	16QAM	8	4	14.88	15.10	15.01		
3	16QAM	8	7	14.86	15.06	14.99		
3	16QAM	15	0	14.77	15.08	15.01		
3	64QAM	1	0	14.81	15.02	15.22	16.00	0
3	64QAM	1	8	14.97	15.10	15.11		
3	64QAM	1	14	14.99	15.23	15.12		
3	64QAM	8	0	14.82	15.05	15.04	16.00	0
3	64QAM	8	4	14.85	15.08	15.05		
3	64QAM	8	7	14.91	15.02	15.04		
3	64QAM	15	0	14.77	15.03	15.11		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	14.80	15.04	15.12	16.00	0
1.4	QPSK	1	3	14.65	14.94	14.88		
1.4	QPSK	1	5	14.80	15.00	14.91		
1.4	QPSK	3	0	14.78	14.95	15.00		
1.4	QPSK	3	1	14.75	14.94	14.93		
1.4	QPSK	3	3	14.76	14.87	14.92		
1.4	QPSK	6	0	14.70	14.94	14.89	16.00	0
1.4	16QAM	1	0	14.90	15.17	15.34	16.00	0
1.4	16QAM	1	3	15.13	15.33	15.25		
1.4	16QAM	1	5	15.13	15.32	15.41		
1.4	16QAM	3	0	14.83	15.10	15.07		
1.4	16QAM	3	1	14.82	15.06	15.00		
1.4	16QAM	3	3	14.87	15.00	14.99		
1.4	16QAM	6	0	14.79	15.07	15.04	16.00	0
1.4	64QAM	1	0	14.82	14.99	15.20	16.00	0
1.4	64QAM	1	3	14.89	15.14	15.13		
1.4	64QAM	1	5	14.99	15.28	15.08		
1.4	64QAM	3	0	14.84	15.00	15.03		
1.4	64QAM	3	1	14.89	15.04	15.12		
1.4	64QAM	3	3	14.90	15.06	15.02		
1.4	64QAM	6	0	14.79	15.00	15.07	16.00	0

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300		
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	14.02	14.14	14.11	15.00	0
20	QPSK	1	49	13.81	13.99	14.04		
20	QPSK	1	99	13.87	13.94	13.95		
20	QPSK	50	0	13.86	14.03	13.96	15.00	0
20	QPSK	50	24	13.94	13.98	13.96		
20	QPSK	50	50	13.92	13.97	14.02		
20	QPSK	100	0	13.96	13.97	13.98		
20	16QAM	1	0	14.28	14.33	14.42	15.00	0
20	16QAM	1	49	14.23	14.39	14.41		
20	16QAM	1	99	14.22	14.36	14.38		
20	16QAM	50	0	13.99	14.14	14.09	15.00	0
20	16QAM	50	24	14.10	14.15	14.13		
20	16QAM	50	50	14.03	14.11	14.15		
20	16QAM	100	0	14.06	14.13	14.09		
20	64QAM	1	0	14.20	14.30	14.19	15.00	0
20	64QAM	1	49	14.18	14.34	14.34		
20	64QAM	1	99	14.15	14.26	14.20		
20	64QAM	50	0	14.03	14.15	14.14	15.00	0
20	64QAM	50	24	14.12	14.15	14.14		
20	64QAM	50	50	14.05	14.09	14.16		
20	64QAM	100	0	14.08	14.12	14.10		
Channel				20025	20175	20325	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	13.99	14.07	14.06	15.00	0
15	QPSK	1	37	13.72	13.90	13.96		
15	QPSK	1	74	13.83	13.88	13.93		
15	QPSK	36	0	13.79	13.95	13.91	15.00	0
15	QPSK	36	20	13.87	13.94	13.88		
15	QPSK	36	39	13.84	13.94	13.99		
15	QPSK	75	0	13.96	13.97	13.92		
15	16QAM	1	0	14.22	14.28	14.37	15.00	0
15	16QAM	1	37	14.16	14.33	14.32		
15	16QAM	1	74	14.14	14.35	14.36		
15	16QAM	36	0	13.97	14.10	14.00	15.00	0
15	16QAM	36	20	14.01	14.11	14.04		
15	16QAM	36	39	13.99	14.04	14.13		
15	16QAM	75	0	14.05	14.07	14.08		
15	64QAM	1	0	14.14	14.20	14.11	15.00	0
15	64QAM	1	37	14.10	14.29	14.26		
15	64QAM	1	74	14.14	14.19	14.11		
15	64QAM	36	0	14.01	14.07	14.12	15.00	0
15	64QAM	36	20	14.10	14.09	14.11		
15	64QAM	36	39	14.01	14.08	14.08		
15	64QAM	75	0	14.06	14.08	14.03		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	13.93	14.09	14.04	15.00	0
10	QPSK	1	25	13.72	13.89	14.02		
10	QPSK	1	49	13.80	13.93	13.90		
10	QPSK	25	0	13.83	14.01	13.90	15.00	0
10	QPSK	25	12	13.92	13.97	13.95		
10	QPSK	25	25	13.90	13.91	14.01		
10	QPSK	50	0	13.89	13.91	13.98		
10	16QAM	1	0	14.22	14.32	14.42	15.00	0
10	16QAM	1	25	14.15	14.35	14.32		
10	16QAM	1	49	14.18	14.30	14.33		
10	16QAM	25	0	13.97	14.07	14.03	15.00	0
10	16QAM	25	12	14.01	14.06	14.05		
10	16QAM	25	25	13.99	14.06	14.10		
10	16QAM	50	0	14.01	14.07	14.07		
10	64QAM	1	0	14.12	14.28	14.12	15.00	0
10	64QAM	1	25	14.14	14.26	14.31		
10	64QAM	1	49	14.09	14.19	14.18		
10	64QAM	25	0	13.95	14.12	14.04	15.00	0
10	64QAM	25	12	14.03	14.11	14.12		
10	64QAM	25	25	13.97	14.02	14.06		
10	64QAM	50	0	13.99	14.08	14.01		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	13.93	14.14	14.07	15.00	0
5	QPSK	1	12	13.76	13.98	13.97		
5	QPSK	1	24	13.81	13.94	13.88		
5	QPSK	12	0	13.82	13.98	13.88	15.00	0
5	QPSK	12	7	13.87	13.96	13.88		
5	QPSK	12	13	13.88	13.88	13.94		
5	QPSK	25	0	13.95	13.92	13.95		
5	16QAM	1	0	14.22	14.26	14.41	15.00	0
5	16QAM	1	12	14.15	14.38	14.39		
5	16QAM	1	24	14.19	14.34	14.37		
5	16QAM	12	0	13.99	14.12	14.08	15.00	0
5	16QAM	12	7	14.08	14.08	14.08		
5	16QAM	12	13	14.00	14.01	14.14		
5	16QAM	25	0	13.97	14.06	14.01		
5	64QAM	1	0	14.18	14.27	14.09	15.00	0
5	64QAM	1	12	14.09	14.29	14.26		
5	64QAM	1	24	14.10	14.24	14.11		
5	64QAM	12	0	13.99	14.10	14.09	15.00	0
5	64QAM	12	7	14.04	14.11	14.13		
5	64QAM	12	13	14.04	13.99	14.08		
5	64QAM	25	0	13.99	14.10	14.07		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	13.93	14.08	14.02	15.00	0
3	QPSK	1	8	13.81	13.96	13.97		
3	QPSK	1	14	13.81	13.88	13.94		
3	QPSK	8	0	13.79	13.98	13.90	15.00	0
3	QPSK	8	4	13.85	13.95	13.96		
3	QPSK	8	7	13.88	13.96	14.00		
3	QPSK	15	0	13.91	13.92	13.97		
3	16QAM	1	0	14.27	14.32	14.35	15.00	0
3	16QAM	1	8	14.20	14.33	14.34		
3	16QAM	1	14	14.21	14.32	14.31		
3	16QAM	8	0	13.92	14.08	14.01	15.00	0
3	16QAM	8	4	14.01	14.10	14.12		
3	16QAM	8	7	14.03	14.08	14.08		
3	16QAM	15	0	14.01	14.08	14.06		
3	64QAM	1	0	14.19	14.20	14.18	15.00	0
3	64QAM	1	8	14.08	14.27	14.30		
3	64QAM	1	14	14.08	14.25	14.16		
3	64QAM	8	0	14.02	14.07	14.09	15.00	0
3	64QAM	8	4	14.06	14.10	14.13		
3	64QAM	8	7	14.04	14.06	14.12		
3	64QAM	15	0	14.00	14.11	14.06		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	14.00	14.09	14.04	15.00	0
1.4	QPSK	1	3	13.72	13.98	13.97		
1.4	QPSK	1	5	13.78	13.87	13.94		
1.4	QPSK	3	0	13.76	14.01	13.95		
1.4	QPSK	3	1	13.85	13.97	13.94		
1.4	QPSK	3	3	13.83	13.88	14.02		
1.4	QPSK	6	0	13.92	13.90	13.89	15.00	0
1.4	16QAM	1	0	14.20	14.28	14.38	15.00	0
1.4	16QAM	1	3	14.19	14.33	14.35		
1.4	16QAM	1	5	14.14	14.31	14.30		
1.4	16QAM	3	0	13.95	14.04	13.99		
1.4	16QAM	3	1	14.04	14.07	14.13		
1.4	16QAM	3	3	13.99	14.05	14.12		
1.4	16QAM	6	0	13.99	14.09	14.01	15.00	0
1.4	64QAM	1	0	14.15	14.25	14.18	15.00	0
1.4	64QAM	1	3	14.11	14.29	14.30		
1.4	64QAM	1	5	14.07	14.17	14.17		
1.4	64QAM	3	0	13.97	14.10	14.06		
1.4	64QAM	3	1	14.03	14.14	14.06		
1.4	64QAM	3	3	14.02	14.02	14.07		
1.4	64QAM	6	0	14.07	14.09	14.02	15.00	0

<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	19.64	19.39	19.53	20.50	0
20	QPSK	1	49	19.68	19.41	19.56		
20	QPSK	1	99	19.59	19.40	19.52		
20	QPSK	50	0	19.79	19.51	19.63	20.50	0
20	QPSK	50	24	19.77	19.50	19.62		
20	QPSK	50	50	19.70	19.50	19.57		
20	QPSK	100	0	19.70	19.50	19.60		
20	16QAM	1	0	20.04	19.86	19.83	20.50	0
20	16QAM	1	49	20.01	19.79	19.86		
20	16QAM	1	99	19.89	19.79	19.88		
20	16QAM	50	0	19.85	19.58	19.68	20.50	0
20	16QAM	50	24	19.82	19.56	19.71		
20	16QAM	50	50	19.78	19.55	19.66		
20	16QAM	100	0	19.78	19.55	19.68		
20	64QAM	1	0	19.65	19.72	19.84	20.50	0
20	64QAM	1	49	19.97	19.74	19.79		
20	64QAM	1	99	19.85	19.68	19.78		
20	64QAM	50	0	19.89	19.61	19.70	20.50	0
20	64QAM	50	24	19.87	19.59	19.70		
20	64QAM	50	50	19.79	19.60	19.69		
20	64QAM	100	0	19.81	19.60	19.70		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	19.58	19.38	19.48	20.50	0
15	QPSK	1	37	19.58	19.35	19.50		
15	QPSK	1	74	19.54	19.37	19.49		
15	QPSK	36	0	19.77	19.47	19.53	20.50	0
15	QPSK	36	20	19.70	19.40	19.53		
15	QPSK	36	39	19.65	19.44	19.50		
15	QPSK	75	0	19.64	19.41	19.51		
15	16QAM	1	0	20.01	19.77	19.78	20.50	0
15	16QAM	1	37	19.93	19.73	19.79		
15	16QAM	1	74	19.88	19.78	19.80		
15	16QAM	36	0	19.81	19.49	19.63	20.50	0
15	16QAM	36	20	19.79	19.47	19.66		
15	16QAM	36	39	19.75	19.48	19.63		
15	16QAM	75	0	19.78	19.45	19.61		
15	64QAM	1	0	19.59	19.64	19.75	20.50	0
15	64QAM	1	37	19.93	19.69	19.75		
15	64QAM	1	74	19.80	19.66	19.74		
15	64QAM	36	0	19.88	19.55	19.61	20.50	0
15	64QAM	36	20	19.81	19.56	19.67		
15	64QAM	36	39	19.76	19.53	19.67		
15	64QAM	75	0	19.80	19.53	19.70		

Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	19.58	19.37	19.52	20.50	0
10	QPSK	1	25	19.64	19.35	19.48		
10	QPSK	1	49	19.58	19.39	19.52		
10	QPSK	25	0	19.76	19.51	19.58	20.50	0
10	QPSK	25	12	19.76	19.43	19.54		
10	QPSK	25	25	19.61	19.47	19.55		
10	QPSK	50	0	19.62	19.44	19.54		
10	16QAM	1	0	19.96	19.81	19.75	20.50	0
10	16QAM	1	25	19.95	19.74	19.80		
10	16QAM	1	49	19.84	19.73	19.83		
10	16QAM	25	0	19.77	19.49	19.61	20.50	0
10	16QAM	25	12	19.75	19.56	19.62		
10	16QAM	25	25	19.68	19.46	19.56		
10	16QAM	50	0	19.71	19.49	19.66		
10	64QAM	1	0	19.59	19.67	19.81	20.50	0
10	64QAM	1	25	19.94	19.72	19.78		
10	64QAM	1	49	19.81	19.59	19.69		
10	64QAM	25	0	19.89	19.60	19.63	20.50	0
10	64QAM	25	12	19.78	19.50	19.63		
10	64QAM	25	25	19.72	19.56	19.60		
10	64QAM	50	0	19.75	19.58	19.60		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	19.60	19.32	19.47	20.50	0
5	QPSK	1	12	19.61	19.39	19.46		
5	QPSK	1	24	19.52	19.31	19.50		
5	QPSK	12	0	19.70	19.45	19.58	20.50	0
5	QPSK	12	7	19.74	19.48	19.55		
5	QPSK	12	13	19.60	19.48	19.50		
5	QPSK	25	0	19.66	19.41	19.52		
5	16QAM	1	0	20.00	19.81	19.78	20.50	0
5	16QAM	1	12	19.98	19.74	19.80		
5	16QAM	1	24	19.89	19.79	19.79		
5	16QAM	12	0	19.77	19.53	19.59	20.50	0
5	16QAM	12	7	19.72	19.49	19.70		
5	16QAM	12	13	19.73	19.46	19.57		
5	16QAM	25	0	19.69	19.52	19.68		
5	64QAM	1	0	19.55	19.63	19.83	20.50	0
5	64QAM	1	12	19.96	19.67	19.78		
5	64QAM	1	24	19.81	19.64	19.78		
5	64QAM	12	0	19.80	19.53	19.70	20.50	0
5	64QAM	12	7	19.86	19.57	19.61		
5	64QAM	12	13	19.78	19.58	19.64		
5	64QAM	25	0	19.73	19.59	19.68		

Product Specific Power Mode
<LTE Band 2>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				18700	18900	19100		
Frequency (MHz)				1860	1880	1900		
20	QPSK	1	0	19.72	20.00	20.04	21.50	0
20	QPSK	1	49	19.77	20.01	20.01		
20	QPSK	1	99	19.84	20.10	20.04		
20	QPSK	50	0	19.89	20.07	20.08	21.50	0
20	QPSK	50	24	19.82	20.06	20.06		
20	QPSK	50	50	19.85	20.00	20.04		
20	QPSK	100	0	19.83	20.01	20.06	21.50	0
20	16QAM	1	0	20.19	20.34	20.31		
20	16QAM	1	49	20.22	20.43	20.36		
20	16QAM	1	99	20.31	20.40	20.29	21.50	0
20	16QAM	50	0	19.96	20.17	20.15		
20	16QAM	50	24	20.00	20.22	20.16		
20	16QAM	50	50	19.99	20.16	20.10	21.50	0
20	16QAM	100	0	19.94	20.15	20.11		
20	64QAM	1	0	20.04	20.25	20.21		
20	64QAM	1	49	20.07	20.30	20.25	21.50	0
20	64QAM	1	99	20.15	20.28	20.21		
20	64QAM	50	0	19.01	19.22	19.14		
20	64QAM	50	24	19.05	19.19	19.13	21.00	0.5
20	64QAM	50	50	19.05	19.17	19.11		
20	64QAM	100	0	19.03	19.19	19.13		
Channel				18675	18900	19125	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1857.5	1880	1902.5		
15	QPSK	1	0	19.64	19.99	19.97	21.50	0
15	QPSK	1	37	19.74	19.97	19.97		
15	QPSK	1	74	19.76	20.06	19.99		
15	QPSK	36	0	19.84	20.01	19.99	21.50	0
15	QPSK	36	20	19.80	20.05	20.03		
15	QPSK	36	39	19.79	19.92	20.00		
15	QPSK	75	0	19.79	19.98	19.98	21.50	0
15	16QAM	1	0	20.10	20.29	20.30		
15	16QAM	1	37	20.15	20.35	20.33		
15	16QAM	1	74	20.26	20.30	20.22	21.50	0
15	16QAM	36	0	19.90	20.15	20.09		
15	16QAM	36	20	19.90	20.16	20.15		
15	16QAM	36	39	19.94	20.06	20.04	21.50	0
15	16QAM	75	0	19.91	20.13	20.04		
15	64QAM	1	0	20.00	20.20	20.19		
15	64QAM	1	37	19.99	20.25	20.16	21.50	0
15	64QAM	1	74	20.14	20.24	20.15		
15	64QAM	36	0	19.03	19.18	19.10		
15	64QAM	36	20	19.06	19.18	19.12	21.00	0.5
15	64QAM	36	39	19.06	19.15	19.07		
15	64QAM	75	0	19.03	19.14	19.05		

Channel				18650	18900	19150	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1855	1880	1905		
10	QPSK	1	0	19.66	19.92	20.03	21.50	0
10	QPSK	1	25	19.73	19.92	19.92		
10	QPSK	1	49	19.80	20.01	20.01		
10	QPSK	25	0	19.87	19.99	20.03	21.50	0
10	QPSK	25	12	19.78	20.03	20.03		
10	QPSK	25	25	19.79	19.96	19.98		
10	QPSK	50	0	19.78	19.99	19.99		
10	16QAM	1	0	20.10	20.32	20.24	21.50	0
10	16QAM	1	25	20.16	20.34	20.35		
10	16QAM	1	49	20.29	20.32	20.28		
10	16QAM	25	0	19.92	20.09	20.07	21.50	0
10	16QAM	25	12	19.94	20.15	20.11		
10	16QAM	25	25	19.97	20.13	20.08		
10	16QAM	50	0	19.93	20.14	20.07		
10	64QAM	1	0	20.01	20.23	20.14	21.50	0
10	64QAM	1	25	20.02	20.27	20.16		
10	64QAM	1	49	20.07	20.21	20.14		
10	64QAM	25	0	19.02	19.18	19.06	21.00	0.5
10	64QAM	25	12	19.07	19.09	19.13		
10	64QAM	25	25	19.04	19.09	19.01		
10	64QAM	50	0	19.05	19.17	19.05		
Channel				18625	18900	19175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1852.5	1880	1907.5		
5	QPSK	1	0	19.69	19.95	20.01	21.50	0
5	QPSK	1	12	19.76	19.94	19.98		
5	QPSK	1	24	19.78	20.07	19.95		
5	QPSK	12	0	19.80	20.06	20.03	21.50	0
5	QPSK	12	7	19.75	20.01	19.98		
5	QPSK	12	13	19.85	19.90	19.98		
5	QPSK	25	0	19.74	20.00	20.02		
5	16QAM	1	0	20.09	20.26	20.22	21.50	0
5	16QAM	1	12	20.15	20.33	20.26		
5	16QAM	1	24	20.23	20.39	20.20		
5	16QAM	12	0	19.95	20.13	20.08	21.50	0
5	16QAM	12	7	19.97	20.15	20.07		
5	16QAM	12	13	19.90	20.08	20.02		
5	16QAM	25	0	19.92	20.11	20.10		
5	64QAM	1	0	19.99	20.19	20.19	21.50	0
5	64QAM	1	12	20.00	20.26	20.18		
5	64QAM	1	24	20.12	20.25	20.13		
5	64QAM	12	0	19.01	19.18	19.12	21.00	0.5
5	64QAM	12	7	19.05	19.17	19.09		
5	64QAM	12	13	19.07	19.16	19.07		
5	64QAM	25	0	19.03	19.16	19.04		

Channel				18615	18900	19185	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1851.5	1880	1908.5		
3	QPSK	1	0	19.68	19.96	19.99	21.50	0
3	QPSK	1	8	19.72	19.92	19.96		
3	QPSK	1	14	19.82	20.07	19.98		
3	QPSK	8	0	19.84	20.05	20.05	21.50	0
3	QPSK	8	4	19.79	20.01	20.02		
3	QPSK	8	7	19.84	19.98	19.99		
3	QPSK	15	0	19.79	19.93	20.03		
3	16QAM	1	0	20.17	20.25	20.25	21.50	0
3	16QAM	1	8	20.15	20.36	20.27		
3	16QAM	1	14	20.27	20.30	20.27		
3	16QAM	8	0	19.88	20.13	20.05	21.50	0
3	16QAM	8	4	19.96	20.18	20.12		
3	16QAM	8	7	19.91	20.15	20.05		
3	16QAM	15	0	19.90	20.11	20.11		
3	64QAM	1	0	20.00	20.23	20.17	21.50	0
3	64QAM	1	8	20.03	20.28	20.22		
3	64QAM	1	14	20.08	20.28	20.19		
3	64QAM	8	0	19.02	19.21	19.11	21.00	0.5
3	64QAM	8	4	19.04	19.12	19.07		
3	64QAM	8	7	19.07	19.11	19.10		
3	64QAM	15	0	19.04	19.16	19.04		
Channel				18607	18900	19193	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1850.7	1880	1909.3		
1.4	QPSK	1	0	19.68	19.98	20.00	21.50	0
1.4	QPSK	1	3	19.71	19.95	19.91		
1.4	QPSK	1	5	19.80	20.07	20.03		
1.4	QPSK	3	0	19.88	20.07	20.06		
1.4	QPSK	3	1	19.81	19.99	19.97		
1.4	QPSK	3	3	19.75	19.92	20.01		
1.4	QPSK	6	0	19.78	20.01	20.01	21.50	0
1.4	16QAM	1	0	20.15	20.32	20.23	21.50	0
1.4	16QAM	1	3	20.13	20.41	20.29		
1.4	16QAM	1	5	20.31	20.31	20.27		
1.4	16QAM	3	0	19.90	20.07	20.10		
1.4	16QAM	3	1	19.92	20.17	20.07		
1.4	16QAM	3	3	19.94	20.13	20.06		
1.4	16QAM	6	0	19.87	20.05	20.10	21.50	0
1.4	64QAM	1	0	19.96	20.20	20.21	21.50	0
1.4	64QAM	1	3	20.00	20.27	20.24		
1.4	64QAM	1	5	19.89	20.15	20.07		
1.4	64QAM	3	0	20.00	20.15	20.12		
1.4	64QAM	3	1	20.00	20.30	20.16		
1.4	64QAM	3	3	20.15	20.25	20.18		
1.4	64QAM	6	0	19.08	19.13	19.11	21.00	0.5

<LTE Band 4>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20050	20175	20300	20.00	0
Frequency (MHz)				1720	1732.5	1745		
20	QPSK	1	0	19.37	19.49	19.42	20.00	0
20	QPSK	1	49	19.32	19.41	19.45		
20	QPSK	1	99	19.31	19.31	19.35		
20	QPSK	50	0	19.35	19.45	19.42	20.00	0
20	QPSK	50	24	19.41	19.45	19.40		
20	QPSK	50	50	19.38	19.39	19.42		
20	QPSK	100	0	19.42	19.44	19.39	20.00	0
20	16QAM	1	0	19.78	19.92	19.88		
20	16QAM	1	49	19.75	19.88	19.92		
20	16QAM	1	99	19.75	19.80	19.82	20.00	0
20	16QAM	50	0	19.47	19.59	19.58		
20	16QAM	50	24	19.57	19.60	19.57		
20	16QAM	50	50	19.50	19.55	19.60	20.00	0
20	16QAM	100	0	19.54	19.56	19.51		
20	64QAM	1	0	19.71	19.86	19.79		
20	64QAM	1	49	19.67	19.79	19.80	20.00	0
20	64QAM	1	99	19.65	19.67	19.74		
20	64QAM	50	0	19.52	19.62	19.56		
20	64QAM	50	24	19.59	19.61	19.60	20.00	0
20	64QAM	50	50	19.54	19.54	19.62		
20	64QAM	100	0	19.55	19.57	19.54		
Channel				20025	20175	20325	20.00	0
Frequency (MHz)				1717.5	1732.5	1747.5		
15	QPSK	1	0	19.33	19.42	19.42	20.00	0
15	QPSK	1	37	19.31	19.34	19.36		
15	QPSK	1	74	19.29	19.29	19.33		
15	QPSK	36	0	19.30	19.40	19.33	20.00	0
15	QPSK	36	20	19.34	19.40	19.34		
15	QPSK	36	39	19.28	19.35	19.40		
15	QPSK	75	0	19.41	19.37	19.35	20.00	0
15	16QAM	1	0	19.78	19.92	19.82		
15	16QAM	1	37	19.69	19.79	19.83		
15	16QAM	1	74	19.67	19.71	19.73	20.00	0
15	16QAM	36	0	19.47	19.56	19.51		
15	16QAM	36	20	19.48	19.57	19.56		
15	16QAM	36	39	19.46	19.46	19.58	20.00	0
15	16QAM	75	0	19.53	19.48	19.42		
15	64QAM	1	0	19.62	19.76	19.77		
15	64QAM	1	37	19.59	19.77	19.72	20.00	0
15	64QAM	1	74	19.59	19.65	19.64		
15	64QAM	36	0	19.44	19.57	19.50		
15	64QAM	36	20	19.58	19.52	19.59	20.00	0
15	64QAM	36	39	19.48	19.49	19.60		
15	64QAM	75	0	19.54	19.54	19.49		

Channel				20000	20175	20350	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1715	1732.5	1750		
10	QPSK	1	0	19.35	19.48	19.42	20.00	0
10	QPSK	1	25	19.27	19.36	19.35		
10	QPSK	1	49	19.24	19.29	19.34		
10	QPSK	25	0	19.33	19.42	19.39	20.00	0
10	QPSK	25	12	19.38	19.37	19.36		
10	QPSK	25	25	19.30	19.31	19.38		
10	QPSK	50	0	19.33	19.35	19.34		
10	16QAM	1	0	19.70	19.86	19.87	20.00	0
10	16QAM	1	25	19.73	19.86	19.84		
10	16QAM	1	49	19.67	19.77	19.75		
10	16QAM	25	0	19.45	19.54	19.56	20.00	0
10	16QAM	25	12	19.56	19.54	19.55		
10	16QAM	25	25	19.46	19.53	19.55		
10	16QAM	50	0	19.50	19.50	19.50		
10	64QAM	1	0	19.62	19.81	19.72	20.00	0
10	64QAM	1	25	19.64	19.70	19.75		
10	64QAM	1	49	19.58	19.64	19.67		
10	64QAM	25	0	19.49	19.53	19.55	20.00	0
10	64QAM	25	12	19.56	19.58	19.55		
10	64QAM	25	25	19.51	19.51	19.58		
10	64QAM	50	0	19.46	19.52	19.48		
Channel				19975	20175	20375	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1712.5	1732.5	1752.5		
5	QPSK	1	0	19.29	19.40	19.34	20.00	0
5	QPSK	1	12	19.30	19.37	19.35		
5	QPSK	1	24	19.30	19.27	19.25		
5	QPSK	12	0	19.34	19.37	19.32	20.00	0
5	QPSK	12	7	19.34	19.42	19.34		
5	QPSK	12	13	19.36	19.35	19.38		
5	QPSK	25	0	19.40	19.39	19.31		
5	16QAM	1	0	19.77	19.86	19.79	20.00	0
5	16QAM	1	12	19.66	19.82	19.87		
5	16QAM	1	24	19.75	19.73	19.73		
5	16QAM	12	0	19.43	19.50	19.55	20.00	0
5	16QAM	12	7	19.50	19.54	19.53		
5	16QAM	12	13	19.48	19.54	19.55		
5	16QAM	25	0	19.47	19.47	19.49		
5	64QAM	1	0	19.64	19.77	19.71	20.00	0
5	64QAM	1	12	19.60	19.72	19.72		
5	64QAM	1	24	19.62	19.58	19.66		
5	64QAM	12	0	19.45	19.60	19.51	20.00	0
5	64QAM	12	7	19.52	19.58	19.52		
5	64QAM	12	13	19.45	19.47	19.61		
5	64QAM	25	0	19.46	19.56	19.48		

Channel				19965	20175	20385	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1711.5	1732.5	1753.5		
3	QPSK	1	0	19.33	19.45	19.39	20.00	0
3	QPSK	1	8	19.27	19.32	19.37		
3	QPSK	1	14	19.30	19.30	19.30		
3	QPSK	8	0	19.33	19.36	19.32	20.00	0
3	QPSK	8	4	19.34	19.37	19.34		
3	QPSK	8	7	19.33	19.33	19.41		
3	QPSK	15	0	19.41	19.37	19.36		
3	16QAM	1	0	19.76	19.92	19.87	20.00	0
3	16QAM	1	8	19.68	19.83	19.86		
3	16QAM	1	14	19.66	19.72	19.78		
3	16QAM	8	0	19.41	19.58	19.51	20.00	0
3	16QAM	8	4	19.48	19.56	19.50		
3	16QAM	8	7	19.45	19.50	19.56		
3	16QAM	15	0	19.50	19.48	19.48		
3	64QAM	1	0	19.70	19.77	19.75	20.00	0
3	64QAM	1	8	19.59	19.77	19.77		
3	64QAM	1	14	19.60	19.63	19.68		
3	64QAM	8	0	19.44	19.53	19.53	20.00	0
3	64QAM	8	4	19.52	19.60	19.51		
3	64QAM	8	7	19.53	19.51	19.53		
3	64QAM	15	0	19.55	19.52	19.49		
Channel				19957	20175	20393	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				1710.7	1732.5	1754.3		
1.4	QPSK	1	0	19.30	19.47	19.38	20.00	0
1.4	QPSK	1	3	19.24	19.39	19.38		
1.4	QPSK	1	5	19.29	19.29	19.33		
1.4	QPSK	3	0	19.31	19.42	19.36		
1.4	QPSK	3	1	19.36	19.44	19.30		
1.4	QPSK	3	3	19.34	19.39	19.36		
1.4	QPSK	6	0	19.41	19.40	19.32	20.00	0
1.4	16QAM	1	0	19.76	19.90	19.79	20.00	0
1.4	16QAM	1	3	19.73	19.85	19.83		
1.4	16QAM	1	5	19.67	19.73	19.79		
1.4	16QAM	3	0	19.45	19.50	19.50		
1.4	16QAM	3	1	19.49	19.55	19.54		
1.4	16QAM	3	3	19.50	19.46	19.56		
1.4	16QAM	6	0	19.49	19.50	19.42	20.00	0
1.4	64QAM	1	0	19.68	19.80	19.74	20.00	0
1.4	64QAM	1	3	19.63	19.70	19.77		
1.4	64QAM	1	5	19.60	19.63	19.73		
1.4	64QAM	3	0	19.50	19.58	19.48		
1.4	64QAM	3	1	19.54	19.53	19.58		
1.4	64QAM	3	3	19.53	19.52	19.53		
1.4	64QAM	6	0	19.47	19.49	19.46	20.00	0

<LTE Band 7>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				20850	21100	21350		
Frequency (MHz)				2510	2535	2560		
20	QPSK	1	0	21.33	21.06	21.21	23.00	0
20	QPSK	1	49	21.28	21.05	21.16		
20	QPSK	1	99	21.19	21.02	21.12		
20	QPSK	50	0	21.39	21.09	21.22	22.00	1
20	QPSK	50	24	21.37	21.11	21.23		
20	QPSK	50	50	21.30	21.12	21.17		
20	QPSK	100	0	21.30	21.10	21.20		
20	16QAM	1	0	21.64	21.46	21.43	22.00	1
20	16QAM	1	49	21.61	21.39	21.46		
20	16QAM	1	99	21.49	21.39	21.48		
20	16QAM	50	0	21.45	21.18	21.28	22.00	1
20	16QAM	50	24	21.42	21.16	21.31		
20	16QAM	50	50	21.38	21.15	21.26		
20	16QAM	100	0	21.38	21.15	21.28		
20	64QAM	1	0	21.25	21.32	21.44	22.00	1
20	64QAM	1	49	21.57	21.34	21.39		
20	64QAM	1	99	21.45	21.28	21.38		
20	64QAM	50	0	20.99	20.71	20.80	21.00	2
20	64QAM	50	24	20.97	20.69	20.80		
20	64QAM	50	50	20.89	20.70	20.79		
20	64QAM	100	0	20.91	20.70	20.80		
Channel				20825	21100	21375		
Frequency (MHz)				2507.5	2535	2562.5		
15	QPSK	1	0	21.27	20.96	21.17	23.00	0
15	QPSK	1	37	21.20	20.97	21.09		
15	QPSK	1	74	21.18	20.93	21.03		
15	QPSK	36	0	21.37	21.00	21.22	22.00	1
15	QPSK	36	20	21.34	21.05	21.13		
15	QPSK	36	39	21.25	21.07	21.16		
15	QPSK	75	0	21.28	21.02	21.14		
15	16QAM	1	0	21.63	21.46	21.35	22.00	1
15	16QAM	1	37	21.58	21.38	21.42		
15	16QAM	1	74	21.45	21.30	21.45		
15	16QAM	36	0	21.35	21.13	21.28	22.00	1
15	16QAM	36	20	21.41	21.15	21.25		
15	16QAM	36	39	21.38	21.12	21.23		
15	16QAM	75	0	21.33	21.13	21.24		
15	64QAM	1	0	21.20	21.23	21.38	22.00	1
15	64QAM	1	37	21.50	21.31	21.37		
15	64QAM	1	74	21.41	21.23	21.32		
15	64QAM	36	0	20.96	20.71	20.71	21.00	2
15	64QAM	36	20	20.96	20.67	20.71		
15	64QAM	36	39	20.83	20.68	20.72		
15	64QAM	75	0	20.83	20.67	20.71		

Channel				20800	21100	21400	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2505	2535	2565		
10	QPSK	1	0	21.26	21.04	21.13	23.00	0
10	QPSK	1	25	21.25	21.02	21.12		
10	QPSK	1	49	21.13	20.95	21.11		
10	QPSK	25	0	21.33	21.01	21.18	22.00	1
10	QPSK	25	12	21.33	21.11	21.15		
10	QPSK	25	25	21.27	21.10	21.11		
10	QPSK	50	0	21.24	21.01	21.12		
10	16QAM	1	0	21.60	21.39	21.39	22.00	1
10	16QAM	1	25	21.58	21.32	21.41		
10	16QAM	1	49	21.42	21.36	21.46		
10	16QAM	25	0	21.42	21.14	21.25	22.00	1
10	16QAM	25	12	21.39	21.15	21.25		
10	16QAM	25	25	21.32	21.08	21.21		
10	16QAM	50	0	21.33	21.11	21.27		
10	64QAM	1	0	21.20	21.28	21.44	22.00	1
10	64QAM	1	25	21.48	21.33	21.30		
10	64QAM	1	49	21.42	21.26	21.28		
10	64QAM	25	0	20.95	20.68	20.76	21.00	2
10	64QAM	25	12	20.92	20.68	20.76		
10	64QAM	25	25	20.85	20.70	20.77		
10	64QAM	50	0	20.82	20.66	20.80		
Channel				20775	21100	21425	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2502.5	2535	2567.5		
5	QPSK	1	0	21.29	21.03	21.16	23.00	0
5	QPSK	1	12	21.26	20.98	21.15		
5	QPSK	1	24	21.18	20.92	21.09		
5	QPSK	12	0	21.37	21.08	21.13	22.00	1
5	QPSK	12	7	21.36	21.07	21.17		
5	QPSK	12	13	21.23	21.06	21.14		
5	QPSK	25	0	21.26	21.02	21.20		
5	16QAM	1	0	21.58	21.42	21.43	22.00	1
5	16QAM	1	12	21.57	21.30	21.37		
5	16QAM	1	24	21.40	21.35	21.40		
5	16QAM	12	0	21.42	21.13	21.27	22.00	1
5	16QAM	12	7	21.33	21.09	21.25		
5	16QAM	12	13	21.28	21.10	21.22		
5	16QAM	25	0	21.29	21.10	21.22		
5	64QAM	1	0	21.23	21.32	21.38	22.00	1
5	64QAM	1	12	21.49	21.28	21.38		
5	64QAM	1	24	21.42	21.19	21.31		
5	64QAM	12	0	20.89	20.65	20.75	21.00	2
5	64QAM	12	7	20.90	20.60	20.74		
5	64QAM	12	13	20.88	20.64	20.75		
5	64QAM	25	0	20.85	20.65	20.80		

<TDD LTE SAR Measurement>

TDD LTE configuration setup for SAR measurement

SAR was tested with a fixed periodic duty factor according to the highest transmission duty factor implemented for the device and supported by 3GPP.

- 3GPP TS 36.211 section 4.2 for Type 2 Frame Structure and Table 4.2-2 for uplink-downlink configurations
- “special subframe S” contains both uplink and downlink transmissions, it has been taken into consideration to determine the transmission duty factor according to the worst case uplink and downlink cyclic prefix requirements for UpPTS
- Establishing connections with base station simulators ensure a consistent means for testing SAR and recommended for evaluating SAR. The Anritsu MT8820C (firmware: #22.52#004) was used for LTE output power measurements and SAR testing.




Figure 4.2-1: Frame structure type 2 (for 5 ms switch-point periodicity).

Table 4.2-2: Uplink-downlink configurations.

Uplink-downlink configuration	Downlink-to-Uplink Switch-point periodicity	Subframe number									
		0	1	2	3	4	5	6	7	8	9
0	5 ms	D	S	U	U	U	D	S	U	U	U
1	5 ms	D	S	U	U	D	D	S	U	U	D
2	5 ms	D	S	U	D	D	D	S	U	D	D
3	10 ms	D	S	U	U	U	D	D	D	D	D
4	10 ms	D	S	U	U	D	D	D	D	D	D
5	10 ms	D	S	U	D	D	D	D	D	D	D
6	5 ms	D	S	U	U	U	D	S	U	U	D

Table 4.2-1: Configuration of special subframe (lengths of DwPTS/GP/UpPTS).

Special subframe configuration	Normal cyclic prefix in downlink			Extended cyclic prefix in downlink		
	DwPTS	UpPTS		DwPTS	UpPTS	
		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink		Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
0	$6592 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$	$7680 \cdot T_s$	$2192 \cdot T_s$	$2560 \cdot T_s$
1	$19760 \cdot T_s$			$20480 \cdot T_s$		
2	$21952 \cdot T_s$			$23040 \cdot T_s$		
3	$24144 \cdot T_s$			$25600 \cdot T_s$		
4	$26336 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$	$7680 \cdot T_s$	$4384 \cdot T_s$	$5120 \cdot T_s$
5	$6592 \cdot T_s$			$20480 \cdot T_s$		
6	$19760 \cdot T_s$			$23040 \cdot T_s$		
7	$21952 \cdot T_s$			$12800 \cdot T_s$	-	-
8	$24144 \cdot T_s$			-		
9	$13168 \cdot T_s$			-		

Special subframe (30720·T _s): Normal cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~4	7.13%	8.33%
	5~9	14.3%	16.7%

Special subframe(30720·T _s): Extended cyclic prefix in downlink (UpPTS)			
	Special subframe configuration	Normal cyclic prefix in uplink	Extended cyclic prefix in uplink
Uplink duty factor in one special subframe	0~3	7.13%	8.33%
	4~7	14.3%	16.7%

The highest duty factor is resulted from:

- Uplink-downlink configuration: 0. In a half-frame consisted of 5 subframes, uplink operation is in 3 uplink subframes and 1 special subframe.
- special subframe configuration: 5-9 for normal cyclic prefix in downlink, 4-7 for extended cyclic prefix in downlink
- for special subframe with extended cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.167)/5 = 63.3\%$
- for special subframe with normal cyclic prefix in uplink, the total uplink duty factor in one half-frame is:
 $(3+0.143)/5 = 62.9\%$
- For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix $63.3\%/62.9\% = 1.006$ is applied to scale-up the measured SAR result. The scaled TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.

Default Power Mode

<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150		
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	23.18	23.12	23.08	24.00	0
20	QPSK	1	49	23.15	23.05	22.88		
20	QPSK	1	99	23.02	23.07	22.86		
20	QPSK	50	0	22.22	22.12	22.04	23.00	1
20	QPSK	50	24	22.12	22.13	22.05		
20	QPSK	50	50	22.09	22.09	21.91		
20	QPSK	100	0	22.12	22.09	22.03	23.00	1
20	16QAM	1	0	22.34	22.24	22.20		
20	16QAM	1	49	22.30	22.18	22.05		
20	16QAM	1	99	22.15	22.19	22.02	22.00	2
20	16QAM	50	0	21.32	21.23	21.17		
20	16QAM	50	24	21.22	21.23	21.16		
20	16QAM	50	50	21.19	21.19	21.00	22.00	2
20	16QAM	100	0	21.22	21.19	21.17		
20	64QAM	1	0	20.96	21.29	20.78		
20	64QAM	1	49	20.90	20.82	20.65	22.00	2
20	64QAM	1	99	20.75	20.79	20.62		
20	64QAM	50	0	20.34	20.21	20.19		
20	64QAM	50	24	20.20	20.22	20.16	21.00	3
20	64QAM	50	50	20.16	20.19	20.01		
20	64QAM	100	0	20.20	20.21	20.15		
Channel				37825	38000	38175		
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	23.09	22.99	22.90	24.00	0
15	QPSK	1	37	23.01	22.92	22.75		
15	QPSK	1	74	22.99	22.97	22.76		
15	QPSK	36	0	22.09	22.03	21.92	23.00	1
15	QPSK	36	20	22.12	21.99	21.85		
15	QPSK	36	39	21.98	21.99	21.77		
15	QPSK	75	0	21.99	22.00	21.89	23.00	1
15	16QAM	1	0	22.41	22.31	22.25		
15	16QAM	1	37	22.33	22.23	22.09		
15	16QAM	1	74	22.23	22.28	22.10	22.00	2
15	16QAM	36	0	21.20	21.12	21.05		
15	16QAM	36	20	21.17	21.13	20.94		
15	16QAM	36	39	21.11	21.11	20.88	22.00	2
15	16QAM	75	0	21.11	21.10	21.03		
15	64QAM	1	0	20.99	21.20	21.11		
15	64QAM	1	37	20.93	21.10	21.04	22.00	2
15	64QAM	1	74	20.83	20.99	20.77		
15	64QAM	36	0	20.42	20.50	20.46		
15	64QAM	36	20	20.28	20.43	20.30	21.00	3
15	64QAM	36	39	20.13	20.31	20.20		
15	64QAM	75	0	20.27	20.40	20.36		

Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	22.95	22.85	22.66	24.00	0
10	QPSK	1	25	22.92	22.85	22.67		
10	QPSK	1	49	22.93	22.85	22.64		
10	QPSK	25	0	22.09	21.97	21.79	23.00	1
10	QPSK	25	12	22.05	22.00	21.78		
10	QPSK	25	25	22.07	21.96	21.77		
10	QPSK	50	0	22.11	21.99	21.81	23.00	1
10	16QAM	1	0	22.33	22.25	22.12		
10	16QAM	1	25	22.33	22.23	22.08		
10	16QAM	1	49	22.35	22.24	22.07	22.00	2
10	16QAM	25	0	21.21	21.08	20.94		
10	16QAM	25	12	21.18	21.13	20.95		
10	16QAM	25	25	21.18	21.09	20.93	22.00	2
10	16QAM	50	0	21.22	21.09	20.92		
10	64QAM	1	0	20.94	20.73	20.59		
10	64QAM	1	25	20.91	20.75	20.64	22.00	2
10	64QAM	1	49	20.72	20.68	20.41		
10	64QAM	25	0	20.45	20.32	20.14		
10	64QAM	25	12	20.31	20.19	19.90	21.00	3
10	64QAM	25	25	20.20	20.07	19.84		
10	64QAM	50	0	20.31	20.23	19.86		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	22.95	22.83	22.66	24.00	0
5	QPSK	1	12	22.92	22.80	22.65		
5	QPSK	1	24	22.92	22.84	22.65		
5	QPSK	12	0	22.05	21.97	21.77	23.00	1
5	QPSK	12	7	22.12	21.99	21.80		
5	QPSK	12	13	22.04	21.99	21.80		
5	QPSK	25	0	22.06	21.93	21.77	23.00	1
5	16QAM	1	0	22.32	22.22	22.08		
5	16QAM	1	12	22.30	22.23	22.06		
5	16QAM	1	24	22.32	22.23	22.07	22.00	2
5	16QAM	12	0	21.14	21.09	20.90		
5	16QAM	12	7	21.22	21.08	20.92		
5	16QAM	12	13	21.16	21.08	20.91	22.00	2
5	16QAM	25	0	21.19	21.08	20.91		
5	64QAM	1	0	20.98	21.10	20.87		
5	64QAM	1	12	20.83	21.09	20.86	22.00	2
5	64QAM	1	24	20.79	21.07	20.88		
5	64QAM	12	0	20.43	20.48	20.47		
5	64QAM	12	7	20.38	20.50	20.46	21.00	3
5	64QAM	12	13	20.12	20.12	20.26		
5	64QAM	25	0	19.94	20.14	20.07		

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	23.21	23.11	23.18	23.00	24.00	0
20	QPSK	1	49	23.10	23.07	23.14	22.85		
20	QPSK	1	99	23.06	23.12	23.13	22.74		
20	QPSK	50	0	22.22	22.11	22.20	21.95	23.00	1
20	QPSK	50	24	22.17	22.20	22.19	21.91		
20	QPSK	50	50	22.15	22.18	22.17	21.82		
20	QPSK	100	0	22.18	22.20	22.20	21.90		
20	16QAM	1	0	22.35	22.27	22.34	22.15	23.00	1
20	16QAM	1	49	22.25	22.19	22.27	22.01		
20	16QAM	1	99	22.19	22.26	22.27	21.84		
20	16QAM	50	0	21.28	21.22	21.30	21.07	22.00	2
20	16QAM	50	24	21.26	21.29	21.29	21.01		
20	16QAM	50	50	21.22	21.25	21.31	20.95		
20	16QAM	100	0	21.25	21.28	21.28	21.02		
20	64QAM	1	0	20.97	20.90	20.98	20.74	22.00	2
20	64QAM	1	49	20.88	20.81	20.89	20.62		
20	64QAM	1	99	20.83	20.86	20.88	20.49		
20	64QAM	50	0	20.30	20.18	20.31	20.05	21.00	3
20	64QAM	50	24	20.26	20.26	20.28	19.99		
20	64QAM	50	50	20.24	20.26	20.30	19.95		
20	64QAM	100	0	20.28	20.25	20.27	19.97		
Channel				40115	40395	40685	41165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5		
15	QPSK	1	0	23.11	23.04	23.10	22.76	24.00	0
15	QPSK	1	37	23.05	22.99	23.05	22.61		
15	QPSK	1	74	23.06	23.08	23.09	22.57		
15	QPSK	36	0	22.10	22.03	22.10	21.70	23.00	1
15	QPSK	36	20	22.08	22.12	22.13	21.66		
15	QPSK	36	39	22.05	22.10	22.07	21.58		
15	QPSK	75	0	22.08	22.12	22.10	21.67		
15	16QAM	1	0	22.40	22.32	22.40	22.05	23.00	1
15	16QAM	1	37	22.31	22.24	22.36	21.92		
15	16QAM	1	74	22.32	22.37	22.38	21.86		
15	16QAM	36	0	21.15	21.11	21.19	20.78	22.00	2
15	16QAM	36	20	21.14	21.20	21.21	20.77		
15	16QAM	36	39	21.14	21.18	21.20	20.69		
15	16QAM	75	0	21.19	21.22	21.23	20.77		
15	64QAM	1	0	21.28	21.12	21.21	20.86	22.00	2
15	64QAM	1	37	21.14	21.03	21.15	20.74		
15	64QAM	1	74	21.17	21.17	21.18	20.67		
15	64QAM	36	0	20.19	20.10	20.24	19.86	21.00	3
15	64QAM	36	20	20.18	20.22	20.25	19.82		
15	64QAM	36	39	20.15	20.17	20.22	19.75		
15	64QAM	75	0	20.19	20.21	20.21	19.79		

Channel				40090	40390	40690	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2540	2570	2600	2650		
10	QPSK	1	0	23.04	22.89	22.98	22.57	24.00	0
10	QPSK	1	25	23.00	22.88	22.96	22.49		
10	QPSK	1	49	23.00	22.99	22.97	22.45		
10	QPSK	25	0	22.09	22.01	22.07	21.62	23.00	1
10	QPSK	25	12	22.14	22.09	22.10	21.61		
10	QPSK	25	25	22.10	22.09	22.09	21.57		
10	QPSK	50	0	22.14	22.12	22.11	21.61	23.00	1
10	16QAM	1	0	22.39	22.29	22.40	21.98		
10	16QAM	1	25	22.38	22.26	22.35	21.88		
10	16QAM	1	49	22.35	22.35	22.36	21.84	22.00	2
10	16QAM	25	0	21.22	21.10	21.16	20.75		
10	16QAM	25	12	21.22	21.22	21.23	20.74		
10	16QAM	25	25	21.20	21.20	21.16	20.69	22.00	2
10	16QAM	50	0	21.23	21.23	21.20	20.73		
10	64QAM	1	0	21.19	21.10	21.19	20.78	22.00	2
10	64QAM	1	25	21.17	21.04	21.14	20.69		
10	64QAM	1	49	21.15	21.14	21.16	20.64		
10	64QAM	25	0	20.29	20.14	20.23	19.82	21.00	3
10	64QAM	25	12	20.26	20.28	20.29	19.82		
10	64QAM	25	25	20.23	20.22	20.23	19.75		
10	64QAM	50	0	20.22	20.19	20.20	19.74	21.00	3
Channel				40065	40385	40705	41215		
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5	Tune-up limit (dBm)	MPR (dB)
5	QPSK	1	0	23.02	22.92	22.98	22.54		
5	QPSK	1	12	22.99	22.86	22.96	22.48	24.00	0
5	QPSK	1	24	22.97	22.86	22.97	22.45		
5	QPSK	12	0	22.11	21.97	22.10	21.58	23.00	1
5	QPSK	12	7	22.10	22.01	22.14	21.60		
5	QPSK	12	13	22.09	22.01	22.10	21.58		
5	QPSK	25	0	22.10	21.98	22.07	21.57	23.00	1
5	16QAM	1	0	22.36	22.19	22.33	21.88		
5	16QAM	1	12	22.32	22.24	22.32	21.87		
5	16QAM	1	24	22.31	22.24	22.35	21.81	22.00	2
5	16QAM	12	0	21.21	21.05	21.21	20.70		
5	16QAM	12	7	21.21	21.12	21.18	20.72		
5	16QAM	12	13	21.20	21.08	21.20	20.68	22.00	2
5	16QAM	25	0	21.17	21.05	21.21	20.69		
5	64QAM	1	0	21.19	21.03	21.17	20.70	22.00	2
5	64QAM	1	12	21.18	21.05	21.16	20.69		
5	64QAM	1	24	21.11	21.02	21.17	20.66		
5	64QAM	12	0	20.22	20.14	20.21	19.76	21.00	3
5	64QAM	12	7	20.30	20.18	20.25	19.79		
5	64QAM	12	13	20.29	20.14	20.22	19.74		
5	64QAM	25	0	20.25	20.14	20.21	19.75	21.00	3
Channel				40065	40385	40705	41215		

Near-body Power Mode

<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150		
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	22.69	22.47	22.49	23.50	0
20	QPSK	1	49	22.48	22.29	22.03		
20	QPSK	1	99	22.32	22.25	21.95		
20	QPSK	50	0	22.36	22.17	21.97	22.50	1
20	QPSK	50	24	22.21	22.12	21.97		
20	QPSK	50	50	22.16	22.10	21.78		
20	QPSK	100	0	22.20	22.15	21.91	22.50	1
20	16QAM	1	0	22.47	22.38	22.22		
20	16QAM	1	49	22.44	22.22	21.97		
20	16QAM	1	99	22.23	22.14	21.89	21.50	2
20	16QAM	50	0	21.46	21.27	21.12		
20	16QAM	50	24	21.35	21.24	21.07		
20	16QAM	50	50	21.30	21.22	20.91	21.50	2
20	16QAM	100	0	21.29	21.26	21.06		
20	64QAM	1	0	21.48	21.36	21.19		
20	64QAM	1	49	21.44	21.24	20.99	21.50	2
20	64QAM	1	99	21.23	21.14	20.86		
20	64QAM	50	0	20.47	20.37	20.35	20.50	3
20	64QAM	50	24	20.41	20.39	20.33		
20	64QAM	50	50	20.32	20.37	20.35		
20	64QAM	100	0	20.38	20.38	20.42		
Channel				37825	38000	38175	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	22.62	22.43	22.42	23.50	0
15	QPSK	1	37	22.38	22.25	21.99		
15	QPSK	1	74	22.25	22.18	21.92		
15	QPSK	36	0	22.49	22.35	22.17	22.50	1
15	QPSK	36	20	22.36	22.30	22.18		
15	QPSK	36	39	22.33	22.23	21.93		
15	QPSK	75	0	22.32	22.30	22.12	22.50	1
15	16QAM	1	0	22.48	22.39	22.18		
15	16QAM	1	37	22.38	22.23	21.98		
15	16QAM	1	74	22.21	22.06	21.88	21.50	2
15	16QAM	36	0	21.49	21.30	21.21		
15	16QAM	36	20	21.39	21.26	21.16		
15	16QAM	36	39	21.38	21.32	20.95	21.50	2
15	16QAM	75	0	21.36	21.33	21.10		
15	64QAM	1	0	21.43	21.32	21.18		
15	64QAM	1	37	21.35	21.19	20.97	21.50	2
15	64QAM	1	74	21.16	21.08	20.80		
15	64QAM	36	0	20.45	20.40	20.31		
15	64QAM	36	20	20.39	20.40	20.37	20.50	3
15	64QAM	36	39	20.30	20.33	20.32		
15	64QAM	75	0	20.40	20.41	20.42		

Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	22.62	22.39	22.44	23.50	0
10	QPSK	1	25	22.46	22.21	21.98		
10	QPSK	1	49	22.32	22.18	21.93		
10	QPSK	25	0	22.45	22.35	22.13	22.50	1
10	QPSK	25	12	22.40	22.28	22.15		
10	QPSK	25	25	22.30	22.27	21.94		
10	QPSK	50	0	22.39	22.27	22.07		
10	16QAM	1	0	22.43	22.36	22.16	22.50	1
10	16QAM	1	25	22.43	22.22	21.96		
10	16QAM	1	49	22.18	22.15	21.81		
10	16QAM	25	0	21.43	21.18	21.09	21.50	2
10	16QAM	25	12	21.35	21.15	21.06		
10	16QAM	25	25	21.25	21.15	20.85		
10	16QAM	50	0	21.20	21.25	21.05		
10	64QAM	1	0	21.41	21.29	21.15	21.50	2
10	64QAM	1	25	21.42	21.18	20.99		
10	64QAM	1	49	21.19	21.08	20.81		
10	64QAM	25	0	20.48	20.35	20.32	20.50	3
10	64QAM	25	12	20.45	20.35	20.33		
10	64QAM	25	25	20.37	20.40	20.34		
10	64QAM	50	0	20.36	20.42	20.46		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	22.61	22.41	22.43	23.50	0
5	QPSK	1	12	22.42	22.27	21.94		
5	QPSK	1	24	22.23	22.21	21.95		
5	QPSK	12	0	22.46	22.34	22.15	22.50	1
5	QPSK	12	7	22.37	22.27	22.11		
5	QPSK	12	13	22.37	22.28	21.97		
5	QPSK	25	0	22.40	22.34	22.04		
5	16QAM	1	0	22.47	22.40	22.20	22.50	1
5	16QAM	1	12	22.43	22.19	21.95		
5	16QAM	1	24	22.21	22.12	21.91		
5	16QAM	12	0	21.46	21.31	21.18	21.50	2
5	16QAM	12	7	21.40	21.25	21.17		
5	16QAM	12	13	21.39	21.25	20.97		
5	16QAM	25	0	21.37	21.33	21.15		
5	64QAM	1	0	21.49	21.37	21.23	21.50	2
5	64QAM	1	12	21.45	21.29	21.09		
5	64QAM	1	24	21.30	21.16	20.90		
5	64QAM	12	0	20.44	20.38	20.37	20.50	3
5	64QAM	12	7	20.43	20.44	20.30		
5	64QAM	12	13	20.31	20.33	20.39		
5	64QAM	25	0	20.41	20.41	20.43		

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	22.45	22.58	22.56	22.33	23.50	0
20	QPSK	1	49	22.45	22.57	22.41	22.00		
20	QPSK	1	99	22.45	22.51	22.35	21.93		
20	QPSK	50	0	22.35	22.49	22.35	21.91	22.50	1
20	QPSK	50	24	22.33	22.46	22.29	21.89		
20	QPSK	50	50	22.33	22.41	22.25	21.81		
20	QPSK	100	0	22.33	22.44	22.29	21.84		
20	16QAM	1	0	22.28	22.35	22.18	22.04	22.50	1
20	16QAM	1	49	22.22	22.28	22.12	21.86		
20	16QAM	1	99	22.33	22.28	21.99	21.82		
20	16QAM	50	0	21.33	21.41	21.20	21.04	21.50	2
20	16QAM	50	24	21.34	21.38	21.20	20.96		
20	16QAM	50	50	21.44	21.40	21.17	20.95		
20	16QAM	100	0	21.43	21.38	21.17	20.99		
20	64QAM	1	0	21.35	21.44	21.26	21.10	21.50	2
20	64QAM	1	49	21.30	21.40	21.21	20.97		
20	64QAM	1	99	21.42	21.41	21.10	20.90		
20	64QAM	50	0	20.28	20.41	20.21	20.02	20.50	3
20	64QAM	50	24	20.30	20.39	20.22	20.01		
20	64QAM	50	50	20.42	20.42	20.19	19.94		
20	64QAM	100	0	20.38	20.40	20.20	20.00		
Channel				40115	40395	40685	41165	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5		
15	QPSK	1	0	22.44	22.52	22.48	22.33	23.50	0
15	QPSK	1	37	22.40	22.53	22.33	21.94		
15	QPSK	1	74	22.45	22.45	22.27	21.87		
15	QPSK	36	0	22.25	22.46	22.29	21.89	22.50	1
15	QPSK	36	20	22.27	22.46	22.27	21.85		
15	QPSK	36	39	22.27	22.37	22.18	21.74		
15	QPSK	75	0	22.23	22.38	22.27	21.78		
15	16QAM	1	0	22.33	22.50	22.41	22.00	22.50	1
15	16QAM	1	37	22.37	22.44	22.30	21.94		
15	16QAM	1	74	22.33	22.32	22.18	21.84		
15	16QAM	36	0	21.26	21.33	21.12	21.02	21.50	2
15	16QAM	36	20	21.26	21.34	21.12	20.95		
15	16QAM	36	39	21.44	21.37	21.17	20.91		
15	16QAM	75	0	21.36	21.37	21.12	20.90		
15	64QAM	1	0	21.25	21.44	21.22	21.09	21.50	2
15	64QAM	1	37	21.23	21.40	21.16	20.94		
15	64QAM	1	74	21.40	21.40	21.01	20.81		
15	64QAM	36	0	20.25	20.39	20.11	19.92	20.50	3
15	64QAM	36	20	20.21	20.36	20.20	19.97		
15	64QAM	36	39	20.33	20.41	20.19	19.93		
15	64QAM	75	0	20.36	20.37	20.17	19.92		

Channel				40090	40390	40690	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2540	2570	2600	2650		
10	QPSK	1	0	22.43	22.47	22.49	22.30	23.50	0
10	QPSK	1	25	22.39	22.55	22.36	21.98		
10	QPSK	1	49	22.35	22.48	22.27	21.84		
10	QPSK	25	0	22.27	22.47	22.30	21.86	22.50	1
10	QPSK	25	12	22.25	22.45	22.21	21.85		
10	QPSK	25	25	22.29	22.33	22.20	21.74		
10	QPSK	50	0	22.32	22.39	22.23	21.82	22.50	1
10	16QAM	1	0	22.37	22.46	22.40	22.05		
10	16QAM	1	25	22.35	22.42	22.28	21.95		
10	16QAM	1	49	22.37	22.41	22.24	21.87	21.50	2
10	16QAM	25	0	21.29	21.40	21.19	21.04		
10	16QAM	25	12	21.25	21.28	21.10	20.93		
10	16QAM	25	25	21.36	21.34	21.09	20.95	21.50	2
10	16QAM	50	0	21.38	21.37	21.15	20.92		
10	64QAM	1	0	21.33	21.35	21.23	21.08		
10	64QAM	1	25	21.25	21.36	21.17	20.96	21.50	2
10	64QAM	1	49	21.33	21.40	21.10	20.82		
10	64QAM	25	0	20.20	20.32	20.21	19.98		
10	64QAM	25	12	20.26	20.38	20.20	19.99	20.50	3
10	64QAM	25	25	20.34	20.39	20.14	19.94		
10	64QAM	50	0	20.38	20.40	20.14	19.97		
Channel				40065	40385	40705	41215	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5		
5	QPSK	1	0	22.42	22.50	22.54	22.32	23.50	0
5	QPSK	1	12	22.37	22.48	22.33	21.95		
5	QPSK	1	24	22.45	22.51	22.25	21.90		
5	QPSK	12	0	22.30	22.49	22.34	21.86	22.50	1
5	QPSK	12	7	22.33	22.45	22.22	21.88		
5	QPSK	12	13	22.29	22.39	22.15	21.76		
5	QPSK	25	0	22.25	22.43	22.26	21.75	22.50	1
5	16QAM	1	0	22.38	22.48	22.46	22.03		
5	16QAM	1	12	22.35	22.41	22.34	21.92		
5	16QAM	1	24	22.33	22.40	22.16	21.81	21.50	2
5	16QAM	12	0	21.32	21.35	21.19	20.94		
5	16QAM	12	7	21.25	21.28	21.20	20.96		
5	16QAM	12	13	21.35	21.33	21.09	20.88	21.50	2
5	16QAM	25	0	21.40	21.36	21.15	20.90		
5	64QAM	1	0	21.27	21.35	21.26	21.08		
5	64QAM	1	12	21.24	21.35	21.12	20.91	21.50	2
5	64QAM	1	24	21.36	21.33	21.07	20.86		
5	64QAM	12	0	20.26	20.36	20.16	19.98		
5	64QAM	12	7	20.30	20.29	20.20	19.93	20.50	3
5	64QAM	12	13	20.39	20.35	20.19	19.87		
5	64QAM	25	0	20.31	20.32	20.10	20.00		

Hotspot Power Mode

<LTE Band 38>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				37850	38000	38150		
Frequency (MHz)				2580	2595	2610		
20	QPSK	1	0	22.69	22.47	22.49	23.50	0
20	QPSK	1	49	22.48	22.29	22.03		
20	QPSK	1	99	22.32	22.25	21.95		
20	QPSK	50	0	22.36	22.17	21.97	22.50	1
20	QPSK	50	24	22.21	22.12	21.97		
20	QPSK	50	50	22.16	22.10	21.78		
20	QPSK	100	0	22.20	22.15	21.91	22.50	1
20	16QAM	1	0	22.47	22.38	22.22		
20	16QAM	1	49	22.44	22.22	21.97		
20	16QAM	1	99	22.23	22.14	21.89	21.50	2
20	16QAM	50	0	21.46	21.27	21.12		
20	16QAM	50	24	21.35	21.24	21.07		
20	16QAM	50	50	21.30	21.22	20.91	21.50	2
20	16QAM	100	0	21.29	21.26	21.06		
20	64QAM	1	0	21.48	21.36	21.19		
20	64QAM	1	49	21.44	21.24	20.99	21.50	2
20	64QAM	1	99	21.23	21.14	20.86		
20	64QAM	50	0	20.47	20.37	20.35	20.50	3
20	64QAM	50	24	20.41	20.39	20.33		
20	64QAM	50	50	20.32	20.37	20.35		
20	64QAM	100	0	20.38	20.38	20.42		
Channel				37825	38000	38175		
Frequency (MHz)				2577.5	2595	2612.5		
15	QPSK	1	0	22.62	22.43	22.42	23.50	0
15	QPSK	1	37	22.38	22.25	21.99		
15	QPSK	1	74	22.25	22.18	21.92		
15	QPSK	36	0	22.49	22.35	22.17	22.50	1
15	QPSK	36	20	22.36	22.30	22.18		
15	QPSK	36	39	22.33	22.23	21.93		
15	QPSK	75	0	22.32	22.30	22.12	22.50	1
15	16QAM	1	0	22.48	22.39	22.18		
15	16QAM	1	37	22.38	22.23	21.98		
15	16QAM	1	74	22.21	22.06	21.88	21.50	2
15	16QAM	36	0	21.49	21.30	21.21		
15	16QAM	36	20	21.39	21.26	21.16		
15	16QAM	36	39	21.38	21.32	20.95	21.50	2
15	16QAM	75	0	21.36	21.33	21.10		
15	64QAM	1	0	21.43	21.32	21.18		
15	64QAM	1	37	21.35	21.19	20.97	21.50	2
15	64QAM	1	74	21.16	21.08	20.80		
15	64QAM	36	0	20.45	20.40	20.31		
15	64QAM	36	20	20.39	20.40	20.37	20.50	3
15	64QAM	36	39	20.30	20.33	20.32		
15	64QAM	75	0	20.40	20.41	20.42		

Channel				37800	38000	38200	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2575	2595	2615		
10	QPSK	1	0	22.62	22.39	22.44	23.50	0
10	QPSK	1	25	22.46	22.21	21.98		
10	QPSK	1	49	22.32	22.18	21.93		
10	QPSK	25	0	22.45	22.35	22.13	22.50	1
10	QPSK	25	12	22.40	22.28	22.15		
10	QPSK	25	25	22.30	22.27	21.94		
10	QPSK	50	0	22.39	22.27	22.07		
10	16QAM	1	0	22.43	22.36	22.16	22.50	1
10	16QAM	1	25	22.43	22.22	21.96		
10	16QAM	1	49	22.18	22.15	21.81		
10	16QAM	25	0	21.43	21.18	21.09	21.50	2
10	16QAM	25	12	21.35	21.15	21.06		
10	16QAM	25	25	21.25	21.15	20.85		
10	16QAM	50	0	21.20	21.25	21.05		
10	64QAM	1	0	21.41	21.29	21.15	21.50	2
10	64QAM	1	25	21.42	21.18	20.99		
10	64QAM	1	49	21.19	21.08	20.81		
10	64QAM	25	0	20.48	20.35	20.32	20.50	3
10	64QAM	25	12	20.45	20.35	20.33		
10	64QAM	25	25	20.37	20.40	20.34		
10	64QAM	50	0	20.36	20.42	20.46		
Channel				37775	38000	38225	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2572.5	2595	2617.5		
5	QPSK	1	0	22.61	22.41	22.43	23.50	0
5	QPSK	1	12	22.42	22.27	21.94		
5	QPSK	1	24	22.23	22.21	21.95		
5	QPSK	12	0	22.46	22.34	22.15	22.50	1
5	QPSK	12	7	22.37	22.27	22.11		
5	QPSK	12	13	22.37	22.28	21.97		
5	QPSK	25	0	22.40	22.34	22.04		
5	16QAM	1	0	22.47	22.40	22.20	22.50	1
5	16QAM	1	12	22.43	22.19	21.95		
5	16QAM	1	24	22.21	22.12	21.91		
5	16QAM	12	0	21.46	21.31	21.18	21.50	2
5	16QAM	12	7	21.40	21.25	21.17		
5	16QAM	12	13	21.39	21.25	20.97		
5	16QAM	25	0	21.37	21.33	21.15		
5	64QAM	1	0	21.49	21.37	21.23	21.50	2
5	64QAM	1	12	21.45	21.29	21.09		
5	64QAM	1	24	21.30	21.16	20.90		
5	64QAM	12	0	20.44	20.38	20.37	20.50	3
5	64QAM	12	7	20.43	20.44	20.30		
5	64QAM	12	13	20.31	20.33	20.39		
5	64QAM	25	0	20.41	20.41	20.43		

<LTE Band 41>

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	22.45	22.58	22.56	22.33	23.50	0
20	QPSK	1	49	22.45	22.57	22.41	22.00		
20	QPSK	1	99	22.45	22.51	22.35	21.93		
20	QPSK	50	0	22.35	22.49	22.35	21.91	22.50	1
20	QPSK	50	24	22.33	22.46	22.29	21.89		
20	QPSK	50	50	22.33	22.41	22.25	21.81		
20	QPSK	100	0	22.33	22.44	22.29	21.84		
20	16QAM	1	0	22.28	22.35	22.18	22.04	22.50	1
20	16QAM	1	49	22.22	22.28	22.12	21.86		
20	16QAM	1	99	22.33	22.28	21.99	21.82		
20	16QAM	50	0	21.33	21.41	21.20	21.04	21.50	2
20	16QAM	50	24	21.34	21.38	21.20	20.96		
20	16QAM	50	50	21.44	21.40	21.17	20.95		
20	16QAM	100	0	21.43	21.38	21.17	20.99		
20	64QAM	1	0	21.35	21.44	21.26	21.10	21.50	2
20	64QAM	1	49	21.30	21.40	21.21	20.97		
20	64QAM	1	99	21.42	21.41	21.10	20.90		
20	64QAM	50	0	20.28	20.41	20.21	20.02	20.50	3
20	64QAM	50	24	20.30	20.39	20.22	20.01		
20	64QAM	50	50	20.42	20.42	20.19	19.94		
20	64QAM	100	0	20.38	20.40	20.20	20.00		
Channel				40115	40395	40685	41165		
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5		
15	QPSK	1	0	22.44	22.52	22.48	22.33	23.50	0
15	QPSK	1	37	22.40	22.53	22.33	21.94		
15	QPSK	1	74	22.45	22.45	22.27	21.87		
15	QPSK	36	0	22.25	22.46	22.29	21.89	22.50	1
15	QPSK	36	20	22.27	22.46	22.27	21.85		
15	QPSK	36	39	22.27	22.37	22.18	21.74		
15	QPSK	75	0	22.23	22.38	22.27	21.78		
15	16QAM	1	0	22.33	22.50	22.41	22.00	22.50	1
15	16QAM	1	37	22.37	22.44	22.30	21.94		
15	16QAM	1	74	22.33	22.32	22.18	21.84		
15	16QAM	36	0	21.26	21.33	21.12	21.02	21.50	2
15	16QAM	36	20	21.26	21.34	21.12	20.95		
15	16QAM	36	39	21.44	21.37	21.17	20.91		
15	16QAM	75	0	21.36	21.37	21.12	20.90		
15	64QAM	1	0	21.25	21.44	21.22	21.09	21.50	2
15	64QAM	1	37	21.23	21.40	21.16	20.94		
15	64QAM	1	74	21.40	21.40	21.01	20.81		
15	64QAM	36	0	20.25	20.39	20.11	19.92	20.50	3
15	64QAM	36	20	20.21	20.36	20.20	19.97		
15	64QAM	36	39	20.33	20.41	20.19	19.93		
15	64QAM	75	0	20.36	20.37	20.17	19.92		

Channel				40090	40390	40690	41190	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2540	2570	2600	2650		
10	QPSK	1	0	22.43	22.47	22.49	22.30	23.50	0
10	QPSK	1	25	22.39	22.55	22.36	21.98		
10	QPSK	1	49	22.35	22.48	22.27	21.84		
10	QPSK	25	0	22.27	22.47	22.30	21.86	22.50	1
10	QPSK	25	12	22.25	22.45	22.21	21.85		
10	QPSK	25	25	22.29	22.33	22.20	21.74		
10	QPSK	50	0	22.32	22.39	22.23	21.82		
10	16QAM	1	0	22.37	22.46	22.40	22.05	22.50	1
10	16QAM	1	25	22.35	22.42	22.28	21.95		
10	16QAM	1	49	22.37	22.41	22.24	21.87		
10	16QAM	25	0	21.29	21.40	21.19	21.04	21.50	2
10	16QAM	25	12	21.25	21.28	21.10	20.93		
10	16QAM	25	25	21.36	21.34	21.09	20.95		
10	16QAM	50	0	21.38	21.37	21.15	20.92		
10	64QAM	1	0	21.33	21.35	21.23	21.08	21.50	2
10	64QAM	1	25	21.25	21.36	21.17	20.96		
10	64QAM	1	49	21.33	21.40	21.10	20.82		
10	64QAM	25	0	20.20	20.32	20.21	19.98	20.50	3
10	64QAM	25	12	20.26	20.38	20.20	19.99		
10	64QAM	25	25	20.34	20.39	20.14	19.94		
10	64QAM	50	0	20.38	20.40	20.14	19.97		
Channel				40065	40385	40705	41215	Tune-up limit (dBm)	MPR (dB)
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5		
5	QPSK	1	0	22.42	22.50	22.54	22.32	23.50	0
5	QPSK	1	12	22.37	22.48	22.33	21.95		
5	QPSK	1	24	22.45	22.51	22.25	21.90		
5	QPSK	12	0	22.30	22.49	22.34	21.86	22.50	1
5	QPSK	12	7	22.33	22.45	22.22	21.88		
5	QPSK	12	13	22.29	22.39	22.15	21.76		
5	QPSK	25	0	22.25	22.43	22.26	21.75		
5	16QAM	1	0	22.38	22.48	22.46	22.03	22.50	1
5	16QAM	1	12	22.35	22.41	22.34	21.92		
5	16QAM	1	24	22.33	22.40	22.16	21.81		
5	16QAM	12	0	21.32	21.35	21.19	20.94	21.50	2
5	16QAM	12	7	21.25	21.28	21.20	20.96		
5	16QAM	12	13	21.35	21.33	21.09	20.88		
5	16QAM	25	0	21.40	21.36	21.15	20.90		
5	64QAM	1	0	21.27	21.35	21.26	21.08	21.50	2
5	64QAM	1	12	21.24	21.35	21.12	20.91		
5	64QAM	1	24	21.36	21.33	21.07	20.86		
5	64QAM	12	0	20.26	20.36	20.16	19.98	20.50	3
5	64QAM	12	7	20.30	20.29	20.20	19.93		
5	64QAM	12	13	20.39	20.35	20.19	19.87		
5	64QAM	25	0	20.31	20.32	20.10	20.00		

<LTE Carrier Aggregation combinations>
General Note:

1. This device supports Carrier Aggregation on downlink only for intra band, Uplink CA is not supported. For the device supports combination bands and configurations are according to 3GPP.
2. In applying the existing power measurement procedure of KDB 941225 D05A for DL CA SAR test exclusion, only the subset with the largest number of combinations of the frequency band and CCs in each row need consideration, and that configurations require power measurement should be highlighted in the below table.

2CC Downlink Carrier Aggregation	
Number	Combination
1	7A-7A
2	7B
3	7C
4	41A-41A
5	41C

<Power verification when LTE Carrier Aggregation Active>
General Note:

- i. According to KDB941225 D05A v01r02, Uplink maximum output power measurement with downlink carrier aggregation active should be measured, using the highest output channel measured without downlink carrier aggregation, to confirm that uplink maximum output power with downlink carrier aggregation active remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output measured without downlink carrier aggregation active.
- ii. Uplink maximum output power with downlink carrier aggregation active does not show more than ¼ dB higher than the maximum output power without downlink carrier aggregation active, therefore SAR evaluation with downlink carrier aggregation active can be excluded.
- iii. The device supports downlink two carrier aggregation. For power measurement were control and acknowledge data is sent on uplink channels that operate identical to specifications when downlink carrier aggregation is inactive.
- iv. Selected highest measured power when downlink carrier aggregation is inactive for conducted power comparison with downlink carrier aggregation is active, to confirm that when downlink carrier aggregation is active uplink maximum output power remains within the specified tune-up tolerance limits and not more than ¼ dB higher than the maximum output power measured when downlink carrier aggregation inactive.
- v. For non-contiguous intra-band CA, the SCC selected to provide maximum separation from the PCC and must remain fully within the downlink transmission band.
- vi. For Intra-band, contiguous CA, the downlink channels selected to perform the uplink power measurement must satisfy 3GPP channel spacing (5.4.1A of 3GPP TS 36.521 or equivalent) and channel bandwidth (5.4.2A) requirements.

$$\text{Nominal channel spacing} = \left\lceil \frac{BW_{\text{Channel}(1)} + BW_{\text{Channel}(2)} - 0.1 |BW_{\text{Channel}(1)} - BW_{\text{Channel}(2)}|}{0.6} \right\rceil 0.3 \text{ [MHz]}$$

<Two Carrier power verification>

Configure		PCC							SCC				Power	
		LTE Band	BW (MHz)	UL Freq. (MHz)	UL Channel	Mod.	UL# RB	UL RB Offset	LTE Band	BW (MHz)	DL Freq. (MHz)	DL Channel	With CA Tx.Power (dBm)	W/O CA Tx.Power (dBm)
Intra-Band	Non-Contiguous	7	20	2510	20850	QPSK	1	0	7	5	2687.5	3425	23.02	23.04
		41	20	2545	40140	QPSK	1	0	41	5	2652.5	41215	23.18	23.21
	Contiguous	7	15	2507.5	20825	QPSK	1	74	7	5	2636.80	2918	22.93	22.98
		7	20	2510	20850	QPSK	1	0	7	20	2649.80	3048	23.02	23.04
		41	20	2545	40140	QPSK	1	0	41	20	2564.80	40338	23.18	23.21

<WLAN Conducted Power>
General Note:

1. Per KDB 248227 D01v02r02, SAR test reduction is determined according to 802.11 transmission mode configurations and certain exposure conditions with multiple test positions. In the 2.4 GHz band, separate SAR procedures are applied to DSSS and OFDM configurations to simplify DSSS test requirements. For OFDM, in both 2.4 and 5 GHz bands, an initial test configuration must be determined for each standalone and aggregated frequency band, according to the transmission mode configuration with the highest maximum output power specified for production units to perform SAR measurements. If the same highest maximum output power applies to different combinations of channel bandwidths, modulations and data rates, additional procedures are applied to determine which test configurations require SAR measurement. When applicable, an initial test position may be applied to reduce the number of SAR measurements required for next to the ear, UMPC mini-tablet or hotspot mode configurations with multiple test positions.
2. For 2.4 GHz 802.11b DSSS, either the initial test position procedure for multiple exposure test positions or the DSSS procedure for fixed exposure position is applied; these are mutually exclusive. For 2.4 GHz and 5 GHz OFDM configurations, the initial test configuration is applied to measure SAR using either the initial test position procedure for multiple exposure test position configurations or the initial test configuration procedures for fixed exposure test conditions. Based on the reported SAR of the measured configurations and maximum output power of the transmission mode configurations that are not included in the initial test configuration, the subsequent test configuration and initial test position procedures are applied to determine if SAR measurements are required for the remaining OFDM transmission configurations. In general, the number of test channels that require SAR measurement is minimized based on maximum output power measured for the test sample(s).
3. For OFDM transmission configurations in the 2.4 GHz and 5 GHz bands, When the same maximum power is specified for multiple transmission modes in a frequency band, the largest channel bandwidth, lowest order modulation, lowest data rate and lowest order 802.11a/g/n/ac mode is used for SAR measurement, on the highest measured output power channel for each frequency band.
4. DSSS and OFDM configurations are considered separately according to the required SAR procedures. SAR is measured in the initial test position using the 802.11 transmission mode configuration required by the DSSS procedure or initial test configuration and subsequent test configuration(s) according to the OFDM procedures.¹⁸ The initial test position procedure is described in the following:
 - a. When the reported SAR of the initial test position is ≤ 0.4 W/kg, further SAR measurement is not required for the other test positions in that exposure configuration and 802.11 transmission mode combinations within the frequency band or aggregated band.
 - b. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
 - c. For all positions/configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions/configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.

Default Power Mode
<2.4GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
2.4GHz WLAN	802.11b 1Mbps	1	2412	18.63	19.00	99.07
		6	2437	19.93	20.00	
		11	2462	18.38	18.50	
	802.11g 6Mbps	1	2412	17.15	17.50	94.71
		6	2437	17.88	18.00	
		11	2462	16.62	17.00	
	802.11n-HT20 MCS0	1	2412	16.80	17.50	95.09
		6	2437	17.69	18.00	
		11	2462	16.50	17.00	
	802.11ac-VHT20 MCS0	1	2412	16.78	17.50	94.87
		6	2437	17.65	18.00	
		11	2462	16.44	17.00	

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	17.16	18.00	95.28
		40	5200	17.15	18.00	
		44	5220	17.18	18.00	
		48	5240	17.12	18.00	
	802.11n-HT20 MCS0	36	5180	17.01	18.00	94.95
		40	5200	16.95	18.00	
		44	5220	16.98	18.00	
		48	5240	16.95	18.00	
	802.11n-HT40 MCS0	38	5190	13.80	14.50	89.32
		46	5230	17.10	18.00	
	802.11ac-VHT20 MCS0	36	5180	16.99	18.00	94.00
		40	5200	16.89	18.00	
		44	5220	16.97	18.00	
		48	5240	16.92	18.00	
	802.11ac-VHT40 MCS0	38	5190	13.77	14.50	89.42
		46	5230	17.09	18.00	
	802.11ac-VHT80 MCS0	42	5210	13.51	14.00	89.16

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	17.06	18.00	95.28
		56	5280	17.01	18.00	
		60	5300	17.05	18.00	
		64	5320	17.04	18.00	
	802.11n-HT20 MCS0	52	5260	16.90	18.00	94.95
		56	5280	16.82	18.00	
		60	5300	16.91	18.00	
		64	5320	16.91	18.00	
	802.11n-HT40 MCS0	54	5270	17.14	18.00	89.32
		62	5310	15.95	17.00	
	802.11ac-VHT20 MCS0	52	5260	16.89	18.00	94.00
		56	5280	16.80	18.00	
		60	5300	16.90	18.00	
		64	5320	16.89	18.00	
	802.11ac-VHT40 MCS0	54	5270	17.11	18.00	89.42
		62	5310	15.94	17.00	
	802.11ac-VHT80 MCS0	58	5290	14.75	15.00	89.16

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	17.97	18.00	95.28
		116	5580	17.32	18.00	
		132	5660	16.83	18.00	
		140	5700	15.35	15.50	
	802.11n-HT20 MCS0	100	5500	17.03	18.00	94.95
		116	5580	17.15	18.00	
		132	5660	16.69	18.00	
		140	5700	15.84	16.00	
	802.11n-HT40 MCS0	102	5510	14.52	15.00	89.32
		110	5550	17.70	18.00	
		134	5670	16.62	18.00	
	802.11ac-VHT20 MCS0	100	5500	17.02	18.00	94.00
		116	5580	17.10	18.00	
		132	5660	16.66	18.00	
		140	5700	15.48	16.00	
	802.11ac-VHT40 MCS0	102	5510	14.50	15.00	89.42
		110	5550	17.67	18.00	
		134	5670	16.60	18.00	
	802.11ac-VHT80 MCS0	106	5530	12.21	12.50	89.16
		138	5690	15.31	16.50	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a MCS0	149	5745	14.50	15.00	95.28
		157	5785	14.30	15.00	
		165	5825	13.57	14.00	
	802.11n-HT20 MCS0	149	5745	15.34	16.00	94.95
		157	5785	13.76	14.50	
		165	5825	12.67	13.50	
	802.11n-HT40 MCS0	151	5755	14.92	15.50	89.32
		159	5795	14.55	15.00	
	802.11ac-VHT20 MCS0	149	5745	15.31	16.00	94.00
		157	5785	13.73	14.50	
		165	5825	12.64	13.50	
	802.11ac-VHT40 MCS0	151	5755	14.84	15.50	89.42
		159	5795	14.52	15.00	
	802.11ac-VHT80 MCS0	155	5775	16.60	17.00	89.16

At-Head Power Mode
<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	15.43	15.50	95.28
		40	5200	15.41	15.50	
		44	5220	15.47	15.50	
		48	5240	15.44	15.50	
	802.11n-HT20 MCS0	36	5180	15.32	15.50	94.95
		40	5200	15.31	15.50	
		44	5220	15.43	15.50	
		48	5240	15.40	15.50	
	802.11n-HT40 MCS0	38	5190	13.80	14.50	89.32
		46	5230	15.46	15.50	
	802.11ac-VHT20 MCS0	36	5180	15.29	15.50	94.00
		40	5200	15.26	15.50	
		44	5220	15.38	15.50	
		48	5240	15.38	15.50	
	802.11ac-VHT40 MCS0	38	5190	13.77	14.50	89.42
		46	5230	15.46	15.50	
	802.11ac-VHT80 MCS0	42	5210	13.51	14.00	89.16

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	15.35	15.50	95.28
		56	5280	15.42	15.50	
		60	5300	15.46	15.50	
		64	5320	15.49	15.50	
	802.11n-HT20 MCS0	52	5260	15.25	15.50	94.95
		56	5280	15.22	15.50	
		60	5300	15.35	15.50	
		64	5320	15.45	15.50	
	802.11n-HT40 MCS0	54	5270	15.37	15.50	89.32
		62	5310	15.24	15.50	
	802.11ac-VHT20 MCS0	52	5260	15.24	15.50	94.00
		56	5280	15.23	15.50	
		60	5300	15.30	15.50	
		64	5320	15.38	15.50	
	802.11ac-VHT40 MCS0	54	5270	15.37	15.50	89.42
		62	5310	15.24	15.50	
	802.11ac-VHT80 MCS0	58	5290	14.75	15.00	89.16

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	14.46	14.50	95.28
		116	5580	14.45	14.50	
		132	5660	14.42	14.50	
		140	5700	14.19	14.50	
	802.11n-HT20 MCS0	100	5500	14.46	14.50	94.95
		116	5580	14.30	14.50	
		132	5660	14.43	14.50	
		140	5700	14.48	14.50	
	802.11n-HT40 MCS0	102	5510	14.35	14.50	89.32
		110	5550	14.29	14.50	
		134	5670	14.31	14.50	
	802.11ac-VHT20 MCS0	100	5500	14.44	14.50	94.00
		116	5580	14.23	14.50	
		132	5660	14.39	14.50	
		140	5700	14.44	14.50	
	802.11ac-VHT40 MCS0	102	5510	14.35	14.50	89.42
		110	5550	14.29	14.50	
		134	5670	14.31	14.50	
	802.11ac-VHT80 MCS0	106	5530	12.21	12.50	89.16
		138	5690	14.44	14.50	

Hotspot Power Mode

<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	16.82	17.00	95.28
		40	5200	16.89	17.00	
		44	5220	16.92	17.00	
		48	5240	16.80	17.00	
	802.11n-HT20 MCS0	36	5180	16.76	17.00	94.95
		40	5200	16.82	17.00	
		44	5220	16.74	17.00	
		48	5240	16.73	17.00	
	802.11n-HT40 MCS0	38	5190	13.80	14.50	89.32
		46	5230	16.94	17.00	
	802.11ac-VHT20 MCS0	36	5180	16.72	17.00	94.00
		40	5200	16.80	17.00	
		44	5220	16.70	17.00	
		48	5240	16.69	17.00	
	802.11ac-VHT40 MCS0	38	5190	13.77	14.50	89.42
		46	5230	16.87	17.00	
	802.11ac-VHT80 MCS0	42	5210	13.51	14.00	89.16

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.8GHz WLAN	802.11a MCS0	149	5745	14.50	15.00	95.28
		157	5785	14.30	15.00	
		165	5825	13.57	14.00	
	802.11n-HT20 MCS0	149	5745	15.34	16.00	94.95
		157	5785	13.76	14.50	
		165	5825	12.67	13.50	
	802.11n-HT40 MCS0	151	5755	14.92	15.50	89.32
		159	5795	14.55	15.00	
	802.11ac-VHT20 MCS0	149	5745	15.31	16.00	94.00
		157	5785	13.73	14.50	
		165	5825	12.64	13.50	
	802.11ac-VHT40 MCS0	151	5755	14.84	15.50	89.42
		159	5795	14.52	15.00	
	802.11ac-VHT80 MCS0	155	5775	16.24	16.50	89.16

Near-body Power Mode
<5GHz WLAN>

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.2GHz WLAN	802.11a 6Mbps	36	5180	16.82	17.00	95.28
		40	5200	16.89	17.00	
		44	5220	16.92	17.00	
		48	5240	16.80	17.00	
	802.11n-HT20 MCS0	36	5180	16.76	17.00	94.95
		40	5200	16.82	17.00	
		44	5220	16.74	17.00	
		48	5240	16.73	17.00	
	802.11n-HT40 MCS0	38	5190	13.80	14.50	89.32
		46	5230	16.94	17.00	
	802.11ac-VHT20 MCS0	36	5180	16.72	17.00	94.00
		40	5200	16.80	17.00	
		44	5220	16.70	17.00	
		48	5240	16.69	17.00	
	802.11ac-VHT40 MCS0	38	5190	13.77	14.50	89.42
		46	5230	16.87	17.00	
	802.11ac-VHT80 MCS0	42	5210	13.51	14.00	89.16

	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
5.3GHz WLAN	802.11a 6Mbps	52	5260	14.90	15.00	95.28
		56	5280	14.88	15.00	
		60	5300	14.70	15.00	
		64	5320	14.74	15.00	
	802.11n-HT20 MCS0	52	5260	14.79	15.00	94.95
		56	5280	14.83	15.00	
		60	5300	14.96	15.00	
		64	5320	14.98	15.00	
	802.11n-HT40 MCS0	54	5270	14.75	15.00	89.32
		62	5310	14.96	15.00	
	802.11ac-VHT20 MCS0	52	5260	14.75	15.00	94.00
		56	5280	14.79	15.00	
		60	5300	14.93	15.00	
		64	5320	14.90	15.00	
	802.11ac-VHT40 MCS0	54	5270	14.67	15.00	89.42
		62	5310	14.88	15.00	
	802.11ac-VHT80 MCS0	58	5290	14.92	15.00	89.16

5.5GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a 6Mbps	100	5500	14.46	14.50	95.28
		116	5580	14.45	14.50	
		132	5660	14.42	14.50	
		140	5700	14.19	14.50	
	802.11n-HT20 MCS0	100	5500	14.46	14.50	94.95
		116	5580	14.30	14.50	
		132	5660	14.43	14.50	
		140	5700	14.48	14.50	
	802.11n-HT40 MCS0	102	5510	14.35	14.50	89.32
		110	5550	14.29	14.50	
		134	5670	14.31	14.50	
	802.11ac-VHT20 MCS0	100	5500	14.44	14.50	94.00
		116	5580	14.23	14.50	
		132	5660	14.39	14.50	
		140	5700	14.44	14.50	
	802.11ac-VHT40 MCS0	102	5510	14.35	14.50	89.42
		110	5550	14.29	14.50	
		134	5670	14.31	14.50	
	802.11ac-VHT80 MCS0	106	5530	12.21	12.50	89.16
		138	5690	14.45	14.50	

5.8GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-Up Limit	Duty Cycle %
	802.11a MCS0	149	5745	14.50	15.00	95.28
		157	5785	14.30	15.00	
		165	5825	13.57	14.00	
	802.11n-HT20 MCS0	149	5745	15.34	16.00	94.95
		157	5785	13.76	14.50	
		165	5825	12.67	13.50	
	802.11n-HT40 MCS0	151	5755	14.92	15.50	89.32
		159	5795	14.55	15.00	
	802.11ac-VHT20 MCS0	149	5745	15.31	16.00	94.00
		157	5785	13.73	14.50	
		165	5825	12.64	13.50	
	802.11ac-VHT40 MCS0	151	5755	14.84	15.50	89.42
		159	5795	14.52	15.00	
	802.11ac-VHT80 MCS0	155	5775	16.24	16.50	89.16

<2.4GHz Bluetooth>
General Note:


1. For 2.4GHz Bluetooth SAR testing was selected 1Mbps due to its highest average power and duty cycle is 76.6% considered in SAR testing, and the duty cycle would be scaled to theoretical 83.3% in reported SAR calculation.

Mode	Channel	Frequency (MHz)	Average power (dBm)		
			1Mbps	2Mbps	3Mbps
BR / EDR	CH 00	2402	11.99	9.46	9.55
	CH 39	2441	11.46	8.54	8.63
	CH 78	2480	11.50	8.95	9.07
Tune-up Limit			13.00	10.50	10.50

Mode	Channel	Frequency (MHz)	Average power (dBm)	
			1Mbps	2Mbps
LE	CH 00	2402	6.99	6.99
	CH 19	2440	6.53	6.53
	CH 39	2480	7.52	7.52
Tune-up Limit			8.00	8.00

12. Antenna Location

<Mobile Phone>



Back View

Distance of the Antenna to the EUT surface/edge						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	≤ 25mm	≤ 25mm	>25mm	≤ 25mm	≤ 25mm	≤ 25mm
BT&WLAN	≤ 25mm	≤ 25mm	≤ 25mm	>25mm	>25mm	≤ 25mm

Positions for SAR tests; Hotspot mode						
Antennas	Back	Front	Top Side	Bottom Side	Right Side	Left Side
WWAN	Yes	Yes	No	Yes	Yes	Yes
BT&WLAN	Yes	Yes	Yes	No	No	Yes

General Note:

- Referring to KDB 941225 D06 v02r01, when the overall device length and width are $\geq 9\text{cm} \times 5\text{cm}$, the test distance is 10 mm. SAR must be measured for all sides and surfaces with a transmitting antenna located within 25mm from that surface or edge

13. SAR Test Results

General Note:

1. Per KDB 447498 D01v06, the reported SAR is the measured SAR value adjusted for maximum tune-up tolerance.
 - a. Tune-up scaling Factor = tune-up limit power (mW) / EUT RF power (mW), where tune-up limit is the maximum rated power among all production units.
 - b. For SAR testing of WLAN signal with non-100% duty cycle, the measured SAR is scaled-up by the duty cycle scaling factor which is equal to "1/(duty cycle)"
 - c. For WWAN: Reported SAR(W/kg)= Measured SAR(W/kg)*Tune-up Scaling Factor
 - d. For WLAN/Bluetooth: Reported SAR(W/kg)= Measured SAR(W/kg)* Duty Cycle scaling factor * Tune-up scaling factor
 - e. For TDD LTE SAR measurement, the duty cycle 1:1.59 (62.9 %) was used perform testing and considering the theoretical duty cycle of 63.3% for extended cyclic prefix in the uplink, and the theoretical duty cycle of 62.9% for normal cyclic prefix in uplink, a scaling factor of extended cyclic prefix 63.3%/62.9% = 1.006 is applied to scale-up the measured SAR result.
The Reported TDD LTE SAR = measured SAR (W/kg)* Tune-up Scaling Factor* scaling factor for extended cyclic prefix.
2. Per KDB 447498 D01v06, for each exposure position, testing of other required channels within the operating mode of a frequency band is not required when the *reported* 1-g or 10-g SAR for the mid-band or highest output power channel is:
 - ≤ 0.8 W/kg or 2.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≤ 100 MHz
 - ≤ 0.6 W/kg or 1.5 W/kg, for 1-g or 10-g respectively, when the transmission band is between 100 MHz and 200 MHz
 - ≤ 0.4 W/kg or 1.0 W/kg, for 1-g or 10-g respectively, when the transmission band is ≥ 200 MHz
3. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
4. Pre KDB648474 D04v01r03, when the reported SAR for a body-worn accessory, measured without a headset connected to the handset, is > 1.2 W/kg, the highest reported SAR configuration for that wireless mode and frequency band should be repeated for that body-worn accessory with a headset attached to the handset.
5. While the device operating in near-body condition by end user, the device will limit different maximum output powers on the GSM850, GSM1900, WCDMA B2 / B4/ B5, LTE B2 / B4 / B7 / B38 / B41 transmitter and detail descriptions of the power reduction mechanism are included in the operational description.
6. While the device operating in mobile hotspot session, the device will reduce output powers on the GSM850, GSM1900, WCDMA B2 / B4 / B5 LTE B2 / B4 / B7 / B38 / B41 transmitter and detail descriptions of the power reduction mechanism are included in the operational description.
7. While the device operating in handheld condition, the device will limit different maximum output powers on the GSM 850, WCDMA B2 / B4 and LTE B2 / B4 / B7 transmitter and detail descriptions of the power reduction mechanism are included in the operational description.
8. While the device operating in Held to head, near-body and mobile hotspot session, the device will limit different maximum output powers on the WLAN transmitter and detail descriptions of the power reduction mechanism are included in the operational description.
9. For front and back position at hotspot exposure condition was choose higher power level for SAR compliance of GSM1900, WCDMA B2/B4 and LTE B2/B4/B41.
10. Per KDB648474 D04v01r03, for smart phones with a display diagonal dimension > 15.0 cm or an overall diagonal dimension > 16.0 cm, when hotspot mode applies, 10-g product specific SAR is required only for the surfaces and edges with hotspot mode 1-g reported SAR > 1.2 W/kg, however, when power reduction applies to hotspot mode the measured SAR must be scaled to the maximum output power, including tolerance, allowed for phablet modes to compare with the 1.2 W/kg SAR test reduction threshold, for this device only for WWAN transmitter scaled to maximum output power is higher than 1.2W/kg of GSM850, GSM1900, WCDMA B2 / B4 / B5, LTE B2 / B4 / B7 / B41 and 5GHz WLAN,, therefore product specific SAR is necessary.
11. For 5.3 / 5.5 GHz WLAN product specific SAR is necessary too, due to an overall diagonal dimension is > 16 cm.
12. Use a higher power level conservative test for the front and back positions of hotspot exposure condition.

GSM Note:

1. Per KDB 941225 D01v03r01, for SAR test reduction for GSM / GPRS / EDGE modes is determined by the source-based time-averaged output power including tune-up tolerance. The mode with highest specified time-averaged output power should be tested for SAR compliance in the applicable exposure conditions. For modes with the same specified maximum output power and tolerance, the higher number time-slot configuration should be tested. For Head SAR Test, the GPRS (4Tx slots) for GSM850/GSM1900 is considered as the primary mode. For Hotspot, Body-worn, Extremity SAR Test, the GPRS (2Tx slots) for GSM850 and GPRS (1Tx slots) for GSM1900 are considered as the primary mode.
2. Other configurations of GSM / GPRS / EDGE are considered as secondary modes. The 3G SAR test reduction procedure is applied, when the maximum output power and tune-up tolerance specified for production units in a secondary mode is $\leq \frac{1}{4}$ dB higher than the primary mode, SAR measurement is not required for the secondary mode.

UMTS Note:

1. Per KDB 941225 D01v03r01, for SAR testing is measured using a 12.2 kbps RMC with TPC bits configured to all "1's".
2. Per KDB 941225 D01v03r01, RMC 12.2kbps setting is used to evaluate SAR. The maximum output power and tune-up tolerance specified for production units in HSDPA / HSUPA / DC-HSDPA is $\leq \frac{1}{4}$ dB higher than RMC 12.2Kbps or when the highest reported SAR of the RMC12.2Kbps is scaled by the ratio of specified maximum output power and tune-up tolerance of HSDPA / HSUPA / DC-HSDPA to RMC12.2Kbps and the adjusted SAR is ≤ 1.2 W/kg, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA, and according to the following RF output power, the output power results of the secondary modes (HSUPA, HSDPA, DC-HSDPA) are less than $\frac{1}{4}$ dB higher than the primary modes; therefore, SAR measurement is not required for HSDPA / HSUPA / DC-HSDPA.

LTE Note:

1. Per KDB 941225 D05v02r05, start with the largest channel bandwidth and measure SAR for QPSK with 1 RB allocation, using the RB offset and required test channel combination with the highest maximum output power for RB offsets at the upper edge, middle and lower edge of each required test channel.
2. Per KDB 941225 D05v02r05, 50% RB allocation for QPSK SAR testing follows 1RB QPSK allocation procedure.
3. Per KDB 941225 D05v02r05, For QPSK with 100% RB allocation, SAR is not required when the highest maximum output power for 100 % RB allocation is less than the highest maximum output power in 50% and 1 RB allocations and the highest reported SAR for 1 RB and 50% RB allocation are ≤ 0.8 W/kg. Otherwise, SAR is measured for the highest output power channel; and if the reported SAR is > 1.45 W/kg, the remaining required test channels must also be tested.
4. Per KDB 941225 D05v02r05, 16QAM output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in QPSK and the reported SAR for the QPSK configuration is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, 16QAM SAR testing is not required.
5. Per KDB 941225 D05v02r05, Smaller bandwidth output power for each RB allocation configuration is $> \text{not } \frac{1}{2}$ dB higher than the same configuration in the largest supported bandwidth, and the reported SAR for the largest supported bandwidth is ≤ 1.45 W/kg; Per KDB 941225 D05v02r05, smaller bandwidth SAR testing is not required.
6. For LTE B4 / B26 the maximum bandwidth does not support three non-overlapping channels, per KDB 941225 D05v02r05, when a device supports overlapping channel assignment in a channel bandwidth configuration, the middle channel of the group of overlapping channels should be selected for testing.
7. LTE band 5 / 38 SAR test was covered by Band 26 / 41; according to TCB workshop, SAR test for overlapping LTE bands can be reduced if
 - a. The maximum output power, including tolerance, for the smaller band is $\leq$ the larger band to qualify for the SAR test exclusion.
 - b. The channel bandwidth and other operating parameters for the smaller band are fully supported by the larger band.

WLAN Note:

1. Per KDB 248227 D01v02r02, for 2.4GHz 802.11g/n SAR testing is not required when the highest reported SAR for DSSS is adjusted by the ratio of OFDM to DSSS specified maximum output power and the adjusted SAR is ≤ 1.2 W/kg.
2. Per KDB 248227 D01v02r02, U-NII-1 SAR testing is not required when the U-NII-2A band highest reported SAR for a test configuration is ≤ 1.2 W/kg, SAR is not required for U-NII-1 band.
3. When the reported SAR of the test position is > 0.4 W/kg, SAR is repeated for the 802.11 transmission mode configuration tested in the initial test position to measure the subsequent next closet/smallest test separation distance and maximum coupling test position on the highest maximum output power channel, until the report SAR is ≤ 0.8 W/kg or all required test position are tested.
4. For all positions / configurations, when the reported SAR is > 0.8 W/kg, SAR is measured for these test positions / configurations on the subsequent next highest measured output power channel(s) until the reported SAR is ≤ 1.2 W/kg or all required channels are tested.
5. During SAR testing the WLAN transmission was verified using a spectrum analyzer.

13.1 Head SAR
<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (4 Tx slots)	Right Cheek	0mm	251	848.8	25.60	27.50	1.549	0.01	0.225	0.348
	GSM850	GPRS (4 Tx slots)	Right Tilted	0mm	251	848.8	25.60	27.50	1.549	-0.13	0.158	0.245
01	GSM850	GPRS (4 Tx slots)	Left Cheek	0mm	251	848.8	25.60	27.50	1.549	-0.04	0.260	0.403
	GSM850	GPRS (4 Tx slots)	Left Tilted	0mm	251	848.8	25.60	27.50	1.549	0.03	0.128	0.198
02	GSM1900	GPRS (4 Tx slots)	Right Cheek	0mm	512	1850.2	23.36	24.50	1.300	0.19	0.050	0.065
	GSM1900	GPRS (4 Tx slots)	Right Tilted	0mm	512	1850.2	23.36	24.50	1.300	0.18	0.025	0.033
	GSM1900	GPRS (4 Tx slots)	Left Cheek	0mm	512	1850.2	23.36	24.50	1.300	-0.04	0.048	0.062
	GSM1900	GPRS (4 Tx slots)	Left Tilted	0mm	512	1850.2	23.36	24.50	1.300	0.03	0.023	0.030

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
03	WCDMA II	RMC 12.2Kbps	Right Cheek	0mm	9400	1880	22.96	24.00	1.271	-0.02	0.087	0.111
	WCDMA II	RMC 12.2Kbps	Right Tilted	0mm	9400	1880	22.96	24.00	1.271	-0.19	0.048	0.061
	WCDMA II	RMC 12.2Kbps	Left Cheek	0mm	9400	1880	22.96	24.00	1.271	0.19	0.078	0.099
	WCDMA II	RMC 12.2Kbps	Left Tilted	0mm	9400	1880	22.96	24.00	1.271	0.09	0.025	0.032
	WCDMA IV	RMC 12.2Kbps	Right Cheek	0mm	1513	1752.6	23.04	24.00	1.247	-0.11	0.077	0.096
	WCDMA IV	RMC 12.2Kbps	Right Tilted	0mm	1513	1752.6	23.04	24.00	1.247	-0.06	0.038	0.047
04	WCDMA IV	RMC 12.2Kbps	Left Cheek	0mm	1513	1752.6	23.04	24.00	1.247	0.13	0.098	0.122
	WCDMA IV	RMC 12.2Kbps	Left Tilted	0mm	1513	1752.6	23.04	24.00	1.247	0.1	0.021	0.026
	WCDMA V	RMC 12.2Kbps	Right Cheek	0mm	4182	836.4	23.94	25.00	1.276	0.04	0.190	0.243
	WCDMA V	RMC 12.2Kbps	Right Tilted	0mm	4182	836.4	23.94	25.00	1.276	0.07	0.136	0.174
05	WCDMA V	RMC 12.2Kbps	Left Cheek	0mm	4182	836.4	23.94	25.00	1.276	-0.02	0.299	0.382
	WCDMA V	RMC 12.2Kbps	Left Tilted	0mm	4182	836.4	23.94	25.00	1.276	-0.17	0.135	0.172

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
06	LTE Band 2	20M	QPSK	1	0	Right Cheek	0mm	19100	1900	22.73	24.00	1.340	0.11	0.090	0.121
	LTE Band 2	20M	QPSK	50	24	Right Cheek	0mm	18900	1880	21.81	23.00	1.315	0.15	0.083	0.109
	LTE Band 2	20M	QPSK	1	0	Right Tilted	0mm	19100	1900	22.73	24.00	1.340	-0.19	0.035	0.047
	LTE Band 2	20M	QPSK	50	24	Right Tilted	0mm	18900	1880	21.81	23.00	1.315	-0.06	0.032	0.042
	LTE Band 2	20M	QPSK	1	0	Left Cheek	0mm	19100	1900	22.73	24.00	1.340	0.12	0.079	0.106
	LTE Band 2	20M	QPSK	50	24	Left Cheek	0mm	18900	1880	21.81	23.00	1.315	0.08	0.071	0.093
	LTE Band 2	20M	QPSK	1	0	Left Tilted	0mm	19100	1900	22.73	24.00	1.340	0.12	0.032	0.043
	LTE Band 2	20M	QPSK	50	24	Left Tilted	0mm	18900	1880	21.81	23.00	1.315	0.12	0.027	0.036
07	LTE Band 4	20M	QPSK	1	0	Right Cheek	0mm	20175	1732.5	22.77	24.00	1.327	0.19	0.095	0.126
	LTE Band 4	20M	QPSK	50	24	Right Cheek	0mm	20175	1732.5	21.82	23.00	1.312	0.04	0.065	0.085
	LTE Band 4	20M	QPSK	1	0	Right Tilted	0mm	20175	1732.5	22.77	24.00	1.327	0.06	0.033	0.044
	LTE Band 4	20M	QPSK	50	24	Right Tilted	0mm	20175	1732.5	21.82	23.00	1.312	0.03	0.029	0.038
	LTE Band 4	20M	QPSK	1	0	Left Cheek	0mm	20175	1732.5	22.77	24.00	1.327	0.11	0.094	0.125
	LTE Band 4	20M	QPSK	50	24	Left Cheek	0mm	20175	1732.5	21.82	23.00	1.312	0.07	0.076	0.100
	LTE Band 4	20M	QPSK	1	0	Left Tilted	0mm	20175	1732.5	22.77	24.00	1.327	0.11	0.029	0.038
	LTE Band 4	20M	QPSK	50	24	Left Tilted	0mm	20175	1732.5	21.82	23.00	1.312	0.04	0.022	0.029
08	LTE Band 7	20M	QPSK	1	0	Right Cheek	0mm	20850	2510	23.04	24.00	1.247	0.09	0.252	0.314
	LTE Band 7	20M	QPSK	50	24	Right Cheek	0mm	20850	2510	22.13	23.00	1.222	0.13	0.198	0.242
	LTE Band 7	20M	QPSK	1	0	Right Tilted	0mm	20850	2510	23.04	24.00	1.247	0.07	0.100	0.125
	LTE Band 7	20M	QPSK	50	24	Right Tilted	0mm	20850	2510	22.13	23.00	1.222	0.13	0.075	0.092
	LTE Band 7	20M	QPSK	1	0	Left Cheek	0mm	20850	2510	23.04	24.00	1.247	0.12	0.161	0.201
	LTE Band 7	20M	QPSK	50	24	Left Cheek	0mm	20850	2510	22.13	23.00	1.222	0.16	0.127	0.155
	LTE Band 7	20M	QPSK	1	0	Left Tilted	0mm	20850	2510	23.04	24.00	1.247	0.08	0.164	0.205
	LTE Band 7	20M	QPSK	50	24	Left Tilted	0mm	20850	2510	22.13	23.00	1.222	0.15	0.124	0.152
	LTE Band 26	15M	QPSK	1	0	Right Cheek	0mm	26865	831.5	22.74	24.00	1.337	0.1	0.199	0.266
	LTE Band 26	15M	QPSK	36	0	Right Cheek	0mm	26865	831.5	21.79	23.00	1.321	0.03	0.105	0.139
	LTE Band 26	15M	QPSK	1	0	Right Tilted	0mm	26865	831.5	22.74	24.00	1.337	0.07	0.074	0.099
	LTE Band 26	15M	QPSK	36	0	Right Tilted	0mm	26865	831.5	21.79	23.00	1.321	0.13	0.074	0.098
09	LTE Band 26	15M	QPSK	1	0	Left Cheek	0mm	26865	831.5	22.74	24.00	1.337	0.01	0.254	0.339
	LTE Band 26	15M	QPSK	36	0	Left Cheek	0mm	26865	831.5	21.79	23.00	1.321	0.03	0.140	0.185
	LTE Band 26	15M	QPSK	1	0	Left Tilted	0mm	26865	831.5	22.74	24.00	1.337	0.02	0.149	0.199
	LTE Band 26	15M	QPSK	36	0	Left Tilted	0mm	26865	831.5	21.79	23.00	1.321	0.06	0.071	0.094

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
10	LTE Band 41	20M	QPSK	1	0	Right Cheek	0mm	40140	2545	23.21	24.00	1.199	62.90	1.006	0.12	0.161	0.194
	LTE Band 41	20M	QPSK	50	0	Right Cheek	0mm	40140	2545	22.22	23.00	1.197	62.90	1.006	0.19	0.126	0.152
	LTE Band 41	20M	QPSK	1	0	Right Tilted	0mm	40140	2545	23.21	24.00	1.199	62.90	1.006	0.13	0.060	0.072
	LTE Band 41	20M	QPSK	50	0	Right Tilted	0mm	40140	2545	22.22	23.00	1.197	62.90	1.006	0.16	0.049	0.059
	LTE Band 41	20M	QPSK	1	0	Left Cheek	0mm	40140	2545	23.21	24.00	1.199	62.90	1.006	0.16	0.091	0.110
	LTE Band 41	20M	QPSK	50	0	Left Cheek	0mm	40140	2545	22.22	23.00	1.197	62.90	1.006	0.08	0.072	0.087
	LTE Band 41	20M	QPSK	1	0	Left Tilted	0mm	40140	2545	23.21	24.00	1.199	62.90	1.006	0.17	0.105	0.127
	LTE Band 41	20M	QPSK	50	0	Left Tilted	0mm	40140	2545	22.22	23.00	1.197	62.90	1.006	0.11	0.086	0.104

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	-0.04	1.120	1.148
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	1	2412	18.63	19.00	1.089	99.07	1.009	-0.08	0.991	1.089
	WLAN2.4GHz	802.11b 1Mbps	Right Cheek	0mm	11	2462	18.38	18.50	1.028	99.07	1.009	0.05	0.758	0.786
11	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	0.06	1.150	1.179
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	1	2412	18.63	19.00	1.089	99.07	1.009	-0.07	0.993	1.091
	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	11	2462	18.38	18.50	1.028	99.07	1.009	-0.06	0.769	0.798
	WLAN2.4GHz	802.11b 1Mbps	Left Cheek	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	-0.11	0.760	0.779
	WLAN2.4GHz	802.11b 1Mbps	Left Tilted	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	-0.01	0.731	0.750
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.02	0.976	1.126
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	62	5310	15.24	15.50	1.062	89.32	1.120	0.16	0.915	1.088
12	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.06	0.978	1.129
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	62	5310	15.24	15.50	1.062	89.32	1.120	0.01	0.889	1.057
	WLAN5GHz	802.11n-HT40 MCS0	Left Cheek	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.08	0.636	0.734
	WLAN5GHz	802.11n-HT40 MCS0	Left Tilted	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.04	0.673	0.777
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	138	5690	14.44	14.50	1.014	89.16	1.122	0.03	0.911	1.037
13	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	102	5510	14.35	14.50	1.035	89.32	1.120	0.07	0.973	1.128
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	138	5690	14.44	14.50	1.014	89.16	1.122	0.01	0.810	0.922
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	102	5510	14.35	14.50	1.035	89.32	1.120	0.01	0.835	0.968
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	138	5690	14.44	14.50	1.014	89.16	1.122	-0.03	0.496	0.564
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	138	5690	14.44	14.50	1.014	89.16	1.122	0.05	0.489	0.557
14	WLAN5GHz	802.11ac-VHT80 MCS0	Right Cheek	0mm	155	5775	16.60	17.00	1.097	89.16	1.122	0.05	0.831	1.023
	WLAN5GHz	802.11n-HT40 MCS0	Right Cheek	0mm	149	5745	15.34	16.00	1.165	94.95	1.053	0.19	0.747	0.917
	WLAN5GHz	802.11ac-VHT80 MCS0	Right Tilted	0mm	155	5775	16.60	17.00	1.097	89.16	1.122	0.12	0.799	0.983
	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	149	5745	15.34	16.00	1.165	94.95	1.053	0.01	0.706	0.866
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Cheek	0mm	155	5775	16.60	17.00	1.097	89.16	1.122	0.13	0.390	0.480
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Tilted	0mm	155	5775	16.60	17.00	1.097	89.16	1.122	0.08	0.410	0.505

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
15	Bluetooth	1Mbps	Right Cheek	0mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.01	0.125	0.171
	Bluetooth	1Mbps	Right Tilted	0mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.03	0.119	0.163
	Bluetooth	1Mbps	Left Cheek	0mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.04	0.086	0.118
	Bluetooth	1Mbps	Left Tilted	0mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.07	0.083	0.113

13.2 Hotspot SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (2 Tx slots)	Front	5mm	251	848.8	29.40	30.00	1.148	0.11	0.549	0.630
16	GSM850	GPRS (2 Tx slots)	Back	5mm	251	848.8	29.40	30.00	1.148	0.02	1.240	1.424
	GSM850	GPRS (2 Tx slots)	Back	5mm	128	824.2	28.50	30.00	1.413	-0.06	0.902	1.274
	GSM850	GPRS (2 Tx slots)	Back	5mm	189	836.4	28.92	30.00	1.282	0.06	1.110	1.423
	GSM850	GPRS (2 Tx slots)	Left Side	5mm	251	848.8	29.40	30.00	1.148	-0.02	0.598	0.687
	GSM850	GPRS (2 Tx slots)	Right Side	5mm	251	848.8	29.40	30.00	1.148	-0.03	0.282	0.324
	GSM850	GPRS (2 Tx slots)	Bottom Side	5mm	251	848.8	29.40	30.00	1.148	-0.01	0.754	0.866
	GSM850	GPRS (2 Tx slots)	Bottom Side	5mm	128	824.2	28.50	30.00	1.413	-0.05	0.553	0.781
	GSM850	GPRS (2 Tx slots)	Bottom Side	5mm	189	836.4	28.92	30.00	1.282	0.1	0.674	0.864
	GSM1900	GPRS (1 Tx slot)	Front	5mm	512	1850.2	26.44	26.50	1.014	0.15	0.913	0.926
	GSM1900	GPRS (1 Tx slot)	Front	5mm	661	1880	26.38	26.50	1.028	-0.03	0.866	0.890
	GSM1900	GPRS (1 Tx slot)	Front	5mm	810	1909.8	26.27	26.50	1.054	0.03	0.843	0.889
17	GSM1900	GPRS (1 Tx slot)	Back	5mm	512	1850.2	26.44	26.50	1.014	-0.08	1.360	1.379
	GSM1900	GPRS (1 Tx slot)	Back	5mm	661	1880	26.38	26.50	1.028	-0.03	1.300	1.336
	GSM1900	GPRS (1 Tx slot)	Back	5mm	810	1909.8	26.27	26.50	1.054	-0.15	1.130	1.191
	GSM1900	GPRS (1 Tx slot)	Left Side	5mm	512	1850.2	24.04	25.00	1.247	0.19	0.029	0.036
	GSM1900	GPRS (1 Tx slot)	Right Side	5mm	512	1850.2	24.04	25.00	1.247	0.1	0.023	0.029
	GSM1900	GPRS (1 Tx slot)	Bottom Side	5mm	512	1850.2	24.04	25.00	1.247	0.05	0.994	1.240
	GSM1900	GPRS (1 Tx slot)	Bottom Side	5mm	661	1880	23.97	25.00	1.268	0.09	1.030	1.306
	GSM1900	GPRS (1 Tx slot)	Bottom Side	5mm	810	1909.8	23.99	25.00	1.262	-0.02	0.739	0.932

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	5mm	9538	1907.6	16.37	17.50	1.297	0.06	0.708	0.918
	WCDMA II	RMC 12.2Kbps	Front	5mm	9262	1852.4	16.11	17.50	1.377	0.04	0.593	0.817
	WCDMA II	RMC 12.2Kbps	Front	5mm	9400	1880	16.25	17.50	1.334	0.07	0.702	0.936
18	WCDMA II	RMC 12.2Kbps	Back	5mm	9538	1907.6	16.37	17.50	1.297	-0.04	1.080	1.401
	WCDMA II	RMC 12.2Kbps	Back	5mm	9262	1852.4	16.11	17.50	1.377	-0.04	1.010	1.391
	WCDMA II	RMC 12.2Kbps	Back	5mm	9400	1880	16.25	17.50	1.334	-0.04	1.050	1.400
	WCDMA II	RMC 12.2Kbps	Left Side	5mm	9538	1907.6	14.33	15.50	1.309	-0.11	0.051	0.067
	WCDMA II	RMC 12.2Kbps	Right Side	5mm	9538	1907.6	14.33	15.50	1.309	0.12	0.028	0.037
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	9538	1907.6	14.33	15.50	1.309	-0.17	1.030	1.348
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	9262	1852.4	14.10	15.50	1.380	0.18	0.942	1.300
	WCDMA II	RMC 12.2Kbps	Bottom Side	5mm	9400	1880	14.23	15.50	1.340	0.01	1.020	1.366
	WCDMA IV	RMC 12.2Kbps	Front	5mm	1513	1752.6	16.85	18.00	1.303	-0.02	0.600	0.782
	WCDMA IV	RMC 12.2Kbps	Back	5mm	1513	1752.6	16.85	18.00	1.303	-0.02	0.919	1.198
19	WCDMA IV	RMC 12.2Kbps	Back	5mm	1312	1712.4	16.56	18.00	1.393	0.06	0.922	1.284
	WCDMA IV	RMC 12.2Kbps	Back	5mm	1413	1732.6	16.66	18.00	1.361	-0.05	0.886	1.206
	WCDMA IV	RMC 12.2Kbps	Left Side	5mm	1513	1752.6	14.84	16.00	1.306	-0.02	0.045	0.059
	WCDMA IV	RMC 12.2Kbps	Right Side	5mm	1513	1752.6	14.84	16.00	1.306	0.1	0.026	0.034
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	1513	1752.6	14.84	16.00	1.306	-0.06	0.863	1.127
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	1312	1712.4	14.55	16.00	1.396	0.12	0.771	1.077
	WCDMA IV	RMC 12.2Kbps	Bottom Side	5mm	1413	1732.6	14.69	16.00	1.352	0.13	0.816	1.103
	WCDMA V	RMC 12.2Kbps	Front	5mm	4182	836.4	23.22	24.50	1.343	-0.08	0.650	0.873
	WCDMA V	RMC 12.2Kbps	Front	5mm	4132	826.4	23.22	24.50	1.343	0.06	0.622	0.835
	WCDMA V	RMC 12.2Kbps	Front	5mm	4233	846.6	23.04	24.50	1.400	0.12	0.618	0.865
	WCDMA V	RMC 12.2Kbps	Back	5mm	4182	836.4	23.22	24.50	1.343	-0.07	1.010	1.356
	WCDMA V	RMC 12.2Kbps	Back	5mm	4132	826.4	23.22	24.50	1.343	-0.1	0.975	1.309
20	WCDMA V	RMC 12.2Kbps	Back	5mm	4233	846.6	23.04	24.50	1.400	-0.11	1.010	1.414
	WCDMA V	RMC 12.2Kbps	Left Side	5mm	4182	836.4	23.22	24.50	1.343	-0.08	0.480	0.645
	WCDMA V	RMC 12.2Kbps	Right Side	5mm	4182	836.4	23.22	24.50	1.343	-0.07	0.236	0.317
	WCDMA V	RMC 12.2Kbps	Bottom Side	5mm	4182	836.4	23.22	24.50	1.343	-0.16	0.589	0.791

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	5mm	18900	1880	16.47	17.50	1.268	0.04	0.655	0.830
	LTE Band 2	20M	QPSK	1	0	Front	5mm	18700	1860	16.26	17.50	1.330	0.03	0.581	0.773
	LTE Band 2	20M	QPSK	1	0	Front	5mm	19100	1900	16.46	17.50	1.271	0.02	0.712	0.905
	LTE Band 2	20M	QPSK	50	0	Front	5mm	19100	1900	16.32	17.50	1.312	0	0.737	0.967
	LTE Band 2	20M	QPSK	50	50	Front	5mm	18700	1860	16.13	17.50	1.371	0.1	0.649	0.890
	LTE Band 2	20M	QPSK	50	24	Front	5mm	18900	1880	16.31	17.50	1.315	0.12	0.682	0.897
	LTE Band 2	20M	QPSK	100	0	Front	5mm	19100	1900	16.27	17.50	1.327	0.01	0.717	0.952
	LTE Band 2	20M	QPSK	1	0	Back	5mm	18900	1880	16.47	17.50	1.268	-0.04	0.917	1.162
	LTE Band 2	20M	QPSK	1	0	Back	5mm	18700	1860	16.26	17.50	1.330	-0.07	0.905	1.204
	LTE Band 2	20M	QPSK	1	0	Back	5mm	19100	1900	16.46	17.50	1.271	-0.1	1.010	1.283
	LTE Band 2	20M	QPSK	50	0	Back	5mm	19100	1900	16.32	17.50	1.312	-0.12	1.030	1.352
	LTE Band 2	20M	QPSK	50	50	Back	5mm	18700	1860	16.13	17.50	1.371	-0.09	0.897	1.230
	LTE Band 2	20M	QPSK	50	24	Back	5mm	18900	1880	16.31	17.50	1.315	-0.07	0.991	1.303
	LTE Band 2	20M	QPSK	100	0	Back	5mm	19100	1900	16.27	17.50	1.327	-0.11	1.050	1.394
	LTE Band 2	20M	QPSK	1	0	Left Side	5mm	19100	1900	15.14	16.00	1.219	0.14	0.040	0.049
	LTE Band 2	20M	QPSK	50	0	Left Side	5mm	19100	1900	15.02	16.00	1.253	-0.06	0.041	0.051
	LTE Band 2	20M	QPSK	1	0	Right Side	5mm	19100	1900	15.14	16.00	1.219	0.17	0.028	0.034
	LTE Band 2	20M	QPSK	50	0	Right Side	5mm	19100	1900	15.02	16.00	1.253	0.05	0.030	0.038
	LTE Band 2	20M	QPSK	1	0	Bottom Side	5mm	19100	1900	15.14	16.00	1.219	0.03	1.030	1.256
	LTE Band 2	20M	QPSK	1	0	Bottom Side	5mm	18700	1860	14.82	16.00	1.312	-0.02	0.815	1.069
	LTE Band 2	20M	QPSK	1	0	Bottom Side	5mm	18900	1880	15.09	16.00	1.233	0.04	1.060	1.307
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	19100	1900	15.02	16.00	1.253	0.14	1.050	1.316
	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	18700	1860	14.85	16.00	1.303	0.01	0.858	1.118
21	LTE Band 2	20M	QPSK	50	0	Bottom Side	5mm	18900	1880	15.01	16.00	1.256	0.01	1.120	1.407
	LTE Band 2	20M	QPSK	100	0	Bottom Side	5mm	19100	1900	14.97	16.00	1.268	0.01	1.090	1.382
	LTE Band 4	20M	QPSK	1	0	Front	5mm	20175	1732.5	16.21	17.00	1.199	-0.04	0.505	0.606
	LTE Band 4	20M	QPSK	50	0	Front	5mm	20175	1732.5	15.83	17.00	1.309	0.03	0.518	0.678
	LTE Band 4	20M	QPSK	1	0	Back	5mm	20175	1732.5	16.21	17.00	1.199	-0.05	0.935	1.122
	LTE Band 4	20M	QPSK	50	0	Back	5mm	20175	1732.5	15.83	17.00	1.309	-0.01	0.921	1.206
22	LTE Band 4	20M	QPSK	100	0	Back	5mm	20175	1732.5	15.77	17.00	1.327	-0.06	0.980	1.301
	LTE Band 4	20M	QPSK	1	0	Left Side	5mm	20175	1732.5	14.14	15.00	1.219	-0.02	0.032	0.039
	LTE Band 4	20M	QPSK	50	0	Left Side	5mm	20175	1732.5	14.03	15.00	1.250	-0.01	0.033	0.041
	LTE Band 4	20M	QPSK	1	0	Right Side	5mm	20175	1732.5	14.14	15.00	1.219	0.17	0.020	0.024
	LTE Band 4	20M	QPSK	50	0	Right Side	5mm	20175	1732.5	14.03	15.00	1.250	0.17	0.025	0.031
	LTE Band 4	20M	QPSK	1	0	Bottom Side	5mm	20175	1732.5	14.14	15.00	1.219	0.09	0.897	1.093
	LTE Band 4	20M	QPSK	50	0	Bottom Side	5mm	20175	1732.5	14.03	15.00	1.250	0.08	0.957	1.196
	LTE Band 4	20M	QPSK	100	0	Bottom Side	5mm	20175	1732.5	13.97	15.00	1.268	0.13	0.875	1.109

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 7	20M	QPSK	1	49	Front	5mm	20850	2510	19.68	20.50	1.208	-0.04	0.858	1.036
	LTE Band 7	20M	QPSK	1	49	Front	5mm	21100	2535	19.41	20.50	1.285	-0.05	0.805	1.035
	LTE Band 7	20M	QPSK	1	49	Front	5mm	21350	2560	19.56	20.50	1.242	0.01	0.798	0.991
	LTE Band 7	20M	QPSK	50	0	Front	5mm	20850	2510	19.79	20.50	1.178	-0.01	0.796	0.937
	LTE Band 7	20M	QPSK	50	0	Front	5mm	21100	2535	19.51	20.50	1.256	0	0.743	0.933
	LTE Band 7	20M	QPSK	50	0	Front	5mm	21350	2560	19.63	20.50	1.222	-0.05	0.768	0.938
	LTE Band 7	20M	QPSK	100	0	Front	5mm	20850	2510	19.70	20.50	1.202	-0.06	0.762	0.916
	LTE Band 7	20M	QPSK	1	49	Back	5mm	20850	2510	19.68	20.50	1.208	0.07	0.818	0.988
	LTE Band 7	20M	QPSK	1	49	Back	5mm	21100	2535	19.41	20.50	1.285	0.09	0.782	1.005
	LTE Band 7	20M	QPSK	1	49	Back	5mm	21350	2560	19.56	20.50	1.242	0.03	0.828	1.028
	LTE Band 7	20M	QPSK	50	0	Back	5mm	20850	2510	19.79	20.50	1.178	0.1	0.906	1.067
	LTE Band 7	20M	QPSK	50	0	Back	5mm	21100	2535	19.51	20.50	1.256	0.06	0.794	0.997
23	LTE Band 7	20M	QPSK	50	0	Back	5mm	21350	2560	19.63	20.50	1.222	0.08	0.988	1.207
	LTE Band 7	20M	QPSK	100	0	Back	5mm	20850	2510	19.70	20.50	1.202	0.02	0.810	0.974
	LTE Band 7	20M	QPSK	1	49	Left Side	5mm	20850	2510	19.68	20.50	1.208	0.03	0.079	0.095
	LTE Band 7	20M	QPSK	50	0	Left Side	5mm	20850	2510	19.79	20.50	1.178	0.07	0.066	0.078
	LTE Band 7	20M	QPSK	1	49	Right Side	5mm	20850	2510	19.68	20.50	1.208	-0.17	0.430	0.519
	LTE Band 7	20M	QPSK	50	0	Right Side	5mm	20850	2510	19.79	20.50	1.178	-0.06	0.401	0.472
	LTE Band 7	20M	QPSK	1	49	Bottom Side	5mm	20850	2510	19.68	20.50	1.208	0.03	0.511	0.617
	LTE Band 7	20M	QPSK	50	0	Bottom Side	5mm	20850	2510	19.79	20.50	1.178	0.11	0.476	0.561
	LTE Band 26	15M	QPSK	1	0	Front	5mm	26865	831.5	22.74	24.00	1.337	-0.11	0.463	0.619
	LTE Band 26	15M	QPSK	36	0	Front	5mm	26865	831.5	21.79	23.00	1.321	-0.1	0.381	0.503
24	LTE Band 26	15M	QPSK	1	0	Back	5mm	26865	831.5	22.74	24.00	1.337	-0.09	0.883	1.180
	LTE Band 26	15M	QPSK	36	0	Back	5mm	26865	831.5	21.79	23.00	1.321	-0.06	0.711	0.939
	LTE Band 26	15M	QPSK	75	0	Back	5mm	26865	831.5	21.72	23.00	1.343	-0.05	0.717	0.963
	LTE Band 26	15M	QPSK	1	0	Left Side	5mm	26865	831.5	22.74	24.00	1.337	-0.08	0.518	0.692
	LTE Band 26	15M	QPSK	36	0	Left Side	5mm	26865	831.5	21.79	23.00	1.321	-0.11	0.278	0.367
	LTE Band 26	15M	QPSK	1	0	Right Side	5mm	26865	831.5	22.74	24.00	1.337	-0.1	0.192	0.257
	LTE Band 26	15M	QPSK	36	0	Right Side	5mm	26865	831.5	21.79	23.00	1.321	-0.1	0.097	0.128
	LTE Band 26	15M	QPSK	1	0	Bottom Side	5mm	26865	831.5	22.74	24.00	1.337	0	0.564	0.754
	LTE Band 26	15M	QPSK	36	0	Bottom Side	5mm	26865	831.5	21.79	23.00	1.321	-0.01	0.450	0.595

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	5mm	40400	2571	22.58	23.50	1.236	62.90	1.006	0	0.612	0.761
	LTE Band 41	20M	QPSK	50	0	Front	5mm	40400	2571	22.49	22.50	1.002	62.90	1.006	-0.06	0.582	0.587
	LTE Band 41	20M	QPSK	1	0	Back	5mm	40400	2571	22.58	23.50	1.236	62.90	1.006	0.01	0.834	1.037
	LTE Band 41	20M	QPSK	1	0	Back	5mm	40140	2545	22.45	23.50	1.274	62.90	1.006	0.05	0.831	1.065
25	LTE Band 41	20M	QPSK	1	0	Back	5mm	40670	2598	22.56	23.50	1.242	62.90	1.006	0.01	0.857	1.070
	LTE Band 41	20M	QPSK	1	0	Back	5mm	41140	2645	22.33	23.50	1.309	62.90	1.006	0.05	0.778	1.025
	LTE Band 41	20M	QPSK	50	0	Back	5mm	40400	2571	22.49	22.50	1.002	62.90	1.006	-0.04	0.838	0.845
	LTE Band 41	20M	QPSK	50	0	Back	5mm	40140	2545	22.35	22.50	1.035	62.90	1.006	0.02	0.798	0.831
	LTE Band 41	20M	QPSK	50	0	Back	5mm	40670	2598	22.35	22.50	1.035	62.90	1.006	0.04	0.837	0.872
	LTE Band 41	20M	QPSK	50	0	Back	5mm	41140	2645	21.91	22.50	1.146	62.90	1.006	0.09	0.905	1.043
	LTE Band 41	20M	QPSK	100	0	Back	5mm	40400	2571	22.44	22.50	1.014	62.90	1.006	0.04	0.793	0.809
	LTE Band 41	20M	QPSK	1	0	Left Side	5mm	40140	2545	22.58	23.50	1.236	62.90	1.006	-0.09	0.129	0.160
	LTE Band 41	20M	QPSK	50	0	Left Side	5mm	40140	2545	22.49	22.50	1.002	62.90	1.006	-0.05	0.126	0.127
	LTE Band 41	20M	QPSK	1	0	Right Side	5mm	40140	2545	22.58	23.50	1.236	62.90	1.006	-0.04	0.632	0.786
	LTE Band 41	20M	QPSK	50	0	Right Side	5mm	40140	2545	22.49	22.50	1.002	62.90	1.006	-0.09	0.578	0.583
	LTE Band 41	20M	QPSK	1	0	Bottom Side	5mm	40140	2545	22.58	23.50	1.236	62.90	1.006	-0.19	0.489	0.608
	LTE Band 41	20M	QPSK	50	0	Bottom Side	5mm	40140	2545	22.49	22.50	1.002	62.90	1.006	-0.01	0.458	0.462

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	6	2437	19.93	20.00	1.016	99.07	1.009	0.05	0.541	0.555
26	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	6	2437	19.93	20.00	1.016	99.07	1.009	0.02	1.100	1.128
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	1	2412	18.63	19.00	1.089	99.07	1.009	0.07	0.862	0.947
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	11	2462	18.38	18.50	1.028	99.07	1.009	0.02	0.706	0.732
	WLAN2.4GHz	802.11b 1Mbps	Left Side	5mm	6	2437	19.93	20.00	1.016	99.07	1.009	0.01	0.182	0.187
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	6	2437	19.93	20.00	1.016	99.07	1.009	0	0.837	0.858
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	1	2412	18.63	19.00	1.089	99.07	1.009	0.04	0.711	0.781
	WLAN2.4GHz	802.11b 1Mbps	Top Side	5mm	11	2462	18.38	18.50	1.028	99.07	1.009	0.12	0.675	0.700
	WLAN5GHz	802.11n-HT40 MCS0	Front	5mm	46	5230	16.94	17.00	1.014	89.32	1.120	-0.15	0.340	0.386
	WLAN5GHz	802.11n-HT40 MCS0	Back	5mm	46	5230	16.94	17.00	1.014	89.32	1.120	-0.03	0.974	1.106
27	WLAN5GHz	802.11a 6Mbps	Back	5mm	44	5220	16.92	17.00	1.019	95.28	1.050	-0.1	1.035	1.107
	WLAN5GHz	802.11n-HT40 MCS0	Left Side	5mm	46	5230	16.94	17.00	1.014	89.32	1.120	-0.07	0.213	0.242
	WLAN5GHz	802.11n-HT40 MCS0	Top Side	5mm	46	5230	16.94	17.00	1.014	89.32	1.120	-0.01	0.700	0.795
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	0.04	0.434	0.517
28	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	-0.05	0.939	1.119
	WLAN5GHz	802.11n-HT40 MCS0	Back	5mm	151	5755	14.92	15.50	1.143	89.32	1.120	-0.04	0.824	1.055
	WLAN5GHz	802.11ac-VHT80 MCS0	Left Side	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	0.03	0.163	0.194
	WLAN5GHz	802.11ac-VHT80 MCS0	Top Side	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	-0.07	0.511	0.609

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	5mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.13	0.069	0.095
29	Bluetooth	1Mbps	Back	5mm	0	2402	11.99	13.00	1.262	76.60	1.087	-0.05	0.118	0.162
	Bluetooth	1Mbps	Left Side	5mm	0	2402	11.99	13.00	1.262	76.60	1.087	-0.12	0.019	0.026
	Bluetooth	1Mbps	Top Side	5mm	0	2402	11.99	13.00	1.262	76.60	1.087	0.08	0.104	0.143

13.3 Body Worn Accessory SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	GSM850	GPRS (2 Tx slots)	Front	5mm	-	251	848.8	29.40	30.00	1.148	0.11	0.549	0.630
30	GSM850	GPRS (2 Tx slots)	Back	5mm	-	251	848.8	29.40	30.00	1.148	0.02	1.240	1.424
	GSM850	GPRS (2 Tx slots)	Back	5mm	-	128	824.2	28.50	30.00	1.413	-0.06	0.902	1.274
	GSM850	GPRS (2 Tx slots)	Back	5mm	-	189	836.4	28.92	30.00	1.282	0.06	1.110	1.423
	GSM850	GPRS (2 Tx slots)	Back	5mm	Headset	251	848.8	29.40	30.00	1.148	0.02	1.140	1.309
	GSM1900	GPRS (1 Tx slot)	Front	5mm	-	512	1850.2	26.44	26.50	1.014	0.15	0.913	0.926
	GSM1900	GPRS (1 Tx slot)	Front	5mm	-	661	1880	26.38	26.50	1.028	-0.03	0.866	0.890
	GSM1900	GPRS (1 Tx slot)	Front	5mm	-	810	1909.8	26.27	26.50	1.054	0.03	0.843	0.889
31	GSM1900	GPRS (1 Tx slot)	Back	5mm	-	512	1850.2	26.44	26.50	1.014	-0.08	1.360	1.379
	GSM1900	GPRS (1 Tx slot)	Back	5mm	-	661	1880	26.38	26.50	1.028	-0.03	1.300	1.336
	GSM1900	GPRS (1 Tx slot)	Back	5mm	-	810	1909.8	26.27	26.50	1.054	-0.15	1.130	1.191
	GSM1900	GPRS (1 Tx slot)	Back	5mm	Headset	512	1850.2	26.44	26.50	1.014	-0.15	1.060	1.075

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	9538	1907.6	16.37	17.50	1.297	0.06	0.708	0.918
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	9262	1852.4	16.11	17.50	1.377	0.04	0.593	0.817
	WCDMA II	RMC 12.2Kbps	Front	5mm	-	9400	1880	16.25	17.50	1.334	0.07	0.702	0.936
32	WCDMA II	RMC 12.2Kbps	Back	5mm	-	9538	1907.6	16.37	17.50	1.297	-0.04	1.080	1.401
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	9262	1852.4	16.11	17.50	1.377	-0.04	1.010	1.391
	WCDMA II	RMC 12.2Kbps	Back	5mm	-	9400	1880	16.25	17.50	1.334	-0.04	1.050	1.400
	WCDMA II	RMC 12.2Kbps	Back	5mm	Headset	9538	1907.6	16.37	17.50	1.297	-0.03	0.884	1.147
	WCDMA IV	RMC 12.2Kbps	Front	5mm	-	1513	1752.6	16.85	18.00	1.303	-0.02	0.600	0.782
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	1513	1752.6	16.85	18.00	1.303	-0.02	0.919	1.198
33	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	1312	1712.4	16.56	18.00	1.393	0.06	0.922	1.284
	WCDMA IV	RMC 12.2Kbps	Back	5mm	-	1413	1732.6	16.66	18.00	1.361	-0.05	0.886	1.206
	WCDMA IV	RMC 12.2Kbps	Back	5mm	Headset	1312	1712.4	16.56	18.00	1.393	-0.05	0.868	1.209
	WCDMA V	RMC 12.2Kbps	Front	5mm	-	4182	836.4	23.22	24.50	1.343	-0.08	0.650	0.873
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	4182	836.4	23.22	24.50	1.343	-0.07	1.010	1.356
	WCDMA V	RMC 12.2Kbps	Back	5mm	-	4132	826.4	23.22	24.50	1.343	-0.1	0.975	1.309
34	WCDMA V	RMC 12.2Kbps	Back	5mm	-	4233	846.6	23.04	24.50	1.400	-0.11	1.010	1.414
	WCDMA V	RMC 12.2Kbps	Back	5mm	Headset	4233	846.6	23.04	24.50	1.400	0.02	0.987	1.381

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 2	20M	QPSK	1	0	Front	5mm	-	18900	1880	16.47	17.50	1.268	0.04	0.655	0.830
	LTE Band 2	20M	QPSK	1	0	Front	5mm	-	18700	1860	16.26	17.50	1.330	0.03	0.581	0.773
	LTE Band 2	20M	QPSK	1	0	Front	5mm	-	19100	1900	16.46	17.50	1.271	0.02	0.712	0.905
	LTE Band 2	20M	QPSK	50	0	Front	5mm	-	19100	1900	16.32	17.50	1.312	0	0.737	0.967
	LTE Band 2	20M	QPSK	50	50	Front	5mm	-	18700	1860	16.13	17.50	1.371	0.1	0.649	0.890
	LTE Band 2	20M	QPSK	50	24	Front	5mm	-	18900	1880	16.31	17.50	1.315	0.12	0.682	0.897
	LTE Band 2	20M	QPSK	100	0	Front	5mm	-	19100	1900	16.27	17.50	1.327	0.01	0.717	0.952
	LTE Band 2	20M	QPSK	1	0	Back	5mm	-	18900	1880	16.47	17.50	1.268	-0.04	0.917	1.162
	LTE Band 2	20M	QPSK	1	0	Back	5mm	-	18700	1860	16.26	17.50	1.330	-0.07	0.905	1.204
	LTE Band 2	20M	QPSK	1	0	Back	5mm	-	19100	1900	16.46	17.50	1.271	-0.1	1.010	1.283
	LTE Band 2	20M	QPSK	50	0	Back	5mm	-	19100	1900	16.32	17.50	1.312	-0.12	1.030	1.352
	LTE Band 2	20M	QPSK	50	50	Back	5mm	-	18700	1860	16.13	17.50	1.371	-0.09	0.897	1.230
	LTE Band 2	20M	QPSK	50	24	Back	5mm	-	18900	1880	16.31	17.50	1.315	-0.07	0.991	1.303
35	LTE Band 2	20M	QPSK	100	0	Back	5mm	-	19100	1900	16.27	17.50	1.327	-0.11	1.050	1.394
	LTE Band 2	20M	QPSK	100	0	Back	5mm	Headset	19100	1900	16.27	17.50	1.327	-0.09	0.936	1.242
	LTE Band 4	20M	QPSK	1	0	Front	5mm	-	20175	1732.5	16.21	17.00	1.199	-0.04	0.505	0.606
	LTE Band 4	20M	QPSK	50	0	Front	5mm	-	20175	1732.5	15.83	17.00	1.309	0.03	0.518	0.678
	LTE Band 4	20M	QPSK	1	0	Back	5mm	-	20175	1732.5	16.21	17.00	1.199	-0.05	0.935	1.122
	LTE Band 4	20M	QPSK	50	0	Back	5mm	-	20175	1732.5	15.83	17.00	1.309	-0.01	0.921	1.206
36	LTE Band 4	20M	QPSK	100	0	Back	5mm	-	20175	1732.5	15.77	17.00	1.327	-0.06	0.980	1.301
	LTE Band 4	20M	QPSK	100	0	Back	5mm	Headset	20175	1732.5	15.77	17.00	1.327	0.08	0.962	1.277
	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	20850	2510	19.68	20.50	1.208	-0.04	0.858	1.036
	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	21100	2535	19.41	20.50	1.285	-0.05	0.805	1.035
	LTE Band 7	20M	QPSK	1	49	Front	5mm	-	21350	2560	19.56	20.50	1.242	0.01	0.798	0.991
	LTE Band 7	20M	QPSK	50	0	Front	5mm	-	20850	2510	19.79	20.50	1.178	-0.01	0.796	0.937
	LTE Band 7	20M	QPSK	50	0	Front	5mm	-	21100	2535	19.51	20.50	1.256	0	0.743	0.933
	LTE Band 7	20M	QPSK	50	0	Front	5mm	-	21350	2560	19.63	20.50	1.222	-0.05	0.768	0.938
	LTE Band 7	20M	QPSK	100	0	Front	5mm	-	20850	2510	19.70	20.50	1.202	-0.06	0.762	0.916
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	20850	2510	19.68	20.50	1.208	0.07	0.818	0.988
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	21100	2535	19.41	20.50	1.285	0.09	0.782	1.005
	LTE Band 7	20M	QPSK	1	49	Back	5mm	-	21350	2560	19.56	20.50	1.242	0.03	0.828	1.028
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	20850	2510	19.79	20.50	1.178	0.1	0.906	1.067
	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	21100	2535	19.51	20.50	1.256	0.06	0.794	0.997
37	LTE Band 7	20M	QPSK	50	0	Back	5mm	-	21350	2560	19.63	20.50	1.222	0.08	0.988	1.207
	LTE Band 7	20M	QPSK	100	0	Back	5mm	-	20850	2510	19.70	20.50	1.202	0.02	0.810	0.974
	LTE Band 7	20M	QPSK	50	0	Back	5mm	Headset	21350	2560	19.63	20.50	1.222	0.08	0.972	1.188
	LTE Band 26	15M	QPSK	1	0	Front	5mm	-	26865	831.5	22.74	24.00	1.337	-0.11	0.463	0.619
	LTE Band 26	15M	QPSK	36	0	Front	5mm	-	26865	831.5	21.79	23.00	1.321	-0.1	0.381	0.503
38	LTE Band 26	15M	QPSK	1	0	Back	5mm	-	26865	831.5	22.74	24.00	1.337	-0.09	0.883	1.180
	LTE Band 26	15M	QPSK	36	0	Back	5mm	-	26865	831.5	21.79	23.00	1.321	-0.06	0.711	0.939
	LTE Band 26	15M	QPSK	75	0	Back	5mm	-	26865	831.5	21.72	23.00	1.343	-0.05	0.717	0.963

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	LTE Band 41	20M	QPSK	1	0	Front	5mm	-	40400	2571	22.58	23.50	1.236	62.90	1.006	0	0.612	0.761
	LTE Band 41	20M	QPSK	50	0	Front	5mm	-	40400	2571	22.49	22.50	1.002	62.90	1.006	-0.06	0.582	0.587
	LTE Band 41	20M	QPSK	1	0	Back	5mm	-	40400	2571	22.58	23.50	1.236	62.90	1.006	0.01	0.834	1.037
	LTE Band 41	20M	QPSK	1	0	Back	5mm	-	40140	2545	22.45	23.50	1.274	62.90	1.006	0.05	0.831	1.065
39	LTE Band 41	20M	QPSK	1	0	Back	5mm	-	40670	2598	22.56	23.50	1.242	62.90	1.006	0.01	0.857	1.070
	LTE Band 41	20M	QPSK	1	0	Back	5mm	-	41140	2645	22.33	23.50	1.309	62.90	1.006	0.05	0.778	1.025
	LTE Band 41	20M	QPSK	50	0	Back	5mm	-	40400	2571	22.49	22.50	1.002	62.90	1.006	-0.04	0.838	0.845
	LTE Band 41	20M	QPSK	50	0	Back	5mm	-	40140	2545	22.35	22.50	1.035	62.90	1.006	0.02	0.798	0.831
	LTE Band 41	20M	QPSK	50	0	Back	5mm	-	40670	2598	22.35	22.50	1.035	62.90	1.006	0.04	0.837	0.872
	LTE Band 41	20M	QPSK	50	0	Back	5mm	-	41140	2645	21.91	22.50	1.146	62.90	1.006	0.09	0.905	1.043
	LTE Band 41	20M	QPSK	100	0	Back	5mm	-	40400	2571	22.44	22.50	1.014	62.90	1.006	0.04	0.793	0.809

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Headset	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	WLAN2.4GHz	802.11b 1Mbps	Front	5mm	-	6	2437	19.93	20.00	1.016	99.07	1.009	0.05	0.541	0.555
40	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	6	2437	19.93	20.00	1.016	99.07	1.009	0.02	1.100	1.128
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	1	2412	18.63	19.00	1.089	99.07	1.009	0.07	0.862	0.947
	WLAN2.4GHz	802.11b 1Mbps	Back	5mm	-	11	2462	18.38	18.50	1.028	99.07	1.009	0.02	0.706	0.732
	WLAN5GHz	802.11n-HT40 MCS0	Front	5mm	-	46	5230	16.94	17.00	1.014	89.32	1.122	-0.15	0.339	0.386
41	WLAN5GHz	802.11n-HT40 MCS0	Back	5mm	-	46	5230	16.94	17.00	1.014	89.32	1.122	-0.03	0.980	1.115
	WLAN5GHz	802.11a 6Mbps	Back	5mm	-	44	5220	16.92	17.00	1.007	95.28	1.120	-0.1	0.972	1.096
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	5mm	-	138	5690	14.45	14.50	1.012	89.16	1.122	-0.06	0.403	0.457
42	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	138	5690	14.45	14.50	1.012	89.16	1.122	-0.08	0.984	1.117
	WLAN5GHz	802.11n-HT40 MCS0	Back	5mm	-	102	5510	14.35	14.50	1.035	89.32	1.120	-0.08	0.842	0.976
	WLAN5GHz	802.11ac-VHT80 MCS0	Front	5mm	-	155	5775	16.24	16.50	1.062	89.16	1.122	0.04	0.434	0.517
43	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	-	155	5775	16.24	16.50	1.062	89.16	1.122	-0.05	0.939	1.119
	WLAN5GHz	802.11n-HT40 MCS0	Back	5mm	-	151	5755	14.92	15.50	1.143	89.32	1.120	-0.04	0.824	1.055

<Bluetooth SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Headset	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Reported 1g SAR (W/kg)
	Bluetooth	1Mbps	Front	5mm	0	-	2402	11.99	13.00	1.262	76.60	1.087	0.13	0.069	0.095
44	Bluetooth	1Mbps	Back	5mm	0	-	2402	11.99	13.00	1.262	76.60	1.087	-0.05	0.118	0.162

13.4 Product Specific SAR

<GSM SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
45	GSM850	GPRS (2 Tx slots)	Back	0mm	128	824.2	28.50	30.00	1.413	-0.11	2.350	3.319
	GSM850	GPRS (2 Tx slots)	Back	0mm	189	836.4	28.92	30.00	1.282	0.15	1.960	2.513
	GSM850	GPRS (2 Tx slots)	Back	0mm	251	848.8	29.40	30.00	1.148	0.05	2.620	3.008
	GSM1900	GPRS (1 Tx slot)	Front	0mm	512	1850.2	30.35	30.50	1.035	0.15	2.790	2.888
	GSM1900	GPRS (1 Tx slot)	Front	0mm	661	1880	30.30	30.50	1.047	0.04	2.610	2.733
	GSM1900	GPRS (1 Tx slot)	Front	0mm	810	1909.8	30.17	30.50	1.079	0.08	2.620	2.827
	GSM1900	GPRS (1 Tx slot)	Back	0mm	512	1850.2	30.35	30.50	1.035	-0.03	2.950	3.054
46	GSM1900	GPRS (1 Tx slot)	Back	0mm	661	1880	30.30	30.50	1.047	-0.18	2.980	3.120
	GSM1900	GPRS (1 Tx slot)	Back	0mm	810	1909.8	30.17	30.50	1.079	-0.04	2.610	2.816
	GSM1900	GPRS (1 Tx slot)	Bottom Side	0mm	512	1850.2	30.35	30.50	1.035	-0.17	2.520	2.609
	GSM1900	GPRS (1 Tx slot)	Bottom Side	0mm	661	1880	30.30	30.50	1.047	-0.12	2.670	2.796
	GSM1900	GPRS (1 Tx slot)	Bottom Side	0mm	810	1909.8	30.17	30.50	1.079	-0.16	2.310	2.492

<WCDMA SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	WCDMA II	RMC 12.2Kbps	Front	0mm	9400	1880	20.25	20.50	1.059	0.02	2.430	2.574
	WCDMA II	RMC 12.2Kbps	Front	0mm	9262	1852.4	20.12	20.50	1.091	0.07	2.310	2.521
	WCDMA II	RMC 12.2Kbps	Front	0mm	9538	1907.6	20.37	20.50	1.030	-0.06	2.510	2.586
	WCDMA II	RMC 12.2Kbps	Back	0mm	9400	1880	20.25	20.50	1.059	-0.03	2.890	3.061
47	WCDMA II	RMC 12.2Kbps	Back	0mm	9262	1852.4	20.12	20.50	1.091	-0.07	2.810	3.067
	WCDMA II	RMC 12.2Kbps	Back	0mm	9538	1907.6	20.37	20.50	1.030	-0.03	2.830	2.916
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	9400	1880	20.25	20.50	1.059	-0.02	2.690	2.849
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	9262	1852.4	20.12	20.50	1.091	0.01	2.740	2.991
	WCDMA II	RMC 12.2Kbps	Bottom Side	0mm	9538	1907.6	20.37	20.50	1.030	0.08	2.610	2.689
	WCDMA IV	RMC 12.2Kbps	Front	0mm	1513	1752.6	19.33	21.00	1.469	0.09	1.500	2.203
	WCDMA IV	RMC 12.2Kbps	Front	0mm	1312	1712.4	19.07	21.00	1.560	0.01	1.570	2.448
	WCDMA IV	RMC 12.2Kbps	Front	0mm	1413	1732.6	19.19	21.00	1.517	0.15	2.000	3.034
	WCDMA IV	RMC 12.2Kbps	Back	0mm	1513	1752.6	19.33	21.00	1.469	-0.11	2.150	3.158
	WCDMA IV	RMC 12.2Kbps	Back	0mm	1312	1712.4	19.07	21.00	1.560	-0.12	2.050	3.197
	WCDMA IV	RMC 12.2Kbps	Back	0mm	1413	1732.6	19.19	21.00	1.517	-0.06	2.090	3.171
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	1513	1752.6	19.33	21.00	1.469	0.01	2.330	3.423
48	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	1312	1712.4	19.07	21.00	1.560	0.04	2.220	3.462
	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	1413	1732.6	19.19	21.00	1.517	0.02	2.230	3.383
49	WCDMA V	RMC 12.2Kbps	Back	0mm	4132	826.4	23.85	25.00	1.303	0.06	1.650	2.150
	WCDMA V	RMC 12.2Kbps	Back	0mm	4182	836.4	23.94	25.00	1.276	0.02	1.660	2.119
	WCDMA V	RMC 12.2Kbps	Back	0mm	4233	846.6	23.89	25.00	1.291	0.03	1.620	2.092

<FDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
	LTE Band 2	20M	QPSK	50	0	Front	0mm	19100	1900	20.08	21.50	1.387	0.1	2.020	2.801
	LTE Band 2	20M	QPSK	50	0	Front	0mm	18700	1860	19.89	21.50	1.449	0.09	1.930	2.796
	LTE Band 2	20M	QPSK	50	0	Front	0mm	18900	1880	20.07	21.50	1.390	0.03	2.050	2.849
	LTE Band 2	20M	QPSK	100	0	Back	0mm	19100	1900	20.06	21.50	1.393	-0.01	2.370	3.302
50	LTE Band 2	20M	QPSK	100	0	Back	0mm	18700	1860	19.83	21.50	1.469	-0.02	2.290	3.364
	LTE Band 2	20M	QPSK	100	0	Back	0mm	18900	1880	20.01	21.50	1.409	-0.07	2.310	3.255
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	19100	1900	20.08	21.50	1.387	-0.13	2.130	2.954
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	18700	1860	19.89	21.50	1.449	-0.16	2.280	3.303
	LTE Band 2	20M	QPSK	50	0	Bottom Side	0mm	18900	1880	20.07	21.50	1.390	-0.18	2.310	3.211
	LTE Band 4	20M	QPSK	50	0	Front	0mm	20175	1732.5	19.45	20.00	1.135	0.09	1.410	1.600
	LTE Band 4	20M	QPSK	100	0	Back	0mm	20175	1732.5	19.44	20.00	1.138	-0.03	2.020	2.298
51	LTE Band 4	20M	QPSK	50	0	Bottom Side	0mm	20175	1732.5	19.45	20.00	1.135	-0.09	2.250	2.554
	LTE Band 7	20M	QPSK	1	49	Front	0mm	21350	2560	21.16	23.00	1.528	0.02	1.925	2.941
	LTE Band 7	20M	QPSK	1	49	Front	0mm	20850	2510	21.28	23.00	1.486	0.06	1.841	2.736
	LTE Band 7	20M	QPSK	1	49	Front	0mm	21100	2535	21.05	23.00	1.567	-0.05	1.829	2.866
52	LTE Band 7	20M	QPSK	50	0	Back	0mm	21350	2560	21.22	23.00	1.507	-0.01	2.060	3.104
	LTE Band 7	20M	QPSK	50	0	Back	0mm	20850	2510	21.39	23.00	1.449	0.08	1.953	2.829
	LTE Band 7	20M	QPSK	50	0	Back	0mm	21100	2535	21.09	23.00	1.552	-0.13	1.875	2.911

<TDD LTE SAR>

Plot No.	Band	BW (MHz)	Modulation	RB Size	RB offset	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
53	LTE Band 41	20M	QPSK	1	0	Back	0mm	40670	2598	23.18	24.00	1.208	62.90	1.006	0.07	1.580	1.920

<WLAN SAR>

Plot No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Reported 10g SAR (W/kg)
54	WLAN5GHz	802.11a 6Mbps	Back	0mm	44	5220	17.18	18.00	1.208	95.28	1.050	0.04	0.749	0.950
	WLAN5GHz	802.11n-HT40 MCS0	Front	0mm	54	5270	17.14	18.00	1.219	89.32	1.120	0	0.464	0.633
55	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	54	5270	17.14	18.00	1.219	89.32	1.120	-0.03	0.918	1.253
	WLAN5GHz	802.11n-HT40 MCS0	Left Side	0mm	54	5270	17.14	18.00	1.219	89.32	1.120	0	0.359	0.490
	WLAN5GHz	802.11n-HT40 MCS0	Top Side	0mm	54	5270	17.14	18.00	1.219	89.32	1.120	-0.05	0.330	0.450
	WLAN5GHz	802.11n-HT40 MCS0	Front	0mm	110	5550	17.70	18.00	1.071	89.32	1.120	-0.08	0.698	0.838
56	WLAN5GHz	802.11n-HT40 MCS0	Back	0mm	110	5550	17.70	18.00	1.071	89.32	1.120	-0.05	1.180	1.416
	WLAN5GHz	802.11n-HT40 MCS0	Left Side	0mm	110	5550	17.70	18.00	1.071	89.32	1.120	0.01	0.315	0.378
	WLAN5GHz	802.11n-HT40 MCS0	Top Side	0mm	110	5550	17.70	18.00	1.071	89.32	1.120	-0.01	0.438	0.526
57	WLAN5GHz	802.11ac-VHT80 MCS0	Back	0mm	155	5775	16.60	17.00	1.097	89.16	1.122	0.09	0.592	0.729

13.5 Repeated SAR Measurement

No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Duty Cycle %	Duty Cycle Scaling Factor	Power Drift (dB)	Measured 1g SAR (W/kg)	Ratio	Reported 1g SAR (W/kg)
1st	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	0.06	1.150	-	1.179
2nd	WLAN2.4GHz	802.11b 1Mbps	Right Tilted	0mm	6	2437	19.93	20.00	1.016	99.07	1.009	-0.07	1.080	1.07	1.107
1st	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.06	0.978	-	1.129
2nd	WLAN5GHz	802.11n-HT40 MCS0	Right Tilted	0mm	54	5270	15.37	15.50	1.030	89.32	1.120	0.01	0.952	1.03	1.099
1st	GSM850	GPRS (2 Tx slots)	Back	5mm	251	848.8	29.40	30.00	1.148	-	1.000	0.02	1.240	-	1.424
2nd	GSM850	GPRS (2 Tx slots)	Back	5mm	251	848.8	29.40	30.00	1.148	-	1.000	0.02	1.140	1.09	1.309
1st	GSM1900	GPRS (1 Tx slot)	Back	5mm	512	1850.2	26.44	26.50	1.014	-	1.000	-0.08	1.360	-	1.379
2nd	GSM1900	GPRS (1 Tx slot)	Back	5mm	512	1850.2	26.44	26.50	1.014	-	1.000	-0.03	1.040	1.31	1.054
1st	LTE Band 4	20M_QPSK_100_0	Back	5mm	20175	1732.5	15.77	17.00	1.327	-	1.000	-0.06	0.980	-	1.301
2nd	LTE Band 4	20M_QPSK_100_0	Back	5mm	20175	1732.5	15.77	17.00	1.327	-	1.000	0.05	0.942	1.04	1.250
1st	LTE Band 7	20M_QPSK_50_0	Back	5mm	21350	2560	19.63	20.50	1.222	-	1.000	0.08	0.988	-	1.207
2nd	LTE Band 7	20M_QPSK_50_0	Back	5mm	21350	2560	19.63	20.50	1.222	-	1.000	0.07	0.958	1.03	1.170
1st	WLAN5GHz	802.11a 6Mbps	Back	5mm	44	5220	16.92	17.00	1.019	95.28	1.050	-0.1	1.035	-	1.107
2nd	WLAN5GHz	802.11a 6Mbps	Back	5mm	44	5220	16.80	17.00	1.047	95.28	1.050	0.02	0.985	1.02	1.083
1st	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	-0.05	0.939	-	1.119
2nd	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	155	5775	16.24	16.50	1.062	89.16	1.122	-0.05	0.928	1.01	1.106
1st	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	138	5690	14.45	14.50	1.012	89.16	1.122	-0.08	0.984	-	1.117
2nd	WLAN5GHz	802.11ac-VHT80 MCS0	Back	5mm	138	5690	14.45	14.50	1.012	89.16	1.122	-0.18	0.967	1.02	1.098

No.	Band	Mode	Test Position	Gap (mm)	Ch.	Freq. (MHz)	Average Power (dBm)	Tune-Up Limit (dBm)	Tune-up Scaling Factor	Power Drift (dB)	Measured 10g SAR (W/kg)	Ratio	Reported 10g SAR (W/kg)
1st	GSM850	GPRS (2 Tx slots)	Back	0mm	251	848.8	29.40	30.00	1.148	0.05	2.620	-	3.008
2nd	GSM850	GPRS (2 Tx slots)	Back	0mm	251	848.8	29.40	30.00	1.148	0.03	2.540	1.03	2.916
1st	GSM1900	GPRS (1 Tx slot)	Back	0mm	661	1880	30.30	30.50	1.047	-0.18	2.980	-	3.120
2nd	GSM1900	GPRS (1 Tx slot)	Back	0mm	661	1880	30.30	30.50	1.047	0.03	2.890	1.03	3.026
1st	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	1513	1752.6	19.33	21.00	1.469	0.01	2.330	-	3.423
2nd	WCDMA IV	RMC 12.2Kbps	Bottom Side	0mm	1513	1752.6	19.33	21.00	1.469	0.02	2.260	1.03	3.320
1st	LTE Band 7	20M_QPSK_50_0	Back	0mm	21350	2560	21.22	23.00	1.507	-0.01	2.060	-	3.104
2nd	LTE Band 7	20M_QPSK_50_0	Back	0mm	21350	2560	21.22	23.00	1.507	0.02	2.010	1.03	3.028

General Note:

1. Per KDB 865664 D01v01r04, for each frequency band, repeated SAR measurement is required only when the measured SAR is ≥ 0.8 W/kg.
2. Per KDB 865664 D01v01r04, if the ratio among the repeated measurement is ≤ 1.2 and the measured SAR < 1.45 W/kg, only one repeated measurement is required.
3. Per KDB 865664 D01v01r04, if the extremity repeated SAR is necessary, the same procedures should be adapted for measurements according to extremity and occupational exposure limits by applying a factor of 2.5 for extremity exposure and a factor of 5 for occupational exposure to the corresponding SAR thresholds.
4. The ratio is the difference in percentage between original and repeated *measured SAR*.
5. All measurement SAR result is scaled-up to account for tune-up tolerance and is compliant.

14. Simultaneous Transmission Analysis

NO.	Simultaneous Transmission Configurations	Portable Handset			
		Head	Body-worn	Hotspot	Product Specific
1.	GSM Voice + WLAN2.4GHz	Yes	Yes		Yes
2.	GPRS/EDGE + WLAN2.4GHz	Yes	Yes	Yes	Yes
3.	WCDMA + WLAN2.4GHz	Yes	Yes	Yes	Yes
4.	LTE + WLAN2.4GHz	Yes	Yes	Yes	Yes
5.	GSM Voice + Bluetooth	Yes	Yes		Yes
6.	GPRS/EDGE + Bluetooth	Yes	Yes	Yes	Yes
7.	WCDMA+ Bluetooth	Yes	Yes	Yes	Yes
8.	LTE + Bluetooth	Yes	Yes	Yes	Yes
9.	GSM Voice + WLAN5GHz	Yes	Yes		Yes
10.	GPRS/EDGE + WLAN5GHz	Yes	Yes	Yes	Yes
11.	WCDMA + WLAN5GHz	Yes	Yes	Yes	Yes
12.	LTE + WLAN5GHz	Yes	Yes	Yes	Yes

General Note:

1. This device WLAN 2.4GHz/5.2GHz/5.8GHz supports Hotspot operation and Bluetooth support tethering applications.
2. WLAN and Bluetooth share the same antenna, and cannot transmit simultaneously.
3. EUT will choose either WLAN 2.4GHz or WLAN 5GHz according to the network signal condition; therefore, 2.4GHz WLAN and 5GHz WLAN will not operate simultaneously at any moment.
4. The Scaled SAR summation is calculated based on the same configuration and test position.
5. Per KDB 447498 D01v06, simultaneous transmission SAR is compliant if,
 - i) Scalar SAR summation < 1.6W/kg.
 - ii) $SPLSR = (SAR1 + SAR2)^{1.5} / (\text{min. separation distance, mm})$, and the peak separation distance is determined from the square root of $[(x1-x2)^2 + (y1-y2)^2 + (z1-z2)^2]$, where (x1, y1, z1) and (x2, y2, z2) are the coordinates of the extrapolated peak SAR locations in the zoom scan.
 - iii) If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary.
 - iv) Simultaneously transmission SAR measurement, and the reported multi-band SAR < 1.6W/kg.
 - v) The SPLSR calculated results please refer to section 14.5.

14.1 Head Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth			
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)			
GSM	GSM850	Right Cheek	0.348	1.148	1.151	0.171	1.496	1.499	0.519
		Right Tilted	0.245	1.179	1.129	0.163	1.424	1.374	0.408
		Left Cheek	0.403	0.779	0.734	0.118	1.182	1.137	0.521
		Left Tilted	0.198	0.750	0.777	0.113	0.948	0.975	0.311
	GSM1900	Right Cheek	0.065	1.148	1.151	0.171	1.213	1.216	0.236
		Right Tilted	0.033	1.179	1.129	0.163	1.212	1.162	0.196
		Left Cheek	0.062	0.779	0.734	0.118	0.841	0.796	0.180
		Left Tilted	0.030	0.750	0.777	0.113	0.780	0.807	0.143
WCDMA	WCDMA II	Right Cheek	0.111	1.148	1.151	0.171	1.259	1.262	0.282
		Right Tilted	0.061	1.179	1.129	0.163	1.240	1.190	0.224
		Left Cheek	0.099	0.779	0.734	0.118	0.878	0.833	0.217
		Left Tilted	0.032	0.750	0.777	0.113	0.782	0.809	0.145
	WCDMA IV	Right Cheek	0.096	1.148	1.151	0.171	1.244	1.247	0.267
		Right Tilted	0.047	1.179	1.129	0.163	1.226	1.176	0.210
		Left Cheek	0.122	0.779	0.734	0.118	0.901	0.856	0.240
		Left Tilted	0.026	0.750	0.777	0.113	0.776	0.803	0.139
	WCDMA V	Right Cheek	0.243	1.148	1.151	0.171	1.391	1.394	0.414
		Right Tilted	0.174	1.179	1.129	0.163	1.353	1.303	0.337
		Left Cheek	0.382	0.779	0.734	0.118	1.161	1.116	0.500
		Left Tilted	0.172	0.750	0.777	0.113	0.922	0.949	0.285
LTE	LTE Band 2	Right Cheek	0.121	1.148	1.151	0.171	1.269	1.272	0.292
		Right Tilted	0.047	1.179	1.129	0.163	1.226	1.176	0.210
		Left Cheek	0.106	0.779	0.734	0.118	0.885	0.840	0.224
		Left Tilted	0.043	0.750	0.777	0.113	0.793	0.820	0.156
	LTE Band 4	Right Cheek	0.126	1.148	1.151	0.171	1.274	1.277	0.297
		Right Tilted	0.044	1.179	1.129	0.163	1.223	1.173	0.207
		Left Cheek	0.125	0.779	0.734	0.118	0.904	0.859	0.243
		Left Tilted	0.038	0.750	0.777	0.113	0.788	0.815	0.151
	LTE Band 7	Right Cheek	0.314	1.148	1.151	0.171	1.462	1.465	0.485
		Right Tilted	0.125	1.179	1.129	0.163	1.304	1.254	0.288
		Left Cheek	0.201	0.779	0.734	0.118	0.980	0.935	0.319
		Left Tilted	0.205	0.750	0.777	0.113	0.955	0.982	0.318
	LTE Band 26	Right Cheek	0.266	1.148	1.151	0.171	1.414	1.417	0.437
		Right Tilted	0.099	1.179	1.129	0.163	1.278	1.228	0.262
		Left Cheek	0.339	0.779	0.734	0.118	1.118	1.073	0.457
		Left Tilted	0.199	0.750	0.777	0.113	0.949	0.976	0.312
	LTE Band 41	Right Cheek	0.194	1.148	1.151	0.171	1.342	1.345	0.365
		Right Tilted	0.072	1.179	1.129	0.163	1.251	1.201	0.235
		Left Cheek	0.110	0.779	0.734	0.118	0.889	0.844	0.228
		Left Tilted	0.127	0.750	0.777	0.113	0.877	0.904	0.240

14.2 Hotspot Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN 1g SAR (W/kg)	2.4GHz WLAN 1g SAR (W/kg)	5GHz WLAN 1g SAR (W/kg)	Bluetooth 1g SAR (W/kg)					
GSM	GSM850	Front	0.630	0.555	0.517	0.095	1.185	1.147	0.725		
		Back	1.424	1.128	1.119	0.162	2.552	2.543	1.586	0.03	Case 1
		Left side	0.687	0.187	0.242	0.026	0.874	0.929	0.713		
		Right side	0.324				0.324	0.324	0.324		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	0.866				0.866	0.866	0.866		
	GSM1900	Front	0.926	0.555	0.517	0.095	1.481	1.443	1.021		
		Back	1.379	1.128	1.119	0.162	2.507	2.498	1.541	0.03	Case 2
		Left side	0.036	0.187	0.242	0.026	0.223	0.278	0.062		
		Right side	0.029				0.029	0.029	0.029		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	1.306				1.306	1.306	1.306		
WCDMA	WCDMA II	Front	0.936	0.555	0.517	0.095	1.491	1.453	1.031		
		Back	1.401	1.128	1.119	0.162	2.529	2.520	1.563	0.03	Case 3
		Left side	0.067	0.187	0.242	0.026	0.254	0.309	0.093		
		Right side	0.037				0.037	0.037	0.037		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	1.366				1.366	1.366	1.366		
	WCDMA IV	Front	0.782	0.555	0.517	0.095	1.337	1.299	0.877		
		Back	1.284	1.128	1.119	0.162	2.412	2.403	1.446	0.02	Case 4
		Left side	0.059	0.187	0.242	0.026	0.246	0.301	0.085		
		Right side	0.034				0.034	0.034	0.034		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	1.127				1.127	1.127	1.127		
	WCDMA V	Front	0.873	0.555	0.517	0.095	1.428	1.390	0.968		
		Back	1.414	1.128	1.119	0.162	2.542	2.533	1.576	0.03	Case 5
		Left side	0.645	0.187	0.242	0.026	0.832	0.887	0.671		
		Right side	0.317				0.317	0.317	0.317		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	0.791				0.791	0.791	0.791		

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth					
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)					
LTE	LTE Band 2	Front	0.967	0.555	0.517	0.095	1.522	1.484	1.062		
		Back	1.394	1.128	1.119	0.162	2.522	2.513	1.556	0.03	Case 6
		Left side	0.051	0.187	0.242	0.026	0.238	0.293	0.077		
		Right side	0.038				0.038	0.038	0.038		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	1.407				1.407	1.407	1.407		
	LTE Band 4	Front	0.678	0.555	0.517	0.095	1.233	1.195	0.773		
		Back	1.301	1.128	1.119	0.162	2.429	2.420	1.463	0.02	Case 7
		Left side	0.041	0.187	0.242	0.026	0.228	0.283	0.067		
		Right side	0.031				0.031	0.031	0.031		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	1.196				1.196	1.196	1.196		
	LTE Band 7	Front	1.036	0.555	0.517	0.095	1.591	1.553	1.131		
		Back	1.207	1.128	1.119	0.162	2.335	2.326	1.369	0.02	Case 8
		Left side	0.095	0.187	0.242	0.026	0.282	0.337	0.121		
		Right side	0.519				0.519	0.519	0.519		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	0.617				0.617	0.617	0.617		
	LTE Band 26	Front	0.619	0.555	0.517	0.095	1.174	1.136	0.714		
		Back	1.180	1.128	1.119	0.162	2.308	2.299	1.342	0.02	Case 9
		Left side	0.692	0.187	0.242	0.026	0.879	0.934	0.718		
		Right side	0.257				0.257	0.257	0.257		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	0.754				0.754	0.754	0.754		
	LTE Band 41	Front	0.761	0.555	0.517	0.095	1.316	1.278	0.856		
		Back	1.070	1.128	1.119	0.162	2.198	2.189	1.232	0.02	Case 10
		Left side	0.160	0.187	0.242	0.026	0.347	0.402	0.186		
		Right side	0.786				0.786	0.786	0.786		
		Top side		0.858	0.795	0.143	0.858	0.795	0.143		
		Bottom side	0.608				0.608	0.608	0.608		

14.3 Body-Worn Accessory Exposure Conditions

WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 1g SAR (W/kg)	1+3 Summed 1g SAR (W/kg)	1+4 Summed 1g SAR (W/kg)	SPLSR	Case No
			WWAN	2.4GHz WLAN	5GHz WLAN	Bluetooth					
			1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)	1g SAR (W/kg)					
GSM	GSM850	Front	0.630	0.555	0.517	0.095	1.185	1.147	0.725		
		Back	1.424	1.128	1.119	0.162	2.552	2.543	1.586	0.03	Case 1
		Back with Headset	1.309	1.128	1.119	0.162	2.437	2.428	1.471	0.02	Case 11
	GSM1900	Front	0.926	0.555	0.517	0.095	1.481	1.443	1.021		
		Back	1.379	1.128	1.119	0.162	2.507	2.498	1.541	0.03	Case 2
		Back with Headset	1.075	1.128	1.119	0.162	2.203	2.194	1.237	0.02	Case 12
WCDMA	WCDMA II	Front	0.936	0.555	0.517	0.095	1.491	1.453	1.031		
		Back	1.401	1.128	1.119	0.162	2.529	2.520	1.563	0.03	Case 3
		Back with Headset	1.147	1.128	1.119	0.162	2.275	2.266	1.309	0.02	Case 13
	WCDMA IV	Front	0.782	0.555	0.517	0.095	1.337	1.299	0.877		
		Back	1.284	1.128	1.119	0.162	2.412	2.403	1.446	0.02	Case 4
		Back with Headset	1.209	1.128	1.119	0.162	2.337	2.328	1.371	0.02	Case 14
	WCDMA V	Front	0.873	0.555	0.517	0.095	1.428	1.390	0.968		
		Back	1.414	1.128	1.119	0.162	2.542	2.533	1.576	0.03	Case 5
		Back with Headset	1.381	1.128	1.119	0.162	2.509	2.500	1.543	0.03	Case 15
LTE	LTE Band 2	Front	0.967	0.555	0.517	0.095	1.522	1.484	1.062		
		Back	1.394	1.128	1.119	0.162	2.522	2.513	1.556	0.03	Case 6
		Back with Headset	1.242	1.128	1.119	0.162	2.370	2.361	1.404	0.02	Case 16
	LTE Band 4	Front	0.678	0.555	0.517	0.095	1.233	1.195	0.773		
		Back	1.301	1.128	1.119	0.162	2.429	2.420	1.463	0.02	Case 7
		Back with Headset	1.277	1.128	1.119	0.162	2.405	2.396	1.439	0.02	Case 17
	LTE Band 7	Front	1.036	0.555	0.517	0.095	1.591	1.553	1.131		
		Back	1.207	1.128	1.119	0.162	2.335	2.326	1.369	0.02	Case 8
		Back with Headset	1.188	1.128	1.119	0.162	2.316	2.307	1.350	0.02	Case 18
	LTE Band 26	Front	0.619	0.555	0.517	0.095	1.174	1.136	0.714		
		Back	1.180	1.128	1.119	0.162	2.308	2.299	1.342	0.02	Case 9
	LTE Band 41	Front	0.761	0.555	0.517	0.095	1.316	1.278	0.856		
		Back	1.070	1.128	1.119	0.162	2.198	2.189	1.232	0.02	Case 10

14.4 Product Specific Exposure Conditions

Remark:

- According to KDB 941225 D06 v02r01 and KDB 648474 D04v01r03, for WWAN / 2.4GHz WLAN / Bluetooth and 5GHz WLAN SAR ("–") was excluded, due to transmitting antenna located larger 25mm from that surface or edge and Hotspot SAR was < 1.2W/Kg.

WWAN Band		Exposure Position	1 WWAN 10g SAR (W/kg)	2 2.4GHz WLAN 10g SAR (W/kg)	3 5GHz WLAN 10g SAR (W/kg)	4 Bluetooth 10g SAR (W/kg)	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)	SPLSR	Case No
GSM	GSM850	Front			0.838		0.000	0.838	0.000		
		Back	3.319		1.416		3.319	4.735	3.319	0.07	Case 19
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side					0.000	0.000	0.000		
	GSM1900	Front	2.888		0.838		2.888	3.726	2.888		
		Back	3.120		1.416		3.120	4.536	3.120	0.07	Case 20
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side	2.796				2.796	2.796	2.796		
WCDMA	WCDMA II	Front	2.586		0.838		2.586	3.424	2.586		
		Back	3.067		1.416		3.067	4.483	3.067	0.06	Case 21
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side	2.991				2.991	2.991	2.991		
	WCDMA IV	Front	3.034		0.838		3.034	3.872	3.034		
		Back	3.197		1.416		3.197	4.613	3.197	0.07	Case 22
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side	3.462				3.462	3.462	3.462		
	WCDMA V	Front			0.838		0.000	0.838	0.000		
		Back	2.150		1.416		2.150	3.566	2.150		
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side					0.000	0.000	0.000		


WWAN Band		Exposure Position	1	2	3	4	1+2 Summed 10g SAR (W/kg)	1+3 Summed 10g SAR (W/kg)	1+4 Summed 10g SAR (W/kg)	SPLSR	Case No
			WWAN 10g SAR (W/kg)	2.4GHz WLAN 10g SAR (W/kg)	5GHz WLAN 10g SAR (W/kg)	Bluetooth 10g SAR (W/kg)					
LTE	LTE Band 2	Front	2.849		0.838		2.849	3.687	2.849		
		Back	3.364		1.416		3.364	4.780	3.364	0.07	Case 23
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side	3.303				3.303	3.303	3.303		
	LTE Band 4	Front	1.600		0.838		1.600	2.438	1.600		
		Back	2.298		1.416		2.298	3.714	2.298		
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side	2.554				2.554	2.554	2.554		
	LTE Band 7	Front	2.941		0.838		2.941	3.779	2.941		
		Back	3.104		1.416		3.104	4.520	3.104	0.07	Case 24
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side					0.000	0.000	0.000		
	LTE Band 41	Front			0.838		0.000	0.838	0.000		
		Back	1.920		1.416		1.920	3.336	1.920		
		Left side			0.490		0.000	0.490	0.000		
		Right side					0.000	0.000	0.000		
		Top side			0.526		0.000	0.526	0.000		
		Bottom side					0.000	0.000	0.000		

14.5 SPLSR Evaluation and Analysis

General Note:

1. $SPLSR = (SAR_1 + SAR_2)^{1.5} / (\text{min. separation distance, mm})$. If $SPLSR \leq 0.04$, simultaneously transmission SAR measurement is not necessary


Case 1	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM850	Back	1.424	5mm	-6.07	-80.08	-1.21	155.2	2.55	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	GSM850		1.424	5mm	-6.07	-80.08	-1.21	152.4	2.54	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 2	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM1900	Back	1.379	5mm	6	-83.8	-2.59	156.9	2.51	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	GSM1900		1.379	5mm	6	-83.8	-2.59	153.7	2.50	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 3	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Back	1.401	5mm	6.12	-83.91	-2.62	157.0	2.53	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA II		1.401	5mm	6.12	-83.91	-2.62	153.8	2.52	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				



Case 4	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	1.284	5mm	2.93	-83.81	-2.64	157.3	2.41	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA IV		1.284	5mm	2.93	-83.81	-2.64	154.2	2.40	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 5	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Back	1.414	5mm	-7.6	-78.5	-1.71	154.0	2.54	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA V		1.414	5mm	-7.6	-78.5	-1.71	151.2	2.53	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 6	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B2	Back	1.394	5mm	-9.23	-81.8	-2.53	157.6	2.52	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B2		1.394	5mm	-9.23	-81.8	-2.53	154.8	2.51	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 7	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B4	Back	1.301	5mm	4.44	-81.82	-2.6	155.1	2.43	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B4		1.301	5mm	4.44	-81.82	-2.6	152.0	2.42	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 8	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B7	Back	1.207	5mm	-27.56	-68.6	-2.41	150.2	2.34	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B7		1.207	5mm	-27.56	-68.6	-2.41	148.2	2.33	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 9	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B26	Back	1.18	5mm	-10.8	-76.9	-1.73	153.2	2.31	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B26		1.18	5mm	-10.8	-76.9	-1.73	150.5	2.30	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 10	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B41	Back	1.07	5mm	-27.17	-71.6	-2.45	152.9	2.20	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B41		1.07	5mm	-27.17	-71.6	-2.45	150.8	2.19	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 11	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM850	Back	1.309	5mm	-6.12	-80.02	-1.18	155.1	2.44	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	GSM850		1.309	5mm	-6.12	-80.02	-1.18	152.3	2.43	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				



Case 12	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM1900	Back	1.075	5mm	6.05	-83.4	-2.57	156.5	2.20	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	GSM1900		1.075	5mm	6.05	-83.4	-2.57	153.3	2.19	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				



Case 13	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA II	Back	1.147	5mm	6.15	-83.85	-2.61	156.9	2.28	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA II		1.147	5mm	6.15	-83.85	-2.61	153.7	2.27	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				



Case 14	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA IV	Back	1.209	5mm	2.85	-83.78	-2.59	157.3	2.34	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA IV		1.209	5mm	2.85	-83.78	-2.59	154.2	2.33	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 15	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA V	Back	1.381	5mm	-7.4	-78.3	-1.69	153.7	2.51	0.03	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	WCDMA V		1.381	5mm	-7.4	-78.3	-1.69	151.0	2.50	0.03	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 16	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B2	Back	1.242	5mm	-9.21	-81.5	-2.49	157.3	2.37	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B2		1.242	5mm	-9.21	-81.5	-2.49	154.5	2.36	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 17	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B4	Back	1.277	5mm	4.41	-81.8	-2.57	155.1	2.41	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B4		1.277	5mm	4.41	-81.8	-2.57	151.9	2.40	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 18	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B7	Back	1.188	5mm	-27.47	-68.58	-2.39	150.2	2.32	0.02	Not required
	WLAN2.4G		1.128	5mm	25.84	71.8	-0.74				
	LTE B7		1.188	5mm	-27.47	-68.58	-2.39	148.1	2.31	0.02	Not required
	WLAN5G		1.119	5mm	29.86	68	-1.99				




Case 19	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM850	Back	3.319	0mm	-12.4	-79.8	-1.07	148.2	4.74	0.07	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				




Case 20	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	GSM1900	Back	3.12	0mm	10.43	-79.72	-2.13	143.8	4.54	0.07	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				




Case 21	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA B2	Back	3.067	0mm	9.43	-84.1	-2.35	148.3	4.48	0.06	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				




Case 22	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	WCDMA B4	Back	3.197	0mm	3.07	-84.01	-2.45	149.1	4.61	0.07	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				



Case 23	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B2	Back	3.364	0mm	9.45	-80.62	-2.44	144.8	4.78	0.07	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				



Case 24	Band	Position	SAR (W/kg)	Gap (mm)	SAR peak location (mm)			3D distance (mm)	Summed SAR (W/kg)	SPLSR Results	Simultaneous SAR
					X	Y	Z				
	LTE B7	Back	3.104	0mm	-23.16	-75.19	-0.25	147.0	4.52	0.07	Not required
	WLAN5G		1.416	0mm	26.44	63.2	-1.16				



15. Supplemental tuner tests results

General Note:

1. The following test procedure was followed to demonstrate that the SAR results in this report represent the appropriate SAR test conditions. For bands with dynamic tuning implemented, SAR will be measured according to the required FCC SAR test procedures with the dynamic tuner active to allow the device to automatically tune to the antenna state for the respective RF exposure test configurations. Additional single point SAR time-sweep measurements will be evaluated for other tuner states to determine that the other tuner configurations would result in equivalent or lower SAR values. The additional tuner hardware has no influence to the antenna characteristics, other than impedance matching.
2. To evaluate all of the tuner states, the 144 tuner states are divided evenly among band, mode and exposure combinations so that at least one single point SAR measurement is measured in each configuration. Single point time-sweep measurements will be performed at the peak SAR location determined by the zoom scan of the configuration with the highest reported SAR for each combination. The tuner state will be established remotely so that the device is not moved for the entire series of single point SAR for the tuner states in each combination. The SAR probe will remain stationary at the same position throughout the entire series of single point measurements for each combination.
3. The device supports LTE B5/B26. Since the supported frequency span for LTE B5 falls completely within the supported frequency span for LTE B26, and both bands have the same target power and both LTE bands share the same transmission path, therefore standalone SAR was only assessed for LTE B26. The single point SAR time-sweep measurements were treated independently for each supported ACL frequency band. For the LTE Band 5 single point SAR measurement selected the highest measured SAR configuration and exposure condition of LTE B26. And the number of required single point measurements at least 11 applies to the band.
4. The tuner state was established remotely through Wi-Fi so that the device is not moved for the entire series of single point SAR for the tuner states in each combination (band, mode, exposure conditions).
5. The operational description contains more information about the design and implementation of the dynamic antenna tuning.

15.1 Supplemental Head SAR results

Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	0	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120	126	132	138			
WCDMA B2	RMC12.2K	1880	9400	N/A	N/A	Right Cheek	0mm	0.087	0.085	0.069	0.074	0.067	0.062	0.06	0.059	0.065	0.078	0.07	0.069	0.065	0.063	0.051	0.057	0.058	0.059	0.073	0.054	0.049	0.045	0.043	0.034	0.069	0.069			
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	1	7	13	19	25	31	37	43	49	55	61	67	73	79	85	91	97	103	109	115	121	127	133	139			
WCDMA B4	RMC12.2K	1752.6	1513	N/A	N/A	Left Cheek	0mm	0.098	0.096	0.043	0.087	0.091	0.09	0.09	0.089	0.033	0.071	0.073	0.073	0.071	0.069	0.054	0.053	0.042	0.031	0.066	0.091	0.094	0.096	0.093	0.074	0.066	0.073			
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	2	8	14	20	26	32	38	44	50	56	62	68	74	80	86	92	98	104	110	116	122	128	134	140			
WCDMA B5	RMC12.2K	836.4	4182	N/A	N/A	Left Cheek	0mm	0.299	0.295	0.01	0.086	0.241	0.221	0.168	0.071	0.011	0.112	0.294	0.226	0.171	0.074	0.072	0.069	0.179	0.001	0.012	0.078	0.228	0.234	0.158	0.047	0.225	0.147			
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	3	9	15	21	27	33	39	45	51	57	63	69	75	81	87	93	99	105	111	117	123	129	135	141			
LTE B2	QPSK	1900	19100	1	0	Right Cheek	0mm	0.09	0.088	0.074	0.061	0.054	0.052	0.05	0.039	0.08	0.067	0.062	0.062	0.059	0.049	0.046	0.044	0.051	0.071	0.05	0.041	0.038	0.035	0.034	0.052	0.065	0.046			
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	4	10	16	22	28	34	40	46	52	58	64	70	76	82	88	94	100	106	112	118	124	130	136	142			
LTE B4	QPSK	1732.5	20175	1	0	Right Cheek	0mm	0.095	0.092	0.091	0.09	0.089	0.09	0.088	0.081	0.079	0.089	0.086	0.089	0.09	0.09	0.079	0.066	0.047	0.051	0.087	0.086	0.087	0.088	0.089	0.064	0.091	0.09			
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																											
									Auto-Tune	5	11	17	23	29	35	41	47	53	59	65	71	77	83	89	95	101	107	113	119	125	131	137	143			
LTE B26	QPSK	831.5	26865	1	0	Left Cheek	0mm	0.254	0.251	0.045	0.145	0.231	0.211	0.171	0.085	0.051	0.175	0.249	0.214	0.174	0.092	0.089	0.096	0.198	0.022	0.041	0.123	0.234	0.232	0.072	0.026	0.233	0.071			

**15.2 Supplemental Body SAR results**

Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	0	6	12	18	24	30	36	42	48	54	60	66	72	78	84	90	96	102	108	114	120	126	132	138
WCDMA B2	RMC12.2K	1907.6	9538	N/A	N/A	Back	5mm	1.08	1.07	0.877	1.038	0.919	0.886	0.845	0.817	0.801	1.06	0.978	0.944	0.904	0.877	0.687	0.789	0.782	0.751	1.065	0.795	0.718	0.653	0.613	0.459	0.983	0.99
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	1	7	13	19	25	31	37	43	49	55	61	67	73	79	85	91	97	103	109	115	121	127	133	139
WCDMA B4	RMC12.2K	1712.4	1312	N/A	N/A	Back	5mm	0.922	0.913	0.435	0.888	0.91	0.891	0.888	0.892	0.329	0.743	0.858	0.882	0.905	0.911	0.789	0.683	0.479	0.337	0.511	0.758	0.859	0.88	0.898	0.899	0.774	0.863
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	2	8	14	20	26	32	38	44	50	56	62	68	74	80	86	92	98	104	110	116	122	128	134	140
WCDMA B5	RMC12.2K	846.6	4233	N/A	N/A	Back	5mm	1.16	1.096	0.0618	0.499	1.031	0.826	0.623	0.288	0.065	0.661	1.067	0.811	0.616	0.285	0.276	0.268	0.877	0.001	0.086	0.507	0.95	0.701	0.479	0.175	0.968	0.467
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	3	9	15	21	27	33	39	45	51	57	63	69	75	81	87	93	99	105	111	117	123	129	135	141
LTE B2	QPSK	1900	19100	100	0	Back	5mm	1.05	1.056	1.038	1.008	0.915	0.899	0.868	0.683	1.009	1.036	0.948	0.932	0.899	0.774	0.701	0.685	0.684	0.952	0.938	0.781	0.746	0.692	0.652	0.682	0.981	0.745
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	4	10	16	22	28	34	40	46	52	58	64	70	76	82	88	94	100	106	112	118	124	130	136	142
LTE B4	QPSK	1732.5	20175	100	0	Back	5mm	0.78	0.77	0.64	0.756	0.742	0.731	0.741	0.756	0.515	0.709	0.746	0.767	0.769	0.699	0.586	0.405	0.258	0.272	0.608	0.721	0.735	0.743	0.758	0.407	0.683	0.65
Mode	Service/Modulation	Frequency (MHz)	Channel	RB Size	RB Offset	Test Position	Spacing	Measured 1g SAR (W/kg)	Average Value of Time Sweep (W/kg)																								
									Auto-Tune	5	11	17	23	29	35	41	47	53	59	65	71	77	83	89	95	101	107	113	119	125	131	137	143
LTE B26	QPSK	831.5	26865	1	0	Back	5mm	0.883	0.879	0.125	0.558	0.819	0.707	0.57	0.264	0.155	0.669	0.868	0.713	0.574	0.288	0.277	0.307	0.727	0.017	0.109	0.459	0.778	0.688	0.197	0.031	0.789	0.197

Test Engineer : Mood Huang, Ted Hsieh, Kurt Liu, Randy Lin, Iran Wang, Galen Chang, Willy Yu, Andy Jiang and Bevis Chang

16. Uncertainty Assessment

Per KDB 865664 D01 SAR measurement 100MHz to 6GHz, when the highest measured 1-g SAR within a frequency band is < 1.5 W/kg and the measured 10-g SAR within a frequency band is < 3.75 W/kg. The expanded SAR measurement uncertainty must be $\leq 30\%$, for a confidence interval of $k = 2$. If these conditions are met, extensive SAR measurement uncertainty analysis described in IEEE Std 1528-2013 is not required in SAR reports submitted for equipment approval. For this device, the highest measured 1-g SAR is less 1.5W/kg and highest measured 10-g SAR is less 3.75W/kg. Therefore, the measurement uncertainty table is not required in this report.

17. References

- [1] FCC 47 CFR Part 2 "Frequency Allocations and Radio Treaty Matters; General Rules and Regulations"
- [2] ANSI/IEEE Std. C95.1-1992, "IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz", September 1992
- [3] IEEE Std. 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", Sep 2013
- [4] SPEAG DASY System Handbook
- [5] FCC KDB 248227 D01 v02r02, "SAR Guidance for IEEE 802.11 (WiFi) Transmitters", Oct 2015.
- [6] FCC KDB 447498 D01 v06, "Mobile and Portable Device RF Exposure Procedures and Equipment Authorization Policies", Oct 2015
- [7] FCC KDB 648474 D04 v01r03, "SAR Evaluation Considerations for Wireless Handsets", Oct 2015.
- [8] FCC KDB 941225 D01 v03r01, "3G SAR MEAUREMENT PROCEDURES", Oct 2015
- [9] FCC KDB 941225 D05 v02r05, "SAR Evaluation Considerations for LTE Devices", Dec 2015
- [10] FCC KDB 941225 D05A v01r02, "Rel. 10 LTE SAR Test Guidance and KDB Inquiries", Oct 2015
- [11] FCC KDB 941225 D06 v02r01, "SAR Evaluation Procedures for Portable Devices with Wireless Router Capabilities", Oct 2015.
- [12] FCC KDB 865664 D01 v01r04, "SAR Measurement Requirements for 100 MHz to 6 GHz", Aug 2015.
- [13] FCC KDB 865664 D02 v01r02, "RF Exposure Compliance Reporting and Documentation Considerations" Oct 2015.