FCC RADIO TEST REPORT

FCC ID	:	**IHDT56XN2**
Equipment	:	**Mobile Cellular Phone**
Brand Name	:	**Motorola**
Model Name	:	**XT1965-2**
Applicant	:	**Motorola Mobility LLC** **222 W,Merchandise Mart Plaza, Chicago IL 60654 USA**
Manufacturer	:	**Motorola Mobility LLC** **222 W,Merchandise Mart Plaza, Chicago IL 60654 USA**
Standard	:	**FCC Part 15 Subpart C §15.247**

The product was received on Sep. 04, 2018 and testing was started from Sep. 11, 2018 and completed on Oct. 02, 2018. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any agency of government.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Approved by: Joseph Lin

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)

Table of Contents

History of this test report **3**

Summary of Test Result **4**

1 General Description **5**

1.1 Product Feature of Equipment Under Test 5
1.2 Product Specification of Equipment Under Test 7
1.3 Modification of EUT 7
1.4 Testing Location 8
1.5 Applicable Standards 8

2 Test Configuration of Equipment Under Test **9**

2.1 Carrier Frequency and Channel 9
2.2 Test Mode 10
2.3 Connection Diagram of Test System 11
2.4 Support Unit used in test configuration and system 12
2.5 EUT Operation Test Setup 12
2.6 Measurement Results Explanation Example 12

3 Test Result **13**

3.1 6dB and 99% Bandwidth Measurement 13
3.2 Output Power Measurement 15
3.3 Power Spectral Density Measurement 16
3.4 Conducted Band Edges and Spurious Emission Measurement 18
3.5 Radiated Band Edges and Spurious Emission Measurement 28
3.6 AC Conducted Emission Measurement 32
3.7 Antenna Requirements 34

4 List of Measuring Equipment **35**

5 Uncertainty of Evaluation **37**

Appendix A. Conducted Test Results

Appendix B. AC Conducted Emission Test Result

Appendix C. Radiated Spurious Emission

Appendix D. Radiated Spurious Emission Plots

Appendix E. Duty Cycle Plots

History of this test report

Report No.	Version	Description	Issued Date
FR890437C	01	Initial issue of report	Oct. 04, 2018

Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)	Power Output Measurement	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges	Pass	-
		Conducted Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 3.45 dB at 2390.000 MHz
3.6	15.207	AC Conducted Emission	Pass	Under limit 11.78 dB at 0.564 MHz
3.7	15.203 & 15.247(b)	Antenna Requirement	Pass	-

Reviewed by: Wii Chang

Report Producer: Natasha Hsieh

1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature		
Equipment	Mobile Cellular Phone	
Brand Name	Motorola	
Model Name	XT1965-2	
Sample 1	Dual SIM	
Sample 2	Single SIM	
FCC ID	IHDT56XN2	
IMEI Code	**Conducted :**	IMEI 1: 355577090032556 IMEI 2: 355577090032564
	Conduction :	IMEI 1: 355577090033497 IMEI 2: 355577090033505
	Radiation :	IMEI 1: 355577090033778 IMEI 2: 355576090002791
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/GNSS/NFC/FM WLAN 11b/g/n/ac HT20/VHT20 WLAN 11a/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE	
HW Version	DVT1-B	
EUT Stage	Identical Prototype	

Remark: The above EUT's information was declared by manufacturer.

Accessory List		
AC Adapter 1	Brand Name :	Motorola
	Model Name :	SC-31
	Manufacturer :	Salom
AC Adapter 1	Brand Name :	Motorola
	Model Name :	SC-32
	Manufacturer :	Salom
AC Adapter 1	Brand Name :	Motorola
	Model Name :	SC-37
	Manufacturer :	Salom
AC Adapter 1	Brand Name :	Motorola
	Model Name :	SC-36
	Manufacturer :	Salom
AC Adapter 1	Brand Name :	Motorola
	Model Name :	SC-32
	Manufacturer :	Salom
AC Adapter 2	Brand Name :	Motorola
	Model Name :	SC-31
	Manufacturer :	Acbel
AC Adapter 2	Brand Name :	Motorola
	Model Name :	SC-32
	Manufacturer :	Acbel
AC Adapter 2	Brand Name :	Motorola
	Model Name :	SC-36
	Manufacturer :	Acbel
AC Adapter 2	Brand Name :	Motorola
	Model Name :	SC-37
	Manufacturer :	Acbel
Battery	Brand Name :	Motorola
	Model Name :	JG40
	Manufacturer :	Amperex
Earphone	Brand Name :	Motorola
	Model Name :	SH38C37773
	Manufacturer :	Lyand
USB Cable 1	Brand Name :	Cabletech
	Model Name :	SC18C37155
USB Cable 2	Brand Name :	Luxshare
	Model Name :	SC18C37156
USB Cable 3	Brand Name :	Saibao
	Model Name :	SC18C37157

1.2 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	2412 MHz ~ 2462 MHz
Maximum (Peak) Output Power to antenna	802.11b : 22.72 dBm (0.1871 W) 802.11g : 22.55 dBm (0.1799 W) 802.11n HT20 : 22.60 dBm (0.1820 W) 802.11ac VHT20 : 22.59 dBm (0.1816 W)
99% Occupied Bandwidth	802.11b : 12.90MHz 802.11g : 17.00MHz 802.11n HT20 : 18.10MHz
Antenna Type / Gain	Internal Antenna with gain -2.04 dBi
Type of Modulation	802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac : OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM)

1.3 Modification of EUT

No modifications are made to the EUT during all test items.

1.4 Testing Location

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1190 and TW0007 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

Test Site	SPORTON INTERNATIONAL INC.	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	**Sporton Site No.**	
	TH05-HY	CO05-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	SPORTON INTERNATIONAL INC.
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	**Sporton Site No.**
	03CH11-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

1.5 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15 Subpart C §15.247
- FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
- FCC KDB 414788 D01 Radiated Test Site v01r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	1	2412	7	2442
	2	2417	8	2447
	3	2422	9	2452
	4	2427	10	2457
	5	2432	11	2462
	6	2437		

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11b	1 Mbps
802.11g	6 Mbps
802.11n HT20	MCS0
802.11ac VHT20 (Covered by HT20)	MCS0

Test Cases	
AC Conducted Emission	Mode 1 :GSM850 Idle + Bluetooth Link + WLAN (2.4GHz) Link + MP3 + Earphone + Battery + USB Cable 1 Type C (Charging from Adapter 1) for Sample 1
Remark: For Radiated Test Cases, the tests were performed with Adapter 1, USB Cable 1 Type C and Sample 1	

2.3 Connection Diagram of Test System

<WLAN Tx Mode>



<AC Conducted Emission Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	Notebook	DELL	P20G	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “CMD” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) ≥ 3 * RBW.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth	Maximum 99% Occupied Bandwidth
	
Date: 18.SEP.2018 10:43:45	Date: 18.SEP.2018 11:27:30

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna with directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

3.2.3 Test Procedures

1. For Peak Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.1.3 PKPM1 Peak power meter method.
2. For Average Power, the testing follows the Measurement Procedure of FCC KDB No. 558074 DTS D01 Meas. Guidance v05 section 9.2.3.1 Method AVGPM.
3. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average output Power (Reporting Only)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure 10.2 Method PKPSD of FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/3kHz)



Date: 18.SEP.2018 10:44:07

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.

3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Test Engineer :	Luffy Lin / Aking Chang	**Temperature :**	21~25℃
		Relative Humidity :	51~54%

Number of TX = 1, Ant. 1 (Measured)

Test Mode :	802.11b	**Test Channel :**	01

100kHz PSD reference Level



Date: 18.SEP.2018 10:38:12

Channel Plot



Date: 18.SEP.2018 10:38:27

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2018 10:40:19

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2018 10:40:35

Test Mode :	802.11b	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Date: 18.SEP.2018 10:44:29

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Date: 18.SEP.2018 10:44:50

Date: 18.SEP.2018 10:45:10

Test Mode :	802.11b	Test Channel :	11

100kHz PSD reference Level



Date: 18.SEP.2018 10:48:32

Channel Plot



Date: 18.SEP.2018 10:48:48

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2018 10:49:09

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2018 10:49:37

Test Mode :	802.11g	Test Channel :	01

100kHz PSD reference Level



Date: 18.SEP.2018 10:52:42

Channel Plot



Date: 18.SEP.2018 10:52:59

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2018 10:54:11

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2018 10:54:28

Test Mode :	802.11g	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Date: 18.SEP.2018 10:56:58

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Date: 18.SEP.2018 10:58:01

Date: 18.SEP.2018 10:58:17

Test Mode :	802.11g	Test Channel :	11

100kHz PSD reference Level



Date: 18.SEP.2018 11:02:48

Channel Plot



Date: 18.SEP.2018 11:04:10

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2018 11:04:48

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2018 11:05:25

Test Mode :	802.11n HT20	Test Channel :	01

100kHz PSD reference Level



Date: 2.OCT.2018 09:54:40

Channel Plot



Date: 2.OCT.2018 09:54:57

Spurious Emission 30MHz~3GHz



Date: 2.OCT.2018 09:55:27

Spurious Emission 2GHz~25GHz



Date: 2.OCT.2018 09:55:53

Test Mode :	802.11n HT20	Test Channel :	06

100kHz PSD reference Level	Channel Plot
	

Date: 18.SEP.2018 11:19:04

Spurious Emission 30MHz~3GHz	Spurious Emission 2GHz~25GHz
	

Date: 18.SEP.2018 11:19:39

Date: 18.SEP.2018 11:20:04

Test Mode :	802.11n HT20	Test Channel :	11

100kHz PSD reference Level



Date: 18.SEP.2018 11:25:27

Channel Plot



Date: 18.SEP.2018 11:26:01

Spurious Emission 30MHz~3GHz



Date: 18.SEP.2018 11:26:50

Spurious Emission 2GHz~25GHz



Date: 18.SEP.2018 11:27:04

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

3.5.3 Test Procedures

1. The testing follows FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.

3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of Emission (MHz)	Conducted Limit (dBµV)	
	Quasi-Peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

3.6.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room, and it was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF bandwidth = 9kHz) with Maximum Hold Mode.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If directional gain of transmitting Antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached Antenna or of an Antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	DTM-303A	TP157075	N/A	Mar. 06, 2018	Sep. 11, 2018~ Oct. 02, 2018	Mar. 05, 2019	Conducted (TH05-HY)
Power Meter	Anritsu	ML2495A	1132003	N/A	Aug. 16, 2018	Sep. 11, 2018~ Oct. 02, 2018	Aug. 15, 2019	Conducted (TH05-HY)
Power Sensor	Anritsu	MA2411B	1126017	300MHz~40GHz	Aug. 16, 2018	Sep. 11, 2018~ Oct. 02, 2018	Aug. 15, 2019	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100057	9kHz-40GHz	Nov. 21, 2017	Sep. 11, 2018~ Oct. 02, 2018	Nov. 20, 2018	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101397	10Hz~40GHz	Nov. 07, 2017	Sep. 11, 2018~ Oct. 02, 2018	Nov. 06, 2018	Conducted (TH05-HY)
Switch Box & RF Cable	Burgeon	ETF-058	EC1300484	N/A	Mar. 01, 2018	Sep. 11, 2018~ Oct. 02, 2018	Feb. 28, 2019	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Sep. 17, 2018	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9KHz~3.6GHz	Dec. 08, 2017	Sep. 17, 2018	Dec. 07, 2018	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Mar. 06, 2018	Sep. 17, 2018	Mar. 05, 2019	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 30, 2017	Sep. 17, 2018	Nov. 29, 2018	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Sep. 17, 2018	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 03, 2018	Sep. 17, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 03, 2018	Sep. 17, 2018	Jan. 02, 2019	Conduction (CO05-HY)
Amplifier	MITEQ	TTA1840-35-HG	1871923	18GHz~40GHz, VSWR : 2.5:1 max	Jul. 16, 2018	Sep. 14, 2018~ Sep. 19, 2018	Jul. 15, 2019	Radiation (03CH11-HY)
Amplifier	SONOMA	310N	187312	9kHz~1GHz	Jan. 16, 2018	Sep. 14, 2018~ Sep. 19, 2018	Jan. 15, 2019	Radiation (03CH11-HY)
Bilog Antenna	TESEQ	CBL 6111D&N-6-06	35414&AT-N0602	30MHz~1GHz	Oct. 14, 2017	Sep. 14, 2018~ Sep. 19, 2018	Oct. 13, 2018	Radiation (03CH11-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1326	1GHz ~ 18GHz	Oct. 16, 2017	Sep. 14, 2018~ Sep. 19, 2018	Oct. 15, 2018	Radiation (03CH11-HY)
Hygrometer	TECPEL	DTN-303B	TP140325	N/A	Oct. 12, 2017	Sep. 14, 2018~ Sep. 19, 2018	Oct. 11, 2018	Radiation (03CH11-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Nov. 23, 2017	Sep. 14, 2018~ Sep. 19, 2018	Nov. 22, 2018	Radiation (03CH11-HY)
Preamplifier	Keysight	83017A	MY53270080	1GHz~26.5GHz	Jan. 16, 2018	Sep. 14, 2018~ Sep. 19, 2018	Jan. 15, 2020	Radiation (03CH11-HY)
Spectrum Analyzer	Keysight	N9010A	MY54200486	10Hz ~ 44GHz	Oct. 19, 2017	Sep. 14, 2018~ Sep. 19, 2018	Oct. 18, 2018	Radiation (03CH11-HY)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Controller	EMEC	EM 1000	N/A	Control Turn table & Ant Mast	N/A	Sep. 14, 2018~ Sep. 19, 2018	N/A	Radiation (03CH11-HY)
Antenna Mast	EMEC	AM-BS-4500-B	N/A	1~4m	N/A	Sep. 14, 2018~ Sep. 19, 2018	N/A	Radiation (03CH11-HY)
Turn Table	EMEC	TT 2000	N/A	0~360 Degree	N/A	Sep. 14, 2018~ Sep. 19, 2018	N/A	Radiation (03CH11-HY)
Preamplifier	Jet-Power	JPA0118-55-303K	1710001800054002	1GHz~18GHz	Apr. 17, 2018	Sep. 14, 2018~ Sep. 19, 2018	Apr. 16, 2019	Radiation (03CH11-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170584	18GHz- 40GHz	Nov. 27, 2017	Sep. 14, 2018~ Sep. 19, 2018	Nov. 26, 2018	Radiation (03CH11-HY)
Software	Audix	E3 6.2009-8-24	RK-001042	N/A	N/A	Sep. 14, 2018~ Sep. 19, 2018	N/A	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	9kHz-30MHz	Mar. 14, 2018	Sep. 14, 2018~ Sep. 19, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30MHz-40GHz	Mar. 14, 2018	Sep. 14, 2018~ Sep. 19, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4PE	30M-18G	Mar. 14, 2018	Sep. 14, 2018~ Sep. 19, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30MHz-40GHz	Mar. 14, 2018	Sep. 14, 2018~ Sep. 19, 2018	Mar. 13, 2019	Radiation (03CH11-HY)
Filter	Wainwright	WLKS1200-8SS	SN3	1.2G Low Pass	Nov. 21, 2017	Sep. 14, 2018~ Sep. 19, 2018	Nov. 20, 2018	Radiation (03CH11-HY)
Filter	Microwave	H3G018G1	SN477220	3.0G High Pass	Nov. 21, 2017	Sep. 14, 2018~ Sep. 19, 2018	Nov. 20, 2018	Radiation (03CH11-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	2.20

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.20

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.50

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	5.20

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Luffy Lin / Aking Chang	Temperature:	21~25	°C
Test Date:	2018/9/11~10/02	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

2.4GHz Band										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)		6dB BW (MHz)		6dB BW Limit (MHz)	Pass/Fail
					Ant 1	Ant 2	Ant 1	Ant 2		
11b	1Mbps	1	1	2412	12.65	-	8.00	-	0.50	Pass
11b	1Mbps	1	6	2437	12.60	-	7.52	-	0.50	Pass
11b	1Mbps	1	11	2462	12.90	-	7.52	-	0.50	Pass
11g	6Mbps	1	1	2412	16.80	-	15.44	-	0.50	Pass
11g	6Mbps	1	6	2437	16.80	-	15.72	-	0.50	Pass
11g	6Mbps	1	11	2462	17.00	-	16.08	-	0.50	Pass
HT20	MCS0	1	1	2412	17.90	-	15.14	-	0.50	Pass
HT20	MCS0	1	6	2437	17.90	-	16.04	-	0.50	Pass
HT20	MCS0	1	11	2462	18.10	-	17.14	-	0.50	Pass

Report Number : FR890437C

TEST RESULTS DATA
Peak Output Power

2.4GHz Band																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)			Conducted Power Limit (dBm)		DG (dBi)		EIRP Power (dBm)		EIRP Power Limit (dBm)		Pass /Fail
					Ant 1	Ant 2	SUM	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	21.65	-	-	30.00	-	-2.04	-	19.61	-	36.00	-	Pass
11b	1Mbps	1	6	2437	22.72	-	-	30.00	-	-2.04	-	20.68	-	36.00	-	Pass
11b	1Mbps	1	11	2462	21.15	-	-	30.00	-	-2.04	-	19.11	-	36.00	-	Pass
11g	6Mbps	1	1	2412	21.72	-	-	30.00	-	-2.04	-	19.68	-	36.00	-	Pass
11g	6Mbps	1	6	2437	22.55	-	-	30.00	-	-2.04	-	20.51	-	36.00	-	Pass
11g	6Mbps	1	11	2462	21.13	-	-	30.00	-	-2.04	-	19.09	-	36.00	-	Pass
HT20	MCS0	1	1	2412	21.75	-	-	30.00	-	-2.04	-	19.71	-	36.00	-	Pass
HT20	MCS0	1	6	2437	22.60	-	-	30.00	-	-2.04	-	20.56	-	36.00	-	Pass
HT20	MCS0	1	11	2462	21.20	-	-	30.00	-	-2.04	-	19.16	-	36.00	-	Pass
VHT20	MCS0	1	1	2412	21.71	-	-	30.00	-	-2.04	-	19.67	-	36.00	-	Pass
VHT20	MCS0	1	6	2437	22.59	-	-	30.00	-	-2.04	-	20.55	-	36.00	-	Pass
VHT20	MCS0	1	11	2462	21.19	-	-	30.00	-	-2.04	-	19.15	-	36.00	-	Pass

Note: Measured power (dBm) has offset with cable loss.

Report Number : FR890437C

TEST RESULTS DATA
Average Output Power

2.4GHz Band									
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)		Average Conducted Power (dBm)		
					Ant 1	Ant 2	Ant 1	Ant 2	SUM
11b	1Mbps	1	1	2412	0.04	-	18.94	-	-
11b	1Mbps	1	6	2437	0.04	-	19.96	-	
11b	1Mbps	1	11	2462	0.04	-	18.41	-	
11g	6Mbps	1	1	2412	0.25	-	17.16	-	
11g	6Mbps	1	6	2437	0.25	-	17.90	-	
11g	6Mbps	1	11	2462	0.25	-	16.75	-	
HT20	MCS0	1	1	2412	0.27	-	16.82	-	
HT20	MCS0	1	6	2437	0.27	-	17.77	-	
HT20	MCS0	1	11	2462	0.27	-	16.61	-	
VHT20	MCS0	1	1	2412	0.26	-	16.67	-	
VHT20	MCS0	1	6	2437	0.26	-	17.70	-	
VHT20	MCS0	1	11	2462	0.26	-	16.59	-	

Note: Measured power (dBm) has offset with cable loss.

Report Number : FR890437C

TEST RESULTS DATA
Peak Power Spectral Density

2.4GHz Band												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm/3kHz)			DG (dBi)		Peak PSD Limit (dBm/3kHz)		Pass/Fail
					Ant 1	Ant 2	Worse + 3.01	Ant 1	Ant 2	Ant 1	Ant 2	
11b	1Mbps	1	1	2412	-3.02	-	-	-2.04	-	8.00	-	Pass
11b	1Mbps	1	6	2437	-1.76	-	-	-2.04	-	8.00	-	Pass
11b	1Mbps	1	11	2462	-2.29	-	-	-2.04	-	8.00	-	Pass
11g	6Mbps	1	1	2412	-7.50	-	-	-2.04	-	8.00	-	Pass
11g	6Mbps	1	6	2437	-7.72	-	-	-2.04	-	8.00	-	Pass
11g	6Mbps	1	11	2462	-7.62	-	-	-2.04	-	8.00	-	Pass
HT20	MCS0	1	1	2412	-9.87	-	-	-2.04	-	8.00	-	Pass
HT20	MCS0	1	6	2437	-8.84	-	-	-2.04	-	8.00	-	Pass
HT20	MCS0	1	11	2462	-8.65	-	-	-2.04	-	8.00	-	Pass

Measured power density (dBm) has offset with cable loss.

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Rick Lin	**Temperature :**	22~23℃
		Relative Humidity :	48~49%

EUT Information

Report NO :	890437
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Line



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.154500	---	30.52	55.75	25.23	L1	OFF	19.5
0.154500	46.27	---	65.75	19.48	L1	OFF	19.5
0.312000	---	25.64	49.92	24.28	L1	OFF	19.5
0.312000	33.74	---	59.92	26.18	L1	OFF	19.5
0.519000	---	25.95	46.00	20.05	L1	OFF	19.5
0.519000	37.02	---	56.00	18.98	L1	OFF	19.5
0.602250	---	24.55	46.00	21.45	L1	OFF	19.6
0.602250	33.65	---	56.00	22.35	L1	OFF	19.6
1.506750	---	23.60	46.00	22.40	L1	OFF	19.6
1.506750	27.18	---	56.00	28.82	L1	OFF	19.6
5.446500	---	25.35	50.00	24.65	L1	OFF	19.7
5.446500	26.95	---	60.00	33.05	L1	OFF	19.7
11.436000	---	27.53	50.00	22.47	L1	OFF	20.0
11.436000	30.32	---	60.00	29.68	L1	OFF	20.0

EUT Information

Report NO :	890437
Test Mode :	Mode 1
Test Voltage :	120Vac/60Hz
Phase :	Neutral



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.152250	---	34.14	55.88	21.74	N	OFF	19.5
0.152250	51.83	---	65.88	14.05	N	OFF	19.5
0.156750	---	33.49	55.63	22.14	N	OFF	19.5
0.156750	50.82	---	65.63	14.81	N	OFF	19.5
0.161250	---	31.29	55.40	24.11	N	OFF	19.5
0.161250	49.42	---	65.40	15.98	N	OFF	19.5
0.503250	---	32.30	46.00	13.70	N	OFF	19.5
0.503250	39.55	---	56.00	16.45	N	OFF	19.5
0.564000	---	34.22	46.00	11.78	N	OFF	19.5
0.564000	38.47	---	56.00	17.53	N	OFF	19.5
0.597750	---	23.55	46.00	22.45	N	OFF	19.5
0.597750	30.71	---	56.00	25.29	N	OFF	19.5
0.656250	---	28.15	46.00	17.85	N	OFF	19.6
0.656250	34.30	---	56.00	21.70	N	OFF	19.6
2.508000	---	26.97	46.00	19.03	N	OFF	19.6
2.508000	30.27	---	56.00	25.73	N	OFF	19.6
11.364000	---	29.88	50.00	20.12	N	OFF	20.0
11.364000	33.26	---	60.00	26.74	N	OFF	20.0

Appendix C. Radiated Spurious Emission

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	Temperature :	21~26°C
		Relative Humidity :	51~56%

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2384.445	52.56	-21.44	74	42.57	27.09	16.5	33.6	132	0	P	H
		2385.285	41.71	-12.29	54	31.72	27.09	16.5	33.6	132	0	A	H
	*	2412	109.37	-	-	99.25	27.18	16.53	33.59	132	0	P	H
	*	2412	106.21	-	-	96.09	27.18	16.53	33.59	132	0	A	H
													H
													H
		2380.875	51.97	-22.03	74	41.99	27.09	16.49	33.6	235	136	P	V
		2385.18	41.3	-12.7	54	31.31	27.09	16.5	33.6	235	136	A	V
	*	2412	104.88	-	-	94.76	27.18	16.53	33.59	235	136	P	V
	*	2412	101.61	-	-	91.49	27.18	16.53	33.59	235	136	A	V
													V
													V
802.11b CH 06 2437MHz		2388.08	51.5	-22.5	74	41.47	27.13	16.5	33.6	132	16	P	H
		2389.84	41.7	-12.3	54	31.66	27.13	16.5	33.59	132	16	A	H
	*	2437	110.02	-	-	99.79	27.27	16.55	33.59	132	16	P	H
	*	2437	106.97	-	-	96.74	27.27	16.55	33.59	132	16	A	H
		2486.24	53.46	-20.54	74	43.09	27.36	16.59	33.58	132	16	P	H
		2484.72	42.32	-11.68	54	31.95	27.36	16.59	33.58	132	16	A	H
		2367.28	51.79	-22.21	74	41.88	27.04	16.47	33.6	269	258	P	V
		2389.36	41.31	-12.69	54	31.28	27.13	16.5	33.6	269	258	A	V
	*	2437	105.7	-	-	95.47	27.27	16.55	33.59	269	258	P	V
	*	2437	102.63	-	-	92.4	27.27	16.55	33.59	269	258	A	V
		2493.28	51.78	-22.22	74	41.36	27.4	16.59	33.57	269	258	P	V
		2484.88	41.75	-12.25	54	31.38	27.36	16.59	33.58	269	258	A	V

802.11b CH 11 2462MHz	*	2462	108.33	-	-	98.03	27.31	16.57	33.58	125	357	P	H
	*	2462	105.08	-	-	94.78	27.31	16.57	33.58	125	357	A	H
		2486.72	56.1	-17.9	74	45.73	27.36	16.59	33.58	125	357	P	H
		2486.56	42.43	-11.57	54	32.06	27.36	16.59	33.58	125	357	A	H
													H
													H
	*	2462	103.98	-	-	93.68	27.31	16.57	33.58	261	258	P	V
	*	2462	100.82	-	-	90.52	27.31	16.57	33.58	261	258	A	V
		2486.04	53.81	-20.19	74	43.44	27.36	16.59	33.58	261	258	P	V
		2485.56	41.87	-12.13	54	31.5	27.36	16.59	33.58	261	258	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		4824	41.08	-32.92	74	56.27	31.29	10.09	56.57	100	0	P	H
													H
													H
													H
		4824	42.66	-31.34	74	57.85	31.29	10.09	56.57	100	0	P	V
													V
													V
													V
802.11b CH 06 2437MHz		4874	44.49	-29.51	74	59.52	31.38	10.14	56.55	100	0	P	H
		7311	41.37	-32.63	74	48.79	36.28	12.53	56.23	100	0	P	H
													H
													H
		4874	44.83	-29.17	74	59.86	31.38	10.14	56.55	100	0	P	V
		7311	41.68	-32.32	74	49.1	36.28	12.53	56.23	100	0	P	V
													V
													V
802.11b CH 11 2462MHz		4924	44.23	-29.77	74	59.07	31.48	10.21	56.53	100	0	P	H
		7386	40.09	-33.91	74	47.3	36.47	12.44	56.12	100	0	P	H
													H
													H
		4924	46.06	-27.94	74	60.9	31.48	10.21	56.53	100	0	P	V
		7386	40.79	-33.21	74	48	36.47	12.44	56.12	100	0	P	V
													V
													V

Remark

1. No other spurious found.
2. All results are PASS against Peak and Average limit line.

2.4GHz 2400~2483.5MHz
WIFI 802.11g (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11g CH 01 2412MHz		2389.905	60.59	-13.41	74	50.55	27.13	16.5	33.59	131	0	P	H
		2390	49.91	-4.09	54	39.86	27.13	16.51	33.59	131	0	A	H
	*	2412	109.25	-	-	99.13	27.18	16.53	33.59	131	0	P	H
	*	2412	101.42	-	-	91.3	27.18	16.53	33.59	131	0	A	H
													H
													H
		2390	56.9	-17.1	74	46.85	27.13	16.51	33.59	235	141	P	V
		2390	46.33	-7.67	54	36.28	27.13	16.51	33.59	235	141	A	V
	*	2412	104.34	-	-	94.22	27.18	16.53	33.59	235	141	P	V
	*	2412	96.52	-	-	86.4	27.18	16.53	33.59	235	141	A	V
													V
													V
802.11g CH 06 2437MHz		2388.4	56.53	-17.47	74	46.5	27.13	16.5	33.6	180	356	P	H
		2388.72	42.85	-11.15	54	32.82	27.13	16.5	33.6	180	356	A	H
	*	2437	109.76	-	-	99.53	27.27	16.55	33.59	180	356	P	H
	*	2437	101.74	-	-	91.51	27.27	16.55	33.59	180	356	A	H
		2484.8	57.87	-16.13	74	47.5	27.36	16.59	33.58	180	356	P	H
		2483.6	43.53	-10.47	54	33.16	27.36	16.59	33.58	180	356	A	H
		2387.92	52.96	-21.04	74	42.93	27.13	16.5	33.6	268	260	P	V
		2389.68	42.33	-11.67	54	32.3	27.13	16.5	33.6	268	260	A	V
	*	2437	105.67	-	-	95.44	27.27	16.55	33.59	268	260	P	V
	*	2437	97.86	-	-	87.63	27.27	16.55	33.59	268	260	A	V
		2486.24	56.38	-17.62	74	46.01	27.36	16.59	33.58	268	260	P	V
		2487.6	42.9	-11.1	54	32.49	27.4	16.59	33.58	268	260	A	V

802.11g CH 11 2462MHz	*	2462	107.58	-	-	97.28	27.31	16.57	33.58	126	352	P	H
	*	2462	100.01	-	-	89.71	27.31	16.57	33.58	126	352	A	H
		2487.4	61.94	-12.06	74	51.57	27.36	16.59	33.58	126	352	P	H
		2483.52	45.72	-8.28	54	35.35	27.36	16.59	33.58	126	352	A	H
													H
													H
	*	2462	103.43	-	-	93.13	27.31	16.57	33.58	263	260	P	V
	*	2462	95.62	-	-	85.32	27.31	16.57	33.58	263	260	A	V
		2486.52	58.92	-15.08	74	48.55	27.36	16.59	33.58	263	260	P	V
		2483.84	43.73	-10.27	54	33.36	27.36	16.59	33.58	263	260	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11g CH 01 2412MHz		4824	39.37	-34.63	74	54.56	31.29	10.09	56.57	100	0	P	H
													H
													H
													H
		4824	39.86	-34.14	74	55.05	31.29	10.09	56.57	100	0	P	V
													V
													V
													V
802.11g CH 06 2437MHz		4874	40.07	-33.93	74	55.1	31.38	10.14	56.55	100	0	P	H
		7311	41.76	-32.24	74	49.18	36.28	12.53	56.23	100	0	P	H
													H
													H
		4874	40.81	-33.19	74	55.84	31.38	10.14	56.55	100	0	P	V
		7311	40.98	-33.02	74	48.4	36.28	12.53	56.23	100	0	P	V
													V
													V
802.11g CH 11 2462MHz		4924	40.95	-33.05	74	55.79	31.48	10.21	56.53	100	0	P	H
		7386	40.56	-33.44	74	47.77	36.47	12.44	56.12	100	0	P	H
													H
													H
		4924	43.15	-30.85	74	57.99	31.48	10.21	56.53	100	0	P	V
		7386	40.42	-33.58	74	47.63	36.47	12.44	56.12	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz
WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 01 2412MHz		2389.905	61.1	-12.9	74	51.06	27.13	16.5	33.59	132	0	P	H
		2390	50.55	-3.45	54	40.5	27.13	16.51	33.59	132	0	A	H
	*	2412	108.59	-	-	98.47	27.18	16.53	33.59	132	0	P	H
	*	2412	100.35	-	-	90.23	27.18	16.53	33.59	132	0	A	H
													H
													H
		2389.59	58.01	-15.99	74	47.98	27.13	16.5	33.6	235	141	P	V
		2390	47.29	-6.71	54	37.24	27.13	16.51	33.59	235	141	A	V
	*	2412	103.78	-	-	93.66	27.18	16.53	33.59	235	141	P	V
	*	2412	95.52	-	-	85.4	27.18	16.53	33.59	235	141	A	V
													V
													V
802.11n HT20 CH 06 2437MHz		2388.56	60.07	-13.93	74	50.04	27.13	16.5	33.6	134	18	P	H
		2386.96	44.2	-9.8	54	34.17	27.13	16.5	33.6	134	18	A	H
	*	2437	109.85	-	-	99.62	27.27	16.55	33.59	134	18	P	H
	*	2437	101.58	-	-	91.35	27.27	16.55	33.59	134	18	A	H
		2487.2	62.95	-11.05	74	52.58	27.36	16.59	33.58	134	18	P	H
		2487.2	45.21	-8.79	54	34.84	27.36	16.59	33.58	134	18	A	H
		2387.28	53.07	-20.93	74	43.04	27.13	16.5	33.6	268	260	P	V
		2386.8	42.3	-11.7	54	32.27	27.13	16.5	33.6	268	260	A	V
	*	2437	104.78	-	-	94.55	27.27	16.55	33.59	268	260	P	V
	*	2437	97.16	-	-	86.93	27.27	16.55	33.59	268	260	A	V
		2486.32	56.04	-17.96	74	45.67	27.36	16.59	33.58	268	260	P	V
		2489.36	42.71	-11.29	54	32.3	27.4	16.59	33.58	268	260	A	V

802.11n HT20 CH 11 2462MHz	*	2462	107.98	-	-	97.68	27.31	16.57	33.58	125	357	P	H
	*	2462	99.45	-	-	89.15	27.31	16.57	33.58	125	357	A	H
		2485.56	62.48	-11.52	74	52.11	27.36	16.59	33.58	125	357	P	H
		2483.52	47.04	-6.96	54	36.67	27.36	16.59	33.58	125	357	A	H
													H
													H
	*	2462	102.9	-	-	92.6	27.31	16.57	33.58	262	262	P	V
	*	2462	94.9	-	-	84.6	27.31	16.57	33.58	262	262	A	V
		2486.8	59.55	-14.45	74	49.18	27.36	16.59	33.58	262	262	P	V
		2483.56	44.25	-9.75	54	33.88	27.36	16.59	33.58	262	262	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBµV/m)	(dB)	(dBµV/m)	(dBµV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11n HT20 CH 01 2412MHz		4824	39.03	-34.97	74	54.22	31.29	10.09	56.57	100	0	P	H
													H
													H
													H
		4824	40.2	-33.8	74	55.39	31.29	10.09	56.57	100	0	P	V
													V
													V
													V
802.11n HT20 CH 06 2437MHz		4874	40.7	-33.3	74	55.73	31.38	10.14	56.55	100	0	P	H
		7311	40.87	-33.13	74	48.29	36.28	12.53	56.23	100	0	P	H
													H
													H
		4874	41.53	-32.47	74	56.56	31.38	10.14	56.55	100	0	P	V
		7311	40.13	-33.87	74	47.55	36.28	12.53	56.23	100	0	P	V
													V
													V
802.11n HT20 CH 11 2462MHz		4924	41.1	-32.9	74	55.94	31.48	10.21	56.53	100	0	P	H
		7386	40.12	-33.88	74	47.33	36.47	12.44	56.12	100	0	P	H
													H
													H
		4924	41.7	-32.3	74	56.54	31.48	10.21	56.53	100	0	P	V
		7386	40.84	-33.16	74	48.05	36.47	12.44	56.12	100	0	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz 802.11n HT20 LF		30	25.33	-14.67	40	32.89	24.17	0.77	32.5			P	H
		67.53	27.34	-12.66	40	46.81	11.88	1.14	32.49			P	H
		185.79	25.1	-18.4	43.5	41.04	14.59	1.87	32.4			P	H
		516.3	25.27	-20.73	46	30.96	23.76	2.94	32.39			P	H
		721.4	31.91	-14.09	46	33.83	26.94	3.55	32.41			P	H
		959.4	33.78	-12.22	46	29.67	31.07	4.16	31.12	100	0	P	H
													H
													H
													H
													H
													H
													H
		30	33.39	-6.61	40	40.95	24.17	0.77	32.5	100	52	P	V
		48.36	31.66	-8.34	40	48.3	14.9	0.95	32.49			P	V
		74.55	28.85	-11.15	40	47.71	12.44	1.19	32.49			P	V
		482	26.89	-19.11	46	32.96	23.47	2.83	32.37			P	V
		721.4	31.67	-14.33	46	33.59	26.94	3.55	32.41			P	V
		946.8	33.67	-12.33	46	30.37	30.41	4.12	31.23			P	V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =

Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Hao Hsu, Ken Wu, and Chuan Zhu	**Temperature :**	21~26°C
		Relative Humidity :	51~56%

Note symbol

-L	**Low channel location**
-R	**High channel location**

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 19	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 19
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 890437 Seting : 19	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:0.010KHz SWT:Auto Detector : Peak Project : 890437 Seting : 19

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - L	
1	Vertical	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH06 2437MHz - R	
1	Vertical	Fundamental
Peak		Left blank
Avg.		Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11b CH11 2462MHz	
1	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH01 2412MHz	
1	Vertical	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - L	
1	Vertical	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH06 2437MHz - R	
1	Vertical	Fundamental
Peak		Left Blank
Avg.		Left Blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11g CH11 2462MHz	
1	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Vertical	Fundamental
Peak	 Site : 03CH11-HY Condition : PEAK_BE_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 17	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 17
Avg.	 Site : 03CH11-HY Condition : AVG_BE_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 17	 Site : 03CH11-HY Condition : AVG_54 3m HORN 9120D-HF VERTICAL : RBW:1000.000KHz VBW:1.000KHz SWT:Auto Detector : Peak Project : 890437 Seting : 17

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Horizontal	Fundamental
Peak		Left blank
Avg.		Left blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - L	
1	Vertical	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH06 2437MHz - R	
1	Vertical	Fundamental
Peak		Left Blank
Avg.		Left Blank

WIFI	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Fundamental
Peak		
Avg.		

WIFI	2.4GHz 2400~2483.5MHz Fundamental @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Vertical	Fundamental
Peak		
Avg.		

2.4GHz 2400~2483.5MHz

WIFI 802.11b (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 890437	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 890437

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11b CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 890437	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 890437

2.4GHz 2400~2483.5MHz

WIFI 802.11g (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11g CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 890437	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 890437

2.4GHz 2400~2483.5MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH01 2412MHz	
1	Horizontal	Vertical
Peak Avg.		

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH06 2437MHz	
1	Horizontal	Vertical
Peak Avg.	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF HORIZONTAL Detector : Peak Project : 890437	 Site : 03CH11-HY Condition : PEAK_74 3m HORN 9120D-HF VERTICAL Detector : Peak Project : 890437

WIFI	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
ANT	802.11n HT20 CH11 2462MHz	
1	Horizontal	Vertical
Peak Avg.		

Emission below 1GHz

2.4GHz WIFI 802.11n HT20 (LF)

WIFI	2.4GHz 2400~2483.5MHz	
ANT	802.11n HT20 LF	
1	Horizontal	Vertical
QP / Peak		

Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting	Duty Factor(dB)
802.11b	99.04	-	-	10Hz	0.04
802.11g	94.50	2060	0.49	1kHz	0.25
2.4GHz 802.11n HT20	94.06	1900	0.53	1kHz	0.27
2.4GHz 802.11ac VHT20	94.15	1930	0.52	1kHz	0.26

802.11b



Date: 11.SEP.2018 05:31:30

802.11g



Date: 11.SEP.2018 05:50:37

802.11n HT20



Date: 11.SEP.2018 05:59:27

802.11ac VHT20



Date: 11.SEP.2018 06:09:16

THE END