FCC RF Test Report

APPLICANT	:	**Motorola Mobility LLC**
EQUIPMENT	:	**Mobile Cellular Phone**
BRAND NAME	:	**Motorola**
MODEL NAME	:	**XT1980-4**
FCC ID	:	**IHDT56XS1**
STANDARD	:	**47 CFR Part 2, 22(H), 24(E), 27(L), 27(M), 27(F) , 27(H)**
CLASSIFICATION	:	**PCS Licensed Transmitter Held to Ear (PCE)**

The product was received on Dec. 28, 2018 and completely tested on Feb. 26, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang

Approved by: James Huang / Manager

TESTING
NVLAP LAB CODE 600155-0

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **6**

1.1 Applicant 6
1.2 Manufacturer 6
1.3 Product Feature of Equipment Under Test 6
1.4 Product Specification of Equipment Under Test 7
1.5 Modification of EUT 7
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 8
1.7 Testing Location 13
1.8 Applicable Standards 13
1.9 Specification of Accessory 14

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **15**

2.1 Test Mode 15
2.2 Connection Diagram of Test System 20
2.3 Support Unit used in test configuration and system 20
2.4 Measurement Results Explanation Example 21
2.5 Frequency List of Low/Middle/High Channels 22

3 CONDUCTED TEST ITEMS **26**

3.1 Measuring Instruments 26
3.2 Test Setup 26
3.3 Test Result of Conducted Test 26
3.4 Conducted Output Power and ERP/EIRP 27
3.5 Peak-to-Average Ratio 28
3.6 Occupied Bandwidth 29
3.7 Conducted Band Edge 30
3.8 Conducted Spurious Emission 32
3.9 Frequency Stability 33

4 RADIATED TEST ITEMS **34**

4.1 Measuring Instruments 34
4.2 Test Setup 34
4.3 Test Result of Radiated Test 34
4.4 Radiated Spurious Emission 35

5 LIST OF MEASURING EQUIPMENT **36**

6 UNCERTAINTY OF EVALUATION **37**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG8D2801-01B	Rev. 01	Initial issue of report	Mar. 12, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power (Band 5)	ERP < 7 Watt	PASS	-
	§27.50(b)(10) §27.50(c)(10)	Effective Radiated Power (Band 12) (Band 13)	ERP < 3 Watt	PASS	-
	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 2)(Band 7)	EIRP < 2Watt	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4) (Band 66)	EIRP < 1Watt	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2)(4) §27.53(g) §27.53(h)	Conducted Band Edge Measurement (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 66)	< 43+10log10(P[Watts])	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7)	§27.53(m)(4)		
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(g) §27.53(h)	Conducted Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13) (Band 66)	< 43+10log10(P[Watts])	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7)	< 55+10log$_{10}$(P[Watts])		
3.9	§2.1055 §22.355	Frequency Stability Temperature & Voltage	< 2.5 ppm for Part 22H	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		

Report Section	FCC Rule	Description	Limit	Result	Remark
4.4	§2.1053 §22.917(a) §24.238(a) §27.53(c)(2) §27.53(f) §27.53(g) §27.53(h)	Radiated Spurious Emission (Band 2) (Band 4) (Band 5) (Band 12) (Band 13)(Band 66)	< 43+10log$_{10}$(P[Watts])	PASS	Under limit 17.42 dB at 5052.000 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7)	< 55+10log$_{10}$(P[Watts])		

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1980-4
FCC ID	IHDT56XS1
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM uplink is not supported)/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
IMEI Code	Conducted: 352157100004433 Radiation: 352157100004805for B2/B5/B7/B12/5B_CA 352157100004755 for B13/B66
HW Version	DVT2
SW Version	PDF29.58
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13 : 748.5 MHz ~ 753.5 MHz LTE Band 66 : 2110.7 MHz~ 2199.3 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 4 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 5 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 7 : 5MHz/ 10MHz / 15MHz / 20MHz LTE Band 12 : 1.4MHz / 3MHz / 5MHz / 10MHz LTE Band 13 : 5MHz / 10MHz LTE Band 66 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 2 : 23.45 dBm LTE Band 4 : 23.01 dBm LTE Band 5 : 23.30 dBm; Band 5B_CA: 23.54 dBm LTE Band 7 : 23.04 dBm LTE Band 13 : 23.05 dBm LTE Band 12 : 23.12 dBm LTE Band 66 : 23.06 dBm
Antenna Gain	LTE Band 2 : -1.00 dBi LTE Band 4 : 1.00 dBi LTE Band 5 : -3.00 dBi LTE Band 7 : 1.00 dBi LTE Band 12 : -3.00 dBi LTE Band 13 : -3.00 dBi LTE Band 66 : 1.00 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 2		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1909.3	1M10G7D	-	0.1706	1M09W7D	-	0.1500
3	1851.5 ~ 1908.5	2M73G7D	-	0.1702	2M73W7D	-	0.1500
5	1852.5 ~ 1907.5	4M51G7D	-	0.1718	4M49W7D	-	0.1503
10	1855.0 ~ 1905.0	9M05G7D	0.0028	0.1754	9M05W7D	-	0.1500
15	1857.5 ~ 1902.5	13M4G7D	-	0.1730	13M5W7D	-	0.1528
20	1860.0 ~ 1900.0	18M3G7D	-	0.1758	18M3W7D	-	0.1476

LTE Band 2		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1850.7 ~ 1909.3	1M09W7D	-	0.1202
3	1851.5 ~ 1908.5	2M72W7D	-	0.1208
5	1852.5 ~ 1907.5	4M49W7D	-	0.1222
10	1855.0 ~ 1905.0	9M05W7D	-	0.1219
15	1857.5 ~ 1902.5	13M5W7D	-	0.1245
20	1860.0 ~ 1900.0	18M2W7D	-	0.1208

LTE Band 4		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1754.3	1M10G7D	-	0.2466	1M09W7D	-	0.2051
3	1711.5 ~ 1753.5	2M72G7D	-	0.2466	2M73W7D	-	0.2070
5	1712.5 ~ 1752.5	4M52G7D	-	0.2489	4M50W7D	-	0.2113
10	1715.0 ~ 1750.0	9M07G7D	0.0023	0.2455	9M01W7D	-	0.2123
15	1717.5 ~ 1747.5	13M5G7D	-	0.2541	13M4W7D	-	0.2153
20	1720.0 ~ 1745.0	18M3G7D	-	0.2547	18M5W7D	-	0.2148

LTE Band 4		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1754.3	1M09W7D	-	0.1972
3	1711.5 ~ 1753.5	2M73W7D	-	0.1694
5	1712.5 ~ 1752.5	4M51W7D	-	0.1698
10	1715.0 ~ 1750.0	9M07W7D	-	0.1718
15	1717.5 ~ 1747.5	13M5W7D	-	0.1746
20	1720.0 ~ 1745.0	18M3W7D	-	0.1742

LTE Band 5		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	824.7 ~ 848.3	1M10G7D	-	0.0650	1M09W7D		0.0553
3	825.5 ~ 847.5	2M72G7D	-	0.0647	2M75W7D		0.0561
5	826.5 ~ 846.5	4M49G7D	-	0.0641	4M50W7D		0.0547
10	829.0 ~ 844.0	9M07G7D	0.0107	0.0653	9M03W7D		0.0558

LTE Band 5		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	824.7 ~ 848.3	1M09W7D	-	0.0448
3	825.5 ~ 847.5	2M73W7D	-	0.0451
5	826.5 ~ 846.5	4M50W7D	-	0.0446
10	829.0 ~ 844.0	9M03W7D	-	0.0451

LTE Band 7		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M52G7D	-	0.2455	4M50W7D	-	0.2104
10	2505.0 ~ 2565.0	9M05G7D	0.0034	0.2449	9M03W7D	-	0.2080
15	2507.5 ~ 2562.5	13M4G7D	-	0.2495	13M5W7D	-	0.2143
20	2510.0 ~ 2560.0	18M3G7D	-	0.2535	18M3W7D	-	0.2173

LTE Band 7		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	2502.5 ~ 2567.5	4M52W7D	-	0.1600
10	2505.0 ~ 2565.0	9M07W7D	-	0.1596
15	2507.5 ~ 2562.5	13M5W7D	-	0.1660
20	2510.0 ~ 2560.0	18M3W7D	-	0.1766

LTE Band 12		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	699.7 ~ 715.3	1M10G7D	-	0.0621	1M09W7D	-	0.0533
3	700.5 ~ 714.5	2M72G7D	-	0.0618	2M73W7D	-	0.0532
5	701.5 ~ 713.5	4M50G7D	-	0.0625	4M52W7D	-	0.0542
10	704.0 ~ 711.0	9M07G7D	0.0092	0.0627	9M07W7D	-	0.0541

LTE Band 12		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
1.4	699.7 ~ 715.3	1M09W7D	-	0.0431
3	700.5 ~ 714.5	2M73W7D	-	0.0433
5	701.5 ~ 713.5	4M51W7D	-	0.0438
10	704.0 ~ 711.0	9M01W7D	-	0.0438

LTE Band 13		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	779.5 ~ 784.5	4M51G7D	-	0.0617	4M51W7D	-	0.0541
10	782.0	8M97G7D	0.0063	0.0617	9M01W7D	-	0.0537

LTE Band 13		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5	779.5 ~ 784.5	4M50W7D	-	0.0436
10	782.0	8M99W7D	-	0.0435

LTE Band 66		QPSK			16QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1779.3	1M10G7D	-	0.2466	1M09W7D	-	0.2051
3	1711.5 ~ 1778.5	2M72G7D	-	0.2466	2M73W7D	-	0.2070
5	1712.5 ~ 1777.5	4M52G7D	-	0.2489	4M50W7D	-	0.2113
10	1715.0 ~ 1775.0	9M07G7D	0.0023	0.2455	9M01W7D	-	0.2123
15	1717.5 ~ 1772.5	13M5G7D	-	0.2541	13M4W7D	-	0.2153
20	1720.0 ~ 1770.0	18M3G7D	-	0.2547	18M5W7D	-	0.2148

LTE Band 66		64QAM		
BW (MHz)	Frequency Range (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1710.7 ~ 1779.3	1M09W7D	-	0.1972
3	1711.5 ~ 1778.5	2M73W7D	-	0.1694
5	1712.5 ~ 1777.5	4M51W7D	-	0.1698
10	1715.0 ~ 1775.0	9M07W7D	-	0.1718
15	1717.5 ~ 1772.5	13M5W7D	-	0.1746
20	1720.0 ~ 1770.0	18M3W7D	-	0.1742

LTE Band 5B_CA	QPSK			16QAM		
BW (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5MHz+10MHz	14M6G7D	-	0.0614	14M4W7D	-	0.0542
10MHz+5MHz	14M5G7D	-	0.0685	14M5W7D	-	0.0601
10MHz+10MHz	19M1G7D	-	0.0690	19M2W7D	-	0.0624

LTE Band 5B_CA	64QAM		
BW (MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum ERP(W)
5MHz+10MHz	14M6W7D	-	0.0334
10MHz+5MHz	14M5W7D	-	0.0368
10MHz+10MHz	19M4W7D	-	0.0446

Note:LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4.

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH02-KS	CN5013	630927

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L), 27(M), 27(F) , 27(H)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1	**Brand Name**	Motorola (Salom)	**Model Name**	SC-51
	Power Rating	I/P: 100-240 Vac, 0.6A O/P: 5Vdc,3A or 9Vdc,2A or 12Vdc,1.5A		
AC Adapter 2	**Brand Name**	Motorola (Chenyang)	**Model Name**	SC-51
	Power Rating	I/P: 100-240 Vac, 0.6A O/P: 5Vdc,3A or 9Vdc,2A or 12Vdc,1.5A		
Battery	**Brand Name**	Motorola (Amperex)	**Model Name**	KZ40
	Power Rating	3.8Vdc,3600mAh	Type	Li-ion
USB Cable 1	**Brand Name**	Motorola (Cabletech)	**Model Name**	SC18C49697
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	**Brand Name**	Motorola (Saibao)	**Model Name**	SC18C24367
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 3	**Brand Name**	Motorola (Luxshare)	**Model Name**	SC18C24368
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	2	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	4	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
	5	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	7	-	-	v	v	v	v	v	v	v	v	v	v	v	v	v
	12	v	v	v	v	-	-	v	v	v	v	v	v	v	v	v
	13	-	-	v		-	-	v	v	v	v	v	v	v	v	v
		-	-		v	-	-	v	v	v	v	v	v	-	v	-
	66	v	v	v	v	v	v	v	v	v	v	v	v	v	v	v
Peak-to-Average Ratio	2						v	v	v	v	v		v	v	v	v
	5				v	-	-	v	v	v	v		v	v	v	v
	7	-	-				v	v	v	v	v		v	v	v	v
	12				v	-	-	v	v	v	v		v	v	v	v
	13	-	-		v	-	-	v	v	v	v		v	v	v	v
	66						v	v	v	v	v		v	v	v	v

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
26dB and 99% Bandwidth	2	v	v	v	v	v	v	v	v	v			v	v	v	v
	5	v	v	v	v	-	-	v	v	v			v	v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v	v
	12	v	v	v	v	-	-	v	v	v			v	v	v	v
	13	-	-	v		-	-	v	v	v			v	v	v	v
					v			v	v	v			v		v	
	66	v	v	v	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	2	v	v	v	v	v	v	v	v	v	v		v	v		v
	5	v	v	v	v	-	-	v	v	v	v		v	v		v
	7	-	-	v	v	v	v	v	v	v	v		v	v		v
	12	v	v	v	v	-	-	v	v	v	v		v	v		v
	13	-	-	v		-	-	v	v	v	v		v	v		v
		-	-		v	-	-	v	v	v	v				v	
	66	v	v	v	v	v	v	v	v	v	v		v	v		v

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Conducted Spurious Emission	2	v	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v	-	-	v	v	v	v			v	v	v
	7	-	-	v	v	v	v	v	v	v	v			v	v	v
	12	v	v	v	v	-	-	v	v	v	v			v	v	v
	13	-	-	v		-	-	v	v	v	v			v	v	v
		-	-		v	-	-	v	v	v	v				v	
	66	v	v	v	v	v	v	v	v	v	v			v	v	v
Frequency Stability	2				v			v					v		v	
	5				v	-	-	v					v		v	
	7	-	-		v			v					v		v	
	12				v	-	-	v					v		v	
	13	-	-		v	-	-	v					v		v	
	66				v			v					v		v	

Test Items	Band	Bandwidth (MHz)						Modulation			RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
E.R.P / E.I.R.P	2	v	v	v	v	v	v	v	v	v	v			v	v	v
	5	v	v	v	v	-	-	v	v	v	v			v	v	v
	7	-	-	v	v	v	v	v	v	v	v			v	v	v
	12	v	v	v	v	-	-	v	v	v	v			v	v	v
	13	-	-	v		-	-	v	v	v	v			v	v	v
		-	-		v	-	-	v	v	v	v				v	
	66	v	v	v	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	2	Worst Case													v	
	5	Worst Case													v	
	7	Worst Case													v	
	12	Worst Case													v	
	13	Worst Case													v	
	66	Worst Case													v	
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. 4. LTE Band 66 overlaps the entire frequency range of LTE Band 4. Therefore, the test results provided in this report covers Band 66 as well as Band 4.															

Test Items	Band	Bandwidth (MHz)			Modulation			RB #			Test Channel		
		10+10	10+5	5+10	QPSK	16QAM	64QAM	1	Half	Full	L	M	H
Max. Output Power	5B_CA	v	v	v	v	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	5B_CA	v	v	v	v	v	v			v	v	v	v
Conducted Band Edge	5B_CA	v	v	v	v	v	v	v		v	v		v
Conducted Spurious Emission	5B_CA	v	v	v	v	v	v	v			v	v	v
E.R.P.	5B_CA	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	5B_CA	Worst Case									-	v	-
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.												

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8m
3.	Earphone	Moto	EM023	N/A	Unshielded,1.2m	N/A

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.3 dB.

Example :

Offset(dB) = RF cable loss(dB)

= 5.3 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 4 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20050	20175	20300
	Frequency	1720	1732.5	1745
15	Channel	20025	20175	20325
	Frequency	1717.5	1732.5	1747.5
10	Channel	20000	20175	20350
	Frequency	1715	1732.5	1750
5	Channel	19975	20175	20375
	Frequency	1712.5	1732.5	1752.5
3	Channel	19965	20175	20385
	Frequency	1711.5	1732.5	1753.5
1.4	Channel	19957	20175	20393
	Frequency	1710.7	1732.5	1754.3

LTE Band 5 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
10	Channel	20450	20525	20600
	Frequency	829	836.5	844
5	Channel	20425	20525	20625
	Frequency	826.5	836.5	846.5
3	Channel	20415	20525	20635
	Frequency	825.5	836.5	847.5
1.4	Channel	20407	20525	20643
	Frequency	824.7	836.5	848.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 12 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	23060	23095	23130
	Frequency	704	707.5	711
5	Channel	23035	23095	23155
	Frequency	701.5	707.5	713.5
3	Channel	23025	23095	23165
	Frequency	700.5	707.5	714.5
1.4	Channel	23017	23095	23173
	Frequency	699.7	707.5	715.3

LTE Band 13 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
10	Channel	-	23230	-
	Frequency	-	782	-
5	Channel	23205	23230	23255
	Frequency	779.5	782	784.5

LTE Band 66 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	132072	132322	132572
	Frequency	1720	1745	1770
15	Channel	132047	132322	132597
	Frequency	1717.5	1745	1772.5
10	Channel	132022	132322	132622
	Frequency	1715	1745	1775
5	Channel	131997	132322	132647
	Frequency	1712.5	1745	1777.5
3	Channel	131987	132322	132657
	Frequency	1711.5	1745	1778.5
1.4	Channel	131979	132322	132665
	Frequency	1710.7	1745	1779.3

LTE Band 5B_CA Channel and Frequency List					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
5 + 10	PCC	Channel	20428	20478	20528
		Frequency	826.8	831.8	836.8
	SCC	Channel	20500	20550	20600
		Frequency	834	839	844
10 + 5	PCC	Channel	20450	20500	20550
		Frequency	829	834	839
	SCC	Channel	20522	20572	20622
		Frequency	836.2	841.2	846.2
10 + 10	PCC	Channel	20450	20476	20501
		Frequency	829	831.6	834.1
	SCC	Channel	20549	20575	20600
		Frequency	838.9	841.5	844

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power Measurement and ERP/EIRP Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for LTE Band 5.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 12, Band 13.

The EIRP of mobile transmitters must not exceed 2 Watts for LTE Band 2 and Band 7.

The EIRP of mobile transmitters must not exceed 1 Watts for LTE Band 4 and Band 66.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

22.917(a)

For operations in the 824 – 849 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 100kHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

24.238 (a)

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53 (c)

For operations in the 776-788 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kHz bands immediately outside and adjacent to the frequency block, a resolution bandwidth of at least 30 kHz may be employed. In addition, the power of any unwanted emissions in any 6.25 kHz bandwidth for all frequencies between 763-775 MHz and 793-806 MHz shall be attenuated below the transmitter power, P (dBW), by at least 65 + 10 log10 p(watts), dB, for mobile and portable equipment.

27.53 (g)

For operations in the 600MHz band and 698 -746 MHz band, the FCC limit is 43 + 10log10(P[Watts]) dB below the transmitter power P(Watts) in a 100 kHz bandwidth. However, in the 100 kilohertz bands immediately outside and adjacent to a licensee's frequency block, a resolution bandwidth of at least 30 kHz may be employed.

27.53 (h)

For operations in the 1710 – 1755 MHz band, the FCC limit is 43 + $10\log_{10}$(P[Watts]) dB below the transmitter power P(Watts) in a 1 MHz bandwidth. However, in the 1MHz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4)

For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW >= 1% EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.
9. For LTE Band 7, the other 40 dB, and 55 dB have additionally applied same calculation above.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 7:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.
11. For Band 7
    The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [55+ 10log(P)] (dB)
    = [30+ 10log(P)] (dBm) - [55+ 10log(P)] (dB)
    = -25dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For Band 7

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 55 + 10 log (P) dB.

For LTE Band 13

For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.
13. For Band 7:
    The limit line is derived from 55 + 10log(P)dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	100319	10Hz~40GHz	Oct. 11, 2018	Jan. 20, 2019~ Feb. 26, 2019	Oct. 10, 2019	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jun. 27, 2018	Jan. 20, 2019~ Feb. 26, 2019	Jun. 26, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr. 17, 2018	Jan. 30, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Dec. 29, 2018	Jan. 30, 2019	Dec. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Jan. 30, 2019	Jan. 26, 2020	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	100MHz-18GHz	Apr. 17, 2018	Jan. 30, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Jan. 30, 2019	Jan. 04, 2020	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2018	Jan. 30, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 18, 2018	Jan. 30, 2019	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35 -HG	1887435	18~40GHz	Jan. 14, 2019	Jan. 30, 2019	Jan. 13, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Jan. 30, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jan. 30, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jan. 30, 2019	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3 dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8 dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.30	23.31	23.45
20	1	49		23.00	23.11	23.25
20	1	99		23.11	23.24	23.22
20	50	0		22.19	22.30	22.40
20	50	24		22.14	22.21	22.37
20	50	50		22.09	22.13	22.30
20	100	0		22.11	22.26	22.30
20	1	0	16-QAM	22.67	22.62	22.69
20	1	49		22.38	22.47	22.61
20	1	99		22.41	22.59	22.65
20	50	0		21.33	21.41	21.40
20	50	24		21.20	21.33	21.47
20	50	50		21.15	21.28	21.42
20	100	0		21.23	21.29	21.37
20	1	0	64-QAM	21.78	21.74	21.82
20	1	49		21.50	21.54	21.72
20	1	99		21.54	21.69	21.74
20	50	0		20.49	20.59	20.58
20	50	24		20.40	20.51	20.64
20	50	50		20.40	20.44	20.60
20	100	0		20.51	20.53	20.58
15	1	0	QPSK	23.12	23.28	23.33
15	1	37		22.94	23.12	23.35
15	1	74		22.97	23.12	23.38
15	36	0		22.07	22.28	22.48
15	36	20		22.13	22.21	22.46
15	36	39		22.08	22.16	22.41
15	75	0		22.14	22.25	22.44

15	1	0		22.50	22.60	22.84
15	1	37		22.30	22.47	22.72
15	1	74		22.35	22.54	22.77
15	36	0	**16-QAM**	21.18	21.36	21.57
15	36	20		21.26	21.34	21.53
15	36	39		21.13	21.30	21.54
15	75	0		21.23	21.30	21.56
15	1	0		21.61	21.69	21.95
15	1	37		21.39	21.52	21.82
15	1	74		21.43	21.59	21.89
15	36	0	**64-QAM**	20.39	20.57	20.78
15	36	20		20.45	20.54	20.72
15	36	39		20.33	20.50	20.71
15	75	0		20.45	20.50	20.74

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.24	23.40	23.44
10	1	25		22.95	23.13	23.34
10	1	49		23.20	23.32	23.29
10	25	0		22.04	22.25	22.41
10	25	12		22.03	22.20	22.40
10	25	25		22.06	22.16	22.36
10	50	0		22.11	22.20	22.40
10	1	0	16-QAM	22.59	22.74	22.75
10	1	25		22.29	22.47	22.70
10	1	49		22.60	22.66	22.76
10	25	0		21.16	21.33	21.55
10	25	12		21.13	21.32	21.54
10	25	25		21.16	21.28	21.48
10	50	0		21.22	21.33	21.53
10	1	0	64-QAM	21.69	21.83	21.86
10	1	25		21.39	21.56	21.78
10	1	49		21.68	21.78	21.79
10	25	0		20.34	20.52	20.75
10	25	12		20.30	20.49	20.74
10	25	25		20.38	20.50	20.66
10	50	0		20.43	20.51	20.71
5	1	0	QPSK	23.06	23.19	23.35
5	1	12		22.95	23.11	23.33
5	1	24		22.98	23.13	23.32
5	12	0		22.03	22.21	22.38
5	12	7		22.01	22.24	22.41
5	12	13		21.97	22.20	22.38
5	25	0		21.97	22.15	22.36
5	1	0	16-QAM	22.42	22.51	22.77
5	1	12		22.34	22.47	22.74
5	1	24		22.33	22.48	22.70
5	12	0		21.16	21.29	21.55
5	12	7		21.14	21.30	21.52

5	12	13		21.09	21.27	21.49
5	25	0		21.10	21.24	21.49
5	1	0		21.45	21.62	21.87
5	1	12		21.47	21.50	21.81
5	1	24		21.50	21.57	21.81
5	12	0	**64-QAM**	20.36	20.48	20.71
5	12	7		20.49	20.47	20.72
5	12	13		20.34	20.45	20.67
5	25	0		20.45	20.46	20.69

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.00	23.19	23.27
3	1	8		22.97	23.10	23.31
3	1	14		22.92	23.11	23.28
3	8	0		21.99	22.20	22.36
3	8	4		22.02	22.18	22.40
3	8	7		21.97	22.16	22.37
3	15	0		22.01	22.19	22.35
3	1	0	16-QAM	22.33	22.47	22.76
3	1	8		22.34	22.51	22.71
3	1	14		22.31	22.45	22.73
3	8	0		21.17	21.30	21.56
3	8	4		21.20	21.31	21.60
3	8	7		21.14	21.26	21.56
3	15	0		21.08	21.26	21.49
3	1	0	64-QAM	21.44	21.58	21.80
3	1	8		21.39	21.50	21.81
3	1	14		21.39	21.59	21.82
3	8	0		20.32	20.48	20.73
3	8	4		20.36	20.47	20.73
3	8	7		20.30	20.43	20.74
3	15	0		20.27	20.46	20.66
1.4	1	0	QPSK	22.90	23.04	23.24
1.4	1	3		22.95	23.13	23.32
1.4	1	5		22.87	23.07	23.21
1.4	3	0		22.93	23.12	23.27
1.4	3	1		22.95	23.11	23.30
1.4	3	3		22.97	23.07	23.30
1.4	6	0		21.93	22.12	22.29
1.4	1	0	16-QAM	22.26	22.35	22.65
1.4	1	3		22.31	22.42	22.76
1.4	1	5		22.24	22.33	22.65
1.4	3	0		22.05	22.17	22.42
1.4	3	1		22.11	22.24	22.48

1.4	3	3		22.05	22.19	22.40
1.4	6	0		21.08	21.29	21.48
1.4	1	0	64-QAM	21.34	21.48	21.70
1.4	1	3		21.40	21.58	21.80
1.4	1	5		21.35	21.47	21.71
1.4	3	0		21.29	21.43	21.65
1.4	3	1		21.31	21.46	21.67
1.4	3	3		21.23	21.39	21.64
1.4	6	0		20.24	20.38	20.61

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.01	22.96	22.85
20	1	49		22.78	22.69	22.72
20	1	99		22.65	22.64	22.72
20	50	0		21.95	21.82	21.80
20	50	24		21.87	21.75	21.73
20	50	50		21.73	21.71	21.80
20	100	0		21.86	21.74	21.75
20	1	0	16-QAM	22.32	22.31	22.27
20	1	49		22.10	22.08	22.06
20	1	99		22.00	21.98	21.93
20	50	0		21.01	20.93	20.89
20	50	24		20.98	20.84	20.82
20	50	50		20.81	20.80	20.89
20	100	0		20.93	20.82	20.84
20	1	0	64-QAM	21.41	21.41	21.32
20	1	49		21.19	21.15	21.15
20	1	99		21.11	21.07	21.04
20	50	0		20.22	20.11	20.08
20	50	24		20.16	20.01	20.01
20	50	50		19.99	19.97	20.03
20	100	0		20.16	20.03	20.04
15	1	0	QPSK	23.00	22.94	22.81
15	1	37		22.77	22.66	22.71
15	1	74		22.78	22.67	22.74
15	36	0		21.90	21.77	21.77
15	36	20		21.84	21.70	21.81
15	36	39		21.81	21.73	21.76
15	75	0		21.83	21.70	21.74
15	1	0	16-QAM	22.27	22.34	22.11
15	1	37		22.02	22.05	21.98
15	1	74		22.13	22.01	21.97
15	36	0		20.95	20.85	20.86
15	36	20		20.89	20.83	20.91

15	36	39		20.87	20.81	20.78
15	75	0		20.93	20.80	20.80
15	1	0	64-QAM	21.40	21.42	21.30
15	1	37		21.11	21.14	21.09
15	1	74		21.21	21.12	21.08
15	36	0		20.15	20.04	20.07
15	36	20		20.08	20.02	20.10
15	36	39		20.06	20.01	20.01
15	75	0		20.13	20.00	19.99

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.94	22.73	22.83
10	1	25		22.87	22.64	22.73
10	1	49		22.72	22.61	22.74
10	25	0		21.95	21.73	21.83
10	25	12		21.82	21.71	21.82
10	25	25		21.79	21.67	21.78
10	50	0		21.83	21.68	21.81
10	1	0	16-QAM	22.22	22.11	22.06
10	1	25		22.17	22.07	21.99
10	1	49		22.07	22.02	21.92
10	25	0		21.02	20.83	20.89
10	25	12		20.91	20.81	20.87
10	25	25		20.90	20.78	20.83
10	50	0		20.89	20.78	20.86
10	1	0	64-QAM	21.33	21.18	21.19
10	1	25		21.24	21.10	21.09
10	1	49		21.18	21.08	21.06
10	25	0		20.22	20.02	20.10
10	25	12		20.11	20.00	20.09
10	25	25		20.09	19.95	20.01
10	50	0		20.09	19.97	20.05
5	1	0	QPSK	22.87	22.66	22.73
5	1	12		22.87	22.61	22.68
5	1	24		22.83	22.60	22.68
5	12	0		21.90	21.69	21.76
5	12	7		21.89	21.71	21.75
5	12	13		21.88	21.66	21.74
5	25	0		21.89	21.66	21.75
5	1	0	16-QAM	22.09	22.04	21.96
5	1	12		22.08	21.94	21.89
5	1	24		22.11	21.93	21.88
5	12	0		20.95	20.78	20.81
5	12	7		20.94	20.78	20.81

5	12	13		20.91	20.76	20.76
5	25	0		20.95	20.76	20.81
5	1	0	64-QAM	21.21	21.15	21.12
5	1	12		21.17	21.07	21.03
5	1	24		21.23	21.04	21.03
5	12	0		20.14	19.95	20.01
5	12	7		20.12	19.96	19.98
5	12	13		20.12	19.96	19.98
5	25	0		20.15	19.94	19.98

LTE Band 4 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.82	22.60	22.70
3	1	8		22.79	22.56	22.68
3	1	14		22.80	22.57	22.70
3	8	0		21.85	21.63	21.74
3	8	4		21.89	21.65	21.73
3	8	7		21.86	21.59	21.72
3	15	0		21.87	21.63	21.74
3	1	0	16-QAM	22.08	21.97	21.96
3	1	8		22.10	21.98	21.88
3	1	14		22.05	21.90	21.86
3	8	0		20.98	20.81	20.79
3	8	4		20.96	20.77	20.84
3	8	7		20.92	20.78	20.76
3	15	0		20.94	20.74	20.79
3	1	0	64-QAM	21.19	21.06	20.99
3	1	8		21.16	21.05	20.98
3	1	14		21.17	21.05	20.98
3	8	0		20.10	19.97	19.96
3	8	4		20.11	19.92	19.99
3	8	7		20.07	19.91	19.94
3	15	0		20.11	19.92	19.96
1.4	1	0	QPSK	22.77	22.50	22.61
1.4	1	3		22.83	22.55	22.70
1.4	1	5		22.70	22.48	22.60
1.4	3	0		22.48	22.56	22.66
1.4	3	1		22.83	22.60	22.70
1.4	3	3		22.79	22.55	22.65
1.4	6	0		21.79	21.55	21.67
1.4	1	0	16-QAM	21.99	21.87	21.81
1.4	1	3		22.05	21.98	21.88
1.4	1	5		21.94	21.89	21.77
1.4	3	0		21.79	21.64	21.65
1.4	3	1		21.84	21.71	21.70

1.4	3	3		21.77	21.66	21.64
1.4	6	0		20.90	20.72	20.76
1.4	1	0	64-QAM	21.09	21.00	20.94
1.4	1	3		21.14	21.03	21.01
1.4	1	5		21.06	20.95	20.90
1.4	3	0		21.04	20.86	20.86
1.4	3	1		21.08	20.93	20.93
1.4	3	3		21.03	20.88	20.88
1.4	6	0		20.05	19.84	19.89

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.17	23.10	23.19
10	1	25		23.22	23.15	23.15
10	1	49		23.30	23.02	23.07
10	25	0		22.29	22.22	22.22
10	25	12		22.30	22.18	22.18
10	25	25		22.33	22.13	22.18
10	50	0		22.27	22.21	22.18
10	1	0	16-QAM	22.51	22.50	22.53
10	1	25		22.56	22.43	22.47
10	1	49		22.62	22.32	22.50
10	25	0		21.37	21.31	21.29
10	25	12		21.37	21.29	21.28
10	25	25		21.40	21.21	21.28
10	50	0		21.39	21.28	21.26
10	1	0	64-QAM	21.62	21.58	21.61
10	1	25		21.62	21.57	21.57
10	1	49		21.69	21.45	21.58
10	25	0		20.55	20.46	20.49
10	25	12		20.57	20.49	20.47
10	25	25		20.60	20.39	20.47
10	50	0		20.53	20.48	20.44
5	1	0	QPSK	23.18	23.17	23.16
5	1	12		23.13	23.12	23.10
5	1	24		23.22	23.10	23.07
5	12	0		22.21	22.17	22.17
5	12	7		22.32	22.17	22.17
5	12	13		22.31	22.12	22.12
5	25	0		22.31	22.18	22.13
5	1	0	16-QAM	22.53	22.52	22.48
5	1	12		22.41	22.41	22.48
5	1	24		22.51	22.41	22.47
5	12	0		21.26	21.28	21.25
5	12	7		21.38	21.29	21.26

5	12	13		21.38	21.23	21.25
5	25	0		21.38	21.23	21.25
5	1	0	64-QAM	21.64	21.58	21.55
5	1	12		21.54	21.52	21.61
5	1	24		21.62	21.49	21.55
5	12	0		20.46	20.47	20.43
5	12	7		20.57	20.47	20.46
5	12	13		20.55	20.41	20.42
5	25	0		20.56	20.42	20.44

LTE Band 5 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.26	23.23	23.22
3	1	8		23.18	23.19	23.15
3	1	14		23.22	23.19	23.18
3	8	0		22.28	22.27	22.23
3	8	4		22.28	22.25	22.23
3	8	7		22.25	22.21	22.19
3	15	0		22.29	22.24	22.22
3	1	0	16-QAM	22.64	22.60	22.62
3	1	8		22.58	22.52	22.62
3	1	14		22.51	22.49	22.59
3	8	0		21.41	21.39	21.40
3	8	4		21.39	21.38	21.41
3	8	7		21.36	21.35	21.38
3	15	0		21.38	21.36	21.33
3	1	0	64-QAM	21.69	21.65	21.65
3	1	8		21.62	21.61	21.65
3	1	14		21.62	21.60	21.67
3	8	0		20.58	20.55	20.55
3	8	4		20.60	20.55	20.60
3	8	7		20.55	20.53	20.55
3	15	0		20.56	20.52	20.52
1.4	1	0	QPSK	23.18	23.13	23.11
1.4	1	3		23.24	23.20	23.17
1.4	1	5		23.15	23.12	23.09
1.4	3	0		23.23	23.17	23.16
1.4	3	1		23.28	23.24	23.16
1.4	3	3		23.23	23.17	23.15
1.4	6	0		22.19	22.17	22.12
1.4	1	0	16-QAM	22.55	22.44	22.51
1.4	1	3		22.57	22.52	22.58
1.4	1	5		22.47	22.40	22.48
1.4	3	0		22.32	22.27	22.29
1.4	3	1		22.32	22.32	22.31

1.4	3	3		22.28	22.23	22.29
1.4	6	0		21.37	21.32	21.33
1.4	1	0	64-QAM	21.61	21.55	21.57
1.4	1	3		21.63	21.58	21.66
1.4	1	5		21.55	21.49	21.56
1.4	3	0		21.54	21.48	21.53
1.4	3	1		21.60	21.52	21.57
1.4	3	3		21.51	21.47	21.53
1.4	6	0		20.48	20.43	20.45

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.04	22.77	22.92
20	1	49		22.97	22.70	22.84
20	1	99		22.92	22.72	22.98
20	50	0		22.05	21.79	21.93
20	50	24		22.03	21.78	21.94
20	50	50		21.97	21.74	21.90
20	100	0		21.94	21.76	21.92
20	1	0	16-QAM	22.37	22.16	22.34
20	1	49		22.30	22.05	22.22
20	1	99		22.26	22.15	22.35
20	50	0		21.13	20.87	20.98
20	50	24		21.14	20.88	20.99
20	50	50		21.03	20.83	21.01
20	100	0		21.00	20.85	21.00
20	1	0	64-QAM	21.45	21.22	21.36
20	1	49		21.39	21.15	21.31
20	1	99		21.36	21.24	21.47
20	50	0		20.29	20.06	20.19
20	50	24		20.33	20.05	20.18
20	50	50		20.20	20.01	20.19
20	100	0		20.23	20.05	20.21
15	1	0	QPSK	22.95	22.97	22.90
15	1	37		22.93	22.80	22.86
15	1	74		22.93	22.83	22.85
15	36	0		21.95	21.83	21.87
15	36	20		21.97	21.87	21.90
15	36	39		21.93	21.84	21.84
15	75	0		21.93	21.81	21.86
15	1	0	16-QAM	22.31	22.23	22.28
15	1	37		22.26	22.10	22.23
15	1	74		22.30	22.13	22.18
15	36	0		21.07	20.96	21.00
15	36	20		21.05	20.93	21.03

15	36	39		21.03	20.92	20.98
15	75	0		21.05	20.94	20.95
15	1	0	64-QAM	21.20	21.18	21.17
15	1	37		21.14	21.02	21.09
15	1	74		21.17	21.05	21.07
15	36	0		20.05	19.96	19.98
15	36	20		20.07	19.96	20.00
15	36	39		20.03	19.91	19.96
15	75	0		20.03	19.91	19.96

LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.89	22.81	22.87
10	1	25		22.87	22.80	22.81
10	1	49		22.88	22.80	22.84
10	25	0		21.76	21.82	21.84
10	25	12		21.93	21.81	21.87
10	25	25		21.92	21.83	21.82
10	50	0		21.93	21.80	21.85
10	1	0	16-QAM	22.17	22.14	22.16
10	1	25		22.18	22.17	22.15
10	1	49		22.13	22.09	22.08
10	25	0		21.06	20.96	20.98
10	25	12		21.06	20.99	21.01
10	25	25		21.02	20.94	20.98
10	50	0		21.03	20.91	20.94
10	1	0	64-QAM	21.00	20.90	20.99
10	1	25		21.01	20.90	21.00
10	1	49		21.03	20.89	20.93
10	25	0		19.89	19.83	19.86
10	25	12		19.93	19.85	19.88
10	25	25		19.91	19.80	19.85
10	50	0		19.91	19.78	19.83
5	1	0	QPSK	22.80	22.64	22.83
5	1	12		22.87	22.80	22.86
5	1	24		22.78	22.73	22.82
5	12	0		22.83	22.74	22.82
5	12	7		22.90	22.81	22.88
5	12	13		22.85	22.76	22.85
5	25	0		21.84	21.76	21.83
5	1	0	16-QAM	22.14	22.07	22.14
5	1	12		22.23	22.15	22.20
5	1	24		22.13	22.07	22.08
5	12	0		21.93	21.85	21.90
5	12	7		21.99	21.89	21.96

5	12	13		21.93	21.83	21.88
5	25	0		21.00	21.03	21.05
5	1	0	64-QAM	20.93	20.82	20.94
5	1	12		20.98	20.90	21.04
5	1	24		20.94	20.80	20.91
5	12	0		20.87	20.80	20.85
5	12	7		20.87	20.85	20.88
5	12	13		20.84	20.78	20.82
5	25	0		19.83	19.73	19.79

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	23.12	22.98	23.03
10	1	25		23.11	23.03	23.00
10	1	49		23.05	23.01	23.08
10	25	0		22.21	22.13	22.12
10	25	12		22.18	22.13	22.12
10	25	25		22.17	22.08	22.11
10	50	0		22.21	22.15	22.10
10	1	0	16-QAM	22.43	22.34	22.41
10	1	25		22.48	22.42	22.35
10	1	49		22.45	22.31	22.33
10	25	0		21.28	21.24	21.22
10	25	12		21.33	21.27	21.21
10	25	25		21.25	21.22	21.15
10	50	0		21.28	21.20	21.21
10	1	0	64-QAM	21.49	21.44	21.54
10	1	25		21.56	21.52	21.47
10	1	49		21.56	21.44	21.44
10	25	0		20.48	20.43	20.39
10	25	12		20.52	20.47	20.39
10	25	25		20.44	20.42	20.34
10	50	0		20.46	20.39	20.39
5	1	0	QPSK	23.06	23.06	22.98
5	1	12		23.01	23.02	23.06
5	1	24		23.11	23.01	23.06
5	12	0		22.10	22.14	22.06
5	12	7		22.13	22.16	22.16
5	12	13		22.09	22.12	22.14
5	25	0		22.21	22.08	22.05
5	1	0	16-QAM	22.39	22.42	22.33
5	1	12		22.41	22.41	22.39
5	1	24		22.49	22.41	22.34
5	12	0		21.22	21.21	21.14
5	12	7		21.23	21.26	21.27

5	12	13		21.22	21.23	21.20
5	25	0		21.29	21.23	21.12
5	1	0	64-QAM	21.48	21.56	21.43
5	1	12		21.48	21.53	21.50
5	1	24		21.50	21.52	21.46
5	12	0		20.41	20.39	20.28
5	12	7		20.40	20.43	20.43
5	12	13		20.40	20.41	20.37
5	25	0		20.49	20.41	20.30

LTE Band 12 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	23.06	23.01	23.04
3	1	8		23.02	23.02	23.02
3	1	14		23.01	23.02	23.03
3	8	0		22.11	22.08	22.09
3	8	4		22.13	22.12	22.13
3	8	7		22.08	22.09	22.10
3	15	0		22.10	22.08	22.12
3	1	0	16-QAM	22.33	22.41	22.39
3	1	8		22.39	22.39	22.34
3	1	14		22.39	22.38	22.30
3	8	0		21.27	21.25	21.22
3	8	4		21.26	21.27	21.23
3	8	7		21.24	21.23	21.21
3	15	0		21.22	21.20	21.19
3	1	0	64-QAM	21.45	21.47	21.44
3	1	8		21.47	21.51	21.41
3	1	14		21.48	21.48	21.41
3	8	0		20.39	20.42	20.36
3	8	4		20.45	20.43	20.38
3	8	7		20.41	20.39	20.35
3	15	0		20.39	20.39	20.37
1.4	1	0	QPSK	22.95	22.91	22.93
1.4	1	3		23.05	23.02	23.01
1.4	1	5		22.94	22.93	22.96
1.4	3	0		23.03	23.02	22.99
1.4	3	1		23.08	23.01	23.05
1.4	3	3		23.05	23.03	23.02
1.4	6	0		22.04	22.00	22.02
1.4	1	0	16-QAM	22.27	22.39	22.22
1.4	1	3		22.42	22.42	22.30
1.4	1	5		22.30	22.35	22.22
1.4	3	0		22.08	22.05	22.04
1.4	3	1		22.12	22.13	22.06

1.4	3	3		22.13	22.06	22.02
1.4	6	0		21.22	21.20	21.17
1.4	1	0	64-QAM	21.43	21.39	21.31
1.4	1	3		21.49	21.49	21.38
1.4	1	5		21.35	21.39	21.32
1.4	3	0		21.32	21.30	21.28
1.4	3	1		21.38	21.37	21.33
1.4	3	3		21.37	21.32	21.25
1.4	6	0		20.35	20.31	20.30

LTE Band 13 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK		23.05	
10	1	25			23.00	
10	1	49			23.01	
10	25	0			22.10	
10	25	12			22.09	
10	25	25			22.05	
10	50	0			22.04	
10	1	0	16-QAM		22.34	
10	1	25			22.34	
10	1	49			22.45	
10	25	0			21.18	
10	25	12			21.15	
10	25	25			21.09	
10	50	0			21.13	
10	1	0	64-QAM		21.44	
10	1	25			21.42	
10	1	49			21.53	
10	25	0			20.37	
10	25	12			20.33	
10	25	25			20.30	
10	50	0			20.32	
5	1	0	QPSK	22.96	23.05	22.98
5	1	12		22.92	22.99	23.03
5	1	24		22.99	22.98	23.00
5	12	0		22.00	22.06	21.99
5	12	7		22.13	22.03	22.03
5	12	13		22.11	22.03	22.07
5	25	0		22.06	22.04	22.02
5	1	0	16-QAM	22.32	22.48	22.32
5	1	12		22.33	22.31	22.41
5	1	24		22.33	22.30	22.45
5	12	0		21.14	21.18	21.11
5	12	7		21.24	21.17	21.10

5	12	13		21.20	21.09	21.22
5	25	0		21.19	21.10	21.09
5	1	0	64-QAM	21.46	21.52	21.41
5	1	12		21.43	21.42	21.52
5	1	24		21.42	21.40	21.54
5	12	0		20.30	20.38	20.44
5	12	7		20.40	20.35	20.38
5	12	13		20.39	20.27	20.38
5	25	0		20.38	20.29	20.26

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	23.06	22.94	22.99
20	1	49		22.74	22.72	22.75
20	1	99		22.72	22.70	22.74
20	50	0		22.04	21.93	21.59
20	50	24		21.96	21.86	21.92
20	50	50		21.87	21.78	21.85
20	100	0		21.95	21.87	21.92
20	1	0	16-QAM	22.28	22.32	22.17
20	1	49		22.13	22.01	22.01
20	1	99		22.19	21.93	22.01
20	50	0		21.07	21.02	21.02
20	50	24		21.02	20.93	20.95
20	50	50		20.95	20.89	20.90
20	100	0		21.02	20.92	20.96
20	1	0	64-QAM	21.39	21.41	21.31
20	1	49		21.29	21.11	21.14
20	1	99		21.28	21.04	21.15
20	50	0		20.24	20.20	20.22
20	50	24		20.18	20.12	20.13
20	50	50		20.16	20.05	20.08
20	100	0		20.23	20.14	20.15
15	1	0	QPSK	23.05	22.97	22.96
15	1	37		22.86	22.73	22.79
15	1	74		22.89	22.76	22.78
15	36	0		22.03	21.90	21.93
15	36	20		21.92	21.85	21.90
15	36	39		21.88	21.81	21.61
15	75	0		21.95	21.86	21.98
15	1	0	16-QAM	22.25	22.33	22.18
15	1	37		22.16	22.01	22.04
15	1	74		22.26	21.99	22.04
15	36	0		21.09	20.98	20.97
15	36	20		21.05	20.94	20.93

15	36	39		21.02	20.85	20.89
15	75	0		21.02	20.92	20.94
15	1	0	64-QAM	21.42	21.39	21.35
15	1	37		21.26	21.21	21.36
15	1	74		21.32	21.39	21.20
15	36	0		20.26	20.12	20.19
15	36	20		20.25	20.12	20.16
15	36	39		20.20	20.07	20.14
15	75	0		20.21	20.14	20.25

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.85	22.87	22.90
10	1	25		22.78	22.80	22.81
10	1	49		22.70	22.72	22.74
10	25	0		22.02	21.91	21.90
10	25	12		21.99	21.86	21.87
10	25	25		21.31	21.85	21.83
10	50	0		21.94	21.88	21.89
10	1	0	16-QAM	22.23	22.18	22.12
10	1	25		22.19	22.08	22.09
10	1	49		22.27	22.00	22.01
10	25	0		21.07	20.94	20.97
10	25	12		21.05	20.94	20.92
10	25	25		21.03	20.91	20.91
10	50	0		21.02	20.91	20.94
10	1	0	64-QAM	21.35	21.27	21.21
10	1	25		21.32	21.19	21.17
10	1	49		21.31	21.10	21.16
10	25	0		20.25	20.14	20.16
10	25	12		20.22	20.14	20.15
10	25	25		20.22	20.10	20.08
10	50	0		20.22	20.12	20.15
5	1	0	QPSK	22.96	22.81	22.84
5	1	12		22.69	22.77	22.78
5	1	24		22.75	22.77	22.77
5	12	0		21.95	21.83	21.85
5	12	7		21.97	21.85	21.87
5	12	13		21.93	21.78	21.83
5	25	0		21.96	21.81	21.83
5	1	0	16-QAM	22.25	22.08	22.12
5	1	12		22.16	22.03	22.06
5	1	24		22.16	21.99	22.00
5	12	0		21.03	20.89	20.90
5	12	7		20.83	20.93	20.94

5	12	13		21.00	20.85	20.91
5	25	0		21.03	20.87	20.89
5	1	0	64-QAM	21.30	21.20	21.22
5	1	12		21.13	21.15	21.17
5	1	24		21.07	21.10	21.18
5	12	0		20.17	20.08	20.09
5	12	7		20.20	20.10	20.10
5	12	13		20.19	20.06	20.07
5	25	0		20.19	20.06	20.08

LTE Band 66 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.92	22.79	22.80
3	1	8		22.89	22.77	22.77
3	1	14		22.87	22.73	22.75
3	8	0		21.94	21.98	21.81
3	8	4		21.95	21.84	21.81
3	8	7		21.88	21.77	21.77
3	15	0		21.93	21.81	21.81
3	1	0	16-QAM	22.16	21.97	22.05
3	1	8		22.13	21.96	22.02
3	1	14		22.13	21.96	22.00
3	8	0		21.04	20.93	20.89
3	8	4		21.05	20.94	20.93
3	8	7		21.01	20.91	20.92
3	15	0		21.02	20.90	20.92
3	1	0	64-QAM	21.29	21.13	21.18
3	1	8		21.28	21.12	21.16
3	1	14		21.23	21.09	21.11
3	8	0		20.15	20.09	20.06
3	8	4		20.09	20.09	20.08
3	8	7		20.07	20.07	20.06
3	15	0		20.06	20.08	20.07
1.4	1	0	QPSK	22.83	22.66	22.70
1.4	1	3		22.90	22.73	22.76
1.4	1	5		22.82	22.66	22.71
1.4	3	0		22.89	22.74	22.74
1.4	3	1		22.92	22.77	22.76
1.4	3	3		22.85	22.75	22.74
1.4	6	0		21.83	21.74	21.74
1.4	1	0	16-QAM	22.03	21.98	22.00
1.4	1	3		22.12	22.03	22.09
1.4	1	5		22.07	21.94	21.97
1.4	3	0		21.88	21.77	21.80
1.4	3	1		21.93	21.79	21.84

1.4	3	3		21.88	21.73	21.77
1.4	6	0		20.96	20.88	20.88
1.4	1	0	64-QAM	21.13	21.07	21.12
1.4	1	3		21.28	21.14	21.15
1.4	1	5		21.19	21.95	21.11
1.4	3	0		21.08	20.99	21.01
1.4	3	1		21.07	21.08	21.09
1.4	3	3		21.13	21.00	21.01
1.4	6	0		20.08	20.03	20.02

CA Power

CA_5B								
Combination 10MHz+10MHz (50RB+50RB)								
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset		
20450	20549	QPSK	0	0	1	49	1	23.38
			1	0	0	0	1	23.5
			50	0	0	0	50	22.55
			50	0	50	0	100	21.54
			1	0	1	49	2	13.02
			1	0	1	0	2	13.03
			1	49	1	0	2	23.54
			50	0	1	49	51	18.56
		16QAM	0	0	1	49	1	22.82
			1	0	0	0	1	22.93
			50	0	0	0	50	21.58
			50	0	50	0	100	20.62
			1	0	1	49	2	13.48
			1	0	1	0	2	13.56
			1	49	1	0	2	23.1
			50	0	1	49	51	18.61
		64QAM	0	0	1	49	1	21.64
			1	0	0	0	1	21.54
			50	0	0	0	50	20.34
			50	0	50	0	100	20.65
			1	0	1	49	2	13.28
			1	0	1	0	2	13.22
			1	49	1	0	2	20.81
			50	0	1	49	51	18.59

20476	20575	QPSK	0	0	1	49	1	22.76
			1	0	0	0	1	23.06
			50	0	0	0	100	22.07
			50	0	50	0	200	21.04
			1	0	1	49	2	12.48
			1	0	1	0	2	12.56
			1	49	1	0	2	22.97
			50	0	1	49	101	18.03
		16QAM	0	0	1	49	1	22.23
			1	0	0	0	1	22.63
			50	0	0	0	100	21.16
			50	0	50	0	200	20.13
			1	0	1	49	2	13.03
			1	0	1	0	2	13.1
			1	49	1	0	2	22.39
			50	0	1	49	101	18.12
		64QAM	0	0	1	49	1	21.2
			1	0	0	0	1	21.42
			50	0	0	0	100	20.15
			50	0	50	0	200	20.11
			1	0	1	49	2	12.79
			1	0	1	0	2	12.87
			1	49	1	0	2	20.26
			50	0	1	49	101	18.08

20501	20600	QPSK	0	0	1	49	1	22.73
			1	0	0	0	1	22.97
			50	0	0	0	100	22.01
			50	0	50	0	200	21.02
			1	0	1	49	2	12.41
			1	0	1	0	2	12.49
			1	49	1	0	2	22.95
			50	0	1	49	101	18.01
		16QAM	0	0	1	49	1	22.13
			1	0	0	0	1	22.6
			50	0	0	0	100	21.1
			50	0	50	0	200	20.07
			1	0	1	49	2	13.01
			1	0	1	0	2	13.04
			1	49	1	0	2	22.45
			50	0	1	49	101	18.11
		64QAM	0	0	1	49	1	21.12
			1	0	0	0	1	21.38
			50	0	0	0	100	20.15
			50	0	50	0	200	20.1
			1	0	1	49	2	12.81
			1	0	1	0	2	12.84
			1	49	1	0	2	20.25
			50	0	1	49	101	18.1

CA_5B								
Combination 10MHz+5MHz (50RB+25RB)								
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset		
20450	20522	QPSK	50	0	25	0	75	21.52
		QPSK	1	0	1	24	2	12.93
		QPSK	1	49	1	0	2	23.51
		16QAM	50	0	25	0	75	20.63
		16QAM	1	0	1	24	2	13.49
		16QAM	1	49	1	0	2	22.9
		64QAM	50	0	25	0	75	20.53
		64QAM	1	0	1	24	2	13.11
		64QAM	1	49	1	0	2	20.81
20500	20572	QPSK	50	0	25	0	75	21.51
		QPSK	1	0	1	24	2	12.99
		QPSK	1	49	1	0	2	23.49
		16QAM	50	0	25	0	75	20.58
		16QAM	1	0	1	24	2	13.47
		16QAM	1	49	1	0	2	22.76
		64QAM	50	0	25	0	75	20.61
		64QAM	1	0	1	24	2	13.22
		64QAM	1	49	1	0	2	20.68
20550	20622	QPSK	50	0	25	0	75	21.48
		QPSK	1	0	1	24	2	12.97
		QPSK	1	49	1	0	2	23.41
		16QAM	50	0	25	0	75	20.57
		16QAM	1	0	1	24	2	13.49
		16QAM	1	49	1	0	2	22.94
		64QAM	50	0	25	0	75	20.55
		64QAM	1	0	1	24	2	13.21
		64QAM	1	49	1	0	2	20.59

Combination 5MHz+10MHz (25RB+50RB)								
PCC Channel	SCC Channel	Modulation	PCC		SCC		Total RB Size	Measured Power (dBm)
			RB Size	RB offset	RB Size	RB offset		
20428	20500	QPSK	25	0	50	0	75	21.02
		QPSK	1	0	1	49	2	12.45
		QPSK	1	24	1	0	2	22.99
		16QAM	25	0	50	0	75	20.12
		16QAM	1	0	1	49	2	12.96
		16QAM	1	24	1	0	2	22.49
		64QAM	25	0	50	0	75	20.09
		64QAM	1	0	1	49	2	12.78
		64QAM	1	24	1	0	2	20.22
20478	20550	QPSK	25	0	50	0	75	21.04
		QPSK	1	0	1	49	2	12.43
		QPSK	1	24	1	0	2	23.03
		16QAM	25	0	50	0	75	20.13
		16QAM	1	0	1	49	2	12.81
		16QAM	1	24	1	0	2	22.41
		64QAM	25	0	50	0	75	20.14
		64QAM	1	0	1	49	2	12.73
		64QAM	1	24	1	0	2	20.39
20528	20600	QPSK	25	0	50	0	75	20.94
		QPSK	1	0	1	49	2	12.43
		QPSK	1	24	1	0	2	22.97
		16QAM	25	0	50	0	75	20.07
		16QAM	1	0	1	49	2	12.91
		16QAM	1	24	1	0	2	22.45
		64QAM	25	0	50	0	75	20.06
		64QAM	1	0	1	49	2	12.8
		64QAM	1	24	1	0	2	20.25

ERP/EIRP

LTE Band 2 (GT - LC = -1.00 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	22.95	23.13	23.32	22.97	23.10	23.31	23.06	23.19	23.35
Conducted Power (Watts)	0.1972	0.2056	0.2148	0.1982	0.2042	0.2143	0.2023	0.2084	0.2163
EIRP(dBm)	21.95	22.13	22.32	21.97	22.10	22.31	22.06	22.19	22.35
EIRP(Watts)	0.1567	0.1633	0.1706	0.1574	0.1622	0.1702	0.1607	0.1656	0.1718

LTE Band 2 (GT - LC = -1.00 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	23.24	23.40	23.44	22.97	23.12	23.38	23.30	23.31	23.45
Conducted Power (Watts)	0.2109	0.2188	0.2208	0.1982	0.2051	0.2178	0.2138	0.2143	0.2213
EIRP(dBm)	22.24	22.40	22.44	21.97	22.12	22.38	22.30	22.31	22.45
EIRP(Watts)	0.1675	0.1738	0.1754	0.1574	0.1629	0.1730	0.1698	0.1702	0.1758

LTE Band 2 (GT - LC = -1.00 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	22.31	22.42	22.76	22.33	22.47	22.76	22.42	22.51	22.77
Conducted Power (Watts)	0.1702	0.1746	0.1888	0.1710	0.1766	0.1888	0.1746	0.1782	0.1892
EIRP(dBm)	21.31	21.42	21.76	21.33	21.47	21.76	21.42	21.51	21.77
EIRP(Watts)	0.1352	0.1387	0.1500	0.1358	0.1403	0.1500	0.1387	0.1416	0.1503

LTE Band 2 (GT - LC = -1.00 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	22.60	22.66	22.76	22.50	22.60	22.84	22.67	22.62	22.69
Conducted Power (Watts)	0.1820	0.1845	0.1888	0.1778	0.1820	0.1923	0.1849	0.1828	0.1858
EIRP(dBm)	21.60	21.66	21.76	21.50	21.60	21.84	21.67	21.62	21.69
EIRP(Watts)	0.1445	0.1466	0.1500	0.1413	0.1445	0.1528	0.1469	0.1452	0.1476

LTE Band 2 (GT - LC = -1.00 dB) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	18607	18900	19193	18615	18900	19185	18625	18900	19175
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1850.7	1880	1909.3	1851.5	1880	1908.5	1852.5	1880	1907.5
Conducted Power (dBm)	21.40	21.58	21.80	21.39	21.59	21.82	21.45	21.62	21.87
Conducted Power (Watts)	0.1380	0.1439	0.1514	0.1377	0.1442	0.1521	0.1396	0.1452	0.1538
EIRP(dBm)	20.40	20.58	20.80	20.39	20.59	20.82	20.45	20.62	20.87
EIRP(Watts)	0.1096	0.1143	0.1202	0.1094	0.1146	0.1208	0.1109	0.1153	0.1222

LTE Band 2 (GT - LC = -1.00 dB) 64QAM									
Bandwidth	10M			15M			20M		
Channel	18650	18900	19150	18675	18900	19125	18650	18900	19100
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1855	1880	1905	1857.5	1880	1902.5	1860	1880	1900
Conducted Power (dBm)	21.69	21.83	21.86	21.61	21.69	21.95	21.78	21.74	21.82
Conducted Power (Watts)	0.1476	0.1524	0.1535	0.1449	0.1476	0.1567	0.1507	0.1493	0.1521
EIRP(dBm)	20.69	20.83	20.86	20.61	20.69	20.95	20.78	20.74	20.82
EIRP(Watts)	0.1172	0.1211	0.1219	0.1151	0.1172	0.1245	0.1197	0.1186	0.1208

LTE Band 5 (GT - LC = -3.00 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	23.28	23.24	23.16	23.26	23.23	23.22	23.22	23.10	23.07
Conducted Power (Watts)	0.2128	0.2109	0.2070	0.2118	0.2104	0.2099	0.2099	0.2042	0.2028
ERP(dBm)	18.13	18.09	18.01	18.11	18.08	18.07	18.07	17.95	17.92
ERP(Watts)	0.0650	0.0644	0.0632	0.0647	0.0643	0.0641	0.0641	0.0624	0.0619

LTE Band 5 (GT - LC = -3.00 dB) QPSK			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	23.30	23.02	23.07
Conducted Power (Watts)	0.2138	0.2004	0.2028
ERP(dBm)	18.15	17.87	17.92
ERP(Watts)	0.0653	0.0612	0.0619

LTE Band 5 (GT - LC = -3.00 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	22.57	22.52	22.58	22.64	22.60	22.62	22.53	22.52	22.48
Conducted Power (Watts)	0.1807	0.1786	0.1811	0.1837	0.1820	0.1828	0.1791	0.1786	0.1770
ERP(dBm)	17.42	17.37	17.43	17.49	17.45	17.47	17.38	17.37	17.33
ERP(Watts)	0.0552	0.0546	0.0553	0.0561	0.0556	0.0558	0.0547	0.0546	0.0541

LTE Band 5 (GT - LC = -3.00 dB) 16QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	22.62	22.32	22.50
Conducted Power (Watts)	0.1828	0.1706	0.1778
ERP(dBm)	17.47	17.17	17.35
ERP(Watts)	0.0558	0.0521	0.0543

LTE Band 5 (GT - LC = -3.00 dB) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	20407	20525	20643	20415	20525	20635	20425	20525	20625
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	824.7	836.5	848.3	825.5	836.5	847.5	826.5	836.5	846.5
Conducted Power (dBm)	21.63	21.58	21.66	21.69	21.65	21.65	21.64	21.58	21.55
Conducted Power (Watts)	0.1455	0.1439	0.1466	0.1476	0.1462	0.1462	0.1459	0.1439	0.1429
ERP(dBm)	16.48	16.43	16.51	16.54	16.50	16.50	16.49	16.43	16.40
ERP(Watts)	0.0445	0.0440	0.0448	0.0451	0.0447	0.0447	0.0446	0.0440	0.0437

LTE Band 5 (GT - LC = -3.00 dB) 64QAM			
Bandwidth	10M		
Channel	20450	20525	20600
	(Low)	(Mid)	(High)
Frequency (MHz)	829	836.5	844
Conducted Power (dBm)	21.69	21.45	21.58
Conducted Power (Watts)	0.1476	0.1396	0.1439
ERP(dBm)	16.54	16.30	16.43
ERP(Watts)	0.0451	0.0427	0.0440

LTE Band 7 (GT - LC = 1.00 dB) QPSK			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency (MHz)	2502.5	2535	2567.5
Conducted Power (dBm)	22.90	22.81	22.88
Conducted Power (Watts)	0.1950	0.1910	0.1941
EIRP(dBm)	23.90	23.81	23.88
EIRP(Watts)	0.2455	0.2404	0.2443

LTE Band 7 (GT - LC = 1.00 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	22.89	22.81	22.87	22.95	22.97	22.90	23.04	22.77	22.92
Conducted Power (Watts)	0.1945	0.1910	0.1936	0.1972	0.1982	0.1950	0.2014	0.1892	0.1959
EIRP(dBm)	23.89	23.81	23.87	23.95	23.97	23.90	24.04	23.77	23.92
EIRP(Watts)	0.2449	0.2404	0.2438	0.2483	0.2495	0.2455	0.2535	0.2382	0.2466

LTE Band 7 (GT - LC = 1.00 dB) 16QAM			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency (MHz)	2502.5	2535	2567.5
Conducted Power (dBm)	22.23	22.15	22.20
Conducted Power (Watts)	0.1671	0.1641	0.1660
EIRP(dBm)	23.23	23.15	23.20
EIRP(Watts)	0.2104	0.2065	0.2089

LTE Band 7 (GT - LC = 1.00 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	22.18	22.17	22.15	22.31	22.23	22.28	22.37	22.16	22.34
Conducted Power (Watts)	0.1652	0.1648	0.1641	0.1702	0.1671	0.1690	0.1726	0.1644	0.1714
EIRP(dBm)	23.18	23.17	23.15	23.31	23.23	23.28	23.37	23.16	23.34
EIRP(Watts)	0.2080	0.2075	0.2065	0.2143	0.2104	0.2128	0.2173	0.2070	0.2158

LTE Band 7 (GT - LC = 1.00 dBi) 64QAM			
Bandwidth	5M		
Channel	20775	21100	21425
	(Low)	(Mid)	(High)
Frequency (MHz)	2502.5	2535	2567.5
Conducted Power (dBm)	20.98	20.90	21.04
Conducted Power (Watts)	0.1253	0.1230	0.1271
EIRP(dBm)	21.98	21.90	22.04
EIRP(Watts)	0.1578	0.1549	0.1600

LTE Band 7 (GT - LC = 1.00 dBi) 64QAM									
Bandwidth	10M			15M			20M		
Channel	20800	21100	21400	20825	21100	21375	20850	21100	21350
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	2505	2535	2565	2507.5	2535	2562.5	2510	2535	2560
Conducted Power (dBm)	21.03	20.89	20.93	21.20	21.18	21.17	21.36	21.24	21.47
Conducted Power (Watts)	0.1268	0.1227	0.1239	0.1318	0.1312	0.1309	0.1368	0.1330	0.1403
EIRP(dBm)	22.03	21.89	21.93	22.20	22.18	22.17	22.36	22.24	22.47
EIRP(Watts)	0.1596	0.1545	0.1560	0.1660	0.1652	0.1648	0.1722	0.1675	0.1766

LTE Band 12 (GT - LC = -3.00 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	23017	23095	23173	23025	23095	23165	23035	23095	23155
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	699.7	707.5	715.3	700.5	707.5	714.5	701.5	707.5	713.5
Conducted Power (dBm)	23.08	23.01	23.05	23.06	23.01	23.04	23.11	23.01	23.06
Conducted Power (Watts)	0.2032	0.2000	0.2018	0.2023	0.2000	0.2014	0.2046	0.2000	0.2023
ERP(dBm)	17.93	17.86	17.90	17.91	17.86	17.89	17.96	17.86	17.91
ERP(Watts)	0.0621	0.0611	0.0617	0.0618	0.0611	0.0615	0.0625	0.0611	0.0618

LTE Band 12 (GT - LC = -3.00 dB) QPSK			
Bandwidth	10M		
Channel	23060	23095	23130
	(Low)	(Mid)	(High)
Frequency (MHz)	704	707.5	711
Conducted Power (dBm)	23.12	22.98	23.03
Conducted Power (Watts)	0.2051	0.1986	0.2009
ERP(dBm)	17.97	17.83	17.88
ERP(Watts)	0.0627	0.0607	0.0614

LTE Band 12 (GT - LC = -3.00 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	23017	23095	23173	23025	23095	23165	23035	23095	23155
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	699.7	707.5	715.3	700.5	707.5	714.5	701.5	707.5	713.5
Conducted Power (dBm)	22.42	22.42	22.30	22.33	22.41	22.39	22.49	22.41	22.34
Conducted Power (Watts)	0.1746	0.1746	0.1698	0.1710	0.1742	0.1734	0.1774	0.1742	0.1714
ERP(dBm)	17.27	17.27	17.15	17.18	17.26	17.24	17.34	17.26	17.19
ERP(Watts)	0.0533	0.0533	0.0519	0.0522	0.0532	0.0530	0.0542	0.0532	0.0524

LTE Band 12 (GT - LC = -3.00 dB) 16QAM			
Bandwidth	10M		
Channel	23060	23095	23130
	(Low)	(Mid)	(High)
Frequency (MHz)	704	707.5	711
Conducted Power (dBm)	22.48	22.42	22.35
Conducted Power (Watts)	0.1770	0.1746	0.1718
ERP(dBm)	17.33	17.27	17.20
ERP(Watts)	0.0541	0.0533	0.0525

LTE Band 12 (GT - LC = -3.00 dB) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	23017	23095	23173	23025	23095	23165	23035	23095	23155
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	699.7	707.5	715.3	700.5	707.5	714.5	701.5	707.5	713.5
Conducted Power (dBm)	21.49	21.49	21.38	21.47	21.51	21.41	21.48	21.56	21.43
Conducted Power (Watts)	0.1409	0.1409	0.1374	0.1403	0.1416	0.1384	0.1406	0.1432	0.1390
ERP(dBm)	16.34	16.34	16.23	16.32	16.36	16.26	16.33	16.41	16.28
ERP(Watts)	0.0431	0.0431	0.0420	0.0429	0.0433	0.0423	0.0430	0.0438	0.0425

LTE Band 12 (GT - LC = -3.00 dB) 64QAM			
Bandwidth	10M		
Channel	23060	23095	23130
	(Low)	(Mid)	(High)
Frequency (MHz)	704	707.5	711
Conducted Power (dBm)	21.56	21.52	21.47
Conducted Power (Watts)	0.1432	0.1419	0.1403
ERP(dBm)	16.41	16.37	16.32
ERP(Watts)	0.0438	0.0434	0.0429

LTE Band 13 (GT - LC = -3.00 dB) QPSK						
Bandwidth	5M			10M		
Channel	23205	23230	23255	23230		
	(Low)	(Mid)	(High)	-	(Mid)	-
Frequency (MHz)	779.5	782	784.5	-	782	-
Conducted Power (dBm)	22.96	23.05	22.98		23.05	-
Conducted Power (Watts)	0.1977	0.2018	0.1986		0.2018	-
ERP(dBm)	17.81	17.90	17.83		17.90	-
ERP(Watts)	0.0604	0.0617	0.0607		0.0617	-

LTE Band 13 (GT - LC = -3.00 dB) 16QAM						
Bandwidth	5M			10M		
Channel	23205	23230	23255	23230		
	(Low)	(Mid)	(High)	-	(Mid)	-
Frequency (MHz)	779.5	782	784.5	-	782	-
Conducted Power (dBm)	22.32	22.48	22.32		22.45	-
Conducted Power (Watts)	0.1706	0.1770	0.1706		0.1758	-
ERP(dBm)	17.17	17.33	17.17		17.30	-
ERP(Watts)	0.0521	0.0541	0.0521		0.0537	-

LTE Band 13 (GT - LC = -3.00 dB) 64QAM						
Bandwidth	5M			10M		
Channel	23205	23230	23255	23230		
	(Low)	(Mid)	(High)	-	(Mid)	-
Frequency (MHz)	779.5	782	784.5	-	782	-
Conducted Power (dBm)	21.42	21.40	21.54		21.53	-
Conducted Power (Watts)	0.1387	0.1380	0.1426		0.1422	-
ERP(dBm)	16.27	16.25	16.39		16.38	-
ERP(Watts)	0.0424	0.0422	0.0436		0.0435	-

LTE Band 66 (GT - LC = 1.00 dB) QPSK									
Bandwidth	1.4M			3M			5M		
Channel	131979	132322	132665	131987	132322	132657	131997	132322	132647
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1745	1779.3	1711.5	1745	1778.5	1712.5	1745	1777.5
Conducted Power (dBm)	22.92	22.77	22.76	22.92	22.79	22.80	22.96	22.81	22.84
Conducted Power (Watts)	0.1959	0.1892	0.1888	0.1959	0.1901	0.1905	0.1977	0.1910	0.1923
EIRP(dBm)	23.92	23.77	23.76	23.92	23.79	23.80	23.96	23.81	23.84
EIRP(Watts)	0.2466	0.2382	0.2377	0.2466	0.2393	0.2399	0.2489	0.2404	0.2421

LTE Band 66 (GT - LC = 1.00 dB) QPSK									
Bandwidth	10M			15M			20M		
Channel	132022	132322	132622	132047	132322	132597	132072	132322	132572
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency (MHz)	1715	1745	1775	1717.5	1745	1772.5	1720	1745	1770
Conducted Power (dBm)	22.85	22.87	22.90	23.05	22.97	22.96	23.06	22.94	22.99
Conducted Power (Watts)	0.1928	0.1936	0.1950	0.2018	0.1982	0.1977	0.2023	0.1968	0.1991
EIRP(dBm)	23.85	23.87	23.90	24.05	23.97	23.96	24.06	23.94	23.99
EIRP(Watts)	0.2427	0.2438	0.2455	0.2541	0.2495	0.2489	0.2547	0.2477	0.2506

LTE Band 66 (GT - LC = 1.00 dB) 16QAM									
Bandwidth	1.4M			3M			5M		
Channel	131979	132322	132665	131987	132322	132657	131997	132322	132647
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1745	1779.3	1711.5	1745	1778.5	1712.5	1745	1777.5
Conducted Power (dBm)	22.12	22.03	22.09	22.16	21.97	22.05	22.25	22.08	22.12
Conducted Power (Watts)	0.1629	0.1596	0.1618	0.1644	0.1574	0.1603	0.1679	0.1614	0.1629
EIRP(dBm)	23.12	23.03	23.09	23.16	22.97	23.05	23.25	23.08	23.12
EIRP(Watts)	0.2051	0.2009	0.2037	0.2070	0.1982	0.2018	0.2113	0.2032	0.2051

LTE Band 66 (GT - LC = 1.00 dB) 16QAM									
Bandwidth	10M			15M			20M		
Channel	132022	132322	132622	132047	132322	132597	132072	132322	132572
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency (MHz)	1715	1745	1775	1717.5	1745	1772.5	1720	1745	1770
Conducted Power (dBm)	22.27	22.00	22.01	22.25	22.33	22.18	22.28	22.32	22.17
Conducted Power (Watts)	0.1687	0.1585	0.1589	0.1679	0.1710	0.1652	0.1690	0.1706	0.1648
EIRP(dBm)	23.27	23.00	23.01	23.25	23.33	23.18	23.28	23.32	23.17
EIRP(Watts)	0.2123	0.1995	0.2000	0.2113	0.2153	0.2080	0.2128	0.2148	0.2075

LTE Band 66 (GT - LC = 1.00 dB) 64QAM									
Bandwidth	1.4M			3M			5M		
Channel	131979	132322	132665	131987	132322	132657	131997	132322	132647
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Frequency (MHz)	1710.7	1745	1779.3	1711.5	1745	1778.5	1712.5	1745	1777.5
Conducted Power (dBm)	21.19	21.95	21.11	21.29	21.13	21.18	21.30	21.20	21.22
Conducted Power (Watts)	0.1315	0.1567	0.1291	0.1346	0.1297	0.1312	0.1349	0.1318	0.1324
EIRP(dBm)	22.19	22.95	22.11	22.29	22.13	22.18	22.30	22.20	22.22
EIRP(Watts)	0.1656	0.1972	0.1626	0.1694	0.1633	0.1652	0.1698	0.1660	0.1667

LTE Band 66 (GT - LC = 1.00 dB) 64QAM									
Bandwidth	10M			15M			20M		
Channel	132022	132322	132622	132047	132322	132597	132072	132322	132572
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(Mid)
Frequency (MHz)	1715	1745	1775	1717.5	1745	1772.5	1720	1745	1770
Conducted Power (dBm)	21.35	21.27	21.21	21.42	21.39	21.35	21.39	21.41	21.31
Conducted Power (Watts)	0.1365	0.1340	0.1321	0.1387	0.1377	0.1365	0.1377	0.1384	0.1352
EIRP(dBm)	22.35	22.27	22.21	22.42	22.39	22.35	22.39	22.41	22.31
EIRP(Watts)	0.1718	0.1687	0.1663	0.1746	0.1734	0.1718	0.1734	0.1742	0.1702

CA EIRP

LTE Band 5B_CA (GT - LC = -3.00 dB) QPSK									
Bandwidth	10M + 10M			5M + 10M			10M+5M		
Channel PCC	20450	20476	20501	20428	20478	20528	20450	20500	20550
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Channel SCC	20549	20575	20600	20500	20550	20600	20522	20572	20622
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Conducted Power (dBm)	23.54	23.06	22.97	22.99	23.03	22.97	23.51	23.49	23.41
Conducted Power (Watts)	0.2259	0.2023	0.1982	0.1991	0.2009	0.1982	0.2244	0.2234	0.2193
ERP(dBm)	18.39	17.91	17.82	17.84	17.88	17.82	18.36	18.34	18.26
ERP(Watts)	0.0690	0.0618	0.0605	0.0608	0.0614	0.0605	0.0685	0.0682	0.0670

LTE Band 5B_CA (GT - LC = -3.00 dB) 16QAM									
Bandwidth	10M + 10M			5M + 10M			10M+5M		
Channel PCC	20450	20476	20501	20450	20476	20501	20450	20476	20501
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Channel SCC	20549	20575	20600	20549	20575	20600	20549	20575	20600
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Conducted Power (dBm)	23.10	22.63	22.6	22.49	22.41	22.45	22.90	22.76	22.94
Conducted Power (Watts)	0.2042	0.1832	0.1820	0.1774	0.1742	0.1758	0.1950	0.1888	0.1968
ERP(dBm)	17.95	17.48	17.45	17.34	17.26	17.30	17.75	17.61	17.79
ERP(Watts)	0.0624	0.0560	0.0556	0.0542	0.0532	0.0537	0.0596	0.0577	0.0601

LTE Band 5B_CA (GT - LC = -3.00 dB) 64QAM									
Bandwidth	10M + 10M			5M + 10M			10M+5M		
Channel PCC	20450	20476	20501	20450	20476	20501	20450	20476	20501
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Channel SCC	20549	20575	20600	20549	20575	20600	20549	20575	20600
	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)	(Low)	(Mid)	(High)
Conducted Power (dBm)	21.64	21.42	21.38	20.22	20.39	20.25	20.81	20.68	20.59
Conducted Power (Watts)	0.1459	0.1387	0.1374	0.1052	0.1094	0.1059	0.1205	0.1169	0.1146
ERP(dBm)	16.49	16.27	16.23	15.07	15.24	15.10	15.66	15.53	15.44
ERP(Watts)	0.0446	0.0424	0.0420	0.0321	0.0334	0.0324	0.0368	0.0357	0.0350

Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.71	4.64	5.19	5.94	PASS
Middle CH	3.51	4.58	5.25	5.91	
Highest CH	3.65	4.64	5.07	5.94	
Mode	LTE Band 2 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	5.57	5.94			PASS
Middle CH	5.30	5.94			
Highest CH	5.33	6.00			

Mode	LTE Band 5 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.65	4.78	4.99	6.03	PASS
Middle CH	3.83	4.55	5.57	5.91	
Highest CH	3.33	4.75	4.81	5.97	
Mode	LTE Band 5 / 10MHz				
Mod.	16QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.58	6.61			PASS
Middle CH	7.01	6.52			
Highest CH	5.86	6.43			

Mode	LTE Band 7 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.33	4.38	4.96	5.74	PASS
Middle CH	3.54	4.43	5.04	5.77	
Highest CH	3.62	4.64	5.59	6.03	
Mod.	64QAM		Limit: 13dB		
RB Size	1RB	Full RB	Result		
Lowest CH	5.19	5.68	PASS		
Middle CH	5.62	5.74			
Highest CH	5.59	5.91			

Mode	LTE Band 12 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.62	4.84	5.07	6.03	PASS
Middle CH	3.68	4.67	5.3	6.03	
Highest CH	3.83	4.55	5.83	5.83	
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.17	6.7			PASS
Middle CH	6.78	6.61			
Highest CH	7.01	6.55			

Mode	LTE Band 13 / 10MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.86	4.93	5.62	6.23	
Highest CH	-	-	-	-	
Mod.	64QAM		Limit: 13dB		
RB Size	1RB	Full RB	Result		
Lowest CH			PASS		
Middle CH	5.51	6.23			
Highest CH					

Mode	LTE Band 66 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.39	4.78	5.01	6.12	PASS
Middle CH	3.80	4.32	5.39	5.62	
Highest CH	3.10	4.38	4.49	5.57	
Mode	LTE Band 66 / 20MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	6.14	6.72			PASS
Middle CH	6.90	6.29			
Highest CH	5.48	6.12			

LTE Band 2 / 20MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB

Highest Channel / Full RB



LTE Band 2 / 20MHz / 16QAM

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB

Highest Channel / Full RB

LTE Band 2 / 20MHz / 64QAM

Lowest Channel / 1RB

Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 5 / 10MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 5 / 10MHz / 16QAM

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 5 / 10MHz / 64QAM

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 7 / 20MHz / QPSK

Lowest Channel / 1RB

Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 7 / 20MHz / 16QAM

Lowest Channel / 1RB

Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB



LTE Band 7 / 20MHz / 64QAM

Lowest Channel / 1RB



Lowest Channel / Full RB

Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB