FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2005-3
FCC ID	:	IHDT56YA3
STANDARD	:	FCC Part 15 Subpart E §15.407
CLASSIFICATION	:	(NII) Unlicensed National Information Infrastructure

The product was received on Feb. 21, 2019 and testing was completed on Mar. 19, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

James Huang

Approved by: James Huang / Manager

TESTING
NVLAP LAB CODE 600155-0

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone,
Jiangsu Province 215335, China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Specification of Accessory 6
1.7 Testing Location 7
1.8 Applicable Standards 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Carrier Frequency and Channel 8
2.2 Test Mode 9
2.3 Connection Diagram of Test System 10
2.4 Support Unit used in test configuration and system 10
2.5 EUT Operation Test Setup 11
2.6 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement 12
3.2 Maximum Conducted Output Power Measurement 15
3.3 Power Spectral Density Measurement 16
3.4 Unwanted Emissions Measurement 18
3.5 AC Conducted Emission Measurement 23
3.6 Automatically Discontinue Transmission 25
3.7 Antenna Requirements 26
4 LIST OF MEASURING EQUIPMENT **27**
5 UNCERTAINTY OF EVALUATION **28**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. AC CONDUCTED EMISSION TEST RESULT
APPENDIX C. RADIATED SPURIOUS EMISSION
APPENDIX D. DUTY CYCLE PLOTS
APPENDIX E. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR922110E	Rev. 01	Initial issue of report	Apr. 24, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.403(i)	6dB, 26dB and 99% Occupied Bandwidth	> 500kHz	Pass	-
3.2	15.407(a)	Maximum Conducted Output Power	≤ 30 dBm	Pass	-
3.3	15.407(a)	Power Spectral Density	≤ 30 dBm/500kHz	Pass	-
3.4	15.407(b)	Unwanted Emissions	15.407(b)(4)(i) &15.209(a)	Pass	Under limit 11.32 dB at 47.460 MHz
3.5	15.207	AC Conducted Emission	15.207(a)	Pass	Under limit 15.03 dB at 0.835 MHz
3.6	15.407(c)	Automatically Discontinue Transmission	Discontinue Transmission	Pass	-
3.7	15.203 & 15.407(a)	Antenna Requirement	N/A	Pass	-

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2005-3
FCC ID	IHDT56YA3
EUT supports Radios application	CDMA/EV-DO/GSM/GPRS/EGPRS/WCDMA/HSPA/ DC-HSDPA/HSPA+(16QAM uplink is not supported)LTE WLAN 2.4GHz 802.11b/g/n HT20/HT40 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth BR / EDR / LE FM Receiver/GNSS
IMEI Code	Radiation: 352179100023098 Conducted: 352179100021738 Conduction: 352179100023486
HW Version	88941-1-12
SW Version	fastboot_surfna_t_oem_t_userdebug_9_PCB29.7_0446_intcfg-test-keys_t
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Channel Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power	**<5745 MHz ~ 5825 MHz>** 802.11a : 19.10 dBm / 0.0813 W 802.11n HT20 : 19.16 dBm / 0.0824 W 802.11n HT40 : 15.46 dBm / 0.0352 W
99% Occupied Bandwidth	802.11a : 25.67 MHz 802.11n HT20 : 26.02 MHz 802.11n HT40 : 37.36 MHz
Type of Modulation	802.11a/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)
Antenna Type / Gain	IFA Antenna with gain -6.00 dBi

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Specification of Accessory

Specification of Accessory				
AC Adapter 1	**Brand Name**	Motorola(Acbel)	**Model Name**	SC-61
	Power Rating	I/P: 100-240 Vac, 130mA ; O/P: 5Vdc,1000mA		
AC Adapter 2	**Brand Name**	Motorola (Chenyang)	**Model Name**	SC-61
	Power Rating	I/P: 100-240 Vac, 130mA ; O/P: 5Vdc,1000mA		
Battery 1	**Brand Name**	Motorola(ATL)	**Model Name**	KE40
	Power Rating	3.8Vdc, 2820/3000mAh（Rated/typ)	**Type**	Li-ion
Battery 2	**Brand Name**	Motorola(Sunwoda)	**Model Name**	KE40
	Power Rating	3.8Vdc, 2820/3000mAh（Rated/typ)	**Type**	Li-ion
USB Cable	**Brand Name**	Motorola (SaiBao)	**Model Name**	711310002241
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0).

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone, Jiangsu Province 215335, China TEL : 86-512-57900158 FAX : 86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC designation No.**	**FCC Test Firm Registration No.**
	TH01-KS CO01-KS 03CH02-KS	CN5013	630927

1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart E
- FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Z plane) were recorded in this report.

b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5745-5825 MHz Band 4 (U-NII-3)	149	5745	159*	5795
	151*	5755	161	5805
	153	5765	165	5825
	157	5785		

Note: The above Frequency and Channel in "*" were 802.11n HT40.

2.2 Test Mode

Final test modes are considering the modulation and worse data rates as below table.

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20	MCS0
802.11n HT40	MCS0

Test Cases	
AC Conducted Emission	Mode 1 : GSM 850 Idle + Bluetooth Link + WLAN Link (5G) + Earphone + USB Cable(Charging from adapter 2) + Battery 2
Remark: For Radiated Test Cases, The tests were performed with Adapter 2, Battery 2, Earphone and USB Cable..	

Ch. #		Band IV：5745-5825 MHz		
		802.11a	802.11n HT20	802.11n HT40
L	Low	149	149	151
M	Middle	157	157	-
H	High	165	165	159

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded,1.8m
2.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8 m
3.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
4.	Notebook	Lenovo	G480	N/A	N/A	AC I/P: Unshielded, 1.8m DC O/P: Shielded, 1.8 m
5.	Earphone	Lenovo	SH100	N/A	Unshielded, 1.2 m	N/A

2.5 EUT Operation Test Setup

For WLAN RF test items, an engineering test program was provided and enabled to make EUT continuously transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss

Following shows an offset computation example with cable loss 6.6 dB

Offset(dB) = RF cable loss(dB)

=6.6 (dB)

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85GHz
2. Set RBW = 100kHz.
3. Set the VBW ≥ 3 x RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Minimum 6dB Bandwidth



Maximum 26dB Bandwidth



Maximum 99% Occupied Bandwidth



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

The testing follows Method PM of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM (Measurement using an RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit continuously with a consistent duty cycle at its maximum power control level.
3. Measure the average power of the transmitter, and the average power is corrected with duty factor, 10 log(1/x), where x is the duty cycle.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

 # Method SA-2 #

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300 kHz.
- Set VBW ≥ 1 MHz.
- Number of points in sweep ≥ 2 Span / RBW.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add 10 log(500kHz/RBW) to the test result.
- Add 10 log(1/x), where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add 10 log(1/0.25) = 6 dB if the duty cycle is 25 percent.

1. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

Worst Case Power Density (dBm/300kHz)



3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions fallen in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

Note: The following formula is used to convert the EIRP to field strength.

$$EIRP = E_{Meas} + 20\log(d_{Meas}) - 104.7$$

where

EIRP is the equivalent isotropically radiated power, in dBm

E_{Meas} is the field strength of the emission at the measurement distance, in dBμV/m

d_{Meas} is the measurement distance, in m

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.

   (1) Procedure for Unwanted Emissions Measurements Below 1000MHz
   - RBW = 120 kHz
   - VBW = 300 kHz
   - Detector = Peak
   - Trace mode = max hold

   (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
   - RBW = 1 MHz
   - VBW ≥ 3 MHz
   - Detector = Peak
   - Sweep time = auto
   - Trace mode = max hold

   (3) Procedures for Average Unwanted Emissions Measurements Above 1000MHz
   - RBW = 1 MHz
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

3.4.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C.

3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix B.

3.6 Automatically Discontinue Transmission

3.6.1 Limit of Automatically Discontinue Transmission

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. These provisions are not intended to preclude the transmission of control or signaling information or the use of repetitive codes used by certain digital technologies to complete frame or burst intervals. Applicants shall include in their application for equipment authorization to describe how this requirement is met.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Result of Automatically Discontinue Transmission

While the EUT is not transmitting any information, the EUT can automatically discontinue transmission and become standby mode for power saving. The EUT can detect the controlling signal of ACK message transmitting from remote device and verify whether it shall resend or discontinue transmission.

3.7 Antenna Requirements

3.7.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.7.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2018	Mar. 19, 2019	Aug. 06, 2019	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 14, 2019	Mar. 19, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Mar. 19, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Max 30dBm	Aug. 06, 2018	Mar. 10, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz-44G,MAX 30dB	Apr. 17, 2018	Mar. 10, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Mar. 10, 2019	Oct. 18, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz-2GHz	Dec. 29, 2018	Mar. 10, 2019	Dec. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75959	1GHz~18GHz	Jan. 27, 2019	Mar. 10, 2019	Jan. 26, 2020	Radiation (03CH02-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	100MHz-18GHz	Apr. 17, 2018	Mar. 10, 2019	Apr. 16, 2019	Radiation (03CH02-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Mar. 10, 2019	Jan. 04, 2020	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2018	Mar. 10, 2019	Aug. 05, 2019	Radiation (03CH02-KS)
Amplifier	Keysight	83017A	MY53270203	500MHz~26.5GHz	Apr. 18, 2018	Mar. 10, 2019	Apr. 17, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-HG	1887435	18~40GHz	Jan. 14, 2019	Mar. 10, 2019	Jan. 13, 2020	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	Mar. 10, 2019	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Mar. 10, 2019	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Mar. 10, 2019	NCR	Radiation (03CH02-KS)
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Feb. 28, 2019	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 12, 2018	Feb. 28, 2019	Oct. 11, 2019	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Nov. 19, 2018	Feb. 28, 2019	Nov. 18, 2019	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP000000811	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2018	Feb. 28, 2019	Oct. 11, 2019	Conduction (CO01-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.9dB**

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**4.8 dB**

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.2 dB**

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.0 dB**

Appendix A. Conducted Test Results

Report Number : FR922110E

Test Engineer:	Imp Xu	Temperature:	21~25	°C
Test Date:	2019/3/19	Relative Humidity:	51~54	%

Report Number : FR922110E

TEST RESULTS DATA
6dB and 26dB EBW and 99% OBW

Band IV									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)	26 dB Bandwidth (MHz)	6 dB Bandwidth (MHz)	6dB Bandwidth min. Limit (MHz)	Pass/Fail
11a	6M bps	1	149	5745	22.93	33.02	16.36	0.5	Pass
11a	6Mbps	1	157	5785	24.88	37.61	16.34	0.5	Pass
11a	6Mbps	1	165	5825	25.67	36.46	16.34	0.5	Pass
HT20	MCS 0	1	149	5745	23.28	37.71	17.56	0.5	Pass
HT20	MCS 0	1	157	5785	24.98	37.51	17.56	0.5	Pass
HT20	MCS 0	1	165	5825	26.02	37.51	17.56	0.5	Pass
HT40	MCS 0	1	151	5755	37.26	45.14	35.12	0.5	Pass
HT40	MCS 0	1	159	5795	37.36	45.23	35.32	0.5	Pass

Report Number : FR922110E

TEST RESULTS DATA
Average Power Table

Band IV										
Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)	FCC Conducted Power Limit (dBm)	DG (dBi)		Pass/Fail
11a	6M bps	1	149	5745	0.59	17.93	30.00	-6.00		Pass
11a	6Mbps	1	157	5785	0.59	18.82	30.00	-6.00		Pass
11a	6Mbps	1	165	5825	0.59	19.10	30.00	-6.00		Pass
HT20	MCS 0	1	149	5745	0.66	17.95	30.00	-6.00		Pass
HT20	MCS 0	1	157	5785	0.66	18.94	30.00	-6.00		Pass
HT20	MCS 0	1	165	5825	0.66	19.16	30.00	-6.00		Pass
HT40	MCS 0	1	151	5755	0.68	14.96	30.00	-6.00		Pass
HT40	MCS 0	1	159	5795	0.68	15.46	30.00	-6.00		Pass

Report Number : FR922110E

TEST RESULTS DATA
Power Spectral Density

Band IV										
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	10log (500kHz /RBW) Factor (dB)	Average Power Density (dBm/500kHz)	Average PSD Limit (dBm/500kHz)	DG (dBi)	Pass/Fail
11a	6M bps	1	149	5745	0.59	2.22	3.43	30.00	-6.00	Pass
11a	6Mbps	1	157	5785	0.59	2.22	4.88	30.00	-6.00	Pass
11a	6Mbps	1	165	5825	0.59	2.22	4.77	30.00	-6.00	Pass
HT20	MCS 0	1	149	5745	0.66	2.22	3.46	30.00	-6.00	Pass
HT20	MCS 0	1	157	5785	0.66	2.22	4.65	30.00	-6.00	Pass
HT20	MCS 0	1	165	5825	0.66	2.22	4.59	30.00	-6.00	Pass
HT40	MCS 0	1	151	5755	0.68	2.22	-2.04	30.00	-6.00	Pass
HT40	MCS 0	1	159	5795	0.68	2.22	-1.56	30.00	-6.00	Pass

Appendix B. AC Conducted Emission Test Results

Test Engineer :	Amos Zhang	**Temperature :**	23.3~24.2℃
		Relative Humidity :	28~30%
Test Voltage :	120Vac / 60Hz	**Phase :**	Line



Site : CO01-KS
Condition : FCC PART 15E LISN-L-181013-060103 LINE

mode : Mode 1
: 352179100023486 #5

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.153	48.30	-17.52	65.82	37.60	0.23	10.47	QP
2	0.153	39.20	-16.62	55.82	28.50	0.23	10.47	Average
3	0.159	48.48	-17.04	65.52	37.79	0.23	10.46	QP
4	0.159	33.28	-22.24	55.52	22.59	0.23	10.46	Average
5	0.212	41.18	-21.96	63.14	30.60	0.22	10.36	QP
6	0.212	25.08	-28.06	53.14	14.50	0.22	10.36	Average
7 *	0.835	40.97	-15.03	56.00	30.50	0.23	10.24	QP
8	0.835	27.97	-18.03	46.00	17.50	0.23	10.24	Average
9	1.049	38.67	-17.33	56.00	28.20	0.24	10.23	QP
10	1.049	27.77	-18.23	46.00	17.30	0.24	10.23	Average
11	2.001	37.29	-18.71	56.00	26.80	0.26	10.23	QP
12	2.001	27.09	-18.91	46.00	16.60	0.26	10.23	Average

Test Engineer :	Amos Zhang	Temperature :	23.3~24.2℃
		Relative Humidity :	28~30%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral



Site : CO01-KS
Condition : FCC PART 15E LISN-N-181013-060103 NEUTRAL

mode : Mode 1
: 352179100023486 #5

		Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
		MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1		0.154	47.28	-18.50	65.78	36.60	0.21	10.47	QP
2		0.154	32.98	-22.80	55.78	22.30	0.21	10.47	Average
3	*	0.171	48.23	-16.67	64.90	37.59	0.21	10.43	QP
4		0.171	32.23	-22.67	54.90	21.59	0.21	10.43	Average
5		0.914	35.64	-20.36	56.00	25.19	0.21	10.24	QP
6		0.914	28.07	-17.93	46.00	17.62	0.21	10.24	Average
7		1.888	35.95	-20.05	56.00	25.50	0.22	10.23	QP
8		1.888	26.75	-19.25	46.00	16.30	0.22	10.23	Average
9		2.121	35.55	-20.45	56.00	25.10	0.22	10.23	QP
10		2.121	26.75	-19.25	46.00	16.30	0.22	10.23	Average
11		19.532	41.31	-18.69	60.00	30.49	0.33	10.49	QP
12		19.532	28.31	-21.69	50.00	17.49	0.33	10.49	Average

Appendix C. Radiated Spurious Emission

Band 4 - 5725~5850MHz

WIFI 802.11a (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		5608	51.28	-17.02	68.3	40.8	34.6	8.52	32.64	228	199	P	H
		5698.8	55.72	-48.7	104.42	45.18	34.7	8.58	32.74	228	199	P	H
		5714.4	66.39	-42.94	109.33	55.85	34.73	8.61	32.8	228	199	P	H
		5724.8	74.1	-47.74	121.84	63.52	34.77	8.61	32.8	228	199	P	H
		5746	106.49	-	-	95.91	34.8	8.64	32.86	228	199	P	H
		5746	99.21	-	-	88.63	34.8	8.64	32.86	228	199	A	H
		5645.6	51.84	-16.46	68.3	41.25	34.67	8.55	32.63	345	86	P	V
		5677.6	51.35	-37.41	88.76	40.75	34.7	8.58	32.68	345	86	P	V
		5719.6	55.19	-55.6	110.79	44.61	34.77	8.61	32.8	345	86	P	V
		5724.8	62.77	-59.07	121.84	52.19	34.77	8.61	32.8	345	86	P	V
		5740	95.6	-	-	85.02	34.8	8.64	32.86	345	86	P	V
		5740	88.23	-	-	77.65	34.8	8.64	32.86	345	86	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		5828	107.91	-	-	97.26	34.97	8.72	33.04	311	203	P	H
		5828	100.68	-	-	90.03	34.97	8.72	33.04	311	203	A	H
		5851.2	68.4	-51.16	119.56	57.78	35	8.72	33.1	311	203	P	H
		5855.6	66.02	-44.71	110.73	55.32	35.03	8.77	33.1	311	203	P	H
		5876	56.35	-48.21	104.56	45.61	35.07	8.77	33.1	311	203	P	H
		5979.6	52.72	-15.58	68.3	41.66	35.27	8.93	33.14	311	203	P	H
		5824	99.18	-	-	88.53	34.97	8.72	33.04	301	314	P	V
		5824	91.68	-	-	81.03	34.97	8.72	33.04	301	314	A	V
		5852.8	59.15	-56.77	115.92	48.53	35	8.72	33.1	301	314	P	V
		5854.8	57.64	-53.72	111.36	46.99	35.03	8.72	33.1	301	314	P	V
		5918.4	51.95	-21.22	73.17	41.12	35.13	8.82	33.12	301	314	P	V
		5928.4	52.87	-15.43	68.3	42	35.17	8.82	33.12	301	314	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	46.92	-27.08	74	58.93	38.08	12.74	62.83	150	360	P	H
		11490	46.02	-27.98	74	58.03	38.08	12.74	62.83	150	360	P	V
802.11a CH 157 5785MHz		11570	45.81	-28.19	74	57.67	38.17	12.79	62.82	100	360	P	H
		11570	46.53	-27.47	74	58.39	38.17	12.79	62.82	100	360	P	V
802.11a CH 165 5825MHz		11650	46.61	-27.39	74	58.33	38.24	12.85	62.81	100	360	P	H
		11650	46.92	-27.08	74	58.64	38.24	12.85	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		5614.8	53.67	-14.63	68.3	43.19	34.6	8.52	32.64	232	172	P	H
		5693.2	58.58	-41.71	100.29	48.04	34.7	8.58	32.74	232	172	P	H
		5720	73.77	-37.13	110.9	63.19	34.77	8.61	32.8	232	172	P	H
		5724.4	80.6	-40.33	120.93	70.02	34.77	8.61	32.8	232	172	P	H
		5740	110.38	-	-	99.8	34.8	8.64	32.86	232	172	P	H
		5740	103	-	-	92.42	34.8	8.64	32.86	232	172	A	H
		5626	53.02	-15.28	68.3	42.48	34.63	8.55	32.64	104	174	P	V
		5693.2	53.76	-46.53	100.29	43.22	34.7	8.58	32.74	104	174	P	V
		5719.6	59.42	-51.37	110.79	48.84	34.77	8.61	32.8	104	174	P	V
		5724.8	69.52	-52.32	121.84	58.94	34.77	8.61	32.8	104	174	P	V
		5742	98.34	-	-	87.76	34.8	8.64	32.86	104	174	P	V
		5742	91.28	-	-	80.7	34.8	8.64	32.86	104	174	A	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 165 5825MHz		5818	110.05	-	-	99.44	34.93	8.72	33.04	238	170	P	H
		5818	102.63	-	-	92.02	34.93	8.72	33.04	238	170	A	H
		5850	74.58	-47.72	122.3	63.96	35	8.72	33.1	238	170	P	H
		5855.2	69.19	-41.65	110.84	58.54	35.03	8.72	33.1	238	170	P	H
		5876.8	58.23	-45.73	103.96	47.49	35.07	8.77	33.1	238	170	P	H
		5934	52.93	-15.37	68.3	42	35.17	8.88	33.12	238	170	P	H
		5830	99.13	-	-	88.48	34.97	8.72	33.04	352	185	P	V
		5830	91.85	-	-	81.2	34.97	8.72	33.04	352	185	A	V
		5850	60.21	-62.09	122.3	49.59	35	8.72	33.1	352	185	P	V
		5854.8	57.15	-54.21	111.36	46.5	35.03	8.72	33.1	352	185	P	V
		5875.6	53.57	-51.28	104.85	42.83	35.07	8.77	33.1	352	185	P	V
		5950	52.93	-15.37	68.3	41.98	35.2	8.88	33.13	352	185	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT20 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT20 CH 149 5745MHz		11490	45.33	-28.67	74	57.34	38.08	12.74	62.83	100	360	P	H
		11490	45.55	-28.45	74	57.56	38.08	12.74	62.83	150	360	P	V
802.11n HT20 CH 157 5785MHz		11570	45.44	-28.56	74	57.3	38.17	12.79	62.82	100	360	P	H
		11570	45.6	-28.4	74	57.46	38.17	12.79	62.82	100	360	P	V
802.11n HT20 CH 165 5825MHz		11650	47.97	-26.03	74	59.69	38.24	12.85	62.81	100	360	P	H
		11650	46.75	-27.25	74	58.47	38.24	12.85	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Band Edge @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		5648	52.88	-15.42	68.3	42.29	34.67	8.55	32.63	235	171	P	H
		5695.2	58.96	-42.8	101.76	48.42	34.7	8.58	32.74	235	171	P	H
		5713.2	65.53	-43.47	109	54.99	34.73	8.61	32.8	235	171	P	H
		5722.4	67.68	-48.69	116.37	57.1	34.77	8.61	32.8	235	171	P	H
		5744	103.92	-	-	93.34	34.8	8.64	32.86	235	171	P	H
		5744	96.54	-	-	85.96	34.8	8.64	32.86	235	171	A	H
		5851.6	52.85	-65.8	118.65	42.23	35	8.72	33.1	235	171	P	H
		5864.8	53.96	-54.19	108.15	43.26	35.03	8.77	33.1	235	171	P	H
		5897.2	53.94	-34.89	88.83	43.13	35.1	8.82	33.11	235	171	P	H
		5930.4	52.68	-15.62	68.3	41.81	35.17	8.82	33.12	235	171	P	H
		5628	53.46	-14.84	68.3	42.92	34.63	8.55	32.64	256	105	P	V
		5699.6	52.53	-52.48	105.01	41.96	34.7	8.61	32.74	256	105	P	V
		5716.8	55.49	-54.52	110.01	44.95	34.73	8.61	32.8	256	105	P	V
		5723.2	55.29	-62.91	118.2	44.71	34.77	8.61	32.8	256	105	P	V
		5744	92.61	-	-	82.03	34.8	8.64	32.86	256	105	P	V
		5744	85.61	-	-	75.03	34.8	8.64	32.86	256	105	A	V
		5852.4	53.2	-63.63	116.83	42.58	35	8.72	33.1	256	105	P	V
		5872.8	52.63	-53.29	105.92	41.89	35.07	8.77	33.1	256	105	P	V
		5900.4	53.07	-33.39	86.46	42.26	35.1	8.82	33.11	256	105	P	V
		5926.4	52.99	-15.31	68.3	42.12	35.17	8.82	33.12	256	105	P	V

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 159 5795MHz		5614.8	53.03	-15.27	68.3	42.55	34.6	8.52	32.64	233	173	P	H
		5692.4	53.79	-45.91	99.7	43.25	34.7	8.58	32.74	233	173	P	H
		5705.2	52.52	-54.24	106.76	41.98	34.73	8.61	32.8	233	173	P	H
		5722.4	52.29	-64.08	116.37	41.71	34.77	8.61	32.8	233	173	P	H
		5782	103.34	-	-	92.78	34.87	8.67	32.98	233	173	P	H
		5782	95.86	-	-	85.3	34.87	8.67	32.98	233	173	A	H
		5854	56.8	-56.38	113.18	46.15	35.03	8.72	33.1	233	173	P	H
		5856	54.91	-55.71	110.62	44.21	35.03	8.77	33.1	233	173	P	H
		5900.4	53.35	-33.11	86.46	42.54	35.1	8.82	33.11	233	173	P	H
		5973.6	52.83	-15.47	68.3	41.77	35.27	8.93	33.14	233	173	P	H
		5617.6	52.75	-15.55	68.3	42.24	34.63	8.52	32.64	206	81	P	V
		5672.8	52.98	-32.23	85.21	42.38	34.7	8.58	32.68	206	81	P	V
		5719.65	52.73	-58.07	110.8	42.15	34.77	8.61	32.8	206	81	P	V
		5720.69	52.73	-59.74	112.47	42.15	34.77	8.61	32.8	206	81	P	V
		5808	92.6	-	-	82.04	34.93	8.67	33.04	206	81	P	V
		5808	85.58	-	-	75.02	34.93	8.67	33.04	206	81	A	V
		5854.4	52.76	-59.51	112.27	42.11	35.03	8.72	33.1	206	81	P	V
		5868.4	51.98	-55.17	107.15	41.28	35.03	8.77	33.1	206	81	P	V
		5879.6	54.5	-47.38	101.88	43.76	35.07	8.77	33.1	206	81	P	V
		5965.2	53	-15.3	68.3	42.03	35.23	8.88	33.14	206	81	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Band 4 5725~5850MHz

WIFI 802.11n HT40 (Harmonic @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11n HT40 CH 151 5755MHz		11510	45.9	-28.1	74	57.89	38.1	12.74	62.83	100	360	P	H
		11510	45.75	-28.25	74	57.74	38.1	12.74	62.83	150	360	P	V
802.11n HT40 CH 159 5795MHz		11590	46.76	-27.24	74	58.57	38.18	12.82	62.81	100	360	P	H
		11590	47.13	-26.87	74	58.94	38.18	12.82	62.81	100	360	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

5GHz WIFI 802.11n HT20 (LF @ 3m)

WIFI Ant. 1	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
5GHz 802.11n HT20 LF		39.7	19.23	-20.77	40	32.39	18.1	0.7	31.96	-	-	P	H
		170.65	24.47	-19.03	43.5	38.92	15.95	1.52	31.92	100	0	P	H
		316.15	22.32	-23.68	46	32.77	19.56	2.02	32.03	-	-	P	H
		503.36	21.69	-24.31	46	28	23.4	2.56	32.27	-	-	P	H
		741.01	24.32	-21.68	46	27.73	25.74	3.12	32.27	-	-	P	H
		929.19	25.55	-20.45	46	26.19	27.04	3.51	31.19	-	-	P	H
		47.46	28.68	-11.32	40	45.31	14.5	0.81	31.94	100	0	P	V
		116.33	19.83	-23.67	43.5	33.84	16.67	1.25	31.93	-	-	P	V
		161.92	20.1	-23.4	43.5	34.39	16.14	1.5	31.93	-	-	P	V
		421.88	19.59	-26.41	46	27.34	22.1	2.31	32.16	-	-	P	V
		542.16	22.27	-23.73	46	27.25	24.73	2.62	32.33	-	-	P	V
		915.61	25.01	-20.99	46	25.92	26.93	3.48	31.32	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.

Appendix D. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
802.11a	87.22	1.365	0.732	0.75kHz
5GHz 802.11n HT20	85.98	1.271	0.787	0.82kHz
5GHz 802.11n HT40	85.56	1.228	0.815	0.82kHz

802.11a



802.11n HT20



802.11n HT40