FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2013-4
FCC ID	:	IHDT56YD3
STANDARD	:	FCC Part 15 Subpart C §15.247
CLASSIFICATION	:	(DTS) Digital Transmission System

The product was received on Jul. 24, 2019 and testing was completed on Aug. 21, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Specification of Accessory 6
1.6 Modification of EUT 6
1.7 Re-use of Measured Data 7
1.8 Testing Location 8
1.9 Applicable Standards 8
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**
2.1 Carrier Frequency Channel 9
2.2 Test Mode 10
2.3 Connection Diagram of Test System 10
2.4 EUT Operation Test Setup 11
2.5 Measurement Results Explanation Example 11
3 TEST RESULT **12**
3.1 6dB and 99% Bandwidth Measurement 12
3.2 Output Power Measurement 21
3.3 Power Spectral Density Measurement 22
3.4 Conducted Band Edges and Spurious Emission Measurement 31
3.5 Radiated Band Edges and Spurious Emission Measurement 40
3.6 Antenna Requirements 44
4 LIST OF MEASURING EQUIPMENT **45**
5 UNCERTAINTY OF EVALUATION **46**
APPENDIX A. CONDUCTED TEST RESULTS
APPENDIX B. RADIATED SPURIOUS EMISSION
APPENDIX C. DUTY CYCLE PLOTS
APPENDIX D. SETUP PHOTOGRAPHS
APPENDIX E. REFERENCE REPORT

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR932901-02B	Rev. 01	Initial issue of report	Sep. 05, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(2)	6dB Bandwidth	≥ 0.5MHz	Pass	-
3.1	-	99% Bandwidth	-	Pass	-
3.2	15.247(b)(3)	Peak Output Power	≤ 30dBm	Pass	-
3.3	15.247(e)	Power Spectral Density	≤ 8dBm/3kHz	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	≤ 20dBc	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	15.209(a) & 15.247(d)	Pass	Under limit 12.22 dB at 2483.500 MHz
-	15.207	AC Conducted Emission	15.207(a)	Not Required	-
3.6	15.203 & 15.247(b)	Antenna Requirement	N/A	Pass	-
Remark: Not required means after assessing, test items are not necessary to carry out.					

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2013-4
FCC ID	IHDT56YD3
EUT supports Radios application	CDMA/GSM/WCDMA/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR / EDR / LE FM Receiver and GNSS
IMEI Code	Conducted: 357235100010413/357235100010403 Radiation: 357235100011064
HW Version	DVT2
SW Version	PPI29.80
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx/Rx Frequency Range	2402 MHz ~ 2480 MHz
Number of Channels	40
Carrier Frequency of Each Channel	40 Channel(37 hopping + 3 advertising channel)
Maximum Output Power to Antenna	Bluetooth v4.2 LE: 9.73 dBm (0.0094 W) Bluetooth v5.0 LE: 9.72 dBm (0.0094 W)
99% Occupied Bandwidth	Bluetooth v4.2 LE: 1.03MHz Bluetooth v5.0 LE: 1.04MHz
Antenna Type / Gain	Fixed Internal PIFA Antenna with gain -0.50 dBi
Type of Modulation	Bluetooth LE : GFSK

1.5 Specification of Accessory

Specification of Accessory				
AC Adapter 1	**Brand Name**	Motorola (Salom)	**Model Name**	SC-41
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc 2000mA		
AC Adapter 2	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-41
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc 2000mA		
Battery	**Brand Name**	Motorola (ATL)	**Model Name**	KR40
	Power Rating	3.8Vdc, 3500mAh (Typ)	**Type**	Li-ion, Polymer
USB Cable 1	**Brand Name**	Motorola (LiQi)	**Model Name**	L32B-053000100/ L32B-053000100L
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	**Brand Name**	Motorola (SaiBao)	**Model Name**	S32B-053000100/ S32B-053000100L
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

1.6 Modification of EUT

No modifications are made to the EUT during all test items.

1.7 Re-use of Measured Data

1.6.1 Introduction Section

This application re-uses data collected on a similar device. The subject device of this application (Model: XT2013-4, FCC ID: IHDT56YD3) is electrically identical to the reference device (Model: XT2013-1, FCC ID: IHDT56YD1) for the portions of the circuitry corresponding to the data being re-used, as treated by KDB Publication 484596 D01

1.6.2 Difference Section

For details concerning the similarity with respect to component placement, mechanical/electrical design etc., please refer to the Product Equality Declaration.

The re-used RF data includes the following bands provided in Appendix D (Sporton RF Report No. FR932901B for the reference device Model: XT2013-1, FCC ID: IHDT56YD1).

1.6.3 Reference detail Section:

Equipment Class	Reference FCC ID	Folder Test	Report Title/Section
DTS (BLE)	IHDT56YD1	Part15C(FR932901B)	Conduction sections applicable； Other test item for full test

1.6.4 Spot Check Verification Data Section

In order to confirm hardware similarity of the subject device with the reference device, all test item for full test except conduction.

Assertions concerning the similarity of these devices are based on representations by the applicant. The applicant accepts full responsibility for the validity of the similarity claim, and for the determination that verification test data are sufficient to support it.

1.8 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C §15.247
- FCC KDB 558074 D01 15.247 Meas Guidance v05r02
- ANSI C63.10-2013

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
	20	2442	-	-

2.2 Test Mode

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in three orthogonal panels, X, Y, Z. The worst cases (Y plane) were recorded in this report.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	**Data Rate / Modulation**
	Bluetooth – LE / GFSK
Conducted TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Radiated TCs	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
Remark: For Radiated Test Cases, The tests were performed with Adapter 1, Earphone 1 and USB Cable 1	

2.3 Connection Diagram of Test System



2.4 EUT Operation Test Setup

For BLE function, the engineering test program was provided and enabled to make EUT continuous transmit/receive.

For AC power line conducted emissions, the EUT was set to connect with the WLAN AP under large package sizes transmission.

2.5 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :
The spectrum analyzer offset is derived from RF cable loss.
Offset = RF cable loss.
Following shows an offset computation example with cable loss 6.0 dB.

Offset(dB) = RF cable loss(dB).
= 6.0 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.1.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.8
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 30kHz and set the Video bandwidth (VBW) = 100kHz.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

Bluetooth v4.2 LE

6 dB Bandwidth Plot on Channel 00



Date: 20.AUG.2019 11:38:21

6 dB Bandwidth Plot on Channel 19



Date: 20.AUG.2019 11:34:09

6 dB Bandwidth Plot on Channel 39



Date: 20.AUG.2019 11:35:34

Bluetooth v5.0 LE

6 dB Bandwidth Plot on Channel 00



Date: 20.AUG.2019 14:03:14

6 dB Bandwidth Plot on Channel 19



Date: 20.AUG.2019 14:07:37

6 dB Bandwidth Plot on Channel 39



Date: 20.AUG.2019 14:09:27

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

Bluetooth v4.2 LE

99% Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19



Date: 20.AUG.2019 11:34:43

99% Occupied Bandwidth Plot on Channel 39



Date: 20.AUG.2019 11:37:27

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Bluetooth v5.0 LE

99% Bandwidth Plot on Channel 00



Date: 20.AUG.2019 14:06:42

99% Occupied Bandwidth Plot on Channel 19



Date: 20.AUG.2019 14:08:38

99% Occupied Bandwidth Plot on Channel 39



Date: 20.AUG.2019 14:11:56

Note : The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5MHz, the limit for peak output power is 30dBm. If transmitting antenna of directional gain greater than 6dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

3.2.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.2.3 Test Procedures

1. The testing follows the Measurement Procedure of ANSI C63.10-2013 clause 11.9.1.3 PKPM1 Peak power meter or ANSI C63.10-2013 clause 11.9.2.3.2 Method AVGPM-G method.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.2.6 Test Result of Average Output Power (Reporting Olny)

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.

3.3.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.3.3 Test Procedures

1. The testing follows Measurement Procedure of ANSI C63.10-2013 clause 11.10.2 Method PKPSD.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100kHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.3.6 Test Result of Power Spectral Density Plots (100kHz)

Bluetooth v4.2 LE

PSD 100kHz Plot on Channel 00



Date: 20.AUG.2019 11:30:55

PSD 100kHz Plot on Channel 19



Date: 20.AUG.2019 11:34:37

PSD 100kHz Plot on Channel 39



Date: 20.AUG.2019 11:36:11

Bluetooth v5.0 LE

PSD 100kHz Plot on Channel 00



Date: 20.AUG.2019 14:03:45

PSD 100kHz Plot on Channel 19



Date: 20.AUG.2019 14:08:05

PSD 100kHz Plot on Channel 39



Date: 20.AUG.2019 14:09:52

3.3.7 Test Result of Power Spectral Density Plots (3kHz)

Bluetooth v4.2 LE

PSD 3kHz Plot on Channel 00



Date: 20.AUG.2019 11:38:35

PSD 3kHz Plot on Channel 19



Date: 20.AUG.2019 11:34:27

PSD 3kHz Plot on Channel 39



Date: 20.AUG.2019 11:35:56

Bluetooth v5.0LE

PSD 3kHz Plot on Channel 00



Date: 20.AUG.2019 14:03:31

PSD 3kHz Plot on Channel 19



Date: 20.AUG.2019 14:07:53

PSD 3kHz Plot on Channel 39



Date: 20.AUG.2019 14:09:42

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.4.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 11.13
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Bluetooth v4.2 LE

Low Band Edge Plot on Channel 00



Date: 20.AUG.2019 11:31:34

High Band Edge Plot on Channel 39



Date: 20.AUG.2019 11:37:00

Bluetooth v5.0 LE

Low Band Edge Plot on Channel 00



Date: 20.AUG.2019 14:05:41

High Band Edge Plot on Channel 39



Date: 20.AUG.2019 14:11:05

3.4.6 Test Result of Conducted Spurious Emission Plots

Bluetooth v4.2 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 20.AUG.2019 11:32:47

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 20.AUG.2019 11:32:56

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.AUG.2019 11:41:12

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.AUG.2019 11:41:20

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.AUG.2019 11:37:10

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 39



Date: 20.AUG.2019 11:37:19

Bluetooth v5.0 LE

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 20.AUG.2019 14:06:12

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 00



Date: 20.AUG.2019 14:06:20

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.AUG.2019 14:08:15

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps GFSK Channel 19



Date: 20.AUG.2019 14:08:23

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 20.AUG.2019 14:11:36

Conducted Spurious Emission Plot on Bluetooth LE 1Mbps

GFSK Channel 39



Date: 20.AUG.2019 14:11:44

3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device was measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments

The section 4.0 of List of Measuring Equipment of this test report is used for test.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 11.11 & 11.12
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
7. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
8. Use the following spectrum analyzer settings:
   (1) Span shall wide enough to fully capture the emission being measured;
   (2) Set RBW=100 kHz for f < 1 GHz; VBW ≥ RBW; Sweep = auto; Detector function = peak; Trace = max hold;
   (3) Set RBW = 1 MHz, VBW= 3MHz for f ≥ 1 GHz for peak measurement.
   For average measurement:
   - VBW = 10 Hz, when duty cycle is no less than 98 percent.
   - VBW ≥ 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.

3.6 Antenna Requirements

3.6.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	Aug. 20, 2019	Aug. 06, 2020	Conducted (TH01-KS)
Pulse Power Senor	Anritsu	MA2411B	0917070	300MHz~40GHz	Jan. 14, 2019	Aug. 20, 2019	Jan. 13, 2020	Conducted (TH01-KS)
Power Meter	Anritsu	ML2495A	1005002	50MHz Bandwidth	Jan. 14, 2019	Aug. 20, 2019	Jan. 13, 2020	Conducted (TH01-KS)
EMI Test Receiver	Keysight	N9038A	MY56400004	3Hz~8.5GHz;Max 30dBm	Oct. 12, 2018	Aug. 21, 2019	Oct. 11, 2019	Radiation (03CH04-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 16, 2019	Aug. 21, 2019	Apr. 15, 2020	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Oct. 19, 2018	Aug. 21, 2019	Oct. 17, 2019	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Aug. 21, 2019	Dec. 27, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Jan. 27, 2019	Aug. 21, 2019	Jan. 26, 2020	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Aug. 21, 2019	Jan. 04, 2020	Radiation (03CH04-KS)
Amplifier	Burgeon	BPA-530	102219	0.01MHz ~3000MHz	Nov. 19, 2018	Aug. 21, 2019	Nov. 18, 2019	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	Aug. 21, 2019	Jan. 13, 2020	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	1Ghz-18Ghz	Aug. 16, 2019	Aug. 21, 2019	Aug. 15, 2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 12, 2018	Aug. 21, 2019	Oct. 11, 2019	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Aug. 21, 2019	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Aug. 21, 2019	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Aug. 21, 2019	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.10-2013. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.0dB**

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.1dB**

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**5.1dB**

Appendix A. Conducted Test Results

Report Number : FR932901-02B

Bluetooth v4.2 LE

Bluetooth Low Energy

Test Engineer:	Weller Liu	Temperature:	21~25	°C
Test Date:	2019/8/20	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.03	0.71	0.50	Pass
BLE	1Mbps	1	19	2440	1.03	0.72	0.50	Pass
BLE	1Mbps	1	39	2480	1.03	0.74	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	9.66	30.00	-0.50	9.16	36.00	Pass
BLE	1Mbps	1	19	2440	9.73	30.00	-0.50	9.23	36.00	Pass
BLE	1Mbps	1	39	2480	8.78	30.00	-0.50	8.28	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	1Mbps	1	0	2402	2.10	9.49
BLE	1Mbps	1	19	2440	2.10	9.42
BLE	1Mbps	1	39	2480	2.10	8.58

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	N_{TX}	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	8.22	-5.95	-0.50	8.00	Pass
BLE	1Mbps	1	19	2440	8.44	-5.58	-0.50	8.00	Pass
BLE	1Mbps	1	39	2480	7.18	-6.78	-0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Report Number : FR932901-02B

Bluetooth v5.0 LE

Bluetooth Low Energy

Test Engineer:	Weller Liu	Temperature:	21~25	°C
Test Date:	2019/8/20	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	1.02	0.71	0.50	Pass
BLE	2Mbps	1	19	2440	1.03	0.72	0.50	Pass
BLE	2Mbps	1	39	2480	1.04	0.74	0.50	Pass

TEST RESULTS DATA
Peak Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	9.63	30.00	-0.50	9.13	36.00	Pass
BLE	2Mbps	1	19	2440	9.72	30.00	-0.50	9.22	36.00	Pass
BLE	2Mbps	1	39	2480	8.75	30.00	-0.50	8.25	36.00	Pass

TEST RESULTS DATA
Average Power Table
(Reporting Only)

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)	Average Conducted Power (dBm)
BLE	2Mbps	1	0	2402	2.10	9.52
BLE	2Mbps	1	19	2440	2.10	9.41
BLE	2Mbps	1	39	2480	2.10	8.67

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	8.34	-5.86	-0.50	8.00	Pass
BLE	2Mbps	1	19	2440	8.48	-5.58	-0.50	8.00	Pass
BLE	2Mbps	1	39	2480	7.25	-6.51	-0.50	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 20dBc limit.

Appendix B. Radiated Spurious Emission

Bluetooth v4.2 LE

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2383.06	44.77	-29.23	74	50.56	25.55	5.61	36.95	100	42	P	H
		2377.34	35.16	-18.84	54	40.95	25.55	5.61	36.95	100	42	A	H
	*	2402	97.85	-	-	103.58	25.6	5.63	36.96	100	42	P	H
	*	2402	97.4	-	-	103.13	25.6	5.63	36.96	100	42	A	H
		2360.44	45.45	-28.55	74	51.32	25.49	5.59	36.95	285	72	P	V
		2386.18	35.26	-18.74	54	40.99	25.6	5.63	36.96	285	72	A	V
	*	2402	93.68	-	-	99.41	25.6	5.63	36.96	285	72	P	V
	*	2402	93.19	-	-	98.92	25.6	5.63	36.96	285	72	A	V
BLE CH 39 2480MHz		2480	98.12	-	-	102.84	26.53	5.72	36.97	100	44	P	H
		2480	97.69	-	-	102.41	26.53	5.72	36.97	100	44	A	H
		2483.5	52.18	-21.82	74	56.9	26.53	5.72	36.97	100	44	P	H
		2483.5	41.55	-12.45	54	46.27	26.53	5.72	36.97	100	44	A	H
		2480	92.24	-	-	96.96	26.53	5.72	36.97	100	185	P	V
		2480	91.82	-	-	96.54	26.53	5.72	36.97	100	185	A	V
		2483.74	46.92	-27.08	74	51.64	26.53	5.72	36.97	100	185	P	V
		2483.5	37.99	-16.01	54	42.71	26.53	5.72	36.97	100	185	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4806	35.68	-38.32	74	60.13	30.88	8.43	63.76	100	360	P	H
		4806	36.24	-37.76	74	60.69	30.88	8.43	63.76	100	0	P	V
BLE CH 19 2440MHz		4878	35.65	-38.35	74	59.9	31.05	8.43	63.73	100	360	P	H
		7320	40.75	-33.25	74	59.48	35.56	10.08	64.37	100	360	P	H
		4878	36.66	-37.34	74	60.91	31.05	8.43	63.73	100	0	P	V
		7320	41.25	-32.75	74	59.98	35.56	10.08	64.37	100	0	P	V
BLE CH 39 2480MHz		4962	38.42	-35.58	74	62.4	31.27	8.44	63.69	100	360	P	H
		7440	42.97	-31.03	74	61.37	35.8	10.18	64.38	100	360	P	H
		4968	37.8	-36.2	74	61.78	31.27	8.44	63.69	100	0	P	V
		7440	42.01	-31.99	74	60.41	35.8	10.18	64.38	100	0	P	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30.97	20.78	-19.22	40	29.64	23.64	0.47	32.97	100	0	P	H
		96.93	20.78	-22.72	43.5	36.65	16.1	0.96	32.93	-	-	P	H
		225.94	21.56	-24.44	46	37.07	15.89	1.55	32.95	-	-	P	H
		579.99	21.31	-24.69	46	27.73	24.36	2.55	33.33	-	-	P	H
		767.2	24.37	-21.63	46	28.69	25.7	3.05	33.07	-	-	P	H
		914.64	24.5	-21.5	46	26.63	26.63	3.38	32.14	-	-	P	H
		34.85	25.59	-14.41	40	36.64	21.4	0.5	32.95	100	0	P	V
		96.93	26.82	-16.68	43.5	42.69	16.1	0.96	32.93	-	-	P	V
		217.21	16.23	-29.77	46	32.39	15.26	1.52	32.94	-	-	P	V
		365.62	18.15	-27.85	46	28.45	20.78	2.02	33.1	-	-	P	V
		551.86	20.95	-25.05	46	27.76	24.02	2.48	33.31	-	-	P	V
		758.47	24.94	-21.06	46	29.4	25.6	3.03	33.09	-	-	P	V
Remark	1. No other spurious found. 2. All results are PASS against limit line.												

Bluetooth v5.0 LE

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2312.73	44.68	-29.32	74	50.75	25.33	5.53	36.93	100	44	P	H
		2377.47	35.46	-18.54	54	41.25	25.55	5.61	36.95	100	44	A	H
	*	2402	98.03	-	-	103.76	25.6	5.63	36.96	100	44	P	H
	*	2402	97.61	-	-	103.34	25.6	5.63	36.96	100	44	A	H
		2364.86	45.48	-28.52	74	51.35	25.49	5.59	36.95	227	74	P	V
		2376.56	35.19	-18.81	54	40.98	25.55	5.61	36.95	227	74	A	V
	*	2402	93.98	-	-	99.71	25.6	5.63	36.96	227	74	P	V
	*	2402	93.55	-	-	99.28	25.6	5.63	36.96	227	74	A	V
BLE CH 39 2480MHz		2480	98.9	-	-	103.62	26.53	5.72	36.97	337	39	P	H
		2480	98.48	-	-	103.2	26.53	5.72	36.97	337	39	A	H
		2483.68	52.59	-21.41	74	57.31	26.53	5.72	36.97	337	39	P	H
		2483.5	41.78	-12.22	54	46.5	26.53	5.72	36.97	337	39	A	H
		2480	95.84	-	-	100.56	26.53	5.72	36.97	218	83	P	V
		2480	95.46	-	-	100.18	26.53	5.72	36.97	218	83	A	V
		2483.68	50.26	-23.74	74	54.98	26.53	5.72	36.97	218	83	P	V
		2483.5	39.87	-14.13	54	44.59	26.53	5.72	36.97	218	83	A	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
BLE CH 00 2402MHz		4806	36.06	-37.94	74	60.51	30.88	8.43	63.76	100	360	P	H
		4806	36.93	-37.07	74	61.38	30.88	8.43	63.76	100	0	P	V
BLE CH 19 2440MHz		4878	35.38	-38.62	74	59.63	31.05	8.43	63.73	100	360	P	H
		7320	40.28	-33.72	74	59.01	35.56	10.08	64.37	100	360	P	H
		4878	35.7	-38.3	74	59.95	31.05	8.43	63.73	100	0	P	V
		7320	40.9	-33.1	74	59.63	35.56	10.08	64.37	100	0	P	V
BLE CH 39 2480MHz		4962	37.79	-36.21	74	61.77	31.27	8.44	63.69	100	360	P	H
		7440	41.15	-32.85	74	59.55	35.8	10.18	64.38	100	360	P	H
		4962	36.82	-37.18	74	60.8	31.27	8.44	63.69	100	0	P	V
		7440	40.79	-33.21	74	59.19	35.8	10.18	64.38	100	0	P	V
Remark	3. No other spurious found. 4. All results are PASS against Peak and Average limit line.												

Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE LF		30.97	25.78	-14.22	40	34.64	23.64	0.47	32.97	100	0	P	H
		96.93	24.78	-18.72	43.5	40.65	16.1	0.96	32.93	-	-	P	H
		290.93	23.18	-22.82	46	35.34	19.07	1.78	33.01	-	-	P	H
		543.13	24.59	-21.41	46	31.52	23.91	2.46	33.3	-	-	P	H
		767.2	24.37	-21.63	46	28.69	25.7	3.05	33.07	-	-	P	H
		969.93	25.53	-28.47	54	26.44	27.13	3.49	31.53	-	-	P	H
		34.85	24.59	-15.41	40	35.64	21.4	0.5	32.95	100	0	P	V
		96.93	26.82	-16.68	43.5	42.69	16.1	0.96	32.93	-	-	P	V
		288.99	17.67	-28.33	46	29.88	19.03	1.77	33.01	-	-	P	V
		556.71	20.17	-25.83	46	26.91	24.08	2.5	33.32	-	-	P	V
		802.12	21.07	-24.93	46	24.79	26.11	3.15	32.98	-	-	P	V
		900.09	22.55	-23.45	46	25.02	26.5	3.35	32.32	-	-	P	V
Remark	3. No other spurious found. 4. All results are PASS against limit line.												

Note symbol

*	**Fundamental Frequency** which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is **over limit** line.
P/A	**P**eak or **A**verage
H/V	**H**orizontal or **V**ertical

A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Peak	Pol.
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
1+2		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11b CH 01 2412MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Level(dBμV/m) =

Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

2. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)

= 55.45 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 55.45(dBμV/m) – 74(dBμV/m)

= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)

= Antenna Factor(dB/m) + Cable Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)

= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)

= 43.54 (dBμV/m)

2. Over Limit(dB)

= Level(dBμV/m) – Limit Line(dBμV/m)

= 43.54(dBμV/m) – 54(dBμV/m)

= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is "PASS".

Appendix C. Duty Cycle Plots

Band	Duty Cycle(%)	T(ms)	1/T(kHz)	VBW Setting
Bluetooth – v4.2 LE	61.66	0.387	1.584	2.7kHz
Bluetooth – v5.0 LE	61.66	0.387	1.584	2.7kHz

Bluetooth – v4.2 LE



Date: 30.JUL.2019 17:55:12

Bluetooth – v5.0 LE



Appendix E. Reference Report

Please refer to Sporton report number FR932901B which is issued separately.