FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2027-3
FCC ID	:	IHDT56YH2
STANDARD	:	47 CFR Part 2, and 90(S)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Aug. 15, 2019 and completely tested on Oct. 09, 219. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator 6
1.7 Testing Site 7
1.8 Applied Standards 7
1.9 Specification of Accessory 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **9**

2.1 Test Mode 9
2.2 Connection Diagram of Test System 10
2.3 Support Unit used in test configuration and system 10
2.4 Measurement Results Explanation Example 10
2.5 Frequency List of Low/Middle/High Channels 11

3 TEST RESULT **12**

3.1 Conducted Output Power Measurement 12
3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement 13
3.3 Emissions Mask Measurement 14
3.4 Emissions Mask – Out Of Band Emissions Measurement 16
3.5 Field Strength of Spurious Radiation Measurement 17
3.6 Frequency Stability Measurement 19

4 LIST OF MEASURING EQUIPMENT **21**

5 UNCERTAINTY OF EVALUATION **22**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FW981517-01	Rev. 01	Initial issue of report	Oct. 29, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	§2.1046	Conducted Output Power	Reporting only	PASS	-
3.2	§2.1049 §90.209	Occupied Bandwidth and 26dB Bandwidth	Reporting only	PASS	-
3.3	§2.1051 §90.691	Emission masks – In-band emissions	< $50+10\log_{10}$(P[Watts])	PASS	-
3.4	§2.1051 §90.691	Emission masks – Out of band emissions	< $43+10\log_{10}$(P[Watts])	PASS	-
3.5	§2.1053 §90.691	Field Strength of Spurious Radiation	< $43+10\log_{10}$(P[Watts])	PASS	Under limit 40.86 dB at 1630.00 MHz
3.6	§2.1055 §90.213	Frequency Stability for Temperature & Voltage	< 2.5 ppm	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2027-3
FCC ID	IHDT56YH2
EUT supports Radios application	GSM/WCDMA/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/ VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver and GNSS
IMEI Code	Conducted: 35722310023693/35722310023601/35722310023701 Radiation: 357223100024352/357223100024360
HW Version	DVT2
SW Version	QPF30.71
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Product Specification subjective to this standard	
Tx Frequency	814.7 ~ 823.3 MHz
Rx Frequency	859.7 ~ 868.3 MHz
Bandwidth	1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz
Maximum Output Power to Antenna	22.92 dBm
Antenna Gain	-2.60 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum Conducted Power, Frequency Tolerance and Emission Designator

FCC Rule	System	Type of Modulation	BW	Frequency Tolerance (ppm)	Emission Designator	Maximum Conducted power(W)
Part 90S	LTE Band 26	QPSK	1.4 MHz	-	1M10G7D	0.1932
Part 90S	LTE Band 26	16QAM	1.4 MHz	-	1M10W7D	0.1644
Part 90S	LTE Band 26	64QAM	1.4 MHz	-	1M09W7D	0.1297
Part 90S	LTE Band 26	QPSK	3 MHz	-	2M74G7D	0.1936
Part 90S	LTE Band 26	16QAM	3 MHz	-	2M74W7D	0.1648
Part 90S	LTE Band 26	64QAM	3 MHz	-	2M73W7D	0.1303
Part 90S	LTE Band 26	QPSK	5 MHz	-	4M50G7D	0.1941
Part 90S	LTE Band 26	16QAM	5 MHz	-	4M50W7D	0.1671
Part 90S	LTE Band 26	64QAM	5 MHz	-	4M52W7D	0.1327
Part 90S	LTE Band 26	QPSK	10 MHz	0.0032	9M09G7D	0.1959
Part 90S	LTE Band 26	16QAM	10 MHz	-	9M03W7D	0.1675
Part 90S	LTE Band 26	64QAM	10 MHz	-	9M05W7D	0.1330
Part 90S	LTE Band 26	QPSK	15 MHz	-	13M4G7D	0.1945
Part 90S	LTE Band 26	16QAM	15 MHz	-	13M5W7D	0.1660
Part 90S	LTE Band 26	64QAM	15 MHz	-	13M4W7D	0.1312

1.7 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.8 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 90(S)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 971168 D02 Misc Rev Approv License Devices v02r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.9 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	Brand Name	Motorola(Salom)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(EU)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(UK)	Brand Name	Motorola(Salom)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(AU)	Brand Name	Motorola(Salom)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(AR)	Brand Name	Motorola(Salom)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 1(Chile)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(US)	Brand Name	Motorola(Chenyang)	Model Name	SC-51
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(EU)	Brand Name	Motorola(Chenyang)	Model Name	SC-52
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(UK)	Brand Name	Motorola(Chenyang)	Model Name	SC-53
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(AU)	Brand Name	Motorola(Chenyang)	Model Name	SC-55
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 2(AR)	Brand Name	Motorola(Chenyang)	Model Name	SC-56
	Power Rating	I/P: 100-240 Vac , 600mA; O/P: 5/9/12Vdc, 3000/2000/1500mA		
AC Adapter 3(US)	Brand Name	Motorola(Chenyang)	Model Name	SC-81
	Power Rating	I/P: 100-240 Vac , 1.2A; O/P: 5/9/15/20Vdc, 4000/4000/3000/2250mA		
AC Adapter 3(EU)	Brand Name	Motorola(Chenyang)	Model Name	SC-82
	Power Rating	I/P: 100-240 Vac , 1.2A; O/P: 5/9/15/20Vdc, 4000/4000/3000/2250mA		
Battery	Brand Name	Motorola(ATL)	Model Name	KG50
	Power Rating	3.8Vdc, 3790/4000mAh	Type	Li-ion; Polymer
Earphone 1	Brand Name	Motorola(Lianyun)	Model Name	SH38C37773
	Signal Line Type	1.11 meter, non-shielded cable, without ferrite core		
Earphone 2	Brand Name	Motorola (Cosonic)	Model Name	SH38C44959
	Signal Line Type	1.11 meter, non-shielded cable, without ferrite core		
USB Cable 1	Brand Name	Motorola(Saibao)	Model Name	SC18C24367
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	Brand Name	Motorola(Luxshare)	Model Name	SC18C24368
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 3	Brand Name	Motorola(Saibao)	Model Name	SC18C57604
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

2 Test Configuration of Equipment Under Test

2.1 Test Mode

During all testing, EUT is in link mode with base station emulator at maximum power level. The spurious emission measurements were carried out in semi-anechoic chamber with 3-meter test range, and EUT is rotated on three test planes to find out the worst emission.

Frequency range investigated for radiated emission is 30 MHz to 9000 MHz.

Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	26	v	v	v	v	v	-	v	v	v	v	v	v	v	v
26dB and 99% Bandwidth	26	v	v	v	v	v	-	v	v			v	v	v	v
Emission masks In-band emissions	26	v	v	v	v	v	-	v	v	v		v	v		v
Emission masks – Out of band emissions	26	v	v	v	v	v	-	v	v	v			v	v	v
Frequency Stability	26				v	v	-	v				v		v	
Radiated Spurious Emission	26	v	v	v	v	v	-	v		v			v	v	v
Note	1. The mark "**v** " means that this configuration is chosen for testing 2. The mark "-" means that this bandwidth is not supported. 3. LTE Band26 transmit frequency for part22 rule is 824MHz-849MHz, for part90 rule is 814MHz-824MHz. ERP over 15MHz bandwidth complies the ERP limit line of part22 rule, therefore ERP of the partial frequency spectrum which falls within part 22 also complies.														

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

The following shows an offset computation example with RF cable loss 4.2 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 4.2 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 26 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
15	Channel	26765	-	-
	Frequency	821.5	-	-
10	Channel	-	26740	-
	Frequency	-	819	-
5	Channel	26715	26740	26765
	Frequency	816.5	819	821.5
3	Channel	26705	26740	26775
	Frequency	815.5	819	822.5
1.4	Channel	26697	26740	26783
	Frequency	814.7	819	823.3

3 Test Result

3.1 Conducted Output Power Measurement

3.1.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.1.4 Test Setup



3.1.5 Test Result of Conducted Output Power

Please refer to Appendix A.

3.2 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.2.1 Description of (Occupied) Bandwidth Limitations Measurement

The 99% occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The emission bandwidth is defined as the width of the signal between two points, located at the 2 sides of the carrier frequency, outside of which all emissions are attenuated at least 26 dB below the transmitter power.

3.2.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.2.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The 26dB and 99% occupied bandwidth (BW) of the middle channel for the highest RF power with full RB sizes were measured.

3.2.4 Test Setup



3.2.5 Test Result of 99% Occupied Bandwidth and 26dB Bandwidth

Please refer to Appendix A.

3.3 Emissions Mask Measurement

3.3.1 Description of Emissions Mask Measurement

Equipment used in this licensed to EA or non-EA systems shall comply with the emission mask provisions of FCC Part 90.691.(a):

(a) Out-of-band emission requirement shall apply only to the “outer” channels included in an EA license and to spectrum adjacent to interior channels used by incumbent licensees. The emission limits are as follows:

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 $Log_{10}(f/6.1)$ decibels or 50 + 10 $Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + $10Log_{10}(P)$ decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.

3.3.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.3.3 Test Procedures

1. The EUT was connected to spectrum analyzer and base station via power divider.
2. The emissions mask of low and high channels for the highest RF powers were measured.
3. The measured RBW and the VBW set 3 times of RBW are then set in spectrum analyzer, and the RBW correction factor 10log (1% of OBW/measured RBW)(dB) was compensated, if required.
4. The test results were shown below plots with a correction offset factor including cable loss, insertion loss of power divider.

3.3.4 Test Setup



3.3.5 Test Result (Plots) of Conducted Emissions Mask

Please refer to Appendix A.

3.4 Emissions Mask – Out Of Band Emissions Measurement

3.4.1 Description of Conducted Emissions Out of band emissions measurement

The power of any emission FCC Part 90.691 (a)(2) on any frequency removed from the assigned frequency by out of the authorized bandwidth at least 43 + 10 log (P) dB. It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.4.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.4.3 Test Procedures

1. The EUT was connected to spectrum analyzer and system simulator via a power divider.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. The middle channel for the highest RF power within the transmitting frequency was measured.
4. The conducted spurious emission for the whole frequency range was taken.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

3.4.4 Test Setup



3.4.5 Test Result (Plots) of Conducted Emission

Please refer to Appendix A.

3.5 Field Strength of Spurious Radiation Measurement

3.5.1 Description of Field Strength of Spurious Radiated Measurement

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission FCC Part 90.691 on any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43+10\log_{10}(P[Watts])$ dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

3.5.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.5.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
5. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, Sweep = 500ms, Taking the record of maximum spurious emission.
6. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
7. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
8. Taking the record of output power at antenna port.
9. Repeat step 7 to step 8 for another polarization.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
13. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.5.4 Test Setup

For radiated test from 30MHz to 1GHz



For radiated test above 1GHz



3.5.5 Test Result of Field Strength of Spurious Radiated

Please refer to Appendix B.

3.6 Frequency Stability Measurement

3.6.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency according to FCC Part 90.213.

3.6.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.6.3 Test Procedures for Temperature Variation

1. The EUT was set up in the thermal chamber and connected with the base station.
2. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized for three hours. Power was applied and the maximum change in frequency was recorded within one minute.
3. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.6.4 Test Procedures for Voltage Variation

1. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
3. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the
4. battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

3.6.5 Test Setup



3.6.6 Test Result of Temperature Variation

Please refer to Appendix A.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	Sep. 30, 2019	Aug. 06, 2020	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Nov. 19, 2018	Sep. 30, 2019	Nov. 18, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 16, 2019	Oct. 09, 2019	Apr. 15, 2020	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Oct. 09, 2019	Dec. 27, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Jan. 27, 2019	Oct. 09, 2019	Jan. 26, 2020	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Oct. 09, 2019	Jan. 04, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06, 2019	Oct. 09, 2019	Aug. 05, 2020	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35-HG	2014749	18~40GHz	Jan. 14, 2019	Oct. 09, 2019	Jan. 13, 2020	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00101800-30-10P	2025788	1Ghz-18Ghz	Aug. 16, 2019	Oct. 09, 2019	Aug. 15, 2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY53270319	500MHz~26.5GHz	Oct. 12, 2018	Oct. 09, 2019	Oct. 11, 2019	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Oct. 09, 2019	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Oct. 09, 2019	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Oct. 09, 2019	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

5 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power)

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
15	1	0	QPSK	**22.89**	-	-
15	1	37		22.79		
15	1	74		22.84		
15	36	0		21.88		
15	36	20		21.98		
15	36	39		21.93		
15	75	0		21.96		
15	1	0	16-QAM	22.20		
15	1	37		22.14		
15	1	74		22.19		
15	36	0		20.91		
15	36	20		21.01		
15	36	39		20.97		
15	75	0		21.03		
15	1	0	64-QAM	21.18		
15	1	37		21.14		
15	1	74		21.18		
15	36	0		20.03		
15	36	20		20.11		
15	36	39		20.07		
15	75	0		20.12		

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	-	22.92	-
10	1	25			22.89	
10	1	49			22.77	
10	25	0			21.96	
10	25	12			21.94	
10	25	25			21.90	
10	50	0			21.92	
10	1	0	16-QAM		22.21	
10	1	25			22.24	
10	1	49			22.16	
10	25	0			21.01	
10	25	12			21.00	
10	25	25			20.95	
10	50	0			21.04	
10	1	0	64-QAM		21.21	
10	1	25			21.24	
10	1	49			21.14	
10	25	0			20.15	
10	25	12			20.12	
10	25	25			20.06	
10	50	0			20.10	
5	1	0	QPSK	22.73	22.87	22.73
5	1	12		22.70	22.88	22.71
5	1	24		22.67	22.84	22.65
5	12	0		21.76	21.91	21.78
5	12	7		21.79	21.97	21.77
5	12	13		21.77	21.88	21.73
5	25	0		21.75	21.90	21.78
5	1	0	16-QAM	22.05	22.23	22.07
5	1	12		22.05	22.19	22.06
5	1	24		22.05	22.15	21.96
5	12	0		20.85	20.98	20.86
5	12	7		20.89	21.03	20.87

5	12	13		20.85	20.99	20.83
5	25	0		20.81	20.97	20.86
5	1	0		21.05	21.23	21.13
5	1	12		21.06	21.23	21.07
5	1	24		21.04	21.20	20.98
5	12	0	**64-QAM**	19.94	20.06	19.93
5	12	7		19.98	20.12	19.96
5	12	13		19.92	20.07	19.91
5	25	0		19.94	20.08	19.97

LTE Band 26 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.73	22.87	22.71
3	1	8		22.69	22.86	22.69
3	1	14		22.67	22.84	22.66
3	8	0		21.74	21.91	21.73
3	8	4		21.81	21.91	21.76
3	8	7		21.77	21.90	21.75
3	15	0		21.76	21.90	21.74
3	1	0	16-QAM	21.95	22.15	22.05
3	1	8		21.99	22.17	22.04
3	1	14		22.00	22.14	21.95
3	8	0		20.86	21.01	20.88
3	8	4		20.90	21.04	20.91
3	8	7		20.85	21.01	20.85
3	15	0		20.86	20.96	20.84
3	1	0	64-QAM	21.02	21.13	21.05
3	1	8		21.02	21.14	21.02
3	1	14		21.02	21.15	21.00
3	8	0		19.91	20.08	19.97
3	8	4		19.94	20.11	19.97
3	8	7		19.90	20.07	19.93
3	15	0		19.93	20.08	19.91
1.4	1	0	QPSK	22.66	22.79	22.62
1.4	1	3		22.71	22.84	22.67
1.4	1	5		22.64	22.77	22.60
1.4	3	0		22.72	22.83	22.66
1.4	3	1		22.74	22.86	22.68
1.4	3	3		22.70	22.83	22.66
1.4	6	0		21.72	21.81	21.66
1.4	1	0	16-QAM	21.92	22.12	21.91
1.4	1	3		22.01	22.16	22.01
1.4	1	5		21.95	22.11	21.90
1.4	3	0		21.75	21.92	21.74
1.4	3	1		21.79	21.98	21.78

1.4	3	3		21.74	21.91	21.73
1.4	6	0		20.86	20.98	20.82
1.4	1	0		20.93	21.11	20.93
1.4	1	3		21.01	21.13	20.97
1.4	1	5		20.92	21.07	20.92
1.4	3	0	**64-QAM**	20.89	21.05	20.88
1.4	3	1		20.94	21.11	20.92
1.4	3	3		20.89	21.04	20.87
1.4	6	0		19.89	20.03	19.83

Peak-to-Average Ratio

Mode	LTE Band 26 / 15MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	-	-	-	-	PASS
Middle CH	3.39	4.49	4.96	5.74	
Highest CH	-	-	-	-	
Mode	LTE Band 26 / 15MHz				
Mod.	64QAM				Limit: 13dB
RB Size	1RB	Full RB			Result
Lowest CH	-	-			PASS
Middle CH	6.35	6.29			
Highest CH	-	-			

LTE Band 26 / 15MHz / QPSK

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 26 / 15MHz / 16QAM

Middle Channel / 1RB



Middle Channel / Full RB



LTE Band 26 / 15MHz / 64QAM

Middle Channel / 1RB



Middle Channel / Full RB



26dB Bandwidth

Mode	LTE Band 26 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.234	1.217	3.039	3.009	4.885	4.845	-	-	14.565	14.296	-	-
Middle CH	1.239	1.239	3.009	2.997	4.965	4.905	9.83	9.65	-	-	-	-
Highest CH	1.222	1.231	3.009	3.039	4.885	4.905	-	-	-	-	-	-

Mode	LTE Band 26 : 26dB BW(MHz)					
BW	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz
Mod.	64QAM	64QAM	64QAM	64QAM	64QAM	64QAM
Lowest CH	1.225	2.991	4.835	-	14.416	-
Middle CH	1.231	3.009	4.915	9.75	-	-
Highest CH	1.236	2.997	4.885	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / 64QAM



Lowest Channel / 3MHz / 64QAM



Middle Channel / 1.4MHz / 64QAM



Middle Channel / 3MHz / 64QAM



Highest Channel / 1.4MHz / 64QAM



Highest Channel / 3MHz / 64QAM



LTE Band 26

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



LTE Band 26
Lowest Channel / 15MHz / 64QAM



Occupied Bandwidth

Mode	LTE Band 26 : 99%OBW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.09	1.09	2.74	2.72	4.50	4.50	-	-	13.40	13.52	-	-
Middle CH	1.09	1.10	2.72	2.73	4.50	4.48	9.09	9.03	-	-	-	-
Highest CH	1.10	1.09	2.72	2.74	4.49	4.50	-	-	-	-	-	-

Mode	LTE Band 26 : 99%OBW(MHz)					
BW	1.4MHz	3MHz	5MHz	10MHz	15MHz	20MHz
Mod.	64QAM	64QAM	64QAM	64QAM	64QAM	64QAM
Lowest CH	1.09	2.72	4.52	-	13.37	-
Middle CH	1.08	2.71	4.49	9.05	-	-
Highest CH	1.09	2.73	4.51	-	-	-

LTE Band 26

Lowest Channel / 1.4MHz / QPSK



Lowest Channel / 1.4MHz / 16QAM



Middle Channel / 1.4MHz / QPSK



Middle Channel / 1.4MHz / 16QAM



Highest Channel / 1.4MHz / QPSK



Highest Channel / 1.4MHz / 16QAM



LTE Band 26

Lowest Channel / 3MHz / QPSK



Lowest Channel / 3MHz / 16QAM



Middle Channel / 3MHz / QPSK



Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK



Highest Channel / 3MHz / 16QAM



LTE Band 26

Lowest Channel / 5MHz / QPSK



Lowest Channel / 5MHz / 16QAM



Middle Channel / 5MHz / QPSK



Middle Channel / 5MHz / 16QAM



Highest Channel / 5MHz / QPSK



Highest Channel / 5MHz / 16QAM



LTE Band 26

Middle Channel / 10MHz / QPSK



Middle Channel / 10MHz / 16QAM



LTE Band 26

Lowest Channel / 15MHz / QPSK



Lowest Channel / 15MHz / 16QAM



LTE Band 26

Lowest Channel / 1.4MHz / 64QAM



Lowest Channel / 3MHz / 64QAM



Middle Channel / 1.4MHz / 64QAM



Middle Channel / 3MHz / 64QAM



Highest Channel / 1.4MHz / 64QAM



Highest Channel / 3MHz / 64QAM



LTE Band 26

Lowest Channel / 5MHz / 64QAM



Middle Channel / 5MHz / 64QAM



Middle Channel / 10MHz / 64QAM



Highest Channel / 5MHz / 64QAM



LTE Band 26
Lowest Channel / 15MHz / 64QAM



Conducted Band Edge

LTE Band 26 / 1.4MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 22.12 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-25.93 dBm	-48.05 dB	-12.93 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.99792 MHz	-32.80 dBm	-54.92 dB	-12.80 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.40208 MHz	-58.51 dBm	-80.63 dB	-38.51 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.57772 MHz	-49.81 dBm	-71.93 dB	-36.81 dB

Date: 30.SEP.2019 18:45:20

Highest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 22.33 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.37350 MHz	-49.11 dBm	-71.44 dB	-36.11 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.59792 MHz	-58.91 dBm	-81.24 dB	-38.91 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.00208 MHz	-33.38 dBm	-55.71 dB	-13.38 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.03953 MHz	-26.10 dBm	-48.42 dB	-13.10 dB

Date: 30.SEP.2019 18:55:28

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.55 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-29.91 dBm	-51.46 dB	-16.91 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.96458 MHz	-38.58 dBm	-60.13 dB	-18.58 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.43542 MHz	-38.88 dBm	-60.43 dB	-18.88 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.43953 MHz	-30.11 dBm	-51.66 dB	-17.11 dB

Date: 30.SEP.2019 18:48:43

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.71 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.56047 MHz	-31.19 dBm	-52.91 dB	-18.19 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.59792 MHz	-39.39 dBm	-61.11 dB	-19.39 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.00208 MHz	-40.84 dBm	-62.55 dB	-20.84 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.03953 MHz	-32.28 dBm	-54.00 dB	-19.28 dB

Date: 30.SEP.2019 18:52:05

LTE Band 26 / 1.4MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.92 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-24.11 dBm	-46.03 dB	-11.11 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.99375 MHz	-30.85 dBm	-52.77 dB	-10.85 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.40625 MHz	-60.00 dBm	-81.92 dB	-40.00 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.59804 MHz	-50.26 dBm	-72.18 dB	-37.26 dB

Date: 30.SEP.2019 18:44:13

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 22.00 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.39383 MHz	-50.25 dBm	-72.25 dB	-37.25 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.59375 MHz	-58.98 dBm	-80.98 dB	-38.98 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.00625 MHz	-33.46 dBm	-55.46 dB	-13.46 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.03953 MHz	-25.90 dBm	-47.90 dB	-12.90 dB

Date: 30.SEP.2019 18:54:20

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.65 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-29.56 dBm	-50.21 dB	-16.56 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.96458 MHz	-37.14 dBm	-57.79 dB	-17.14 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.43125 MHz	-37.51 dBm	-58.16 dB	-17.51 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.43953 MHz	-29.74 dBm	-50.39 dB	-16.74 dB

Date: 30.SEP.2019 18:47:35

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.78 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.56047 MHz	-30.16 dBm	-50.94 dB	-17.16 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.57708 MHz	-37.77 dBm	-58.54 dB	-17.77 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.03542 MHz	-38.42 dBm	-59.20 dB	-18.42 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.03953 MHz	-30.86 dBm	-51.63 dB	-17.86 dB

Date: 30.SEP.2019 18:50:58

LTE Band 26 / 1.4MHz / 64QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.71 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-25.87 dBm	-46.58 dB	-12.87 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.99792 MHz	-32.85 dBm	-53.56 dB	-12.85 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.43125 MHz	-61.14 dBm	-81.85 dB	-41.14 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.60211 MHz	-51.90 dBm	-72.61 dB	-38.90 dB

Date: 30.SEP.2019 18:46:28

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.70 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.41415 MHz	-52.15 dBm	-72.85 dB	-39.15 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.57292 MHz	-60.81 dBm	-81.51 dB	-40.81 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.00208 MHz	-33.30 dBm	-54.00 dB	-13.30 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.03953 MHz	-26.27 dBm	-46.96 dB	-13.27 dB

Date: 30.SEP.2019 18:56:35

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.56 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	813.96047 MHz	-30.83 dBm	-50.39 dB	-17.83 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	813.99375 MHz	-37.75 dBm	-57.31 dB	-17.75 dB
700.000 kHz	737.500 kHz	20.000 kHz	815.43125 MHz	-38.83 dBm	-58.39 dB	-18.83 dB
737.500 kHz	1.400 MHz	100.000 kHz	815.43953 MHz	-31.54 dBm	-51.09 dB	-18.54 dB

Date: 30.SEP.2019 18:49:50

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.76 dBm Tx Bandwidth 1.400 MHz RBW 20.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-1.400 MHz	-737.500 kHz	100.000 kHz	822.56047 MHz	-29.89 dBm	-49.65 dB	-16.89 dB
-737.500 kHz	-700.000 kHz	20.000 kHz	822.59375 MHz	-36.69 dBm	-56.45 dB	-16.69 dB
700.000 kHz	737.500 kHz	20.000 kHz	824.03542 MHz	-38.21 dBm	-57.97 dB	-18.21 dB
737.500 kHz	1.400 MHz	100.000 kHz	824.04360 MHz	-30.95 dBm	-50.70 dB	-17.95 dB

Date: 30.SEP.2019 18:53:13

LTE Band 26 / 3MHz / QPSK

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 21.90 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-17.38 dBm	-39.28 dB	-4.38 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-21.01 dBm	-42.91 dB	-1.01 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-53.72 dBm	-75.62 dB	-33.72 dB
1.538 MHz	3.000 MHz	100.000 kHz	817.04235 MHz	-49.44 dBm	-71.35 dB	-36.44 dB

Date: 30.SEP.2019 20:20:01

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.87 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	820.95765 MHz	-46.05 dBm	-67.92 dB	-33.05 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-49.59 dBm	-71.46 dB	-29.59 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-21.08 dBm	-42.95 dB	-1.08 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-17.17 dBm	-39.04 dB	-4.17 dB

Date: 30.SEP.2019 19:18:28

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.61 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-22.81 dBm	-44.42 dB	-9.81 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-26.43 dBm	-48.04 dB	-6.43 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-26.93 dBm	-48.54 dB	-6.93 dB
1.538 MHz	3.000 MHz	100.000 kHz	817.04235 MHz	-23.01 dBm	-44.62 dB	-10.01 dB

Date: 30.SEP.2019 19:11:39

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.70 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	820.95765 MHz	-23.88 dBm	-45.57 dB	-10.88 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-27.12 dBm	-48.82 dB	-7.12 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-27.39 dBm	-49.08 dB	-7.39 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-23.77 dBm	-45.46 dB	-10.77 dB

Date: 30.SEP.2019 19:15:04

LTE Band 26 / 3MHz / 16QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.52 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-17.48 dBm	-39.00 dB	-4.48 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-21.79 dBm	-43.31 dB	-1.79 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-56.28 dBm	-77.80 dB	-36.28 dB
1.538 MHz	3.000 MHz	100.000 kHz	818.02572 MHz	-51.45 dBm	-72.96 dB	-38.45 dB

Date: 30.SEP.2019 19:07:06

Highest Band Edge /1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.64 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	820.95765 MHz	-49.01 dBm	-70.65 dB	-36.01 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-53.76 dBm	-75.41 dB	-33.76 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-22.17 dBm	-43.81 dB	-2.17 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-18.98 dBm	-40.62 dB	-5.98 dB

Date: 30.SEP.2019 19:17:20

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.68 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-26.08 dBm	-46.77 dB	-13.08 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-29.76 dBm	-50.45 dB	-9.76 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-29.89 dBm	-50.58 dB	-9.89 dB
1.538 MHz	3.000 MHz	100.000 kHz	817.04235 MHz	-26.23 dBm	-46.92 dB	-13.23 dB

Date: 30.SEP.2019 19:10:30

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.77 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	820.95765 MHz	-26.83 dBm	-47.61 dB	-13.83 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-30.12 dBm	-50.90 dB	-10.12 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-30.17 dBm	-50.94 dB	-10.17 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-26.51 dBm	-47.28 dB	-13.51 dB

Date: 30.SEP.2019 19:13:55

LTE Band 26 / 3MHz / 64QAM

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.32 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-20.86 dBm	-41.18 dB	-7.86 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-25.18 dBm	-45.50 dB	-5.18 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-61.55 dBm	-81.88 dB	-41.55 dB
1.538 MHz	3.000 MHz	100.000 kHz	818.01702 MHz	-53.10 dBm	-73.42 dB	-40.10 dB

Date: 30.SEP.2019 19:09:22

Highest Band Edge /1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.66 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	819.99168 MHz	-53.81 dBm	-74.47 dB	-40.81 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-60.98 dBm	-81.64 dB	-40.98 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-25.34 dBm	-46.00 dB	-5.34 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-20.90 dBm	-41.56 dB	-7.90 dB

Date: 30.SEP.2019 19:19:37

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.68 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	813.95765 MHz	-28.68 dBm	-48.36 dB	-15.68 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	813.99525 MHz	-32.08 dBm	-51.76 dB	-12.08 dB
1.500 MHz	1.538 MHz	30.000 kHz	817.00475 MHz	-31.73 dBm	-51.41 dB	-11.73 dB
1.538 MHz	3.000 MHz	100.000 kHz	817.04235 MHz	-28.30 dBm	-47.98 dB	-15.30 dB

Date: 30.SEP.2019 19:12:47

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.82 dBm Tx Bandwidth 3.000 MHz RBW 30.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-3.000 MHz	-1.538 MHz	100.000 kHz	820.95765 MHz	-28.25 dBm	-48.07 dB	-15.25 dB
-1.538 MHz	-1.500 MHz	30.000 kHz	820.99525 MHz	-31.98 dBm	-51.79 dB	-11.98 dB
1.500 MHz	1.538 MHz	30.000 kHz	824.00475 MHz	-31.47 dBm	-51.29 dB	-11.47 dB
1.538 MHz	3.000 MHz	100.000 kHz	824.04235 MHz	-27.91 dBm	-47.73 dB	-14.91 dB

Date: 30.SEP.2019 19:16:12

LTE Band 26 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.74 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-24.53 dBm	-46.28 dB	-11.53 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-25.58 dBm	-47.33 dB	-5.58 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-60.12 dBm	-81.86 dB	-40.12 dB
2.538 MHz	5.000 MHz	100.000 kHz	820.79761 MHz	-51.39 dBm	-73.13 dB	-38.39 dB

Date: 30.SEP.2019 19:30:31

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.48 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	817.17343 MHz	-52.17 dBm	-73.65 dB	-39.17 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-60.39 dBm	-81.87 dB	-40.39 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-25.53 dBm	-47.01 dB	-5.53 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-24.64 dBm	-46.11 dB	-11.64 dB

Date: 30.SEP.2019 19:40:46

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.65 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-27.91 dBm	-49.56 dB	-14.91 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-29.41 dBm	-51.05 dB	-9.41 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-29.68 dBm	-51.33 dB	-9.68 dB
2.538 MHz	5.000 MHz	100.000 kHz	819.04524 MHz	-28.18 dBm	-49.83 dB	-15.18 dB

Date: 30.SEP.2019 19:33:56

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 21.59 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	818.95476 MHz	-29.09 dBm	-50.68 dB	-16.09 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-30.33 dBm	-51.92 dB	-10.33 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-30.49 dBm	-52.08 dB	-10.49 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-29.42 dBm	-51.02 dB	-16.42 dB

Date: 30.SEP.2019 19:37:21

LTE Band 26 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 21.50 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-24.06 dBm	-45.56 dB	-11.06 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-25.31 dBm	-46.80 dB	-5.31 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-62.10 dBm	-83.59 dB	-42.10 dB
2.538 MHz	5.000 MHz	100.000 kHz	820.81209 MHz	-51.67 dBm	-73.17 dB	-38.67 dB

Date: 30.SEP.2019 19:29:23

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 21.31 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	817.17343 MHz	-53.25 dBm	-74.57 dB	-40.25 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-61.91 dBm	-83.22 dB	-41.91 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-26.50 dBm	-47.82 dB	-6.50 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-25.68 dBm	-47.00 dB	-12.68 dB

Date: 30.SEP.2019 19:39:37

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.65 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-31.75 dBm	-52.40 dB	-18.75 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-32.97 dBm	-53.62 dB	-12.97 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-33.50 dBm	-54.15 dB	-13.50 dB
2.538 MHz	5.000 MHz	100.000 kHz	819.04524 MHz	-31.86 dBm	-52.52 dB	-18.86 dB

Date: 30.SEP.2019 19:32:48

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 20.68 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	818.95476 MHz	-32.16 dBm	-52.84 dB	-19.16 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-33.48 dBm	-54.16 dB	-13.48 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-33.94 dBm	-54.62 dB	-13.94 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-32.64 dBm	-53.32 dB	-19.64 dB

Date: 30.SEP.2019 19:36:13

LTE Band 26 / 5MHz / 64QAM

Lowest Band Edge / 1RB



Spectrum Emission Mask Standard: None
Tx Power 20.34 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-27.12 dBm	-47.47 dB	-14.12 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-27.82 dBm	-48.16 dB	-7.82 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-63.67 dBm	-84.01 dB	-43.67 dB
2.538 MHz	5.000 MHz	100.000 kHz	820.82657 MHz	-53.59 dBm	-73.94 dB	-40.59 dB

Date: 30.SEP.2019 19:31:40

Highest Band Edge / 1 RB



Spectrum Emission Mask Standard: None
Tx Power 20.50 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	817.17343 MHz	-54.95 dBm	-75.45 dB	-41.95 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-63.60 dBm	-84.10 dB	-43.60 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-27.30 dBm	-47.81 dB	-7.30 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-26.32 dBm	-46.82 dB	-13.32 dB

Date: 30.SEP.2019 19:41:54

Lowest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.64 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	813.95476 MHz	-32.72 dBm	-52.36 dB	-19.72 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	813.99050 MHz	-34.36 dBm	-54.00 dB	-14.36 dB
2.500 MHz	2.538 MHz	50.000 kHz	819.00950 MHz	-34.58 dBm	-54.22 dB	-14.58 dB
2.538 MHz	5.000 MHz	100.000 kHz	819.04524 MHz	-33.12 dBm	-52.76 dB	-20.12 dB

Date: 30.SEP.2019 19:35:04

Highest Band Edge / Full RB



Spectrum Emission Mask Standard: None
Tx Power 19.75 dBm Tx Bandwidth 5.000 MHz RBW 50.000 kHz

Range Low	Range Up	RBW	Frequency	Power Abs	Power Rel	ΔLimit
-5.000 MHz	-2.538 MHz	100.000 kHz	818.95476 MHz	-32.72 dBm	-52.46 dB	-19.72 dB
-2.538 MHz	-2.500 MHz	50.000 kHz	818.99050 MHz	-34.43 dBm	-54.17 dB	-14.43 dB
2.500 MHz	2.538 MHz	50.000 kHz	824.00950 MHz	-34.60 dBm	-54.35 dB	-14.60 dB
2.538 MHz	5.000 MHz	100.000 kHz	824.04524 MHz	-33.15 dBm	-52.90 dB	-20.15 dB

Date: 30.SEP.2019 19:38:29