



# FCC Test Report

**APPLICANT** : Motorola Mobility LLC  
**EQUIPMENT** : Mobile Cellular Phone  
**BRAND NAME** : Motorola  
**MODEL NAME** : XT2045-1  
**FCC ID** : IHDT56YK2  
**STANDARD** : 47 CFR Part 15 Subpart B  
**CLASSIFICATION** : Certification

The product was received on Oct. 21, 2019 and testing was completed on Nov. 02, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

---

Reviewed by: Jason Jia / Supervisor

James Huang

---

Approved by: James Huang / Manager



***Sporton International (Kunshan) Inc.***

***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300  
People's Republic of China***



## TABLE OF CONTENTS

|                                                               |           |
|---------------------------------------------------------------|-----------|
| <b>REVISION HISTORY .....</b>                                 | <b>3</b>  |
| <b>SUMMARY OF TEST RESULT .....</b>                           | <b>4</b>  |
| <b>1. GENERAL DESCRIPTION .....</b>                           | <b>5</b>  |
| 1.1. Applicant.....                                           | 5         |
| 1.2. Manufacturer .....                                       | 5         |
| 1.3. Product Feature of Equipment Under Test .....            | 5         |
| 1.4. Product Specification of Equipment Under Test .....      | 6         |
| 1.5. Specification of Accessory .....                         | 7         |
| 1.6. Modification of EUT .....                                | 8         |
| 1.7. Test Location .....                                      | 8         |
| 1.8. Test Software .....                                      | 8         |
| 1.9. Applicable Standards .....                               | 8         |
| <b>2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>    | <b>9</b>  |
| 2.1. Test Mode .....                                          | 9         |
| 2.2. Connection Diagram of Test System .....                  | 11        |
| 2.3. Support Unit used in test configuration and system ..... | 12        |
| 2.4. EUT Operation Test Setup .....                           | 12        |
| <b>3. TEST RESULT .....</b>                                   | <b>13</b> |
| 3.1. Test of AC Conducted Emission Measurement .....          | 13        |
| 3.2. Test of Radiated Emission Measurement .....              | 17        |
| <b>4. LIST OF MEASURING EQUIPMENT .....</b>                   | <b>21</b> |
| <b>5. UNCERTAINTY OF EVALUATION .....</b>                     | <b>22</b> |
| <b>APPENDIX A. SETUP PHOTOGRAPHS</b>                          |           |



## REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION             | ISSUED DATE   |
|------------|---------|-------------------------|---------------|
| FC902103   | Rev. 01 | Initial issue of report | Dec. 06, 2019 |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |
|            |         |                         |               |

## SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description           | Limit           | Result | Remark                                  |
|----------------|----------|-----------------------|-----------------|--------|-----------------------------------------|
| 3.1            | 15.107   | AC Conducted Emission | < 15.107 limits | PASS   | Under limit<br>9.83 dB at<br>0.179 MHz  |
| 3.2            | 15.109   | Radiated Emission     | < 15.109 limits | PASS   | Under limit<br>5.56 dB at<br>39.700 MHz |

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.



## 1. General Description

### 1.1. Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.2. Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

### 1.3. Product Feature of Equipment Under Test

| Product Feature                 |                                                                                                                                                           |
|---------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Equipment                       | Mobile Cellular Phone                                                                                                                                     |
| Brand Name                      | Motorola                                                                                                                                                  |
| Model Name                      | XT2045-1                                                                                                                                                  |
| FCC ID                          | IHDT56YK2                                                                                                                                                 |
| EUT supports Radios application | GSM/WCDMA/LTE<br>WLAN 2.4GHz 802.11b/g/n HT20<br>Bluetooth BR/EDR/LE<br>GNSS/FM Receiver                                                                  |
| IMEI Code                       | Conduction:<br>359107100039759/359107100039767 for Sample 1<br>Radiation:<br>359107100039874/359107100039882 for Sample 1<br>359108100006376 for Sample 2 |
| HW Version                      | DVT2                                                                                                                                                      |
| SW Version                      | QPJ30.36                                                                                                                                                  |
| EUT Stage                       | Identical Prototype                                                                                                                                       |

**Remark:**

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the sample 1 is dual SIM slot, sample 2 is single SIM slot. According to the difference, we choose sample 1 to perform full test, sample 2 to verify the worst case of Radiation.

## 1.4. Product Specification of Equipment Under Test

| Standards-related Product Specification |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Tx Frequency</b>                     | GSM850: 824.2 MHz ~ 848.8 MHz<br>GSM1900: 1850.2 MHz ~ 1909.8MHz<br>WCDMA Band V: 826.4 MHz ~ 846.6 MHz<br>WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz<br>WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz<br>LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz<br>LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz<br>LTE Band 5 : 824.7 MHz ~ 848.3 MHz<br>LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz<br>LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz<br>802.11b/g/n: 2412 MHz ~ 2462 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz                                                       |
| <b>Rx Frequency</b>                     | GSM850: 869.2 MHz ~ 893.8 MHz<br>GSM1900: 1930.2 MHz ~ 1989.8 MHz<br>WCDMA Band V: 871.4 MHz ~ 891.6 MHz<br>WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz<br>WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz<br>LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz<br>LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz<br>LTE Band 5 : 869.7 MHz ~ 893.3 MHz<br>LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz<br>LTE Band 66 : 2110.7 MHz~ 2179.3 MHz<br>802.11b/g/n: 2412 MHz ~ 2462 MHz<br>Bluetooth: 2402 MHz ~ 2480 MHz<br>GNSS : 1559 MHz ~ 1610 MHz<br>FM: 88 MHz - 108 MHz |
| <b>Antenna Type</b>                     | WWAN : Loop Antenna<br>WLAN : PIFA Antenna<br>Bluetooth : PIFA Antenna<br>GNSS: PIFA Antenna<br>FM: External Earphone Antenna                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>Type of Modulation</b>               | GSM: GMSK<br>GPRS: GMSK<br>EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK<br>WCDMA : BPSK (Uplink)<br>HSDPA/DC-HSDPA : QPSK (Uplink)<br>HSUPA : QPSK (Uplink)<br>HSPA+ : 16QAM (16QAM uplink is not supported)<br>DC-HSDPA : 64QAM<br>LTE: QPSK / 16QAM / 64QAM<br>802.11b : DSSS (DBPSK / DQPSK / CCK)<br>802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM)<br>Bluetooth LE : GFSK<br>Bluetooth (1Mbps) : GFSK<br>Bluetooth (2Mbps) : $\pi/4$ -DQPSK<br>Bluetooth (3Mbps) : 8-DPSK<br>GNSS : BPSK<br>FM                                    |

**Note:** GNSS Rx = GLONASS + GPS + Galileo



## 1.5. Specification of Accessory

| Specification of Accessory |                  |                                                     |            |                 |
|----------------------------|------------------|-----------------------------------------------------|------------|-----------------|
| AC Adapter 1(US)           | Brand Name       | Motorola (Acbel)                                    | Model Name | SC-41           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 1(EU)           | Brand Name       | Motorola (Acbel)                                    | Model Name | SC-42           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 1(UK)           | Brand Name       | Motorola (Acbel)                                    | Model Name | SC-43           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 1(AU)           | Brand Name       | Motorola (Acbel)                                    | Model Name | SC-45           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 1(AR)           | Brand Name       | Motorola (Acbel)                                    | Model Name | SC-46           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 2(US)           | Brand Name       | Motorola(Chenyang)                                  | Model Name | SC-41           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 2(EU)           | Brand Name       | Motorola(Chenyang)                                  | Model Name | SC-42           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 2(AR)           | Brand Name       | Motorola(Chenyang)                                  | Model Name | SC-46           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 3 (Chile)       | Brand Name       | Motorola (Salom)                                    | Model Name | SC-42           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 3(BR)           | Brand Name       | Motorola(Salom)                                     | Model Name | SC-47           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 3(BR)           | Brand Name       | Motorola(Salom/Flex)                                | Model Name | SC-47           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| AC Adapter 4(BR)           | Brand Name       | Motorola(Cliptech/Tenpao)                           | Model Name | SC-47           |
|                            | Power Rating     | I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA  |            |                 |
| Battery                    | Brand Name       | Motorola (ATL)                                      | Model Name | KR40            |
|                            | Power Rating     | 3.8Vdc, 4000mAh                                     | Type       | Li-ion, Polymer |
| Earphone 1                 | Brand Name       | Motorola(Lianyun)                                   | Model Name | LYM500B-36C-001 |
|                            | Signal Line Type | 1.1 meter, non-shielded cable, without ferrite core |            |                 |
| Earphone 2                 | Brand Name       | Motorola(Lianyun)                                   | Model Name | SH38C37773      |
|                            | Signal Line Type | 1.1 meter, non-shielded cable, without ferrite core |            |                 |
| Earphone 3                 | Brand Name       | Motorola(Cosonic)                                   | Model Name | SH38C44959      |
|                            | Signal Line Type | 1.1 meter, non-shielded cable, without ferrite core |            |                 |
| USB Cable 1                | Brand Name       | Motorola ( LiQi)                                    | Model Name | L52B-053000100  |
|                            | Signal Line Type | 1.0 meter, shielded cable, without ferrite core     |            |                 |
| USB Cable 2                | Brand Name       | Motorola (SaiBao)                                   | Model Name | S52B-053000100  |
|                            | Signal Line Type | 1.0 meter, shielded cable, without ferrite core     |            |                 |
| USB Cable 3                | Brand Name       | Motorola (I SHENG)                                  | Model Name | SC18C28955      |
|                            | Signal Line Type | 1.0 meter, shielded cable, without ferrite core     |            |                 |

## 1.6. Modification of EUT

No modifications are made to the EUT during all test items.

## 1.7. Test Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

|                           |                                                                                                                                                                          |                            |                                       |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------|---------------------------------------|
| <b>Test Firm</b>          | Sporton International (Kunshan) Inc.                                                                                                                                     |                            |                                       |
| <b>Test Site Location</b> | No. 1098, Pengxi North Road, Kunshan Economic Development Zone<br>Jiangsu Province 215300 People's Republic of China<br>TEL : +86-512-57900158<br>FAX : +86-512-57900958 |                            |                                       |
| <b>Test Site No.</b>      | <b>Sporton Site No.</b>                                                                                                                                                  | <b>FCC Designation No.</b> | <b>FCC Test Firm Registration No.</b> |
|                           | CO01-KS<br>03CH02-KS                                                                                                                                                     | CN1257                     | 314309                                |

## 1.8. Test Software

| Item | Site      | Manufacture | Name | Version      |
|------|-----------|-------------|------|--------------|
| 1.   | 03CH02-KS | AUDIX       | E3   | 6.2009-8-24a |
| 2.   | CO01-KS   | AUDIX       | E3   | 6.2009-8-24  |

## 1.9. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 15 Subpart B
- ♦ ANSI C63.4-2014

**Remark:** All test items were verified and recorded according to the standards and without any deviation during the test.

## 2. Test Configuration of Equipment Under Test

### 2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

| Test Items            | Function Type                                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| AC Conducted Emission | Mode 1: GSM850 Idle (Middle CH) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Earphone 1 + USB Cable 1(Charging from Adapter 1) for Sample 1    |
|                       | Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + Earphone 2 + USB Cable 2(Charging from Adapter 2) for Sample 1        |
|                       | Mode 3: LTE Band 5 Idle (Low CH) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + Earphone 3 + USB Cable 3(Charging from Adapter 3) for Sample 1          |
|                       | Mode 4: LTE Band 5 Idle (High CH) + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx (98MHz) + Earphone 2 + USB Cable 2(Charging from Adapter 4) for Sample 1 |
|                       | Mode 5: LTE Band 2 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 2 + USB Cable 1(Data Link with Notebook) for Sample 1                 |
|                       | Mode 6: LTE Band 4 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 2 + USB Cable 2(Data Link with Notebook) for Sample 1                 |
|                       | Mode 7: LTE Band 7 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 2 + USB Cable 3(Data Link with Notebook) for Sample 1                 |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Radiated Emissions                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | <p>Mode 1: GSM850 Idle (Middle CH) + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Rear) + Earphone 1 + USB Cable 1(Charging from Adapter 1) for Sample 1</p> <p>Mode 2: WCDMA Band II Idle + Bluetooth Idle + WLAN (2.4G) Idle + Camera(Front) + Earphone 2 + USB Cable 2(Charging from Adapter 2) for Sample 1</p> <p>Mode 3: LTE Band 5 Idle (Low CH) + Bluetooth Idle + WLAN (2.4G) Idle + MPEG4 + Earphone 3 + USB Cable 3(Charging from Adapter 3) for Sample 1</p> <p>Mode 4: LTE Band 5 Idle (High CH) + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx (88MHz) + Earphone 1 + USB Cable 1(Charging from Adapter 4) for Sample 1</p> <p>Mode 5: LTE Band 2 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 1 + USB Cable 1(Data Link with Notebook) for Sample 1</p> <p>Mode 6: LTE Band 4 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 1 + USB Cable 2(Data Link with Notebook) for Sample 1</p> <p>Mode 7: LTE Band 7 Idle + Bluetooth Idle + WLAN (2.4G) Idle + GNSS Rx + Earphone 1 + USB Cable 3(Data Link with Notebook) for Sample 1</p> <p>Mode 8: LTE Band 5 Idle (High CH) + Bluetooth Idle + WLAN (2.4G) Idle + FM Rx (88MHz) + Earphone 1 + USB Cable 1(Charging from Adapter 4) for Sample 2</p> |
| <p><b>Remark:</b></p> <ol style="list-style-type: none"> <li>1. The worst case of AC is mode 4; only the test data of this mode is reported.</li> <li>2. The worst case of RE is mode 4; only the test data of this mode is reported.</li> <li>3. Data Link with Notebook means data application transferred mode between EUT and Notebook.</li> <li>4. Pre-scanned Low/Middle/High channel for GSM 850/WCDMA B5/LTE Band 5 and FM Rx, the worst channel was recorded in this report.</li> </ol> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |

## 2.2.Connection Diagram of Test System



The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application

## 2.3. Support Unit used in test configuration and system

| Item | Equipment               | Trade Name | Model Name   | FCC ID        | Data Cable     | Power Cord                                                 |
|------|-------------------------|------------|--------------|---------------|----------------|------------------------------------------------------------|
| 1.   | System Simulator        | Anritsu    | MT8820C      | N/A           | N/A            | Unshielded, 1.8m                                           |
| 2.   | System Simulator        | R&S        | CMU 200      | N/A           | N/A            | Unshielded, 1.8 m                                          |
| 3.   | Vector Signal Generator | R&S        | SMBV100A     | 258305        | N/A            | N/A                                                        |
| 4.   | WLAN AP                 | TP-Link    | TL-WDR5600   | N/A           | N/A            | Unshielded, 1.8m                                           |
| 5.   | WLAN AP                 | D-link     | DIR-655      | KA21R655B1    | N/A            | Unshielded, 1.8m                                           |
| 6.   | WLAN AP                 | ASUS       | AC66U        | N/A           | N/A            | Unshielded, 1.8m                                           |
| 7.   | Bluetooth Earphone      | Lenovo     | LBH308       | N/A           | N/A            | N/A                                                        |
| 8.   | Bluetooth Earphone      | Xiaomi     | LYEJ02LM     | N/A           | N/A            | N/A                                                        |
| 9.   | Notebook                | Lenovo     | G480         | QDS-BRCM1050I | N/A            | AC I/P:<br>Unshielded, 1.8 m<br>DC O/P:<br>Shielded, 1.8 m |
| 10.  | Notebook                | Dell       | Latitude3440 | N/A           | N/A            | AC I/P:<br>Unshielded, 1.8 m<br>DC O/P:<br>Shielded, 1.8 m |
| 11.  | Hard Disk               | Lenovo     | F310         | DoC           | Shielded, 1.2m | N/A                                                        |
| 12.  | SD Card                 | Kingston   | 8GB          | N/A           | N/A            | N/A                                                        |
| 13.  | SD Card                 | SanDisk    | Uitra        | N/A           | N/A            | N/A                                                        |

## 2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on camera to capture images.
4. Turn on MPEG4 function.
5. Turn on FM receiver function to make the EUT receive continuous signals from FM station.
6. Turn on camera to capture images.

### 3. Test Result

#### 3.1. Test of AC Conducted Emission Measurement

##### 3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B Limit>

| Frequency of emission<br>(MHz) | Conducted limit (dBuV) |           |
|--------------------------------|------------------------|-----------|
|                                | Quasi-peak             | Average   |
| 0.15-0.5                       | 66 to 56*              | 56 to 46* |
| 0.5-5                          | 56                     | 46        |
| 5-30                           | 60                     | 50        |

\*Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

##### 3.1.3 Test Procedure


1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.1.4 Test Setup






## 3.1.5 Test Result of AC Conducted Emission





|                 |               |                     |            |
|-----------------|---------------|---------------------|------------|
| Test Engineer : | Amos Zhang    | Temperature :       | 25.3~26.2℃ |
|                 |               | Relative Humidity : | 38~40%     |
| Test Voltage :  | 120Vac / 60Hz | Phase :             | Neutral    |



Site : CO01-KS  
Condition : FCC CLASS-B LISN-N-181119-060105 NEUTRAL

mode : Mode 4  
: 359107100039759/359107100039767 #8

|     | Freq   | Level | Over   | Limit | Read  | LISN   | Cable |         |
|-----|--------|-------|--------|-------|-------|--------|-------|---------|
|     | MHz    | dBuV  | Limit  | Line  | Level | Factor | Loss  | Remark  |
|     |        |       | dB     | dBuV  | dBuV  | dB     | dB    |         |
| 1   | 0.192  | 41.15 | -22.78 | 63.93 | 30.60 | 0.17   | 10.38 | QP      |
| 2   | 0.192  | 26.05 | -27.88 | 53.93 | 15.50 | 0.17   | 10.38 | Average |
| 3 * | 0.266  | 45.99 | -15.26 | 61.25 | 35.51 | 0.16   | 10.32 | QP      |
| 4   | 0.266  | 31.79 | -19.46 | 51.25 | 21.31 | 0.16   | 10.32 | Average |
| 5   | 0.552  | 37.48 | -18.52 | 56.00 | 27.09 | 0.15   | 10.24 | QP      |
| 6   | 0.552  | 27.18 | -18.82 | 46.00 | 16.79 | 0.15   | 10.24 | Average |
| 7   | 0.675  | 39.28 | -16.72 | 56.00 | 28.90 | 0.14   | 10.24 | QP      |
| 8   | 0.675  | 27.88 | -18.12 | 46.00 | 17.50 | 0.14   | 10.24 | Average |
| 9   | 0.775  | 35.28 | -20.72 | 56.00 | 24.90 | 0.14   | 10.24 | QP      |
| 10  | 0.775  | 23.98 | -22.02 | 46.00 | 13.60 | 0.14   | 10.24 | Average |
| 11  | 13.337 | 40.01 | -19.99 | 60.00 | 29.49 | 0.14   | 10.38 | QP      |
| 12  | 13.337 | 29.41 | -20.59 | 50.00 | 18.89 | 0.14   | 10.38 | Average |

Note:

1. Level(dBμV) = Read Level(dBμV) + LISN Factor(dB) + Cable Loss(dB)
2. Over Limit(dB) = Level(dBμV) – Limit Line(dBμV)

## 3.2. Test of Radiated Emission Measurement

### 3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

**<Class B Limit>**

| Frequency<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|--------------------|--------------------------------------|----------------------------------|
| 30 – 88            | 100                                  | 3                                |
| 88 – 216           | 150                                  | 3                                |
| 216 - 960          | 200                                  | 3                                |
| Above 960          | 500                                  | 3                                |

### 3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

### 3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

### 3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz






## 3.2.5. Test Result of Radiated Emission





|                 |                                                                                                                    |                     |          |
|-----------------|--------------------------------------------------------------------------------------------------------------------|---------------------|----------|
| Test Engineer : | Carl Ni                                                                                                            | Temperature :       | 21~22°C  |
|                 |                                                                                                                    | Relative Humidity : | 41~42%   |
| Test Distance : | 3m                                                                                                                 | Polarization :      | Vertical |
| Remark :        | #3 is Base station (FM option) signal which can be ignored.<br>#7 is system simulator signal which can be ignored. |                     |          |



Site : 03CH02-KS  
Condition : FCC CLASS-B 3m LF 49922-3M VERTICAL  
Mode : 4  
IMEI : 359107100039874 359107100039882 #4

|    | Freq     | Level  | Over   | Limit  | ReadAntenna | Cable  | Preamp | A/Pos  | T/Pos | Remark |
|----|----------|--------|--------|--------|-------------|--------|--------|--------|-------|--------|
|    | MHz      | dBuV/m | Limit  | Line   | Level       | Factor | Loss   | Factor |       |        |
|    |          |        | dB     | dBuV/m | dBuV        | dB/m   | dB     | dB     | cm    | deg    |
| 1  | 39.700   | 34.44  | -5.56  | 40.00  | 46.00       | 19.70  | 0.70   | 31.96  | 100   | 0 Peak |
| 2  | 56.190   | 27.42  | -12.58 | 40.00  | 45.65       | 12.86  | 0.85   | 31.94  | ---   | ---    |
| 3  | 88.200   | 34.79  |        |        | 50.86       | 14.76  | 1.09   | 31.92  | ---   | ---    |
| 4  | 97.900   | 26.81  | -16.69 | 43.50  | 41.64       | 15.96  | 1.14   | 31.93  | ---   | ---    |
| 5  | 213.330  | 29.89  | -13.61 | 43.50  | 44.04       | 16.07  | 1.70   | 31.92  | ---   | ---    |
| 6  | 303.540  | 25.69  | -20.31 | 46.00  | 36.31       | 19.40  | 1.99   | 32.01  | ---   | ---    |
| 7  | 889.420  | 39.80  |        |        | 38.68       | 29.22  | 3.43   | 31.53  | ---   | ---    |
| 8  | 950.530  | 31.14  | -14.86 | 46.00  | 27.68       | 30.89  | 3.55   | 30.98  | ---   | ---    |
| 9  | 3536.000 | 43.86  | -30.14 | 74.00  | 36.13       | 32.62  | 6.99   | 31.88  | ---   | ---    |
| 10 | 4984.000 | 45.05  | -28.95 | 74.00  | 34.08       | 33.87  | 8.36   | 31.26  | ---   | ---    |
| 11 | 5368.000 | 45.79  | -28.21 | 74.00  | 33.87       | 34.35  | 8.66   | 31.09  | ---   | ---    |
| 12 | 6824.000 | 45.24  | -28.76 | 74.00  | 31.51       | 35.30  | 9.89   | 31.46  | ---   | ---    |
| 13 | 7280.000 | 46.40  | -27.60 | 74.00  | 32.11       | 35.80  | 10.13  | 31.64  | ---   | ---    |
| 14 | 8048.000 | 45.99  | -28.01 | 74.00  | 30.88       | 36.14  | 11.01  | 32.04  | ---   | ---    |

Note:

- Level(dBμV/m) = Read Level(dBμV) + Antenna Factor(dB/m) + Cable Loss(dB) - Preamp Factor(dB)
- Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)



## 4. List of Measuring Equipment

| Instrument                        | Manufacturer | Model No. | Serial No.   | Characteristics         | Calibration Date | Test Date     | Due Date      | Remark                |
|-----------------------------------|--------------|-----------|--------------|-------------------------|------------------|---------------|---------------|-----------------------|
| EMI Receiver                      | R&S          | ESC17     | 100768       | 9kHz~7GHz;              | Apr. 16, 2019    | Nov. 02, 2019 | Apr. 15, 2020 | Conduction (CO01-KS)  |
| AC LISN                           | MessTec      | AN3016    | 060103       | 9kHz~30MHz              | Oct. 11, 2019    | Nov. 02, 2019 | Oct. 10, 2020 | Conduction (CO01-KS)  |
| AC LISN (for auxiliary equipment) | MessTec      | AN3016    | 060105       | 9kHz~30MHz              | Nov. 19, 2018    | Nov. 02, 2019 | Nov. 18, 2019 | Conduction (CO01-KS)  |
| AC Power Source                   | Chroma       | 61602     | ABP000000811 | AC 0V~300V, 45Hz~1000Hz | Oct. 11, 2019    | Nov. 02, 2019 | Oct. 10, 2020 | Conduction (CO01-KS)  |
| EMI Test Receiver                 | R&S          | ESR7      | 101403       | 9kHz~7GHz;Max 30dBm     | Aug. 06, 2019    | Nov. 02, 2019 | Aug. 05, 2020 | Radiation (03CH02-KS) |
| EXA Spectrum Analyzer             | Keysight     | N9010A    | MY55150208   | 10Hz~44G,MAX 30dB       | Apr. 15, 2019    | Nov. 02, 2019 | Apr. 16, 2020 | Radiation (03CH02-KS) |
| Bilog Antenna                     | TeseQ        | CBL6111D  | 49922        | 30MHz~1GHz              | May 30, 2019     | Nov. 02, 2019 | May 29, 2020  | Radiation (03CH02-KS) |
| Double Ridge Horn Antenna         | ETS-Lindgren | 3117      | 75959        | 1GHz~18GHz              | Jan. 27, 2019    | Nov. 02, 2019 | Jan. 26, 2020 | Radiation (03CH02-KS) |
| Amplifier                         | SONOMA       | 310N      | 187289       | 9KHz~1GHz               | Aug. 06, 2019    | Nov. 02, 2019 | Aug. 05, 2020 | Radiation (03CH02-KS) |
| Amplifier                         | Keysight     | 83017A    | MY57280106   | 500MHz~26.5GHz          | Apr. 15, 2019    | Nov. 02, 2019 | Apr. 14, 2020 | Radiation (03CH02-KS) |
| AC Power Source                   | Chroma       | 61601     | 616010002473 | N/A                     | NCR              | Nov. 02, 2019 | NCR           | Radiation (03CH02-KS) |
| Turn Table                        | MF           | MF7802    | N/A          | 0~360 degree            | NCR              | Nov. 02, 2019 | NCR           | Radiation (03CH02-KS) |
| Antenna Mast                      | MF           | MF7802    | N/A          | 1 m~4 m                 | NCR              | Nov. 02, 2019 | NCR           | Radiation (03CH02-KS) |

NCR: No Calibration Required.

## 5. Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

|                                                                            |       |
|----------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 2.9dB |
|----------------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

|                                                                            |       |
|----------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 4.9dB |
|----------------------------------------------------------------------------|-------|

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

|                                                                            |       |
|----------------------------------------------------------------------------|-------|
| Measuring Uncertainty for a Level of Confidence<br>of 95% ( $U = 2Uc(y)$ ) | 5.0dB |
|----------------------------------------------------------------------------|-------|