FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2045-1
FCC ID	:	IHDT56YK2
STANDARD	:	47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Oct. 21, 2019 and completely tested on Nov. 18, 2019. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**

SUMMARY OF TEST RESULT **4**

1 GENERAL DESCRIPTION **5**

1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Modification of EUT 6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 7
1.7 Testing Location 7
1.8 Test Software 7
1.9 Applicable Standards 8
1.10 Specification of Accessory 8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **10**

2.1 Test Mode 10
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration 11
2.4 Measurement Results Explanation Example 11
2.5 Frequency List of Low/Middle/High Channels 12

3 CONDUCTED TEST RESULT **13**

3.1 Measuring Instruments 13
3.2 Test Setup 13
3.3 Test Result of Conducted Test 13
3.4 Conducted Output Power and ERP/EIRP 14
3.5 Peak-to-Average Ratio 15
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 16
3.7 Conducted Band Edge 17
3.8 Conducted Spurious Emission 18
3.9 Frequency Stability 19

4 RADIATED TEST ITEMS **20**

4.1 Measuring Instruments 20
4.2 Test Setup 20
4.3 Test Result of Radiated Test 20
4.4 Field Strength of Spurious Radiation Measurement 21

5 LIST OF MEASURING EQUIPMENT **22**

6 UNCERTAINTY OF EVALUATION **23**

APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG9O2103A	Rev. 01	Initial issue of report	Dec. 06, 2019

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 31.59 dB at 2510 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W,Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2045-1
FCC ID	IHDT56YK2
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE GNSS/FM Receiver
IMEI Code	Conducted: 359107100041193/359107100041201 Radiation: 359107100039874/359107100039882
HW Version	DVT2
SW Version	QPJ30.36
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT, the sample 1 is dual SIM slot, sample 2 is single SIM slot. According to the difference, we choose sample 1 to perform full test.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz **WCDMA:** Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz **WCDMA:** Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	**GSM/GPRS/EDGE:** 850: 32.60 dBm 1900: 29.51 dBm **WCDMA:** Band V: 22.72 dBm Band II: 22.78 dBm Band IV: 22.71 dBm
Antenna Type	Loop Antenna
Antenna Gain	Cellular Band: -1.4 dBi PCS Band: -0.9 dBi AWS Band: -1.0 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM (16QAM uplink is not supported) DC-HSDPA : 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.8035	0.0311 ppm	247KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.2014	0.0287 ppm	248KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.0826	0.0203 ppm	4M13F9W
Part 24	GSM1900 GSM	GMSK	0.7261	0.0090 ppm	247KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.2972	0.0202 ppm	247KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.1542	0.0101 ppm	4M13F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1483	0.0232 ppm	4M13F9W

1.7 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	TH01-KS 03CH04-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacture	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.10 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-41
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 1(EU)	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-42
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 1(UK)	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-43
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 1(AU)	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-45
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 1(AR)	**Brand Name**	Motorola (Acbel)	**Model Name**	SC-46
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 2(US)	**Brand Name**	Motorola(Chenyang)	**Model Name**	SC-41
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 2(EU)	**Brand Name**	Motorola(Chenyang)	**Model Name**	SC-42
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 2(AR)	**Brand Name**	Motorola(Chenyang)	**Model Name**	SC-46
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 3 (Chile)	**Brand Name**	Motorola (Salom)	**Model Name**	SC-42
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 3(BR)	**Brand Name**	Motorola(Salom)	**Model Name**	SC-47
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 3(BR)	**Brand Name**	Motorola(Salom/Flex)	**Model Name**	SC-47
	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
AC Adapter 4(BR)	**Brand Name**	Motorola(Cliptech/Tenpao)	**Model Name**	SC-47

	Power Rating	I/P: 100-240 Vac, 300mA ,50/60HZ O/P: 5Vdc, 2000mA		
Battery	**Brand Name**	Motorola (ATL)	**Model Name**	KG40
	Power Rating	3.8Vdc, 4000mAh	**Type**	Li-ion, Polymer
Earphone 1	**Brand Name**	Motorola(Lianyun)	**Model Name**	LYM500B-36C-001
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
Earphone 2	**Brand Name**	Motorola(Lianyun)	**Model Name**	SH38C37773
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
Earphone 3	**Brand Name**	Motorola(Cosonic)	**Model Name**	SH38C44959
	Signal Line Type	1.1 meter, non-shielded cable, without ferrite core		
USB Cable 1	**Brand Name**	Motorola (LiQi)	**Model Name**	L52B-053000100
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 2	**Brand Name**	Motorola (SaiBao)	**Model Name**	S52B-053000100
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
USB Cable 3	**Brand Name**	Motorola (I SHENG)	**Model Name**	SC18C28955
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
GSM 1900	■ GSM Link ■ EDGE class 8 Link	■ GSM Link ■ EDGE class 8 Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.9 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.9 + 10 = 14.9 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Aug. 07, 2019	Nov. 02, 2019 ~Nov.18,2019	Aug. 06, 2020	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Nov. 19, 2018	Nov. 02, 2019 ~Nov.18,2019	Nov. 18, 2019	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr.16, 2019	Nov. 02, 2019	Apr. 15, 2020	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	44483	30MHz-1GHz	Dec. 28, 2018	Nov. 02, 2019	Dec. 27, 2019	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1648	1GHz~18GHz	Jan. 27, 2019	Nov. 02, 2019	Jan. 26, 2020	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101070	18GHz~40GHz	Jan. 05, 2019	Nov. 02, 2019	Jan.04, 2020	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Aug. 06.2019	Nov. 02, 2019	Aug.05.2020	Radiation (03CH04-KS)
Amplifier	MITEQ	TTA1840-35 -HG	2014749	18~40GHz	Jan. 14, 2019	Nov. 02, 2019	Jan.13, 2020	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Aug.16.2019	Nov. 02, 2019	Aug.15,2020	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Apr. 15, 2019	Nov. 02, 2019	Apr. 14, 2020	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Nov. 02, 2019	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Nov. 02, 2019	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Nov. 02, 2019	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.1dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	32.16	32.51	32.60	29.32	29.51	29.30
GPRS class 8	32.13	32.49	32.58	29.31	29.49	29.25
GPRS class 10	30.11	30.35	30.52	27.58	27.72	27.59
GPRS class 11	28.50	28.68	28.80	25.43	25.53	25.38
GPRS class 12	26.92	26.51	26.62	23.71	23.73	23.68
EGPRS class 8	26.39	26.44	26.59	25.59	25.63	25.47
EGPRS class 10	24.22	24.18	24.30	23.50	23.53	23.37
EGPRS class 11	22.01	22.05	22.18	21.38	21.45	21.24
EGPRS class 12	20.52	20.45	20.49	19.81	19.70	19.60

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	22.61	22.71	22.57	22.61	22.76	22.70	22.59	22.69	22.55
RMC 12.2K	22.63	22.72	22.58	22.63	22.78	22.72	22.60	22.71	22.56
HSDPA Subtest-1	21.57	21.70	21.56	21.64	21.69	21.66	21.59	21.62	21.56
HSDPA Subtest-2	21.59	21.68	21.60	21.63	21.70	21.66	21.57	21.63	21.59
HSDPA Subtest-3	21.12	21.12	21.17	21.16	21.25	21.12	21.08	21.12	21.09
HSDPA Subtest-4	21.13	21.16	21.16	21.12	21.20	21.16	21.08	21.14	21.07
DC-HSDPA Subtest-1	21.56	21.64	21.54	21.60	21.65	21.65	21.59	21.64	21.56
DC-HSDPA Subtest-2	21.54	21.65	21.55	21.61	21.66	21.69	21.55	21.61	21.55
DC-HSDPA Subtest-3	21.10	21.11	21.16	21.11	21.21	21.10	21.07	21.11	21.00
DC-HSDPA Subtest-4	21.13	21.15	21.13	21.11	21.20	21.11	21.06	21.13	21.05
HSUPA Subtest-1	21.64	21.61	21.65	21.57	21.71	21.68	21.57	21.57	21.57
HSUPA Subtest-2	19.58	19.54	19.50	19.63	19.72	19.71	19.55	19.59	19.54
HSUPA Subtest-3	20.64	20.54	20.66	20.61	20.72	20.69	20.54	20.62	20.55
HSUPA Subtest-4	19.66	19.56	19.64	19.62	19.65	19.67	19.55	19.61	19.55
HSUPA Subtest-5	21.70	21.56	21.60	21.70	21.70	21.60	21.60	21.60	21.60

ERP/EIRP

GSM850 (G_T - L_C= -1.4 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	32.16	32.51	32.60
Conducted Power (Watts)	1.6444	1.7824	1.8197
ERP(dBm)	28.61	28.96	29.05
ERP(Watts)	0.7261	0.7870	0.8035

EDGE850 (G_T - L_C= -1.4 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	26.39	26.44	26.59
Conducted Power (Watts)	0.4355	0.4406	0.4560
ERP(dBm)	22.84	22.89	23.04
ERP(Watts)	0.1923	0.1945	0.2014

GSM1900 (G_T - L_C= -0.9 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	29.32	29.51	29.30
Conducted Power (Watts)	0.8551	0.8933	0.8511
EIRP(dBm)	28.42	28.61	28.40
EIRP(Watts)	0.6950	0.7261	0.6918

EDGE1900 (G_T - L_C= -0.9 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	25.59	25.63	25.47
Conducted Power (Watts)	0.3622	0.3656	0.3524
EIRP(dBm)	24.69	24.73	24.57
EIRP(Watts)	0.2944	0.2972	0.2864

WCDMA Band V (G_T - L_C = -1.4 dB)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.4	846.6
Conducted Power (dBm)	22.63	22.72	22.58
Conducted Power (Watts)	0.1832	0.1871	0.1811
ERP(dBm)	19.08	19.17	19.03
ERP(Watts)	0.0809	0.0826	0.0800

WCDMA Band II (G_T - L_C = -0.9 dB)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Conducted Power (dBm)	22.63	22.78	22.72
Conducted Power (Watts)	0.1832	0.1897	0.1871
EIRP(dBm)	21.73	21.88	21.82
EIRP(Watts)	0.1489	0.1542	0.1521

WCDMA Band IV (G_T - L_C =-1.0 dB)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	22.60	22.71	22.56
Conducted Power (Watts)	0.1820	0.1866	0.1803
EIRP(dBm)	21.60	21.71	21.56
EIRP(Watts)	0.1445	0.1483	0.1432

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.39	PASS
Middle CH	0.17	3.33	
Highest CH	0.12	3.54	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.30	PASS
Middle CH	0.12	3.25	
Highest CH	0.12	3.30	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

26dB Bandwidth

Mode	GSM850 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.3127	0.3127
Middle CH	0.3107	0.3127
Highest CH	0.3117	0.3127

Mode	GSM1900 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.3137	0.3087
Middle CH	0.3057	0.3137
Highest CH	0.3137	0.3107

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	GSM850 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.2428	0.2418
Middle CH	0.2468	0.2458
Highest CH	0.2438	0.2478

Mode	GSM1900 (MHz)	
Mod.	GSM	EDGE class 8
Lowest CH	0.2468	0.2448
Middle CH	0.2448	0.2438
Highest CH	0.2438	0.2468

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.45005 MHz	-48.35 dBm	-35.35 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-23.34 dBm	-10.34 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.20709 MHz	19.20 dBm	-15.80 dB

Date: 2.NOV.2019 11:30:02

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.77395 MHz	17.69 dBm	-17.31 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01497 MHz	-23.70 dBm	-10.70 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.53197 MHz	-48.43 dBm	-35.43 dB

Date: 2.NOV.2019 11:33:20

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.47702 MHz	-48.40 dBm	-35.40 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99102 MHz	-22.85 dBm	-9.85 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.22505 MHz	17.82 dBm	-17.18 dB

Date: 2.NOV.2019 11:45:47

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.80689 MHz	17.65 dBm	-17.35 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.03693 MHz	-25.42 dBm	-12.42 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.60190 MHz	-48.20 dBm	-35.20 dB

Date: 2.NOV.2019 11:48:49

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84897 GHz	-39.17 dBm	-26.17 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84999 GHz	-26.52 dBm	-13.52 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85016 GHz	19.49 dBm	-15.51 dB

Date: 2.NOV.2019 12:40:55

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90979 GHz	20.98 dBm	-14.02 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91001 GHz	-25.67 dBm	-12.67 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91116 GHz	-39.50 dBm	-26.50 dB

Date: 2.NOV.2019 12:36:24

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84897 GHz	-39.45 dBm	-26.45 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.84997 GHz	-26.07 dBm	-13.07 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85018 GHz	18.69 dBm	-16.31 dB

Date: 2.NOV.2019 12:58:11

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90980 GHz	19.22 dBm	-15.78 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-24.66 dBm	-11.66 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91102 GHz	-39.43 dBm	-26.43 dB

Date: 2.NOV.2019 12:53:56

Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	902.80610 MHz	-45.57 dBm	-32.57 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.53652 GHz	-44.89 dBm	-31.89 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.97471 GHz	-43.79 dBm	-30.79 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.70116 GHz	-39.63 dBm	-26.63 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.32636 GHz	-41.99 dBm	-28.99 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.91867 GHz	-37.71 dBm	-24.71 dB

Date: 2.NOV.2019 12:41:35

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	911.53173 MHz	-46.07 dBm	-33.07 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.84352 GHz	-43.53 dBm	-30.53 dB
1.915 GHz	3.000 GHz	1.000 MHz	1.92036 GHz	-44.33 dBm	-31.33 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.70066 GHz	-36.10 dBm	-23.10 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.32777 GHz	-41.04 dBm	-28.04 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.72383 GHz	-38.17 dBm	-25.17 dB

Date: 2.NOV.2019 12:59:16

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	952.73613 MHz	-45.05 dBm	-32.05 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.68981 GHz	-44.71 dBm	-31.71 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.97891 GHz	-44.50 dBm	-31.50 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.94176 GHz	-39.66 dBm	-26.66 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.52764 GHz	-41.27 dBm	-28.27 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.71597 GHz	-37.57 dBm	-24.57 dB

Date: 2.NOV.2019 12:42:11

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	936.73913 MHz	-45.66 dBm	-32.66 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.68981 GHz	-44.19 dBm	-31.19 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.14777 GHz	-45.52 dBm	-32.52 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.59730 GHz	-40.15 dBm	-27.15 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.70883 GHz	-41.81 dBm	-28.81 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.12648 GHz	-38.49 dBm	-25.49 dB

Date: 2.NOV.2019 12:59:57

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	788.88806 MHz	-46.01 dBm	-33.01 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.84352 GHz	-42.60 dBm	-29.60 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.99817 GHz	-43.95 dBm	-30.95 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.82015 GHz	-33.99 dBm	-20.99 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.77435 GHz	-42.11 dBm	-29.11 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.72226 GHz	-37.87 dBm	-24.87 dB

Date: 2.NOV.2019 12:42:39

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	906.68416 MHz	-45.00 dBm	-32.00 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.84352 GHz	-41.17 dBm	-28.17 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.61101 GHz	-44.85 dBm	-31.85 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.82015 GHz	-36.29 dBm	-23.29 dB
7.000 GHz	13.600 GHz	1.000 MHz	11.73681 GHz	-41.70 dBm	-28.70 dB
13.600 GHz	19.100 GHz	1.000 MHz	15.82361 GHz	-38.15 dBm	-25.15 dB

Date: 2.NOV.2019 13:00:23

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0036	0.0275	PASS
40	Normal Voltage	0.0036	0.0239	
30	Normal Voltage	0.0263	0.0084	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0060	0.0167	
0	Normal Voltage	0.0120	0.0287	
-10	Normal Voltage	0.0143	0.0227	
-20	Normal Voltage	0.0036	0.0012	
-30	Normal Voltage	0.0203	0.0108	
20	Maximum Voltage	0.0024	0.0132	
20	Normal Voltage	0.0239	0.0203	
20	Battery End Point	0.0311	0.0036	

Note: Normal Voltage = 3.8V ；Battery End Point (BEP) =3.6V.；Maximum Voltage =4.4

Test Conditions	Middle Channel	GSM1900 (GSM)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0080	0.0112	PASS
40	Normal Voltage	0.0069	0.0106	
30	Normal Voltage	0.0053	0.0080	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0000	0.0138	
0	Normal Voltage	0.0043	0.0181	
-10	Normal Voltage	0.0027	0.0202	
-20	Normal Voltage	0.0090	0.0154	
-30	Normal Voltage	0.0064	0.0149	
20	Maximum Voltage	0.0005	0.0186	
20	Normal Voltage	0.0016	0.0170	
20	Battery End Point	0.0053	0.0059	

Note:

1. Normal Voltage = 3.8V ；Battery End Point (BEP) =3.6V.；Maximum Voltage =4.4
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	3.16	3.22	3.28	PASS
Middle CH	3.10	3.13	3.28	
Highest CH	3.19	3.19	3.22	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	WCDMA Band V (MHz)	WCDMA Band II (MHz)	WCDMA Band IV (MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.715	4.695	4.695
Middle CH	4.685	4.705	4.695
Highest CH	4.695	4.695	4.705

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band II (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	WCDMA Band V (MHz)	WCDMA Band II (MHz)	WCDMA Band IV (MHz)
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.126	4.116	4.116
Middle CH	4.126	4.126	4.126
Highest CH	4.126	4.126	4.126

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



Conducted Band Edge

WCDMA Band V (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.80370 MHz	-33.13 dBm	-20.13 dB
823.000 MHz	824.000 MHz	50.000 kHz	823.84132 MHz	-27.42 dBm	-14.42 dB
824.000 MHz	829.000 MHz	100.000 kHz	826.83966 MHz	7.42 dBm	-27.58 dB

Date: 2.NOV.2019 23:27:46

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
844.000 MHz	849.000 MHz	100.000 kHz	845.70579 MHz	7.25 dBm	-27.75 dB
849.000 MHz	850.000 MHz	50.000 kHz	849.15469 MHz	-28.37 dBm	-15.37 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.15734 MHz	-36.08 dBm	-23.08 dB

Date: 2.NOV.2019 23:30:32

WCDMA Band II (RMC 12.2Kbps)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84892 GHz	-25.85 dBm	-12.85 dB
1.849 GHz	1.850 GHz	50.000 kHz	1.84985 GHz	-27.32 dBm	-14.32 dB
1.850 GHz	1.855 GHz	100.000 kHz	1.85273 GHz	7.74 dBm	-27.26 dB

Date: 2.NOV.2019 23:46:41

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.905 GHz	1.910 GHz	100.000 kHz	1.90671 GHz	7.70 dBm	-27.30 dB
1.910 GHz	1.911 GHz	50.000 kHz	1.91015 GHz	-28.02 dBm	-15.02 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91118 GHz	-25.23 dBm	-12.23 dB

Date: 2.NOV.2019 23:49:29

WCDMA Band IV (RMC 12.2Kbps)	
Lowest Band Edge	**Highest Band Edge**





Conducted Spurious Emission

WCDMA Band V (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	799.06797 MHz	-35.40 dBm	-22.40 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.70447 GHz	-32.27 dBm	-19.27 dB
1.760 GHz	3.000 GHz	1.000 MHz	2.11948 GHz	-35.92 dBm	-22.92 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.73028 GHz	-30.78 dBm	-17.78 dB
7.000 GHz	13.600 GHz	1.000 MHz	10.55932 GHz	-34.81 dBm	-21.81 dB
13.600 GHz	18.000 GHz	1.000 MHz	16.80030 GHz	-31.04 dBm	-18.04 dB

Date: 3.NOV.2019 00:09:38

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	837.84858 MHz	-36.64 dBm	-23.64 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.25103 GHz	-36.65 dBm	-23.65 dB
1.760 GHz	3.000 GHz	1.000 MHz	2.59604 GHz	-35.75 dBm	-22.75 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.93976 GHz	-30.91 dBm	-17.91 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.01258 GHz	-34.94 dBm	-21.94 dB
13.600 GHz	18.000 GHz	1.000 MHz	15.55770 GHz	-31.73 dBm	-18.73 dB

Date: 3.NOV.2019 00:10:59

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	620.19240 MHz	-36.08 dBm	-23.08 dB
1.000 GHz	1.705 GHz	1.000 MHz	1.52549 GHz	-37.37 dBm	-24.37 dB
1.760 GHz	3.000 GHz	1.000 MHz	1.76054 GHz	-30.53 dBm	-17.53 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.82977 GHz	-31.78 dBm	-18.78 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.20379 GHz	-34.56 dBm	-21.56 dB
13.600 GHz	18.000 GHz	1.000 MHz	17.92348 GHz	-31.80 dBm	-18.80 dB

Date: 3.NOV.2019 00:12:28

Frequency Stability

Test Conditions	Middle Channel	WCDMA Band V (RMC 12.2Kbps)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0108	PASS
40	Normal Voltage	0.0120	
30	Normal Voltage	0.0143	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0024	
0	Normal Voltage	0.0155	
-10	Normal Voltage	0.0131	
-20	Normal Voltage	0.0000	
-30	Normal Voltage	0.0072	
20	Maximum Voltage	0.0203	
20	Normal Voltage	0.0000	
20	Battery End Point	0.0024	

Note: Normal Voltage = 3.8 V ；Battery End Point (BEP) =3.6V.；Maximum Voltage =4.4V

Test Conditions	Middle Channel	WCDMA Band II (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0032	PASS
40	Normal Voltage	0.0037	
30	Normal Voltage	0.0085	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0043	
0	Normal Voltage	0.0101	
-10	Normal Voltage	0.0090	
-20	Normal Voltage	0.0005	
-30	Normal Voltage	0.0011	
20	Maximum Voltage	0.0096	
20	Normal Voltage	0.0027	
20	Battery End Point	0.0085	

Note:

1. Normal Voltage = 3.8 V ；Battery End Point (BEP) =3.6V.；Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Test Conditions	Middle Channel	WCDMA Band IV (RMC 12.2Kbps)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)	Result
50	Normal Voltage	0.0073	PASS
40	Normal Voltage	0.0049	
30	Normal Voltage	0.0219	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0146	
0	Normal Voltage	0.0195	
-10	Normal Voltage	0.0061	
-20	Normal Voltage	0.0146	
-30	Normal Voltage	0.0061	
20	Maximum Voltage	0.0207	
20	Normal Voltage	0.0024	
20	Battery End Point	0.0232	

Note:

1. Normal Voltage = 3.8 V ；Battery End Point (BEP) =3.6V.；Maximum Voltage =4.4V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

GSM850 (GSM)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-53.14	-13	-40.14	-60.11	1.58	10.70	H
	2510	-44.59	-13	-31.59	-52.84	2.102	12.50	H
	3348	-63.48	-13	-50.48	-72.37	2.856	13.90	H
	1672	-55.90	-13	-42.90	-62.87	1.58	10.70	V
	2510	-45.38	-13	-32.38	-53.63	2.10	12.50	V
	3348	-60.46	-13	-47.46	-69.35	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM850 (EDGE class 8)								
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-54.54	-13	-41.54	-61.51	1.58	10.70	H
	2510	-57.55	-13	-44.55	-65.80	2.102	12.50	H
	3348	-64.26	-13	-51.26	-73.15	2.856	13.90	H
	1672	-60.41	-13	-47.41	-67.38	1.58	10.70	V
	2510	-56.69	-13	-43.69	-64.94	2.10	12.50	V
	3348	-64.06	-13	-51.06	-72.95	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (GSM)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-57.05	-13	-44.05	-69.31	2.641	14.90	H
	5640	-55.39	-13	-42.39	-67.25	2.94	14.80	H
	7524	-50.07	-13	-37.07	-59.84	3.39	13.16	H
	3759	-56.72	-13	-43.72	-68.98	2.64	14.90	V
	5640	-55.29	-13	-42.29	-67.15	2.94	14.80	V
	7524	-49.82	-13	-36.82	-59.59	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

GSM1900 (EDGE class 8)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-56.87	-13	-43.87	-69.13	2.64	14.90	H
	5640	-55.33	-13	-42.33	-67.19	2.94	14.80	H
	7524	-50.37	-13	-37.37	-60.14	3.39	13.16	H
	3759	-56.70	-13	-43.70	-68.96	2.64	14.90	V
	5640	-55.12	-13	-42.12	-66.98	2.94	14.80	V
	7524	-50.08	-13	-37.08	-59.85	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band V(RMC 12.2Kbps)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3759	-56.42	-13	-43.42	-68.68	2.64	14.90	H
	5640	-55.31	-13	-42.31	-67.17	2.94	14.80	H
	7524	-50.53	-13	-37.53	-60.30	3.39	13.16	H
	3759	-56.55	-13	-43.55	-68.81	2.64	14.90	V
	5640	-55.42	-13	-42.42	-67.28	2.94	14.80	V
	7524	-50.10	-13	-37.10	-59.87	3.39	13.16	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band II(RMC 12.2Kbps)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	1672	-66.16	-13	-53.16	-73.13	1.58	10.70	H
	2510	-63.83	-13	-50.83	-72.08	2.102	12.50	H
	3348	-64.11	-13	-51.11	-73.00	2.856	13.90	H
	1672	-64.77	-13	-51.77	-71.74	1.58	10.70	V
	2510	-63.89	-13	-50.89	-72.14	2.10	12.50	V
	3348	-63.79	-13	-50.79	-72.68	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.

WCDMA Band IV((RMC 12.2Kbps)								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	3465	-61.79	-13	-48.79	-72.53	2.604	13.34	H
	5199	-57.34	-13	-44.34	-67.85	3.011	13.52	H
	6936	-53.06	-13	-40.06	-63.26	3.271	13.47	H
	3465	-61.56	-13	-48.56	-72.30	2.604	13.34	V
	5199	-57.07	-13	-44.07	-67.58	3.011	13.52	V
	6936	-52.38	-13	-39.38	-62.58	3.271	13.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.