

22_GSM1900_GPRS 4 Tx slots_Back_5mm_Ch512


Communication System: UID 0, PCS-4UP (0); Frequency: 1850.2 MHz; Duty Cycle: 1:2.08
Medium: HSL_1900 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.37$ S/m; $\epsilon_r = 40.147$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch512/Area Scan (71x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 1.08 W/kg

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 8.338 V/m; Power Drift = 0.01 dB
Peak SAR (extrapolated) = 2.01 W/kg
SAR(1 g) = 0.971 W/kg; SAR(10 g) = 0.449 W/kg
Maximum value of SAR (measured) = 1.32 W/kg



23_WCDMA Band V_RMC 12.2Kbps_Back_5mm_Ch4182

Communication System: UID 0, WCDMA (0); Frequency: 836.4 MHz; Duty Cycle: 1:1
Medium: HSL_835 Medium parameters used: $f = 836.4$ MHz; $\sigma = 0.9$ S/m; $\epsilon_r = 41.201$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(6.39, 6.39, 6.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch4182/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.09 W/kg


Ch4182/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 19.40 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 2.04 W/kg

SAR(1 g) = 0.985 W/kg; SAR(10 g) = 0.568 W/kg

Maximum value of SAR (measured) = 1.25 W/kg



0 dB = 1.25 W/kg = 0.97 dBW/kg

24_WCDMA Band II_RMC 12.2Kbps_Back_5mm_Ch9262


Communication System: UID 0, WCDMA (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: HSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.372$ S/m; $\epsilon_r = 40.137$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9262/Area Scan (71x71x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 1.09 W/kg

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 7.661 V/m; Power Drift = -0.10 dB
Peak SAR (extrapolated) = 1.84 W/kg
SAR(1 g) = 0.935 W/kg; SAR(10 g) = 0.444 W/kg
Maximum value of SAR (measured) = 1.08 W/kg



25_LTE Band 2_20M_QPSK_1RB_49Offset_Back_5mm_Ch18700

Communication System: UID 0, LTE-FDD (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: HSL_1900 Medium parameters used: $f = 1860$ MHz; $\sigma = 1.381$ S/m; $\epsilon_r = 40.115$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18700/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500mm

Maximum value of SAR (interpolated) = 1.21 W/kg


Ch18700/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 8.255 V/m; Power Drift = -0.08 dB

Peak SAR (extrapolated) = 1.87 W/kg

SAR(1 g) = 0.951 W/kg; SAR(10 g) = 0.453 W/kg

Maximum value of SAR (measured) = 1.23 W/kg



26_LTE Band 26_15M_QPSK_1RB_37Offset_Back_5mm_Ch26865

Communication System: UID 0, LTE-FDD (0); Frequency: 831.5 MHz; Duty Cycle: 1:1

Medium: HSL_835 Medium parameters used: $f = 831.5$ MHz; $\sigma = 0.894$ S/m; $\epsilon_r = 41.272$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(6.39, 6.39, 6.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch26865/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 1.02 W/kg


Ch26865/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 18.91 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.85 W/kg

SAR(1 g) = 0.889 W/kg; SAR(10 g) = 0.512 W/kg

Maximum value of SAR (measured) = 1.13 W/kg



0 dB = 1.13 W/kg = 0.53 dBW/kg

27_LTE Band 7_20M_QPSK_1RB_49Offset_Back_5mm_Ch21350

Communication System: UID 0, LTE-FDD (0); Frequency: 2560 MHz; Duty Cycle: 1:1

Medium: HSL_2600 Medium parameters used: $f = 2560$ MHz; $\sigma = 1.993$ S/m; $\epsilon_r = 39.849$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.39, 4.39, 4.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch21350/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.46 W/kg

Ch21350/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.231 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.60 W/kg

SAR(1 g) = 1.07 W/kg; SAR(10 g) = 0.421 W/kg

Maximum value of SAR (measured) = 1.46 W/kg


Ch21350/Zoom Scan (7x7x7)/Cube 1: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.231 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 2.64 W/kg

SAR(1 g) = 0.934 W/kg; SAR(10 g) = 0.350 W/kg

Maximum value of SAR (measured) = 1.44 W/kg



0 dB = 1.44 W/kg = 1.58 dBW/kg

28_LTE Band 41_20M_QPSK_1RB_0Offset_Back_5mm_Ch40670

Communication System: UID 0, LTE-TDD (0); Frequency: 2598 MHz; Duty Cycle: 1:1.59

Medium: HSL_2600 Medium parameters used: $f = 2598$ MHz; $\sigma = 2.037$ S/m; $\epsilon_r = 39.683$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.39, 4.39, 4.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch40670/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 1.72 W/kg


Ch40670/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 3.438 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 3.31 W/kg

SAR(1 g) = 1.24 W/kg; SAR(10 g) = 0.478 W/kg

Maximum value of SAR (measured) = 1.72 W/kg



0 dB = 1.72 W/kg = 2.36 dBW/kg

29_WLAN2.4GHz_802.11b 1Mbps_Back_5mm_Ch11

Communication System: UID 0, 802.11b (0); Frequency: 2462 MHz; Duty Cycle: 1:1

Medium: HSL_2450 Medium parameters used: $f = 2462$ MHz; $\sigma = 1.876$ S/m; $\epsilon_r = 38.423$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.9 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.6, 4.6, 4.6); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch11/Area Scan (91x91x1): Interpolated grid: $dx=1.200$ mm, $dy=1.200$ mm

Maximum value of SAR (interpolated) = 0.971 W/kg


Ch11/Zoom Scan (7x7x7)/Cube 0: Measurement grid: $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 7.013 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 1.86 W/kg

SAR(1 g) = 0.725 W/kg; SAR(10 g) = 0.308 W/kg

Maximum value of SAR (measured) = 1.01 W/kg



0 dB = 1.01 W/kg = 0.04 dBW/kg

30_Bluetooth_1Mbps_Back_5mm_Ch39

Communication System: UID 0, Bluetooth (0); Frequency: 2441 MHz; Duty Cycle: 1:1.304

Medium: HSL_2450 Medium parameters used: $f = 2441$ MHz; $\sigma = 1.853$ S/m; $\epsilon_r = 38.506$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.9 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.6, 4.6, 4.6); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch39/Area Scan (91x91x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 0.0356 W/kg


Ch39/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.437 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 0.0740 W/kg

SAR(1 g) = 0.029 W/kg; SAR(10 g) = 0.012 W/kg

Maximum value of SAR (measured) = 0.0399 W/kg



0 dB = 0.0399 W/kg = -13.99 dBW/kg

31_GSM850_GPRS 4 Tx slots_Back_0mm_Ch251

Communication System: UID 0, GSM850-4UP (0); Frequency: 848.8 MHz; Duty Cycle: 1:2.08
Medium: HSL_835 Medium parameters used: $f = 848.8$ MHz; $\sigma = 0.911$ S/m; $\epsilon_r = 41.055$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.2 °C ; Liquid Temperature : 22.6 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(6.39, 6.39, 6.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch251/Area Scan (71x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 4.63 W/kg


Ch251/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 17.00 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 16.7 W/kg

SAR(1 g) = 4.87 W/kg; SAR(10 g) = 2.07 W/kg

Maximum value of SAR (measured) = 7.57 W/kg



0 dB = 7.57 W/kg = 8.79 dBW/kg

32_GSM1900_GPRS 4 Tx slots_Bottom Side_0mm_Ch512


Communication System: UID 0, PCS-4UP (0); Frequency: 1850.2 MHz; Duty Cycle: 1:2.08
Medium: HSL_1900 Medium parameters used: $f = 1850.2$ MHz; $\sigma = 1.37$ S/m; $\epsilon_r = 40.147$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch512/Area Scan (41x81x1): Interpolated grid: $dx=1.500$ mm, $dy=1.500$ mm
Maximum value of SAR (interpolated) = 6.11 W/kg

Ch512/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8$ mm, $dy=8$ mm, $dz=5$ mm
Reference Value = 50.33 V/m; Power Drift = -0.02 dB
Peak SAR (extrapolated) = 10.7 W/kg
SAR(1 g) = 4.71 W/kg; SAR(10 g) = 1.93 W/kg
Maximum value of SAR (measured) = 6.69 W/kg



33_WCDMA Band II_RMC 12.2Kbps_Bottom Side_0mm_Ch9262


Communication System: UID 0, WCDMA (0); Frequency: 1852.4 MHz; Duty Cycle: 1:1
Medium: HSL_1900 Medium parameters used: $f = 1852.4$ MHz; $\sigma = 1.372$ S/m; $\epsilon_r = 40.137$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch9262/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm
Maximum value of SAR (interpolated) = 8.46 W/kg

Ch9262/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm
Reference Value = 60.24 V/m; Power Drift = -0.05 dB
Peak SAR (extrapolated) = 15.0 W/kg
SAR(1 g) = 6.6 W/kg; SAR(10 g) = 2.69 W/kg
Maximum value of SAR (measured) = 9.31 W/kg



34_LTE Band 2_20M_QPSK_1RB_49Offset_Bottom Side_0mm_Ch18700

Communication System: UID 0, LTE-FDD (0); Frequency: 1860 MHz; Duty Cycle: 1:1

Medium: HSL_1900 Medium parameters used: $f = 1860$ MHz; $\sigma = 1.381$ S/m; $\epsilon_r = 40.115$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.8 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(5.32, 5.32, 5.32); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM2; Type: SAM; Serial: TP-1503
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch18700/Area Scan (41x81x1): Interpolated grid: dx=1.500 mm, dy=1.500 mm

Maximum value of SAR (interpolated) = 9.06 W/kg


Ch18700/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 62.37 V/m; Power Drift = -0.01 dB

Peak SAR (extrapolated) = 15.1 W/kg

SAR(1 g) = 6.68 W/kg; SAR(10 g) = 2.75 W/kg

Maximum value of SAR (measured) = 9.35 W/kg



36_LTE Band 7_20M_QPSK_1RB_49Offset_Back_0mm_Ch21100


Communication System: UID 0, LTE-FDD (0); Frequency: 2535 MHz; Duty Cycle: 1:1
Medium: HSL_2600 Medium parameters used: $f = 2535$ MHz; $\sigma = 1.96$ S/m; $\epsilon_r = 39.936$; $\rho = 1000$ kg/m³
Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.39, 4.39, 4.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch21100/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm
Maximum value of SAR (interpolated) = 7.96 W/kg

Ch21100/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm
Reference Value = 2.117 V/m; Power Drift = 0.02 dB
Peak SAR (extrapolated) = 15.9 W/kg
SAR(1 g) = 5.36 W/kg; SAR(10 g) = 1.82 W/kg
Maximum value of SAR (measured) = 8.26 W/kg



37_LTE Band 41_20M_QPSK_1RB_0Offset_Back_0mm_Ch40400

Communication System: UID 0, LTE-TDD (0); Frequency: 2571 MHz; Duty Cycle: 1:1.59

Medium: HSL_2600 Medium parameters used: $f = 2571$ MHz; $\sigma = 2.005$ S/m; $\epsilon_r = 39.815$; $\rho = 1000$ kg/m³

Ambient Temperature : 23.1 °C ; Liquid Temperature : 22.7 °C

DASY5 Configuration:

- Probe: ES3DV3 - SN3293; ConvF(4.39, 4.39, 4.39); Calibrated: 2019.11.25
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1338; Calibrated: 2019.11.20
- Phantom: SAM1; Type: SAM; Serial: TP-1839
- Measurement SW: DASY52, Version 52.10 (1); SEMCAD X Version 14.6.11 (7439)

Ch40400/Area Scan (91x81x1): Interpolated grid: dx=1.200 mm, dy=1.200 mm

Maximum value of SAR (interpolated) = 7.07 W/kg


Ch40400/Zoom Scan (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 1.841 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 16.4 W/kg

SAR(1 g) = 5.5 W/kg; SAR(10 g) = 1.89 W/kg

Maximum value of SAR (measured) = 8.38 W/kg





Appendix C. DASY Calibration Certificate

The DASY calibration certificates are shown as follows.



In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **Sporton**

Certificate No: **Z19-60082**

CALIBRATION CERTIFICATE

Object **D835V2 - SN: 4d151**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **March 27, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Power sensor NRP8S	104291	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Reference Probe EX3DV4	SN 3617	31-Jan-19(SPEAG,No.EX3-3617_Jan19)	Jan-20
DAE4	SN 1331	06-Feb-19(SPEAG,No.DAE4-1331_Feb19)	Feb-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-19 (CTTL, No.J19X00336)	Jan-20
NetworkAnalyzer E5071C	MY46110673	24-Jan-19 (CTTL, No.J19X00547)	Jan-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: March 30, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.cn

http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	15 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	835 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	41.5	0.90 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	42.7 $\pm$ 6 %	0.93 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm^3 (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	2.36 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	9.30 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm^3 (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	1.56 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	6.16 W/kg $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	55.2	0.97 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	56.7 $\pm$ 6 %	0.94 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm^3 (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	2.32 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	9.53 W /kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm^3 (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	1.52 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	6.20 W/kg $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	50.8Ω- 3.28jΩ
Return Loss	- 29.5dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	46.7Ω- 3.98jΩ
Return Loss	- 25.5dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.253 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 03.26.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d151

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.925$ S/m; $\epsilon_r = 42.68$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(9.75, 9.75, 9.75) @ 835 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 57.34 V/m; Power Drift = 0.00 dB

Peak SAR (extrapolated) = 3.55 W/kg

SAR(1 g) = 2.36 W/kg; SAR(10 g) = 1.56 W/kg

Maximum value of SAR (measured) = 3.14 W/kg



0 dB = 3.14 W/kg = 4.97 dBW/kg




In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 03.26.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN: 4d151

Communication System: UID 0, CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835$ MHz; $\sigma = 0.944$ S/m; $\epsilon_r = 56.66$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(9.61, 9.61, 9.61) @ 835 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 56.03 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 3.53 W/kg

SAR(1 g) = 2.32 W/kg; SAR(10 g) = 1.52 W/kg

Maximum value of SAR (measured) = 3.12 W/kg



0 dB = 3.12 W/kg = 4.94 dBW/kg




In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client

Sporton

Certificate No: **Z19-60085**

CALIBRATION CERTIFICATE

Object **D1900V2 - SN: 5d170**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **March 26, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)℃ and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Power sensor NRP8S	104291	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Reference Probe EX3DV4	SN 3617	31-Jan-19(SPEAG,No.EX3-3617_Jan19)	Jan-20
DAE4	SN 1331	06-Feb-19(SPEAG,No.DAE4-1331_Feb19)	Feb-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-19 (CTTL, No.J19X00336)	Jan-20
NetworkAnalyzer E5071C	MY46110673	24-Jan-19 (CTTL, No.J19X00547)	Jan-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: March 29, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
 Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
 E-mail: cttl@chinattl.com http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	1900 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	40.0	1.40 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	40.5 $\pm$ 6 %	1.44 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	9.90 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	39.0 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	5.12 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	20.3 W/kg $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	53.3	1.52 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	54.5 $\pm$ 6 %	1.56 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	10.1 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	40.0 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.28 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	21.0 W/kg $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: ctl@chinattl.com

<http://www.chinattl.cn>

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$51.7\Omega + 6.73j\Omega$
Return Loss	- 23.3dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$47.8\Omega + 6.72j\Omega$
Return Loss	- 22.8dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.066 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 03.26.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d170

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.441$ S/m; $\epsilon_r = 40.48$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(8.14, 8.14, 8.14) @ 1900 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:
 $dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 97.54 V/m; Power Drift = 0.08 dB

Peak SAR (extrapolated) = 18.9 W/kg

SAR(1 g) = 9.9 W/kg; SAR(10 g) = 5.12 W/kg

Maximum value of SAR (measured) = 15.6 W/kg



0 dB = 15.6 W/kg = 11.93 dBW/kg




In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 03.26.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN: 5d170

Communication System: UID 0, CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900$ MHz; $\sigma = 1.56$ S/m; $\epsilon_r = 54.52$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.78, 7.78, 7.78) @ 1900 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)

System Performance Check/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid:


$dx=5$ mm, $dy=5$ mm, $dz=5$ mm

Reference Value = 95.48 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 18.6 W/kg

SAR(1 g) = 10.1 W/kg; SAR(10 g) = 5.28 W/kg

Maximum value of SAR (measured) = 15.7 W/kg






In Collaboration with

s p e a k
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client

Sporton

Certificate No: **Z19-60087**

CALIBRATION CERTIFICATE

Object **D2450V2 - SN: 908**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **March 25, 2019**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRP2	106277	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Power sensor NRP8S	104291	20-Aug-18 (CTTL, No.J18X06862)	Aug-19
Reference Probe EX3DV4	SN 3617	31-Jan-19(SPEAG,No.EX3-3617_Jan19)	Jan-20
DAE4	SN 1331	06-Feb-19(SPEAG,No.DAE4-1331_Feb19)	Feb-20
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-19 (CTTL, No.J19X00336)	Jan-20
NetworkAnalyzer E5071C	MY46110673	24-Jan-19 (CTTL, No.J19X00547)	Jan-20

	Name	Function	Signature
Calibrated by:	Zhao Jing	SAR Test Engineer	
Reviewed by:	Lin Hao	SAR Test Engineer	
Approved by:	Qi Dianyuan	SAR Project Leader	

Issued: March 28, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2450 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.2	1.80 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.6 $\pm$ 6 %	1.84 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	13.3 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	52.8 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.07 W/kg
SAR for nominal Head TSL parameters	normalized to 1W	24.2 W/kg $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.7	1.95 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	53.8 $\pm$ 6 %	2.00 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	12.8 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	50.8 W/kg $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	5.91 W/kg
SAR for nominal Body TSL parameters	normalized to 1W	23.6 W/kg $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Appendix (Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	$57.3\Omega + 5.18j\Omega$
Return Loss	- 21.6dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	$52.6\Omega + 5.81j\Omega$
Return Loss	- 24.1dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.020 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 03.25.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 908

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 1.841$ S/m; $\epsilon_r = 39.63$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.62, 7.62, 7.62) @ 2450 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 96.04 V/m; Power Drift = 0.04 dB

Peak SAR (extrapolated) = 28.3 W/kg

SAR(1 g) = 13.3 W/kg; SAR(10 g) = 6.07 W/kg

Maximum value of SAR (measured) = 22.4 W/kg



0 dB = 22.4 W/kg = 13.50 dBW/kg




In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Head TSL





In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 03.25.2019

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN: 908

Communication System: UID 0, CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450$ MHz; $\sigma = 2.003$ S/m; $\epsilon_r = 53.78$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN3617; ConvF(7.79, 7.79, 7.79) @ 2450 MHz; Calibrated: 1/31/2019
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1331; Calibrated: 2/6/2019
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 95.51 V/m; Power Drift = -0.02 dB

Peak SAR (extrapolated) = 27.1 W/kg

SAR(1 g) = 12.8 W/kg; SAR(10 g) = 5.91 W/kg

Maximum value of SAR (measured) = 21.4 W/kg



0 dB = 21.4 W/kg = 13.30 dBW/kg



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China


Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





In Collaboration with
s p e a g
CALIBRATION LABORATORY



中国认可
国际互认
校准
CALIBRATION
CNAS L0570

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Client **Sporton**

Certificate No: **Z18-60537**

CALIBRATION CERTIFICATE

Object **D2600V2 - SN: 1070**

Calibration Procedure(s) **FF-Z11-003-01**
Calibration Procedures for dipole validation kits

Calibration date: **December 7, 2018**

This calibration Certificate documents the traceability to national standards, which realize the physical units of measurements(SI). The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature(22±3)°C and humidity<70%.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Power Meter NRVD	102196	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Power sensor NRV-Z5	100596	07-Mar-18 (CTTL, No.J18X01510)	Mar-19
Reference Probe EX3DV4	SN 7514	27-Aug-18(SPEAG,No.EX3-7514_Aug18)	Aug-19
DAE4	SN 1555	20-Aug-18(SPEAG,No.DAE4-1555_Aug18)	Aug-19
Secondary Standards	ID #	Cal Date(Calibrated by, Certificate No.)	Scheduled Calibration
Signal Generator E4438C	MY49071430	23-Jan-18 (CTTL, No.J18X00560)	Jan-19
Network Analyzer E5071C	MY46110673	24-Jan-18 (CTTL, No.J18X00561)	Jan-19

	Name	Function
Calibrated by:	Zhao Jing	SAR Test Engineer
Reviewed by:	Lin Hao	SAR Test Engineer
Approved by:	Qi Dianyuan	SAR Project Leader

Signature



Issued: December 10, 2018

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



In Collaboration with

s p e a g
CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Glossary:

TSL	tissue simulating liquid
ConvF	sensitivity in TSL / NORM _{x,y,z}
N/A	not applicable or not measured

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices- Part 1: Device used next to the ear (Frequency range of 300MHz to 6GHz)", July 2016
- IEC 62209-2, "Procedure to measure the Specific Absorption Rate (SAR) For wireless communication devices used in close proximity to the human body (frequency range of 30MHz to 6GHz)", March 2010
- KDB865664, SAR Measurement Requirements for 100 MHz to 6 GHz

Additional Documentation:

- DASY4/5 System Handbook

Methods Applied and Interpretation of Parameters:

- Measurement Conditions:** Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- Antenna Parameters with TSL:** The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- Feed Point Impedance and Return Loss:** These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- Electrical Delay:** One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- SAR measured:** SAR measured at the stated antenna input power.
- SAR normalized:** SAR as measured, normalized to an input power of 1 W at the antenna connector.
- SAR for nominal TSL parameters:** The measured TSL parameters are used to calculate the nominal SAR result.

The reported uncertainty of measurement is stated as the standard uncertainty of Measurement multiplied by the coverage factor $k=2$, which for a normal distribution Corresponds to a coverage probability of approximately 95%.



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Measurement Conditions

DASY system configuration, as far as not given on page 1.

DASY Version	DASY52	52.10.2.1495
Extrapolation	Advanced Extrapolation	
Phantom	Triple Flat Phantom 5.1C	
Distance Dipole Center - TSL	10 mm	with Spacer
Zoom Scan Resolution	dx, dy, dz = 5 mm	
Frequency	2600 MHz $\pm$ 1 MHz	

Head TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Head TSL parameters	22.0 °C	39.0	1.96 mho/m
Measured Head TSL parameters	(22.0 $\pm$ 0.2) °C	39.1 $\pm$ 6 %	1.93 mho/m $\pm$ 6 %
Head TSL temperature change during test	<1.0 °C	----	----

SAR result with Head TSL

SAR averaged over 1 cm ³ (1 g) of Head TSL	Condition	
SAR measured	250 mW input power	14.4 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	58.1 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Head TSL	Condition	
SAR measured	250 mW input power	6.50 mW / g
SAR for nominal Head TSL parameters	normalized to 1W	26.1 mW / g $\pm$ 18.7 % (k=2)

Body TSL parameters

The following parameters and calculations were applied.

	Temperature	Permittivity	Conductivity
Nominal Body TSL parameters	22.0 °C	52.5	2.16 mho/m
Measured Body TSL parameters	(22.0 $\pm$ 0.2) °C	51.0 $\pm$ 6 %	2.18 mho/m $\pm$ 6 %
Body TSL temperature change during test	<1.0 °C	----	----

SAR result with Body TSL

SAR averaged over 1 cm ³ (1 g) of Body TSL	Condition	
SAR measured	250 mW input power	13.8 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	54.6 mW / g $\pm$ 18.8 % (k=2)
SAR averaged over 10 cm ³ (10 g) of Body TSL	Condition	
SAR measured	250 mW input power	6.18 mW / g
SAR for nominal Body TSL parameters	normalized to 1W	24.6 mW / g $\pm$ 18.7 % (k=2)



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

Appendix(Additional assessments outside the scope of CNAS L0570)

Antenna Parameters with Head TSL

Impedance, transformed to feed point	48.6Ω- 6.33jΩ
Return Loss	- 23.7dB

Antenna Parameters with Body TSL

Impedance, transformed to feed point	44.8Ω- 5.36jΩ
Return Loss	- 22.1dB

General Antenna Parameters and Design

Electrical Delay (one direction)	1.015 ns
----------------------------------	----------

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals. On some of the dipoles, small end caps are added to the dipole arms in order to improve matching when loaded according to the position as explained in the "Measurement Conditions" paragraph. The SAR data are not affected by this change. The overall dipole length is still according to the Standard.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

Additional EUT Data

Manufactured by	SPEAG
-----------------	-------



In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

DASY5 Validation Report for Head TSL

Date: 12.06.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1070

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 1.926$ S/m; $\epsilon_r = 39.1$; $\rho = 1000$ kg/m³

Phantom section: Center Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(6.92, 6.92, 6.92) @ 2600 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 99.07 V/m; Power Drift = 0.01 dB

Peak SAR (extrapolated) = 31.1 W/kg

SAR(1 g) = 14.4 W/kg; SAR(10 g) = 6.5 W/kg


Maximum value of SAR (measured) = 24.7 W/kg



0 dB = 24.7 W/kg = 13.93 dBW/kg



Impedance Measurement Plot for Head TSL





In Collaboration with

s p e a g

CALIBRATION LABORATORY

Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China

Tel: +86-10-62304633-2079

Fax: +86-10-62304633-2504

E-mail: cttl@chinattl.com

http://www.chinattl.cn

DASY5 Validation Report for Body TSL

Date: 12.06.2018

Test Laboratory: CTTL, Beijing, China

DUT: Dipole 2600 MHz; Type: D2600V2; Serial: D2600V2 - SN: 1070

Communication System: UID 0, CW; Frequency: 2600 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2600$ MHz; $\sigma = 2.181$ S/m; $\epsilon_r = 51.03$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY5 Configuration:

- Probe: EX3DV4 - SN7514; ConvF(7.06, 7.06, 7.06) @ 2600 MHz; Calibrated: 8/27/2018
- Sensor-Surface: 1.4mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn1555; Calibrated: 8/20/2018
- Phantom: MFP_V5.1C ; Type: QD 000 P51CA; Serial: 1062
- Measurement SW: DASY52, Version 52.10 (2); SEMCAD X Version 14.6.12 (7450)


Dipole Calibration/Zoom Scan (7x7x7) (7x7x7)/Cube 0: Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 87.90 V/m; Power Drift = -0.04 dB

Peak SAR (extrapolated) = 29.5 W/kg

SAR(1 g) = 13.8 W/kg; SAR(10 g) = 6.18 W/kg

Maximum value of SAR (measured) = 23.6 W/kg




0 dB = 23.6 W/kg = 13.73 dBW/kg



Add: No.51 Xueyuan Road, Haidian District, Beijing, 100191, China
Tel: +86-10-62304633-2079 Fax: +86-10-62304633-2504
E-mail: cttl@chinattl.com http://www.chinattl.cn

Impedance Measurement Plot for Body TSL





D2600V2, Serial No. 1070 Extended Dipole Calibrations

Referring to KDB 865664 D01 v01r02, if dipoles are verified in return loss ($< -20\text{dB}$, within 20% of prior calibration), and in impedance (within 5 ohm of prior calibration), the annual calibration is not necessary and the calibration interval can be extended.


D2600V2 – serial no. 1070												
	2600 Head						2600 Body					
Date of Measurement	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)	Return-Loss (dB)	Delta (%)	Real Impedance (ohm)	Delta (ohm)	Imaginary Impedance (ohm)	Delta (ohm)
2018.12.7	-23.7		48.6		-6.33		-22.1		44.8		-5.36	
2019.11.25	-23.1	2.5	48.6	0	-6.82	-0.49	-22.0	0.5	45.3	0.5	-4.65	0.71

<Justification of the extended calibration>


The return loss is $< -20\text{dB}$, within 20% of prior calibration; the impedance is within 5 ohm of prior calibration. Therefore the verification result should support extended calibration.

Dipole Verification Data> D2600V2, serial no. 1070

2600MHz - Head



2600MHz - Body





Accredited by the Swiss Accreditation Service (SAS)
The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 0108

Client **Sporton**

Certificate No: DAE4-1338_Nov19

CALIBRATION CERTIFICATE

Object **DAE4 - SD 000 D04 BM - SN: 1338**

Calibration procedure(s) **QA CAL-06.v29**
Calibration procedure for the data acquisition electronics (DAE)

Calibration date: **November 20, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID #	Cal Date (Certificate No.)	Scheduled Calibration
Keithley Multimeter Type 2001	SN: 0810278	03-Sep-19 (No:25949)	Sep-20
Secondary Standards	ID #	Check Date (in house)	Scheduled Check
Auto DAE Calibration Unit Calibrator Box V2.1	SE LWS 053 AA 1001	07-Jan-19 (in house check)	In house check: Jan-20
	SE UMS 006 AA 1002	07-Jan-19 (in house check)	In house check: Jan-20

Calibrated by:	Name Eric Hainfeld	Function Laboratory Technician	Signature
----------------	------------------------------	-----------------------------------	---------------

Approved by:	Sven Kühn	Deputy Manager	
--------------	-----------	----------------	--

Issued: November 20, 2019

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Glossary

DAE	data acquisition electronics
Connector angle	information used in DASY system to align probe sensor X to the robot coordinate system.

Methods Applied and Interpretation of Parameters

- *DC Voltage Measurement:* Calibration Factor assessed for use in DASY system by comparison with a calibrated instrument traceable to national standards. The figure given corresponds to the full scale range of the voltmeter in the respective range.
- *Connector angle:* The angle of the connector is assessed measuring the angle mechanically by a tool inserted. Uncertainty is not required.
- The following parameters as documented in the Appendix contain technical information as a result from the performance test and require no uncertainty.
 - *DC Voltage Measurement Linearity:* Verification of the Linearity at +10% and -10% of the nominal calibration voltage. Influence of offset voltage is included in this measurement.
 - *Common mode sensitivity:* Influence of a positive or negative common mode voltage on the differential measurement.
 - *Channel separation:* Influence of a voltage on the neighbor channels not subject to an input voltage.
 - *AD Converter Values with inputs shorted:* Values on the internal AD converter corresponding to zero input voltage
 - *Input Offset Measurement:* Output voltage and statistical results over a large number of zero voltage measurements.
 - *Input Offset Current:* Typical value for information; Maximum channel input offset current, not considering the input resistance.
 - *Input resistance:* Typical value for information: DAE input resistance at the connector, during internal auto-zeroing and during measurement.
 - *Low Battery Alarm Voltage:* Typical value for information. Below this voltage, a battery alarm signal is generated.
 - *Power consumption:* Typical value for information. Supply currents in various operating modes.

Appendix (Additional assessments outside the scope of SCS0108)

1. DC Voltage Linearity

High Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	200032.47	-3.15	-0.00
Channel X + Input	20005.24	-0.41	-0.00
Channel X - Input	-20006.33	-0.08	0.00
Channel Y + Input	200035.56	-0.12	-0.00
Channel Y + Input	20004.04	-1.44	-0.01
Channel Y - Input	-20008.42	-2.09	0.01
Channel Z + Input	200033.57	-2.10	-0.00
Channel Z + Input	20004.49	-0.96	-0.00
Channel Z - Input	-20008.50	-2.10	0.01

Low Range	Reading (μV)	Difference (μV)	Error (%)
Channel X + Input	2001.19	0.11	0.01
Channel X + Input	201.01	-0.01	-0.00
Channel X - Input	-199.18	-0.36	0.18
Channel Y + Input	2001.08	0.17	0.01
Channel Y + Input	199.87	-0.94	-0.47
Channel Y - Input	-200.25	-1.26	0.64
Channel Z + Input	2000.89	-0.01	-0.00
Channel Z + Input	199.87	-0.86	-0.43
Channel Z - Input	-199.91	-0.91	0.46

2. Common mode sensitivity

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Common mode Input Voltage (mV)	High Range Average Reading (μV)	Low Range Average Reading (μV)
Channel X	200	7.80	5.74
	- 200	-6.09	-7.67
Channel Y	200	-21.26	-21.58
	- 200	19.76	19.35
Channel Z	200	-2.47	-2.52
	- 200	0.78	0.74

3. Channel separation

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	Input Voltage (mV)	Channel X (μV)	Channel Y (μV)	Channel Z (μV)
Channel X	200	-	3.28	-2.96
Channel Y	200	7.86	-	4.97
Channel Z	200	8.87	6.08	-

DC Voltage Measurement

A/D - Converter Resolution nominal

High Range: 1LSB = 6.1 μ V , full range = -100...+300 mV

Low Range: 1LSB = 61 nV , full range = -1.....+3mV

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Calibration Factors	X	Y	Z
High Range	403.688 $\pm$ 0.02% (k=2)	404.268 $\pm$ 0.02% (k=2)	404.224 $\pm$ 0.02% (k=2)
Low Range	3.97425 $\pm$ 1.50% (k=2)	3.97933 $\pm$ 1.50% (k=2)	3.97493 $\pm$ 1.50% (k=2)

Connector Angle

Connector Angle to be used in DASY system	239.5 $^{\circ}$ $\pm$ 1 $^{\circ}$
---	-------------------------------------

4. AD-Converter Values with inputs shorted

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

	High Range (LSB)	Low Range (LSB)
Channel X	16190	14025
Channel Y	16291	16862
Channel Z	16104	15099

5. Input Offset Measurement

DASY measurement parameters: Auto Zero Time: 3 sec; Measuring time: 3 sec

Input 10M Ω

	Average (μ V)	min. Offset (μ V)	max. Offset (μ V)	Std. Deviation (μ V)
Channel X	-0.07	-1.18	1.09	0.42
Channel Y	-0.64	-1.62	0.80	0.39
Channel Z	-0.63	-1.81	0.20	0.36

6. Input Offset Current

Nominal Input circuitry offset current on all channels: <25fA

7. Input Resistance (Typical values for information)

	Zeroing (kOhm)	Measuring (MOhm)
Channel X	200	200
Channel Y	200	200
Channel Z	200	200

8. Low Battery Alarm Voltage (Typical values for information)

Typical values	Alarm Level (VDC)
Supply (+ Vcc)	+7.9
Supply (- Vcc)	-7.6

9. Power Consumption (Typical values for information)

Typical values	Switched off (mA)	Stand by (mA)	Transmitting (mA)
Supply (+ Vcc)	+0.01	+6	+14
Supply (- Vcc)	-0.01	-8	-9



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 0108**

Client **Sporton**

Certificate No: **ES3-3293_Nov19**

CALIBRATION CERTIFICATE

Object **ES3DV3 - SN:3293**

Calibration procedure(s) **QA CAL-01.v9, QA CAL-23.v5, QA CAL-25.v7
Calibration procedure for dosimetric E-field probes**

Calibration date: **November 25, 2019**

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature $(22 \pm 3)^{\circ}\text{C}$ and humidity $< 70\%$.

Calibration Equipment used (M&TE critical for calibration)

Primary Standards	ID	Cal Date (Certificate No.)	Scheduled Calibration
Power meter NRP	SN: 104778	03-Apr-19 (No. 217-02892/02893)	Apr-20
Power sensor NRP-Z91	SN: 103244	03-Apr-19 (No. 217-02892)	Apr-20
Power sensor NRP-Z91	SN: 103245	03-Apr-19 (No. 217-02893)	Apr-20
Reference 20 dB Attenuator	SN: S5277 (20x)	04-Apr-19 (No. 217-02894)	Apr-20
DAE4	SN: 660	07-Oct-19 (No. DAE4-660_Oct19)	Oct-20
Reference Probe ES3DV2	SN: 3013	31-Dec-18 (No. ES3-3013_Dec18)	Dec-19
Secondary Standards	ID	Check Date (in house)	Scheduled Check
Power meter E4419B	SN: GB41293874	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: MY41498087	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
Power sensor E4412A	SN: 000110210	06-Apr-16 (in house check Jun-18)	In house check: Jun-20
RF generator HP 8648C	SN: US3642U01700	04-Aug-99 (in house check Jun-18)	In house check: Jun-20
Network Analyzer E8358A	SN: US41080477	31-Mar-14 (in house check Oct-19)	In house check: Oct-20

	Name	Function	Signature
Calibrated by:	Leif Klysner	Laboratory Technician	
Approved by:	Katja Pokovic	Technical Manager	
This calibration certificate shall not be reproduced except in full without written approval of the laboratory.			
Issued: November 26, 2019			



Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 0108**

The Swiss Accreditation Service is one of the signatories to the EA
Multilateral Agreement for the recognition of calibration certificates

Glossary:

TSL	tissue simulating liquid
NORM _{x,y,z}	sensitivity in free space
ConvF	sensitivity in TSL / NORM _{x,y,z}
DCP	diode compression point
CF	crest factor (1/duty_cycle) of the RF signal
A, B, C, D	modulation dependent linearization parameters
Polarization ϕ	ϕ rotation around probe axis
Polarization ϑ	ϑ rotation around an axis that is in the plane normal to probe axis (at measurement center), i.e., $\vartheta = 0$ is normal to probe axis
Connector Angle	information used in DASY system to align probe sensor X to the robot coordinate system

Calibration is Performed According to the Following Standards:

- IEEE Std 1528-2013, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", June 2013
- IEC 62209-1, "Measurement procedure for the assessment of Specific Absorption Rate (SAR) from hand-held and body-mounted devices used next to the ear (frequency range of 300 MHz to 6 GHz)", July 2016
- IEC 62209-2, "Procedure to determine the Specific Absorption Rate (SAR) for wireless communication devices used in close proximity to the human body (frequency range of 30 MHz to 6 GHz)", March 2010
- KDB 865664, "SAR Measurement Requirements for 100 MHz to 6 GHz"

Methods Applied and Interpretation of Parameters:

- NORM_{x,y,z}**: Assessed for E-field polarization $\vartheta = 0$ ($f \leq 900$ MHz in TEM-cell; $f > 1800$ MHz: R22 waveguide). NORM_{x,y,z} are only intermediate values, i.e., the uncertainties of NORM_{x,y,z} does not affect the E²-field uncertainty inside TSL (see below ConvF).
- NORM(f)_{x,y,z}** = NORM_{x,y,z} * frequency_response (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of ConvF.
- DCP_{x,y,z}**: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- PAR**: PAR is the Peak to Average Ratio that is not calibrated but determined based on the signal characteristics
- A_{x,y,z}; B_{x,y,z}; C_{x,y,z}; D_{x,y,z}; VR_{x,y,z}**: A, B, C, D are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- ConvF and Boundary Effect Parameters**: Assessed in flat phantom using E-field (or Temperature Transfer Standard for $f \leq 800$ MHz) and inside waveguide using analytical field distributions based on power measurements for $f > 800$ MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to NORM_{x,y,z} * ConvF whereby the uncertainty corresponds to that given for ConvF. A frequency dependent ConvF is used in DASY version 4.4 and higher which allows extending the validity from ± 50 MHz to ± 100 MHz.
- Spherical isotropy (3D deviation from isotropy)**: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- Sensor Offset**: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.
- Connector Angle**: The angle is assessed using the information gained by determining the NORM_x (no uncertainty required).

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293

Basic Calibration Parameters

	Sensor X	Sensor Y	Sensor Z	Unc (k=2)
Norm ($\mu\text{V}/(\text{V}/\text{m})^2$) ^A	1.09	0.90	0.71	± 10.1 %
DCP (mV) ^B	105.6	104.0	109.8	

Calibration Results for Modulation Response

UID	Communication System Name		A dB	B dB $\sqrt{\mu\text{V}}$	C	D dB	VR mV	Max dev.	Unc ^E (k=2)
0	CW	X	0.0	0.0	1.0	0.00	197.9	±3.5 %	± 4.7 %
		Y	0.0	0.0	1.0		199.0		
		Z	0.0	0.0	1.0		206.6		

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

^A The uncertainties of Norm X,Y,Z do not affect the E²-field uncertainty inside TSL (see Page 5).

^B Numerical linearization parameter: uncertainty not required.

^E Uncertainty is determined using the max. deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293

Other Probe Parameters

Sensor Arrangement	Triangular
Connector Angle (°)	-4.6
Mechanical Surface Detection Mode	enabled
Optical Surface Detection Mode	disabled
Probe Overall Length	337 mm
Probe Body Diameter	10 mm
Tip Length	10 mm
Tip Diameter	4 mm
Probe Tip to Sensor X Calibration Point	2 mm
Probe Tip to Sensor Y Calibration Point	2 mm
Probe Tip to Sensor Z Calibration Point	2 mm
Recommended Measurement Distance from Surface	3 mm

DASY/EASY - Parameters of Probe: ES3DV3 - SN:3293

Calibration Parameter Determined in Head Tissue Simulating Media

f (MHz) ^C	Relative Permittivity ^F	Conductivity (S/m) ^F	ConvF X	ConvF Y	ConvF Z	Alpha ^G	Depth ^H (mm)	Unc (k=2)
750	41.9	0.89	6.56	6.56	6.56	0.80	1.23	± 12.0 %
835	41.5	0.90	6.39	6.39	6.39	0.80	1.26	± 12.0 %
900	41.5	0.97	6.23	6.23	6.23	0.72	1.30	± 12.0 %
1450	40.5	1.20	5.89	5.89	5.89	0.48	1.49	± 12.0 %
1750	40.1	1.37	5.53	5.53	5.53	0.55	1.38	± 12.0 %
1900	40.0	1.40	5.32	5.32	5.32	0.67	1.30	± 12.0 %
2000	40.0	1.40	5.25	5.25	5.25	0.50	1.55	± 12.0 %
2300	39.5	1.67	4.89	4.89	4.89	0.63	1.42	± 12.0 %
2450	39.2	1.80	4.60	4.60	4.60	0.80	1.33	± 12.0 %
2600	39.0	1.96	4.39	4.39	4.39	0.75	1.41	± 12.0 %


^C Frequency validity above 300 MHz of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2), else it is restricted to ± 50 MHz. The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band. Frequency validity below 300 MHz is ± 10, 25, 40, 50 and 70 MHz for ConvF assessments at 30, 64, 128, 150 and 220 MHz respectively. Validity of ConvF assessed at 6 MHz is 4-8 MHz, and ConvF assessed at 13 MHz is 9-19 MHz. Above 5 GHz frequency validity can be extended to ± 110 MHz.

^F At frequencies below 3 GHz, the validity of tissue parameters (ϵ and σ) can be relaxed to ± 10% if liquid compensation formula is applied to measured SAR values. At frequencies above 3 GHz, the validity of tissue parameters (ϵ and σ) is restricted to ± 5%. The uncertainty is the RSS of the ConvF uncertainty for indicated target tissue parameters.

^G Alpha/Depth are determined during calibration. SPEAG warrants that the remaining deviation due to the boundary effect after compensation is always less than ± 1% for frequencies below 3 GHz and below ± 2% for frequencies between 3-6 GHz at any distance larger than half the probe tip diameter from the boundary.

Frequency Response of E-Field


(TEM-Cell:ifi110 EXX, Waveguide: R22)





Uncertainty of Frequency Response of E-field: $\pm 6.3\%$ ($k=2$)

Receiving Pattern (ϕ), $\theta = 0^\circ$

f=600 MHz,TEM




f=1800 MHz,R22




Uncertainty of Axial Isotropy Assessment: $\pm 0.5\%$ ($k=2$)

Dynamic Range f(SAR_{head})
(TEM cell , f_{eval}= 1900 MHz)





Uncertainty of Linearity Assessment: ± 0.6% (k=2)

Conversion Factor Assessment



Deviation from Isotropy in Liquid

Error (ϕ, θ), $f = 900 \text{ MHz}$



Uncertainty of Spherical Isotropy Assessment: $\pm 2.6\%$ ($k=2$)



Appendix E. Conducted RF Output Power Table

The detailed power table are shown as follows.

Full Power Mode

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.8		824.2	836.4	848.8	
GSM 1 Tx slot		33.60	33.59	33.38	34.00	24.60	24.59	24.38	25.00
GPRS 1 Tx slot		33.59	33.58	33.36	34.00	24.59	24.58	24.36	25.00
GPRS 2 Tx slots		32.46	32.47	32.23	33.00	26.46	26.47	26.23	27.00
GPRS 3 Tx slots		30.24	30.24	30.00	31.00	25.98	25.98	25.74	26.74
GPRS 4 Tx slots		29.08	29.11	28.89	30.00	26.08	26.11	25.89	27.00
EDGE 1 Tx slot		26.52	26.60	26.56	28.00	17.52	17.60	17.56	19.00
EDGE 2 Tx slots		25.36	25.31	25.15	27.00	19.36	19.31	19.15	21.00
EDGE 3 Tx slots		22.81	22.82	22.70	24.00	18.55	18.56	18.44	19.74
EDGE 4 Tx slots		21.61	21.39	21.40	23.00	18.61	18.39	18.40	20.00

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	661	810		512	661	810	
Frequency (MHz)		1850.2	1880	1909.8		1850	1880	1910	
GSM 1 Tx slot		30.43	30.34	30.58	31.00	21.43	21.34	21.58	22.00
GPRS 1 Tx slot		30.41	30.33	30.57	31.00	21.41	21.33	21.57	22.00
GPRS 2 Tx slots		29.43	29.35	29.63	30.00	23.43	23.35	23.63	24.00
GPRS 3 Tx slots		27.41	27.31	27.62	29.00	23.15	23.05	23.36	24.74
GPRS 4 Tx slots		26.30	26.20	26.55	28.00	23.30	23.20	23.55	25.00
EDGE 1 Tx slot		26.10	26.33	26.20	27.00	17.10	17.33	17.20	18.00
EDGE 2 Tx slots		25.12	25.37	25.20	26.00	19.12	19.37	19.20	20.00
EDGE 3 Tx slots		23.11	23.32	23.17	24.00	18.85	19.06	18.91	19.74
EDGE 4 Tx slots		22.02	22.09	21.92	23.00	19.02	19.09	18.92	20.00

Band		WCDMA II			Tune-up Limit (dBm)	WCDMA V			Tune-up Limit (dBm)
TX Channel		8262	8400	8538		4132	4182	4233	
Rx Channel		9602	8800	9038		4357	4407	4458	
Frequency (MHz)		1852.4	1880	1907.6		826.4	836.4	846.6	
3GPP Rel 99	AMR 12.2kbps	23.62	23.91	23.75	24.50	24.16	24.30	24.32	25.00
3GPP Rel 99	RMC 12.2kbps	23.63	23.93	23.76	24.50	24.17	24.31	24.34	25.00
3GPP Rel 6	HSDPA Subtest-1	22.62	22.96	22.61	23.50	23.33	23.50	23.57	24.00
3GPP Rel 6	HSDPA Subtest-2	22.56	22.80	22.51	23.50	23.30	23.41	23.43	24.00
3GPP Rel 6	HSDPA Subtest-3	22.04	22.34	22.04	23.00	22.80	22.90	22.92	23.50
3GPP Rel 6	HSDPA Subtest-4	22.00	22.32	22.02	23.00	22.80	22.87	22.91	23.50
3GPP Rel 8	DC-HSDPA Subtest-1	22.59	22.90	22.54	23.50	23.30	23.48	23.52	24.00
3GPP Rel 8	DC-HSDPA Subtest-2	22.50	22.75	22.46	23.50	23.24	23.36	23.35	24.00
3GPP Rel 8	DC-HSDPA Subtest-3	22.00	22.26	22.01	23.00	22.77	22.83	22.86	23.50
3GPP Rel 8	DC-HSDPA Subtest-4	21.99	22.27	22.00	23.00	22.75	22.80	22.82	23.50
3GPP Rel 6	HSUPA Subtest-1	20.65	20.95	20.68	21.50	21.36	21.51	21.62	22.00
3GPP Rel 6	HSUPA Subtest-2	20.67	20.93	20.68	21.50	21.34	21.51	21.53	22.00
3GPP Rel 6	HSUPA Subtest-3	21.65	21.91	21.64	22.50	22.34	22.53	22.60	23.00
3GPP Rel 6	HSUPA Subtest-4	20.20	20.42	20.16	21.50	20.84	21.04	21.08	22.00
3GPP Rel 6	HSUPA Subtest-5	21.60	21.90	21.60	23.50	22.30	22.40	22.50	24.00
3GPP Rel 7	ISPA+ (16QAM) Subtest	21.68	21.90	21.74	23.50	22.31	22.51	22.53	24.00

Band 2									
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Turn-up limit (dBm)	MPR (dB)	
Channel				18700	18800	19100			
20	QPSK	1	0	23.13	23.21	23.20	24	0	
20	QPSK	1	49	23.53	23.61	23.47			
20	QPSK	1	99	23.15	23.18	23.16	23	1	
20	QPSK	50	0	22.51	22.59	22.65			
20	QPSK	50	24	22.57	22.60	22.58	23	1	
20	QPSK	50	50	22.52	22.60	22.61			
20	QPSK	100	0	22.52	22.61	22.60	23	1	
20	16QAM	1	0	22.39	22.52	22.48			
20	16QAM	1	49	22.80	22.74	22.72	22	1	
20	16QAM	1	99	22.35	22.38	22.32			
20	16QAM	50	0	21.48	21.67	21.62	22	2	
20	16QAM	50	24	21.63	21.57	21.53			
20	16QAM	50	50	21.50	21.55	21.55	22	2	
20	16QAM	100	0	21.49	21.58	21.54			
20	64QAM	1	0	21.30	21.43	21.40	22	2	
20	64QAM	1	49	21.71	21.68	21.64			
20	64QAM	1	99	21.25	21.30	21.25	22	2	
20	64QAM	50	0	20.48	20.65	20.59			
20	64QAM	50	24	20.52	20.56	20.54	21	3	
20	64QAM	50	50	20.50	20.55	20.54			
20	64QAM	100	0	20.49	20.59	20.56			
Channel				18875	18900	19125	Turn-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1887.5	18900	1902.5			
15	QPSK	1	0	23.26	23.39	23.32	24	0	
15	QPSK	1	37	23.53	23.54	23.58			
15	QPSK	1	74	23.23	23.28	23.34	23	1	
15	QPSK	36	0	22.45	22.61	22.60			
15	QPSK	36	20	22.51	22.55	22.56	23	1	
15	QPSK	36	36	22.53	22.57	22.60			
15	QPSK	75	0	22.50	22.59	22.63	23	1	
15	16QAM	1	0	22.53	22.63	22.56			
15	16QAM	1	37	22.80	22.80	22.74	22	2	
15	16QAM	1	74	22.53	22.51	22.50			
15	16QAM	36	0	21.42	21.56	21.53	22	2	
15	16QAM	36	20	21.45	21.48	21.48			
15	16QAM	36	36	21.47	21.49	21.52	22	2	
15	16QAM	75	0	21.45	21.54	21.55			
15	64QAM	1	0	21.43	21.55	21.49	22	2	
15	64QAM	1	37	21.70	21.69	21.69			
15	64QAM	1	74	21.41	21.43	21.43	21	3	
15	64QAM	36	0	20.40	20.55	20.53			
15	64QAM	36	20	20.45	20.50	20.50	21	3	
15	64QAM	36	36	20.45	20.48	20.51			
15	64QAM	75	0	20.45	20.52	20.56			
Channel				18950	18900	19150	Turn-up limit (dBm)	MPR (dB)	
Frequency (MHz)				18950	18900	1905			
10	QPSK	1	0	23.29	23.42	23.38	24	0	
10	QPSK	1	25	23.41	23.51	23.52			
10	QPSK	1	49	23.36	23.37	23.43	23	1	
10	QPSK	25	0	22.47	22.60	22.62			
10	QPSK	25	12	22.45	22.57	22.60	23	1	
10	QPSK	25	25	22.53	22.56	22.61			
10	QPSK	50	0	22.48	22.59	22.64	23	1	
10	16QAM	1	0	22.55	22.69	22.59			
10	16QAM	1	25	22.67	22.76	22.76	22	2	
10	16QAM	1	49	22.64	22.64	22.59			
10	16QAM	25	0	21.44	21.55	21.57	22	2	
10	16QAM	25	12	21.42	21.53	21.57			
10	16QAM	25	25	21.50	21.55	21.60	22	2	
10	16QAM	50	0	21.45	21.56	21.58			
10	64QAM	1	0	21.45	21.58	21.53	22	2	
10	64QAM	1	25	21.54	21.65	21.69			
10	64QAM	1	49	21.51	21.53	21.49	21	3	
10	64QAM	25	0	20.43	20.56	20.57			
10	64QAM	25	12	20.41	20.52	20.55	21	3	
10	64QAM	25	25	20.51	20.52	20.52			
10	64QAM	50	0	20.45	20.55	20.57			
Channel				19025	18900	19175	Turn-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1902.5	1890	1907.5			
5	QPSK	1	0	23.20	23.29	23.35	24	0	
5	QPSK	1	12	23.49	23.51	23.56			
5	QPSK	1	24	23.14	23.27	23.36	23	1	
5	QPSK	12	0	22.37	22.49	22.52			
5	QPSK	12	7	22.42	22.52	22.57	23	1	
5	QPSK	12	13	22.36	22.48	22.51			
5	QPSK	25	0	22.38	22.51	22.52	23	1	
5	16QAM	1	0	22.44	22.54	22.60			
5	16QAM	1	12	22.70	22.76	22.77	22	2	
5	16QAM	1	24	22.41	22.51	22.51			
5	16QAM	12	0	21.35	21.45	21.49	22	2	
5	16QAM	12	7	21.39	21.48	21.57			
5	16QAM	12	13	21.33	21.44	21.49	22	2	
5	16QAM	25	0	21.37	21.46	21.53			
5	64QAM	1	0	21.36	21.47	21.52	22	2	
5	64QAM	1	12	21.62	21.73	21.70			
5	64QAM	1	24	21.36	21.47	21.41	21	3	
5	64QAM	12	0	20.34	20.42	20.49			
5	64QAM	12	7	20.37	20.49	20.56	21	3	
5	64QAM	12	13	20.31	20.43	20.49			
5	64QAM	25	0	20.36	20.45	20.51			
Channel				18915	18900	19185	Turn-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1891.5	1890	1909.5			
3	QPSK	1	0	23.14	23.25	23.30	24	0	
3	QPSK	1	8	23.13	23.23	23.30			
3	QPSK	1	14	23.12	23.23	23.30	23	1	
3	QPSK	8	0	22.24	22.35	22.36			
3	QPSK	8	4	22.25	22.37	22.41	23	1	
3	QPSK	8	7	22.21	22.34	22.36			
3	QPSK	15	0	22.24	22.36	22.40	23	1	
3	16QAM	1	8	22.38	22.52	22.45			
3	16QAM	1	14	22.39	22.51	22.47	22	2	
3	16QAM	8	0	21.25	21.38	21.38			
3	16QAM	8	4	21.26	21.39	21.44	22	2	
3	16QAM	8	7	21.22	21.33	21.38			
3	16QAM	15	0	21.19	21.33	21.38	22	2	
3	64QAM	1	0	21.31	21.41	21.39			
3	64QAM	1	8	21.30	21.44	21.40	22	2	
3	64QAM	1	14	21.27	21.42	21.36			
3	64QAM	8	0	20.22	20.34	20.37	21	3	
3	64QAM	8	4	20.21	20.36	20.41			
3	64QAM	8	7	20.19	20.32	20.37			
3	64QAM	15	0	20.17	20.32	20.38			
Channel				19007	18900	19193	Turn-up limit (dBm)	MPR (dB)	
Frequency (MHz)				1900.7	1890	1909.3			
1.4	QPSK	1	0	23.14	23.22	23.30	24	0	
1.4	QPSK	1	3	23.23	23.34	23.40			
1.4	QPSK	1	5	23.12	23.25	23.29	23	1	
1.4	QPSK	3	1	23.30	23.41	23.48			
1.4	QPSK	3	1	23.26	23.36	23.42	23	1	
1.4	QPSK	6	0	22.29	22.41	22.45			
1.4	16QAM	1	0	22.35	22.64	22.67	23	1	
1.4	16QAM	1	3	22.51	22.62	22.67			
1.4	16QAM	1	5	22.38	22.52	22.42	23	1	
1.4	16QAM	3	0	22.20	22.35	22.29			
1.4	16QAM	3	1	22.27	22.40	22.36	22	2	
1.4	16QAM	3	3	22.20	22.34	22.28			
1.4	16QAM	6	0	21.34	21.46	21.50	22	2	
1.4	64QAM	1	0	21.29	21.43	21.37			
1.4	64QAM	1	3	21.40	21.53	21.44	22	2	
1.4	64QAM	1	5	21.33	21.42	21.41			
1.4	64QAM	3	0	21.25	21.38	21.36	22	2	
1.4	64QAM	3	1	21.33	21.44	21.44			
1.4	64QAM	3	3	21.27	21.38	21.34	21	3	
1.4	64QAM	6	0	20.26	20.39	20.44			

Band 7									
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)	
Channel				2090	2100	2130	24	0	
Frequency (MHz)				2510	2535	2560			
20	QPSK	1	0	23.05	23.15	23.11			
20	QPSK	1	49	23.08	23.54	23.15	23	1	
20	QPSK	1	99	23.07	23.13	23.08			
20	QPSK	50	0	22.06	22.28	22.17			
20	QPSK	50	24	22.10	22.43	22.15	23	1	
20	QPSK	50	50	22.13	22.47	22.06			
20	QPSK	100	0	22.02	22.39	22.15			
20	16QAM	1	0	22.11	22.28	22.12	23	1	
20	16QAM	1	49	22.38	22.60	22.50			
20	16QAM	1	99	22.19	22.31	22.12			
20	16QAM	50	0	21.16	21.34	21.20	22	2	
20	16QAM	50	24	21.12	21.48	21.19			
20	16QAM	50	50	21.15	21.51	21.11			
20	16QAM	100	0	20.99	21.43	21.15	22	2	
20	84QAM	1	0	21.18	21.13	21.01			
20	84QAM	1	49	21.28	21.46	21.43			
20	84QAM	1	99	21.07	21.19	21.19	21	3	
20	84QAM	50	0	20.14	20.36	20.17			
20	84QAM	50	24	20.11	20.49	20.15			
20	84QAM	50	50	20.14	20.52	20.10	21	3	
20	84QAM	100	0	20.01	20.48	20.20			
Channel				2090	2100	2130			
Frequency (MHz)				2597.5	2635	2662.5	Tune-up limit (dBm)	MPR (dB)	
15	QPSK	1	0	23.10	23.16	23.15	24	0	
15	QPSK	1	37	23.11	23.53	23.15			
15	QPSK	1	74	23.05	23.22	23.14	23	1	
15	QPSK	36	0	22.09	22.37	22.17			
15	QPSK	36	20	22.07	22.46	22.12			
15	QPSK	36	39	22.13	22.45	22.06	23	1	
15	QPSK	75	0	22.02	22.40	22.11			
15	16QAM	1	0	22.24	22.49	22.37	23	1	
15	16QAM	1	37	22.35	22.67	22.53			
15	16QAM	1	74	22.28	22.51	22.19	22	2	
15	16QAM	36	0	21.13	21.42	21.14			
15	16QAM	36	20	21.05	21.47	21.14			
15	16QAM	36	39	21.12	21.49	21.06	22	2	
15	16QAM	75	0	21.02	21.45	21.17			
15	84QAM	1	0	21.15	21.37	21.24	22	2	
15	84QAM	1	37	21.30	21.50	21.44			
15	84QAM	1	74	21.17	21.41	21.17	21	3	
15	84QAM	36	0	20.20	20.44	20.15			
15	84QAM	36	20	20.06	20.47	20.13			
15	84QAM	36	39	20.10	20.50	20.08	21	3	
15	84QAM	75	0	20.03	20.47	20.15			
Channel				2090	2100	2140	Tune-up limit (dBm)	MPR (dB)	
Frequency (MHz)				2595	2635	2665	24 <td rowspan="2">0</td> <td rowspan="2"></td>	0	
10	QPSK	1	0	23.14	23.26	23.18			
10	QPSK	1	25	22.95	23.44	23.02	23	1	
10	QPSK	1	49	23.08	23.31	23.17			
10	QPSK	25	0	22.08	22.37	22.08	23	1	
10	QPSK	25	12	21.97	22.39	22.06			
10	QPSK	25	25	22.13	22.45	22.03	23	1	
10	QPSK	50	0	22.02	22.41	22.09			
10	16QAM	1	0	22.19	22.62	22.36	23	1	
10	16QAM	1	25	22.26	22.56	22.40			
10	16QAM	1	49	22.26	22.64	22.24	22	2	
10	16QAM	25	0	21.10	21.45	21.11			
10	16QAM	25	12	21.07	21.45	21.07	22	2	
10	16QAM	25	25	21.13	21.56	21.10			
10	16QAM	50	0	21.06	21.49	21.11	22	2	
10	84QAM	1	0	21.05	21.45	21.22			
10	84QAM	1	25	21.19	21.53	21.30	21	3	
10	84QAM	1	49	21.13	21.50	21.12			
10	84QAM	25	0	20.07	20.44	20.12	21	3	
10	84QAM	25	12	20.06	20.46	20.07			
10	84QAM	25	25	20.12	20.51	20.09			
10	84QAM	50	0	20.00	20.47	20.11	21	3	
Channel				2077.5	2100	2142.5			
Frequency (MHz)				2592.5	2635	2657.5	Tune-up limit (dBm)	MPR (dB)	
5	QPSK	1	0	23.05	23.21	23.02	24	0	
5	QPSK	1	12	22.93	23.42	23.06			
5	QPSK	1	24	23.06	23.24	23.07	23	1	
5	QPSK	12	0	21.90	22.29	21.95			
5	QPSK	12	7	21.96	22.37	21.98	23	1	
5	QPSK	12	13	21.94	22.38	21.97			
5	QPSK	25	0	21.91	22.33	21.96	23	1	
5	16QAM	1	0	22.09	22.53	22.17			
5	16QAM	1	12	22.33	22.57	22.35	23	1	
5	16QAM	1	24	22.09	22.50	22.09			
5	16QAM	12	0	21.03	21.38	20.98	22	2	
5	16QAM	12	7	20.98	21.45	21.00			
5	16QAM	12	13	20.99	21.46	20.97	22	2	
5	16QAM	25	0	20.92	21.41	21.06			
5	84QAM	1	0	21.09	21.39	21.08	22	2	
5	84QAM	1	12	21.18	21.49	21.24			
5	84QAM	1	24	21.01	21.46	21.01	21	3	
5	84QAM	12	0	20.01	20.34	19.93			
5	84QAM	12	7	19.94	20.41	19.97	21	3	
5	84QAM	12	13	19.96	20.41	19.96			
5	84QAM	25	0	19.94	20.44	20.02	21	3	

Band 26									
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. (Freq.)	Power Middle Ch. (Freq.)	Power High Ch. (Freq.)	Tune-up limit (dBm)	MPR (dB)	
Channel				26705	26805	26905	24.5	0	
Frequency (MHz)				821.5	831.5	841.5			
15	QPSK	1	0	23.43	23.58	23.65			
15	QPSK	1	37	23.81	23.90	24.00	23.5	1	
15	QPSK	1	74	23.66	23.67	23.69			
15	QPSK	36	0	22.65	22.82	22.87	23.5	1	
15	QPSK	36	20	22.76	22.84	22.86			
15	QPSK	36	39	22.83	22.78	22.75			
15	QPSK	75	0	22.70	22.81	22.83	23.5	1	
15	16QAM	1	0	22.76	22.83	22.93			
15	16QAM	1	37	22.78	22.88	22.67	22.5	2	
15	16QAM	1	74	22.89	22.97	22.96			
15	16QAM	36	0	21.63	21.83	21.91	22.5	2	
15	16QAM	36	20	21.77	21.87	21.88			
15	16QAM	36	39	21.83	21.81	21.80	21.5	3	
15	16QAM	75	0	21.75	21.83	21.88			
15	84QAM	1	0	21.66	21.76	21.87	22.5	2	
15	84QAM	1	37	22.00	21.65	21.67			
15	84QAM	1	74	21.79	21.88	21.90	21.5	3	
15	84QAM	36	0	20.60	20.82	20.90			
15	84QAM	36	20	20.80	20.86	20.90	21.5	3	
15	84QAM	36	39	20.83	20.81	20.78			
15	84QAM	75	0	20.74	20.85	20.87	21.5	3	
Channel				26740	26805	26900			
Frequency (MHz)				819	831.5	844	24.5	0	
10	QPSK	1	0	23.46	23.67	23.75			
10	QPSK	1	25	23.66	23.81	23.82	23.5	1	
10	QPSK	1	49	23.66	23.71	23.78			
10	QPSK	25	0	22.63	22.92	22.89	23.5	1	
10	QPSK	25	12	22.67	22.84	22.81			
10	QPSK	25	25	22.76	22.78	22.72	23.5	1	
10	QPSK	50	0	22.73	22.87	22.83			
10	16QAM	1	0	22.75	22.87	22.67	23.5	1	
10	16QAM	1	25	23.00	23.00	22.66			
10	16QAM	1	49	22.86	22.76	23.00	22.5	2	
10	16QAM	25	0	21.63	21.94	21.92			
10	16QAM	25	12	21.70	21.89	21.88	22.5	2	
10	16QAM	25	25	21.82	21.80	21.77			
10	16QAM	50	0	21.73	21.91	21.88	22.5	2	
10	84QAM	1	0	21.67	21.77	21.92			
10	84QAM	1	25	21.88	21.93	21.96	22.5	2	
10	84QAM	1	49	21.81	21.90	21.91			
10	84QAM	25	0	20.65	20.96	20.95	21.5	3	
10	84QAM	25	12	20.69	20.90	20.90			
10	84QAM	25	25	20.82	20.82	20.78	21.5	3	
10	84QAM	50	0	20.73	20.88	20.90			
Channel				26715	26805	27015	24.5	0	
Frequency (MHz)				816.5	831.5	846.5			
5	QPSK	1	0	23.41	23.66	23.67	24.5	0	
5	QPSK	1	12	23.66	23.86	23.88			
5	QPSK	1	24	23.46	23.66	23.70	23.5	1	
5	QPSK	12	0	22.56	22.83	22.88			
5	QPSK	12	7	22.65	22.82	22.89	23.5	1	
5	QPSK	12	13	22.66	22.73	22.88			
5	QPSK	25	0	22.61	22.79	22.80	23.5	1	
5	16QAM	1	0	22.69	22.82	22.89			
5	16QAM	1	12	22.97	22.67	22.66	23.5	1	
5	16QAM	1	24	22.86	22.54	22.84			
5	16QAM	12	0	21.57	21.83	21.94	22.5	2	
5	16QAM	12	7	21.65	21.84	21.87			
5	16QAM	12	13	21.63	21.77	21.85	22.5	2	
5	16QAM	25	0	21.63	21.85	21.93			
5	84QAM	1	0	21.71	21.77	21.80	22.5	2	
5	84QAM	1	12	21.89	21.67	21.65			
5	84QAM	1	24	21.76	21.81	21.89	21.5	3	
5	84QAM	12	0	20.56	20.82	20.79			
5	84QAM	12	7	20.64	20.84	20.82	21.5	3	
5	84QAM	12	13	20.63	20.76	20.82			
5	84QAM	25	0	20.63	20.88	20.95	21.5	3	
Channel				26705	26805	27025			
Frequency (MHz)				815.5	831.5	847.5	24.5	0	
3	QPSK	1	0	23.50	23.74	23.80			
3	QPSK	1	8	23.47	23.72	23.78	24.5	0	
3	QPSK	1	16	23.50	23.74	23.78			
3	QPSK	8	0	22.58	22.79	22.85	23.5	1	
3	QPSK	8	4	22.63	22.80	22.89			
3	QPSK	8	7	22.60	22.78	22.83	23.5	1	
3	QPSK	15	0	22.60	22.82	22.86			
3	16QAM	1	0	22.81	22.98	22.97	23.5	1	
3	16QAM	1	8	22.81	22.94	22.66			
3	16QAM	1	16	22.86	22.99	22.76	23.5	1	
3	16QAM	8	0	21.62	21.89	21.97			
3	16QAM	8	4	21.68	21.90	21.99	22.5	2	
3	16QAM	8	7	21.67	21.87	21.93			
3	16QAM	15	0	21.61	21.86	21.94	22.5	2	
3	84QAM	1	0	21.70	21.86	21.93			
3	84QAM	1	8	21.73	21.88	21.98	22.5	2	
3	84QAM	1	16	21.77	21.96	21.93			
3	84QAM	8	0	20.61	20.86	20.95	21.5	3	
3	84QAM	8	4	20.68	20.90	20.95			
3	84QAM	8	7	20.62	20.88	20.90	21.5	3	
3	84QAM	15	0	20.59	20.83	20.91			
Channel				26937	26805	27033	24.5	0	
Frequency (MHz)				814.7	831.5	848.3			
1.4	QPSK	1	0	23.54	23.46	23.70	24.5	0	
1.4	QPSK	1	3	23.68	23.71	23.91			
1.4	QPSK	1	5	23.58	23.54	23.79	24.5	0	
1.4	QPSK	3	0	23.57	23.62	23.75			
1.4	QPSK	3	1	23.62	23.60	23.78	23.5	1	
1.4	QPSK	3	3	23.45	23.56	23.63			
1.4	QPSK	6	0	22.48	22.44	22.35	23.5	1	
1.4	16QAM	1	0	22.68	22.77	22.99			
1.4	16QAM	1	3	22.60	22.78	22.63	23.5	1	
1.4	16QAM	1	5	22.54	22.69	22.72			
1.4	16QAM	3	0	22.47	22.65	22.70	23.5	1	
1.4	16QAM	3	1	22.81	22.81	22.69			
1.4	16QAM	3	3	22.60	22.74	22.73	22.5	2	
1.4	16QAM	6	0	21.53	21.68	21.83			
1.4	84QAM	1	0	21.75	21.57	21.51	22.5	2	
1.4	84QAM	1	3	21.70	21.71	21.65			
1.4	84QAM	1	5	21.61	21.71	21.71	22.5	2	
1.4	84QAM	3	0	21.65	21.66	21.72			
1.4	84QAM	3	1	21.67	21.60	21.62	21.5	3	
1.4	84QAM	3	3	21.59	21.73	21.60			
1.4	84QAM	6	0	20.63	20.76	20.81	21.5	3	

Band 41									
BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Low Ch. / Freq.	Power Middle High Ch. / Freq.	Power High Ch. / Freq.	Tune-up limit (dBm)	MPR (dB)
Channel				40140	40400	40670	41140		
Frequency (MHz)				2545	2571	2598	2645		
20	QPSK	1	0	23.82	23.87	23.97	23.76	24	0
20	QPSK	1	49	23.92	23.88	23.89	23.67		
20	QPSK	1	99	23.77	23.85	23.78	23.73		
20	QPSK	50	0	22.66	22.98	22.91	22.85		
20	QPSK	50	24	22.76	22.88	22.99	22.88	23	1
20	QPSK	50	50	22.77	22.78	22.67	22.82		
20	QPSK	100	0	22.74	22.87	22.89	22.84		
20	16QAM	1	0	22.77	22.75	22.78	22.82		
20	16QAM	1	49	22.45	22.65	22.66	22.76	23	1
20	16QAM	1	99	22.84	22.91	22.80	22.88		
20	16QAM	50	0	21.77	21.56	21.97	21.78		
20	16QAM	50	24	21.86	21.76	21.88	21.67		
20	16QAM	50	50	21.87	21.77	21.89	21.66	22	2
20	16QAM	100	0	21.84	21.77	21.78	21.76		
20	64QAM	1	0	21.60	21.53	21.58	21.61		
20	64QAM	1	49	21.66	21.72	21.71	21.67		
20	64QAM	1	99	21.65	21.41	21.32	21.60	22	2
20	64QAM	50	0	20.77	20.78	20.68	20.93		
20	64QAM	50	24	20.88	20.89	20.79	20.95		
20	64QAM	50	50	20.89	20.96	20.88	20.85		
20	64QAM	100	0	20.92	20.92	20.87	20.67		
Channel				40115	40395	40685	41165		
Frequency (MHz)				2542.5	2570.5	2599.5	2647.5	Tune-up limit (dBm)	MPR (dB)
15	QPSK	1	0	23.63	23.89	23.90	23.73	24	0
15	QPSK	1	37	23.94	23.80	23.80	23.78		
15	QPSK	1	74	23.73	23.74	23.63	23.71		
15	QPSK	36	0	22.75	22.77	22.72	22.89		
15	QPSK	36	20	22.81	22.82	22.76	22.90	23	1
15	QPSK	36	39	22.81	22.87	22.83	22.87		
15	QPSK	75	0	22.77	22.79	22.71	22.89		
15	16QAM	1	0	22.69	22.95	22.95	22.82		
15	16QAM	1	37	22.67	22.66	22.76	22.67	23	1
15	16QAM	1	74	22.79	22.77	22.98	22.77		
15	16QAM	36	0	21.76	21.56	21.95	21.84		
15	16QAM	36	20	21.81	21.66	21.67	21.88		
15	16QAM	36	39	21.78	21.54	21.66	21.80	22	2
15	16QAM	75	0	21.84	21.55	21.56	21.86		
15	64QAM	1	0	21.46	21.71	21.74	21.58		
15	64QAM	1	37	21.74	21.91	21.92	21.76		
15	64QAM	1	74	21.54	21.86	21.74	21.53	22	2
15	64QAM	36	0	20.80	20.82	20.74	20.90		
15	64QAM	36	20	20.89	20.84	20.76	20.90		
15	64QAM	36	39	20.85	20.90	20.82	20.84		
15	64QAM	75	0	20.83	20.87	20.76	20.89		
Channel				40090	40390	40690	41190		
Frequency (MHz)				2540	2570	2600	2650	Tune-up limit (dBm)	MPR (dB)
10	QPSK	1	0	23.72	23.71	23.71	23.86	24	0
10	QPSK	1	25	23.66	23.69	23.66	23.79		
10	QPSK	1	49	23.76	23.75	23.71	23.81		
10	QPSK	25	0	22.76	22.79	22.74	22.91		
10	QPSK	25	12	22.80	22.80	22.75	22.92	23	1
10	QPSK	25	25	22.79	22.82	22.76	22.87		
10	QPSK	50	0	22.78	22.81	22.73	22.89		
10	16QAM	1	0	22.75	22.78	22.77	22.95		
10	16QAM	1	25	22.78	22.71	22.71	22.84	23	1
10	16QAM	1	49	22.80	22.84	22.74	22.87		
10	16QAM	25	0	21.84	21.87	21.82	21.93		
10	16QAM	25	12	21.86	21.89	21.84	21.92		
10	16QAM	25	25	21.84	21.87	21.87	21.89	22	2
10	16QAM	50	0	21.90	21.90	21.79	21.91		
10	64QAM	1	0	21.53	21.81	21.81	21.66		
10	64QAM	1	25	21.54	21.77	21.76	21.61		
10	64QAM	1	49	21.57	21.89	21.80	21.61	22	2
10	64QAM	25	0	20.81	20.82	20.76	20.88		
10	64QAM	25	12	20.79	20.85	20.82	20.90		
10	64QAM	25	25	20.81	20.85	20.82	20.86		
10	64QAM	50	0	20.82	20.85	20.76	20.85		
Channel				40065	40385	40705	41215		
Frequency (MHz)				2537.5	2569.5	2601.5	2652.5	Tune-up limit (dBm)	MPR (dB)
5	QPSK	1	0	23.80	23.94	23.88	23.74	24	0
5	QPSK	1	12	23.94	23.90	23.80	23.67		
5	QPSK	1	24	23.86	23.68	23.60	23.71		
5	QPSK	12	0	22.72	22.76	22.70	22.84		
5	QPSK	12	7	22.75	22.83	22.80	22.88	23	1
5	QPSK	12	13	22.75	22.77	22.78	22.87		
5	QPSK	25	0	22.73	22.78	22.74	22.85		
5	16QAM	1	0	22.70	22.75	22.68	22.82		
5	16QAM	1	12	22.56	22.90	22.87	22.56	23	1
5	16QAM	1	24	22.71	22.77	22.67	22.80		
5	16QAM	12	0	21.75	21.78	21.69	21.83		
5	16QAM	12	7	21.82	21.82	21.80	21.85		
5	16QAM	12	13	21.76	21.78	21.78	21.86	22	2
5	16QAM	25	0	21.85	21.85	21.82	21.92		
5	64QAM	1	0	21.46	21.80	21.76	21.58		
5	64QAM	1	12	21.75	21.96	21.93	21.77		
5	64QAM	1	24	21.48	21.82	21.74	21.59	21	3
5	64QAM	12	0	20.72	20.75	20.67	20.82		
5	64QAM	12	7	20.84	20.84	20.79	20.86		
5	64QAM	12	13	20.71	20.76	20.75	20.85		
5	64QAM	25	0	20.78	20.80	20.75	20.87		

Reduced Power Mode for Sensor on/Handheld on

GSM850		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		128	189	251		128	189	251	
Frequency (MHz)		824.2	836.4	848.6		824.2	836.4	848.6	
GSM 1 Tx slot		32.30	32.02	31.94	33.00	23.30	23.02	22.94	24.00
GPRS 1 Tx slot		32.28	32.01	31.93	33.00	23.28	23.01	22.93	24.00
GPRS 2 Tx slots		31.18	30.95	30.85	32.00	25.18	24.95	24.85	26.00
GPRS 3 Tx slots		29.04	28.90	28.83	30.00	24.78	24.64	24.57	25.74
GPRS 4 Tx slots		28.58	28.65	28.64	29.00	25.58	25.65	25.64	26.00
EDGE 1 Tx slot		25.41	25.33	25.34	27.00	16.41	16.33	16.34	18.00
EDGE 2 Tx slots		24.17	24.06	24.16	26.00	18.17	18.06	18.16	20.00
EDGE 3 Tx slots		21.84	21.71	21.73	23.00	17.58	17.45	17.47	18.74
EDGE 4 Tx slots		20.62	20.44	20.39	22.00	17.62	17.44	17.39	19.00

GSM1900		Burst Average Power (dBm)			Tune-up Limit (dBm)	Frame-Average Power (dBm)			Tune-up Limit (dBm)
TX Channel		512	681	810		512	681	810	
Frequency (MHz)		1850.2	1880	1909.8		1850.2	1880	1909.8	
GSM 1 Tx slot		28.00	28.24	28.21	28.50	19.00	19.24	19.21	19.50
GPRS 1 Tx slot		27.99	28.23	28.20	28.50	18.99	19.23	19.20	19.50
GPRS 2 Tx slots		27.15	27.24	27.25	27.50	21.15	21.24	21.25	21.50
GPRS 3 Tx slots		25.32	25.39	25.56	26.50	21.06	21.13	21.30	22.24
GPRS 4 Tx slots		24.39	24.47	24.61	25.50	21.39	21.47	21.61	22.50
EDGE 1 Tx slot		24.22	23.80	24.29	24.50	15.22	14.80	15.29	15.50
EDGE 2 Tx slots		23.16	22.79	23.25	23.50	17.18	16.79	17.25	17.50
EDGE 3 Tx slots		21.14	20.76	21.21	21.50	16.88	16.50	16.95	17.24
EDGE 4 Tx slots		20.08	19.99	20.09	20.50	17.08	16.99	17.09	17.50

Band		WCDMA II			Tune-up Limit (dBm)
TX Channel		9262	9400	9538	
Rx Channel		9602	9800	9938	
Frequency (MHz)		1852.4	1880	1907.6	
3GPP Rel 99	AMR 12.2Kbps	21.16	21.37	21.36	22.50
3GPP Rel 99	AMR 12.2Kbps	21.19	21.35	21.37	22.50
3GPP Rel 6	HSDPA Subtest-1	20.30	20.40	20.51	21.50
3GPP Rel 6	HSDPA Subtest-2	20.30	20.35	20.43	21.50
3GPP Rel 6	HSDPA Subtest-3	19.66	19.83	19.89	21.00
3GPP Rel 6	HSDPA Subtest-4	19.75	19.86	19.91	21.00
3GPP Rel 6	DC-HSDPA Subtest-1	20.33	20.41	20.45	21.50
3GPP Rel 6	DC-HSDPA Subtest-2	20.32	20.40	20.43	21.50
3GPP Rel 6	DC-HSDPA Subtest-3	19.70	19.82	19.88	21.00
3GPP Rel 6	DC-HSDPA Subtest-4	19.71	19.82	19.89	21.00
3GPP Rel 6	HSUPA Subtest-1	18.40	18.53	18.48	19.50
3GPP Rel 6	HSUPA Subtest-2	18.31	18.51	18.49	19.50
3GPP Rel 6	HSUPA Subtest-3	19.40	19.49	19.52	20.50
3GPP Rel 6	HSUPA Subtest-4	17.92	18.02	18.07	19.50
3GPP Rel 6	HSUPA Subtest-5	19.53	19.57	19.62	21.50
3GPP Rel 7	HSPA+ (16QAM) Subtest-1	19.50	19.56	19.66	21.50

Band 2									
BW (MHz)	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	Turn-up limit (dBm)	MPR (dB)	
Channel				18700	18800	19000			
Frequency (MHz)				1860	1880	1900			
20	QPSK	1	0	20.33	20.23	20.38	22	0	
20	QPSK	1	49	20.66	20.73	20.70			
20	QPSK	1	99	20.39	20.42	20.38			
20	QPSK	50	0	19.65	19.88	19.82			
20	QPSK	50	24	19.43	19.41	19.52	21	1	
20	QPSK	50	50	19.40	19.45	19.42			
20	QPSK	100	0	19.41	19.71	19.69			
20	16QAM	1	0	19.18	19.25	19.51			
20	16QAM	1	49	19.30	19.36	19.55	21	1	
20	16QAM	1	99	19.42	19.55	19.25			
20	16QAM	50	0	18.50	18.37	18.31			
20	16QAM	50	24	18.30	18.26	18.30			
20	16QAM	50	50	18.15	18.28	18.42	20	2	
20	16QAM	100	0	18.24	18.32	18.32			
20	64QAM	1	0	18.17	18.14	18.13			
20	64QAM	1	49	18.21	18.30	18.27			
20	64QAM	1	99	18.06	18.28	18.34	20	2	
20	64QAM	50	0	17.35	17.36	17.35			
20	64QAM	50	24	17.27	17.25	17.45			
20	64QAM	50	50	17.33	17.29	17.51			
20	64QAM	100	0	17.26	17.28	17.27	Turn-up limit (dBm)	MPR (dB)	
Channel				18675	18800	19125			
Frequency (MHz)				1867.5	18800	1902.5			
15	QPSK	1	0	20.17	20.10	20.11	22	0	
15	QPSK	1	37	20.42	20.23	20.45			
15	QPSK	1	74	20.02	20.24	20.42			
15	QPSK	36	0	19.25	19.28	19.35			
15	QPSK	36	20	19.23	19.33	19.40	21	1	
15	QPSK	36	39	19.26	19.26	19.49			
15	QPSK	75	0	19.32	19.35	19.35			
15	16QAM	1	0	19.40	19.38	19.14			
15	16QAM	1	37	19.42	19.51	19.52	21	1	
15	16QAM	1	74	19.32	19.48	19.40			
15	16QAM	36	0	18.38	18.23	18.36			
15	16QAM	36	20	18.41	18.28	18.43			
15	16QAM	36	39	18.26	18.31	18.43	20	2	
15	16QAM	75	0	18.35	18.37	18.43			
15	64QAM	1	0	18.48	18.22	18.31			
15	64QAM	1	37	18.35	18.34	18.51			
15	64QAM	1	74	18.37	18.51	18.43	20	2	
15	64QAM	36	0	17.25	17.32	17.39			
15	64QAM	36	20	17.37	17.19	17.39			
15	64QAM	36	39	17.20	17.29	17.43			
15	64QAM	75	0	17.27	17.25	17.34	Turn-up limit (dBm)	MPR (dB)	
Channel				18650	18800	19150			
Frequency (MHz)				18650	18800	19050			
10	QPSK	1	0	20.33	20.10	20.24	22	0	
10	QPSK	1	25	20.42	20.26	20.46			
10	QPSK	1	49	20.08	20.24	20.29			
10	QPSK	25	0	19.30	19.17	19.33			
10	QPSK	25	12	19.32	19.30	19.40	21	1	
10	QPSK	25	25	19.25	19.20	19.46			
10	QPSK	50	0	19.28	19.21	19.38			
10	16QAM	1	0	19.32	19.15	19.45			
10	16QAM	1	25	19.68	19.33	19.41	21	1	
10	16QAM	1	49	19.35	19.59	19.74			
10	16QAM	25	0	18.30	18.25	18.30			
10	16QAM	25	12	18.39	18.40	18.51			
10	16QAM	25	25	18.14	18.27	18.28	20	2	
10	16QAM	50	0	18.24	18.19	18.30			
10	64QAM	1	0	18.62	18.35	18.28			
10	64QAM	1	25	18.69	18.38	18.62			
10	64QAM	1	49	18.29	18.45	18.74	19	3	
10	64QAM	25	0	17.37	17.16	17.25			
10	64QAM	25	12	17.30	17.23	17.58			
10	64QAM	25	25	17.30	17.23	17.44			
10	64QAM	50	0	17.33	17.17	17.49	Turn-up limit (dBm)	MPR (dB)	
Channel				18625	18800	19175			
Frequency (MHz)				1862.5	18800	1907.5			
5	QPSK	1	0	20.12	20.02	20.24	22	0	
5	QPSK	1	12	20.30	20.25	20.43			
5	QPSK	1	24	20.16	20.06	20.28			
5	QPSK	12	0	19.21	19.15	19.39			
5	QPSK	12	7	19.34	19.26	19.50	21	1	
5	QPSK	12	13	19.30	19.27	19.48			
5	QPSK	25	0	19.21	19.19	19.34			
5	16QAM	1	0	19.42	19.32	19.47			
5	16QAM	1	12	19.31	19.47	19.55	21	1	
5	16QAM	1	24	19.30	19.23	19.10			
5	16QAM	12	0	18.28	18.29	18.47			
5	16QAM	12	7	18.27	18.29	18.52			
5	16QAM	12	13	18.25	18.32	18.35	20	2	
5	16QAM	25	0	18.22	18.14	18.27			
5	64QAM	1	0	18.17	18.28	18.29			
5	64QAM	1	12	18.55	18.31	18.44			
5	64QAM	1	24	18.44	18.14	18.39	20	2	
5	64QAM	12	0	17.18	17.14	17.38			
5	64QAM	12	7	17.31	17.34	17.43			
5	64QAM	12	13	17.35	17.31	17.39			
5	64QAM	25	0	17.31	17.29	17.38	Turn-up limit (dBm)	MPR (dB)	
Channel				18615	18800	19185			
Frequency (MHz)				1861.5	18800	1908.5			
3	QPSK	1	0	20.25	20.12	20.39	22	0	
3	QPSK	1	8	20.24	20.23	20.43			
3	QPSK	1	14	20.31	20.28	20.36			
3	QPSK	8	0	19.34	19.23	19.38			
3	QPSK	8	4	19.27	19.17	19.56	21	1	
3	QPSK	8	7	19.28	19.12	19.48			
3	QPSK	15	0	19.28	19.19	19.47			
3	16QAM	1	0	19.33	19.22	19.54			
3	16QAM	1	8	19.29	19.22	19.49	21	1	
3	16QAM	1	14	19.30	19.33	19.65			
3	16QAM	8	0	18.33	18.31	18.47			
3	16QAM	8	4	18.43	18.38	18.42			
3	16QAM	8	7	18.33	18.20	18.42	20	2	
3	16QAM	15	0	18.28	18.17	18.40			
3	64QAM	1	0	18.18	18.50	18.22			
3	64QAM	1	8	18.46	18.32	18.42			
3	64QAM	1	14	18.35	18.48	18.44	20	2	
3	64QAM	8	0	17.21	17.15	17.48			
3	64QAM	8	4	17.26	17.31	17.46			
3	64QAM	8	7	17.18	17.39	17.33			
3	64QAM	15	0	17.11	17.23	17.47	Turn-up limit (dBm)	MPR (dB)	
Channel				18607	18800	19193			
Frequency (MHz)				1860.7	18800	1909.3			
1.4	QPSK	1	0	20.26	20.08	20.16	22	0	
1.4	QPSK	1	3	20.35	20.21	20.35			
1.4	QPSK	1	5	20.22	20.17	20.38			
1.4	QPSK	3	0	20.33	20.27	20.46			
1.4	QPSK	3	1	20.29	20.18	20.46	21	1	
1.4	QPSK	3	3	20.29	20.13	20.46			
1.4	QPSK	6	0	19.25	19.25	19.43			
1.4	16QAM	1	0	19.30	19.47	19.46			
1.4	16QAM	1	3	19.24	19.62	19.52	21	1	
1.4	16QAM	1	5	19.35	19.37	19.70			
1.4	16QAM	3	0	19.28	19.20	19.23			
1.4	16QAM	3	1	19.21	19.21	19.48			
1.4	16QAM	3	3	19.25	19.15	19.24	20	2	
1.4	16QAM	6	0	18.42	18.31	18.42			
1.4	64QAM	1	0	18.58	18.49	18.50			
1.4	64QAM	1	3	18.55	18.31	18.46			
1.4	64QAM	1	5	18.21	18.29	18.63	20	2	
1.4	64QAM	3	0	18.34	18.11	18.35			
1.4	64QAM	3	1	18.31	18.35	18.55			
1.4	64QAM	3	3	18.50	18.38	18.59			
1.4	64QAM	6	0	17.29	17.12	17.42	19	3	