FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2097-12
FCC ID	:	IHDT56ZJ2
STANDARD	:	47 CFR Part 2, 22(H), 24(E), 27(L)
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Dec. 07, 2020 and completely tested on Dec. 23, 2020. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

James Huang

Approved by: James Huang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.

No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 6
1.5 Specification of Accessory 7
1.6 Modification of EUT 7
1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator 8
1.8 Testing Location 8
1.9 Test Software 8
1.10 Applicable Standards 9
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **10**
2.1 Test Mode 10
2.2 Connection Diagram of Test System 11
2.3 Support Unit used in test configuration 11
2.4 Measurement Results Explanation Example 11
2.5 Frequency List of Low/Middle/High Channels 12
3 CONDUCTED TEST RESULT **13**
3.1 Measuring Instruments 13
3.2 Test Setup 13
3.3 Test Result of Conducted Test 13
3.4 Conducted Output Power and ERP/EIRP 14
3.5 Peak-to-Average Ratio 15
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement 16
3.7 Conducted Band Edge 17
3.8 Conducted Spurious Emission 18
3.9 Frequency Stability 19
4 RADIATED TEST ITEMS **20**
4.1 Measuring Instruments 20
4.2 Test Setup 20
4.3 Test Result of Radiated Test 20
4.4 Field Strength of Spurious Radiation Measurement 21
5 LIST OF MEASURING EQUIPMENT **22**
6 UNCERTAINTY OF EVALUATION **23**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG0D0715A	Rev. 01	Initial issue of report	Jan. 14, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
	§22.913(a)(5)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
	§27.50(d)(4)	Equivalent Isotropic Radiated Power	< 1 Watts	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a) §27.53(h)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235 §27.54		Within Authorized Band		
4.4	§2.1053; §22.917(a); §24.238(a); §27.53(h)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 21.37 dB at 2510.00 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza,Chicago,IL60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza,Chicago,IL60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Phone
Brand Name	Motorola
Model Name	XT2097-12
FCC ID	IHDT56ZJ2
EUT supports Radios application	GSM/WCDMA/LTE WLAN 2.4GHz 802.11b/g/n HT20 Bluetooth BR/EDR/LE GNSS and FM Receiver
IMEI Code	Conducted: 354249350009283 Radiation: 356615380007281/356615380032289
HW Version	DVT2
SW Version	QOJ30.26
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	**GSM/GPRS/EDGE:** 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz **WCDMA:** Band V: 826.4 MHz ~ 846.6 MHz Band II: 1852.4 MHz ~ 1907.6 MHz Band IV: 1712.4 MHz ~ 1752.6 MHz
Rx Frequency	**GSM/GPRS/EDGE:** 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz **WCDMA:** Band V: 871.4 MHz ~ 891.6 MHz Band II: 1932.4 MHz ~ 1987.6 MHz Band IV: 2112.4 MHz ~ 2152.6 MHz
Maximum Output Power to Antenna	**GSM/GPRS/EDGE:** 850: 33.21 dBm 1900: 30.25 dBm **WCDMA:** Band V: 23.58 dBm Band II: 23.73 dBm Band IV: 23.69 dBm
Antenna Type	Fixed Internal Antenna
Antenna Gain	Cellular Band: -4.6 dBi PCS Band: -2.7 dBi AWS Band: -2.1 dBi
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA : BPSK HSDPA/DC-HSDPA : QPSK HSUPA : QPSK HSPA+ : 16QAM DC-HSDPA : 64QAM

1.5 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-101
AC Adapter 1(EU)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-102
AC Adapter 1(UK)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-103
AC Adapter 1(AU)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-105
AC Adapter 1(AR)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-106
AC Adapter 1(BR)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-107
AC Adapter 2(IN)	**Brand Name**	Motorola (Chenyang)	**Model Name**	MC-104
AC Adapter 3(US)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-101
AC Adapter 3(EU)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-102
AC Adapter 3(UK)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-103
AC Adapter 3(AU)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-105
AC Adapter 3(AR)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-106
AC Adapter 3(Chile)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-109
AC Adapter 4(US)	**Brand Name**	Motorola (Aohai)	**Model Name**	MC-101
AC Adapter 4(EU)	**Brand Name**	Motorola (Aohai)	**Model Name**	MC-102
AC Adapter 4(UK)	**Brand Name**	Motorola (Aohai)	**Model Name**	MC-103
AC Adapter 4(AU)	**Brand Name**	Motorola (Aohai)	**Model Name**	MC-105
AC Adapter 4(AR)	**Brand Name**	Motorola (Aohai)	**Model Name**	MC-106
AC Adapter 5(BR)	**Brand Name**	Motorola (Flex)	**Model Name**	MC-107
AC Adapter 6(BR)	**Brand Name**	Motorola (Salcomp)	**Model Name**	MC-107
AC Adapter 7(UK)	**Brand Name**	Lenovo (Chenyang)	**Model Name**	SC-43
AC Adapter 8(EU)	**Brand Name**	Lenovo(Salom)	**Model Name**	SC-42
AC Adapter 8(US)	**Brand Name**	Lenovo(Salom)	**Model Name**	SC-41
Battery 1	**Brand Name**	Motorola (Sunwoda)	**Model Name**	JK50
Battery 2	**Brand Name**	Motorola (ATL)	**Model Name**	JK50
Battery 3	**Brand Name**	Motorola (SCUD)	**Model Name**	JK50
Earphone 1	**Brand Name**	Motorola (NEW LEADER)	**Model Name**	NLD-EM313A-23SF
Earphone 2	**Brand Name**	Motorola (Ju wei)	**Model Name**	JWPE1185-ZN01H
USB Cable 1	**Brand Name**	Motorola (Washin)	**Model Name**	HX-ZN-04
USB Cable 2	**Brand Name**	Motorola (Ju wei)	**Model Name**	JWUB1472-ZN01H
USB Cable 3	**Brand Name**	Motorola (I SHENG)	**Model Name**	SC18C28955

1.6 Modification of EUT

No modifications are made to the EUT during all test items.

1.7 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GSM	GMSK	0.4426	0.0320 ppm	244KGXW
Part 22	GSM850 EDGE 1 Tx slots	8PSK	0.0776	0.0236 ppm	240KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	BPSK	0.0482	0.0278 ppm	4M15F9W
Part 24	GSM1900 GPRS 1 Tx slots	GMSK	0.5689	0.0145 ppm	243KGXW
Part 24	GSM1900 EDGE 1 Tx slots	8PSK	0.4083	0.0181 ppm	254KG7W
Part 24	WCDMA Band II RMC 12.2Kbps	BPSK	0.1268	0.0174 ppm	4M15F9W
Part 27	WCDMA Band IV RMC 12.2Kbps	BPSK	0.1442	0.0150 ppm	4M15F9W

1.8 Testing Location

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.9 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.10 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, 22(H), 24(E), 27(L)
- ANSI C63.26-2015
- FCC KDB 971168 D01 Power Meas. License Digital Systems v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements were performed with rotating EUT in different three orthogonal test planes to find the maximum emission.

Radiated emissions were investigated as following frequency range:

1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 18000 MHz for WCDMA Band IV.
3. 30 MHz to 19100 MHz for GSM1900 and WCDMA Band II.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	**Radiated TCs**	**Conducted TCs**
GSM 850	■ GSM Link ■ EDGE 1 Tx slots Link	■ GSM Link ■ EDGE 1 Tx slots Link
GSM 1900	■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link	■ GPRS 1 Tx slots Link ■ EDGE 1 Tx slots Link
WCDMA Band V	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band II	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link
WCDMA Band IV	■ RMC 12.2Kbps Link	■ RMC 12.2Kbps Link

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

The following shows an offset computation example with RF cable loss 4.8 dB and a 10dB attenuator.

Example :

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.8 + 10 = 14.8 (dB)

2.5 Frequency List of Low/Middle/High Channels

Frequency List				
Band	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
GSM850	Channel	128	189	251
	Frequency	824.2	836.4	848.8
WCDMA Band V	Channel	4132	4182	4233
	Frequency	826.4	836.4	846.6
GSM1900	Channel	512	661	810
	Frequency	1850.2	1880.0	1909.8
WCDMA Band II	Channel	9262	9400	9538
	Frequency	1852.4	1880.0	1907.6
WCDMA Band IV	Channel	1312	1413	1513
	Frequency	1712.4	1732.6	1752.6

3 Conducted Test Result

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power and ERP/EIRP

3.4.1 Description of the Conducted Output Power and ERP/EIRP

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 7 Watts for GSM850 and WCDMA Band V.

The EIRP of mobile transmitters must not exceed 2 Watts for GSM1900 and WCDMA Band II.

The EIRP of mobile transmitters must not exceed 1 Watts for WCDMA Band IV.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5ppm) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

4.4 Field Strength of Spurious Radiation Measurement

4.4.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a rotatable wooden table 0.8 meters for frequency below 1GHz and 1.5 meter for frequency above 1GHz above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
12. ERP (dBm) = EIRP - 2.15
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from 43 + 10log(P) dB below the transmitter power P(Watts)

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 02, 2020	Dec. 17, 2020	Nov. 01, 2021	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 27, 2020	Dec. 17, 2020	Oct. 26, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 15, 2020	Dec. 23, 2020	Apr. 14, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jan. 03, 2020	Dec. 23, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 20, 2020	Dec. 23, 2020	Apr. 19, 2021	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Nov. 09, 2020	Dec. 23, 2020	Nov. 08, 2021	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 03, 2020	Dec. 23, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 08, 2020	Dec. 23, 2020	Jan. 07, 2021	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 03, 2020	Dec. 23, 2020	Jan. 02, 2021	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Dec. 23, 2020	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Dec. 23, 2020	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Dec. 23, 2020	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Dec. 23, 2020	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GSM	33.21	33.14	33.17	30.05	30.08	30.05
GPRS 1 Tx slots	33.19	33.13	33.16	30.04	30.25	30.21
GPRS 2 Tx slots	31.04	31.06	30.96	28.11	28.24	28.23
GPRS 3 Tx slots	29.19	29.22	29.21	26.58	26.61	26.67
GPRS 4 Tx slots	27.20	27.14	27.20	24.61	24.52	24.65
EGPRS 1 Tx slots	25.65	25.60	25.50	28.81	28.46	28.35
EGPRS 2 Tx slots	24.24	24.30	24.30	27.41	27.42	27.40
EGPRS 3 Tx slots	21.60	21.72	21.64	25.25	25.17	25.18
EGPRS 4 Tx slots	18.80	19.00	18.84	23.20	23.06	22.85

Conducted Power (*Unit: dBm)									
Band	WCDMA Band V			WCDMA Band II			WCDMA Band IV		
Channel	4132	4182	4233	9262	9400	9538	1312	1413	1513
Frequency	826.4	836.4	846.6	1852.4	1880	1907.6	1712.4	1732.6	1752.6
AMR 12.2K	23.52	23.55	23.43	23.71	23.56	23.24	23.57	23.62	23.67
RMC 12.2K	23.53	23.58	23.44	23.73	23.58	23.23	23.59	23.69	23.68
HSDPA Subtest-1	22.67	22.65	22.66	22.61	22.65	22.65	22.54	22.31	22.50
HSDPA Subtest-2	22.76	22.56	22.86	22.56	22.83	22.75	22.94	22.75	22.89
HSDPA Subtest-3	22.23	22.23	22.32	22.12	22.05	21.98	22.10	22.12	22.21
HSDPA Subtest-4	22.32	22.12	22.21	22.09	22.03	22.04	22.24	22.21	22.12
DC-HSDPA Subtest-1	22.63	22.62	22.64	22.58	22.63	22.61	22.52	22.27	22.47
DC-HSDPA Subtest-2	22.72	22.53	22.84	22.53	22.81	22.71	22.92	22.71	22.86
DC-HSDPA Subtest-3	22.19	22.20	22.30	22.09	22.03	21.94	22.08	22.08	22.18
DC-HSDPA Subtest-4	22.28	22.09	22.19	22.06	22.01	22.00	22.22	22.17	22.09
HSUPA Subtest-1	22.65	22.56	22.74	22.23	22.25	22.54	22.44	22.54	22.43
HSUPA Subtest-2	20.56	20.54	20.67	20.36	20.21	20.30	20.84	20.86	20.93
HSUPA Subtest-3	21.38	20.99	21.24	21.49	21.52	21.54	21.31	21.29	21.39
HSUPA Subtest-4	20.34	20.76	20.81	20.25	20.32	20.43	20.86	20.87	20.56
HSUPA Subtest-5	22.65	22.56	22.67	22.65	22.54	22.45	22.50	22.65	22.56

ERP/EIRP

GSM850 (G_T - L_C= -4.6 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	33.21	33.14	33.17
Conducted Power (Watts)	2.0941	2.0606	2.0749
ERP(dBm)	26.46	26.39	26.42
ERP(Watts)	0.4426	0.4355	0.4385

EDGE850 (G_T - L_C= -4.6 dB)			
Channel	128	189	251
	(Low)	(Mid)	(High)
Frequency (MHz)	824.2	836.4	848.8
Conducted Power (dBm)	25.65	25.60	25.50
Conducted Power (Watts)	0.3673	0.3631	0.3548
ERP(dBm)	18.90	18.85	18.75
ERP(Watts)	0.0776	0.0767	0.0750

GSM1900 (G_T - L_C= -2.7 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	30.04	30.25	30.21
Conducted Power (Watts)	1.0093	1.0593	1.0495
EIRP(dBm)	27.34	27.55	27.51
EIRP(Watts)	0.5420	0.5689	0.5636

EDGE1900 (G_T - L_C= -2.7 dB)			
Channel	512	661	810
	(Low)	(Mid)	(High)
Frequency (MHz)	1850.2	1880	1909.8
Conducted Power (dBm)	28.81	28.46	28.35
Conducted Power (Watts)	0.7603	0.7015	0.6839
EIRP(dBm)	26.11	25.76	25.65
EIRP(Watts)	0.4083	0.3767	0.3673

WCDMA Band V (G_T - L_C = -4.6 dB)			
Channel	4132	4182	4233
	(Low)	(Mid)	(High)
Frequency (MHz)	826.4	836.4	846.6
Conducted Power (dBm)	23.53	23.58	23.44
Conducted Power (Watts)	0.2254	0.2280	0.2208
ERP(dBm)	16.78	16.83	16.69
ERP(Watts)	0.0476	0.0482	0.0467

WCDMA Band II (G_T - L_C = -2.7 dB)			
Channel	9262	9400	9538
	(Low)	(Mid)	(High)
Frequency (MHz)	1852.4	1880	1907.6
Conducted Power (dBm)	23.73	23.58	23.23
Conducted Power (Watts)	0.2360	0.2280	0.2104
EIRP(dBm)	21.03	20.88	20.53
EIRP(Watts)	0.1268	0.1225	0.1130

WCDMA Band IV (G_T - L_C = -2.1 dB)			
Channel	1312	1413	1513
	(Low)	(Mid)	(High)
Frequency (MHz)	1712.4	1732.6	1752.6
Conducted Power (dBm)	23.59	23.69	23.68
Conducted Power (Watts)	0.2286	0.2339	0.2333
EIRP(dBm)	21.49	21.59	21.58
EIRP(Watts)	0.1409	0.1442	0.1439

A1. GSM

Peak-to-Average Ratio

Mode	GSM850		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	3.13	PASS
Middle CH	0.12	3.13	
Highest CH	0.20	3.13	

Mode	GSM1900		Limit: 13dB
Mod.	GSM	EDGE class 8	Result
Lowest CH	0.12	2.96	PASS
Middle CH	0.12	2.87	
Highest CH	0.12	2.49	

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

26dB Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.3127	0.3137
Middle CH	0.3127	0.3137
Highest CH	0.3117	0.3007

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.3087	0.3197
Middle CH	0.3117	0.3187
Highest CH	0.3107	0.3257

GSM850 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM850 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (GSM)

Lowest Channel



Middle Channel



Highest Channel



GSM1900 (EDGE class 8)

Lowest Channel



Middle Channel



Highest Channel



Occupied Bandwidth

Mode	GSM850	
Mod.	GSM	EDGE class 8
Lowest CH	0.241	0.240
Middle CH	0.243	0.237
Highest CH	0.244	0.235

Mode	GSM1900	
Mod.	GSM	EDGE class 8
Lowest CH	0.243	0.249
Middle CH	0.242	0.251
Highest CH	0.238	0.254

GSM850 (GSM)	GSM850 (EDGE class 8)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

GSM1900 (GSM)	GSM1900 (EDGE class 8)
Lowest Channel	**Lowest Channel**





Middle Channel	Middle Channel





Highest Channel	Highest Channel





Conducted Band Edge

GSM850 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.80969 MHz	-49.52 dBm	-36.52 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99701 MHz	-16.58 dBm	-3.58 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.26796 MHz	22.81 dBm	-12.19 dB

Date: 17.DEC.2020 20:51:18

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.86976 MHz	22.27 dBm	-12.73 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.01697 MHz	-19.11 dBm	-6.11 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.09241 MHz	-49.58 dBm	-36.58 dB

Date: 17.DEC.2020 20:52:57

GSM850 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
820.000 MHz	823.000 MHz	100.000 kHz	822.96254 MHz	-45.32 dBm	-32.32 dB
823.000 MHz	824.000 MHz	3.000 kHz	823.99501 MHz	-17.83 dBm	-4.83 dB
824.000 MHz	824.500 MHz	10.000 kHz	824.21307 MHz	18.79 dBm	-16.21 dB

Date: 17.DEC.2020 21:26:22

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
848.500 MHz	849.000 MHz	10.000 kHz	848.80090 MHz	19.36 dBm	-15.64 dB
849.000 MHz	850.000 MHz	3.000 kHz	849.00299 MHz	-21.15 dBm	-8.15 dB
850.000 MHz	855.000 MHz	100.000 kHz	850.01748 MHz	-45.98 dBm	-32.98 dB

Date: 17.DEC.2020 21:24:45

GSM1900 (GSM)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84898 GHz	-37.76 dBm	-24.76 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-17.62 dBm	-4.62 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85027 GHz	23.91 dBm	-11.09 dB

Date: 17.DEC.2020 21:39:39

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90987 GHz	24.10 dBm	-10.90 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91002 GHz	-20.12 dBm	-7.12 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-35.76 dBm	-22.76 dB

Date: 17.DEC.2020 21:41:20

GSM1900 (EDGE class 8)

Lowest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.845 GHz	1.849 GHz	1.000 MHz	1.84899 GHz	-35.60 dBm	-22.60 dB
1.849 GHz	1.850 GHz	3.000 kHz	1.85000 GHz	-21.87 dBm	-8.87 dB
1.850 GHz	1.851 GHz	10.000 kHz	1.85023 GHz	20.53 dBm	-14.47 dB

Date: 17.DEC.2020 21:52:23

Highest Band Edge



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
1.909 GHz	1.910 GHz	10.000 kHz	1.90983 GHz	21.31 dBm	-13.69 dB
1.910 GHz	1.911 GHz	3.000 kHz	1.91000 GHz	-19.80 dBm	-6.80 dB
1.911 GHz	1.915 GHz	1.000 MHz	1.91101 GHz	-34.98 dBm	-21.98 dB

Date: 17.DEC.2020 21:54:02

Conducted Spurious Emission

GSM850 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	609.76762 MHz	-46.09 dBm	-33.09 dB
855.000 MHz	1.000 GHz	1.000 MHz	953.94928 MHz	-46.71 dBm	-33.71 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.75278 GHz	-41.40 dBm	-28.40 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.95926 GHz	-40.44 dBm	-27.44 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.21560 GHz	-44.67 dBm	-31.67 dB

Date: 17.DEC.2020 20:53:37

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	663.06597 MHz	-46.68 dBm	-33.68 dB
855.000 MHz	1.000 GHz	1.000 MHz	861.41304 MHz	-45.24 dBm	-32.24 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.50919 GHz	-35.70 dBm	-22.70 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.87989 GHz	-41.57 dBm	-28.57 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.31621 GHz	-44.84 dBm	-31.84 dB

Date: 17.DEC.2020 20:53:58

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	708.46827 MHz	-47.01 dBm	-34.01 dB
855.000 MHz	1.000 GHz	1.000 MHz	983.44203 MHz	-45.97 dBm	-32.97 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.07474 GHz	-46.86 dBm	-33.86 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.78640 GHz	-41.25 dBm	-28.25 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.69354 GHz	-44.57 dBm	-31.57 dB

Date: 17.DEC.2020 20:54:21

GSM850 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	273.79060 MHz	-45.49 dBm	-32.49 dB
855.000 MHz	1.000 GHz	1.000 MHz	955.47101 MHz	-45.93 dBm	-32.93 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.47294 GHz	-38.84 dBm	-25.84 dB
3.000 GHz	7.000 GHz	1.000 MHz	5.86689 GHz	-41.99 dBm	-28.99 dB
7.000 GHz	9.000 GHz	1.000 MHz	8.56618 GHz	-44.42 dBm	-31.42 dB

Date: 17.DEC.2020 21:26:48

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	361.04198 MHz	-47.02 dBm	-34.02 dB
855.000 MHz	1.000 GHz	1.000 MHz	907.13768 MHz	-45.58 dBm	-32.58 dB
1.000 GHz	3.000 GHz	1.000 MHz	1.82752 GHz	-46.28 dBm	-33.28 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.35083 GHz	-41.79 dBm	-28.79 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.07762 GHz	-44.87 dBm	-31.87 dB

Date: 17.DEC.2020 21:27:02

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	820.000 MHz	1.000 MHz	182.19640 MHz	-45.06 dBm	-32.06 dB
855.000 MHz	1.000 GHz	1.000 MHz	856.19565 MHz	-46.39 dBm	-33.39 dB
1.000 GHz	3.000 GHz	1.000 MHz	2.54593 GHz	-43.01 dBm	-30.01 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.53231 GHz	-41.42 dBm	-28.42 dB
7.000 GHz	9.000 GHz	1.000 MHz	7.48631 GHz	-43.88 dBm	-30.88 dB

Date: 17.DEC.2020 21:27:19

GSM1900 (GSM)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	976.48926 MHz	-45.15 dBm	-32.15 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.58635 GHz	-46.71 dBm	-33.71 dB
1.915 GHz	3.000 GHz	1.000 MHz	1.91507 GHz	-44.45 dBm	-31.45 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.82015 GHz	-34.11 dBm	-21.11 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.81112 GHz	-43.52 dBm	-30.52 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.75972 GHz	-41.17 dBm	-28.17 dB

Date: 17.DEC.2020 21:41:39

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	861.11694 MHz	-45.44 dBm	-32.44 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.71008 GHz	-46.84 dBm	-33.84 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.53900 GHz	-44.90 dBm	-31.90 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.82727 GHz	-41.07 dBm	-28.07 dB
7.000 GHz	13.600 GHz	1.000 MHz	13.53471 GHz	-42.82 dBm	-29.82 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.43839 GHz	-41.72 dBm	-28.72 dB

Date: 17.DEC.2020 21:41:55

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	621.16192 MHz	-46.06 dBm	-33.06 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.81481 GHz	-46.57 dBm	-33.57 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.03033 GHz	-45.31 dBm	-32.31 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.79028 GHz	-39.77 dBm	-26.77 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.46795 GHz	-43.41 dBm	-30.41 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.34214 GHz	-41.25 dBm	-28.25 dB

Date: 17.DEC.2020 21:42:06

GSM1900 (EDGE class 8)

Lowest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	267.28886 MHz	-45.52 dBm	-32.52 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.49429 GHz	-43.35 dBm	-30.35 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.16052 GHz	-45.34 dBm	-32.34 dB
3.000 GHz	7.000 GHz	1.000 MHz	3.81965 GHz	-38.14 dBm	-25.14 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.88560 GHz	-43.07 dBm	-30.07 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.44506 GHz	-40.68 dBm	-27.68 dB

Date: 17.DEC.2020 21:54:23

Middle Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	942.07146 MHz	-45.85 dBm	-32.85 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.49344 GHz	-42.02 dBm	-29.02 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.99736 GHz	-45.46 dBm	-32.46 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.40982 GHz	-40.96 dBm	-27.96 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.84600 GHz	-43.65 dBm	-30.65 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.37003 GHz	-40.93 dBm	-27.93 dB

Date: 17.DEC.2020 21:54:40

Highest Channel



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	925.58971 MHz	-46.09 dBm	-33.09 dB
1.000 GHz	1.845 GHz	1.000 MHz	1.49429 GHz	-45.46 dBm	-32.46 dB
1.915 GHz	3.000 GHz	1.000 MHz	2.74458 GHz	-46.29 dBm	-33.29 dB
3.000 GHz	7.000 GHz	1.000 MHz	6.74328 GHz	-41.56 dBm	-28.56 dB
7.000 GHz	13.600 GHz	1.000 MHz	12.44626 GHz	-43.57 dBm	-30.57 dB
13.600 GHz	19.100 GHz	1.000 MHz	16.54013 GHz	-41.17 dBm	-28.17 dB

Date: 17.DEC.2020 21:54:56

Frequency Stability

Test Conditions	Middle Channel	GSM850 (GSM)	GSM850 (EDGE class 8)	Limit 2.5ppm
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0191	0.0236	PASS
40	Normal Voltage	0.0120	0.0178	
30	Normal Voltage	0.0130	0.0032	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0145	0.0155	
0	Normal Voltage	0.0078	0.0169	
-10	Normal Voltage	0.0175	0.0234	
-20	Normal Voltage	0.0159	0.0065	
-30	Normal Voltage	0.0143	0.0109	
20	Maximum Voltage	0.0096	0.0187	
20	Normal Voltage	0.032	0.0203	
20	Battery End Point	0.0108	0.0024	

Test Conditions	Middle Channel	GSM1900 (GPRS class 8)	GSM1900 (EDGE class 8)	Limit Note 2.
Temperature (°C)	Voltage (Volt)	Deviation (ppm)		Result
50	Normal Voltage	0.0124	0.0027	PASS
40	Normal Voltage	0.0011	0.0134	
30	Normal Voltage	0.0119	0.0023	
20(Ref.)	Normal Voltage	0.0000	0.0000	
10	Normal Voltage	0.0145	0.0112	
0	Normal Voltage	0.0136	0.0135	
-10	Normal Voltage	0.0089	0.0174	
-20	Normal Voltage	0.0021	0.0127	
-30	Normal Voltage	0.0118	0.0119	
20	Maximum Voltage	0.0052	0.0018	
20	Normal Voltage	0.0015	0.0131	
20	Battery End Point	0.0058	0.0181	

Note:

1. Normal Voltage = 3.8V. ; Battery End Point (BEP) =3.5V. ; Maximum Voltage =4.4 V
2. The frequency fundamental emissions stay within the authorized frequency block based on the frequency deviation measured is small.

A2. WCDMA

Peak-to-Average Ratio

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV	Limit: 13dB
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps	Result
Lowest CH	2.84	2.87	2.67	PASS
Middle CH	2.99	2.84	2.78	
Highest CH	2.87	2.90	2.75	

WCDMA Band V (RMC 12.2Kbps)	WCDMA Band II (RMC 12.2Kbps)
Lowest Channel	**Lowest Channel**
	
Middle Channel	**Middle Channel**
	
Highest Channel	**Highest Channel**
	

WCDMA Band IV (RMC 12.2Kbps)

Lowest Channel



Middle Channel



Highest Channel



26dB Bandwidth

Mode	WCDMA Band V	WCDMA Band II	WCDMA Band IV
Mod.	RMC 12.2Kbps	RMC 12.2Kbps	RMC 12.2Kbps
Lowest CH	4.675	4.665	4.685
Middle CH	4.675	4.665	4.675
Highest CH	4.675	4.675	4.675