FCC RF Test Report

APPLICANT	:	Motorola Mobility LLC
EQUIPMENT	:	Mobile Cellular Phone
BRAND NAME	:	Motorola
MODEL NAME	:	XT2139-1, XT2139-2
FCC ID	:	IHDT56ZU1
STANDARD	:	47 CFR Part 2, Part 27 Subpart Q
CLASSIFICATION	:	PCS Licensed Transmitter Held to Ear (PCE)
TEST DATE(S)	:	Jun. 11, 2021 ~ Jun. 21, 2021

We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26-2015 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Jason Jia

Reviewed by: Jason Jia / Supervisor

Alex Wang

Approved by: Alex Wang / Manager

ACCREDITED
Cert #5145.02

Sporton International (Kunshan) Inc.
No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China

TABLE OF CONTENTS

REVISION HISTORY **3**
SUMMARY OF TEST RESULT **4**
1 GENERAL DESCRIPTION **5**
1.1 Applicant 5
1.2 Manufacturer 5
1.3 Product Feature of Equipment Under Test 5
1.4 Product Specification of Equipment Under Test 5
1.5 Modification of EUT 6
1.6 Maximum EIRP Power and Emission Designator 6
1.7 Testing Site 6
1.8 Test Software 6
1.9 Applied Standards 7
1.10 Specification of Accessory 7
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST **8**
2.1 Test Mode 8
2.2 Connection Diagram of Test System 9
2.3 Support Unit used in test configuration and system 9
2.4 Measurement Results Explanation Example 9
2.5 Frequency List of Low/Middle/High Channels 10
3 CONDUCTED TEST ITEMS **11**
3.1 Measuring Instruments 11
3.2 Test Setup 11
3.3 Test Result of Conducted Test 11
3.4 Conducted Output Power Measurement 12
3.5 Peak-to-Average Ratio 13
3.6 EIRP 14
3.7 Occupied Bandwidth 15
3.8 Conducted Band Edge Measurement 16
3.9 Conducted Spurious Emission Measurement 17
3.10 Frequency Stability Measurement 18
4 RADIATED TEST ITEMS **19**
4.1 Measuring Instruments 19
4.2 Test Setup 19
4.3 Test Result of Radiated Test 20
4.4 Radiated Spurious Emission Measurement 21
5 LIST OF MEASURING EQUIPMENT **22**
6 UNCERTAINTY OF EVALUATION **23**
APPENDIX A. TEST RESULTS OF CONDUCTED TEST
APPENDIX B. TEST RESULTS OF RADIATED TEST
APPENDIX C. TEST SETUP PHOTOGRAPHS

REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG152401E	Rev. 01	Initial issue of report	Jul. 01, 2021

SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§27.50 (k)(4)	Peak-to-Average Ratio	<13dB	PASS	
3.6	§27.50 (k)(3)	EIRP	EIRP < 1W (30dBm)	PASS	-
3.7	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.8	§2.1051 §27.53 (n)(2)	Conducted Band Edge Measurement	-13dBm/MHz	PASS	-
3.9	§2.1051 §27.53 (n)(2)	Conducted Spurious Emission	-13dBm/MHz	PASS	-
3.10	§2.1055 §27.54	Frequency Stability Temperature & Voltage	Within the band	PASS	-
4.4	§2.1053 §27.53 (n)(2)	Radiated Spurious Emission	-13dBm/MHz	PASS	Under limit 42.95 dB at 6984.000 MHz

Declaration of Conformity:
The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.
Comments and Explanations:
The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Applicant

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2 Manufacturer

Motorola Mobility LLC
222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2139-1, XT2139-2
FCC ID	IHDT56ZU1
EUT supports Radios application	GSM/WCDMA/LTE/5G NR WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 WLAN 5GHz 802.11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE FM Receiver, NFC and GNSS
IMEI Code	Conducted: 351214780015915/351214780015901 Radiation: 868253050047485/868253050047493
HW Version	DVT2
SW Version	RRK31.Q3-3
EUT Stage	Identical Prototype

1.4 Product Specification of Equipment Under Test

Product Feature	
Tx/Rx Frequency	LTE Band 42: 3450 MHz ~ 3550 MHz
Bandwidth	5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 42 : 22.92 dBm
Antenna Gain	LTE Band 42 : -1.20 dBi
Type of Modulation	QPSK / 16QAM / 64QAM

1.5 Modification of EUT

No modifications are made to the EUT during all test items.

1.6 Maximum EIRP Power and Emission Designator

LTE Band 42		QPSK		16QAM/64QAM	
BW (MHz)	Frequency Range (MHz)	Maximum EIRP(W)	Emission Designator (99%OBW)	Maximum EIRP(W)	Emission Designator (99%OBW)
20	3460 ~ 3540	0.1486	17M9G7D	0.1178	17M9W7D

Note: Based on engineering evaluation, only the maximum bandwidth and the worst modulation test results are shown in the report.

1.7 Testing Site

Sporton International (Kunshan) Inc. is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

Test Firm	Sporton International (Kunshan) Inc.		
Test Site Location	No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China TEL : +86-512-57900158 FAX : +86-512-57900958		
Test Site No.	**Sporton Site No.**	**FCC Designation No.**	**FCC Test Firm Registration No.**
	03CH04-KS TH01-KS	CN1257	314309

1.8 Test Software

Item	Site	Manufacturer	Name	Version
1.	03CH04-KS	AUDIX	E3	6.2009-8-24a

1.9 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 27 Subpart Q
- ANSI C63.26-2015
- FCC KDB 971168 Power Meas License Digital Systems D01 v03r01
- FCC KDB 412172 D01 Determining ERP and EIRP v01r01

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

1.10 Specification of Accessory

Specification of Accessory				
AC Adapter 1(US)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-301
AC Adapter 1(EU)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-302
AC Adapter 1(UK)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-303
AC Adapter 1(AU)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-305
AC Adapter 1(AR)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-306
AC Adapter 1(BR)	**Brand Name**	Motorola(Salom)	**Model Name**	MC-307
AC Adapter 2(US)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-301
AC Adapter 2(EU)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-302
AC Adapter 2(UK)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-303
AC Adapter 2(IN)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-304
AC Adapter 2(AU)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-305
AC Adapter 2(AR)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-306
AC Adapter 2(CHILE)	**Brand Name**	Motorola(Acbel)	**Model Name**	MC-309
AC Adapter 3(BR)	**Brand Name**	Motorola(Flex)	**Model Name**	MC-307
Battery	**Brand Name**	Motorola(ATL)	**Model Name**	NT50
Earphone 1	**Brand Name**	Motorola(Lyand)	**Model Name**	MH191(SH38C81577)
Earphone 2	**Brand Name**	Motorola(LCHSE)	**Model Name**	MH191(SH38C81576)
Earphone 3	**Brand Name**	Motorola(NEW LEADER)	**Model Name**	MH202(S928D09678)
USB Cable 1	**Brand Name**	Motorola(Saibao)	**Model Name**	SC18D13215
USB Cable 2	**Brand Name**	Motorola(Cabletech)	**Model Name**	SC18D13216
USB Cable 3	**Brand Name**	Motorola(Luxshare)	**Model Name**	SC18D13217

2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.

Test Cases	Band	Bandwidth (MHz)	Modulation	RB #	Test Channel
		eg. 5M, 10M, 15M, 20M	eg. QPSK, 16QAM, 64QAM	1RB, Partial RB, Full RB	L/M/H
Max. Output Power	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB, Partial RB, Full RB	L, M, H
Peak-to-Average Ratio	LTE Band 42	20M	QPSK, 16QAM, 64QAM	Full RB	M
E.I.R.P	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB, Partial RB, Full RB	L, M, H
26dB and 99% Bandwidth	LTE Band 42	20M	QPSK, 16QAM	Full RB	M
Conducted Band Edge	LTE Band 42	5M, 10M, 15M, 20M	QPSK, 16QAM, 64QAM	1RB, Full RB	L, H
Conducted Spurious Emission	LTE Band 42	5M, 10M, 15M, 20M	QPSK	1RB	L, M, H
Frequency Stability	LTE Band 42	20M	QPSK	1RB	M
Radiated Spurious Emission	LTE Band 42	Worst case from maximum power			M

Note:

1. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.
2. All test items are based on engineering evaluation.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Power Supply	GWINSTEK	PSS-2002	N/A	N/A	Unshielded, 1.8 m
2.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.5 dB.

Example :

Offset(dB) = RF cable loss(dB).

= 5.5 (dB)

2.5 Frequency List of Low/Middle/High Channels

LTE Band 42 Channel and Frequency List				
BW [MHz]	**Channel/Frequency(MHz)**	**Lowest**	**Middle**	**Highest**
20	Channel	42190	42590	42990
	Frequency	3460	3500	3540
15	Channel	42165	42590	43015
	Frequency	3457.5	3500	3542.5
10	Channel	42140	42590	43040
	Frequency	3455	3500	3545
5	Channel	42115	42590	43065
	Frequency	3452.5	3500	3547.5

3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.2 Test Setup

3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied / 26dB Bandwidth, Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power Measurement

3.4.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2.3.4 (CCDF).
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 EIRP

3.6.1 Description of EIRP Limit

§ 27.50 (k)(3)

Mobile devices are limited to 1Watt (30 dBm) EIRP. Mobile devices operating in these bands must employ a means for limiting power to the minimum necessary for successful communications

3.6.2 Test Procedures

1. According to KDB 412172 D01 Power Approach,
2. EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

   P_T = transmitter output power in dBm

   G_T = gain of the transmitting antenna in dBi

   L_C = signal attenuation in the connecting cable between the transmitter and antenna in dB

3.7 Occupied Bandwidth

3.7.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.7.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.8 Conducted Band Edge Measurement

3.8.1 Description of Conducted Band Edge Measurement

§ 27.53 (n)(2)

For mobile operations in the 3450-3550 MHz band, the conducted power of any emission outside the licensee's authorized bandwidth shall not exceed −13 dBm/MHz.

Compliance with this paragraph is based on the use of measurement instrumentation employing a resolution bandwidth of 1 megahertz or greater. However, in the 1 megahertz bands immediately outside and adjacent to the licensee's frequency block, a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed, but limited to a maximum of 200 kHz. In the bands between 1 and 5 MHz removed from the licensee's frequency block, the minimum resolution bandwidth for the measurement shall be 500 kHz.

3.8.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW ≥ 1% EBW but limited to a maximum of 200 kHz in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz and 5 MHz removed from the band edge, set RBW ≥ 500KHz.
6. Beyond the 5 MHz removed from the band edge, set RBW = 1MHz.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. Checked that all the results comply with the emission limit line.

3.9 Conducted Spurious Emission Measurement

3.9.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges shall not exceed −13 dBm/MHz.

It is measured by means of a calibrated spectrum analyzer and scanned from 9 kHz up to a frequency including its 10th harmonic.

3.9.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
10. Checked that all the results comply with the emission limit line.

3.10 Frequency Stability Measurement

3.10.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block.

3.10.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.10.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

4 Radiated Test Items

4.1 Measuring Instruments

See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test below 30MHz



4.2.2 For radiated test from 30MHz to 1GHz



4.2.3 For radiated test above 1GHz



4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

4.4 Radiated Spurious Emission Measurement

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI/TIA-603-E. The power of any emission outside of the authorized operating frequency ranges shall not exceed −13 dBm/MHz.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
   EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
   ERP (dBm) = EIRP - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Nov. 01, 2020	Jun. 11, 2021	Oct. 31, 2021	Conducted (TH01-KS)
Power divider	STI	STI08-0055	-	0.5~40GHz	Aug. 27, 2020	Jun. 11, 2021	Aug. 26, 2021	Conducted (TH01-KS)
Temperature & humidity chamber	Hongzhan	LP-150U	H2014011440	-40~+150°C 20%~95%RH	Jul. 03, 2020	Jun. 11, 2021	Jul. 02, 2021	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150244	10Hz-44G,MAX 30dB	Apr. 13, 2021	Jun. 21, 2021	Apr. 12, 2022	Radiation (03CH04-KS)
Loop Antenna	R&S	HFH2-Z2	100321	9kHz~30MHz	Nov. 1, 2020	Jun. 21, 2021	Oct. 31, 2021	Radiation (03CH04-KS)
Bilog Antenna	TeseQ	CBL6111D	49922	30MHz-1GHz	Jun. 07, 2021	Jun. 21, 2021	Jun. 06, 2022	Radiation (03CH04-KS)
Horn Antenna	Schwarzbeck	BBHA9120D	1356	1GHz~18GHz	Apr. 18, 2021	Jun. 21, 2021	Apr. 17, 2022	Radiation (03CH04-KS)
SHF-EHF Horn	Com-power	AH-840	101115	18GHz~40GHz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	SONOMA	310N	187289	9KHz-1GHz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	MITEQ	EM18G40G GA	060728	18~40GHz	Jan. 07, 2021	Jun. 21, 2021	Jan. 06, 2022	Radiation (03CH04-KS)
high gain Amplifier	MITEQ	AMF-7D-00 101800-30-1 0P	2025788	1Ghz-18Ghz	Jan. 06, 2021	Jun. 21, 2021	Jan. 05, 2022	Radiation (03CH04-KS)
Amplifier	Keysight	83017A	MY57280106	500MHz~26.5GHz	Oct. 14, 2020	Jun. 21, 2021	Oct. 13, 2021	Radiation (03CH04-KS)
AC Power Source	Chroma	61601	F104090004	N/A	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)
Turn Table	ChamPro	EM 1000-T	060762-T	0~360 degree	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)
Antenna Mast	ChamPro	EM 1000-A	060762-A	1 m~4 m	NCR	Jun. 21, 2021	NCR	Radiation (03CH04-KS)

NCR: No Calibration Required.

6 Uncertainty of Evaluation

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**3.3dB**

Uncertainty of Radiated Emission Measurement (1 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	**2.8dB**

Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power) and EIRP

BW [MHz]	Modulation	RB Size	RB Offset	Power Low Ch. / Freq.	Power Middle Ch. / Freq.	Power High Ch. / Freq.	EIRP		
Channel				42190	42590	42990			
Frequency (MHz)				3460	3500	3540	L	M	H
20	QPSK	1	0	22.81	22.92	22.78	0.1449	0.1486	0.1439
20	QPSK	1	99	22.56	22.73	22.77	0.1368	0.1422	0.1435
20	QPSK	100	0	21.55	21.71	21.77	0.1084	0.1125	0.1140
20	16QAM	1	0	21.58	21.73	21.91	0.1091	0.1130	0.1178
20	64QAM	1	0	20.58	20.73	20.79	0.0867	0.0897	0.0910
Channel				42165	42590	43015	EIRP		
Frequency (MHz)				3457.5	3500	3542.5	L	M	H
15	QPSK	1	0	22.46	22.89	22.87	0.1337	0.1476	0.1469
15	16QAM	1	0	21.48	21.90	21.85	0.1067	0.1175	0.1161
Channel				42140	42590	43040	EIRP		
Frequency (MHz)				3455	3500	3545	L	M	H
10	QPSK	1	0	22.48	22.89	22.83	0.1343	0.1476	0.1455
10	16QAM	1	0	21.55	21.90	21.88	0.1084	0.1175	0.1169
Channel				42115	42590	43065	EIRP		
Frequency (MHz)				3452.5	3500	3547.5	L	M	H
5	QPSK	1	0	22.50	22.89	22.75	0.1348	0.1475	0.1428
5	16QAM	1	0	21.55	21.70	21.75	0.1083	0.1122	0.1134

Peak-to-Average Ratio

Mode	LTE Band 42 / 20MHz			
Mod.	QPSK	16QAM	64QAM	Limit: 13dB
RB Size	Full RB	Full RB	Full RB	Result
Middle CH	5.22	6.06	6.32	PASS

LTE Band 42/ 20MHz

Middle Channel / Full RB / QPSK



Middle Channel / Full RB / 16QAM



Middle Channel / Full RB / 64QAM



26dB Bandwidth

Mode	LTE Band 42 : 26dB BW(MHz)	
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	18.66	18.66

LTE Band 42	
Middle Channel / 20MHz / QPSK	Middle Channel / 20MHz / 16QAM
	

Occupied Bandwidth

Mode	LTE Band 42 : 99%OBW(MHz)	
BW	20MHz	
Mod.	QPSK	16QAM
Middle CH	17.86	17.94

LTE Band 42	
Middle Channel / 20MHz / QPSK	Middle Channel / 20MHz / 16QAM
	

Conducted Band Edge

LTE Band 42 / 5MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44465 GHz	-28.27 dBm	-15.27 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44893 GHz	-17.45 dBm	-4.45 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.45000 GHz	-16.14 dBm	-3.14 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45035 GHz	22.57 dBm	-7.43 dB

Date: 11.JUN.2021 18:34:56

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54964 GHz	22.49 dBm	-7.51 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55000 GHz	-15.59 dBm	-2.59 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55141 GHz	-19.52 dBm	-6.52 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55579 GHz	-35.98 dBm	-22.98 dB

Date: 11.JUN.2021 18:45:17

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44471 GHz	-33.12 dBm	-20.12 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44889 GHz	-25.59 dBm	-12.59 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.44999 GHz	-29.32 dBm	-16.32 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45375 GHz	8.38 dBm	-21.62 dB

Date: 11.JUN.2021 18:32:00

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54559 GHz	8.76 dBm	-21.24 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55001 GHz	-28.56 dBm	-15.56 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55105 GHz	-25.33 dBm	-12.33 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55514 GHz	-34.33 dBm	-21.33 dB

Date: 11.JUN.2021 18:42:28

LTE Band 42 / 5MHz / 16QAM

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44455 GHz	-28.88 dBm	-15.88 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44899 GHz	-17.32 dBm	-4.32 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.44999 GHz	-15.25 dBm	-2.25 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45036 GHz	21.49 dBm	-8.51 dB

Date: 11.JUN.2021 18:34:25

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54965 GHz	21.09 dBm	-8.91 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55002 GHz	-16.59 dBm	-3.59 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55108 GHz	-17.48 dBm	-4.48 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55503 GHz	-30.03 dBm	-17.03 dB

Date: 11.JUN.2021 18:44:50

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44472 GHz	-35.14 dBm	-22.14 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44900 GHz	-26.53 dBm	-13.53 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.44999 GHz	-29.49 dBm	-16.49 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45113 GHz	7.66 dBm	-22.34 dB

Date: 11.JUN.2021 18:32:49

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54595 GHz	7.53 dBm	-22.47 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55003 GHz	-29.10 dBm	-16.10 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55115 GHz	-28.82 dBm	-15.82 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55542 GHz	-38.87 dBm	-25.87 dB

Date: 11.JUN.2021 18:43:24

LTE Band 42 / 5MHz / 64QAM

Lowest Band Edge / 1RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44303 GHz	-35.00 dBm	-22.00 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44895 GHz	-28.64 dBm	-15.64 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.44998 GHz	-18.37 dBm	-5.37 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45034 GHz	20.24 dBm	-9.76 dB

Date: 11.JUN.2021 18:33:46

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54968 GHz	20.06 dBm	-9.94 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55000 GHz	-15.95 dBm	-2.95 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55110 GHz	-28.92 dBm	-15.92 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55510 GHz	-39.03 dBm	-26.03 dB

Date: 11.JUN.2021 18:44:19

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44109 GHz	-32.71 dBm	-19.71 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44788 GHz	-23.19 dBm	-10.19 dB
3.449 GHz	3.450 GHz	50.000 kHz	3.44998 GHz	-30.64 dBm	-17.64 dB
3.450 GHz	3.455 GHz	100.000 kHz	3.45100 GHz	6.53 dBm	-23.47 dB

Date: 11.JUN.2021 18:33:13

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.545 GHz	3.550 GHz	100.000 kHz	3.54636 GHz	6.38 dBm	-23.62 dB
3.550 GHz	3.551 GHz	50.000 kHz	3.55002 GHz	-31.00 dBm	-18.00 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55103 GHz	-29.19 dBm	-16.19 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55504 GHz	-39.40 dBm	-26.40 dB

Date: 11.JUN.2021 18:43:43

LTE Band 42 / 10MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44354 GHz	-25.63 dBm	-12.63 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44869 GHz	-22.53 dBm	-9.53 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.44999 GHz	-17.80 dBm	-4.80 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45061 GHz	21.78 dBm	-8.22 dB

Date: 11.JUN.2021 18:29:51

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54944 GHz	21.57 dBm	-8.43 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55001 GHz	-17.16 dBm	-4.16 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55108 GHz	-22.34 dBm	-9.34 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55516 GHz	-29.97 dBm	-16.97 dB

Date: 11.JUN.2021 18:50:07

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44401 GHz	-26.78 dBm	-13.78 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44752 GHz	-26.62 dBm	-13.62 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.44999 GHz	-33.26 dBm	-20.26 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45347 GHz	5.27 dBm	-24.73 dB

Date: 11.JUN.2021 18:27:12

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54697 GHz	5.50 dBm	-24.50 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55000 GHz	-28.48 dBm	-15.48 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55139 GHz	-26.01 dBm	-13.01 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55501 GHz	-30.24 dBm	-17.24 dB

Date: 11.JUN.2021 18:47:21

LTE Band 42 / 10MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44366 GHz	-30.49 dBm	-17.49 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44859 GHz	-21.22 dBm	-8.22 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.45000 GHz	-18.14 dBm	-5.14 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45055 GHz	20.91 dBm	-9.09 dB

Date: 11.JUN.2021 18:29:24

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54937 GHz	21.02 dBm	-8.98 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55000 GHz	-18.43 dBm	-5.43 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55133 GHz	-23.71 dBm	-10.71 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55553 GHz	-30.68 dBm	-17.68 dB

Date: 11.JUN.2021 18:49:45

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44265 GHz	-27.23 dBm	-14.23 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44777 GHz	-27.06 dBm	-14.06 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.44996 GHz	-31.91 dBm	-18.91 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45313 GHz	4.41 dBm	-25.59 dB

Date: 11.JUN.2021 18:28:08

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54462 GHz	4.32 dBm	-25.68 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55008 GHz	-29.21 dBm	-16.21 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55119 GHz	-24.95 dBm	-11.95 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55521 GHz	-30.04 dBm	-17.04 dB

Date: 11.JUN.2021 18:48:16

LTE Band 42 / 10MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.43832 GHz	-27.57 dBm	-14.57 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44764 GHz	-22.69 dBm	-9.69 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.44998 GHz	-18.47 dBm	-5.47 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45060 GHz	19.70 dBm	-10.30 dB

Date: 11.JUN.2021 18:28:54

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54941 GHz	19.58 dBm	-10.42 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55001 GHz	-18.87 dBm	-5.87 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55104 GHz	-20.81 dBm	-7.81 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55688 GHz	-31.27 dBm	-18.27 dB

Date: 11.JUN.2021 18:49:18

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44231 GHz	-28.97 dBm	-15.97 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44878 GHz	-23.31 dBm	-10.31 dB
3.449 GHz	3.450 GHz	100.000 kHz	3.44992 GHz	-28.96 dBm	-15.96 dB
3.450 GHz	3.460 GHz	100.000 kHz	3.45423 GHz	3.61 dBm	-26.39 dB

Date: 11.JUN.2021 18:28:28

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.540 GHz	3.550 GHz	100.000 kHz	3.54745 GHz	3.38 dBm	-26.62 dB
3.550 GHz	3.551 GHz	100.000 kHz	3.55006 GHz	-32.90 dBm	-19.90 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55101 GHz	-30.28 dBm	-17.28 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55508 GHz	-32.66 dBm	-19.66 dB

Date: 11.JUN.2021 18:48:43

LTE Band 42 / 15MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44418 GHz	-24.03 dBm	-11.03 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44711 GHz	-22.46 dBm	-9.46 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44998 GHz	-16.43 dBm	-3.43 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.45084 GHz	22.02 dBm	-7.98 dB

Date: 11.JUN.2021 18:22:08

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.54916 GHz	21.15 dBm	-8.85 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55003 GHz	-16.01 dBm	-3.01 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55102 GHz	-23.05 dBm	-10.05 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55503 GHz	-29.00 dBm	-16.00 dB

Date: 11.JUN.2021 18:54:00

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44493 GHz	-27.10 dBm	-14.10 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44754 GHz	-26.51 dBm	-13.51 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44999 GHz	-27.47 dBm	-14.47 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.46359 GHz	3.80 dBm	-26.20 dB

Date: 11.JUN.2021 18:18:43

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.53651 GHz	3.69 dBm	-26.31 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55004 GHz	-26.94 dBm	-13.94 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55117 GHz	-26.03 dBm	-13.03 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55509 GHz	-28.78 dBm	-15.78 dB

Date: 11.JUN.2021 18:51:45

LTE Band 42 / 15MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44393 GHz	-30.72 dBm	-17.72 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44895 GHz	-21.08 dBm	-8.08 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44997 GHz	-16.80 dBm	-3.80 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.45081 GHz	20.36 dBm	-9.64 dB

Date: 11.JUN.2021 18:21:33

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.54914 GHz	21.13 dBm	-8.87 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55002 GHz	-17.72 dBm	-4.72 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55109 GHz	-24.39 dBm	-11.39 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55633 GHz	-29.19 dBm	-16.19 dB

Date: 11.JUN.2021 18:53:38

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44192 GHz	-29.43 dBm	-16.43 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44805 GHz	-27.83 dBm	-14.83 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44915 GHz	-27.85 dBm	-14.85 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.45544 GHz	2.80 dBm	-27.20 dB

Date: 11.JUN.2021 18:19:56

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.53766 GHz	2.35 dBm	-27.65 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55010 GHz	-31.66 dBm	-18.66 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55114 GHz	-29.28 dBm	-16.28 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55511 GHz	-30.64 dBm	-17.64 dB

Date: 11.JUN.2021 18:52:27

LTE Band 42 / 15MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.43686 GHz	-26.84 dBm	-13.84 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44834 GHz	-23.70 dBm	-10.70 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44999 GHz	-18.98 dBm	-5.98 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.45084 GHz	21.48 dBm	-8.52 dB

Date: 11.JUN.2021 18:20:57

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.54914 GHz	19.64 dBm	-10.36 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55000 GHz	-18.17 dBm	-5.17 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55104 GHz	-24.02 dBm	-11.02 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55655 GHz	-28.62 dBm	-15.62 dB

Date: 11.JUN.2021 18:53:12

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44400 GHz	-30.65 dBm	-17.65 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44871 GHz	-28.04 dBm	-15.04 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44984 GHz	-30.72 dBm	-17.72 dB
3.450 GHz	3.465 GHz	100.000 kHz	3.45093 GHz	2.82 dBm	-27.18 dB

Date: 11.JUN.2021 18:20:19

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.535 GHz	3.550 GHz	100.000 kHz	3.53755 GHz	1.70 dBm	-28.30 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55003 GHz	-30.54 dBm	-17.54 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55136 GHz	-30.36 dBm	-17.36 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55561 GHz	-31.45 dBm	-18.45 dB

Date: 11.JUN.2021 18:52:47

LTE Band 42 / 20MHz / QPSK

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44333 GHz	-27.14 dBm	-14.14 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44869 GHz	-21.66 dBm	-8.66 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44999 GHz	-18.86 dBm	-5.86 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.45106 GHz	21.95 dBm	-8.05 dB

Date: 11.JUN.2021 18:25:23

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.54893 GHz	22.38 dBm	-7.62 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55005 GHz	-20.75 dBm	-7.75 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55105 GHz	-24.75 dBm	-11.75 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55813 GHz	-32.37 dBm	-19.37 dB

Date: 11.JUN.2021 18:58:00

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44463 GHz	-29.63 dBm	-16.63 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44875 GHz	-27.30 dBm	-14.30 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44995 GHz	-28.38 dBm	-15.38 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.45550 GHz	2.93 dBm	-27.07 dB

Date: 11.JUN.2021 18:23:29

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.53584 GHz	2.08 dBm	-27.92 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55019 GHz	-32.57 dBm	-19.57 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55108 GHz	-31.73 dBm	-18.73 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55565 GHz	-31.75 dBm	-18.75 dB

Date: 11.JUN.2021 18:55:28

LTE Band 42 / 20MHz / 16QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44457 GHz	-28.67 dBm	-15.67 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44897 GHz	-23.17 dBm	-10.17 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44997 GHz	-19.93 dBm	-6.93 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.45108 GHz	21.11 dBm	-8.89 dB

Date: 11.JUN.2021 18:25:07

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.54888 GHz	21.18 dBm	-8.82 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55003 GHz	-20.75 dBm	-7.75 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55138 GHz	-24.67 dBm	-11.67 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55522 GHz	-32.77 dBm	-19.77 dB

Date: 11.JUN.2021 18:57:38

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44300 GHz	-30.73 dBm	-17.73 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44662 GHz	-30.13 dBm	-17.13 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44963 GHz	-33.22 dBm	-20.22 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.46052 GHz	1.49 dBm	-28.51 dB

Date: 11.JUN.2021 18:23:50

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.53242 GHz	1.35 dBm	-28.65 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55005 GHz	-31.96 dBm	-18.96 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55155 GHz	-31.74 dBm	-18.74 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55504 GHz	-32.58 dBm	-19.58 dB

Date: 11.JUN.2021 18:56:11

LTE Band 42 / 20MHz / 64QAM

Lowest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44363 GHz	-26.23 dBm	-13.23 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44875 GHz	-21.48 dBm	-8.48 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44999 GHz	-16.86 dBm	-3.86 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.45108 GHz	19.73 dBm	-10.27 dB

Date: 11.JUN.2021 18:24:45

Highest Band Edge / 1 RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.54890 GHz	20.09 dBm	-9.91 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55005 GHz	-22.62 dBm	-9.62 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55102 GHz	-29.11 dBm	-16.11 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.56425 GHz	-38.31 dBm	-25.31 dB

Date: 11.JUN.2021 18:57:07

Lowest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.425 GHz	3.445 GHz	1.000 MHz	3.44317 GHz	-31.22 dBm	-18.22 dB
3.445 GHz	3.449 GHz	500.000 kHz	3.44883 GHz	-28.55 dBm	-15.55 dB
3.449 GHz	3.450 GHz	200.000 kHz	3.44966 GHz	-29.86 dBm	-16.86 dB
3.450 GHz	3.470 GHz	100.000 kHz	3.45936 GHz	0.74 dBm	-29.26 dB

Date: 11.JUN.2021 18:24:23

Highest Band Edge / Full RB



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
3.530 GHz	3.550 GHz	100.000 kHz	3.53359 GHz	0.38 dBm	-29.62 dB
3.550 GHz	3.551 GHz	200.000 kHz	3.55006 GHz	-37.36 dBm	-24.36 dB
3.551 GHz	3.555 GHz	500.000 kHz	3.55131 GHz	-35.05 dBm	-22.05 dB
3.555 GHz	3.575 GHz	1.000 MHz	3.55532 GHz	-34.39 dBm	-21.39 dB

Date: 11.JUN.2021 18:56:36

Conducted Spurious Emission

LTE Band 42 / 5MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	926.07446 MHz	-50.27 dBm	-37.27 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.37318 GHz	-47.47 dBm	-34.47 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.90158 GHz	-42.53 dBm	-29.53 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.98706 GHz	-45.65 dBm	-32.65 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99300 GHz	-44.05 dBm	-31.05 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.67229 GHz	-39.30 dBm	-26.30 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00056 GHz	-40.03 dBm	-27.03 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.89969 GHz	-35.36 dBm	-22.36 dB

Date: 11.JUN.2021 14:08:22

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	939.16292 MHz	-50.36 dBm	-37.36 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.36045 GHz	-47.71 dBm	-34.71 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.99572 GHz	-43.57 dBm	-30.57 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.98556 GHz	-45.62 dBm	-32.62 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.98634 GHz	-44.04 dBm	-31.04 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.67079 GHz	-39.36 dBm	-26.36 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00281 GHz	-39.91 dBm	-26.91 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.90229 GHz	-35.27 dBm	-22.27 dB

Date: 11.JUN.2021 14:10:35

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	893.59570 MHz	-50.07 dBm	-37.07 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.36651 GHz	-47.70 dBm	-34.70 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.94095 GHz	-44.97 dBm	-31.97 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.97094 GHz	-45.44 dBm	-32.44 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99967 GHz	-43.98 dBm	-30.98 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66579 GHz	-39.45 dBm	-26.45 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.01181 GHz	-39.93 dBm	-26.93 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.89232 GHz	-35.35 dBm	-22.35 dB

Date: 11.JUN.2021 14:12:00

LTE Band 42 / 10MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	972.12644 MHz	-49.99 dBm	-36.99 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.39015 GHz	-44.01 dBm	-31.01 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.90158 GHz	-42.76 dBm	-29.76 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.97994 GHz	-45.69 dBm	-32.69 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99767 GHz	-44.11 dBm	-31.11 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66279 GHz	-39.42 dBm	-26.42 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00056 GHz	-39.81 dBm	-26.81 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.91832 GHz	-35.26 dBm	-22.26 dB

Date: 11.JUN.2021 14:13:39

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	973.09595 MHz	-50.04 dBm	-37.04 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.37742 GHz	-46.88 dBm	-33.88 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.99230 GHz	-43.61 dBm	-30.61 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.97732 GHz	-45.62 dBm	-32.62 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99767 GHz	-43.76 dBm	-30.76 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66929 GHz	-39.29 dBm	-26.29 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00844 GHz	-39.90 dBm	-26.90 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.89622 GHz	-35.23 dBm	-22.23 dB

Date: 11.JUN.2021 14:15:23

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	941.10195 MHz	-50.26 dBm	-37.26 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.36469 GHz	-47.62 dBm	-34.62 dB
3.575 GHz	7.000 GHz	1.000 MHz	3.58099 GHz	-43.28 dBm	-30.28 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.97132 GHz	-45.60 dBm	-32.60 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.98100 GHz	-44.11 dBm	-31.11 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.67979 GHz	-39.47 dBm	-26.47 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00394 GHz	-40.09 dBm	-27.09 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.98982 GHz	-35.32 dBm	-22.32 dB

Date: 11.JUN.2021 14:17:14

LTE Band 42 / 15MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	954.67516 MHz	-50.18 dBm	-37.18 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.38651 GHz	-43.18 dBm	-30.18 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.90158 GHz	-43.56 dBm	-30.56 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.98181 GHz	-45.37 dBm	-32.37 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99833 GHz	-44.01 dBm	-31.01 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.65979 GHz	-39.32 dBm	-26.32 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00394 GHz	-39.89 dBm	-26.89 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.92352 GHz	-35.32 dBm	-22.32 dB

Date: 11.JUN.2021 14:18:53

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	999.27286 MHz	-50.29 dBm	-37.29 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.41318 GHz	-45.67 dBm	-32.67 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.98716 GHz	-43.19 dBm	-30.19 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.97019 GHz	-45.64 dBm	-32.64 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.99100 GHz	-44.11 dBm	-31.11 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.69829 GHz	-39.44 dBm	-26.44 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00619 GHz	-39.99 dBm	-26.99 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.88452 GHz	-35.38 dBm	-22.38 dB

Date: 11.JUN.2021 14:20:39

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	851.90655 MHz	-50.35 dBm	-37.35 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.39924 GHz	-45.88 dBm	-32.88 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.75951 GHz	-44.98 dBm	-31.98 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.99569 GHz	-45.63 dBm	-32.63 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.98300 GHz	-44.03 dBm	-31.03 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66729 GHz	-39.26 dBm	-26.26 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.00281 GHz	-40.02 dBm	-27.02 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.90012 GHz	-35.47 dBm	-22.47 dB

Date: 11.JUN.2021 13:57:33

LTE Band 42 / 20MHz

Lowest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	937.22389 MHz	-50.05 dBm	-37.05 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.35257 GHz	-45.97 dBm	-32.97 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.90329 GHz	-43.08 dBm	-30.08 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.96044 GHz	-45.68 dBm	-32.68 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.97500 GHz	-43.80 dBm	-30.80 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66779 GHz	-39.38 dBm	-26.38 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.01406 GHz	-39.98 dBm	-26.98 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.89319 GHz	-35.39 dBm	-22.39 dB

Date: 11.JUN.2021 13:59:41

Middle Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	942.07146 MHz	-50.17 dBm	-37.17 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.42227 GHz	-43.84 dBm	-30.84 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.98203 GHz	-44.19 dBm	-31.19 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.99269 GHz	-45.48 dBm	-32.48 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.97034 GHz	-44.00 dBm	-31.00 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.66579 GHz	-39.24 dBm	-26.24 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.01069 GHz	-39.80 dBm	-26.80 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.90359 GHz	-35.27 dBm	-22.27 dB

Date: 11.JUN.2021 14:01:32

Highest Channel / QPSK



Spurious Emissions

Range Low	Range Up	RBW	Frequency	Power Abs	ΔLimit
30.000 MHz	1.000 GHz	1.000 MHz	988.60820 MHz	-50.15 dBm	-37.15 dB
1.000 GHz	3.425 GHz	1.000 MHz	3.39682 GHz	-46.80 dBm	-33.80 dB
3.575 GHz	7.000 GHz	1.000 MHz	6.90329 GHz	-44.98 dBm	-31.98 dB
7.000 GHz	10.000 GHz	1.000 MHz	9.95294 GHz	-45.62 dBm	-32.62 dB
10.000 GHz	14.000 GHz	1.000 MHz	13.97234 GHz	-43.95 dBm	-30.95 dB
14.000 GHz	18.000 GHz	1.000 MHz	17.68129 GHz	-39.46 dBm	-26.46 dB
18.000 GHz	27.000 GHz	1.000 MHz	18.01069 GHz	-39.96 dBm	-26.96 dB
27.000 GHz	40.000 GHz	1.000 MHz	39.89622 GHz	-35.26 dBm	-22.26 dB

Date: 11.JUN.2021 14:02:59

Frequency Stability

Test Conditions		LTE Band 42 (QPSK) / Middle Channel	Limit
Temperature (°C)	Voltage (Volt)	BW 20MHz	Note 2.
		Deviation (ppm)	Result
50	Normal Voltage	0.0035	PASS
40	Normal Voltage	0.0004	
30	Normal Voltage	0.0011	
20(Ref.)	Normal Voltage	0.0000	
10	Normal Voltage	0.0015	
0	Normal Voltage	0.0020	
-10	Normal Voltage	0.0016	
-20	Normal Voltage	0.0002	
-30	Normal Voltage	0.0001	
20	Maximum Voltage	0.0016	
20	Normal Voltage	0.0008	
20	Battery End Point	0.0004	

Note:

1. Normal Voltage =3.87 V. ; Battery End Point (BEP) =3.6 V. ; Maximum Voltage =4.45 V.
2. Note: The frequency fundamental emissions stay within the authorized frequency block.

Appendix B. Test Results of Radiated Test

Radiated Spurious Emission

LTE Band 42 / 20MHz / QPSK								
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Middle	6984	-57.85	-13	-44.85	-64.82	1.58	10.70	H
	10476	-58.51	-13	-45.51	-66.76	2.10	12.50	H
	13962	-59.75	-13	-46.75	-68.64	2.86	13.90	H
	6984	-55.95	-13	-42.95	-62.92	1.58	10.70	V
	10476	-58.53	-13	-45.53	-66.78	2.10	12.50	V
	13962	-58.21	-13	-45.21	-67.10	2.86	13.90	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.