



**ADR TESTING SERVICES
EMC LABORATORY
EMC TEST REPORT**

Test Report Number – 26015-1 WLAN

The test results and statements contained herein relate only to the model(s) identified and tested. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical characteristics.

As the responsible EMC Engineer, I hereby declare that the equipment tested as specified in this report conforms to the requirements indicated.

Signature: 

Name: Thanigaiselvan Palaniswami

Title: EMC Engineer

Date: July 27, 2015

This report must not be reproduced, except in full, without written approval from this laboratory.



TESTING CERT# 3465.01

Table of Contents

Test Report Details	3
Applicable Standards	3
Summary of Testing.....	4
General and Special Conditions.....	4
Equipment and Cable Configurations	4
Measuring Equipment and Calibration Information	5
Description of WLAN Transmitter	5
Measurement Procedures and Data.....	6
Measurement Procedure.....	6
Measurement Results	6
Peak Output Power	13
Measurement Procedure.....	13
Measurement Results	13
Peak Power Spectral Density	16
Measurement Procedure.....	16
Measurement Results	16
Spurious RF Conducted Emissions.....	18
Measurement Procedure.....	18
Measurement Results	18
Conducted Spurious Emissions at the Band Edge	37
Measurement Procedure.....	37
Measurement Results	37
Radiated Spurious Emissions – Restricted Band	41
Measurement Procedure.....	41
Measurement Results	41
AC Line Conducted Emissions	46
Measurement Procedure.....	46
Measurement Results	46

Test Report Details

Tests Performed By: ADR Testing Services
Motorola Mobility LLC
Product Safety and Compliance Group
222 W. Merchandise Mart, Suite 1800
Chicago, IL 60654

Tests Requested By: Motorola Mobility LLC
222 W. Merchandise Mart, Suite 1800
Chicago, IL 60654

Product Type : Smart Watch

Signaling Capability: Bluetooth V3.0, Bluetooth LE V4.0 + EDR,
802.11b/g/n HT20

FCC ID: IHDT6UA1

Serial Numbers: LD4X250063, LD4X250141, LD4X250204
LD4X240119

Testing Complete Date: July 22, 2015

Applicable Standards

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-part J as well as the following parts:

 X Part 15 Subpart C – Intentional Radiators

Applicable Standards: ANSI C63.4 2009, ANSI 63.10 2009

All testing was performed according to KDB 558074 v03r03 and KDB 648474 D03 v01r02

Revision History

Revision Version	Date	Notes
Rev. 0	07/23/15	Initial issue of report.
Rev. 1	07/27/15	Updated KDB version and FCC ID.

Summary of Testing

Test	Test Name	Pass/Fail
1	6 dB Bandwidth	Pass
2	Peak Power	Pass
3	Peak Power Spectral Density	Pass
4	Spurious RF Conducted Emissions	Pass
5	Radiated Spurious Emissions	Pass
6	AC Line Conducted Emissions	Pass

Test	Test Name	Results
1	6 dB Bandwidth	See plots
2	Peak Power	See tables
3	Peak Power Spectral Density	See tables
4	Spurious RF Conducted Emissions	See plots
5	Radiated Spurious Emissions	See tables
6	AC Line Conducted Emissions	See Plots

General and Special Conditions

This product utilizes an internal battery that is not removable. All EMC radiated testing was performed with the internal battery fully charged. All Conducted testing was performed with a board level pigtail unit which was powered using an external power supply.

All testing was done in an indoor controlled environment. The temperature and the relative humidity were maintained within the ANSI C63.4 2009 Standard requirements during the entire duration of testing.

Based on the conducted power measurements the below data rates were tested for each mode.

802.11 b @ 11 Mbps
802.11 g @ 18 Mbps
802.11 n @ 28.9 Mbps

Equipment and Cable Configurations

For all radiated testing the EUT was tested in a standalone and while charging in a Wireless Charger configuration that is representative of typical use. In standalone configuration the EUT was evaluated in X, Y and Z orientation.

Measuring Equipment and Calibration Information

Manufacturer	Equipment Type	Model No.	Serial Number	Calibration Due Date
Rohde & Schwarz	Receiver	ESU40	100286	10/04/15
Agilent	Signal Generator	83623B	3844A00935	04/03/16
ETS-Lindgren	Horn Antenna	3115	6222	09/10/15
ETS-Lindgren	Horn Antenna	3116	00071568	03/12/16
TDK RF Solutions	Biconical Antenna	MBA-2060	130401	03/12/16
ETS	Log-Periodic Antenna	PLP-3003	130395	03/12/16
Weinschel	Attenuator	AS-6	7074	NCR
Agilent	Attenuator	8491A	50772	02/09/16
Agilent	Attenuator	8491A	56248	02/09/16
ETS-Lindgren	LISN	3810/2NM	00023630	09/12/15
ETS-Lindgren	Loop Antenna	6507	00049471	03/11/16
Agilent	Call Box	N1912A	MY45100116	04/03/16
Agilent	Signal Analyzer	N9020A	US46470586	01/13/16
Rohde & Schwarz	Signal Generator	SMF100A	102150	10/14/15
Agilent	Power Meter	N1912A	MY45100116	04/03/16
Agilent	Power Sensor	N1912A	MY45240662	04/03/16
Tektronix	Power Supply	PS282C	TW50294	NCR
Rohde & Schwarz	Preamplifier	TS-PR18	100068	10/01/15
Rohde & Schwarz	Preamplifier	TS-PR26	100039	10/01/15

Note that the signal analyzer and power meter are on a two-year calibration cycle. All test equipment was within their calibration date during the time of testing. When equipment went out of calibration during testing it was replaced using a similar piece of calibrated equipment. All these equipments are listed in the equipment list. All other equipment is on a one-year calibration cycle.

Description of WLAN Transmitter

The EUT offers WLAN as a feature. The WLAN antenna is mounted inside of the EUT. The antenna installation is permanent. For a more thorough description of the functionality please refer to Exhibit 12 of this package.

As a WLAN transmitter, it is designed operate with other WLAN devices as defined by the industrial standard. In this application, the device is battery operated.

De Facto EIRP Limit – Pursuant 47 CFR 15.247(b) (4)

Criterion: The conducted output power limit of 1-watt is based on the use of antennas with directional gains that do not exceed 6dB_i. If transmitting antennas of directional gain greater than 6dB_i are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dB_i.

The peak antenna gain of the antenna employed by this transmitter is less than 6dB_i.

Measurement Procedures and Data

6 dB Bandwidth

CFR 47 Part 15.247(a)(2)

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20 dB passive attenuator.

The spectrum analyzer used the following settings:



1. $RBW \geq 100 \text{ kHz}$
2. $VBW \geq 3 \times RBW$
3. Sweep = auto couple
4. Detector function = peak
5. Trace = max hold
6. Span = 30 MHz


The trace was allowed to stabilize. The automatic occupied bandwidth measurement function of the spectrum analyzer, set to 6dB or 26dB, is used.

The test results shown below represent the worst case condition.

Measurement Results


See attached

802.11b Mode**6dB Bandwidth Channel 1 @ 11Mbps****6dB Bandwidth Channel 6 @ 11Mbps**




6dB Bandwidth Channel 11 @ 1Mbps


802.11g Mode





6dB Bandwidth Channel 1 @ 18 Mbps




6dB Bandwidth Channel 6 @ 18 Mbps



6dB Bandwidth Channel 11 @ 18 Mbps

802.11n Mode**6dB Bandwidth Channel 1 @ 28.9 Mbps****6dB Bandwidth Channel 6 @ 28.9 Mbps**



6dB Bandwidth Channel 11 @ 28.9 Mbps

Peak Output Power

CFR 47 Part 15.247(b)

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the broad band power meter through a specialized RF connector and a 20dB passive attenuator. . The power meter is capable of measuring both peak and average power measurements.

Measurement Results

See Attached

Channel	Peak power (dBm) for <u>802.11b</u> Data Rates			
	1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
1	19.7	19.95	19.8	19.9
6	19.8	19.89	20.17	20.58
11	20.33	20.33	20.24	20.42

Channel	Peak power (dBm) for <u>802.11g</u> Data Rates							
	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
1	25.46	25.13	24.66	25.09	25.2	23.39	24.6	22.67
6	24.91	25.47	25.69	25.08	24.24	24.02	23.76	22.42
11	25.61	24.69	25.68	25.86	25.11	24.53	23.8	24.18

Channel	Peak power (dBm) for <u>802.11n</u> Data Rates							
	20 MHz BW, 400 ns GI							
	7.2 Mbps	14.4 Mbps	21.7 Mbps	28.9 Mbps	43.3 Mbps	57.8 Mbps	65 Mbps	72.2 Mbps
1	24.3	24.52	24.57	23.98	23.86	24.13	22.27	21.99
6	23.49	24.09	24.33	24.8	24.15	23.22	23.06	24
11	25.25	25.25	25.46	26.14	25.59	24.21	23.07	23.39

Channel	Average power (dBm) for <u>802.11b</u> Data Rates			
	1 Mbps	2 Mbps	5.5 Mbps	11 Mbps
1	17.3	17.44	17.36	17.46
6	17.48	17.6	17.61	17.65
11	17.81	17.92	17.86	17.98

Channel	Average power (dBm) for <u>802.11g</u> Data Rates							
	6 Mbps	9 Mbps	12 Mbps	18 Mbps	24 Mbps	36 Mbps	48 Mbps	54 Mbps
1	17.46	17.3	17.54	17.11	16.35	15.54	14.74	13.38
6	17.74	17.74	17.77	17.52	16.11	15.38	14.52	13.43
11	17.95	17.93	17.8	17.75	17.23	15.93	14.98	13.72

Channel	Average power (dBm) for <u>802.11n</u> Data Rates							
	20 MHz BW							
	7.2 Mbps	14.4 Mbps	21.7 Mbps	28.9 Mbps	43.3 Mbps	57.8 Mbps	65 Mbps	72.2 Mbps
1	16.64	16.01	16.31	15.94	15.06	14.18	13.19	12.48
6	16.17	16.28	16.25	16.18	15.08	14.27	13.62	12.49
11	17.19	17.06	16.94	17.03	16.43	15.5	14.49	14.02

Peak Power Spectral Density

CFR 47 Part 15.247(e)

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the EMC analyzer through a specialized RF connector and a 20 dB passive attenuator.

The spectrum analyzer used the following settings:

1. Span = 1.5 x DTS BW (6 dB Bandwidth)
2. RBW = 3 kHz
3. VBW= 10 kHz
4. Sweep = auto couple
5. Detector function = Peak
6. Trace = max hold

The trace was allowed to stabilize. The peak power is measured by the spectrum analyzer, using the peak marker function to determine the maximum amplitude level.

Measurement Results

See Attached

2412 MHz	2437 MHz	2462 MHz
-5.067 dBm	-4.288 dBm	-3.711 dBm

802.11 b 11 Mbps

2412 MHz	2437 MHz	2462 MHz
-4.837 dBm	-5.272 dBm	-4.991 dBm

802.11 g 18 Mbps

2412 MHz	2437 MHz	2462 MHz
-6.967 dBm	-6.384 dBm	-6.469 dBm

802.11n 28.9 Mbps

Spurious RF Conducted Emissions

CFR 47 Part 15.247(d)

Measurement Procedure

The RF output port of the Equipment-Under-Test is directly coupled to the input of the spectrum analyzer through a specialized RF connector and a 20 dB passive attenuator.

The reference level for 20 dB down is established using Power Spectral Density measurement using the below settings.

1. Span = 1.5 x DTS BW (6 dB Bandwidth)
2. RBW = 100 kHz
3. VBW = 300 kHz
4. Sweep = auto couple
5. Detector function = Peak
6. Trace = max hold

The trace was allowed to stabilize. The peak marker function is used to determine the maximum amplitude level.



The emission level measurement is performed using the below Spectrum Analyzer Settings.


1. RBW = 100 kHz
2. VBW $\geq$ 300 kHz
3. Detector function = Peak
4. Sweep = auto couple
5. Trace = max hold


The trace was allowed to stabilize. The peak marker function is used to determine the maximum amplitude level.

Measurement Results


See attached:

802.11b Mode @ 11 Mbps**Conducted Spurious Emissions 30 MHz-3000 MHz (Low Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (Low Channel)**


**Conducted Spurious Emissions 10 GHz-20 GHz (Low Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (Low Channel)**




Conducted Spurious Emissions 30 MHz-3000 MHz (Mid Channel)




Conducted Spurious Emissions 3 GHz-10 GHz (Mid Channel)




Conducted Spurious Emissions 10 GHz-20 GHz (Mid Channel)





Conducted Spurious Emissions 20 GHz-26 GHz (Mid Channel)







Conducted Spurious Emissions 30 MHz-3000 MHz (High Channel)




Conducted Spurious Emissions 3 GHz-10 GHz (High Channel)


**Conducted Spurious Emissions 10 GHz-20 GHz (High Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (High Channel)**

802.11 g @ 18 Mbps**Conducted Spurious Emissions 30 MHz-3000 MHz (Low Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (Low Channel)**



**Conducted Spurious Emissions 10 GHz-20 GHz (Low Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (Low Channel)**







Conducted Spurious Emissions 30 MHz-3000 MHz (Mid Channel)







Conducted Spurious Emissions 3 GHz-10 GHz (Mid Channel)



**Conducted Spurious Emissions 10 GHz-20 GHz (Mid Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (Mid Channel)**



**Conducted Spurious Emissions 30 MHz-3000 MHz (High Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (High Channel)**



**Conducted Spurious Emissions 10 GHz-20 GHz (High Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (High Channel)**



802.11 n @ 28.9 Mbps**Conducted Spurious Emissions 30 MHz-3000 MHz (Low Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (Low Channel)**

**Conducted Spurious Emissions 10 GHz-20 GHz (Low Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (Low Channel)**

**Conducted Spurious Emissions 30 MHz-3000 MHz (Mid Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (Mid Channel)**

**Conducted Spurious Emissions 10 GHz-20 GHz (Mid Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (Mid Channel)**

**Conducted Spurious Emissions 30 MHz-3000 MHz (High Channel)****Conducted Spurious Emissions 3 GHz-10 GHz (High Channel)**

**Conducted Spurious Emissions 10 GHz-20 GHz (High Channel)****Conducted Spurious Emissions 20 GHz-26 GHz (High Channel)**

Conducted Spurious Emissions at the Band Edge

CFR 47 Part 15.247(d)

Measurement Procedure



The RF output port of the Equipment-Under-Test is directly coupled to the input of the spectrum analyzer through a specialized RF connector and a 20dB passive attenuator.



The Spectrum Analyzer used the following settings:



1. Center Frequency = 2.4 GHz (lower band edge) or 2.4835 GHz (upper band edge)
2. RBW = 100kHz
3. VBW $\geq$ 300kHz
4. Detector function = peak
5. Sweep = auto couple
6. Trace = max hold
7. Sweep = Auto

Measurement Results

See attached:

802.11b @ 11 Mbps Band edge**Channel 1 – Lower Band Edge****Channel 11 – Upper Band Edge**

802.11g @ 18 Mbps Band Edge**Channel 1 – Lower Band Edge****Channel 11 – Upper Band Edge**

802.11n @ 28.9 Mbps Band Edge**Channel 1 – Lower Band Edge****Channel 11 – Upper Band Edge**

Radiated Spurious Emissions – Restricted Band

CFR 47 Part 15.247(d) 15.209(a)

Measurement Procedure

The EUT is placed inside the semi-anechoic chamber on a Styrofoam table at the turntable center. The Styrofoam table is 0.8 meter above the ground plane. For each spurious frequency, the antenna mast is raised and lowered from 1 to 4 meters and the turntable is rotated 360 degrees to obtain a maximum reading on the spectrum analyzer. This is repeated for both horizontal and vertical polarizations of the receive antenna.

For all measurements up to 12 GHz the EUT was 3 meters from the measuring antenna. All emissions above 12 GHz were measured at 1 meter measuring distance.

The EUT was tested in a standalone and while charging in a Wireless Charger configuration that is representative of typical use. In standalone configuration the EUT was evaluated in X, Y and Z orientation.

Field Strength dBuV/m = Measured Level + Antenna Factor + Cable Loss – Preamp Gain

The below Spectrum Analyzer settings were used for measurements

RBW = 100 kHz for $f < 1$ GHz and 1 MHz for $f > 1$ GHz

VBW $\geq$ RBW for $F < 1$ GHz

VBW – 3 MHz for Peak Measurements for $f > 1$ GHz

VBW – 3 kHz for Average Measurements for $f > 1$ GHz

Detector – Peak

Sweep – auto couple

Trace – max hold

Measurement Results

See attached:

No significant emissions were found in the below frequency range.

9 kHz – 30 MHz

30 MHz – 1 GHz

12 GHz – 26.5 GHz

Worst case emissions reported.

802.11b Mode @ 11 Mbps**Channel 1 @ 11 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4824	53.88	41.28	40.61	28.01	74	54	-20.12	-12.72	H
	53.59	40.39	40.32	27.12	74	54	-20.41	-13.61	V
7236	57.43	43.9	39	25.47	74	54	-16.57	-10.1	H
	57.45	43.9	39.02	25.47	74	54	-16.55	-10.1	V
9648	60.74	47.25	38.47	24.98	74	54	-13.26	-6.75	H
	61.13	47.14	38.86	24.87	74	54	-12.87	-6.86	V

Channel 6 @ 11 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4874	53.71	40.51	40.44	27.24	74	54	-20.29	-13.49	H
	53.22	40.39	39.95	27.12	74	54	-20.78	-13.61	V
7311	57.44	43.49	39.01	25.06	74	54	-16.56	-10.51	H
	57.32	43.53	38.89	25.1	74	54	-16.68	-10.47	V
9748	60.7	48.37	38.43	26.1	74	54	-13.3	-5.63	H
	61.2	48.47	38.93	26.2	74	54	-12.8	-5.53	V
12185	63.85	51.27	38.15	25.57	74	54	-10.15	-2.73	H
	64.17	51.39	38.47	25.69	74	54	-9.83	-2.61	V

Channel 11 @ 11 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4924	53.18	40.39	39.91	27.12	74	54	-20.82	-13.61	H
	53.27	41.34	40	28.07	74	54	-20.73	-12.66	V
7386	57.08	43.89	38.65	25.46	74	54	-16.92	-10.11	H
	57.13	43.81	38.7	25.38	74	54	-16.87	-10.19	V
9848	60.54	51.01	38.27	28.74	74	54	-13.46	-2.99	H
	59.66	49.3	37.39	27.03	74	54	-14.34	-4.7	V
12310	63.86	51.28	38.16	25.58	74	54	-10.14	-2.72	H
	64.18	51.37	38.48	25.67	74	54	-9.82	-2.63	V

802.11 g @ 18 Mbps**Channel 1 @ 18 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4824	53.51	40.82	40.24	27.55	74	54	-20.49	-13.18	H
	53.1	40.81	39.83	27.54	74	54	-20.9	-13.19	V
7236	55.23	44.12	36.8	25.69	74	54	-18.77	-9.88	H
	53.62	44.21	35.19	25.78	74	54	-20.38	-9.79	V
9648	61.26	48.92	38.99	26.65	74	54	-12.74	-5.08	H
	59.73	48.13	37.46	25.86	74	54	-14.27	-5.87	V
12060	64.32	51.17	38.62	25.47	74	54	-9.68	-2.83	H
	64.36	51.27	38.66	25.57	74	54	-9.64	-2.73	V

Channel 6 @ 18 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4874	53.73	40.25	40.46	26.98	74	54	-20.27	-13.75	H
	53.13	39.66	39.86	26.39	74	54	-20.87	-14.34	V
7311	57.71	44.42	39.28	25.99	74	54	-16.29	-9.58	H
	57.52	44.34	39.09	25.91	74	54	-16.48	-9.66	V
9748	60.82	48.99	38.55	26.72	74	54	-13.18	-5.01	H
	61.04	47.42	38.77	25.15	74	54	-12.96	-6.58	V
12185	64.22	51.23	38.52	25.53	74	54	-9.78	-2.77	H
	63.56	51.16	37.86	25.46	74	54	-10.44	-2.84	V

Channel 11 @ 18 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4924	53.44	40.38	40.17	27.11	74	54	-20.56	-13.62	H
	53.1	40.54	39.83	27.27	74	54	-20.9	-13.46	V
7386	57.75	44.29	39.32	25.86	74	54	-16.25	-9.71	H
	57.69	44.34	39.26	25.91	74	54	-16.31	-9.66	V
9848	60.98	48.48	38.71	26.21	74	54	-13.02	-5.52	H
	60.48	47.61	38.21	25.34	74	54	-13.52	-6.39	V
12310	64.35	51.26	38.65	25.56	74	54	-9.65	-2.74	H
	63.39	51.38	37.69	25.68	74	54	-10.61	-2.62	V

802.11 n @ 28.9 Mbps**Channel 1 @ 28.9 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4824	52.99	40.55	39.72	27.28	74	54	-21.01	-13.45	H
	53.42	40.45	40.15	27.18	74	54	-20.58	-13.55	V
7236	59.08	45.26	39.08	25.26	74	54	-16.49	-10.31	H
	58.8	45.27	38.8	25.27	74	54	-16.77	-10.3	V
9648	59.46	45.84	39.46	25.84	74	54	-12.27	-5.89	H
	58.4	44.96	38.4	24.96	74	54	-13.33	-6.77	V

Channel 6 @ 28.9 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4874	53.2	40.64	39.93	27.37	74	54	-20.8	-13.36	H
	53.82	40.66	40.55	27.39	74	54	-20.18	-13.34	V
7311	57.24	44.59	38.81	26.16	74	54	-16.76	-9.41	H
	57.66	44.53	39.23	26.1	74	54	-16.34	-9.47	V
9748	60.82	47.61	38.55	25.34	74	54	-13.18	-6.39	H
	60.4	47.67	38.13	25.4	74	54	-13.6	-6.33	V

Channel 11 @ 28.9 Mbps

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
4874	53.45	41.01	40.18	27.74	74	54	-20.55	-12.99	H
	52.99	40.63	39.72	27.36	74	54	-21.01	-13.37	V
7386	57.25	44.22	38.82	25.79	74	54	-16.75	-9.78	H
	57.42	44.07	38.99	25.64	74	54	-16.58	-9.93	V
9848	60.93	48.44	38.66	26.17	74	54	-13.07	-5.56	H
	60.42	47.46	38.15	25.19	74	54	-13.58	-6.54	V

Radiated Band Edge**802.11b Mode @ 11 Mbps****Channel 1 and 11 @ 11 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
2310-2390	58.22	44.52	52	38.3	74	54	-15.78	-9.48	H
	57.65	44.42	51.43	38.2	74	54	-16.35	-9.58	V
2483.5-2500	28.42	45.25	21.72	38.55	74	54	-45.58	-8.75	H
	63.49	50.27	56.79	43.57	74	54	-10.51	-3.73	V

802.11g Mode @ 18 Mbps**Channel 1 and 11 @ 18 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
2310-2390	58.22	45.29	52	39.07	74	54	-15.78	-8.71	H
	62.96	50.24	56.74	44.02	74	54	-11.04	-3.76	V
2483.5-2500	65.87	52.15	59.17	45.45	74	54	-8.13	-1.85	H
	67.85	52.67	61.15	45.97	74	54	-6.15	-1.33	V

802.11n Mode @ 28.9 Mbps**Channel 1 and 11 @ 28.9 Mbps**

Frequency	Peak Level	Average Level	Peak Measured	Average Measured	Peak Limit	Average Limit	Peak Margin	Average Margin	Pol
MHz	dBμV/m	dBμV/m	dBμV	dBμV	dBμV/m	dBμV/m	dB	dB	
2310-2390	60.1	44.81	53.88	38.59	74	54	-13.9	-9.19	H
	58.95	44.06	52.73	37.84	74	54	-15.05	-9.94	V
2483.5-2500	66.92	51.76	60.22	45.06	74	54	-7.08	-2.24	H
	66.57	51.9	59.87	45.2	74	54	-7.43	-2.1	V

AC Line Conducted Emissions

CFR 47 Part 15.207(a)

Measurement Procedure

AC power-line conducted emission measurements are made over the frequency range from 150 kHz to 30 MHz to determine the line-to-ground radio-noise voltage that is conducted from all of the EUT current-carrying power input terminals that are directly or indirectly connected to a public power network. The measurements are made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN.


Preliminary measurements are made using a peak detector and final measurements are performed using Quasi Peak and Average Detectors. The RBW of the EMI receiver is set to 9 kHz for all final measurements. If there is enough margin using the peak detector then no final measurements are performed.

Conducted Emission (dBuV) = EMI Receiver Level (dBuV) + Loss (dB)


The EUT is setup according to the procedures in ANSI C63.10-2009. The test is performed with the EUT connected to the LISN while charging in the Wireless Charger.

Measurement Results

See attached:


802.11b @ 1Mbps**WLAN Channel 1 - TX Mode - Line Coupling**

Freq	(PEAK) EMI (L1)	(AVG) EMI (L1)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.15	46.37	30.95	66	56	19.63	25.05
0.17	43.8	28.56	65.09	55.09	21.29	26.53
1.86	38.41	27.02	56	46	17.59	18.98
5.18	39	28.12	60	50	21	21.88
13.47	36.09	27.95	60	50	23.91	22.05
14.3	39.4	32.87	60	50	20.6	17.13
15.95	38.72	28.67	60	50	21.28	21.33
17.62	38.26	29.21	60	50	21.74	20.79
19.27	33.1	24.27	60	50	26.9	25.73
22.6	31.42	17.5	60	50	28.58	32.5
27.57	25.47	11.02	60	50	34.53	38.98

WLAN Channel 1 - TX Mode – Neutral Coupling


Freq	(PEAK) EMI (N)	(AVG) EMI (N)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.19	44.91	27.81	64.1	54.1	19.19	26.29
0.62	35.24	24.14	56	46	20.76	21.86
1.03	31.47	22.85	56	46	24.53	23.15
1.45	35.38	27.02	56	46	20.62	18.98
1.84	32.41	20.48	56	46	23.59	25.52
6.02	33.63	27.48	60	50	26.37	22.52
6.85	36.27	30	60	50	23.73	20
7.27	32.63	24.08	60	50	27.37	25.92
13.07	31.74	25.79	60	50	28.26	24.21
14.73	32.37	26.73	60	50	27.63	23.27
26.76	27.7	17.1	60	50	32.3	32.9

WLAN Channel 6 - TX Mode - Line Coupling




Freq	(PEAK) EMI (L1)	(AVG) EMI (L1)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.35	40.38	30.19	59.06	49.06	18.68	18.87
0.5	40.53	26.95	56	46	15.47	19.05
0.69	40.15	26.8	56	46	15.85	19.2
1.41	39.57	26.9	56	46	16.43	19.1
1.84	40.63	27.33	56	46	15.37	18.67
4.83	37.86	25.98	56	46	18.14	20.02
4.88	39.37	26.04	56	46	16.63	19.96
6.45	37.04	22.67	60	50	22.96	27.33
24.23	34.83	26.08	60	50	25.17	23.92
26.5	26.22	17.85	60	50	33.78	32.15

WLAN Channel 6 - TX Mode - Neutral Coupling




Freq	(PEAK) EMI (N)	(AVG) EMI (N)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.17	47.21	31.04	64.84	54.84	17.63	23.8
0.35	39.96	27.25	58.98	48.98	19.02	21.73
1.44	33.95	22.61	56	46	22.05	23.39
1.94	34.16	22.07	56	46	21.84	23.93
4.29	33.84	20.97	56	46	22.16	25.03
4.98	35.11	21.97	56	46	20.89	24.03
22.15	20.77	9.48	60	50	39.23	40.52
22.37	26.82	16.31	60	50	33.18	33.69
23.52	27.82	21.74	60	50	32.18	28.26

WLAN Channel 11 - TX Mode - Line Coupling

Freq	(PEAK) EMI (L1)	(AVG) EMI (L1)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.15	47.87	31.12	65.75	55.75	17.88	24.63
0.35	40.71	30.33	59.06	49.06	18.35	18.73
0.61	40.26	26.88	56	46	15.74	19.12
1.44	40.33	26.95	56	46	15.67	19.05
1.88	40.67	27.5	56	46	15.33	18.5
4.74	39.61	27.11	56	46	16.39	18.89
6.26	36.84	23.08	60	50	23.16	26.92
12.82	33.72	23.13	60	50	26.28	26.87
15.95	33.54	23.27	60	50	26.46	26.73
24.23	28.27	13.8	60	50	31.73	36.2

WLAN Channel 11 - TX Mode - Neutral Coupling



Freq	(PEAK) EMI (N)	(AVG) EMI (N)	QP Limit	AVG Limit	QP Margin	AVG Margin
MHz	dBuV	dBuV	dBuV	dBuV	dB	dB
0.15	46.44	29.08	65.75	55.75	19.31	26.67
0.28	41.64	21.66	60.79	50.79	19.15	29.13
0.5	37.35	23.51	56.08	46.08	18.73	22.57
1.45	35.39	22.55	56	46	20.61	23.45
1.88	34.83	23.18	56	46	21.17	22.82
4.74	34.88	23.06	56	46	21.12	22.94
8.19	31.94	14.96	60	50	28.06	35.04
15.33	30.8	18.73	60	50	29.2	31.27
23.28	25.78	19.68	60	50	34.22	30.32
25.98	23.72	11.03	60	50	36.28	38.97

End of Test Report