



REVISION	
DESCRIPTION	BY APPR



- | | | |
|--------------------------------|---------------------|--|
| 3 | SPECIFICATION TABLE | |
| FREQUENCY (GHz) | 2.4 TO 2.5 | |
| VSWR | 2:1 | |
| NOMINAL IMPEDANCE (Ω) | 50 | |
| PEAK GAIN (dBi) | 0 | |
| OPERATING TEMPERATURE(°C) | -40 TO 85 | |
| POWER RATING (WATT) | 10 | |
- 
- TITLE

ANTENNA, SNAP-ON, LC 1 PIECE


SIZE B

DWG NO. 1900.0049

REV A

2	ASSEMBLY WELD PARAMETERS	
	BOOSTER	ALUM 1:1.5
	MODE	TIME
	LIMITS	FACTORY DEFAULTS
	PRESSURE(P/PSI)	25
	WELD TIME(m/s)	125
	HOLD TIME(m/s)	1050

SPECIFICATION TABLE	
FREQUENCY (GHz)	2.4 TO 2.5
VSWR	2:1
NOMINAL IMPEDANCE (Ω)	50
PEAK GAIN (dBi)	0
OPERATING TEMPERATURE(°C)	-40 TO 85
POWER RATING (WATT)	10

UNLESS OTHERWISE SPECIFIED		DRAWN		L. NICOLI		06/09/98	
DIMENSIONS ARE IN INCHES		DESIGN		L. NICOLI		06/09/98	
TOLERANCES							
XX .00 .01 ANGULAR							
XXX .00 .005 1/32A							
BREAK ALL SHARP EDGES							
APPROX. .010							
MACHINE SURFACES							
DIMENSIONS APPLY AFTER FINISH							
DO NOT SCALE DRAWING							
CHECKED AND APPROVED		FINISH		N/A			
-ms 8/27/98							
TITLE							
 ANTENNA, SNAP-ON, LC 1 PIECE							
SIZE		DWG NO.		1900.0049		REV	
B						A	
SCALE		2/1		FILE NAME		19000049	
				SHEET		1 OF 1	