



TEST REPORT

For RF

Report No..... : CHTW26075017

Project No : SHT2606068002W

FCC ID : IN2TX65

Applicant's name : Hunter Fan Company

Address..... : 7130 Goodlett Farms Parkway, Suite 400 Memphis Tennessee 38016
USA

Product Name..... : Remote control

Trade Mark..... : -

Model No..... : KM278

Listed Model(s) : KM422,KM578,KM579

Standard : **FCC CFR Title 47 Part 15 Subpart C § 15.231**

Date of receipt of test sample..... : 2026/6/30

Date of testing..... : 2026/6/30 - 2026/7/14

Date of issue..... : 2026/7/21

Result..... : **Pass**



CHT26075017

Compiled by
(Position+Printed name+Signature) : File administrator Xiaodong Zhao *Xiaodong Zhao*

Supervised by
(Position+Printed name+Signature) : Project Engineer Kiki Kong *Kiki Kong*

Approved by
(Position+Printed name+Signature) : RF Manager Xu Yang *Xu Yang*

Testing Laboratory Name : **Shenzhen Huatongwei International Inspection Co., Ltd.**

Address..... : Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China

Test Report Form No. : R0054

Test Report Form(s) Originator : Shenzhen Huatongwei International Inspection Co., Ltd.

Master TRF : Dated 2025-04

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context. The test report merely correspond to the test sample. The authenticity of this Test Report and its contents can be verified by contacting the Laboratory, responsible for this Test Report.

Contents

<u>1.</u>	<u>TEST STANDARDS AND REPORT VERSION</u>	<u>3</u>
1.1.	Test Standards	3
1.2.	Report version	3
<u>2.</u>	<u>TEST DESCRIPTION</u>	<u>4</u>
<u>3.</u>	<u>SUMMARY</u>	<u>5</u>
3.1.	Client Information	5
3.2.	Product Description	5
3.3.	Radio Specification Description	5
3.4.	Testing Laboratory Information	6
<u>4.</u>	<u>TEST CONFIGURATION</u>	<u>7</u>
4.1.	Test frequency list	7
4.2.	Descriptions of Test mode	7
4.3.	Test sample information	7
4.4.	Test software name and power settings	7
4.5.	Support unit used in test configuration and system	8
4.6.	Testing environmental condition	8
4.7.	Statement of the measurement uncertainty	8
4.8.	Equipment Used during the Test	9
<u>5.</u>	<u>TEST CONDITIONS AND RESULTS</u>	<u>11</u>
5.1.	Antenna Requirement	11
5.2.	AC Conducted Emission	12
5.3.	20dB bandwidth	13
5.4.	99% Occupied Bandwidth	14
5.5.	Transmission Time	15
5.6.	Duty Cycle Corrected Factor	16
5.7.	Radiated field strength of the fundamental signal	17
5.8.	Radiated Spurious Emission	19
<u>6.</u>	<u>TEST SETUP PHOTOS</u>	<u>28</u>
<u>7.</u>	<u>EXTERNAL AND INTERNAL PHOTOS</u>	<u>30</u>
7.1.	External Photos	30
7.2.	Internal Photos	39
<u>8.</u>	<u>APPENDIX REPORT</u>	<u>46</u>

1. TEST STANDARDS AND REPORT VERSION

1.1. Test Standards

The tests were performed according to following standards:

- [FCC CFR Title 47 Part 15 Subpart C § 15.231](#): Periodic operation in the band 40.66-40.70 MHz and above 70 MHz
- [ANSI C63.10-2020+Cor 1-2023+C63.10a-2024 + Errata to c63.10a-2024](#) American National Standard for Procedures for Compliance Testing of Unlicensed Wireless Devices Amendment 1

1.2. Report version

Revision No.	Date of issue	Description
N/A	2026-07-21	Original

2. TEST DESCRIPTION

Report clause	Test Items	Standard Requirement	Result	Test Engineer
5.1	Antenna Requirement	15.203	PASS	Kiki kong
5.2	AC Conducted Emission	15.207	N/A	N/A
5.3	20dB Bandwidth	15.231(c)	PASS	Kiki kong
5.4	99% Occupied Bandwidth	-	PASS ^{*1}	Kiki kong
5.5	Transmission time	15.231(a)(1)	PASS	Kiki kong
5.6	Duty cycle corrected factor	-	PASS ^{*1}	Kiki kong
5.7	Field strength of the Fundamental signal	15.231(b)	PASS	Junxu Lin
5.8	Radiated Spurious Emission	15.231(b)/15.205/15.209	PASS	Junxu Lin ZIWEN.WANG

Note:

- The measurement uncertainty is not included in the test result.
- ^{*1}: No requirement on standard, only report these test data.
- The EUT is powered by a battery

3. SUMMARY

3.1. Client Information

Applicant:	Hunter Fan Company
Address:	7130 Goodlett Farms Parkway, Suite 400 Memphis Tennessee 38016 USA
Manufacturer:	Hunter Fan Company
Address:	7130 Goodlett Farms Parkway, Suite 400 Memphis Tennessee 38016 USA
Factory:	H&T Intelligent Control (Vietnam) Co, Ltd
Address:	Steel structure workshop No. 35, Plot CN8 and C-24 belong to land lot CN10, An Duong Industrial Park, Hong Phong Commune, An Duong District, Hai Phong City

3.2. Product Description

Main unit information:	
Product Name:	Remote control
Trade Mark:	-
Model No.:	KM278
Listed Model(s):	KM422,KM578,KM579
Power supply:	DC 3.0V from Battery
Hardware version:	V01
Software version:	V01

3.3. Radio Specification Description

Operation frequency:	433.92MHz
Modulation:	OOK
Channel number:	1
Antenna type:	PCB Antenna

3.4. Testing Laboratory Information

Laboratory Name	Shenzhen Huatongwei International Inspection Co., Ltd.	
Laboratory Location	Building 7, Baiwang Idea Factory, No.1051, Songbai Road, Yangguang Community, Xili Subdistrict, Nanshan District, Shenzhen, Guangdong, China	
Contact information:	Phone: 400-963-0755 E-mail: cs@szhtw.com.cn http://www.szhtw.com.cn	
Qualifications	Type	Accreditation Number
	FCC Registration Number	762235
	FCC Designation Number	CN1181

4. TEST CONFIGURATION

4.1. Test frequency list

According to section ANSI C63.10 section 5.6.1,

Measurements of unlicensed wireless devices shall be performed and, if required, reported for each band in which the EUT can be operated with the device operating at the number of frequencies in each band specified in Table 4

Table 4—Number of frequencies to be tested

Frequency range in which device operates	Number of frequencies	Location in frequency range of operation
1 MHz or less	1	Middle
1 MHz to 10 MHz	2	1 near top and 1 near bottom
More than 10 MHz	3	1 near top, 1 near middle, and 1 near bottom

So test frequency as follow:

Channel	Frequency (MHz)
CH_M	433.92

4.2. Descriptions of Test mode

For RF test items
The engineering test program was provided and enabled to make EUT continuous transmit.
For Radiated spurious emissions test item:
The engineering test program was provided and enabled to make EUT continuous transmit. The EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data Recorded in the report.

4.3. Test sample information

Test item	HTW sample no.
RF Conducted test items	Please refer to the description in the appendix report
RF Radiated test items	YPHT26060680001
EMI test items	-

Note:

RF Conducted test items: 20dB Bandwidth ,99% Occupied Bandwidth, Transmission time, Duty cycle corrected factor

RF Radiated test items: Field strength of the Fundamental signal

4.4. Test software name and power settings

Test software	power settings
EUT burning 433.92MHz for continuous modulation wave transmission mode	Default

4.5. Support unit used in test configuration and system

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

The following peripheral devices and interface cables were connected during the measurement:

Whether support unit is used?			
✓ No			
Item	Equipment	Trade Name	Model No.
1			
2			

4.6. Testing environmental condition

Type	Requirement	Actual
Temperature:	15~35°C	25°C
Relative Humidity:	25~75%	50%
Air Pressure:	860~1060mbar	1000mbar

4.7. Statement of the measurement uncertainty

No.	Test Items	Measurement Uncertainty
1	AC Conducted Emission	3.21dB
2	20dB Bandwidth	0.002%
3	99% Occupied Bandwidth	0.002%
4	Transmission time	2.3ns
5	Duty cycle corrected factor	-
6	Field strength of the Fundamental signal	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz
7	Radiated Spurious Emission	4.54dB for 30MHz-1GHz 5.10dB for above 1GHz

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

4.8. Equipment Used during the Test

● EMC Test Software					
Used	Test Item	Software Name	Manufacturer	Equipment No.	Version
●	Radiated Emission	EMC32	R&S	HTWER012	V10.60.20
●	Radiated Emission	TS+	Tonscend	/	V5.0.0

● RF Conducted test item							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Signal and spectrum Analyzer	R&S	HTWE0242	FSV40	100048	2025/8/19	2026/8/18
●	Vector signal generator	R&S	HTWE0244	SMBV100A	260790	2026/3/13	2027/3/12
●	OSP	R&S	HTWE0243	OSP120	101317	2025/8/19	2026/8/18
●	10dB Attenuator	R&S	HTWE0250-01	10dB Attenuator-1	N/A	2025/8/22	2026/8/21
●	10dB Attenuator	R&S	HTWE0250-02	10dB Attenuator-2	N/A	2025/8/22	2026/8/21
●	10dB Attenuator	R&S	HTWE0250-03	10dB Attenuator-3	N/A	2025/8/22	2026/8/21
●	10dB Attenuator	R&S	HTWE0250-04	10dB Attenuator-4	N/A	2025/8/22	2026/8/21
●	30dB Attenuator	R&S	HTWE0250-05	30dB Attenuator-5	N/A	2025/8/22	2026/8/21

● Auxiliary Equipment							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Climate chamber	ESPEC	HTWS0715	GPL-2	N/A	2026/6/5	2027/6/4
●	Walk-in Constant Temperature And Humidity Cabinet	重庆银河	HTWS0383	SDJ610A	201800463	2026/6/5	2027/6/4
○	DC Power Supply	Gwinstek	HTWE0274	SPS-2415	GER835793	N/A	N/A
○	DC Power Supply	MESTEK	HTWE0705	DP6010	00230820197	N/A	N/A

● Radiated emission- 9kHz~30MHz							
Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2026/3/24	2029/3/23
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2025/8/6	2026/8/5
●	Loop Antenna	R&S	HTWE0546	HFH2-Z2E	101073	2024/4/8	2027/4/7

● Radiated emission- 30MHz~1GHz

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Semi-Anechoic Chamber	Albatross projects	HTWE0127	SAC-3m-02	C11121	2026/3/24	2029/3/23
●	EMI Test Receiver	R&S	HTWE0099	ESCI 7	100900	2025/8/6	2026/8/5
●	Ultra-Broadband Antenna	SCHWARZBECK	HTWE0119	VULB9163	546	2025/12/16	2028/12/15
●	Pre-Amplifier	SCHWARZBECK	HTWE0295	BBV 9742	/	2026/5/12	2027/5/11
●	CMAD	SCHWARZBECK	HTWE0537	CMAD1614	1614-530	2025/8/4	2026/8/3

● Radiated emission- Above 1GHz

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
●	Full-Anechoic Chamber	Albatross projects	HTWE0122	SAC-3m-01	C11122	2026/3/19	2029/3/18
●	Spectrum Analyzer	R&S	HTWE0098	FSP40	100597	2025/8/6	2026/8/5
●	Horn Antenna	SCHWARZBECK	HTWE0126	BBHA 9120D	1011	2026/1/23	2029/1/22
●	Broadband Pre-amplifier	SCHWARZBECK	HTWE0551	SCU18F	100855	2026/5/12	2027/5/11

● Auxiliary Equipment

Used	Test Equipment	Manufacturer	Equipment No.	Model No.	Serial No.	Last Cal. Date (YY-MM-DD)	Next Cal. Date (YY-MM-DD)
○	DC Power Supply	Gwinstek	HTWE0274	SPS-2415	GER835793	N/A	N/A
○	DC Power Supply	MESTEK	HTWE0705	DP6010	00230820197	N/A	N/A

5. TEST CONDITIONS AND RESULTS

5.1. Antenna Requirement

Requirement

FCC CFR Title 47 Part 15 Subpart C Section 15.203:


An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

TEST RESULT

☒ **Passed** ☐ **Not Applicable**

The antenna type is a PCB antenna, the directional gain of the antenna less than 6 dBi, please refer to the below antenna photo.

|



5.2. AC Conducted Emission


LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.207

Frequency range (MHz)	Limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup according to ANSI C63.10 requirements.
2. The EUT was placed on a platform of nominal size, 1 m by 1.5 m, raised 80 cm above the conducting ground plane. The vertical conducting plane was located 40 cm to the rear of the EUT. All other surfaces of EUT were at least 80 cm from any other grounded conducting surface.
3. The EUT and simulators are connected to the main power through a line impedances stabilization network (LISN). The LISN provides a 50 ohm /50uH coupling impedance for the measuring equipment.
4. The peripheral devices are also connected to the main power through a LISN. (Please refer to the block diagram of the test setup and photographs)
5. Each current-carrying conductor of the EUT power cord, except the ground (safety) conductor, was individually connected through a LISN to the input power source.
6. The excess length of the power cord between the EUT and the LISN receptacle were folded back and forth at the center of the lead to form a bundle not exceeding 40 cm in length.
7. Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9 kHz.
8. During the above scans, the emissions were maximized by cable manipulation.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☐ Passed ☒ Not Applicable

Note: The EUT is powered by a battery


5.3. 20dB bandwidth

LIMIT

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900 MHz.

For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
 Center Frequency = channel center frequency
 $\text{Span} \geq 1.5 \times \text{OBW}$
 $\text{RBW} = 1\% \sim 5\% \text{OBW}$
 $\text{VBW} \geq 3 \times \text{RBW}$
 Sweep time = auto couple
 Detector = Peak
 Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission, and record the pertinent measurements.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA:


Refer to the appendix report on the section 8

5.4. 99% Occupied Bandwidth

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. Connect the antenna port(s) to the spectrum analyzer input.
2. Configure the spectrum analyzer as shown below (enter all losses between the transmitter output and the spectrum analyzer).
Center Frequency = channel center frequency
Span $\geq 1.5 \times \text{OBW}$
RBW = 1%~5%OBW
VBW $\geq 3 \times \text{RBW}$
Sweep time = auto couple
Detector = Peak
Trace mode = max hold
3. Place the radio in continuous transmit mode, allow the trace to stabilize, view the transmitter waveform on the spectrum analyzer.

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report on the section 8

5.5. Transmission Time

LIMIT

A manually operated transmitter shall employ a switch that will auto-matically deactivate the transmitter within not more than 5 seconds of being released.

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Frequency=Center carrier frequency
RBW=100kHz, VBW=300kHz, Span= zero,
Sweep time= 10second, Detector function = peak, Trace = single
4. Measure and record the results in the test report.

TEST MODE:

Please refer to the clause 4.2

TEST RESULTS

☒ Passed ☐ Not Applicable

TEST DATA


Refer to the appendix report on the section 8

5.6. Duty Cycle Corrected Factor

LIMIT

N/A

TEST CONFIGURATION



TEST PROCEDURE

1. The transmitter output was connected to the spectrum analyzer through an attenuator, the path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. Use the following spectrum analyzer settings:
Span=zero span, Frequency=centered channel, RBW= 100KHz, VBW $\geq$ RBW
Sweep time=as necessary to capture the entire dwell time,
Detector function = peak, Trigger mode
4. Measure and record the duty cycle data

TEST MODE:

Please refer to the clause 4.2

TEST DATA

Refer to the appendix report on the section 8


5.7. Radiated field strength of the fundamental signal

LIMIT

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

¹Linear interpolations.

TEST CONFIGURATION



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1GHz, The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

TEST MODE:

Please refer to the clause 4.2


TEST RESULTS

☒ Passed ☐ Not Applicable

Note:

1) Level= Reading + Factor; Factor =Antenna Factor+ Cable Loss- Preamp Factor

2) Margin = Limit - Level



5.8. Radiated Spurious Emission

LIMIT

FCC CFR Title 47 Part 15 Subpart C Section 15.231(b)

Fundamental frequency (MHz)	Field strength of fundamental (microvolts/meter)	Field strength of spurious emissions (microvolts/meter)
40.66-40.70	2,250	225
70-130	1,250	125
130-174	¹ 1,250 to 3,750	¹ 125 to 375
174-260	3,750	375
260-470	¹ 3,750 to 12,500	¹ 375 to 1,250
Above 470	12,500	1,250

FCC CFR Title 47 Part 15 Subpart C Section 15.209

Frequency	Limit (dBuV/m)	Value
0.009 MHz ~0.49 MHz	2400/F(kHz) @300m	Quasi-peak
0.49 MHz ~ 1.705 MHz	24000/F(kHz) @30m	Quasi-peak
1.705 MHz ~30 MHz	30 @30m	Quasi-peak


Note: Limit dBuV/m @3m = Limit dBuV/m @300m + 40*log(300/3)= Limit dBuV/m @300m +80,

Limit dBuV/m @3m = Limit dBuV/m @30m +40*log(30/3)= Limit dBuV/m @30m + 40.


Frequency	Limit (dBuV/m @3m)	Value
30MHz~88MHz	40.00	Quasi-peak
88MHz~216MHz	43.50	Quasi-peak
216MHz~960MHz	46.00	Quasi-peak
960MHz~1GHz	54.00	Quasi-peak
Above 1GHz	54.00	Average
	74.00	Peak

TEST CONFIGURATION


- 9 kHz ~ 30 MHz



- 30 MHz ~ 1 GHz



- Above 1 GHz



TEST PROCEDURE

1. The EUT was setup and tested according to ANSI C63.10.
2. The EUT is placed on a turn table which is 0.8 meter above ground for below 1 GHz, and 1.5 m for above 1 GHz. The turn table is rotated 360 degrees to determine the position of the maximum emission level.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the top of a variable height antenna tower.
4. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
5. Set to the maximum power setting and enable the EUT transmit continuously.
6. Use the following spectrum analyzer settings
 - a) Span shall wide enough to fully capture the emission being measured;
 - b) Below 1 GHz:

RBW=120 kHz, VBW=300 kHz, Sweep=auto, Detector function=peak, Trace=max hold;

If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
 - c) Set RBW=1MHz, VBW=3MHz for >1GHz, Sweep time=auto, Detector=peak, Trace=max hold for Peak measurement

For average measurement:

Average level = Peak level – DCCF

TEST MODE:

Please refer to the clause 4.2

TEST RESULT

☒ **Passed** ☐ **Not Applicable**


Note:

- 1) Level= Reading + Factor/Transd; Factor/Transd =Antenna Factor+ Cable Loss- Preamp Factor
- 2) Margin = Limit – Level
- 3) Over Limit = Level – Limit

FOR 9 kHz ~ 30 MHz

Polarization:

X

**Final Data List**


NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pol
1	0.0165	-30.28	53.06	22.78	123.79	101.01	100	0	X
2	0.0390	-30.72	50.81	20.09	115.81	95.72	100	0	X
3	0.0690	-31.13	45.15	14.02	110.84	96.82	100	0	X
4	0.1665	-31.34	30.4	-0.94	103.24	104.18	100	330	X
5	0.4514	-31.23	29.31	-1.92	94.52	96.44	100	330	X
6	1.1374	-31.21	29.36	-1.85	66.50	68.35	100	303	X

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

Polarization:

Y



Final Data List


NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pol
1	0.0165	-30.28	52.21	21.93	123.79	101.86	100	290	Y
2	0.0615	-31.05	45.4	14.35	111.84	97.49	100	290	Y
3	0.1065	-31.25	33.24	1.99	107.07	105.08	100	290	Y
4	0.1290	-31.28	30.72	-0.56	105.45	106.01	100	204	Y
5	0.3352	-31.47	29.29	-2.18	97.12	99.30	100	204	Y
6	0.8000	-31.03	29.56	-1.47	69.54	71.01	100	290	Y

Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

Polarization:

Z



Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pol
1	0.0090	-30.14	55.59	25.45	128.52	103.07	100	143	Z
2	0.0390	-30.72	52.75	22.03	115.81	93.78	100	143	Z
3	0.2227	-31.42	29.96	-1.46	100.68	102.14	100	269	Z
4	0.3277	-31.48	30.46	-1.02	97.32	98.34	100	189	Z
5	0.6013	-31.10	29.22	-1.88	72.03	73.91	100	143	Z
6	0.9725	-31.20	30.02	-1.18	67.85	69.03	100	336	Z


Note:(1)Level=Reading+Factor

(2)Margin=Limit-Level

FOR 30 MHz ~ 1000 MHz

Polarization:

Horizontal

**Final Data List**

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pol
1	38.1238	-10.28	32.39	22.11	80.80	58.69	100	165	Horizontal
2	434.1263	-3.46	76.44	72.98	100.80	27.82	100	1	Horizontal
3	513.0600	-1.71	34.28	32.57	80.80	48.23	100	153	Horizontal
4	687.5388	2.16	38.43	40.59	80.80	40.21	100	135	Horizontal
5	742.5863	3.62	37.21	40.83	80.80	39.97	100	11	Horizontal
6	867.8375	5.75	59.97	65.72	80.80	15.08	100	67	Horizontal


Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level

Spurious Emission of Average

No.	Freq. [MHz]	PK level [dBμV/m]	DCCF [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	38.1238	22.11	-13.03	9.08	60.80	51.72	Horizontal	AV
2	434.1263	72.98	-13.03	59.95	80.80	20.85	Horizontal	AV
3	513.0600	32.57	-13.03	19.54	60.80	41.26	Horizontal	AV
4	687.5388	40.59	-13.03	27.56	60.80	33.24	Horizontal	AV
5	742.5863	40.83	-13.03	27.8	60.80	33.00	Horizontal	AV
6	867.8375	65.72	-13.03	52.69	60.80	8.11	Horizontal	AV

Polarization: Vertical



Final Data List

NO.	Frequency [MHz]	Factor [dB/m]	QP Reading [dBμV/m]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Height [cm]	Angle [°]	Pol
1	85.5325	-14.09	33.12	19.03	80.80	61.77	100	90	Vertical
2	433.8838	-3.46	87.18	83.72	100.80	17.08	100	180	Vertical
3	513.0600	-1.71	37.26	35.55	80.80	45.25	100	163	Vertical
4	687.5388	2.16	35.29	37.45	80.80	43.35	100	175	Vertical
5	742.5863	3.62	38.47	42.09	80.80	38.71	100	132	Vertical
6	867.8375	5.75	41.74	47.49	80.80	33.31	100	78	Vertical

Note: (1) Level = Reading + Factor

(2) Margin = Limit - Level


Spurious Emission of Average

No.	Freq. [MHz]	PK level [dBμV/m]	DCCF [dB]	Level [dBμV/m]	Limit [dBμV/m]	Margin [dB]	Polarity	Detector
1	85.5323	19.03	-13.03	6.00	60.80	54.80	Vertical	AV
2	433.8838	83.72	-13.03	70.69	80.80	10.11	Vertical	AV
3	513.0600	35.22	-13.03	22.19	60.80	38.61	Vertical	AV
4	687.5388	37.45	-13.03	24.42	60.80	36.38	Vertical	AV
5	742.5863	42.09	-13.03	29.06	60.80	31.74	Vertical	AV
6	867.8375	47.49	-13.03	34.46	60.80	26.34	Vertical	AV

FOR 1 GHz ~ 5 GHz

Polarization:

Horizontal




Mark	Frequency MHz	Reading dBuV/m	Antenna dB	Cable dB	Preamp dB	Level dBuV/m	Limit dBuV/m	Over limit	Remark
1	2168.73	56.25	28.15	4.04	41.03	47.41	80.80	-33.39	Peak
2	2605.48	48.57	28.41	4.56	41.00	40.54	80.80	-40.26	Peak
3	3040.80	64.65	29.18	4.71	40.80	57.74	80.80	-23.06	Peak
4	3475.38	53.42	29.40	5.06	40.77	47.11	80.80	-33.69	Peak
5	3908.66	55.91	30.30	5.47	40.50	51.18	74.00	-22.82	Peak
6	4779.68	48.96	32.00	6.13	40.12	46.97	74.00	-27.03	Peak

Spurious Emission of Average

No.	Freq. [MHz]	PK level [dBuV/m]	DCCF [dB]	Level [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Polarity	Detector
1	2168.73	47.41	-13.03	34.38	60.80	26.42	Horizontal	AV
2	2605.48	40.54	-13.03	27.51	60.80	33.29	Horizontal	AV
3	3040.80	57.74	-13.03	44.71	60.80	16.09	Horizontal	AV
4	3475.38	47.11	-13.03	34.08	60.80	26.72	Horizontal	AV
5	3908.66	51.18	-13.03	38.15	54.00	15.85	Horizontal	AV
6	4779.68	46.97	-13.03	33.94	54.00	20.06	Horizontal	AV

Polarization: Vertical




Mark	Frequency MHz	Reading dBUV/m	Antenna dB	Cable dB	Preamp dB	Level dBUV/m	Limit dBUV/m	Over limit	Remark
1	1302.06	59.79	26.00	2.99	41.56	47.22	74.00	-26.78	Peak
2	2605.48	58.99	28.41	4.56	41.00	50.96	80.80	-29.84	Peak
3	3040.80	64.97	29.18	4.71	40.80	58.06	80.80	-22.74	Peak
4	3475.38	55.27	29.40	5.06	40.77	48.96	80.80	-31.84	Peak
5	3908.66	52.90	30.30	5.47	40.50	48.17	74.00	-25.83	Peak
6	4339.71	51.16	30.98	5.89	40.28	47.75	74.00	-26.25	Peak

Spurious Emission of Average								
No.	Freq. [MHz]	PK level [dBUV/m]	DCCF [dB]	Level [dBUV/m]	Limit [dBUV/m]	Margin [dB]	Polarity	Detector
1	1302.06	47.22	-13.03	34.19	54.00	19.81	Vertical	AV
2	2605.48	50.96	-13.03	37.93	60.80	22.87	Vertical	AV
3	3040.80	58.06	-13.03	45.03	60.80	15.77	Vertical	AV
4	3475.38	48.96	-13.03	35.93	60.80	24.87	Vertical	AV
5	3908.66	48.17	-13.03	35.14	54.00	18.86	Vertical	AV
6	4339.71	47.75	-13.03	34.72	54.00	19.28	Vertical	AV

6. TEST SETUP PHOTOS


Radiated Emission







7. EXTERNAL AND INTERNAL PHOTOS

7.1. External Photos




KM278









KM422







KM578








KM579












7.2. Internal Photos




KM278








KM422









KM578





KM579





8. APPENDIX REPORT