

RF Exposure Evaluation of

E.U.T. : Wireless Conference System
Model No. : CS-W4C
Serial Model : ---
FCC ID : INGCS-W4C

for

APPLICANT : JTS Professional Co., Ltd.
ADDRESS : No. 148, Gongye 9th Rd., Tali Dist.,
Taichung City 41280 Taiwan, R.O.C.

Test Performed by

Taiwan Testing and Certification Center

No.34, Dingfu, Linkou Dist., New Taipei City 244, Taiwan (R.O.C.)

TEL : (02)26023052 FAX: (02)26010910

http : // www.etc.org.tw; e-mail : emc@etc.org.tw

Report Number : 19-01-RBF-027-02-MPE

TEST REPORT CERTIFICATION

Applicant : JTS Professional Co., Ltd.
No. 148, Gongye 9th Rd., Dali Dist., Taichung City 41280
Taiwan, R.O.C.

Manufacturer : JTS Professional Co., Ltd.
No. 148, Gongye 9th Rd., Dali Dist., Taichung City 41280
Taiwan, R.O.C.

Description of EUT

- a) Type of EUT : Wireless Conference System
- b) Trade Name : JTS
- c) Model No. : CS-W4C
- d) Serial Model : ---
- e) Power Supply : I/P : 100~240V 0.6A max. 50/60Hz
O/P : 12V 3A
- f) Frequency Range : 2412MHz~2424MHz

Regulation Applied : FCC KDB447498 D01. The equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Note: 1. The result of the testing report relate only to the item tested.

2. The testing report shall not be reproduced expect in full, without the written approval of ETC

Date Test Item Received : 01/19/2019
Date Test Campaign Completed : 09/28/2021
Date of Issue : 11/29/2021

Test Engineer :

Brian Huang
(Brian Huang, Engineer)



Approve & Authorized Signer :

Vincent Chang
Vincent Chang, Supervisor
EMC Dept. II

Product Information:

Type of EUT: Wireless Conference System

FCC ID: INGCS-W4C

Model: CS-W4C

Serial Model:

Description: CS-W4C is designed with JTS newest wireless and conferencing technology of short range device for a wireless microphone system

Maximum Field Strength (measured) : 89.59 dBuV/m

Maximum conducted output power (rated): -5.61 dBm or 0.274 mW

The following table lists the provided authorized antennas:

Model	Antenna Type	Antenna Gain	
		(dBi)	Numeric
N/A	PCB Antenna	3.3	2.13

Note : The Antenna information was declared by manufacturer

Below is an example of the RF Exposure Statement:

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

Relative Requirement for Compliance

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following:

TABLE 1 – LIMITS FOR MAXIMUN PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided. This calculation is based on the highest EIRP possible from the system, considering maximum power and antenna gain, and considering a 1.0 mW/cm² uncontrolled exposure limit. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from page 19 of OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4 \pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

hence

$$R = (PG / 4 \pi S)^{1/2}$$

For our device

P = 0.274 mW

G = 2.13

R = 0.5 cm

S = (0.274 * 2.13) / (4 * π * 0.5²) = **0.185** mW/cm² < 1.0 mW/cm²

For complying the FCC limits for general population/uncontrolled exposure, the power density limit is 1.0 mW/cm². The calculation result of the power density at a distance of 0.5 cm of our device is less than the limit.

This means that according to OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), the equipment fulfills the requirements on power density for general population/uncontrolled exposure and therefore fulfills the requirements of section 1.1310 of FCC 47 CFR Part 1.

Conducted Test Equipment

Equipment	Manufacturer	Model No.	Calibration Date	Next Cal. Date
EMI Test Receiver	Rohde & Schwarz	ESU 40	2021/03/25	2022/03/24
Horn Antenna	EMCO	3115	2020/10/16	2021/10/15
Amplifier	HP	83051A	2021/09/09	2022/09/08

Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Radiated emissions	1GHz ~ 18GHz	$\pm 4.44\text{dB}$ ($1\text{GHz} \leq f \leq 18\text{GHz}$)

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

The test result(s) does not consider the uncertainty of measurement when the test standard(s) and/or test method which refer by the labs has the limit or judgments for the test result(s).