

FCC Test Report

Product Name	KENWOOD Motorsports CAM
Model No	STZ-RF200WD
FCC ID.	IOMZ1059

Applicant	JVCKENWOOD Corporation
Address	3-12 Moriya-cho, Kanagawa-ku, Yokohama.Kanagawa 221-0022, Japan

Date of Receipt	Feb. 20, 2021
Issue Date	Mar. 31, 2021
Report No.	2120401R-E3032110113
Report Version	V1.0



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.

This report must not be used to claim product endorsement by TAF or any agency of the government.

The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test Report


Issue Date: Mar. 31, 2021

Report No.: 2120401R-E3032110113



Product Name	KENWOOD Motorsports CAM
Applicant	JVCKENWOOD Corporation
Address	3-12 Moriya-cho, Kanagawa-ku, Yokohama.Kanagawa 221-0022, Japan
Manufacturer	Altek Corporation
Model No.	STZ-RF200WD
FCC ID.	IOMZ1059
EUT Rated Voltage	DC 12V by Battery
EUT Test Voltage	DC 12V by Battery
Trade Name	JVCKENWOOD
Applicable Standard	FCC CFR Title 47 Part 15 Subpart C ANSI C63.4: 2014, ANSI C63.10: 2013
Test Result	Complied

Documented By :



(Senior Adm. Specialist / Genie Chang)

Tested By :



(Engineer / Yunche Chen)

Approved By :



(Director / Vincent Lin)

TABLE OF CONTENTS

Description	Page
1. GENERAL INFORMATION	6
1.1. EUT Description.....	6
1.2. Tested System Details.....	8
1.3. Configuration of Tested System	8
1.4. EUT Exercise Software	9
1.5. Test Facility	10
1.6. List of Test Item and Equipment	11
1.7. Uncertainty	12
2. Conducted Emission.....	13
2.1. Test Setup	13
2.2. Limits	13
2.3. Test Procedure	13
2.4. Test Result of Conducted Emission.....	14
3. Peak Power Output	15
3.1. Test Setup	15
3.2. Limits	15
3.3. Test Procedure	15
3.4. Test Result of Peak Power Output.....	16
4. Radiated Emission.....	20
4.1. Test Setup	20
4.2. Limits	21
4.3. Test Procedure	22
4.4. Test Result of Radiated Emission.....	24
5. RF antenna conducted test.....	50
5.1. Test Setup	50
5.2. Limits	50
5.3. Test Procedure	50
5.4. Test Result of RF antenna conducted test.....	51
6. Band Edge	55
6.1. Test Setup	55
6.2. Limits	56
6.3. Test Procedure	56
6.4. Test Result of Band Edge	58
7. 6dB Bandwidth	90
7.1. Test Setup	90
7.2. Limits	90
7.3. Test Procedure	90
7.4. Test Result of 6dB Bandwidth.....	91
8. Power Density	99

8.1.	Test Setup	99
8.2.	Limits	99
8.3.	Test Procedure	99
8.4.	Test Result of Power Density	100
9.	Duty Cycle	108
9.1.	Test Setup	108
9.2.	Test Procedure	108
9.3.	Test Result of Duty Cycle.....	109
10.	EMI Reduction Method During Compliance Testing	112
Attachment 1: EUT Test Photographs		
Attachment 2: EUT Detailed Photographs		

Revision History

Report No.	Version	Description	Issued Date
2120401R-E3032110113	V1.0	Initial issue of report.	2021-03-31

1. GENERAL INFORMATION

1.1. EUT Description

Product Name	KENWOOD Motorsports CAM
Trade Name	JVCKENWOOD
Model No.	STZ-RF200WD
FCC ID.	IOMZ1059
Frequency Range	2412-2462MHz for 802.11b/g/n-20BW, 2422-2452MHz for 802.11n-40BW
Number of Channels	802.11b/g/n-20MHz: 11, n-40MHz: 7
Data Speed	802.11b: 1-11Mbps, 802.11g: 6-54Mbps, 802.11n: up to 150Mbps
Channel separation	802.11b/g/n: 5 MHz
Type of Modulation	802.11b:DSSS (DBPSK, DQPSK, CCK) 802.11g/n:OFDM (BPSK, QPSK, 16QAM, 64QAM)
Antenna Type	Ceramic Antenna
Antenna Gain	Refer to the table "Antenna List"
Channel Control	Auto
Camera lens*2	MAR: JVCKENWOOD, M/N: STZ-RFUC, Shielded, 1.4m
SW unit	MAR: JVCKENWOOD, M/N: STZ-RFUS, Shielded, 1.5m
GPS Antenna	MAR: JVCKENWOOD, M/N: STZ-RTUG, Shielded, 1.6m

Antenna List

No.	Manufacturer	Part No.	Antenna Type	Peak Gain
1	PulseLARSEN	W3006	Ceramic Antenna	2.2dBi for 2.4GHz

Note: The antenna of EUT is conforming to FCC 15.203.

802.11b/g/n-20MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 01:	2412 MHz	Channel 02:	2417 MHz	Channel 03:	2422 MHz	Channel 04:	2427 MHz
Channel 05:	2432 MHz	Channel 06:	2437 MHz	Channel 07:	2442 MHz	Channel 08:	2447 MHz
Channel 09:	2452 MHz	Channel 10:	2457 MHz	Channel 11:	2462 MHz		

802.11n-40MHz Center Frequency of Each Channel:

Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
Channel 03:	2422 MHz	Channel 04:	2427 MHz	Channel 05:	2432 MHz	Channel 06:	2437 MHz
Channel 07:	2442 MHz	Channel 08:	2447 MHz	Channel 09:	2452 MHz		

Note:

1. The EUT is a KENWOOD Motorsports CAM with a built-in 2.4 GHz and 5 GHz WLAN transceiver , this report for 2.4GHz WLAN.
2. The radiation measurements are performed in X, Y, Z axis positioning. Only the worst case is shown in the report.
3. Regarding to the operation frequency, the lowest, middle and highest frequency are selected to perform the test.
4. Lowest and highest data rates are tested in each mode. Only worst case is shown in the report. (802.11b is 1Mbps 、802.11g is 6Mbps 、802.11n(20M-BW) is 7.2Mbps and 802.11n(40M-BW) is 15Mbps)
5. These tests are conducted on a sample for the purpose of demonstrating compliance of 802.11b/g/n transmitter with Part 15 Subpart C Paragraph 15.247 of spread spectrum devices.

Test Mode:	Mode 1: Transmit (802.11b 1Mbps)
	Mode 2: Transmit (802.11g 6Mbps)
	Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)
	Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)


1.2. Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

	Product	Manufacturer	Model No.	Serial No.	Power Cord
1	Notebook PC	DELL	Latitude E5440	B6TYTZ1	Non-shielded, 0.8m
2	DC 12V Battery	TRANE	12B50PE	N/A	N/A
3	Camera lens	JVCKENWOOD	STZ-RFUC	N/A	N/A
4	Camera lens	JVCKENWOOD	STZ-RFUC	N/A	N/A
5	SW unit	JVCKENWOOD	STZ-RFUS	N/A	N/A
6	GPS Antenna	JVCKENWOOD	STZ-RTUG	N/A	N/A

Signal Cable Type	Signal cable Description
A USB Cable	Shielded, 0.9m
B Power Cable	Shielded, 0.3m
C Power Cable	Non-shielded, 0.7m
D Signal Cable	Shielded, 0.6m, two PCS.
E Camera lens Cable	Shielded, 1.4m, two PCS.
F Signal Cable	Shielded, 0.5m
G SW unit Cable	Shielded, 1.5m
H Signal Cable	Shielded, 0.4m
I GPS Antenna Cable	Shielded, 1.6m

1.3. Configuration of Tested System



1.4. EUT Exercise Software

1. Setup the EUT as shown in Section 1.3.
2. Execute software “QRCT v3.0.303.0” on the EUT.
3. Configure the test mode, the test channel, and the data rate.
4. Press “OK” to start the continuous Transmit.
5. Verify that the EUT works properly.

1.5. Test Facility

Ambient conditions in the laboratory:

Performed Item	Items	Required	Actual
Radiated Emission	Temperature (°C)	10~40 °C	18.7 °C
	Humidity (%RH)	10~90 %	59.7 %
Conductive	Temperature (°C)	10~40 °C	22 °C
	Humidity (%RH)	10~90 %	55 %

USA : FCC Registration Number: TW0023

Canada : IC Registration Number: 25880

Site Description : Accredited by TAF
Accredited Number: 3023

Test Laboratory : DEKRA Testing and Certification Co., Ltd
Address : No.159, Sec. 2, Wenhua 1st Rd., Linkou Dist.,
New Taipei City 24457, Taiwan, R.O.C.

Phone number : 886-2-2602-7968
Fax number : 866-2-2602-3286
Email address : info.tw@dekra.com
Website : <http://www.dekra.com.tw>

1.6. List of Test Item and Equipment

For Conducted measurements /ASR2

	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
X	Spectrum Analyzer	R&S	FSV30	103466	2020.12.28	2021.12.27
X	Peak Power Analyzer	KEYSIGHT	8900B	MY51000539	2020.05.13	2021.05.12
X	Power Sensor	KEYSIGHT	N1923A	MY59240002	2020.05.22	2021.05.21
X	Power Sensor	KEYSIGHT	N1923A	MY59240003	2020.05.22	2021.05.21

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.
3. Test Software version : DEKRA Conduction Test System V9.0.5.

For Radiated measurements /ACB2

	Equipment	Manufacturer	Model No.	Serial No.	Cali. Data	Due. Data
X	Loop Antenna	AMETEK	HLA6121	56736	2020.03.19	2021.03.18
X	Bi-Log Antenna	SCHWARZBECK	VULB9168	9168-953	2021.01.29	2022.01.28
X	Horn Antenna	ETS-Lindgren	3117	00203800	2020.12.22	2021.12.21
	Horn Antenna	ETS-Lindgren	3117	00203761	2020.11.23	2021.11.22
	Horn Antenna	Com-Power	AH-840	101087	2020.06.08	2021.06.07
X	Pre-Amplifier	EMCI	EMC001330	980316	2020.06.23	2021.06.22
X	Pre-Amplifier	EMCI	EMC051835SE	980311	2020.06.23	2021.06.22
X	Pre-Amplifier	EMCI	EMC05820SE	980310	2020.06.24	2021.06.23
	Pre-Amplifier	EMCI	EMC184045SE	980314	2020.06.10	2021.06.09
X	Filter	MICRO TRONICS	BRM50702	G251	2020.09.17	2021.09.16
	Filter	MICRO TRONICS	BRM50716	G188	2020.09.17	2021.09.16
X	EMI Test Receiver	R&S	ESR7	101601	2020.05.28	2021.05.27
X	Spectrum Analyzer	R&S	FSV40	101148	2020.03.16	2021.03.15
X	Coaxial Cable	SUHNER	SUCOFLEX 106	RF002	2020.07.03	2021.07.02
X	Mircoflex Cable	HUBER SUHNER	SUCOFLEX 102	MY3381/2	2020.06.10	2021.06.09

Note:

1. All equipments are calibrated every one year.
2. The test instruments marked with “X” are used to measure the final test results.
3. Test Software version : DEKRA Testing System V2.0.

1.7. Uncertainty

Uncertainties have been calculated according to the DEKRA internal document, and is described in each test chapter of this report.


The reported expanded uncertainties are based on a standard uncertainty multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Test item	Uncertainty	
Conducted Emission	$\pm 3.42\text{dB}$	
Peak Power Output	$\pm 0.91\text{ dB}$	
Radiated Emission	Under 1GHz $\pm 4.06\text{ dB}$	Above 1GHz $\pm 3.73\text{ dB}$
RF antenna conducted test	$\pm 2.53\text{ dB}$	
Band Edge	Under 1GHz $\pm 4.06\text{ dB}$	Above 1GHz $\pm 3.73\text{ dB}$
6dB Bandwidth	$\pm 682.83\text{ Hz}$	
Power Density	$\pm 2.53\text{ dB}$	
Duty Cycle (2.4GHz)	$\pm 2.31\text{ ms}$	

2. Conducted Emission

2.1. Test Setup



2.2. Limits

FCC Part 15 Subpart C Paragraph 15.207 (dB μ V) Limit		
Frequency MHz	Limits	
	QP	AVG
0.15 - 0.50	66-56	56-46
0.50-5.0	56	46
5.0 - 30	60	50

2.3. Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm /50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2014 on conducted measurement.


Conducted emissions were investigated over the frequency range from 0.15MHz to 30MHz using a receiver bandwidth of 9kHz.

2.4. Test Result of Conducted Emission

Owing to the EUT use DC supply voltage, this test item is not performed.

3. Peak Power Output

3.1. Test Setup



3.2. Limits

The maximum peak power shall be less 1 Watt.

3.3. Test Procedure

The EUT was tested according to C63.10:2013 for compliance to FCC 47CFR 15.247 requirements. The maximum peak conducted output power using C63.10:2013 Section 11.9.1.3 PKPM1 Peak power meter method. The maximum average conducted output power using C63.10:2013 Section 11.9.2.3 Measurement using a power meter (PM). (Measurement using a gated RF average-reading power meter).

3.4. Test Result of Peak Power Output

Product : KENWOOD Motorsports CAM
 Test Item : Peak Power Output Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)
 Test Date : 2021/03/15

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)				Peak Power	Required Limit	Result
		1	2	5.5	11	1		
		Measurement Level (dBm)						
01	2412	15.78	--	--	--	18.27	<30dBm	Pass
06	2437	15.84	15.8	15.75	15.69	18.42	<30dBm	Pass
11	2462	15.57	--	--	--	18.22	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : KENWOOD Motorsports CAM
 Test Item : Peak Power Output Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)
 Test Date : 2021/03/15

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		6	9	12	18	24	36	48	54	6		
		Measurement Level (dBm)										
01	2412	13.55	--	--	--	--	--	--	--	20.47	<30dBm	Pass
06	2437	13.72	13.68	13.64	13.59	13.55	13.51	13.47	13.42	21.48	<30dBm	Pass
11	2462	13.66	--	--	--	--	--	--	--	21.36	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : KENWOOD Motorsports CAM
 Test Item : Peak Power Output Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)
 Test Date : 2021/03/15

Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		7.2	14.4	21.7	28.9	43.3	57.8	65	72.2	7.2		
		Measurement Level (dBm)										
01	2412	11.52	--	--	--	--	--	--	--	19.76	<30dBm	Pass
06	2437	11.68	11.63	11.58	11.54	11.5	11.46	11.41	11.37	19.95	<30dBm	Pass
11	2462	11.71	--	--	--	--	--	--	--	19.98	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss

Product : KENWOOD Motorsports CAM
 Test Item : Peak Power Output Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)
 Test Date : 2021/03/15


Channel No	Frequency (MHz)	Average Power For different Data Rate (Mbps)								Peak Power	Required Limit	Result
		15	30	45	60	90	120	135	150			
		Measurement Level (dBm)										
03	2422	11.75	--	--	--	--	--	--	--	19.52	<30dBm	Pass
06	2437	11.68	11.64	11.6	11.55	11.5	11.44	11.4	11.35	19.5	<30dBm	Pass
09	2452	11.66	--	--	--	--	--	--	--	19.48	<30dBm	Pass

Note: Peak Power Output Value = Reading value on power meter + cable loss


4. Radiated Emission

4.1. Test Setup


Radiated Emission Under 30MHz



Radiated Emission Below 1GHz



Radiated Emission Above 1GHz



4.2. Limits

➤ General Radiated Emission Limits

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20dB below the level of the fundamental or to the general radiated emission limits in paragraph 15.209, whichever is the lesser attenuation.

FCC Part 15 Subpart C Paragraph 15.209 Limits		
Frequency MHz	Field strength (microvolts/meter)	Measurement distance (meter)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

- Remarks:
1. RF Voltage (dBuV) = 20 log RF Voltage (uV)
 2. In the Above Table, the tighter limit applies at the band edges.
 3. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.

4.3. Test Procedure

The EUT was setup according to ANSI C63.10: 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

Measuring the frequency range below 1GHz, the EUT is placed on a turn table which is 0.8 meter above ground, when measuring the frequency range above 1GHz, the EUT is placed on a turn table which is 1.5 meter above ground.

The turn table is rotated 360 degrees to determine the position of the maximum emission level.

The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned between 1 meter and 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10: 2013 on radiated measurement.

The resolution bandwidth below 30MHz setting on the field strength meter is 9kHz and 30MHz~1GHz is 120kHz and above 1GHz is 1MHz.

Radiated emission measurements below 30MHz are made using Loop Antenna and 30MHz~1GHz are made using broadband Bilog antenna and above 1GHz are made using Horn Antennas.

The measurement is divided into the Preliminary Measurement and the Final Measurement.

The suspected frequencies are searched for in Preliminary Measurement with the measurement antenna kept pointed at the source of the emission both in azimuth and elevation, with the polarization of the antenna oriented for maximum response. The antenna is pointed at an angle towards the source of the emission, and the EUT is rotated in both height and polarization to maximize the measured emission. The emission is kept within the illumination area of the 3 dB bandwidth of the antenna. The measurement frequency range from 9kHz - 10th Harmonic of fundamental was investigated.

RBW and VBW Parameter setting:

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

$VBW \geq 3 \times RBW$.

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1MHz.

VBW = 10Hz, when duty cycle $\geq 98\%$

$VBW \geq 1/T$, when duty cycle $< 98\%$

(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)


2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	97.59	8.2319	121	200
802.11g	87.50	1.3696	730	1k
802.11n20	86.70	1.2754	784	1k
802.11n40	76.17	0.6391	1565	2k

Note: Duty Cycle Refer to Section 9

4.4. Test Result of Radiated Emission

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	44.12	74.00	-29.88	45.29	-1.17	PK
2	7236.000	46.83	74.00	-27.17	44.86	1.97	PK
* 3	9648.000	47.13	74.00	-26.87	43.05	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	45.27	74.00	-28.73	46.44	-1.17	PK
2	7236.000	46.26	74.00	-27.74	44.29	1.97	PK
* 3	9648.000	46.74	74.00	-27.26	42.66	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	42.85	74.00	-31.15	44.10	-1.25	PK
2	7311.000	45.52	74.00	-28.48	43.55	1.97	PK
* 3	9748.000	46.63	74.00	-27.37	42.37	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2437 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	42.98	74.00	-31.02	44.23	-1.25	PK
2	7311.000	45.44	74.00	-28.56	43.47	1.97	PK
* 3	9748.000	47.61	74.00	-26.39	43.35	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.56	74.00	-31.44	43.78	-1.22	PK
2	7386.000	44.48	74.00	-29.52	42.45	2.03	PK
* 3	9848.000	45.92	74.00	-28.08	41.70	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.86	74.00	-31.14	44.08	-1.22	PK
2	7386.000	45.03	74.00	-28.97	43.00	2.03	PK
* 3	9848.000	46.53	74.00	-27.47	42.31	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	43.38	74.00	-30.62	44.55	-1.17	PK
2	7236.000	45.74	74.00	-28.26	43.77	1.97	PK
* 3	9648.000	46.34	74.00	-27.66	42.26	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	42.71	74.00	-31.29	43.88	-1.17	PK
2	7236.000	45.56	74.00	-28.44	43.59	1.97	PK
* 3	9648.000	47.38	74.00	-26.62	43.30	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	42.52	74.00	-31.48	43.77	-1.25	PK
2	7311.000	45.34	74.00	-28.66	43.37	1.97	PK
* 3	9748.000	46.79	74.00	-27.21	42.53	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2437 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	42.43	74.00	-31.57	43.68	-1.25	PK
2	7311.000	45.91	74.00	-28.09	43.94	1.97	PK
* 3	9748.000	47.37	74.00	-26.63	43.11	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.25	74.00	-31.75	43.47	-1.22	PK
2	7386.000	44.66	74.00	-29.34	42.63	2.03	PK
* 3	9848.000	45.87	74.00	-28.13	41.65	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.80	74.00	-31.20	44.02	-1.22	PK
2	7386.000	45.12	74.00	-28.88	43.09	2.03	PK
* 3	9848.000	46.37	74.00	-27.63	42.15	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	42.93	74.00	-31.07	44.10	-1.17	PK
* 2	7236.000	46.14	74.00	-27.86	44.17	1.97	PK
3	9648.000	45.95	74.00	-28.05	41.87	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4824.000	46.13	74.00	-27.87	47.30	-1.17	PK
2	7236.000	45.86	74.00	-28.14	43.89	1.97	PK
* 3	9648.000	46.42	74.00	-27.58	42.34	4.08	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	46.19	74.00	-27.81	47.44	-1.25	PK
2	7311.000	45.46	74.00	-28.54	43.49	1.97	PK
* 3	9748.000	47.26	74.00	-26.74	43.00	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2437 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	43.37	74.00	-30.63	44.62	-1.25	PK
2	7311.000	45.43	74.00	-28.57	43.46	1.97	PK
* 3	9748.000	47.24	74.00	-26.76	42.98	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.78	74.00	-31.22	44.00	-1.22	PK
2	7386.000	44.48	74.00	-29.52	42.45	2.03	PK
* 3	9848.000	45.93	74.00	-28.07	41.71	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4924.000	42.55	74.00	-31.45	43.77	-1.22	PK
2	7386.000	44.99	74.00	-29.01	42.96	2.03	PK
* 3	9848.000	46.88	74.00	-27.12	42.66	4.22	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4844.000	43.53	74.00	-30.47	44.76	-1.23	PK
* 2	7266.000	46.36	74.00	-27.64	44.31	2.05	PK
3	9688.000	46.21	74.00	-27.79	42.11	4.10	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4844.000	43.18	74.00	-30.82	44.41	-1.23	PK
2	7266.000	45.84	74.00	-28.16	43.79	2.05	PK
* 3	9688.000	46.49	74.00	-27.51	42.39	4.10	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2437 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
* 1	4874.000	47.20	74.00	-26.80	48.45	-1.25	PK
2	7311.000	45.37	74.00	-28.63	43.40	1.97	PK
3	9748.000	46.87	74.00	-27.13	42.61	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2437 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4874.000	42.40	74.00	-31.60	43.65	-1.25	PK
2	7311.000	45.53	74.00	-28.47	43.56	1.97	PK
* 3	9748.000	47.09	74.00	-26.91	42.83	4.26	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452 MHz)
 Test Date : 2021/03/11

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4904.000	42.55	74.00	-31.45	43.86	-1.31	PK
2	7356.000	45.27	74.00	-28.73	43.34	1.93	PK
* 3	9808.000	46.25	74.00	-27.75	42.00	4.25	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : Harmonic Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452 MHz)
 Test Date : 2021/03/11

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	4904.000	42.30	74.00	-31.70	43.61	-1.31	PK
2	7356.000	45.21	74.00	-28.79	43.28	1.93	PK
* 3	9808.000	46.84	74.00	-27.16	42.59	4.25	PK

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The average measurement was not performed when the peak measured data under the limit of average detection.
5. The emission levels of other frequencies are very lower than the limit and not show in test report.

Product : KENWOOD Motorsports CAM
 Test Item : General Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)(2437 MHz)
 Test Date : 2021/03/24

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	42.652	27.43	40.00	-12.57	37.89	-10.46	QP
2	209.942	30.56	43.50	-12.94	43.68	-13.12	QP
3	280.232	29.07	46.00	-16.93	39.27	-10.20	QP
4	422.217	30.78	46.00	-15.22	37.52	-6.74	QP
* 5	491.101	37.07	46.00	-8.93	42.67	-5.60	QP
6	631.681	33.16	46.00	-12.84	36.08	-2.92	QP

Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. No emission found between lowest internal used/generated frequency to 30MHz.

Product : KENWOOD Motorsports CAM
 Test Item : General Radiated Emission Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)(2437 MHz)
 Test Date : 2021/03/24

Vertical



No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
* 1	49.681	29.13	40.00	-10.87	39.39	-10.26	QP
2	253.522	29.85	46.00	-16.15	41.17	-11.32	QP
3	422.217	28.72	46.00	-17.28	35.46	-6.74	QP
4	492.507	33.18	46.00	-12.82	38.75	-5.57	QP
5	633.087	30.78	46.00	-15.22	33.67	-2.89	QP
6	843.957	33.11	46.00	-12.89	33.00	0.11	QP


Note:

1. All Readings below 1GHz are Quasi-Peak, above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.
3. Correct Factor = Antenna factor + Cable loss – Amplifier gain.
4. The emission levels of other frequencies are very lower than the limit and not show in test report.
5. No emission found between lowest internal used/generated frequency to 30MHz.

5. RF antenna conducted test

5.1. Test Setup

RF antenna Conducted Measurement:



5.2. Limits

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

5.3. Test Procedure


The EUT was tested according to C63.10:2013 Section 11.11 for compliance to FCC 47CFR 15.247 requirements.

Set RBW = 100 kHz, Set VBW > RBW, scan up through 10th harmonic.


5.4. Test Result of RF antenna conducted test

Product : KENWOOD Motorsports CAM
Test Item : RF antenna conducted test
Test Mode : Mode 1: Transmit (802.11b 1Mbps)
Test Date : 2021/03/15


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : KENWOOD Motorsports CAM
Test Item : RF Antenna Conducted Spurious
Test Mode : Mode 2: Transmit (802.11g 6Mbps)
Test Date : 2021/03/15


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : KENWOOD Motorsports CAM
Test Item : RF Antenna Conducted Spurious
Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)
Test Date : 2021/03/15


Channel 01 (2412MHz)



Channel 06 (2437MHz)




Channel 11 (2462MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

Product : KENWOOD Motorsports CAM
Test Item : RF Antenna Conducted Spurious
Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)
Test Date : 2021/03/15


Channel 03 (2422MHz)



Channel 06 (2437MHz)



Channel 09 (2452MHz)




Note: The above test pattern is synthesized by multiple of the frequency range.

6. Band Edge


6.1. Test Setup

RF Conducted Measurement



RF Radiated Measurement:

Above 1GHz



6.2. Limits

According to FCC Section 15.247(d). In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

6.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013 and tested according to C63.10:2013 Section 11.12.1 for compliance to FCC 47CFR 15.247 requirements.

The EUT is placed on a turn table which is 1.5 meter above ground. The turn table is rotated 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 3 meters.

The antenna is scanned from 1 meter to 4 meters to find out the maximum emission level. This is repeated for both horizontal and vertical polarization of the antenna. In order to find the maximum emission, all of the interface cables were manipulated according to ANSI C63.10:2013 on radiated measurement.

RBW and VBW Parameter setting:

According to C63.10 Section 11.12.2.4 Peak measurement procedure.

RBW = as specified in Table 1.

$VBW \geq 3 \times RBW$.

Table 1 —RBW as a function of frequency

Frequency	RBW
9-150 kHz	200-300 Hz
0.15-30 MHz	9-10 kHz
30-1000 MHz	100-120 kHz
> 1000 MHz	1 MHz

According to C63.10 Section 11.12.2.5 Average measurement procedure.

RBW = 1MHz.

VBW = 10Hz, when duty cycle $\geq 98 \%$

$VBW \geq 1/T$, when duty cycle $< 98 \%$

(T refers to the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.)


2.4GHz band	Duty Cycle (%)	T (ms)	1/T (Hz)	VBW (Hz)
802.11b	97.59	8.2319	121	200
802.11g	87.50	1.3696	730	1k
802.11n20	86.70	1.2754	784	1k
802.11n40	76.17	0.6391	1565	2k

Note: Duty Cycle Refer to Section 9

6.4. Test Result of Band Edge

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/10

Horizontal




Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2387.391	35.62	54.00	-18.38	24.39	11.23	AV
2	2390.000	35.15	54.00	-18.85	23.92	11.23	AV
! 3	2397.536	60.56	--	--	49.34	11.22	AV
! 4	2400.000	54.19	--	--	42.97	11.22	AV
! 5	2411.304	100.13	--	--	88.86	11.27	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/10

Vertical




Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2412MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2387.246	34.98	54.00	-19.02	23.75	11.23	AV
2	2390.000	34.68	54.00	-19.32	23.45	11.23	AV
! 3	2397.826	59.42	--	--	48.20	11.22	AV
4	2400.000	52.74	--	--	41.52	11.22	AV
! 5	2411.304	99.03	--	--	87.76	11.27	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2460.746	104.75	--	--	93.42	11.33	PK
2	2483.500	49.85	74.00	-24.15	38.47	11.38	PK
3	2486.688	52.11	74.00	-21.89	40.73	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2461.181	100.96	--	--	89.63	11.33	AV
2	2483.500	37.87	54.00	-16.13	26.49	11.38	AV
3	2486.254	42.76	54.00	-11.24	31.38	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2460.746	102.32	--	--	90.99	11.33	PK
2	2483.500	48.67	74.00	-25.33	37.29	11.38	PK
3	2485.964	51.01	74.00	-22.99	39.63	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2461.181	98.55	--	--	87.22	11.33	AV
2	2483.500	36.71	54.00	-17.29	25.33	11.38	AV
3	2486.399	40.40	54.00	-13.60	29.02	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	63.27	74.00	-10.73	52.04	11.23	PK
! 2	2399.130	82.48	--	--	71.26	11.22	PK
! 3	2400.000	81.37	--	--	70.15	11.22	PK
! 4	2419.130	105.61	--	--	94.37	11.24	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	44.78	54.00	-9.22	33.55	11.23	AV
! 2	2400.000	64.45	--	--	53.23	11.22	AV
! 3	2419.130	95.36	--	--	84.12	11.24	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	61.23	74.00	-12.77	50.00	11.23	PK
! 2	2399.420	78.44	--	--	67.22	11.22	PK
! 3	2400.000	77.75	--	--	66.53	11.22	PK
! 4	2418.986	102.67	--	--	91.43	11.24	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2412MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	42.42	54.00	-11.58	31.19	11.23	AV
! 2	2400.000	61.91	--	--	50.69	11.22	AV
! 3	2419.420	92.66	--	--	81.42	11.24	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2455.529	105.67	--	--	94.34	11.33	PK
2	2483.500	66.66	74.00	-7.34	55.28	11.38	PK
3	2483.935	67.31	74.00	-6.69	55.93	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2455.239	94.57	--	--	83.24	11.33	AV
2	2483.500	47.07	54.00	-6.93	35.69	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2456.833	103.32	--	--	91.99	11.33	PK
2	2483.500	66.34	74.00	-7.66	54.96	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2457.703	92.56	--	--	81.22	11.34	AV
2	2483.500	45.81	54.00	-8.19	34.43	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	63.73	74.00	-10.27	52.50	11.23	PK
! 2	2399.130	80.72	--	--	69.50	11.22	PK
! 3	2400.000	78.66	--	--	67.44	11.22	PK
! 4	2419.130	104.60	--	--	93.36	11.24	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	44.56	54.00	-9.44	33.33	11.23	AV
! 2	2400.000	62.40	--	--	51.18	11.22	AV
! 3	2419.130	94.18	--	--	82.94	11.24	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	61.93	74.00	-12.07	50.70	11.23	PK
! 2	2398.696	76.97	--	--	65.75	11.22	PK
! 3	2400.000	76.62	--	--	65.40	11.22	PK
! 4	2419.130	101.53	--	--	90.29	11.24	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2412MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	43.10	54.00	-10.90	31.87	11.23	AV
! 2	2400.000	59.52	--	--	48.30	11.22	AV
! 3	2419.710	91.31	--	--	80.07	11.24	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2456.109	104.03	--	--	92.70	11.33	PK
2	2483.500	65.73	74.00	-8.27	54.35	11.38	PK
3	2484.080	66.56	74.00	-7.44	55.18	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2457.123	92.95	--	--	81.62	11.33	AV
2	2483.500	46.02	54.00	-7.98	34.64	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2455.384	102.05	--	--	90.72	11.33	PK
2	2483.500	63.65	74.00	-10.35	52.27	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW) (2462MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2457.558	90.78	--	--	79.44	11.34	AV
2	2483.500	45.32	54.00	-8.68	33.94	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/10

Horizontal




Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	43.67	54.00	-10.33	32.44	11.23	AV
! 2	2400.000	55.76	--	--	44.54	11.22	AV
! 3	2427.681	90.06	--	--	78.79	11.27	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	53.93	74.00	-20.07	42.70	11.23	PK
2	2400.000	70.94	--	--	59.72	11.22	PK
! 3	2426.087	97.67	--	--	86.41	11.26	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2422MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
1	2390.000	39.83	54.00	-14.17	28.60	11.23	AV
2	2400.000	52.30	--	--	41.08	11.22	AV
! 3	2427.536	86.48	--	--	75.21	11.27	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2456.833	101.18	--	--	89.85	11.33	PK
2	2483.500	66.25	74.00	-7.75	54.87	11.38	PK
3	2484.080	68.56	74.00	-5.44	57.18	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452MHz)
 Test Date : 2021/03/10

Horizontal




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2450.312	89.33	--	--	78.03	11.30	AV
2	2483.500	52.23	54.00	-1.77	40.85	11.38	AV

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2458.428	97.14	--	--	85.80	11.34	PK
2	2483.500	59.64	74.00	-14.36	48.26	11.38	PK
3	2485.529	60.85	74.00	-13.15	49.47	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

Product : KENWOOD Motorsports CAM
 Test Item : Band Edge Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW) (2452MHz)
 Test Date : 2021/03/10

Vertical




No	Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Reading Level (dBuV)	Correct Factor (dB)	Detector Type
! 1	2454.804	85.95	--	--	74.62	11.33	PK
2	2483.500	46.85	74.00	-27.15	35.47	11.38	PK

Note:

1. All readings above 1GHz are performed with peak and/or average measurements as necessary.
2. Emission Level = Reading Level + Correct Factor.

7. 6dB Bandwidth

7.1. Test Setup



7.2. Limits

The minimum bandwidth shall be at least 500 kHz.

7.3. Test Procedure

The EUT was setup according to ANSI C63.4, 2014; tested according to ANSI C63.10 Section 11.8 for compliance to FCC 47CFR 15.247 requirements.

7.4. Test Result of 6dB Bandwidth

Product : KENWOOD Motorsports CAM
 Test Item : 6dB Bandwidth Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	8700	>500	Pass
06	2437	8650	>500	Pass
11	2462	8200	>500	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : 6dB Bandwidth Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	16450	>500	Pass
06	2437	16400	>500	Pass
11	2462	16400	>500	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : 6dB Bandwidth Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
01	2412	17650	>500	Pass
06	2437	17450	>500	Pass
11	2462	17650	>500	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : 6dB Bandwidth Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)

Channel No.	Frequency (MHz)	Measurement Level (kHz)	Required Limit (kHz)	Result
03	2422	35300	>500	Pass
06	2437	35300	>500	Pass
09	2452	35500	>500	Pass

Figure Channel 03:




Figure Channel 06:






Figure Channel 09:



8. Power Density

8.1. Test Setup



8.2. Limits

The transmitted power density averaged over any 1 second interval shall not be greater +8dBm in any 3kHz bandwidth.

8.3. Test Procedure

The EUT was setup according to ANSI C63.10, 2013; tested according to DTS test procedure of KDB 558074 for compliance to FCC 47CFR 15.247 requirements.

The maximum power spectral density using C63.10 Section 11.10.2 Method PKPSD (peak PSD)

8.4. Test Result of Power Density

Product : KENWOOD Motorsports CAM
 Test Item : Power Density Data
 Test Mode : Mode 1: Transmit (802.11b 1Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	7.59	$\leq 8\text{dBm}$	Pass
06	2437	7.92	$\leq 8\text{dBm}$	Pass
11	2462	7.85	$\leq 8\text{dBm}$	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : Power Density Data
 Test Mode : Mode 2: Transmit (802.11g 6Mbps)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	3.05	$\leq 8\text{dBm}$	Pass
06	2437	3.47	$\leq 8\text{dBm}$	Pass
11	2462	2.93	$\leq 8\text{dBm}$	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : Power Density Data
 Test Mode : Mode 3: Transmit (802.11n MCS0 7.2Mbps 20M-BW)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
01	2412	2.28	$\leq 8\text{dBm}$	Pass
06	2437	1.63	$\leq 8\text{dBm}$	Pass
11	2462	1.09	$\leq 8\text{dBm}$	Pass

Figure Channel 01:




Figure Channel 06:





Figure Channel 11:



Product : KENWOOD Motorsports CAM
 Test Item : Power Density Data
 Test Mode : Mode 4: Transmit (802.11n MCS0 15Mbps 40M-BW)

Channel No.	Frequency (MHz)	Measure Level (dBm)	Limit (dBm)	Result
03	2422	-1.48	≤ 8 dBm	Pass
06	2437	-1.08	≤ 8 dBm	Pass
09	2452	-1.54	≤ 8 dBm	Pass

Figure Channel 03:




Figure Channel 06:






Figure Channel 09:



9. Duty Cycle

9.1. Test Setup



9.2. Test Procedure

The EUT was setup according to ANSI C63.10 2013; tested according to ANSI C63.10 2013 for compliance to FCC 47CFR 15.247 requirements.

9.3. Test Result of Duty Cycle

Product : KENWOOD Motorsports CAM
 Test Item : Duty Cycle
 Test Mode : Transmit

Duty Cycle Formula:


Duty Cycle = Ton / (Ton + Toff)

Duty Factor = 10 Log (1/Duty Cycle)

Results:


2.4GHz band	Ton (ms)	Ton + Toff (ms)	Duty Cycle (%)	Duty Factor (dB)
802.11b	8.2319	8.4348	97.59	0.11
802.11g	1.3696	1.5652	87.50	0.58
802.11n20	1.2754	1.4710	86.70	0.62
802.11n40	0.6391	0.8391	76.17	1.18

802.11b




Date: 10.MAR.2021 23:28:56

802.11g




Date: 10.MAR.2021 23:31:11

802.11n20



Date: 10.MAR.2021 23:34:05

802.11n40



Date: 10. MAR. 2021 23:38:58

10. EMI Reduction Method During Compliance Testing

No modification was made during testing.