



FCC / ISED Test Report

For:
Garmin International, Inc.

Model Name:
A03675

Product Description:
N/A

FCC ID: IPH-03675
IC ID: 1792A-03675

Applied Rules and Standards:
47 CFR Part 15.247 (DTS)
RSS-247 Issue 2 (DTSs) & RSS-Gen Issue 5

REPORT #: EMC_GARMI-064-19001_15.247_BTLE_DTS_REV4

DATE: 2020-05-18



A2LA Accredited

IC recognized #
3462B-1,2

CETECOM Inc.

411 Dixon Landing Road ♦ Milpitas, CA 95035 ♦ U.S.A.

Phone: + 1 (408) 586 6200 ♦ Fax: + 1 (408) 586 6299 ♦ E-mail: info@cetecom.com ♦ <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2905571

TABLE OF CONTENTS

1	ASSESSMENT.....	3
2	ADMINISTRATIVE DATA	4
2.1	IDENTIFICATION OF THE TESTING LABORATORY ISSUING THE EMC TEST REPORT	4
2.2	IDENTIFICATION OF THE CLIENT	4
2.3	IDENTIFICATION OF THE MANUFACTURER.....	4
3	EQUIPMENT UNDER TEST (EUT).....	5
3.1	EUT SPECIFICATIONS	5
3.2	EUT SAMPLE DETAILS	6
3.3	ACCESSORY EQUIPMENT (AE) DETAILS.....	6
3.4	TEST SAMPLE CONFIGURATION	6
3.5	JUSTIFICATION FOR WORST CASE MODE OF OPERATION.....	7
4	SUBJECT OF INVESTIGATION	8
5	MEASUREMENT RESULTS SUMMARY	8
6	MEASUREMENT UNCERTAINTY.....	9
6.1	ENVIRONMENTAL CONDITIONS DURING TESTING:.....	9
6.2	DATES OF TESTING:	9
7	MEASUREMENT PROCEDURES	10
7.1	RADIATED MEASUREMENT.....	10
7.2	POWER LINE CONDUCTED MEASUREMENT PROCEDURE	12
7.3	RF CONDUCTED MEASUREMENT PROCEDURE	12
8	TEST RESULT DATA	13
8.1	MAXIMUM PEAK CONDUCTED OUTPUT POWER.....	13
8.2	POWER SPECTRAL DENSITY	17
8.3	DUTY CYCLE.....	21
8.4	BAND EDGE COMPLIANCE	22
8.5	EMISSION BANDWIDTH 6dB AND 99% OCCUPIED BANDWIDTH.....	27
8.6	RADIATED TRANSMITTER SPURIOUS EMISSIONS AND RESTRICTED BANDS	34
9	TEST SETUP PHOTOS	47
10	TEST EQUIPMENT AND ANCILLARIES USED FOR TESTING	47
11	HISTORY	48

1 Assessment

The following device was evaluated against the applicable criteria specified in FCC rules Parts 15.247 of Title 47 of the Code of Federal Regulations and the relevant ISED Canada standard RSS-247.

No deviations were ascertained.

Company	Description	Model #
Garmin International Inc.	N/A	A03675

Responsible for Testing Laboratory:

2020-05-18	Compliance	Cindy Li (EMC Lab Manager)	 Digitally signed by cindy.li@cetecom.com DN: CN=Cindy Li, email=cindy.li@cetecom.com Reason: I am approving this document Location: Date: 2020-05-21 16:10:43
Date	Section	Name	Signature

Responsible for the Report:

2020-05-18	Compliance	Chin Ming Lui (Associate EMC Engineer)	Chin Ming Lui  Digitally signed by: Chin Ming Lui DN: CN = Chin Ming Lui email = chinming.lui@cetecom.com C = US O = CETECOM Date: 2020.05.18 17:02:12 - 07'00'
Date	Section	Name	Signature

The test results of this test report relate exclusively to the test item specified in Section 3.

CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2 Administrative Data

2.1 Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Street Address:	411 Dixon Landing Road
City/Zip Code	Milpitas, CA 95035
Country	USA
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
EMC Lab Manager:	Cindy Li
Responsible Project Leader:	Sangeetha Sivaraman

2.2 Identification of the Client

Client's Name:	Garmin International, Inc.
Street Address:	1200 East 151 st Street
City/Zip Code	Olathe, KS 66062
Country	USA
Contact Person:	Jeff Hailey
Phone No.	(913) 440-1592
e-mail:	Jeffrey.Hailey@garmin.com

2.3 Identification of the Manufacturer

Manufacturer's Name:	Same as Client /-----
Manufacturers Address:	-----
City/Zip Code	-----
Country	-----

3 Equipment Under Test (EUT)

3.1 EUT Specifications

Model No:	A03675
HW Version :	1
SW Version :	1.20
FCC-ID :	IPH-03675
IC-ID:	1792A-03675
FWIN:	N/A
HVIN:	A03675
PMN:	N/A
Product Description:	N/A
Frequency Range / number of channels:	Nominal band: 2400 MHz – 2483.5 MHz; Center to center: 2402 MHz (ch 0) – 2480 MHz (ch 39), 40 channels
Radio Information:	<u>Bluetooth:</u> • Module Name: Nordic Semiconductor • Module Number: nRF51422 • Modulation: Bluetooth version 4.0 Low Energy
Antenna Information as declared:	<u>Main Antenna:</u> • Type: Printed-Circuit Inverted F Antenna (PIFA) • Location: Internal • Maximum Gain: 4 dBi
Max. Peak Output Power:	Conducted Power: 2.95 dBm
Power Supply/ Rated Operating Voltage Range:	Vmin: 10 VDC/ Vnom: 12 VDC / Vmax: 32 VDC
Operating Temperature Range	-15°C to 55 °C
Other Radios included in the device:	Cellular; GPS; WiFi; ANT
Sample Revision Note 1	☐ Prototype Unit; ☐ Production Unit; ☒ Pre-Production

Note 1: Pre-production PCB has a new communication circuit that was made functional using wire mods.
 From a radio perspective the units tested are production quality per client communication.

3.2 EUT Sample details

EUT #	Serial Number	HW Version	SW Version	Notes/Comments
1	Test Unit C	1	1.20	Conducted RF
2	Test Unit D	1	1.20	Radiated

3.3 Accessory Equipment (AE) details

N/A

3.4 Test Sample Configuration

EUT Set-up #	Combination of AE used for test set up	Comments
1	EUT#1	<u>Conducted Setup:</u> The radio of the EUT was configured using the “Factory Test” software: • Modulation: BLE Modulate Test • Channel (Fixed): ○ Ch. 0 (Low, 2402 MHz) ○ Ch. 20 (Mid, 2442 MHz) ○ Ch. 39 (High, 2480 MHz) The “Factory Test” software will not available to the end user. The power was controlled through software updated by the client. The latest software was used for the measurements. The measurement equipment was connected to the 50 ohm RF port of the EUT.
2	EUT#2	<u>Radiated Setup:</u> The radio of the EUT was configured using the “Factory Test” software: • Modulation: BLE Modulate Test • Channel (Fixed): ○ Ch. 0 (Low, 2402 MHz) ○ Ch. 20 (Mid, 2442 MHz) ○ Ch. 39 (High, 2480 MHz) The “Factory Test” software will not available to the end user. The power was controlled through software updated by the client. The latest software was used for the measurements. The internal antenna was connected.

3.5 Justification for Worst Case Mode of Operation

During the testing process, the EUT was tested with transmitter set on low, mid, and high channels. For radiated measurements, all data in this report shows the worst case between horizontal and vertical antenna polarizations and for all orientations of the EUT.

4 Subject of Investigation

The objective of the measurements done by CETECOM Inc. was to assess the performance of the EUT according to the relevant requirements specified in FCC rules Part 15.247 of Title 47 of the Code of Federal Regulations and Radio Standard Specification RSS-247 of ISED Canada.

This test report is to support a request for new equipment authorization under the FCC ID: IPH-03675 IC ID: 1792A-03675

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.

5 Measurement Results Summary

Test Specification	Test Case	Temperature and Voltage Conditions	Mode	Pass	NA	NP	Result
§15.247(a)(1) RSS-247 5.2(a)	Emission Bandwidth	Nominal	BTLE	■	□	□	Complies
§15.247(e) RSS-247 5.2(b)	Power Spectral Density	Nominal	BTLE	■	□	□	Complies
§15.247(b)(1) RSS-247 5.4(d)	Maximum Conducted Output Power and EIRP	Nominal	BTLE	■	□	□	Complies
§15.247(d) RSS-247 5.5	Band edge compliance Unrestricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247; 15.209; 15.205 RSS-Gen 8.9; 8.10	Band edge compliance Restricted Band Edges	Nominal	BTLE	■	□	□	Complies
§15.247(d); §15.209 RSS-Gen 6.13	TX Spurious emissions- Radiated	Nominal	BTLE	■	□	□	Complies
§15.207(a) RSS Gen 8.8	AC Conducted Emissions	Nominal	BTLE	□	□	■	N/A

Note: NA= Not Applicable; NP= Not Performed.

6 **Measurement Uncertainty**

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus, with 95% confidence interval (in dB delta to result), based on a coverage factor $k=1$.

Radiated measurement

9 kHz to 30 MHz	± 2.5 dB (Magnetic Loop Antenna)
30 MHz to 1000 MHz	± 2.0 dB (Biconilog Antenna)
1 GHz to 40 GHz	± 2.3 dB (Horn Antenna)

Conducted measurement

150 kHz to 30 MHz	± 0.7 dB (LISN)
-------------------	---------------------

RF conducted measurement	± 0.5 dB
--------------------------	--------------

According to TR 102 273 a multiplicative propagation of error is assumed for RF measurement systems. For this reason the RMS method is applied to dB values and not to linear values as appropriate for additive propagation of error.

6.1 **Environmental Conditions During Testing:**

The following environmental conditions were maintained during the course of testing:

- Ambient Temperature: 20-25° C
- Relative humidity: 40-60%

6.2 **Dates of Testing:**


12/12/2019 – 03/06/2020

7 Measurement Procedures


7.1 Radiated Measurement

The radiated measurement is performed according to ANSI C63.10 (2013)


- The exploratory measurement is accomplished by running a matrix of 16 sweeps over the required frequency range with R&S Test-SW EMC32 for 4 positions of the turntable, two orthogonal positions of the EUT and both antenna polarizations. This procedure exceeds the requirement of the above standards to cover the 3 orthogonal axis of the EUT. A max peak detector is utilized during the exploratory measurement. The Test-SW creates an overall maximum trace for all 12 sweeps and saves the settings for each point of this trace. The maximum trace is part of the test report.
- The 10 highest emissions are selected with an automatic algorithm of EMC32 searching for peaks in the noise floor and ensuring that broadband signals are not selected multiple times.
- The maxima are then put through the final measurement and again maximized in a 90deg range of the turntable, fine search in frequency domain and height scan between 1m and 4m.
- The above procedure is repeated for all possible ways of power supply to EUT and for all supported modulations.
- In case there are no emissions above noise floor level only the maximum trace is reported as described above.
- The results are split up into up to 4 frequency ranges due to antenna bandwidth restrictions. A magnetic loop is used from 9 kHz to 30 MHz, a Biconilog antenna is used from 30 MHz to 1 GHz, and two different horn antennas are used to cover frequencies up to 40 GHz.



Radiated Emissions Test Setup 30MHz-1GHz Measurements



Radiated Emissions Test Setup above 1GHz Measurements



7.1.1 Sample Calculations for Field Strength Measurements

Field Strength is calculated from the Spectrum Analyzer/ Receiver readings, taking into account the following parameters:

1. Measured reading in dB μ V
2. Cable Loss between the receiving antenna and SA in dB and
3. Antenna Factor in dB/m

All radiated measurement plots in this report are taken from a test SW that calculates the Field Strength based on the following equation:

$$FS \text{ (dB}\mu\text{V/m)} = \text{Measured Value on SA (dB}\mu\text{V)} + \text{Cable Loss (dB)} + \text{Antenna Factor (dB/m)}$$

Example:


Frequency (MHz)	Measured SA (dB μ V)	Cable Loss (dB)	Antenna Factor Correction (dB)	Field Strength Result (dB μ V/m)
1000	80.5	3.5	14	98.0

7.2 Power Line Conducted Measurement Procedure

AC Power Line conducted emissions measurements performed according to: ANSI C63.4 (2014)

7.3 RF Conducted Measurement Procedure

Testing procedures are based on 558074 D01 15.247 Meas Guidance v05r02 – “GUIDANCE FOR COMPLIANCE MEASUREMENTS ON DIGITAL TRANSMISSION SYSTEM, FREQUENCY HOPPING SPREAD SPECTRUM SYSTEM, AND HYBRID SYSTEM DEVICES OPERATING UNDER SECTION 15.247 OF THE FCC RULES” - April 2, 2019, by the Federal Communications Commission, Office of Engineering and Technology, Laboratory Division.



- Connect the equipment as shown in the above diagram.
- Adjust the settings of the SA (Rohde-Schwarz Spectrum Analyzer) to connect the EUT at the required mode of test.
- Measurements are to be performed with the EUT set to the low, middle and high channels and for worst case modulation schemes.

8 Test Result Data

8.1 Maximum Peak Conducted Output Power

8.1.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

- $RBW \geq DTS \text{ bandwidth}$
- $VBW \geq 3 \times RBW$
- $Span \geq 3 \times RBW$
- Sweep = Auto couple
- Detector function = Peak
- Trace = Max hold
- Use peak marker function to determine the peak amplitude level

8.1.2 Limits:

Maximum Peak Output Power:

- FCC §15.247 (b)(1): 1 W
- IC RSS-247: 1 W


8.1.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
23.8°C	1	Bluetooth LE	12 VDC	4 dBi


8.1.4 Measurement result:

Plot #	Frequency (MHz)	Maximum Peak Conducted Output Power (dBm)	EIRP (dBm)	Limit (dBm)	Result
1	2402	2.95	6.95	30 (Pk) / 36 (EIRP)	Pass
2	2442	2.72	6.72	30 (Pk) / 36 (EIRP)	Pass
3	2480	1.90	5.90	30 (Pk) / 36 (EIRP)	Pass

8.1.5 Measurement Plots:







8.2 Power Spectral Density

8.2.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings for Peak PSD method:

- Set analyzer center frequency to DTS channel center frequency
- Set the span to 1.5 x DTS bandwidth
- Set RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$
- Set the VBW $\geq 3 \times \text{RBW}$
- Detector = Peak
- Sweep time = Auto couple
- Trace mode = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level within the RBW
- If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat

8.2.2 Limits:

FCC§15.247(e) & RSS-247 5.2(2)

- For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.


8.2.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
23.8°C	1	Bluetooth LE	12 VDC	4 dBi


8.2.4 Measurement result:

Plot #	Frequency (MHz)	Maximum Power Spectral Density (dBm/3 kHz)	Limit (dBm / 3 kHz)	Result
1	2402	-9.53	8	Pass
2	2442	-11.75	8	Pass
3	2480	-11.16	8	Pass

8.2.5 Measurement Plots:








8.3 Duty cycle

8.3.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

- Set the center frequency and of the instrument to the center frequency of the transmission
- Zero span
- Set RBW $\geq$ OBW if possible; otherwise, set RBW to the largest available value
- Detector = Peak or average

8.3.2 Measurement result



Test Mode Duty cycle = 69.8%

Duty cycle correction factor = $10 \cdot \log(1/0.698) = 1.56$ dB

8.4 Band Edge Compliance

8.4.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings for band edge:

- Set the center frequency and span to encompass frequency range to be measured
- RBW = 100 kHz
- VBW $\geq 3 \times$ RBW
- Sweep Time: Auto couple
- Detector = Peak
- Trace = Max hold
- Allow trace to fully stabilize
- Use the peak marker function to determine the maximum amplitude level
- Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge

8.4.2 Limits non restricted band:

FCC§15.247 (d)

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 5/5

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30dB instead of 20dB.

Spectrum Analyzer settings for restricted band:

- Peak measurements are made using a peak detector and RBW=1 MHz

8.4.3 Limits restricted band §15.247/15.209/15.205 and RSS-Gen 8.9/8.10

- *PEAK LIMIT= 74 dBμV/m @3m =-21.23 dBm
- *AVG. LIMIT= 54 dBμV/m @3m =-41.23 dBm
- Start frequency & stop frequency according to frequency range specified in the restricted band table in FCC section 15.205 & RSS-Gen 8.10
- Measurements with a peak detector were used to show compliance to average limits, thus showing compliance to both peak and average limits.

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

8.4.4 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input	Antenna Gain
23.8°C	1	Bluetooth LE	12 VDC	4 dBi


8.4.5 Measurement result:


Plot #	EUT operating mode	Band Edge	Band Edge Delta (dBc)	Limit (dBc)	Result
1	Bluetooth LE	Lower, Non-restricted	45.62	20	Pass


Plot #	EUT operating mode	Band Edge	Measured Peak Value (dBm)	Corrected by duty cycle (dB) ^{Note}	Corrected by Antenna Gain (dBm)	Limit (dBm)	Result
2	Bluetooth LE	Upper Restricted Peak	-39.54	NA due to peak detector, and trace max hold	-35.54	-21.23 Peak	Pass
3	Bluetooth LE	Upper Restricted AVG	-58.99	1.56	-53.43	-41.23 AVG	Pass

Note: EUT operating at 69.8% Duty Cycle

8.4.6 Measurement Plots:







8.5 Emission Bandwidth 6dB and 99% Occupied Bandwidth

8.5.1 Measurement according to FCC 558074 D01 15.247 Meas Guidance v05r02

Spectrum Analyzer settings:

- Set RBW = 100 kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

8.5.2 Limits:

FCC §15.247(a)(1) and RSS-247 5.2(1)

- Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

8.5.3 Test conditions and setup:


Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23.8°C	1	Bluetooth LE	12 VDC


8.5.4 Measurement result:


Plot #	Frequency (MHz)	6dB Emissions Bandwidth (MHz)	Limit (MHz)	Result
1	2402	0.68109	> 0.5	Pass
2	2442	0.69712	> 0.5	Pass
3	2480	0.68910	> 0.5	Pass


Plot #	Frequency (MHz)	99% Occupied Bandwidth (MHz)	Limit (MHz)	Result
4	2402	1.0577	> 0.5	Pass
5	2442	1.0577	> 0.5	Pass
6	2480	1.0577	> 0.5	Pass


8.5.5 Measurement Plots:














8.6 Radiated Transmitter Spurious Emissions and Restricted Bands

8.6.1 Measurement according to ANSI C63.10 (2013)

Spectrum Analyzer Settings:

- Frequency = 9 KHz – 30 MHz
- RBW = 9 KHz
- Detector: Peak

- Frequency = 30 MHz – 1 GHz
- Detector = Peak / Quasi-Peak
- RBW= 120 KHz (<1GHz)

- Frequency > 1 GHz
- Detector = Peak / Average
- RBW = 1 MHz

- Radiated spurious emissions shall be measured for the transmit frequencies, transmit power, and data rate for the lowest, middle and highest channel in each frequency band of operation and for the highest gain antenna for each antenna type, and using the appropriate parameters and test requirements.
- The highest (or worst-case) data rate shall be recorded for each measurement.
- For testing at distance other than the specified in the standard, the limit conversion is calculated by using 40 dB/decade extrapolation factor as follow: Conversion factor (CF) = $40 \log (D/d) = 40 \log (300m / 3m) = 80dB$

8.6.2 Limits:

FCC §15.247

- In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

FCC §15.209 & RSS-Gen 8.9

- Except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency of emission (MHz)	Field strength (μV/m)	Measurement Distance (m)	Field strength @ 3m (dBμV/m)
0.009–0.490	2400/F(kHz) / -----	300	-
0.490–1.705	24000/F(kHz) / -----	30	-
1.705–30.0	30 / (29.5)	30	-
30–88	100	3	40 dBμV/m
88–216	150	3	43.5 dBμV/m
216–960	200	3	46 dBμV/m
Above 960	500	3	54 dBμV/m

FCC §15.205 & RSS-Gen 8.10

- Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
10.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	Above 38.6
13.36-13.41			

- Radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

*PEAK LIMIT= 74 dBμV/m

*AVG. LIMIT= 54 dBμV/m


8.6.3 Test conditions and setup:

Ambient Temperature	EUT Set-Up #	EUT operating mode	Power Input
23.8° C	2	Bluetooth LE	12 VDC

8.6.4 Measurement result:

Plot #	Channel #	Scan Frequency	Limit	Result
1-3	Low	30 MHz – 18 GHz	See section 8.5.2	Pass
4-8	Mid	9 kHz – 26 GHz	See section 8.5.2	Pass
9-11	High	30 MHz – 18 GHz	See section 8.5.2	Pass

8.6.5 Measurement Plots:



Plot #2 Radiated Emissions: 1-3 GHz

Modulation: BT LE


Channel: Low

69.8% Duty Cycle


Final Result


Frequency (MHz)	MaxPeak (dBμV/m)	RMS (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)
2331.995	58.948	---	73.99	15.05	300.0	1000.000	234.0	H	286.0	6.4	-21.5
2331.995	---	37.543	53.98	16.44	300.0	1000.000	234.0	H	286.0	6.4	-21.5
2387.970	59.758	---	73.99	14.24	300.0	1000.000	142.0	H	236.0	6.6	-21.3
2387.970	---	38.469	53.98	15.51	300.0	1000.000	142.0	H	236.0	6.6	-21.3

Frequency (MHz)	Preamplifier (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)	Comment
2331.995	0.0	27.9	52.6	3:17:48 PM - 3/6/2020
2331.995	0.0	27.9	31.1	3:17:48 PM - 3/6/2020
2387.970	0.0	28.0	53.1	3:14:41 PM - 3/6/2020
2387.970	0.0	28.0	31.8	3:14:41 PM - 3/6/2020



— Preview Result 1-PK+
--- FCC 15C AVG
* Critical_Freqs PK+
◆ Final_Result PK+
◆ Final_Result RMS
— FCC 15C PK





Plot #5 Radiated Emissions: 30 MHz – 1GHz


Modulation: BT LE

Channel: Mid


69.8% Duty Cycle


Final Result


Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
285.904	38.50	46.02	7.52	200.0	120.000	140.0	H	188.0	14.2
354.918	41.10	46.02	4.92	200.0	120.000	140.0	H	224.0	17.5
364.768	37.51	46.02	8.51	200.0	120.000	214.0	V	3.0	17.8
374.639	39.37	46.02	6.65	200.0	120.000	212.0	V	12.0	17.6
384.497	42.43	46.02	3.60	200.0	120.000	194.0	V	26.0	18.4
394.338	35.90	46.02	10.12	200.0	120.000	199.0	V	17.0	18.3



— Preview Result 1-PK+ — FCC 15 ◆ Final_Result QPK







Plot #9 Radiated Emissions: 30 MHz – 1GHz


Modulation: BT LE

Channel: High

69.8% Duty Cycle

Final Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
345.046	38.44	46.02	7.58	200.0	120.000	152.0	H	210.0	17.1
354.908	40.05	46.02	5.97	200.0	120.000	151.0	H	216.0	17.5
374.626	40.23	46.02	5.79	200.0	120.000	226.0	V	17.0	17.6
384.471	42.79	46.02	3.23	200.0	120.000	217.0	V	8.0	18.4
394.336	35.19	46.02	10.83	200.0	120.000	177.0	V	22.0	18.3
414.052	35.71	46.02	10.31	200.0	120.000	323.0	V	240.0	18.0



Plot #10 Radiated Emissions: 1-3 GHz

Modulation: BT LE


Channel: High

69.8% Duty Cycle


Final Result

Frequency (MHz)	MaxPeak (dBμV/m)	RMS (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)	Sig Path (dB)
2508.115	63.680	---	73.99	10.31	300.0	1000.000	305.0	H	277.0	7.0	-21.1
2508.115	---	43.246	53.98	10.73	300.0	1000.000	305.0	H	277.0	7.0	-21.1
2576.970	63.535	---	73.99	10.46	300.0	1000.000	138.0	H	268.0	7.1	-21.3
2576.970	---	41.454	53.98	12.53	300.0	1000.000	138.0	H	268.0	7.1	-21.3

Frequency (MHz)	Preamp (dB)	Trd Corr. (dB/m)	Raw Rec (dBμV)	Comment
2508.115	0.0	28.1	56.7	3:41:18 PM - 3/6/2020
2508.115	0.0	28.1	36.3	3:41:18 PM - 3/6/2020
2576.970	0.0	28.3	56.5	3:38:19 PM - 3/6/2020
2576.970	0.0	28.3	34.4	3:38:20 PM - 3/6/2020



— Preview Result 1-PK+
 * Critical_Freqs PK+
 — FCC 15C PK
--- FCC 15C AVG
 ◆ Final_Result PK+
 ◆ Final_Result RMS



9 Test setup photos

Setup photos are included in supporting file name: "EMC_GARMI-064-19001_15.247_BTLE_DTS_Setup_Photos.pdf"

10 Test Equipment And Ancillaries Used For Testing

Equipment Type	Manufacturer	Model	Serial #	Calibration Cycle	Last Calibration Date
Loop Antenna	ETS Lindgren	6507	161344	3 years	10/26/2017
Biconlog Antenna	ETS Lindgren	3142E	166067	3 years	06/27/2017
Horn Antenna	ETS Lindgren	3115	35111	3 years	04/17/2019
Horn Antenna	ETS Lindgren	3117-PA	169547	3 years	08/08/2017
Horn Antenna	ETS Lindgren	3116C-PA	169535	3 years	09/24/2017
EMI Receiver	R&S	ESU40	100251	3 years	07/16/2019
Signal Analyzer	R&S	FSV40	101022	3 years	07/15/2019
Spectrum Analyzer	R&S	FSU26	200065	3 years	07/16/2019
Thermometer Humidity Monitor	Control Company	36934-164	181230565	2 years	04/27/2018
Thermometer Humidity Monitor	Control Company	36934-164	191871994	2 years	01/10/2019

Note: Equipment used meets the measurement uncertainty requirements as required per applicable standards for 95% confidence levels. Calibration due dates, unless defined specifically, falls on the last day of the month. Items indicated "N/A" for cal status either do not specifically require calibration or is internally characterized before use.

11 History

Date	Report Name	Changes to report	Report prepared by
2020-04-16	EMC_GARMI-064-19001_15.247_BTLE_DTS	Initial Version	Chin Ming Lui
2020-04-20	EMC_GARMI-064-19001_15.247_BTLE_DTS_REV1	Modified sample revision note for pre-production PCB from N2K to communication circuit	Chin Ming Lui
2020-05-06	EMC_GARMI-064-19001_15.247_BTLE_DTS_REV2	Updated test sample configuration, and radio & antenna information	Chin Ming Lui
2020-05-11	EMC_GARMI-064-19001_15.247_BTLE_DTS_REV3	Updated EUT SW version from Test Rev 7 to 1.20	Chin Ming Lui
2020-05-18	EMC_GARMI-064-19001_15.247_BTLE_DTS_REV4	Updated test sample configuration by adding power control through SW	Chin Ming Lui

<<< The End >>>