



FCC LISTED, REGISTRATION
NUMBER: 2764.01

ISED LISTED REGISTRATION
NUMBER: 23595-1

Test report No:

3428ERM.008

Test report

FCC Rules and Regulations CFR 47, Part 15, Subpart B (10-1-20 Edition)
&
ICES-003 ISSUE 7 – October (2020)

(*) Identification of item tested	Infotainment Head Unit
(*) Trademark	Garmin
(*) Model and /or type reference tested	IDC23 High 8155
Other identification of the product	FCC ID: IPH-03911 IC:1792A-03911
(*) Features	Bluetooth classic; BLE; Wi-Fi 2.4GHz; Wi-Fi 5GHz; GNSS
Manufacturer	GARMIN INTERNATIONAL, INC. 1200 E. 151st Street, Olathe, Kansas 66062, USA
Test method requested, standard	FCC Rules and Regulations CFR 47, Part 15, Subpart B (10-1-20 Edition) ICES-003 ISSUE 7 – October (2020)
Summary	IN COMPLIANCE
Approved by (name / position & signature)	Domingo Galvez EMC&RF Lab Manager 
Date of issue	07-28-2022
Report template No	FDT08_23 (*) "Data provided by the client"

Digitally signed by Domingo Galvez
DN: cn=Domingo Galvez,
o=DEKRA Certification Inc.,
ou=Regulatory Lab,
email=dgalvez@dekra.com,
c=US
Date: 2022.07.28 19:47:07 -04'00'

Index

Competences and guarantees3

General conditions3

Uncertainty3

Data provided by the client.....4

Usage of samples4

Test sample description5

Identification of the client.....6

Testing period and place6

Document history6

Environmental conditions7

Remarks and comments7

Testing verdicts.....8

Summary8

List of equipment used during the test.....9

Appendix A: Test results10

Competences and guarantees

DEKRA Certification Inc. is a testing laboratory accredited by A2LA (The American Association for Laboratory Accreditation), to perform the tests indicated in the Certificate 2764.01

DEKRA Certification Inc. is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA Certification Inc. has a calibration and maintenance program for its measurement equipment.

DEKRA Certification Inc. guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated on the report and, it is based on the knowledge and technical facilities available at DEKRA Certification at the time of performance of the test.

DEKRA Certification Inc. is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA Certification Inc.

General conditions

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA Certification Inc.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA Certification Inc. and the Accreditation Bodies.

Uncertainty

Uncertainty (factor $k=2$) was calculated according to the DEKRA Certification internal document PODT000.

	Frequency (MHz)	U (k=2)	Units
Radiated emission	30 - 1000	5.94	dB
	1000-18000	5.89	dB

Data provided by the client

The sample consists of an Infotainment Head Unit. The main functionalities are: Navigation, USB, voice recognition and several interfaces to the vehicle and Bluetooth / WLAN. The Head-unit provides different interfaces like: AR-CAM input, Video-out APIX3 (for the connection of an external Display), 3 USB interfaces.

DEKRA declines any responsibility with respect to the information provided by the client and that may affect the validity of results.

Usage of samples

Samples used for test have been selected by **The Client**.

Sample S/01 is composed of the following elements:

Control N°	Description	Model	Serial N°	Date of reception
3428/04	Infotainment Head Unit	IDC23 High 8155	GAB443N0001134	03/16/2022
2874/05	Harness	-	-	03/26/2021
2874/73	Antenna port cable with SMA connectors	-	-	10/22/2021
3171/18	GPS Antenna	Taoglas- Magma AA.171	171TT20120060	03/12/2021

Sample S/01 is composed of the following accessories:

Control N°	Description	Model	Serial N°	Date of reception
2874/70	Automotive Ethernet Adapter	Rad Moon	13401	10/18/2021

Sample S/01, was used for the following test(s): Radiated emission test indicated in appendix A.

Test sample description

Ports..... :	Port name and description		Cable								
			Specified length [m]	Attached during test	Shielded	Coupled to patient					
	BT/Wifi Antenna		2	☒	☐	☐					
	USB1/2		2	☒	☐	☐					
	Power		2	☒	☐	☐					
	CID		2	☒	☐	☐					
	AR-Cam		2	☒	☐	☐					
	100 Base T1/1G Base T1/GPS/DCS/HUD/DFE		2	☒	☐	☐					
Supplementary information to the ports..... :	N/A										
Rated power supply	Voltage and Frequency		Reference poles								
			L1	L2	L3	N PE					
	☐	AC:	☐	☐	☐	☐					
	☐	AC:	☐	☐	☐	☐					
	☒	DC: 8 - 16 Vdc									
	☐	DC:									
Rated Power	No Data Provided										
Clock frequencies.....	No Data Provided										
Other parameters	No Data Provided										
Software version	STS 21w24.4-1-41-072221-1409										
Hardware version	1.5.2										
Dimensions in cm (W x H x D)	No Data Provided										
Mounting position	☐	Table top equipment									
	☐	Wall/Ceiling mounted equipment									
	☐	Floor standing equipment									
	☐	Hand-held equipment									
	☒	Other: Automotive									
Modules/parts..... :	Module/parts of test item		Type		Manufacturer						
	N/A										

Copy of marking plate:



Garmin International, Inc.
1200 E. 151st Street, Olathe, Kansas 66062, USA

Report number	Date	Description
3428ERM 008	07-28-2022	First release

Environmental conditions

In the control chamber, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the semi-anechoic chamber, the following limits were not exceeded during the test.

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 75 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

In the chamber for conducted measurements, the following limits were not exceeded during the test:

Temperature	Min. = 15 °C Max. = 35 °C
Relative humidity	Min. = 30 % Max. = 60 %
Air pressure	Min. = 860 mbar Max. = 1060 mbar

Remarks and comments

1. The tests have been performed by the technical personnel: Koji Nishimoto, Nasir Khan and Lourdes Valverde.

Testing verdicts

Not applicable :	N/A
Pass :	P
Fail :	F
Not measured :	N/M

Summary

Emission Test			
Report Section	Requirement – Test case	Verdict	Remark
A.1	Radiated emission test (30 MHz – 1000 MHz)	P	N/A
A.1	Radiated emission test (1 GHz – 18 GHz)	P	N/A
A.1	Radiated emission test (18 GHz – 40 GHz)	P	N/A
-	Conducted emission test (150 kHz to 30 MHz)	N/A	Refer 1
<u>Supplementary information and remarks:</u> 1) According with the requirements of FCC Rules and Regulations, title 47, Chapter I, Subchapter A, Part 15, Subpart B, §15.107 Conducted limits, (d) Measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation, and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines. Devices that include, or make provision for, the use of battery chargers which permit operating while charging, AC adaptors or battery eliminators or that connect to the AC power lines indirectly, obtaining their power through another device which is connected to the AC power lines, shall be tested to demonstrate compliance with the conducted limits.			

List of equipment used during the test

Radiated Emission Equipment

Control Number	Description	Manufacturer	Model	Last Calibration	Next Calibration
981	RF pre-amplifier 1-18 GHz	Bonn Elektronik	BLMA 0118-2A	2020/11	2022/11
1012	ESR26 EMI Test Receiver	Rohde & Schwarz	ESR26	2022/04	2024/02
1056	Double-ridge Waveguide Horn antenna	ETS Lindgren	3116C	2020/01	2023/01
1057	Double-ridge Waveguide Horn antenna	ETS Lindgren	3115	2020/06	2023/06
1064	Biconical log Antenna	ETS Lindgren	3142E	2021/12	2024/12
1108	Ethernet SNMP Thermometer- CR Room	HW Group	HWg-STE Plain	2020/08	2022/08
1111	Ethernet SNMP Thermometer- SAC	HW Group	HWg-STE Plain	2020/08	2022/08
1179	Semi-Anechoic Chamber	Frankonia	SAC 3plus 'L'	N/A	N/A
1217	Frankonia Transparent Test Table 1	Frankonia	FFT-Square	N/A	N/A
1314	Wireless measurement software EMC 32	Rohde & Schwarz	-	N/A	N/A

Appendix A: Test results

Appendix A Content

DESCRIPTION OF THE OPERATION MODES.....12

A.1. RADIATED EMISSION ELECTROMAGNETIC FIELD13

DESCRIPTION OF THE OPERATION MODES

The operation modes described in this paragraph represent functionalities of the sample under test.

The following operation modes of the samples were used during the test executions:

OPERATION MODE	DESCRIPTION
OM#01*	DUT ON. Power supply 12 Vdc. Wi-Fi and BT in IDLE mode. GPS in RX mode.

* Worst case observed

A.1. RADIATED EMISSION ELECTROMAGNETIC FIELD

LIMITS:	Product standard:	FCC CFR 47, Part 15, Subpart B (10-1-20 Edition), Secs. 15.109 & ICES-003 Issue 7 – October (2020)
	Test standard:	FCC CFR 47, Part 15, Subpart B (10-1-20 Edition), Secs. 15.109 & ICES-003 Issue 7 – October (2020); ANSI C63.4 (2014)

Limits of interference Class B

The applied limit for radiated emissions, 3 m distance, in the frequency range 30 MHz to 40 GHz for class B equipment, according with the requirements of:

FCC Rules and Regulations 47 CFR Part 15, Subpart B, Secs. 15.109 (a) (10-01-20 Edition).

Frequency range (MHz)	QP Limit for 3 m	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30 to 88	100	40
88 to 216	150	43.5
216 to 960	200	46
Above 960	500	54

Frequency range (MHz)	AVG Limit for 3 m		PK Limit for 3 m (1) (dB $\mu\text{V/m}$)
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)	
Above 1000	500	54	74

(1) Frequencies above 1 GHz, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test, as per §15.35(b)

ICES-003 Issue 7, Secs 3.2.2, table 2 & 4 (October 2020).

Frequency range (MHz)	QP Limit for 3 m	
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)
30 to 88	100	40
88 to 216	150	43.5
216 to 230	200	46
230 to 960	224	47
Above 960	500	54

Frequency range (MHz)	AVG Limit for 3 m		PK Limit for 3 m (1) (dB $\mu\text{V/m}$)
	($\mu\text{V/m}$)	(dB $\mu\text{V/m}$)	
Above 1000	500	54	74

TEST SETUP

All radiated tests were performed in a semi-anechoic chamber. The measurement antenna is situated at a distance of 3 m for the frequency range 30-1000 MHz (Bilog antenna) and 1-18 GHz (Double ridge horn antenna). and at a distance of 1m for the frequency range 18-40 GHz (18-40 GHz Double ridge horn antenna).

For radiated emissions in the range 18-40 GHz that is performed at a distance closer than the specified distance, an inverse proportionality factor of 20 dB per decade is used to normalize the measured data for determining compliance.

The equipment under test was set up on a non-conductive platform above the ground plane and the situation and orientation was varied to find the maximum radiated emission. It was also rotated 360° and the antenna height was varied from 1 to 4 meters to find the maximum radiated emission.

Measurements were made in both horizontal and vertical planes of polarization.

The field strength is calculated by adding correction factor to the measured level from the spectrum analyzer. This correction factor includes antenna factor, cable loss and pre-amplifiers gain.

TEST SETUP (CONT.)




Fig A1: Generic setup for measurements from 30 to 1000 MHz




Fig A2: Generic setup for measurements from 1 to 18 GHz





Fig A3: Generic setup for measurements from 18 to 40 GHz

TESTED SAMPLES:	S/01
TESTED CONDITIONS MODES:	OM#01
TEST RESULTS:	CRmmnnxx: CR: Radiation Condition, mm: Sample number, nn: Operation mode, xx: Frequency Range

CRmmnnxx	Description	Result
CR0101LR	Range: 30 - 1000 MHz Horizontal and Vertical Polarization	P
CR0101HR1	Range: 1 - 18 GHz Horizontal and Vertical Polarization	P
CR0101HR2	Range: 18 - 40 GHz Horizontal and Vertical Polarization	P

TEST RESULTS (Cont.):

CR0101LR




- Preview Result 1-PK+
- ICES-003 Class B Radiated emissions limit QP+AV
- Final_Result QPK
- Final_Result PK+
- FCC Part 15 Class B Electric Field Strength QP+AV

Frequency (MHz)	QuasiPeak (dBμV/m)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
75.928507	17.60	22.99	40.00	22.40	114.0	V	89.0
114.971516	20.04	25.43	40.00	19.96	122.0	V	-22.0
240.004938	20.79	30.43	46.00	25.21	100.0	V	-54.0
374.980552	32.59	36.78	46.00	13.41	148.0	H	178.0
825.011022	37.96	43.16	46.00	8.04	155.0	H	167.0
875.014696	34.01	41.90	46.00	11.99	115.0	H	-103.0

TEST RESULTS (Cont.):

CR0101HR1




- Preview Result 2-AVG
- Preview Result 1-PK+
- FCC Part 15 Class B Electric Field Strength PK
- FCC Part 15 Class B Electric Field Strength QP+AV
- Final_Result PK+
- Final_Result AVG

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)
1499.700000	38.52	---	73.90	35.38	100.0	V	-49.0
1499.800000	---	21.64	53.90	32.26	148.0	V	23.0
1538.000000	35.22	---	73.90	38.68	126.0	H	-21.0
2995.200000	36.01	---	73.90	37.89	192.0	V	-82.0
2995.300000	---	22.49	53.90	31.41	100.0	V	73.0
17949.800000	---	53.59	53.90	0.31	114.0	V	-69.0

TEST RESULTS (Cont.):

CR0101HR2



- AVG_MAXH
- PK+_MAXH
- FCC Part 15 Class B Electric Field Strength PK
- FCC Part 15 Class B Electric Field Strength QP+AV

Frequency (MHz)	PK+_MAXH (dBμV/m)	AVG_MAXH (dBμV/m)	Pol	Margin - AVG (dB)	Limit - AVG (dBμV/m)
39989.000000	48.6	39.1	V	14.8	53.9