

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Rd.
Lenexa, KS 66214
Phone / Fax (913) 660-0666

47CFR Paragraph 15.247 FHSS
Application For Grant of Certification
HVIN: GMN-03000

2402-2480 MHz (FHSS)
Frequency Hopping Spread Spectrum
License Exempt Intentional Radiator
FCC ID: IPH-04286

Garmin International, Inc.

1200 East 151st Street
Olathe, KS 66062

Test Report Number: 250128
Test Date: January 28, 2025 – April 4, 2025

Authorized Signatory: 

Patrick Powell
Rogers Labs, a division of The Compatibility Center LLC
FCC Designation: US5305
ISED Registration: 3041A

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS.....	2
REVISIONS.....	4
EXECUTIVE SUMMARY	5
OPINION / INTERPRETATION OF RESULTS	5
EQUIPMENT TESTED.....	8
Equipment Operational Modes.....	9
Equipment Function	10
Equipment Configuration.....	11
APPLICATION FOR CERTIFICATION.....	12
APPLICABLE STANDARDS.....	13
TEST PROCEDURES.....	14
AC Line Conducted Emission Test Procedure	14
Radiated Emission Procedure	14
Antenna Port Conducted Emission Test Procedure.....	14
Diagram 1 Test arrangement for power-line conducted emissions.....	15
Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	16
Diagram 3 Test arrangement for radiated emissions tested in Semi-Anechoic Chamber (SAC) and Outdoor Area Test Site (OATS)	17
Diagram 4 Test arrangement for Antenna Port Conducted emissions.....	18
TEST SITE LOCATIONS	18
UNITS OF MEASUREMENTS	19
ENVIRONMENTAL CONDITIONS.....	19
STATEMENT OF MODIFICATIONS AND DEVIATIONS	20
INTENTIONAL RADIATORS.....	20

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Road

Lenexa, KS 66214

Phone: (913) 660-0666

Revision 3

HVIN: GMN-03000

Test #: 250128

Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc

FCC ID: IPH-04286

SN: 78F000511 & 78F000512

Date: July 9, 2025

Page 2 of 46

Antenna Requirements	20
Restricted Bands of Operation	20
Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1, BT BR (GFSK)	21
Summary of Results for Radiated Emissions in Restricted Bands	21
AC Line Conducted EMI Procedure	22
General Radiated Emissions Procedure	23
Table 2 General Radiated Emissions Data – Worst Case (Horizontal Polarization)	23
Figure 1 Plot of General Radiated Emissions – Horizontal Polarization	24
Table 3 General Radiated Emissions Data – Worst Case (Vertical Polarization)	24
Figure 2 Plot of General Radiated Emissions – Vertical Polarization	25
Summary of Results for General Radiated Emissions	25
Operation in the Band 2400 – 2483.5 MHz	26
Figure 3 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1, BT BR	28
Figure 4 Plot of Transmitter Emissions 20-dB Occupied Bandwidth Mode 1, BT BR	29
Figure 5 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1, BT BR	30
Figure 6 Plot of Number of Hopping Channels Mode 1, BT BR	31
Figure 7 Plot of Number of Hopping Channels Mode 1, BT BR	32
Figure 8 Plot of Number of Hopping Channels Mode 1, BT BR	33
Figure 9 Plot of Number of Hopping Channels Mode 1, BT BR	34
Figure 10 Plot of Channel Separation Mode 1, BT BR	35
Figure 11 Plot of Dwell time On Channel Mode 1, BT BR	36
Figure 12 Plot of Number of Times on Channel over 10 Second Period Mode 1, BT BR	37
Figure 13 Plot of Transmitter Emissions Low Band Edge Mode 1, BT BR	38
Figure 14 Plot of Transmitter Emissions High Band Edge Mode 1, BT BR	39
Transmitter Emissions Data	40
Table 4 Transmitter Radiated Emissions Mode 1, BT BR	40
Table 5 Transmitter Antenna Port Conducted Data Mode 1, BT BR	41
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator	41
ANNEX	42
Annex A Measurement Uncertainty Calculations	43

Rogers Labs, a division of The Compatibility Center LLC 7915 Nieman Road Lenexa, KS 66214 Phone: (913) 660-0666 Revision 3	HVIN: GMN-03000 Test #: 250128 Test to: 47CFR 15C File: GMN-03000 FCC DSS TstRpt 250128 r3	Garmin International, Inc FCC ID: IPH-04286 SN: 78F000511 & 78F000512 Date: July 9, 2025 Page 3 of 46
--	---	---

Annex B Test Equipment.....44

Annex C Laboratory Certificate of Accreditation.....46

Revisions

- Revision 1 Issued May 20, 2025 – Initial Formal Release
- Revision 2 Issued May 25, 2025 – Incorporated internal review findings.
- Revision 3 Issued July 9, 2025 – Incorporated external review findings.

Executive Summary

License Exempt Digital Transmission System Intentional Radiator operating under Title 47 of the Code of Federal Regulations (47CFR) Paragraph 15.247 and Industry Canada RSS-247 Issue 3 and RSS-GEN Issue 5, Frequency Hopping Spread Spectrum (FHSS) or Direct Sequence Spread Spectrum (DSS) transmitter operations in the 2400-2483.5 MHz frequency band.

Name of Applicant: Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

HVIN: GMN-03000

FCC ID: IPH-04286

Operating Frequency Range: 2402-2480 MHz

GMN-03000 was chosen for transmitter configuration testing and used for final measurements.

Mode	Antenna Port Conducted Power Watts	99% OBW (kHz)	20-dB OBW (kHz)
Mode 1, BT BR (GFSK)	0.001	913.5	1,047.5

This report addresses EUT Operations as Frequency Hopping Spread Spectrum (FHSS) Transmitter Mode 1. Note, the production device utilizes integral non-user accessible antenna system providing 8.0 dBi gain.

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Bands 47CFR 15.205, RSS-210 4.1	-6.7	Complies
Conducted Emissions as per 47CFR 15.207, RSS-GEN 8.8	N/A	Complies
Radiated Emissions 47CFR 15.209, RSS-GEN 8.9	-3.3	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-1.5	Complies

Tests performed include

Rogers Labs, a division of The Compatibility Center LLC
 7915 Nieman Road
 Lenexa, KS 66214
 Phone: (913) 660-0666
 Revision 3

HVIN: GMN-03000
 Test #: 250128
 Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc
 FCC ID: IPH-04286
 SN: 78F000511 & 78F000512
 Date: July 9, 2025
 Page 5 of 46

47CFR

§15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz.

(a) Operation under the provisions of this Section is limited to frequency hopping and digitally modulated intentional radiators that comply with the following provisions:

(1) Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20-dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20-dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(iii) Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(1) For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

(c) Operation with directional antenna gains greater than 6 dBi.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.

Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

RSS-247 Issue 3

5.1 Frequency hopping systems (FHS)

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Road

Lenexa, KS 66214

Phone: (913) 660-0666

Revision 3

HVIN: GMN-03000

Test #: 250128

Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc

FCC ID: IPH-04286

SN: 78F000511 & 78F000512

Date: July 9, 2025

Page 6 of 46

FHSs employ a spread spectrum technology in which the carrier is modulated with coded information in a conventional manner, causing a conventional spreading of the radio frequency (RF) energy around the carrier frequency. The carrier frequency is not fixed, but changes at fixed intervals under the direction of a coded sequence.

FHSs are not required to employ all available hopping frequencies during each transmission.

However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the requirements in this section in case the transmitter is presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of frequency hopping equipment and must distribute its transmissions over the minimum number of hopping channels specified in this section.

Incorporation of intelligence into an FHS that enables it to recognize other users of the band and to avoid occupied frequencies is permitted provided that the FHS does it individually and independently chooses or adapts its hopset. The coordination of FHSs in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

The following applies to FHSs in each of the three bands:

a) The bandwidth of a frequency hopping channel is the 20 dB emission bandwidth, measured with the hopping stopped. The system's radio frequency (RF) bandwidth is equal to the channel bandwidth multiplied by the number of channels in the hopset. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

b) FHSs shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

c) For FHSs in the band 902-928 MHz: if the 20 dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 20-second period. If the 20 dB bandwidth of the hopping channel is 250 kHz or greater, the system shall use at least 25 hopping channels and the average time of occupancy on any channel shall not be greater than 0.4 seconds within a 10-second period. The maximum 20 dB bandwidth of the hopping channel shall be 500 kHz.

d) FHSs operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

e) FHSs operating in the band 5725-5850 MHz shall use at least 75 hopping channels. The maximum 20 dB bandwidth of the hopping channel shall be 1 MHz. The average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 30-second period.

Equipment Tested

HVIN: GMN-03000
 Garmin International, Inc.
 1200 East 151st Street
 Olathe, KS 66062

Description	Part Number	Serial Number
GMN-03000 (Radiated EUT #1)	011-05799-05	78F000512
GMN-03000 (Conducted EUT #2)	011-05799-05	78F000511
X3 Main Harness	T00-00846-00	N/A
SMA RF 50Ω Load	N/A	N/A
BNC RF 50Ω Load	N/A	N/A
USB-C Drive	N/A	N/A
RS-232 to serial adapter	N/A	N/A
Laptop Computer	Latitude 74870	EFSPSN2

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

The design may operate one transmitter chain at a time on a given radio (#1 or #2) but is capable of simultaneous transmission of one radio #1 transmitter and one radio #2 transmitter.

Software (FVIN): 1.00b; Antennas: Bluetooth & 2.4 GHz WiFi - PIFA (8.0 dBi); 5.2 GHz PIFA (-4.4 dBi)

Equipment Operational Modes

Radio #	Mode #	Standard
1	1	BT BR (GFSK)
1	2	BT (2EDR $\pi/4$ DQPSK)
1	3	BT (3EDR 8DPSK)
1	4	BT BLE (GMSK)
1	5	2.4G 802.11b
1	6	2.4G 802.11g
1	7	2.4G 802.11n
1	8	U-NII-1 802.11a
1	9	U-NII-1 802.11n20
1	10	U-NII-1 802.11n40
1	11	U-NII-1 802.11ac20
1	12	U-NII-1 802.11ac40
1	13	U-NII-1 802.11ac80
2	14	2.4G 802.11b
2	15	2.4G 802.11g
2	16	2.4G 802.11n
2	17	U-NII-1 802.11a
2	18	U-NII-1 802.11n20
2	19	U-NII-1 802.11n40
2	20	U-NII-1 802.11ac20
2	21	U-NII-1 802.11ac40
2	22	U-NII-1 802.11ac80

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Road

Lenexa, KS 66214

Phone: (913) 660-0666

Revision 3

HVIN: GMN-03000

Test #: 250128

Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc

FCC ID: IPH-04286

SN: 78F000511 & 78F000512



Date: July 9, 2025

Page 9 of 46

Equipment Function

The GMN-03000 is an aeronautical display providing 2.4 GHz and 5 GHz wireless communication. The device is marketed as Aircraft Panel Mounted Display Unit. This report documents the performed testing and results for applicable configuration and product operation. The test software provided the ability to operate the transmitter at near 100% duty cycle for testing purposes. The testing mode of operation exceeds typical duty cycle operation of production equipment. As requested by the manufacturer, the equipment was tested for emissions compliance using the available configurations with the worst-case data presented. Test results in this report relate only to the products described in this report.

Equipment Configuration



Application for Certification

- (1) Manufacturer: Garmin International, Inc.
1200 East 151st Street
Olathe, KS 66062
- (2) Identification: HVIN: GMN-03000
FCC ID: IPH-04286
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from installation vehicle. The EUT provides interface ports for power, loads and communications as presented in this filing.
- (9) Transition Provisions of 47CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DSS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Applicable Standards

The following information is submitted in accordance with the eCFR (electronic Title 47 Code of Federal Regulations) (47CFR), dated January 13, 2025: Part 2, Subpart J, Part 15C Paragraph 15.247, RSS-247 Issue 3, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2020. This report documents compliance for the EUT operations as Frequency Hopping Spread Spectrum (FHSS) Transmitter.

Test Procedures

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions were performed as required in CFR47 15B, RSS-GEN, and directed in ANSI C63.4-2014. The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in the test setup exhibit for EUT placement used during testing.


Radiated Emission Procedure

Radiated emissions testing was performed as required in 47CFR 15C, RSS-247 Issue 3, RSS-GEN and specified in ANSI C63.10-2020. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. Per above requirements, the frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions and all significant results reported. All other unreported findings were at least 20 dB below limits. Refer to diagrams two and three showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure


The EUT was assembled as required for operation placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed presented in the regulations and specified in ANSI C63.10-2020. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and the spectrum analyzer. Refer to diagram 4 showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.

Diagram 1 Test arrangement for power-line conducted emissions



1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long see (see 6.2.3.1).
2. I/O cables that are not connected to an accessory shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m (see 6.2.2).
3. EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. LISN can be placed on top of, or immediately beneath, reference ground plane (see 6.2.2 and 6.2.3).
 - 3.1 All other equipment powered from additional LISN(s).
 - 3.2 Multiple-outlet strip can be used for multiple power cords of non-EUT equipment.
 - 3.3 LISN at least 80 cm from nearest part of EUT chassis.
4. Non-EUT components of EUT system being tested.
5. Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop (see 6.2.3.1).
6. Edge of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane (see 6.2.2 for options).
7. Antenna may be integral or detachable. If detachable, the antenna shall be attached for this test


Diagram 2 Test arrangement for radiated emissions of tabletop equipment



1. A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).
 - 1.1. LISN spaced at least 80 cm from the nearest part of the EUT chassis.
2. Antenna can be integral or detachable, depending on the EUT (see 6.3.1).
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).
4. For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 3 Test arrangement for radiated emissions tested in Semi-Anechoic Chamber (SAC) and Outdoor Area Test Site (OATS)

Below 1 GHz



Above 1 GHz:





Diagram 4 Test arrangement for Antenna Port Conducted emissions
Spectrum Analyzer



Test Site Locations

Conducted EMI AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS (or satellite location).

Antenna port Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS (or satellite location).

Radiated EMI The radiated emissions tests were performed at the 3 meters Semi-Anechoic Chamber (SAC) located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS or at the 3 meters Outdoor Area Test Site (OATS) in the satellite location.

Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096

NVLAP Accreditation Lab code 200087-0

Units of Measurements

Conducted EMI Data presented in dB μ V; dB referenced to one microvolt

Antenna port Conducted Data is in dBm; dB referenced to one milliwatt

Radiated EMI Data presented in dB μ V/m; dB referenced to one microvolt per meter

Note: The limit is expressed for a measurement in dB μ V/m when the measurement is taken at a distance of 3 or 10 meters. Data taken for this report was taken at distance of 3 meters. Sample calculation demonstrates corrected field strength reading for Semi-Anechoic Chamber using the measurement reading and correcting for receive antenna factor, cable losses, and amplifier gains.

Sample Calculation:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, Losses = attenuators/cable losses, Gain = amplification gains

$RFS (dB\mu V/m @ 3m) = FSM (dB\mu V) + A.F. (dB/m) + Losses (dB) - Gain (dB)$

Frequency: 9 kHz-30 MHz	Frequency: 30 MHz- 1 GHZ	Frequency: Above 1 GHz
Loop Antenna	Broadband Biconilog	Horn
RBW = 9 kHz	RBW = 120 kHz	RBW = 1 MHz
VBW = 30 kHz	VBW = 500 kHz	VBW = 3 MHz
Sweep time = Auto	Sweep time = Auto	Sweep time = Auto
Detector = PK, QP	Detector = PK, QP	Detector = PK, AV
Antenna Height 1m	Antenna Height 1-4m	Antenna Height 1-4m

Environmental Conditions

Ambient Temperature 21.9° C

Relative Humidity 23.0 %

Atmospheric Pressure 1011.9 mb

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Road

Lenexa, KS 66214

Phone: (913) 660-0666

Revision 3

HVIN: GMN-03000

Test #: 250128

Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc

FCC ID: IPH-04286

SN: 78F000511 & 78F000512

Date: July 9, 2025

Page 19 of 46

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with the 47CFR Part 15C, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Intentional Radiators

The following information is submitted supporting compliance with the requirements of 47CFR, Subpart C, paragraph 15.247, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5.

Antenna Requirements

The EUT incorporates integral non-user accessible system. Production equipment offers no provision for connection to alternate antenna system. The antenna connection point complies with the unique antenna connection requirements. There are no deviations or exceptions to the specification.

Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the SAC. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the SAC, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2020 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1, BT BR (GFSK)

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2390.0	50.1	36.4	50.0	36.4	54.0	-17.6	-17.6
2483.5	52.0	37.5	50.3	37.1	54.0	-16.5	-16.9
4804.0	50.7	36.9	50.4	36.8	54.0	-17.1	-17.2
4882.0	50.0	37.3	49.6	36.8	54.0	-16.7	-17.2
4960.0	49.9	36.4	49.3	36.5	54.0	-17.6	-17.5
7206.0	53.7	40.2	53.5	40.2	54.0	-13.8	-13.8
7323.0	53.6	40.3	53.7	40.3	54.0	-13.7	-13.7
7440.0	53.3	39.9	52.8	39.9	54.0	-14.1	-14.1
12010.0	60.2	46.4	60.1	46.1	54.0	-7.6	-7.9
12205.0	60.3	47.3	60.5	47.2	54.0	-6.7	-6.8
12400.0	60.1	47.0	59.8	47.0	54.0	-7.0	-7.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C and RSS-247 Issue 3 Intentional Radiator requirements. The EUT demonstrated a worst-case minimum margin of -6.7 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted EMI Procedure

The equipment operates solely from direct current power and offers no provision for connection to utility power systems. Therefore, no AC line conducted emissions testing was required or performed.

General Radiated Emissions Procedure

Testing for the radiated emissions were performed as specified in CFR47 15B, RSS-GEN, and directed in ANSI C63.10:2020. For testing purposes, the EUT was arranged as presented in the applicable configuration diagrams above and operated through all modes as presented.

Exploratory radiated emissions measurements were performed in the SAC chamber or screen room, finding maximized emissions over frequency, EUT orientation, antenna height and polarity. This data is then used to focus the final radiated emissions measurements on these maximized points.

Final radiated emissions data were taken with the EUT located in the OATS or SAC at distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 6,000 MHz was searched for radiated emissions. Measured emission levels were maximized by EUT placement on the table, changing cable location, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop, Biconical, Broadband Biconilog, Log Periodic, and Double Ridge or Pyramidal Horns and mixers above 1 GHz.

Table 2 General Radiated Emissions Data – Worst Case (Horizontal Polarization)

Frequency (MHz)	Peak (dBμV/m)	Quasi-Peak (dBμV/m)	Limit @ 3m (dBμV/m)	Margin (dBm)
676.2	38.5	29.7	47	-17.3
707.0	41.1	43.7	47	-3.3
740.4	38.9	31.7	47	-15.3
746.4	41.2	36.1	47	-10.9
766.1	40.1	34.7	47	-12.3

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Figure 1 Plot of General Radiated Emissions – Horizontal Polarization





Table 3 General Radiated Emissions Data – Worst Case (Vertical Polarization)

Frequency (MHz)	Peak (dB μ V/m)	Quasi-Peak (dB μ V/m)	Limit @ 3m (dB μ V/m)	Margin (dBm)
707.2	27.6	35.9	47	-11.1
712.1	28.0	22.7	47	-24.3
766.3	41.6	36.7	47	-10.3
796.8	29.5	21.3	47	-25.7
913.6	31.2	23.4	47	-23.6

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Figure 2 Plot of General Radiated Emissions – Vertical Polarization



Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C paragraph 15.209, RSS-247 Issue 3, and RSS-GEN Issue 5 Intentional Radiators. The EUT configuration demonstrated a minimum margin of -3.3 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 2400 – 2483.5 MHz

Test procedures of ANSI C63.10-2020 and KDB 558074 D01 15.247 Meas Guidance v05 were used during transmitter testing. The transmitter peak power was measured at the antenna port as described in ANSI C63.10-2020. The 20-dB and 99% emission bandwidths were measured as described in C63.10-2013. The channel separation and the number of hopping channels were measured at the antenna port as described in C63.10-2013. The system utilizes at least 15 channels with average time of occupancy on any channel not exceeding 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. The transmitter radiated spurious and general emissions were measured on an open area test site @ 3 meters. During radiated emissions measurements, the EUT sample #1 was placed on a turntable elevated as required above the ground plane at a distance of 3 meters from the measurement antenna. The amplitude of each emission was then recorded from the measurement results. The test system gains and losses were accounted for in the measurement results presented. The amplitude of each radiated emission was maximized by equipment orientation and placement on the turn table, raising and lowering the FSM (Field Strength Measuring) antenna, changing the FSM antenna polarization, and by rotating the turntable. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Emissions were measured in dB μ V/m @ 3 meters. Antenna port conducted emission data and plots were taken using test sample #2.

Requirement:

Average occupancy time Requirement:

Average time of occupancy on any channel shall not be greater than 400 mS (0.4 seconds) within a 30 second period (0.4 times the number of hopping channels of 79).

Time on channel:

The design resides on channel 60 times in 6 seconds (300 times in a 30 second period) transmitting each time for 141.9 μ S. This equates to an average time of occupancy of (300*141.9 μ S) 42.6 mS over 30 seconds.

The 42.6 mS average time of occupancy over 30 seconds demonstrates compliance with the requirement of less than 400 mS in 30 second period. Additional Frequency Hopping detail may be found in the operational description exhibits.

Refer to figures three through twelve showing plots taken of the 2402-2480 MHz BT BR (GFSK) Frequency Hopping Spread Spectrum operation displaying compliance with the specifications.

Figure 3 Plot of Transmitter Emissions Operation in 2402-2480 MHz Mode 1, BT BR




Figure 4 Plot of Transmitter Emissions 20-dB Occupied Bandwidth Mode 1, BT BR




Figure 5 Plot of Transmitter Emissions 99% Occupied Bandwidth Mode 1, BT BR




Figure 6 Plot of Number of Hopping Channels Mode 1, BT BR




Figure 7 Plot of Number of Hopping Channels Mode 1, BT BR




Figure 8 Plot of Number of Hopping Channels Mode 1, BT BR




Figure 9 Plot of Number of Hopping Channels Mode 1, BT BR




Figure 10 Plot of Channel Separation Mode 1, BT BR




Figure 11 Plot of Dwell time On Channel Mode 1, BT BR




Figure 12 Plot of Number of Times on Channel over 10 Second Period Mode 1, BT BR




Figure 13 Plot of Transmitter Emissions Low Band Edge Mode 1, BT BR





Figure 14 Plot of Transmitter Emissions High Band Edge Mode 1, BT BR



Transmitter Emissions Data

Table 4 Transmitter Radiated Emissions Mode 1, BT BR

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2402.0	--	--	--	--	--	--	--
4804.0	50.7	36.9	50.4	36.8	54.0	-17.1	-17.2
7206.0	53.7	40.2	53.5	40.2	54.0	-13.8	-13.8
9608.0	57.1	43.5	57.0	43.5	54.0	-10.5	-10.5
12010.0	60.2	46.4	60.1	46.1	54.0	-7.6	-7.9
14412.0	61.0	47.4	60.7	47.3	54.0	-6.6	-6.7
16814.0	66.6	52.4	65.8	52.5	54.0	-1.6	-1.5
2441.0	--	--	--	--	--	--	--
4882.0	50.0	37.3	49.6	36.8	54.0	-16.7	-17.2
7323.0	53.6	40.3	53.7	40.3	54.0	-13.7	-13.7
9764.0	56.5	43.5	57.1	43.5	54.0	-10.5	-10.5
12205.0	60.3	47.3	60.5	47.2	54.0	-6.7	-6.8
14646.0	61.2	47.4	60.0	47.5	54.0	-6.6	-6.5
17087.0	64.9	51.7	64.5	51.7	54.0	-2.3	-2.3
2480.0	--	--	--	--	--	--	--
4960.0	49.9	36.4	49.3	36.5	54.0	-17.6	-17.5
7440.0	53.3	39.9	52.8	39.9	54.0	-14.1	-14.1
9920.0	57.6	44.1	57.2	44.1	54.0	-9.9	-9.9
12400.0	60.1	47.0	59.8	47.0	54.0	-7.0	-7.0
14880.0	60.6	47.6	60.6	47.6	54.0	-6.4	-6.4
17360.0	64.0	50.8	63.6	50.9	54.0	-3.2	-3.1

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 5 Transmitter Antenna Port Conducted Data Mode 1, BT BR

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	20-dB Occupied Bandwidth (kHz)
Mode 1, BT BR			
2402	0.001	911.3	1,037.4
2441	0.001	912.0	1,047.5
2480	0.001	913.5	1,042.1

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Paragraph 15.247, Industry Canada RSS-247 Issue 3, and RSS-GEN Issue 5. The antenna port conducted output power measured was 0.001 Watts. The unit utilizes 79 hopping channels with the average time of occupancy less than 0.4 seconds over the required time. The EUT worst-case configuration demonstrated minimum radiated harmonic emission margin of -1.5 dB below the limit. No other radiated emissions were found in the restricted bands less than 20 dB below limits than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the limits.

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Laboratory Certificate of Accreditation

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16–4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.46
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

Equipment	Manufacturer	Model (SN)	Band	Cal Date(m/d/y)	Due
☒ LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/20/2025	3/20/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	9/16/2024	9/16/2025
☐ Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	9/16/2024	9/16/2025
☒ Antenna	Com Power	AL-130 (121055)	.001-30 MHz	9/16/2024	9/16/2025
☐ Antenna:	EMCO	6509	.001-30 MHz	9/16/2024	9/16/2026
☒ Antenna	ARA	BCD-235-B (169)	20-350MHz	9/16/2024	9/16/2025
☒ Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	9/16/2024	9/16/2025
☐ Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	9/16/2024	9/16/2026
☒ Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/17/2025	3/17/2027
☒ Antenna	Com Power	AH-118 (10110)	1-18 GHz	9/16/2024	9/16/2026
☒ Antenna	Com Power	AH-840 (101046)	18-40 GHz	3/17/2025	3/17/2027
☒ Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	7/8/2024	7/8/2025
☒ Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/21/2025	1/21/2026
☐ Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
☐ Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	9/16/2024	9/16/2025
☐ Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	9/16/2024	9/16/2025
☒ Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	9/16/2024	9/16/2025
☒ Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	9/16/2024	9/16/2025
☒ Pwr Sensor	Rohde & Schwarz	NRP33T	0.05-33 GHz	9/26/2023	9/26/2025
☒ Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/19/2025	3/19/2026
☐ RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/21/2025	3/21/2026
☒ Weather station	Davis	6152 (A70927D44N)		7/11/2024	7/11/2025

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
☐ Frequency Counter: Leader		LDC-825 (8060153)		3/19/2025	3/19/2026
☐ ISN	Com-Power	Model ISN T-8 (600111)		3/19/2025	3/19/2026
☐ LISN	Compliance Design	FCC-LISN-2.Mod.cd,(126)	.15-30MHz	9/16/2024	9/16/2025
☐ LISN:	Com-Power	Model LI-220A		9/16/2024	9/16/2026
☒ LISN:	Com-Power	Model LI-550C		9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303072)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L1M)(281183)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(4M)(281184)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(317546)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Time Microwave	4M-750HF290-750 (L4M)	9kHz-24 GHz	9/16/2024	9/16/2025
☒ Cable	Mini-Circuits	KBL-2M-LOW+ (23090329)	9kHz-40 GHz	3/22/2025	3/22/2026
☒ Analyzer	HP	8562A (3051A05950)	9kHz-125GHz	3/20/2025	3/20/2026
☐ Antenna:	Solar	9229-1 & 9230-1		2/5/2025	2/5/2026
☐ CDN:	Com-Power	Model CDN M325E		9/16/2024	9/16/2025
☐ Oscilloscope Scope: Tektronix		MDO 4104		2/5/2025	2/5/2026
☐ EMC Transient Generator HVT		TR 3000		2/5/2025	2/5/2026
☐ AC Power Source (Ametech, California Instruments)				2/5/2025	2/5/2026
☒ Field Intensity Meter: EFM-018				2/5/2025	2/5/2026
☒ ESD Simulator: MZ-15				2/5/2025	2/5/2026
☐ Injection Clamp Luthi Model EM101				not required	
☐ R.F. Power Amp ACS 230-50W				not required	
☐ R.F. Power Amp EIN Model: A301				not required	
☐ R.F. Power Amp A.R. Model: 10W 1010M7				not required	
☐ R.F. Power Amp A.R. Model: 50U1000				not required	
☒ Temperature Chamber				not required	
☒ Shielded Room				not required	
POSSIBLY USE FOR GARMIN GPS TESTING					
☐ GNSS Sig Gen SG80K, SN: GNSS-00952				not required	

Annex C Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology

NVLAP[®] **ilac-MRA**

Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, a division of The Compatibility Center LLC
Lenexa, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué dated January 2009).*

2024-03-18 through 2025-03-31
Effective Dates

 
For the National Voluntary Laboratory Accreditation Program

United States Department of Commerce
National Institute of Standards and Technology

NVLAP[®] **ilac-MRA**

Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0


Rogers Labs, a division of The Compatibility Center LLC
Lenexa, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communiqué on ISO/IEC 17025).*

2025-03-11 through 2026-03-31
Effective Dates

 
For the National Voluntary Laboratory Accreditation Program

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Road

Lenexa, KS 66214

Phone: (913) 660-0666

Revision 3

HVIN: GMN-03000

Test #: 250128

Test to: 47CFR 15C

File: GMN-03000 FCC DSS TstRpt 250128 r3

Garmin International, Inc

FCC ID: IPH-04286

SN: 78F000511 & 78F000512

Date: July 9, 2025

Page 46 of 46