

FCC/ISED Test Report

Prepared for: Garmin International, Inc.

Address: 1200 E. 151st Street
Olathe, Kansas, 66062, USA

Product: A04354

Test Report No: R20220303-21-E2A

Approved by:



Nic S. Johnson, NCE
Technical Manager
iNARTE Certified EMC Engineer #EMC-003337-NE

DATE: 5 July 2022

Total Pages: 29

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.



Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

REVISION PAGE

Rev. No.	Date	Description
0	24 June 2022	Original – NJohnson Prepared by FLane, GLarsen, KVepuri
A	5 July 2022	Corrected the Table in Section 1.0 -NJ

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

CONTENTS

Revision Page	2
1.0 Summary of test results	4
2.0 EUT Description	5
2.1 Equipment under test	5
2.2 Description of test modes	5
2.3 Description of support units	5
3.0 Laboratory and General Test Description	6
3.1 Laboratory description	6
3.2 Test personnel	6
3.3 Test equipment	7
3.4 General test procedure and setup for radio measurements	8
4.0 Results	9
4.1 Duty Cycle	10
4.2 Radiated emissions	11
4.3 Band edges	16
4.4 Conducted Spurious Emissions	17
4.5 Conducted AC Mains Emissions	20
Appendix A: Sample Calculation	23
Appendix B – Measurement Uncertainty	24
Appendix C – Graphs and Tables	25
REPORT END	29

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

1.0 SUMMARY OF TEST RESULTS

The worst-case measurements were reported in this report. Summary of test results presented in this report correspond to the following section:

FCC Part 15.249

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISSED RSS-Gen, Issue 5
- (3) ISSED RSS-210, Issue 10
- (4) IEEE ANSI C63.10-2013

SUMMARY			
Requirement	Test Type and Limit	Result	Remark
FCC 15.203	Unique Antenna Requirement	Pass	PCB Antenna
FCC 15.35 RSS-Gen, 8.2	Duty cycle of pulsed emissions	N/A	Informational Purpose Only
NA	Minimum Bandwidth	N/A	Informational Purpose Only
FCC 15.209 RSS-Gen, 7.1, 7.3	Receiver Radiated Emissions	Pass	Meets the requirement of the limit.
FCC 15.209 RSS-Gen, 8.9 RSS-210 F1a FCC 15.249(a)	Transmitter Radiated Emissions	Pass	Meets the requirement of the limit.
FCC 15.209, 15.205, 15.249(d) RSS-Gen, 8.9 RSS-210, 5	Band Edge Measurement	Pass	Meets the requirement of the limit.
FCC 15.207 RSS-Gen 8.8	Conducted AC Emissions	Pass	Meets the requirement of the limit.

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

2.0 EUT DESCRIPTION

2.1 EQUIPMENT UNDER TEST

Summary and Operating Condition:

EUT	A04354
EUT Received	23 March 2022
EUT Tested	29 March 2022- 28 April 2022
Serial No.	3405902265 (Radiated Measurements) 3405902263 (Conducted Measurements)
Operating Band	2400 – 2483.5 MHz
Device Type	☐ GMSK ☒ GFSK ☐ BT BR ☐ BT EDR 2MB ☐ BT EDR 3MB ☐ 802.11x ☐ NFC
Power Supply / Voltage	Internal Battery/ 5VDC Charger: Garmin (Phi Hong) MN: PSAF10R-050Q (Representative Power Supply)

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.2 DESCRIPTION OF TEST MODES

The operating range of the EUT is dependent on the device type found in section 2.1:

For GFSK Transmissions:

Channel	Frequency
Low	2402 MHz
Mid	2441 MHz
High	2480 MHz

These are the only representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

2.3 DESCRIPTION OF SUPPORT UNITS

None

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

3.0 LABORATORY AND GENERAL TEST DESCRIPTION

3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
4740 Discovery Drive
Lincoln, NE 68521

A2LA Certificate Number:	1953.01
FCC Accredited Test Site Designation No:	US1060
Industry Canada Test Site Registration No:	4294A-1
NCC CAB Identification No:	US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of $35 \pm 4\%$
Temperature of $22 \pm 3^\circ$ Celsius



3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Fox Lane	Test Engineer	Testing and Report
2	Karthik Vepuri	Test Engineer	Review/Editing and Report
3	Blake Winter	Test Engineer	Testing
4	Grace Larsen	Test Technician	Testing and Report

Notes:

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.



Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.

3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Keysight MXE Signal Analyzer (44GHz)	N9038A	MY59050109	July 21, 2021	July 21, 2023
Keysight MXE Signal Analyzer (26.5GHz)	N9038A	MY56400083	May 5, 2020	May 5, 2022
Keysight EXA Signal Analyzer	N9010A	MY56070862	July 20, 2021	July 20, 2023
SunAR RF Motion	JB1	A091418	July 27, 2021	July 27, 2022
EMCO Horn Antenna	3115	6416	July 28, 2021	July 28, 2023
EMCO Horn Antenna	3116	2576	March 9, 2020	March 9, 2023
Com-Power LISN 50μH / 250μH - 50Ω	LI-220C	20070017	September 22, 2020	September 22, 2022
8447F POT H64 Preamplifier*	8447F POT H64	3113AD4667	March 21, 2022	March 21, 2024
Rohde & Schwarz Preamplifier*	TS-PR18	3545700803	March 21, 2022	March 21, 2024
Trilithic High Pass Filter*	6HC330	23042	March 21, 2022	March 21, 2024
ETS – Lindgren- VSWR on 10m Chamber	10m Semi-anechoic chamber-VSWR	4740 Discovery Drive	July 30, 2020	July 30, 2023
NCEE Labs-NSA on 10m Chamber	10m Semi-anechoic chamber-NSA	NCEE-001	October 25, 2019	October 25, 2022
TDK Emissions Lab Software	V11.25	700307	NA	NA
RF Cable (preamplifier to antenna)*	MFR-57500	01-07-002	March 21, 2022	March 21, 2024
RF Cable (antenna to 10m chamber bulkhead)*	FSCM 64639	01E3872	September 24, 2021	September 24, 2023
RF Cable (10m chamber bulkhead to control room bulkhead)*	FSCM 64639	01E3864	September 24, 2021	September 24, 2023
RF Cable (control room bulkhead to test receiver)*	FSCM 64639	01F1206	September 24, 2021	September 24, 2023
N connector bulkhead (10m chamber)**	PE9128	NCEEBH1	September 24, 2021	September 24, 2023
N connector bulkhead (control room)**	PE9128	NCEEBH2	September 24, 2021	September 24, 2023

*Internal Characterization

**2 Year Cal Cycle

Notes:

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

3.4 General test procedure and setup for radio measurements

Measurement type presented in this report (Please see the checked box below):

Conducted ☒

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 1 - Bandwidth Measurements Test Setup

Radiated ☒

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 2 - Radiated Emissions Test Setup



Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.

4.0 RESULTS

Unrestricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Corrected Highest Unrestricted level (dBuV/m @ 3m)	Measurement Type	Limit (dBuV/m @ 3m)	Margin	Result
Low	GFSK	2400.00	53.42	Average	53.98	0.56	PASS
*Limit shown is the average limit taken from FCC Part 15.209 **Highest out of band level = SA Peak Level + DCCF (For Emissions). C63.10 Sec. 11.12.2.5.2 See Sec 4.3 for more information on DCCF and Appendix C for SA peak levels.							

Unrestricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level (dBuV)	Relative Fundamental (dBuV)	Delta (dB)	Min Delta (dB)	Result
High	GFSK	2483.50	57.83	110.53	52.70	50.00	PASS

Peak Restricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)	Measurement Type	Limit (dBuV/m @ 3m)	Margin	Result
Low	GFSK	2390.00	63.03	Peak	73.98	10.95	PASS
High	GFSK	2483.50	60.95	Peak	73.98	13.03	PASS
*Limit shown is the peak limit taken from FCC Part 15.209							
Average Restricted Band-Edge							
CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)**	Measurement Type	Limit (dBuV/m @ 3m)*	Margin	Result
Low	GFSK	2390.00	45.83	Average	53.98	8.15	PASS
High	GFSK	2483.50	43.75	Average	53.98	10.23	PASS
*Limit shown is the average limit taken from FCC Part 15.209 **Average Highest out of band level = SA Peak Level + DCCF (For Emissions). C63.10 Sec. 11.12.2.5.2 See Sec 4.3 for more information on DCCF and Appendix C for SA peak levels.							



Report Number:

R20220303-21-E2

Rev

A

Prepared for:

Garmin International, Inc.

4.1 DUTY CYCLE

Test Method: IEEE ANSI C63.10-2013, Section 7.5

Manufacturer declared that the maximum possible duty cycle is 13.8% so the duty cycle correction factor (DCCF) $20 \log (0.138) = -17.2$ dB was used as the correction for emissions.

DCCF For Emissions = -17.2 dB

4.2 RADIATED EMISSIONS

Test Method: ANSI C63.10-2013, Section 6.5, 6.6

Limits for radiated emissions measurements:

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH ($\mu\text{V/m}$)	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 * \log * \text{Emission level } (\mu\text{V/m})$.
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.
4. The EUT was investigated for spurious emissions while running off of battery power and external USB power. The worse-case emissions were produced while running off of USB power, so results from this mode are presented.



Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

Test procedures:

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements from 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.
- h. The EUT was tested with all radios transmitting simultaneously as part of the preview scan. If intermodulation products were found during the preview scan, they were maximized and reported in the data and identified as intermodulation products.

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

Test setup:




Figure 3 - Radiated Emissions Test Setup

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

Deviations from test standard:

No deviation.

EUT operating conditions

Details can be found in section 2.1 of this report.

Test results:




Figure 4 - Radiated Emissions Plot, Receive




Figure 5 - Radiated Emissions Plot, Low Channel, GFSK

	Report Number:	R20220303-21-E2	Rev	A
	Prepared for:	Garmin International, Inc.		

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Limit value – Emission Level

The EUT was maximized in all 3 orthogonal axes and multiple data rates were investigated. The worst-case is shown in the plot and table above. If the measurements were found to be 6 dB below the limit, the tabular data is not provided.

Peak Measurements, GFSK								
Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
2402.164000	102.40	114.00	11.60	186	172	V	Low	GFSK
2440.866000	99.21	114.00	14.79	213	127	V	Mid	GFSK
2479.846000	100.12	114.00	13.88	115	123	V	High	GFSK
All other emissions found to be at least 6dB below limit line. Limits from FCC Part 15.249 were used.								

Average Measurements, GFSK								
Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
2402.164000	85.20	94.00	8.80	186	172	V	Low	GFSK
2440.866000	82.01	94.00	11.99	213	127	V	Mid	GFSK
2479.846000	82.92	94.00	11.08	115	123	V	High	GFSK
*Average Level = Peak level + DCCF (From section 4.2), See Sec 4.3 for more information on DCCF All other emissions found to be at least 6dB below limit line. Limits from FCC Part 15.249 were used.								



Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

4.3 BAND EDGES

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of band-edge measurements:

For FCC Part 15.249 Device:

For emissions outside of the allowed band of operation, the emission level needs to be 50dB under the maximum fundamental field strength. However, if the emissions fall within one of the restricted bands from 15.205 the field strength levels need to be under that of the limits in 15.209.

Test procedures:

The highest emissions level beyond the band-edge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209. More details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the band edge plots can be found in the Appendix C.
2. All data is in the table in results section 4.0.
3. If the device falls under FCC Part 15.249 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 50 dB between peak and the band edge or band edge was compared to FCC Part 209 limit.
4. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.



Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

4.4 CONDUCTED SPURIOUS EMISSIONS

Test Method: ANSI C63.10-2013, Section 6.7

Limits of spurious emissions:

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in § 15.209, whichever is the lesser attenuation.

Test procedures:

The highest emissions level was measured and recorded. All spurious measurements were evaluated to 50dB below the fundamental. More details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:




Figure 6 - Radiated Emissions Plot, GFSK, 30MHz – 1GHz, Low




Figure 7 - Radiated Emissions Plot, GFSK, 1GHz – 3.6GHz, Low

Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		




Figure 8 - Radiated Emissions Plot, GFSK, 3.6GHz – 25GHz, Low

4.5 CONDUCTED AC MAINS EMISSIONS

Test Method: ANSI C63.10-2013, Section(s) 6.2

Limits for conducted emissions measurements:

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

Test Procedures:

- a. The EUT was placed 0.8m above a ground reference plane and 0.4 meters from the conducting wall of a shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). The LISN provides 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference as well as the ground.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits are not reported.
- d. Results were compared to the 15.207 limits.

Deviation from the test standard:

No deviation

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test Results:




Figure 9 - Conducted Emissions Plot, TX, Line




Figure 10 - Conducted Emissions Plot, TX, Neutral




Figure 11 - Conducted Emissions Plot, Idle, Line




Figure 12 - Conducted Emissions Plot, Idle, Neutral



Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.

APPENDIX A: SAMPLE CALCULATION

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

AV = Averaging Factor (if applicable)

Assume a receiver reading of 55 dB μ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB μ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm } [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$

AV is calculated by taking the $20 \cdot \log(T_{\text{on}}/100)$ where T_{on} is the maximum transmission time in any 100ms window.

EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

$$EIRP (\text{Watts}) = [\text{Field Strength (V/m)} \times \text{antenna distance (m)}]^2 / 30$$

$$\text{Power (watts)} = 10^{[\text{Power (dBm)}]/10} / 1000$$

$$\text{Voltage (dB}\mu\text{V)} = \text{Power (dBm)} + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$\text{Field Strength (V/m)} = 10^{[\text{Field Strength (dB}\mu\text{V/m)} / 20] / 10^6}$$

$$\text{Gain} = 1 \text{ (numeric gain for isotropic radiator)}$$

$$\text{Conversion from 3m field strength to EIRP (d=3):}$$

$$EIRP = [FS(\text{V/m}) \times d^2] / 30 = FS [0.3] \quad \text{for } d = 3$$

$$EIRP(\text{dBm}) = FS(\text{dB}\mu\text{V/m}) - 10(\log 10^9) + 10\log[0.3] = FS(\text{dB}\mu\text{V/m}) - 95.23$$

$10\log(10^9)$ is the conversion from micro to milli



Report Number:	R20220303-21-E2	Rev	A
Prepared for:	Garmin International, Inc.		

APPENDIX B – MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	±4.31
Radiated Emissions, 3m	1GHz - 18GHz	±5.08
Emissions limits, conducted	30MHz – 18GHz	±3.03

Expanded uncertainty values are calculated to a confidence level of 95%.




Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.


APPENDIX C – GRAPHS AND TABLES



01 LBE Unrestricted, GFSK

* The average value reported in section 4.0 is calculated by subtracting DCCF from section 4.2 from the peak value found in the above plot.

$$\text{Corrected Average level} = 70.620 - 17.2 = 53.42 \text{ dBuV/m}$$



02 HBE Unrestricted, GFSK




Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.



03 LBE Restricted, GFSK

* Please ignore the average value from above plot. The average value reported in section 4.0 is calculated by subtracting DCCF from section 4.2 from the peak value found in the above plot.
Corrected Average level = 63.03-17.2=45.83 dBuV/m




Report Number: R20220303-21-E2

Rev

A

Prepared for: Garmin International, Inc.



04 HBE Restricted, GFSK

* Please ignore the average value from above plot. The average value reported in section 4.0 is calculated by subtracting DCCF from section 4.2 from the peak value found in the above plot.

$$\text{Corrected Average level} = 60.95 - 17.2 = 43.75 \text{ dBuV/m}$$



Report Number:

R20220303-21-E2

Rev

A

Prepared for:

Garmin International, Inc.

REPORT END