

RF Exposure Evaluation Report

Client: Garmin International
1200 E 151st Street
Olathe Kansas 66062 USA

Model: A04535

FCC ID: IPH-04535
IC: 1792A-04535

Test Report No.: RFE20221003-20-01A

ISED CAB Identifier: US0177

Approved By:



Fox Lane,
EMC Test Engineer

Date: February 27, 2023

Total Pages: 6

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.

Revision Page

Rev. No.	Date	Description
Original	2 February 2023	Prepared by – FLane
A	27 February 2023	Changed to Body Worn Limit - FL

Regulatory Requirements:

FCC Part 1.1310, 2.1091, 2.1093
KDB 447498 D01
RSS-102, Issue 5

Summary:

The EUT's EIRP and conducted output power were used to evaluate for exemption from routine SAR testing.

EUT:

FCC ID: IPH-04535
IC: 1792A-04535

MPE Lab Nebraska Center for Excellence in Electronics
MPE Labs FCC Cab Designation: US1060
MPE Labs ISED Cab Designation: US0177

EIRP: 3.78 dBm EIRP / 0.00238 W
Conducted Power: 2.543 dBm / 0.001796 W
EIRP + 10% tune-up tolerance: 4.158 dBm / 0.002605 W
Antenna gain: 1.237 dBi / 1.330 numeric

$\text{EIRP (mW)} = \text{Conducted power (mW)} \times \text{antenna gain (numeric)}$

Antenna gain was measured by lab by comparing radiated sample to conducted sample

Calculations:

Parameters:

Test separation < 5 mm

max. EIRP of channel, including tune-up tolerance, mW = 2.38 mW

f(GHz) = 2.480 GHz (highest frequency of range chosen for worse-case)

EIRP + 10% tolerance was used as it is higher than the conducted value.

KDB 447498 D01, Section 4.3.1(a):

For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,³⁰ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz

Limit / numeric threshold = 7.5 for extremity SAR

$[7 / 5] \times \text{SQRT}(2.480) = 2.20 \leq 7.5$ **EXEMPT**

EIRP + power tolerance was rounded up to the nearest mW as instructed in the KDB

RSS 102, Issue 5, Section 2.5.1

2.5.1 Exemption Limits for Routine Evaluation — SAR Evaluation

SAR evaluation is required if the separation distance between the user and/or bystander and the antenna and/or radiating element of the device is less than or equal to 20 cm, except when the device operates at or below the applicable output power level (adjusted for tune-up tolerance) for the specified separation distance defined in Table 1. $f(\text{MHz}) = 2.400 \text{ GHz}$ (lowest limit frequency within range)

Table 1: SAR evaluation — Exemption limits for routine evaluation based on frequency and separation distance ^{4,5}					
Frequency (MHz)	Exemption Limits (mW)				
	At separation distance of ≤5 mm	At separation distance of 10 mm	At separation distance of 15 mm	At separation distance of 20 mm	At separation distance of 25 mm
≤300	71 mW	101 mW	132 mW	162 mW	193 mW
450	52 mW	70 mW	88 mW	106 mW	123 mW
835	17 mW	30 mW	42 mW	55 mW	67 mW
1900	7 mW	10 mW	18 mW	34 mW	60 mW
2450	4 mW	7 mW	15 mW	30 mW	52 mW
3500	2 mW	6 mW	16 mW	32 mW	55 mW
5800	1 mW	6 mW	15 mW	27 mW	41 mW

Exemption limit = 3.94 mW (extrapolated to 2480 MHz and x2.5)
 EIRP with 10% tolerance = 2.605 mW
 Conducted power with 10% tolerance = 1.904 mW

Both EIRP and conducted power with tolerance are **EXEMPT**

Result:

The EUT was found to be exempt from routine SAR testing and **COMPLIANT** with RF exposure requirements

REPORT END