

TEST REPORT

APPLICANT

Garmin International Inc

MODEL NAME

A05146

FCC ID

IPH-05146

ISED ID

1792A-05146

REPORT NUMBER

HA260504-GAR-001-R01

TEST REPORT

Date of Issue
August 06, 2026

Test Site
HCT America, Inc.
840 Yosemite Way, Milpitas, CA 95035, USA

Applicant	Garmin International Inc
Applicant Address	1200 E. 151st Street Olathe, Kansas 66062, USA
FCC ID	IPH-05146
ISED ID	1792A-05146
EUT Type	Portable Digital Transceiver
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
FCC Classification	Spread Spectrum Transmitter (DSS)
FCC Rule Part(s)	Part 15.247
ISED Rule Part(s)	RSS-247 Issue 4 (July 24, 2025) RSS-Gen Issue 5 Amd 2 (February 2021)
Test Procedure	ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024 + Errata to C63.10a-2024, KDB 558074 D01 v05r02

The device bearing the trade name and model specified above, has been shown to comply with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures required. The results of testing in this report apply only to the product which was tested. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all people taking them.

Authorized & Released By:



Dan Corona
Technical Manager

Tested By:



Joe Vang
RF Engineer

REVISION HISTORY

The revision history for this document is shown in table.

TEST REPORT NO.	REVISION	DATE	DESCRIPTION
HA260504-GAR-001	0	August 02, 2026	Initial Issue
HA260504-GAR-001-R01	01	August 06, 2026	- Page 1: Update ANSI C63.10 - Update Section 4

TABLE OF CONTENTS

1. GENERAL INFORMATION	4
2. METHODOLOGY	6
3. INSTRUMENT CALIBRATION	6
4. FACILITIES AND ACCREDITATIONS	7
5. ANTENNA REQUIREMENTS	8
6. MEASUREMENT UNCERTAINTY	9
7. DESCRIPTION OF TESTS	10
8. SUMMARY OF TEST RESULTS	23
9. TEST RESULT	26
9.1. 20 dB BANDWIDTH	26
9.2. OUTPUT POWER	29
9.3. NUMBER OF HOPPING CHANNELS	32
9.4. CARRIER FREQUENCY SEPARATION	34
9.5. TIME OF OCCUPANCY	35
9.6. CONDUCTED BAND EDGE & SPURIOUS EMISSIONS	37
9.7. RADIATED SPURIOUS EMISSIONS	41
9.8. RADIATED RESTRICTED BAND EDGES	46
9.9. POWERLINE CONDUCTED EMISSIONS	48
10. LIST OF TEST EQUIPMENT	50
APPENDIX A. TEST SETUP PHOTOS	51
APPENDIX B. PHOTOGRAPHS OF EUT	52

1. GENERAL INFORMATION

EUT DESCRIPTION

Model	A05146
Serial Number	Conducted: 8WR000283 Radiated: 8WR000211
Power Supply	5 V d.c. (USB type C - External adaptor)
RF Specification	ANT 2.4 GHz ISM Bluetooth 5.0 LE (BR / EDR / 1M / 2M), WIFI 2.4 GHz: 802.11b /g/ n (HT20) NFC
Transmitter Chain	1

RF SPECIFICATION SUBJECT TO THE REPORT

RF Specification	Bluetooth BR/EDR
Transmitter Chain	1
Frequency Range	2 400 MHz – 2 480 MHz
Max. RF Output Power	Peak: 9.63 dBm (9.183 mW)
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Number of Channels	79 Channels
Antenna Specification ¹⁾	Antenna Type: Inverted-F Peak Gain: -0.028 dBi
Firmware Version ²⁾	22.21
Hardware Version ²⁾	V2
Date(s) of Tests	May 20, 2026, ~ June 2, 2026
Test Environment	Temperature: 18.9°C ~ 25°C Humidity: 35% ~ 50% R.H.

Note:

1. Antenna information is based on the document provided.
2. Firmware and Hardware Version are as received by the client.

OPERATING FREQUENCY CHANNELS

Bluetooth (BR/EDR)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2 402	20	2 422	40	2 442	60	2 462
01	2 403	21	2 423	41	2 443	61	2 463
02	2 404	22	2 424	42	2 444	62	2 464
03	2 405	23	2 425	43	2 445	63	2 465
04	2 406	24	2 426	44	2 446	64	2 466
05	2 407	25	2 427	45	2 447	65	2 467
06	2 408	26	2 428	46	2 448	66	2 468
07	2 409	27	2 429	47	2 449	67	2 469
08	2 410	28	2 430	48	2 450	68	2 470
09	2 411	29	2 431	49	2 451	69	2 471
10	2 412	30	2 432	50	2 452	70	2 472
11	2 413	31	2 433	51	2 453	71	2 473
12	2 414	32	2 434	52	2 454	72	2 474
13	2 415	33	2 435	53	2 455	73	2 475
14	2 416	34	2 436	54	2 456	74	2 476
15	2 417	35	2 437	55	2 457	75	2 477
16	2 418	36	2 438	56	2 458	76	2 478
17	2 419	37	2 439	57	2 459	77	2 479
18	2 420	38	2 440	58	2 460	78	2 480
19	2 421	39	2 441	59	2 461	-	-

2. METHODOLOGY

FCC KDB 558074 D01 DTS Measurement Guidance v05r02 dated April 2nd, 2019 entitled “Guidance for Performing Compliance Measurements on Digital Transmission Systems, Frequency Hopping Spread Spectrum System, and Hybrid System Devices Operating Under Section 15.247 of the FCC Rules” and the measurement procedures described in ANSI C63.10 (Version: 2020) ‘the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices’.

EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

EUT EXERCISE

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. According to its specifications, the EUT must comply with the requirements of Section 15.207, 15.209 and 15.247 under the FCC Rule Part 15 Subpart C and Section 2.1091 under the FCC Rule Part 2 / the RSS-GEN issue 5 and 2, RSS-247 issue 4.

GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2 of ANSI C63.10. (Version:2020) Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane below 1GHz. Above 1GHz with 1.5m using absorbers between the EUT and receive antenna. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3 m away from the receiving antenna, which varied from 1 m to 4 m to find the highest emission. Also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. To find out the maximum emission, the relative positions of this hand-held transmitter (EUT) were rotated through three orthogonal axes according to the requirements in Section 8 of ANSI C63.10. (Version: 2020)

Conducted Antenna Terminal

KDB 558074 D01 v05r02

DESCRIPTION OF TEST MODES

The EUT has been tested at 2.4GHz ISM test mode. EUT’s test mode was used to control the channels, power setting, continuous TX and normal RX mode. EUT is equipped with 2.4GHz ISM.

3. INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognize national standards. Especially, all antenna for measurement is calibrated in accordance with the requirements of C63.5 (Version: 2017).

4. FACILITIES AND ACCREDITATIONS

FACILITIES

HCT America, Inc. holds A2LA accreditation (certificate no. 4201.01) covering all testing included in the scope of this report. All tests were conducted at the facilities listed below.

	Address	ISED CABID	ISED Company Number	FCC Registration	FCC Designation Number
☒	840 Yosemite Way, Milpitas, CA 95035 USA	US0198	25729	898494	US01202
☐	1177 Comstock Road, Hollister, CA 95023 USA	US0198	25729	898494	US01202



EQUIPMENT

Radiated emissions are measured with one or more of the following types of Linearly polarized antennas: tuned dipole, bi-conical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers. Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5. ANTENNA REQUIREMENTS

According to FCC 47 CFR §15.203:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

- (1) The antenna of this E.U.T is permanently attached and there is no provision for connection to an external antenna.
- (2) The E.U.T Complies with the requirement of §15.203

According to RSS-Gen Issue 5 and 2 (Section 6.8):

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotopically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

6. MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.10-2020.


All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95 % level of confidence. The measurement data shown herein meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Parameter	Expanded Uncertainty
Output Power, Conducted	$\pm 0.54 \text{ dB}$
Frequency Tolerance	$\pm 16.78 \text{ kHz}$
Occupied Bandwidth	$\pm 120.66 \text{ kHz}$
Unwanted Emissions, Conducted	$\pm 0.54 \text{ dB}$
Radiated Emissions (below 1 GHz)	$\pm 5.29 \text{ dB}$
Radiated Emissions (Above 1 GHz)	$\pm 4.29 \text{ dB}$

7. DESCRIPTION OF TESTS

7.1. 20 dB BANDWIDTH / 99% OCCUPIED BANDWIDTH

TEST SETUP



TEST PROCEDURE (20 dB Bandwidth)

The transmitter output is connected to the Spectrum Analyzer.
(Procedure Section 6.9.2 in ANSI C63.10-2020)

The Spectrum Analyzer Setting:

- RBW = 1% ~ 5% of 20 dB bandwidth
- VBW $\cong$ 3 x RBW
- Span: 2-5 times the 20 dB bandwidth, centered on the hopping channel
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Used the automatic bandwidth measurement capability of a spectrum analyzer, setting X dB as 20 dB.

TEST PROCEDURE (99% Bandwidth)

The transmitter output is connected to the Spectrum Analyzer.
(Procedure Section 6.9.3 in ANSI C63.10-2020)

- RBW = 1% ~ 5% of the occupied bandwidth
- VBW $\cong$ 3 x RBW
- Detector = Peak
- Trace mode = Max hold
- Sweep = Auto couple
- Allow the trace to stabilize
- Used the automatic bandwidth measurement capability of a spectrum analyzer.

Note:

Occupied bandwidth profile installed on the spectrum analyzer was used during measurement.

7.2. OUTPUT POWER

LIMIT


§15.247(b)(1)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels: 1 W

RSS-247 Issue 4, Section 6.2.3.2(1)

For FHSS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the host uses 75 or more hopping channels. The e.i.r.p. shall not exceed 4 W.

TEST SETUP



TEST PROCEDURE

The EUT is connected to the Spectrum Analyzer. Hopping mode shall be disabled.

Use the following Spectrum Analyzer setting:
(Procedure Section 7.8.5 in ANSI C63.10-2020)

- RBW $\geq$ 20 dB Bandwidth
- VBW $\geq$ RBW
- SPAN = Approximately 5 x RBW
- Detector Mode = Peak
- Sweep = Auto couple
- Trace Mode = Max hold
- Allow trace to fully stabilize.
- Use marker-to-peak function to determine the peak emission level

Note:

Sample Calculation

- Conducted Output Power (Peak) = Reading Value + ATT loss + Cable loss


7.3. NUMBER OF HOPPING CHANNELS

LIMIT

§15.247(a)(1)(iii) / RSS-247 Issue 4, Section 6.2.3.1(2)

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

TEST SETUP



TEST PROCEDURE

The transmitter output is connected to the Spectrum Analyzer.
(Procedure 7.8.3 in ANSI C63.10-2020)

- $RBW \leq 30\%$ of the channel spacing or the 20 dB bandwidth, whichever is smaller
- $VBW = 8 \text{ MHz}$ ($\geq RBW$)
- $SPAN$ = Frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans to allow the individual channels to be clearly seen.
- Sweep = Auto.
- Detector = Peak.
- Trace mode = Max hold.
- Allow the trace to stabilize.


7.4. CARRIER FREQUENCY SEPARATION

LIMIT

§15.247(a)(1) / RSS-247 Issue 4, Section 6.2.3.1(1)

For the frequency hopping systems operated in 2400 MHz~2483.5 MHz may have the hopping channel carrier frequencies separated by 25 kHz or two thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power less than or equal to 125 mW.

TEST SETUP



TEST PROCEDURE

The EUT output shall be in hopping mode and connected to the Spectrum Analyzer.

Use the following spectrum analyzer setting:
(Procedure 7.8.2 in ANSI C63.10-2020)

- RBW = Start with approximately 30% of the channel spacing; Then adjust as needed to best identify of each individual channel.
- VBW $\geq$ RBW.
- SPAN = Wide enough to capture two adjacent peaks.
- Sweep = Auto coupled.
- Detector = Peak.
- Trace mode = Max hold.
- Allow the trace to stabilize.


7.5. TIME OF OCCUPANCY (DWELL TIME)

LIMIT

§15.247(a)(1)(iii) / RSS-247 Issue 4 Section 6.2.3.1(2)

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

TEST SETUP



TEST PROCEDURE

The EUT output shall be in hopping mode and connected to the Spectrum Analyzer.

Use the following spectrum analyzer setting:
(Procedure 7.8.4 in ANSI C63.10-2020)

- $RBW \leq \text{Channel spacing}$ and where possible, RBW should be set $\gg 1/T$, where T is the expected dwell time per channel.
- $VBW \geq RBW$.
- Span = Zero span, centered on a hopping channel.
- Sweep = As needed to capture entire dwell time per hopping channel (Use video trigger and trigger delay for the transmitted signal to better show the plot little after start). Second plot might be needed with longer sweep time to show two successive hops on a channel
- Detector = Peak.
- Trace mode = Max hold.

Use the marker-delta function to determine transmit time per hop. Repeat the test for each different mode of operation.

Note:

Sample Calculation

No of hops specified in the requirement

- No of hops on spectrum analyzer x (period specified in the requirement / sweep time on SA)

Dwell Time (s)

- Transmit time per hops x No of hops specified in the requirement

7.6. CONDUCTED BAND EDGE / CONDUCTED SPURIOUS EMISSIONS


LIMIT

§15.247(d) / RSS-247 Issue 4, Section 6.6

The maximum conducted (peak) output power was used to demonstrate compliance, then the peak power in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz.

[Conducted > 20 dBc]

TEST SETUP



TEST PROCEDURE

The transmitter output port is connected to the spectrum analyzer.
(Procedure 7.8.6 and 7.8.8 in ANSI C63.10-2020)

- RBW = 100 kHz
- VBW = 300 kHz
- Set span to encompass the spectrum to be examined
- Detector = Peak
- Trace Mode = max hold
- Sweep time = auto couple
- Ensure that the number of measurement points $\geq 2 \cdot \text{Span} / \text{RBW}$
- Allow trace to fully stabilize.
- Use peak marker function to determine the maximum amplitude level.

Measurements are made from 30 MHz to ten times operating frequency in GHz for the lowest, middle, and highest channels.

7.6. RADIATED EMISSIONS

RADIATION EMISSION LIMIT

FCC: 47 CFR § 15.209		
Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

ISED: RSS-GEN Section 8.9		
Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	6.37/F(kHz)	300
0.490 – 1.705	63.7/F(kHz)	30
1.705 – 30	0.08	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

RECEIVER RADIATED EMISSION LIMIT

ISED: RSS-GEN Section 7.3		
Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3


RESTRICTED BANDS OF OPERATION

FCC: 47 CFR § 15.205(a)				
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
0.090 - 0.110	12.29 - 12.293	149.9 - 150.05	1660.0 - 1710.0	8025 - 8500
0.495 - 0.505	12.51975 - 12.52025	156.52475 - 156.52525	1718.8 - 1722.2	9000 - 9200
2.1735 - 2.1905	12.57675 - 12.57725	156.7 - 156.9	2200.0 - 2300.0	9300 - 9500
4.125 - 4.128	13.36 - 13.41	162.0125 - 167.17	2310.0 - 2390.0	10600 - 12700
4.17725 - 4.17775	16.42 - 16.423	167.72 - 173.2	2483.5 - 2500.0	13250 - 13400
4.20725 - 4.20775	16.69475 - 16.69525	240.0 - 285.0	2690.0 - 2900.0	14470 - 14500
6.215 - 6.218	16.80425 - 16.80475	322.0 - 335.4	3260.0 - 3267.0	15350 - 16200
6.26775 - 6.26825	25.5 - 25.67	399.9 - 410.0	3332.0 - 3339.0	17700 - 21400
6.31175 - 6.31225	37.5 - 38.25	608.0 - 614.0	3345.8 - 3358.0	22010 - 23120
8.291 - 8.294	73 - 74.6	960.0 - 1240.0	3600.0 - 4400.0	23600 - 24000
8.362 - 8.366	74.8 - 75.2	1300.0 - 1427.0	4500.0 - 5150.0	31200 - 31800
8.37625 - 8.38675	108 - 121.94	1435.0 - 1626.5	5350.0 - 5460.0	36430 - 36500
8.41425 - 8.41475	123 - 138	1645.5 - 1646.5	7250.0 - 7750.0	Above 38600


ISED: RSS-GEN Section 8.10				
Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)	Frequency (MHz)
0.090 - 0.110	8.37625 - 8.38675	108 - 138	1660 - 1710	8025 - 8500
0.495 - 0.505	8.41425 - 8.41475	149.9 - 150.05	1718.8 - 1722.2	9000 - 9200
2.1735 - 2.1905	12.29 - 12.293	156.52475 - 156.52525	2200 - 2300	9300 - 9500
3.020 - 3.026	12.51975 - 12.52025	156.7 - 156.9	2310 - 2390	10600 - 12700
4.125 - 4.128	12.57675 - 12.57725	162.0125 - 167.17	2483.5 - 2500	13250 - 13400
4.17725 - 4.17775	13.36 - 13.41	167.72 - 173.2	2655 - 2900	14470 - 14500
4.20725 - 4.20775	16.42 - 16.423	240 - 285	3260 - 3267	15350 - 16200
5.677 - 5.683	16.69475 - 16.69525	322 - 335.4	3332 - 3339	17700 - 21400
6.215 - 6.218	16.80425 - 16.80475	399.9 - 410	3345.8 - 3358	22010 - 23120
6.26775 - 6.26825	25.5 - 25.67	608 - 614	3500 - 4400	23600 - 24000
6.31175 - 6.31225	37.5 - 38.25	960 - 1427	4500 - 5150	31200 - 31800
8.291 - 8.294	73 - 74.6	1435 - 1626.5	5350 - 5460	36430 - 36500
8.362 - 8.366	74.8 - 75.2	1645.5 - 1646.5	7250 - 7750	Above 38600

TEST SETUP


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (BELOW 30 MHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The loop antenna was placed at a location 3m from the EUT
3. The EUT is placed on a turntable, which is 0.8m above ground plane.
4. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
5. The turntable shall be rotated to 360 degrees to determine the position of maximum emission level.
6. Distance Correction Factor (0.009 MHz – 0.490 MHz) = $40 \cdot \log(3 \text{ m}/300 \text{ m}) = -80 \text{ dB}$
Measurement Distance: 3 m
7. Distance Correction Factor (0.490 MHz – 30 MHz) = $40 \cdot \log(3 \text{ m}/30 \text{ m}) = -40 \text{ dB}$
Measurement Distance: 3 m
8. Spectrum Setting
 - Frequency Range = 9 kHz ~ 30 MHz
 - Detector = Peak
 - Trace = Max hold
 - RBW = 9 kHz
 - VBW $\geq 3 \cdot \text{RBW}$
9. Total = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L)
10. There is a comparison data both open-field test site and alternative test site – semi-Anechoic chamber according to 414788 D01. And the results are properly calibrated.

TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (30 MHz – 1 GHz)

1. The EUT was placed on a non-conductive table located on semi-anechoic chamber.
2. The EUT is placed on a turntable, which is 0.8 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated to 360 degrees to determine the position of maximum emission level.
5. Spectrum Setting

(1) Measurement Type (Peak):

- Measured Frequency Range: 30 MHz – 1 GHz
- Detector = Peak
- Trace = Max hold
- RBW = 100 kHz
- VBW $\geq 3 \cdot \text{RBW}$

(2) Measurement Type(Quasi-peak):

- Measured Frequency Range: 30 MHz – 1 GHz
- Detector = Quasi-Peak
- RBW = 120 kHz

6. Total = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L)

TEST PROCEDURE OF RADIATED SPURIOUS EMISSION (ABOVE 1 GHz)

1. The EUT is placed on a turntable, which is 1.5 m above ground plain.
2. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
3. The turntable shall be rotated to 360 degrees to determine the position of maximum emission level.
4. EUT is set 3 m away from the receiving antenna, which varies from 1m to 4m to reach the highest emissions.
5. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting

(1) Measurement Type (Peak):

- Measured Frequency Range: 1 GHz – 25 GHz
- Detector = Peak
- Trace = Max hold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$

- Measured Frequency Range: 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range: 1 GHz – 25 GHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factors should be added to the measurement results prior to comparing them to the emission limit to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
- Duty Cycle Factor (dB): Please refer to the please refer to section 9.1.

10. Measurement value only up to 6 maximum emissions noted or would be lesser if no specific emissions from the EUT are recorded (*i.e.*: margin > 20 dB from the applicable limit) and considered that is already beyond the background noise floor.

11. Sample Calculation

- (1) Total (Peak) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L) - Amp Gain(G)
- (2) Total (Average, Duty $\geq 98\%$) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L) - Amp Gain(G)
- (3) Total (Average, Duty $< 98\%$) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L) - Amp Gain(G) + Duty Cycle Factor
- (4) Alternative Method: Total (Average) = Total (Peak) + 20 log (Duty Cycle)

TEST PROCEDURE OF RADIATED RESTRICTED BAND EDGE

1. Radiated test is performed with hopping off (if there is any)
2. The EUT is placed on a turntable, which is 1.5 m above ground plane.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.
4. The turntable shall be rotated to 360 degrees to determine the position of maximum emission level.
5. EUT is set 3 m away from the receiving antenna, which varies from 1m to 4m to find out the highest emissions.
6. Each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
7. The unit was tested with its standard battery.
8. Spectrum Setting

(1) Measurement Type (Peak):

- Detector = Peak
- Trace = Max hold
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW

(2) Measurement Type(Average): Duty cycle $\geq 98\%$,

- Measured Frequency Range: 2310 MHz – 2390 MHz / 2483.5 MHz – 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).

(3) Measurement Type(Average): Duty cycle $< 98\%$, duty cycle variations are less than $\pm 2\%$

- Measured Frequency Range: 2310 MHz – 2390 MHz / 2483.5 MHz – 2500 MHz
- Detector = RMS
- Averaging type = power (*i.e.*, RMS)
- RBW = 1 MHz
- VBW $\geq 3 \times$ RBW
- Sweep time = auto.
- Trace mode = average (at least 100 traces).
- Correction factors should be added to the measurement results prior to comparing them to the emission limit to compute the emission level that would have been measured had the test been performed at 100 % duty cycle.
- Duty Cycle Factor (dB): Please refer to the please refer to section 9.1.

9. Measurement value only up to 6 maximum emissions noted or would be lesser if no specific emissions from the EUT are recorded (*i.e.*: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.

10. Sample Calculation

- (1) Total (Peak) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L)
- (2) Total (Average, Duty $\geq 98\%$) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L) - Amp Gain(G)
- (3) Total (Average, Duty $< 98\%$) = Reading Value + Antenna Factor (A.F) + Cable Loss (C.L) - Amp Gain(G) + Duty Cycle Factor

7.7. AC POWER LINE CONDUCTED EMISSIONS

LIMIT

47 CFR § 15.207, RSS-GEN Section 8.8

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

*Decreases with the logarithm of the frequency.

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

TEST SETUP

See test photographs attached in Annex A for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is situated on a wooden table 80 cm above the reference ground plain.
2. EUT is connected via LISN to test power supply.
3. The measurement results are obtained as described below:
4. Detectors: Quasi Peak and Average Detector.

According to FCC KDB 174176 D01 Line Conducted FAQ v01r01:

Devices Operating Above 30 MHz

For a device with a permanent or detachable antenna operating above 30 MHz, measurements must be performed with the antenna connected as specified in clause 6.2 of ANSI C63.10-2020.

Devices Operating Below 30 MHz

For a device with a permanent or detachable antenna operating at or below 30 MHz, the FCC will accept measurements performed with a suitable dummy load in lieu of the antenna under the following conditions:

- (1) Perform the AC powerline conducted tests with the antenna connected to determine compliance with Section 15.207 limits outside the transmitter's fundamental emission band;
- (2) Retest with a dummy load in lieu of the antenna to determine compliance with Section 15.207 limits within the transmitter's fundamental emission band. For a detachable antenna, remove the antenna and connect a suitable dummy load to the antenna connector. For a permanent antenna, remove the antenna and terminate the RF output with a dummy load or network which simulates the antenna in the fundamental frequency band. All measurements must be performed as specified in clause 6.2 of ANSI C63.10-2020.

Sample Calculation

Quasi-peak (Final Result) = Reading Value + Correction Factor

8. SUMMARY OF TEST RESULTS

Test Description	FCC Part Section(s)	ISED Part Section(s)	Test Limit	Test Condition	Test Result
20 dB Bandwidth	§15.247(a)(1)	RSS-247, 6.2.1(a)	-	Conducted	PASS
Occupied Bandwidth	-	RSS-GEN, 6.7	-		PASS
Conducted Maximum Peak Output Power	§15.247(b)(1)	RSS-247, 6.2	≤ 1.0 W (channels ≥ 75)		PASS
Maximum e.i.r.p.	-	RSS-247, 6.2	≤ 4 W e.i.r.p. (channels ≥ 75)		PASS
Number of Hopping Channels	§15.247(a)(1)(iii)	RSS-247, 6.2	channels ≥ 15		PASS
Carrier Frequency Separation	§15.247(a)(1)	RSS-247, 6.2	≥ 25 kHz or 2/3 of 20dB BW ¹⁾ Whichever is greater		PASS
Time of Occupancy	§15.247(a)(1)(iii)	RSS-247, 6.2	≤ 0.4 s (within 0.4 s period)		PASS
Conducted Band Edge Conducted Spurious Emission	§15.247(d)	RSS-247, 6.6	≥ 20 dBc		PASS
AC Power line Conducted Emissions	§15.207	RSS-GEN, 8.8	cf. Section 7.8		PASS
Radiated Spurious Emissions	§15.209(a) §15.205(a)	RSS-GEN, 8.9 RSS-GEN, 8.10	cf. Section 7.7	Radiated	PASS

Note:

- 2/3 of the 20 dB BW, which is greater than 25 kHz, was used as the limit in this report since the peak output power did not exceed 125 mW.

WORST CASE CONFIGURATION

RADIATED TEST

1. EUT Axis

All X, Y, and Z positions for horizontal / vertical antenna polarization were investigated to find the worst-case position. Z position was selected for the final evaluation.


CONDUCTED TEST

1. AC line conducted emission test was performed at the worst-case channel

OUTPUT POWER SETTING

The output is preset as declared by the manufacturer

TEST CONFIGURATION



LIST OF SUPPORT EQUIPMENT

Equipment Type	Model No.	Serial No.	Manufacturer	Qty	Note
AC adaptor	C210001	ICES-003	eero LLC	1	

9. TEST RESULT

9.1. 20 dB BANDWIDTH


BR (GFSK)		99% Bandwidth (kHz)	20 dB Bandwidth (MHz)	
Frequency (MHz)	Channel	Result	Result	Limit
2 402	0	982.84	1.045	
2 441	39	965.14	1.046	
2 480	78	954.77	1.042	

EDR ($\pi/4$ -DQPSK)		99% Bandwidth (MHz)	20 dB Bandwidth (MHz)	
Frequency (MHz)	Channel	Result	Result	Limit
2 402	0	1.2117	1.356	
2 441	39	1.1741	1.254	
2 480	78	1.1602	1.252	


EDR (8DPSK)		99% Bandwidth (MHz)	20 dB Bandwidth (MHz)	
Frequency (MHz)	Channel	Result	Result	Limit
2 402	0	1.1880	1.257	
2 441	39	1.1803	1.253	
2 480	78	1.1668	1.253	

TEST PLOTS


BR (GFSK): 20 dB BW / OBW (CH0)



EDR ($\pi/4$ -DQPSK): 20 dB BW / OBW (CH0)




BR (GFSK): 20 dB BW / OBW (CH39)



EDR ($\pi/4$ -DQPSK): 20 dB BW / OBW (CH39)



BR (GFSK): 20 dB BW / OBW (CH78)



EDR ($\pi/4$ -DQPSK): 20 dB BW / OBW (CH78)



TEST PLOTS

EDR (8DPSK): 20dB BW / OBW (CH0)



EDR (8DPSK): 20dB BW / OBW (CH39)



EDR (8DPSK): 20dB BW / OBW (CH78)



9.2. OUTPUT POWER


Peak Power

BR (GFSK)			Test Result
Frequency (MHz)	Channel No.	Measured Power (dBm)	Limit (dBm)
2 402	0	6.81	30
2 441	39	8.32	30
2 480	78	9.05	30

EDR ($\pi/4$ -DQPSK)			Test Result
Frequency (MHz)	Channel No.	Measured Power (dBm)	Limit (dBm)
2 402	0	8.40	30
2 441	39	8.85	30
2 480	78	9.63	30


EDR (8DPSK)			Test Result
Frequency (MHz)	Channel No.	Measured Power (dBm)	Limit (dBm)
2 402	0	6.29	30
2 441	39	7.73	30
2 480	78	8.58	30

TEST PLOTS



TEST PLOTS

EDR (8DPSK): Output Power (CH0)



EDR (8DPSK): Output Power (CH39)



EDR (8DPSK): Output Power (CH78)



Note:

1. To simplify the report, attached plots were only Peak power.

9.3. NUMBER OF HOPPING CHANNELS


BR (GFSK)		Test Result	
Frequency Range (MHz)	No. of Channels	Limit	Result
2 402 – 2 480	79	≥ 15	Compliant

EDR ($\pi/4$ -DQPSK)		Test Result	
Frequency Range (MHz)	No. of Channels	Limit	Result
2 402 – 2 480	79	≥ 15	Compliant


EDR (8DPSK)		Test Result	
Frequency Range (MHz)	No. of Channels	Limit	Result
2 402 – 2 480	79	≥ 15	Compliant

TEST PLOTS

BR (GFSK): Number of Hopping Channels



EDR ($\pi/4$ -DQPSK): Number of Hopping Channels



EDR (8DPSK): Number of Hopping Channels



9.4. CARRIER FREQUENCY SEPARATION

Mode	Test Result	
	Separation (kHz)	Limit (kHz) ¹⁾
BR (GFSK)	978.0	≥0.894
EDR ($\pi/4$ -DQPSK)	1121.0	≥0.7
EDR (8DPSK)	994.0	≥0.879

Note:

1. 2/3 of the highest 20 dB in each channel was used as the limit since it is greater than 25 kHz and the peak output power did not exceed 0.125 W.

TEST PLOTS



9.5. TIME OF OCCUPANCY


Mode	Data Rate	Frequency (MHz)	Pulse Time (ms)	No of Hops	Dwell Time (ms)	Limit (ms)
BR (GFSK)	1-DH5	2 441	2.87	106.6	305.942	≤ 400
EDR ($\pi/4$ -DQPSK)	2-DH5	2 441	2.88	106.6	307.008	≤ 400
EDR (8DPSK)	3-DH5	2 441	2.87	106.6	305.942	≤ 400

Note:


1. Max permitted DH5 packet: $1600 / 79 / 6 = 3.37$ hops/sec on each channel.
2. Number of hops within 31.6 seconds = $3.37 \text{ hops/sec} \times 31.6 \text{ sec} = 106.6$ hops
3. Time of Occupancy (Dwell Time) = Pulse Time x Number of Hops within 31.6 seconds.

TEST PLOTS


BR (GFSK): 1-DH5



EDR ($\pi/4$ -DQPSK): 2-DH5




EDR (8DPSK): 3-DH5



9.6. CONDUCTED BAND EDGE & SPURIOUS EMISSIONS

TEST PLOTS




TEST PLOTS



TEST PLOTS

Conducted Spurious Emission


EDR (8DPSK): (CH0)



EDR (8DPSK): (CH39)



EDR (8DPSK): (CH78)



Note:

1. The worst-case plots are included in this report.

9.7. RADIATED SPURIOUS EMISSIONS

Frequency Range: 9 kHz ~ 30 MHz

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
All emissions were at least 20dB below the applicable limit, therefore detailed data is not reported.							

Note(s):

1. The Measured value of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
2. Distance extrapolation factor = $40\log(\text{specific distance} / \text{test distance})$ (dB)
3. Limit line = specific Limits (dBuV) + Distance extrapolation factor

Frequency Range: Below 1 GHz

Frequency (MHz)	Polarization	Reading (dBuV)	Corr. ¹⁾ (dB)	Total (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Measurement Type
All emissions were at least 20dB below the applicable limit, therefore detailed data is not reported.							

Note(s):

1. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.

Frequency Range: Above 1 GHz

Band	Test Mode	Test Frequency (MHz)	Frequency (MHz)	PK Level	PK Limit	PK Margin	AV Level	AV Limit	AV Margin	Factor	Polarization
BT	BR (GFSK)	2402	4800.03	41.68	74	32.32	29.19	54	24.81	-16.67	H
			4804.23	42.72	74	31.28	31.08	54	22.92	-16.75	V
			7201.18	45.41	74	28.59	34.22	54	19.78	-10.47	H
			7201.52	46.77	74	27.23	34.02	54	19.98	-10.68	V
		2441	4,881.94	42.42	74	31.58	31.36	54	22.64	-16.23	H
			4,882.22	43.76	74	30.24	33.49	54	20.51	-16.31	V
			7,322.72	46.38	74	27.62	34.09	54	19.91	-10.49	V
			7,323.84	46.1	74	27.9	34.25	54	19.75	-10.34	H
		2480	4,960.23	42.83	74	31.17	31.45	54	22.55	-15.99	V
			4,961.33	42	74	32	29.99	54	24.01	-15.91	H
			7,435.21	45.27	74	28.73	33.88	54	20.12	-10.84	V
			7,449.31	45.34	74	28.66	33.97	54	20.03	-10.62	H
	EDR ($\pi/4$ -DQPSK)	2402	4803.70	42.27	74	31.73	30.63	54	23.37	-16.76	V
			4804.52	41.1	74	32.9	29.53	54	24.47	-16.64	H
			7205.83	46.21	74	27.79	34.24	54	19.76	-10.44	H
			7,206.87	46.13	74	27.87	34.05	54	19.95	-10.65	V
		2441	4,881.71	43.34	74	30.66	32.73	54	21.27	-16.24	H
			4,885.57	41.44	74	32.56	29.7	54	24.3	-16.27	V
			7,323.11	45.82	74	28.18	34.11	54	19.89	-10.48	V
			7,324.46	46.29	74	27.71	34.3	54	19.7	-10.33	H
		2480	4,954.57	42.25	74	31.75	29.85	54	24.15	-16.06	V
			4,964.52	41.85	74	32.15	30	54	24	-15.9	H
			7,437.58	46.15	74	27.85	33.84	54	20.16	-10.86	V
			7,439.90	45.65	74	28.35	34.03	54	19.97	-10.67	H
	EDR (8DPSK)	2402	4800.89	41.29	74	32.71	29.1	54	24.9	-16.74	V
			4803.66	40.83	74	33.17	29.27	54	24.73	-16.67	H
			7204.93	46.21	74	27.79	34.18	54	19.82	-10.41	H
			7,207.97	45.64	74	28.36	33.95	54	20.05	-10.65	V
		2441	4,881.88	45.16	74	28.84	32.84	54	21.16	-16.32	V
			4,884.75	41.79	74	32.21	29.78	54	24.22	-16.2	H
			7,325.59	46.63	74	27.37	34.33	54	19.67	-10.34	H
			7,326.73	45.99	74	28.01	34.19	54	19.81	-10.53	V
		2480	4,959.80	44.53	74	29.47	32.81	54	21.19	-15.99	V
			4,960.52	42.32	74	31.68	30.37	54	23.63	-15.92	H
			7,436.09	45.58	74	28.42	34.22	54	19.78	-10.57	H
			7,441.06	46.22	74	27.78	33.93	54	20.07	-10.85	V

Note(s):

1. Correction Factor: Antenna Factor + Cable loss + Preamplifier Gain.
2. All modes of operation were investigated, and the worst-case configuration results are reported in this section.
3. The Duty Factor is applied only to the harmonic components.

TEST PLOTS




Note(s):


1. The worst-case plot is included in this report.

■ TEST PLOTS

Radiated Spurious Emission 1 GHz – 3 GHz: EDR 8DPSK (CH 78)




Radiated Spurious Emission 3 GHz – 18 GHz: EDR 8DPSK (CH 78)



Note:

1. The worst-case plot is included in this report.

▣ TEST PLOTS




Note:

1. There were no major peaks, and representative plots are included in this report
2. The plots include all used factor values for cables, antenna, preamplifier, etc.

9.8. RADIATED RESTRICTED BAND EDGES

Band	Test Mode	Test Frequency (MHz)	Frequency (MHz)	PK Level	PK Limit	PK Margin	AV Level	AV Limit	AV Margin	Factor	Polarization
BT Low Band-Edge	BR (GFSK)	2402	2389.91	51.03	74.00	22.97	35.45	54.00	18.55	-8.35	H
			2389.51	50.83	74.00	23.17	35.06	54.00	18.94	-8.39	V
	EDR ($\pi/4$ -DQPSK)	2402	2389.74	51.01	74.00	22.99	35.36	54.00	18.64	-8.36	H
			2389.85	51.48	74.00	22.52	35.04	54.00	18.96	-8.38	V
	EDR (8DPSK)	2402	2389.79	51.41	74.00	22.59	35.09	54.00	18.91	-8.36	H
			2389.44	50.93	74.00	23.07	35.09	54.00	18.91	-8.39	V
BT High Band-Edge	BR (GFSK)	2480	2483.51	52.24	74.00	21.76	37.69	54.00	16.31	-7.84	H
			2483.57	52.52	74.00	21.48	36.95	54.00	17.05	-7.83	V
	EDR ($\pi/4$ -DQPSK)	2480	2483.51	52.92	74.00	21.08	37.28	54.00	16.72	-7.84	H
			2483.53	52.28	74.00	21.72	37.12	54.00	16.88	-7.83	V
	EDR (8DPSK)	2480	2483.59	53.30	74.00	20.70	37.30	54.00	16.70	-7.84	H
			2483.54	51.79	74.00	22.21	36.59	54.00	17.41	-7.83	V

TEST PLOTS



9.9 POWERLINE CONDUCTED EMISSIONS

Frequency (MHz)	Line	Reading (dBμV)		Corr. ¹⁾ (dB)	Level (dBμV)		Limit (dBμV)		Margin (dB)	
		QP	CAV		QP	CAV	QP	CAV	QP	CAV
0.459	N	11.5	6.6	9.6	21.1	16.2	56.7	46.7	35.6	30.5
0.361	N	8.6	3.6	9.6	18.2	13.2	58.7	48.7	40.5	35.5
0.346	N	8.0	2.8	9.6	17.6	12.4	59.1	49.1	41.5	36.7
3.576	N	10.2	4.6	9.8	20.0	14.4	56	46	36.0	31.6
0.717	N	8.9	3.0	9.6	18.5	12.6	56	46	37.5	33.4
2.401	N	9.2	3.7	9.7	18.9	13.4	56	46	37.1	32.6
8.481	N	13.8	8.0	10.0	23.8	18.0	60	50	36.2	32.0
8.985	N	13.7	7.9	10.1	23.8	18.0	60	50	36.2	32.0
20.482	N	11.6	6.8	10.4	22.0	17.2	60	50	38.0	32.8


Frequency (MHz)	Line	Reading (dBμV)		Corr. ¹⁾ (dB)	Level (dBμV)		Limit (dBμV)		Margin (dB)	
		QP	CAV		QP	CAV	QP	CAV	QP	CAV
0.458	L1	14.3	9.3	9.6	23.9	18.9	56.7	46.7	32.8	27.8
0.213	L1	9.4	5.0	9.6	19.0	14.6	63.1	53.1	44.1	38.5
0.167	L1	9.6	4.8	9.6	19.2	14.4	65.1	55.1	45.9	40.7
2.079	L1	12.3	7.4	9.7	22.0	17.1	56	46	34.0	28.9
3.639	L1	12.5	7.3	9.8	22.3	17.1	56	46	33.7	28.9
1.534	L1	12.2	7.4	9.7	21.9	17.1	56	46	34.1	28.9
7.403	L1	14.9	9.9	10.0	24.9	19.9	60	50	35.1	30.1
8.689	L1	14.5	9.0	10.0	24.5	19.0	60	50	35.5	31.0
6.922	L1	14.5	8.9	10.0	24.5	18.9	60	50	35.5	31.1

Note :


1. Quasi-peak (Final Result) = Reading Value + Correction Factor

■ TEST PLOTS

AC Line Conducted Emission (L1)



AC Line Conducted Emission (N)



10. LIST OF TEST EQUIPMENT

No.	Instrument	Model No.	Calibration Due (mm/dd/yy)	Manufacture	Serial No.
☒	Signal Analyzer (1 Hz ~ 44.0 GHz)	ESW44	08/05/2026	Rohde & Schwarz	103176
☒	Signal Analyzer (20 Hz ~ 26.5 GHz)	N9020A	10/09/2026	Keysight	MY53280148
☒	Attenuator (20 dB, DC ~ 26.5 GHz)	8493C 20 dB	10/14/2026	KEYSIGHT	9072
☒	Loop Antenna (0.009 ~ 30 MHz)	HLA 6121	03/03/2027	TESEQ	43964
☒	BI-LOG Antenna (30 MHz ~ 6 GHz)	JB6	02/27/2027	Sunol	A060916
☒	Horn Antenna (1 GHz ~ 18 GHz)	BBHA 9120 D	07/15/2027	Schwarzbeck	03023
☒	Horn Antenna (15 GHz ~ 40 GHz)	BBHA 9170	01/21/2027	Schwarzbeck	1342
☒	RF Switch Matrix System	HRSMS-VL	01/02/2027	HCT Ltd.	2-51-001
☒	EMI Test Receiver	ESR3	07/18/2026	Rohde & Schwarz	102363
☒	LISN	ENV216	08/28/2026	Rohde & Schwarz	101550
☒	Temperature & Humidity Chamber	SH-662	08/05/2026	ESPEC	93024017
☒	ESR Test Receiver	ESR3	07/18/2026	Rohde & Schwarz	102363
☒	Test Software	R&S*ELEKTRA	-	Rohde & Schwarz	-

Note:

- Equipment listed above that calibrated during the testing period was set for test after the calibration.
- Equipment listed above that has a calibration due date during the testing period, the testing is completed before equipment expiration date.

APPENDIX A. TEST SETUP PHOTOS

The setup photos are provided as a separate document.

APPENDIX B. PHOTOGRAPHS OF EUT

B.1. EXTERNAL PHOTOS

The external photos are provided as a separate document.

B.2. INTERNAL PHOTOS

The internal photos are provided as a separate document.

END OF TEST REPORT