**MEASUREMENT REPORT****FCC PART 15.247 / ISED RSS-247 Bluetooth (Low Energy)****Applicant Name:**

Garmin International Inc.
1200 E. 151st. Street
Olathe, Kansas 66062
United States

Date of Testing:

02/17/2026 - 06/12/2026

Test Report Issue Date:

7/9/2026

Test Site/Location:

Element Materials Technolgy, Morgan Hill, CA, USA

Test Report Serial No.:

1C2605260039-06.IPH

FCC ID:

IPH-05171

IC:

1792A-05171

APPLICANT:

Garmin International Inc.

Application Type:

Certification

Model/HVIN:

A05171

EUT Type:

Portable Digital Transceiver

Max. RF Output Power:

2.793 mW (4.46 dBm) Peak Conducted

Frequency Range:

2402 – 2480 MHz

FCC Classification:

Digital Transmission System (DTS)

FCC Rule Part(s):

Part 15 Subpart C (15.247)

ISED Specification:

RSS-GEN Issue 5 + A1 +2

RSS-247 Issue 4

Test Procedure(s):

ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to
C63.10a:2024, KDB 558074 D01 v05r02

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

RJ Ortanez

Executive Vice President



FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 1 of 62

Revision Summary

Revision	Date	Comments	Revised By
-		Initial Release	WKR0000010305

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 2 of 62

TABLE OF CONTENTS

1	INTRODUCTION	4
1.1	Scope	4
1.2	Element Materials Technology Test Location	4
1.3	Test Facility / Accreditations	4
2	PRODUCT INFORMATION	5
2.1	Equipment Description	5
2.2	Device Capabilities	5
2.3	Antenna Description	6
2.4	Test Configuration	7
2.5	Software and Firmware	7
2.6	EMI Suppression Device(s)/Modifications	7
3	DESCRIPTION OF TESTS	8
3.1	Evaluation Procedure	8
3.2	AC Line Conducted Emissions	8
3.3	Radiated Emissions	9
3.4	Environmental Conditions	9
4	ANTENNA REQUIREMENTS	10
5	MEASUREMENT UNCERTAINTY	11
6	TEST EQUIPMENT CALIBRATION DATA	12
7	TEST RESULTS	13
7.1	Summary	13
7.2	99% Occupied Bandwidth	14
7.3	6 dB Bandwidth	20
7.4	Transmitter Output Power and Max EIRP	26
7.5	Power Spectral Density	29
7.6	Conducted Authorized Band Edge	34
7.7	Conducted Spurious Emissions	39
7.8	Radiated Spurious Emissions – Above 1 GHz	46
7.9	Radiated Spurious Emissions – Below 1 GHz	54
7.10	AC Line-Conducted Emissions	58
8	CONCLUSION	62

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 3 of 62

1 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology located in Morgan Hill, CA 95037, U.S.A.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISED Standards (RSS).
- Element Materials Technology facility is a registered test laboratory with the site description on file with ISED (Wireless Test Lab number 22831) and FCC (Designation Number US1163).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 4 of 62

2 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Garmin Portable Digital Transceiver FCC ID: IPH-05171** and **IC: 1792A-05171**. The data found in this test report was taken with the EUT operating in Bluetooth low energy mode. While in low energy mode, the Bluetooth transmitter hops pseudo-randomly between 40 channels, three of which are “advertising channels”. When the transmitter is hopping only between the three advertising channels, the EUT does not fall under the category of a “hopper” as defined in 15.247(a)(iii) which states that a “frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels.” As operation on only the advertising channels does not qualify the EUT as a hopper, the EUT is certified as a DTS device in this mode. The data found in this report is representative of the device when it transmits on its advertising channels. Typical Bluetooth operation is covered under the DSS report found with this application.

Test Device Serial No.: 3637488121, 3637488182, 3627310943, 3627311023

2.2 Device Capabilities

This device contains the following capabilities:

Multi-band LTE (CAT-M1), Multi-band NTN, Bluetooth (1x, EDR, LE), ANT+, 802.11b/g/n WLAN, NFC

LE1M		LE2M	
Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
37	2402	00	2404
:	:	:	:
17	2440	17	2440
:	:	:	:
39	2480	36	2478

Table 2-1. Bluetooth LE Frequency / Channel Operations

This device is capable of operating in hopping and non-hopping mode. The EUT can hop between 40 different channels in the 2400 – 2483.5 MHz band.

This device supports simultaneous transmission operations, which allows multiple transmitters to transmit simultaneously on the same antenna. The table below shows all configurations possible.

Simultaneous Tx Config	Bluetooth 2.4 GHz	WLAN	LTE / NTN		
	BDR, EDR, LE, ANT+	802.11 b/g/n	LB	MB/HB	UHB
Config 1	✓	✗	✗	✓	✗
Config 2	✓	✗	✓	✗	✗

Table 2-2. Simultaneous Transmission Configurations

✓ = Support; ✗ = Not Support

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 5 of 62

Note:

All the above simultaneous transmission configurations have been tested and the worst-case configuration was found to be Config 1 and reported in RF Part 27a test reports.

Mode	Data Rate	Modulation	Bandwidth (MHz)
LE1M	1Mbps	GFSK	1
LE2M	2Mbps	GFSK	2

Table 2-3. . Bluetooth LE Configuration

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8 MHz, VBW = 50 MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2020. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

BLE Mode	Duty Cycle [%]	DCCF [dB]
LE1M	100	N/A
LE2M	100	N/A

Table 2-4. Measured Duty Cycles

2.3 Antenna Description

Following antennas gains provided by manufacturer were used for testing. The validity of the calculated results is based on the accuracy of the information provided.

Frequency [GHz]	Antenna Gain (dBi)
2.4	-2.12

Table 2-5. Highest Antenna Gain

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 6 of 62

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2020 and KDB 558074 D01 v05r02. ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6 and 7.7 for antenna port conducted emissions test setups.

For emissions from 1 GHz – 18 GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1 GHz and above 18 GHz were tested with the highest transmitting power and the worst case channel were reported.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1 GHz, following configuration were investigated and the worst case was reported.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger

EUT was configured to be operated at a 100% duty cycle using software provided by the customer.

2.5 Software and Firmware

The test was conducted with firmware version 5.16 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 7 of 62

3 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7 m x 3.66 m x 2.7 m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1 m x 1.5 m wooden table 80 cm high is placed 40 cm away from the vertical wall and 80 cm away from the sidewall of the shielded room. Two 10 kHz-30 MHz, 50 Ω /50 μ H Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100 dB Attenuation, 14 kHz-18 GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14 kHz – 10 GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40 cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150 kHz to 30 MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10 kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9 kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.10. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 8 of 62

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1 GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1 GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30 MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149 kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3 m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77 dB at 149 kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30 MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1 GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30 MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106 kPa (860-1060 mbar).

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 9 of 62

4 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antenna(s) of the EUT are **permanently attached**.
- There are no provisions for connection to an external antenna.

Conclusion:

The EUT complies with the requirement of §15.203.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 10 of 62

5 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	2.00
Line Conducted Disturbance	1.88
Radiated Disturbance (<30MHz)	4.24
Radiated Disturbance (30MHz - 1 GHz)	4.96
Radiated Disturbance (1 - 18 GHz)	5.18
Radiated Disturbance (>18 GHz)	5.18

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 11 of 62

6 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9020A	MXA Signal Analyzer	7/7/2025	Biennial	7/7/2027	MY56470202
Anritsu	ML2496A	Power Meter	6/27/2025	Annual	6/27/2026	1840005
Anritsu	MA2411B	Pulse Power Sensor	6/27/2025	Annual	6/27/2026	1911105
Anritsu	MA2411B	Pulse Power Sensor	7/3/2025	Annual	7/3/2026	1726261
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/31/2026	Annual	3/31/2027	T058601-02
ETS-Lindgren	3117	Double Ridged Guide Horn (1-18 GHz)	4/21/2026	Annual	4/21/2027	218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2026	Annual	6/10/2027	-
Keysight Technology	N9040B	UXA Signal Analyzer	3/19/2026	Annual	3/19/2027	MY60080210
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/6/2025	Annual	8/6/2026	101639
Rohde & Schwarz	FSW43	Spectrum Analyzer 2Hz to 43GHz	8/5/2025	Annual	8/5/2026	104093
Rohde & Schwarz	ESW44	EMI Test Receiver 2Hz to 44 GHz	3/11/2026	Annual	3/11/2027	101716
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	10/14/2025	Annual	10/14/2026	102328
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	7/3/2025	Annual	7/3/2026	100057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	6/26/2025	Annual	6/26/2026	100519
Rohde & Schwarz	ENV216	Two-Line V-Network	8/18/2025	Annual	8/18/2026	101363
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	7/17/2025	Annual	7/17/2026	00302

Table 6-1. Test Equipment List

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- * denotes passive equipment that have been internally verified/calibrated.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 12 of 62

7 TEST RESULTS

7.1 Summary

Company Name: Garmin International Inc.
 FCC ID: IPH-05171
 IC: 1792A-05171
 FCC Classification: Digital Transmission System (DTS)
 Number of Channels: 40

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
15.247(a)(2)	RSS-247 [6.3.1(a)]	6 dB Bandwidth	> 500 kHz	CONDUCTED	PASS	Section 7.3
2.1049	RSS-Gen [6.7]	99% Occupied Bandwidth	N/A		N/A	Section 7.2
15.247(b)(3)	RSS-247 [6.3.2]	Transmitter Output Power	< 1 Watt		PASS	Section 7.4
15.247(e)	RSS-247 [6.3.1(b)]	Transmitter Power Spectral Density	< 8 dBm / 3kHz Band		PASS	Section 7.5
15.247(d)	RSS-247 [6.6]	Band Edge / Out-of-Band Emissions	≥ 20 dBc		PASS	Section 7.6, 7.8.2
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Section 7.8, 7.9
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150 kHz – 30 MHz	< FCC 15.207 limits (RSS-Gen [8.8])	LINE CONDUCTED	PASS	Section 7.10

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Conducted Automation," Version 1.5.0.
5. For radiated testing, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.6.1.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 13 of 62

7.2 99% Occupied Bandwidth

§2.1049; RSS-Gen [6.7]

Test Overview and Limit

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.8.2 Option 2

KDB 558074 D01 v05r02 – Section 8.2

RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Span = between 1.5x to 5x the OBW
3. RBW = in the range of 1- 5% of the OBW
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 14 of 62

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes


1. All supported modulation have been tested on the unit and only worst case configuration is reported.
2. Low, mid and high channels were tested and tabular data has been reported.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 15 of 62

Frequency [MHz]	Data Rate [Mbps]	Channel	Measured 99% Occupied Bandwidth [MHz]
2402	1.0	37	1.384
2440	1.0	17	1.316
2480	1.0	39	1.300
2404	2.0	0	2.781
2440	2.0	17	2.744
2478	2.0	36	2.710

Table 7-2. 99% OBW Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 16 of 62




Plot 7-1. 99% OBW Plot (Bluetooth (LE), 1Mbps – Ch. 37)



Plot 7-2. 99% OBW Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 17 of 62



Plot 7-3. 99% OBW Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-4. 99% OBW Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 18 of 62



Plot 7-5. 99% OBW Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-6. 99% OBW Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 19 of 62

7.3 6 dB Bandwidth

§15.247(a)(2); RSS-247 [6.3.1(a)]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies. All modes of operation were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to $X = 6$. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 20 of 62

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-2. Test Instrument & Measurement Setup

Test Notes


None

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 21 of 62


Frequency [MHz]	Data Rate [Mbps]	Channel	Measured 6dB Bandwidth [MHz]	Minimum 6dB Bandwidth [MHz]	Pass/Fail
2402	1.0	37	0.825	0.50	Pass
2440	1.0	17	0.801	0.50	Pass
2480	1.0	39	0.810	0.50	Pass
2404	2.0	0	1.638	0.50	Pass
2440	2.0	17	1.605	0.50	Pass
2478	2.0	36	1.637	0.50	Pass

Table 7-3. 6dB BW Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 22 of 62




Plot 7-7.6dB BW Plot (Bluetooth (LE), 1Mbps – Ch. 37)



Plot 7-8. 6dB BW Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 23 of 62



Plot 7-9. 6dB BW Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-10. 6dB BW Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 24 of 62



Plot 7-11.6dB BW Plot (Bluetooth (LE), 2Mbps – Ch. 17)



Plot 7-12.6dB BW Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 25 of 62

7.4 Transmitter Output Power and Max EIRP

§15.247(b)(3); RSS-247 [6.3.2]

Test Overview and Limits

The transmitter antenna terminal of the EUT is connected to the input of a spectrum analyzer. Measurements are made while the EUT is operating at maximum power and at the appropriate frequencies.

The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.9.1.2 PKPM1 Peak Power Method
KDB 558074 D01 v05r02 – Section 8.3.1.3 PKPM1 Peak-reading Power Meter Method
ANSI C63.10-2020 – Subclause 11.9.2.3.2 Method AVGPM-G
KDB 558074 D01 v05r02 – Section 8.3.2.3 Measurement using a Power Meter (PM)

Test Settings

Method PKPM1 (Peak Power Measurement)

The maximum peak conducted output power may be measured using a broadband peak RF power meter. The power meter shall have a video bandwidth that is greater than or equal to the DTS bandwidth and shall utilize a fast-responding diode detector.

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-3. Test Instrument & Measurement Setup for Peak and Average Power Measurement

Test Notes

None

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 26 of 62

7.4.1 Peak Output Power and Max EIRP Measurement – Bluetooth (LE)

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Peak Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
			[dBm]	[mW]						
2402	1.0	37	2.02	1.592	30.00	-27.98	-2.12	-0.10	36.02	-36.12
2404	1.0	0	4.46	2.793	30.00	-25.54	-2.12	2.34	36.02	-33.68
2440	1.0	19	4.09	2.564	30.00	-25.91	-2.12	1.97	36.02	-34.05
2476	1.0	35	3.73	2.360	30.00	-26.27	-2.12	1.61	36.02	-34.41
2478	1.0	36	0.76	1.191	30.00	-29.24	-2.12	-1.36	36.02	-37.38
2480	1.0	39	0.71	1.178	30.00	-29.29	-2.12	-1.41	36.02	-37.43
2404	2.0	0	4.36	2.729	30.00	-25.64	-2.12	2.24	36.02	-33.78
2440	2.0	19	4.20	2.630	30.00	-25.80	-2.12	2.08	36.02	-33.94
2476	2.0	35	3.85	2.427	30.00	-26.15	-2.12	1.73	36.02	-34.29
2478	2.0	36	0.70	1.175	30.00	-29.30	-2.12	-1.42	36.02	-37.44

Table 7-4. Peak Conducted Output Power and Max EIRP Measurements (Bluetooth LE)

7.4.2 Average Output Power Measurement and Max EIRP– Bluetooth (LE)

Frequency [MHz]	Data Rate [Mbps]	Channel No.	Average Conducted Power		Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	EIRP [dBm]	EIRP Limit [dBm]	EIRP Margin [dB]
			[dBm]	[mW]						
2402	1.0	37	1.88	1.542	30.00	-28.12	-2.12	-0.24	36.02	-36.26
2404	1.0	0	4.38	2.742	30.00	-25.62	-2.12	2.26	36.02	-33.76
2440	1.0	19	4.00	2.512	30.00	-26.00	-2.12	1.88	36.02	-34.14
2476	1.0	35	3.63	2.307	30.00	-26.37	-2.12	1.51	36.02	-34.51
2478	1.0	36	0.56	1.138	30.00	-29.44	-2.12	-1.56	36.02	-37.58
2480	1.0	39	0.51	1.125	30.00	-29.49	-2.12	-1.61	36.02	-37.63
2404	2.0	0	4.27	2.673	30.00	-25.73	-2.12	2.15	36.02	-33.87
2440	2.0	19	4.12	2.582	30.00	-25.88	-2.12	2.00	36.02	-34.02
2476	2.0	35	3.74	2.366	30.00	-26.26	-2.12	1.62	36.02	-34.40
2478	2.0	36	0.49	1.119	30.00	-29.51	-2.12	-1.63	36.02	-37.65

Table 7-5. Average Conducted Output Power and Max EIRP Measurements Antenna 1 (Bluetooth LE)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 27 of 62

7.4.3 Sample e.i.r.p. Calculation:

At 2402MHz, the peak conducted output power was calculated to be 2.02 dBm with an antenna gain of -2.12 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$2.02 \text{ dBm} + (-2.12) \text{ dBi} = -0.10 \text{ dBm}$$

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 28 of 62

7.5 Power Spectral Density

§15.247(e); RSS-247 [6.3.1(b)]

Test Overview and Limit

The peak power density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at maximum power and at the appropriate frequencies.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.10.2 Method PKPSD

KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span > 1.5 times the DTS channel bandwidth
3. RBW = 3kHz
4. VBW $\geq 3 \times$ RBW
5. Detector = peak
6. Sweep time = auto couple
7. Trace mode = max hold
8. Trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 29 of 62


Frequency [MHz]	Data Rate [Mbps]	Channel No.	Measured Power Density [dBm/3 kHz]	Max Power Density [dBm/3 kHz]	Margin [dB]
2402	1.0	37	-15.95	8.0	-23.95
2440	1.0	17	-13.92	8.0	-21.92
2480	1.0	39	-16.75	8.0	-24.75
2404	2.0	0	-13.57	8.0	-21.57
2440	2.0	17	-14.37	8.0	-22.37
2478	2.0	36	-18.00	8.0	-26.00

Table 7-6. Conducted Power Density Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 30 of 62




Plot 7-13. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-14. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 17)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 31 of 62





Plot 7-15. Power Spectral Density Plot (Bluetooth (LE), 1Mbps – Ch. 39)



Plot 7-16. Power Spectral Density Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 32 of 62



FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 33 of 62

7.6 Conducted Authorized Band Edge

§15.247(d); RSS-247 [6.6]

Test Overview and Limit

For the following out of band conducted spurious emissions plots at the band edge, the EUT was set to transmit at maximum power with the largest packet size available. These settings produced the worst-case emissions.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.






Figure 7-5. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 34 of 62






Plot 7-21. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch.35)




Plot 7-22. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch. 36)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 36 of 62




Plot 7-23. Band Edge Plot (Bluetooth (LE), 1Mbps – Ch.39)




Plot 7-24. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 37 of 62



Plot 7-25. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 35)



Plot 7-26. Band Edge Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 38 of 62

7.7 Conducted Spurious Emissions

§15.247(d); RSS-247 [6.6]

Test Overview and Limit

For the following out of band conducted spurious emissions plots, the EUT was set to transmit at maximum power with the largest packet size available. The worst case spurious emissions were found in this configuration.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 8.5 of KDB 558074 D01 v05r02 and Section 11.11 of ANSI C63.10-2020.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.11.3
KDB 558074 D01 v05r02 – Section 8.5
ANSI C63.10-2020 – Subclause 14.5.3
KDB 662911 D01 v02r01 – Section E3)b)

Test Settings

1. Start frequency was set to 30 Mhz and stop frequency was set to 25 GHz (separated into two plots per channel)
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-6. Test Instrument & Measurement Setup


Test Notes

None.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 39 of 62




Plot 7-27. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 37)




Plot 7-28. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 37)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 40 of 62




Plot 7-29. Conducted Spurious Plot (Bluetooth (LE), 1Mbps - Ch. 17)



Plot 7-30. Conducted Spurious Plot (Bluetooth (LE), 1Mbps - Ch. 17)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 41 of 62




Plot 7-31. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)




Plot 7-32. Conducted Spurious Plot (Bluetooth (LE), 1Mbps – Ch. 39)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 42 of 62




Plot 7-33. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 0)




Plot 7-34. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 0)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 43 of 62




Plot 7-35. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 17)




Plot 7-36. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 17)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 44 of 62



Plot 7-37. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 36)



Plot 7-38. Conducted Spurious Plot (Bluetooth (LE), 2Mbps – Ch. 36)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 45 of 62

7.8 Radiated Spurious Emissions – Above 1 GHz

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at maximum power and at the appropriate frequencies. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-7 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-7. Radiated Limits

Test Procedures Used

ANSI C63.10-2020 – Subclause 6.6.4.3
KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3 Mhz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1 Mhz
3. VBW = 3 Mhz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 46 of 62

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Radiated Test Setup >1 GHz

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All radiated spurious emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in §15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-7.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9 kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1 GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18 GHz were measured at a 3 meters test distance while emissions above 18 GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
8. All supported modulation have been tested on the unit and only worst case configuration is reported.
9. No significant radiated band edge emissions were found in the 2310 – 2390 Mhz restricted band.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 47 of 62

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{\text{[dB}\mu\text{V/m]}} = \text{Analyzer Level}_{\text{[dBm]}} + 107 + \text{AFCL}_{\text{[dB/m]}}$
- $\text{AFCL}_{\text{[dB/m]}} = \text{Antenna Factor}_{\text{[dB/m]}} + \text{Cable Loss}_{\text{[dB]}} - \text{Preamplifier Gain}_{\text{[dB]}}$
- $\text{Margin}_{\text{[dB]}} = \text{Field Strength Level}_{\text{[dB}\mu\text{V/m]}} - \text{Limit}_{\text{[dB}\mu\text{V/m]}}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8.2 was calculated using the formula:
Offset (dB) = (Antenna Factor + Cable Loss + Attenuator) – Preamplifier Gain

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 48 of 62

7.8.1 Radiated Spurious Emission Measurements

§15.205 §15.209 §15.247(d); RSS-Gen [8.9]




Plot 7-39. Radiated Spurious Emissions 1-18 GHz (1Mbps – Ch. 0)

Bluetooth Mode:	LE
Data Rate:	1Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2402 Mhz
Channel:	37


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4804.00	Avg	H	-	-	-82.30	9.68	34.38	53.98	-19.60
4804.00	Peak	H	-	-	-71.11	9.68	45.58	73.98	-28.40
12010.00	Avg	H	-	-	-84.89	21.00	43.11	53.98	-10.87
12010.00	Peak	H	-	-	-73.24	21.00	54.75	73.98	-19.23

Table 7-8. Radiated Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 49 of 62



Plot 7-40. Radiated Spurious Emissions 1-18 GHz (1Mbps – Ch. 17)




Plot 7-41. Radiated Spurious Emissions Above 18 GHz (1Mbps – Ch. 17)

Bluetooth Mode:	LE
Data Rate:	1Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2440 Mhz
Channel:	17

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Dist. Corr. Factor [dB]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
4880.00	Avg	H	-	-	-82.51	9.93	0.00	34.42	53.98	-19.56
4880.00	Peak	H	-	-	-70.99	9.93	0.00	45.94	73.98	-28.04
7320.00	Avg	H	-	-	-83.90	13.52	0.00	36.62	53.98	-17.36
7320.00	Peak	H	-	-	-72.30	13.52	0.00	48.23	73.98	-25.75
12200.00	Avg	H	-	-	-85.15	21.50	0.00	43.35	53.98	-10.63
12200.00	Peak	H	-	-	-74.16	21.50	0.00	54.34	73.98	-19.64
19520.00	Avg	H	-	-	-62.69	-6.07	-9.54	28.70	53.98	-25.28
19520.00	Peak	H	-	-	-51.18	-6.07	-9.54	40.21	73.98	-33.77

Table 7-9. Radiated Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 50 of 62



Plot 7-42. Radiated Spurious Emissions 1-18 GHz (1Mbps – Ch. 39)

Bluetooth Mode: LE
Data Rate: 1Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2480 Mhz
Channel: 39

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
4960.00	Avg	H	-	-	-82.30	9.97	34.67	53.98	-19.31
4960.00	Peak	H	-	-	-71.28	9.97	45.68	73.98	-28.29
7440.00	Avg	H	-	-	-84.05	13.78	36.73	53.98	-17.25
7440.00	Peak	H	-	-	-72.67	13.78	48.11	73.98	-25.87
12400.00	Avg	H	-	-	-85.20	22.37	44.16	53.98	-9.82
12400.00	Peak	H	-	-	-73.54	22.37	55.83	73.98	-18.15


Table 7-10. Radiated Measurements

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 51 of 62


7.8.2 Radiated Restricted Band Edge Measurements

§15.205 §15.209; RSS-Gen [8.9]

Bluetooth Mode:	LE
Data Rate:	1Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2480 Mhz
Channel:	39




Plot 7-43. Radiated Restricted Upper Band Edge Measurement (Average)




Plot 7-44. Radiated Restricted Upper Band Edge Measurement (Peak)

Bluetooth Mode:	LE
Data Rate:	2Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2476 Mhz
Channel:	35




Plot 7-45. Radiated Restricted Lower Band Edge Measurement (Average)




Plot 7-46. Radiated Restricted Lower Band Edge Measurement (Peak)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 52 of 62

Bluetooth Mode:	LE
Data Rate:	2Mbps
Measurement Distance:	3 Meters
Operating Frequency:	2478 Mhz
Channel:	36



Plot 7-47. Radiated Restricted Upper Band Edge Measurement (Average)



Plot 7-48. Radiated Restricted Upper Band Edge Measurement (Peak)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 53 of 62

7.9 Radiated Spurious Emissions – Below 1 GHz

§15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-11 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [μV/m]	Measured Distance [Meters]
0.009 – 0.490 MHz	2400/F (kHz)	300
0.490 – 1.705 MHz	24000/F (kHz)	30
1.705 – 30.00 MHz	30	30
30.00 – 88.00 MHz	100	3
88.00 – 216.0 MHz	150	3
216.0 – 960.0 MHz	200	3
Above 960.0 MHz	500	3

Table 7-11. Radiated Limits

Test Procedures Used

ANSI C63.10-2020

Test Settings

Quasi-Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120 kHz (for emissions from 30 Mhz – 1 GHz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 120 kHz (for emissions from 30 Mhz – 1 GHz)
3. VBW = 300 kHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 54 of 62

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.




Figure 7-8. Radiated Test Setup < 30 Mhz




Figure 7-9. Radiated Test Setup < 1 GHz

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 55 of 62

Test Notes

1. All emissions lying in restricted bands specified in §15.205 and RSS-Gen (8.10) are below the limit shown in Table 7-11.
2. The broadband receive antenna is manipulated through vertical and horizontal polarizations during the tests. The EUT is manipulated through three orthogonal planes. For below 30 Mhz the loop antenna was positioned in 3 orthogonal planes (X front, Y side, Z top) to determine the orientation resulting in the worst case emissions.
3. This unit was tested with its standard battery.
4. The spectrum is investigated using a peak detector and final measurements are recorded using CISPR quasi peak detector on emissions that were within 6dB of the limit.
5. Emissions were measured at a 3 meter test distance.
6. Emissions are investigated while operating on the center channel of the mode, band, and modulation that produced the worst case results during the transmitter spurious emissions testing.
7. No spurious emissions were detected within 20dB of the limit below 30 Mhz.
8. The results recorded using the broadband antenna is known to correlate with the results obtained by using a tuned dipole with an acceptable degree of accuracy. The VSWR for the measurement antenna was found to be less than 2:1.
9. All supported modulation have been tested on the unit and only worst case configuration is reported.
10. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger

Sample Calculations


Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level}_{[dBm]} + 107 + \text{AFCL}_{[dB/m]}$
- $\text{AFCL}_{[dB/m]} = \text{Antenna Factor}_{[dB/m]} + \text{Cable Loss}_{[dB]} - \text{Preamplifier Gain}_{[dB]}$
- $\text{Margin}_{[dB]} = \text{Field Strength Level}_{[dB\mu V/m]} - \text{Limit}_{[dB\mu V/m]}$

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 56 of 62

7.9.1 Radiated Spurious Emissions Measurements (Below 1 GHz)

§15.209; RSS-Gen [8.9]



Plot 7-49. Radiated Spurious Emissions Below 1 GHz (1Mbps – Ch.17, Pol. H & V, with AC/DC Adapter)

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
35.46	Max-Peak	V	100	8	-62.76	-20.44	23.80	40.00	-16.20
67.62	Max-Peak	V	100	329	-63.49	-20.96	22.54	40.00	-17.46
138.72	Max-Peak	H	200	249	-61.56	-22.30	23.14	43.50	-20.36
181.81	Max-Peak	H	200	69	-63.51	-20.10	23.39	43.50	-20.11
251.17	Max-Peak	V	100	154	-67.28	-16.66	23.06	46.00	-22.94
890.02	Max-Peak	H	300	254	-76.11	-4.35	26.53	46.00	-19.47

Table 7-12. Radiated Spurious Emissions Below 1 GHz (1Mbps – Ch.17, Pol. H & V, with AC/DC Adapter)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 57 of 62

7.10 AC Line-Conducted Emissions

§15.207; RSS-Gen [8.8]

Test Overview and Limit

All AC line conducted spurious emissions are measured with a receiver connected to a grounded LISN while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for AC Line conducted spurious emissions. Only the conducted emissions of the configuration that produced the worst case emissions are reported in this section.

All conducted emissions must not exceed the limits shown in the table below, per Section 15.207 and RSS-Gen (8.8).

Frequency of emission (MHz)	Conducted Limit (dBμV)	
	Quasi-peak	Average
0.15 – 0.5	66 to 56*	56 to 46*
0.5 – 5	56	46
5 – 30	60	50

Table 7-13. Conducted Limits

*Decreases with the logarithm of the frequency.

Test Procedures Used

ANSI C63.10-2020, Subclause 6.2

Test Settings

Quasi-Peak Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9 kHz (for emissions from 150 kHz – 30 Mhz)
3. Detector = quasi-peak
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

Average Measurements

1. Analyzer center frequency was set to the frequency of the spurious emission of interest
2. RBW = 9 kHz (for emissions from 150 kHz – 30 Mhz)
3. Detector = RMS
4. Sweep time = auto couple
5. Trace mode = max hold
6. Trace was allowed to stabilize

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 58 of 62

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-10. Test Instrument & Measurement Setup

Test Notes

1. All modes of operation were investigated and the worst-case emissions are reported. The emissions found were not affected by the choice of channel used during testing.
2. Both configurations below were investigated, and the worst case has been reported.
 - a. EUT powered by AC/DC adaptor via USB-C cable with wire charger
3. The limit for an intentional radiator from 150 kHz to 30 Mhz are specified in Part 15.207 and RSS-Gen (8.8).
4. $\text{Corr. (dB)} = \text{Cable loss (dB)} + \text{LISN insertion factor (dB)}$
5. $\text{QP/AV Level (dB}\mu\text{V)} = \text{QP/AV Analyzer/Receiver Level (dB}\mu\text{V)} + \text{Correction Factor (dB)}$
6. $\text{Margin (dB)} = \text{QP/AV Level (dB}\mu\text{V)} - \text{QP/AV Limit (dB}\mu\text{V)}$
7. Traces shown in plot are made using a quasi peak and average detectors.
8. Deviations to the Specifications: None.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 59 of 62




Plot 7-50. AC Line Conducted Plot with Bluetooth LE (L1, 1Mbps – Ch.17 with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBμV]	Average [dBμV]	Limit [dBμV]	Margin [dB]	Line	PE
0.182	FINAL	---	9.18	54.42	-45.24	L1	GND
0.184	FINAL	24.72	---	64.31	-39.59	L1	GND
0.440	FINAL	---	15.42	47.06	-31.64	L1	GND
0.440	FINAL	20.32	---	57.06	-36.74	L1	GND
1.664	FINAL	---	6.71	46.00	-39.29	L1	GND
1.682	FINAL	11.46	---	56.00	-44.54	L1	GND
4.754	FINAL	---	8.68	46.00	-37.32	L1	GND
4.758	FINAL	15.44	---	56.00	-40.56	L1	GND
14.010	FINAL	---	16.81	50.00	-33.19	L1	GND
14.033	FINAL	25.17	---	60.00	-34.83	L1	GND
24.245	FINAL	12.73	---	60.00	-47.27	L1	GND
24.248	FINAL	---	6.40	50.00	-43.60	L1	GND

Table 7-14. AC Line Conducted Data with Bluetooth LE (L1, 1Mbps – Ch.17 with AC/DC Adapter)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 60 of 62



Plot 7-51. AC Line Conducted Plot with Bluetooth LE (N, 1Mbps – Ch.17, with AC/DC Adapter)

Frequency [MHz]	Process State	QuasiPeak [dBµV]	Average [dBµV]	Limit [dBµV]	Margin [dB]	Line	PE
0.182	FINAL	---	13.65	54.42	-40.77	N	GND
0.184	FINAL	23.69	---	64.31	-40.62	N	GND
0.443	FINAL	---	22.04	47.02	-24.98	N	GND
0.443	FINAL	26.76	---	57.02	-30.26	N	GND
1.325	FINAL	---	12.63	46.00	-33.37	N	GND
1.329	FINAL	17.67	---	56.00	-38.33	N	GND
4.718	FINAL	---	14.02	46.00	-31.98	N	GND
4.767	FINAL	20.00	---	56.00	-36.00	N	GND
8.999	FINAL	---	16.40	50.00	-33.60	N	GND
9.026	FINAL	22.97	---	60.00	-37.03	N	GND
16.175	FINAL	---	11.50	50.00	-38.50	N	GND
16.175	FINAL	17.16	---	60.00	-42.84	N	GND

Table 7-15. AC Line Conducted Data with Bluetooth LE (N, 1Mbps – Ch.17 with AC/DC Adapter)

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 61 of 62

8 CONCLUSION

The data collected relate only to the item(s) tested and show that the **Garmin Portable Digital Transceiver FCC ID: IPH-05171 and IC: 1792A-05171** is in compliance with Part 15 Subpart C (15.247) of the FCC Rules and RSS-247 of the Innovation, Science and Economic Development Canada Rules.

FCC ID: IPH-05171 IC: 1792A-05171		Test Dates: 02/17/2026 - 06/12/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-06.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 62 of 62