

FCC/ISED Test Report

Prepared for: Garmin International, Inc.

Address: 1200 E. 151st Street
Olathe, Kansas, 66062, USA

Product: A04112

Test Report No: R20210128-20-E11A

Approved by:



Nic S. Johnson, NCE

Technical Manager

iNARTE Certified EMC Engineer #EMC-003337-NE

DATE: December 6, 2021

Total Pages: 60

The Nebraska Center for Excellence in Electronics (NCEE) authorizes the above named company to reproduce this report provided it is reproduced in its entirety for use by the company's employees only. Any use that a third party makes of this report, or any reliance on or decisions made based on it, are the responsibility of such third parties. NCEE accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report. This report applies only to the items tested.



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

REVISION PAGE

Rev. No.	Date	Description
0	21 October 2021	Original – NJohnson Prepared by FLane
A	6 December 2021	Commented on radiated spurious emissions Added Conducted spurious emission section - FL

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

CONTENTS

Revision Page.....	2
1.0 Summary of test results.....	4
2.0 EUT Description.....	5
2.1 Equipment under test	5
2.2 Description of test modes	5
2.3 Description of support units	5
3.0 Laboratory and General Test Description.....	6
3.1 Laboratory description	6
3.2 Test personnel	6
3.3 Test equipment	7
3.4 General Test Procedure and Setup for Radio Measuremnts	8
4.0 Results	9
4.1 Output Power	10
4.2 Bandwidth	11
4.3 Duty Cycle	12
4.4 Radiated emissions	13
4.5 Band edges	23
4.6 Power Spectral Density	25
4.7 Conducted AC Mains Emissions	26
Appendix A: Sample Calculation	31
Appendix B – Measurement Uncertainty	33
Appendix C – Graphs and Tables	34
REPORT END	60

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

1.0 SUMMARY OF TEST RESULTS

The worst-case measurements were reported in this report. Summary of test results presented in this report correspond to the following section (Please see the checked box below for the rule part used):

FCC Part 15.247 ☒

The EUT has been tested according to the following specifications:

- (1) US Code of Federal Regulations, Title 47, Part 15
- (2) ISSED RSS-Gen, Issue 5
- (3) ISSED RSS-247, Issue 2

APPLIED STANDARDS AND REGULATIONS		
Standard Section	Test Type	Result
FCC Part 15.35 RSS Gen, Issue 5, Section 6.10	Duty Cycle	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 2 Section 5.2	Peak output power	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 2 Section 5.2	Bandwidth	Pass
FCC Part 15.209 RSS-Gen Issue 4, Section 7.1	Receiver Radiated Emissions	Pass
FCC Part 15.209 (restricted bands), 15.247 (unrestricted) RSS-247 Issue 2 Section 5.5, RSS-Gen Issue 4, Section 8.9	Transmitter Radiated Emissions	Pass
FCC Part 15.247(a)(1) RSS-247 Issue 2 Section 5.2	Power Spectral Density	Pass
FCC Part 15.209, 15.247(d) RSS-247 Issue 2 Section 11.13	Band Edge Measurement	Pass
FCC Part 15.207 RSS-Gen Issue 4, Section 7.1	Conducted Emissions	Pass



Report Number: R20210128-20-E11

Rev

A

Prepared for: Garmin International, Inc.

2.0 EUT DESCRIPTION

2.1 EQUIPMENT UNDER TEST

Summary and Operating Condition:

EUT	A04112
EUT Received	9 March 2021
EUT Tested	9 March 2021- 6 October 2021
Serial No.	3319808469 (Radiated Measurements) 3319808431 (Radiated Measurements) 3319808429 (Conducted Measurements)
Operating Band	2400 – 2483.5 MHz
Device Type	☐ GMSK ☐ GFSK ☐ BT BR ☒ BT EDR 2MB ☒ BT EDR 3MB ☐ 802.11x
Power Supply / Voltage	Internal Battery/ 5VDC Charger: Garmin (Phi Hong) MN: PSAI10R-050Q (Representative Power Supply)

NOTE: For more detailed features description, please refer to the manufacturer's specifications or user's manual.

2.2 DESCRIPTION OF TEST MODES

The operating range of the EUT is dependent on the device type found in section 2.1:

For Bluetooth Transmissions:

Channel	Frequency
Low	2402 MHz
Mid	2440 MHz
High	2480 MHz

For 802.11x Transmissions:

Channel	Frequency
Low	2412 MHz
Mid	2437 MHz
High	2462 MHz

These are the only representative channels tested in the frequency range according to FCC Part 15.31 and RSS-Gen Table A1. See the operational description for a list of all channel frequency and designations.

2.3 DESCRIPTION OF SUPPORT UNITS

None

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

3.0 LABORATORY AND GENERAL TEST DESCRIPTION

3.1 LABORATORY DESCRIPTION

All testing was performed at the following Facility:

The Nebraska Center for Excellence in Electronics (NCEE Labs)
4740 Discovery Drive
Lincoln, NE 68521

A2LA Certificate Number:	1953.01
FCC Accredited Test Site Designation No:	US1060
Industry Canada Test Site Registration No:	4294A-1
NCC CAB Identification No:	US0177

Environmental conditions varied slightly throughout the tests:

Relative humidity of $35 \pm 4\%$
Temperature of $22 \pm 3^\circ$ Celsius



3.2 TEST PERSONNEL

No.	PERSONNEL	TITLE	ROLE
1	Nic Johnson	Technical Manager	Review/editing
2	Karthik Vepuri	Test Engineer	Testing and report
3	Grace Larsen	Test Technician	Testing
4	Samuel Probst	Test Technician	Testing
5	Matthew Emory	Test Technician	Testing

Notes:

All personnel are permanent staff members of NCEE Labs. No testing or review was sub-contracted or performed by sub-contracted personnel.



Report Number: R20210128-20-E11

Rev

A

Prepared for: Garmin International, Inc.

3.3 TEST EQUIPMENT

DESCRIPTION AND MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CALIBRATION DATE	CALIBRATION DUE DATE
Keysight MXE Signal Analyzer (44GHz)	N9038A	MY59050109	July 21, 2021	July 21, 2023
Keysight MXE Signal Analyzer (26.5GHz)	N9038A	MY56400083	May 5, 2020	May 5, 2022
Keysight EXA Signal Analyzer	N9010A	MY56070862	July 20, 2021	July 20, 2023
SunAR RF Motion	JB1	A091418	July 27, 2021	July 27, 2022
EMCO Horn Antenna	3115	6415	March 16, 2020	March 16, 2022
Com-Power LISN 50 μ H / 250 μ H - 50 Ω	LI-220C	20070017	September 22, 2020	September 22, 2022
8447F POT H64 Preamplifier*	8447F POT H64	3113AD4667	February 1, 2021	February 1, 2022
Rohde & Schwarz Preamplifier*	TS-PR18	3545700803	April 14, 2020	April 14, 2022
Trilithic High Pass Filter*	6HC330	23042	April 14, 2020	April 14, 2022
TDK Emissions Lab Software	V11.25	700307	NA	NA

*Internal Characterization

Notes:

All equipment is owned by NCEE Labs and stored permanently at NCEE Labs facilities.

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

3.4 GENERAL TEST PROCEDURE AND SETUP FOR RADIO MEASUREMENTS

Measurement type presented in this report (Please see the checked box below):

Conducted ☒

The conducted measurements were performed by connecting the output of the transmitter directly into a spectrum analyzer using an impedance matched cable and connector soldered to the EUT in place of the antenna. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 1 - Bandwidth Measurements Test Setup

Radiated ☒

All the radiated measurements were taken at a distance of 3m from the EUT. The information regarding resolution bandwidth, video bandwidth, span and the detector used can be found in the graphs provided in the Appendix C. All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.




Figure 2 - Radiated Emissions Test Setup



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

4.0 RESULTS

DTS Radio Measurements

CHANNEL	Transmitter	Occupied Bandwidth (MHz)	6 dB Bandwidth (MHz)	PEAK OUTPUT POWER (dBm)	PEAK OUTPUT POWER (mW)	PSD (dBm)	RESULT
Low	2EDR	1.2482	1.0440	12.294	16.959	-5.256	PASS
Mid	2EDR	1.2371	1.0380	12.055	16.051	-5.007	PASS
High	2EDR	1.2373	1.0400	12.664	18.467	-4.660	PASS
Low	3EDR	1.2385	1.0290	12.591	18.159	-4.864	PASS
Mid	3EDR	1.2318	1.0230	12.579	18.109	-4.977	PASS
High	3EDR	1.2307	1.0230	12.772	18.932	-4.647	PASS
Occupied Bandwidth = N/A; 6 dB Bandwidth Limit = 500 kHz				Peak Output Power Limit = 30 dBm; PSD Limit = 8 dBm			

Unrestricted Band-Edge

CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Relative Highest out of band level (dBuV)	Relative Fundamental (dBuV)	Delta (dB)	Min Delta (dB)	Result
Low	2EDR	2400.00	59.57	118.18	58.61	20.00	PASS
Low	3EDR	2400.00	71.25	117.37	46.13	20.00	PASS
High	2EDR	2483.50	71.97	118.19	46.22	20.00	PASS
High	3EDR	2483.50	57.91	117.70	59.79	20.00	PASS

Peak Restricted Band-Edge

CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)	Measurement Type	Limit (dBuV/m @ 3m)	Margin	Result
Low	2EDR	2390.00	51.73	Peak	73.98	22.25	PASS
Low	3EDR	2390.00	52.91	Peak	73.98	21.07	PASS
High	2EDR	2483.50	55.68	Peak	73.98	18.30	PASS
High	3EDR	2483.50	56.80	Peak	73.98	17.18	PASS

*Limit shown is the peak limit taken from FCC Part 15.209

Average Restricted Band-Edge

CHANNEL	Mode	Band edge /Measurement Frequency (MHz)	Highest out of band level (dBuV/m @ 3m)**	Measurement Type	Limit (dBuV/m @ 3m)*	Margin	Result
Low	2EDR	2390.00	42.60	Average	53.98	11.38	PASS
Low	3EDR	2390.00	42.80	Average	53.98	11.18	PASS
High	2EDR	2483.50	45.93	Average	53.98	8.05	PASS
High	3EDR	2483.50	46.49	Average	53.98	7.49	PASS

*Limit shown is the average limit taken from FCC Part 15.209

**Average Highest out of band level = SA Average Level – DCCF. C63.10 Sec. 11.12.2.5.2

See Sec 4.3 for more information on DCCF



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

4.1 OUTPUT POWER

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of power measurements:

For FCC Part 15.247 Device:

The maximum allowed peak output power is 30 dBm.

Test procedures:

Details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the output power plots can be found in the Appendix C.
2. All the measurements were found to be compliant.
3. The measurements are listed in the tables below.
4. Compiled values can be found in the Results section, 4.0.



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

4.2 BANDWIDTH

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of bandwidth measurements:

For FCC Part 15.247 Device:

The 99% occupied bandwidth is for informational purpose only. The 6dB bandwidth of the signal must be greater than 500 kHz.

Test procedures:

Details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

1. All the bandwidth plots can be found in the Appendix C.
2. All the measurements were found to be compliant.

4.3 DUTY CYCLE




Figure 3 – 2EDR Duty Cycle

$$\text{DCCF (Duty Cycle Correction Factor)} = 20 * \text{Log}(\text{Duty Cycle} / 100)$$

$$-2.27 = 20 * \text{Log}(77 / 100)$$




Figure 4 – 3EDR Duty Cycle

$$\text{DCCF (Duty Cycle Correction Factor)} = 20 * \text{Log}(\text{Duty Cycle} / 100)$$

$$-2.27 = 20 * \text{Log}(77 / 100)$$

4.4 RADIATED EMISSIONS

Test Method: ANSI C63.10-2013, Section 6.5, 6.6

Limits for radiated emissions measurements:

Emissions radiated outside of the specified bands shall be applied to the limits in 15.209 as followed:

FREQUENCIES (MHz)	FIELD STRENGTH ($\mu\text{V/m}$)	MEASUREMENT DISTANCE (m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	3
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 * \log * \text{Emission level } (\mu\text{V/m})$.
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits by more than 20dB under any condition of modulation.
4. The EUT was tested for spurious emissions while running off of battery power and external USB power. The worse-case emissions were produced while running off of USB power, so results from this mode are presented.



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

Test procedures:

- a. The EUT was placed on the top of a rotating table above the ground plane in a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The table was 0.8m high for measurements from 30MHz-1Ghz and 1.5m for measurements from 1GHz and higher.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna was a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are used to make the measurement.
- d. For each suspected emission, the EUT was arranged to maximize its emissions and then the antenna height was varied from 1 meter to 4 meters and the rotating table was turned from 0 degrees to 360 degrees to find the maximum emission reading.
- e. The test-receiver system was set to use a peak detector with a specified resolution bandwidth. For spectrum analyzer measurements, the composite maximum of several analyzer sweeps was used for final measurements.
- f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
- g. The EUT was maximized in all 3 orthogonal positions. The results are presented for the axis that had the highest emissions.

Test setup:




Figure 5 - Radiated Emissions Test Setup

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Peak detection (PK) and Quasi-peak detection (QP) at frequencies below 1GHz.
2. The resolution bandwidth 1 MHz for all measurements and at frequencies above 1GHz, A peak detector was used for all measurements above 1GHz. Measurements were made with an EMI Receiver.

Deviations from test standard:

No deviation.

EUT operating conditions

Details can be found in section 2.1 of this report.

Test results:




Figure 6 - Radiated Emissions Plot, Receive




Figure 7 - Radiated Emissions Plot, BT EDR 2MB




Figure 8 - Radiated Emissions Plot, BT EDR 3MB

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB)
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value

Peak Measurements, Bluetooth Classic								
Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
2402.212000	101.39	NA	NA	140	152	H	Low	BT EDR 2MB
2439.934000	100.98	NA	NA	131	158	H	Mid	BT EDR 2MB
2479.856000	101.01	NA	NA	123	157	H	High	BT EDR 2MB
5418.652000	44.22	73.98	29.76	153	307	H	Low	BT EDR 2MB
4834.056000	42.53	73.98	31.45	326	193	H	Mid	BT EDR 2MB
9757.344000	49.28	73.98	24.70	540	287	V	Mid	BT EDR 2MB
7451.334000	46.68	73.98	27.30	355	36	V	High	BT EDR 2MB
2401.908000	105.87	NA	NA	173	166	H	Low	BT EDR 3MB
2440.784000	105.02	NA	NA	163	161	H	Mid	BT EDR 3MB
2480.082000	105.61	NA	NA	190	160	H	High	BT EDR 3MB
7189.066000	46.00	73.98	27.98	217	333	V	Low	BT EDR 3MB
4885.270000	42.21	73.98	31.77	258	134	H	Mid	BT EDR 3MB
4811.536000	42.18	73.98	31.80	407	325	H	High	BT EDR 3MB

Average Measurements, Bluetooth Classic

Frequency	Level	Limit	Margin	Height	Angle	Pol	Channel	Modulation
MHz	dBμV/m	dBμV/m	dB	cm.	deg.			
2402.212000	99.11	NA	NA	140	152	H	Low	BT EDR 2MB
2439.934000	98.70	NA	NA	131	158	H	Mid	BT EDR 2MB
2479.856000	98.73	NA	NA	123	157	H	High	BT EDR 2MB
5418.652000	41.94	53.98	12.04	153	307	H	Low	BT EDR 2MB
4834.056000	40.25	53.98	13.73	326	193	H	Mid	BT EDR 2MB
9757.344000	47.00	53.98	6.98	540	287	V	Mid	BT EDR 2MB
7451.334000	44.40	53.98	9.58	355	36	V	High	BT EDR 2MB
2401.908000	103.59	NA	NA	173	166	H	Low	BT EDR 3MB
2440.784000	102.74	NA	NA	163	161	H	Mid	BT EDR 3MB
2480.082000	103.33	NA	NA	190	160	H	High	BT EDR 3MB
7189.066000	43.72	53.98	10.26	217	333	V	Low	BT EDR 3MB
4885.270000	39.93	53.98	14.05	258	134	H	Mid	BT EDR 3MB
4811.536000	39.90	53.98	14.08	407	325	H	High	BT EDR 3MB

*Average Level = Peak level + DCCF

See Sec 4.3 for more information on DCCF

4.5 CONDUCTED SPURIOUS EMISSIONS

Test Method: ANSI C63.10-2013, Section 7.8.8

Limits of spurious emissions:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Test procedures:

The highest emissions level was measured and recorded. All spurious measurements were evaluated to 20dB below the fundamental. More details can be found in section 3.4 of this report.

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

The highest value measured was 12.104 dBm at the fundamental emissions. All other values were at least 20 dB lower. Testing was performed on the low, middle and high channels with all modulation settings. The worst-case results are reported.




Figure 9 - Radiated Emissions Plot, 2EDR, 30M – 1G




Figure 10 - Radiated Emissions Plot, 2EDR, 1G – 3.6G




Figure 11 - Radiated Emissions Plot, 2EDR, 3.6G – 25G

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		




Figure 12 - Radiated Emissions Plot, 3EDR, 30M – 1G




Figure 13 - Radiated Emissions Plot, 3EDR, 1G – 3.6G

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




Figure 14 - Radiated Emissions Plot, 3EDR, 3.6G – 25G

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		

4.5 BAND EDGES

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of band-edge measurements:

For FCC Part 15.247 Device:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c))

Test procedures:

The highest emissions level beyond the band-edge was measured and recorded. All band edge measurements were evaluated to the general limits in Part 15.209. More details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Test setup details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

Test results:

Pass

Comments:

1. All the band edge plots can be found in the Appendix C.
2. If the device falls under FCC Part 15.247 (Details can be found in summary of test results), compliance is shown in the unrestricted band edges by showing minimum delta of 20 dB between peak and the band edge.
3. The restricted band edge compliance is shown by comparing to the general limit defined in Part 15.209. The limit shown in the graph accounts for the antenna gain of the device.



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

4.6 POWER SPECTRAL DENSITY

Test Method: All the radio measurements were performed using the sections from ANSI C63.10, details about the section used can be found in the spectrum analyzer titles on the graph.

Limits of power measurements:

For FCC Part 15.247 Device:

The maximum PSD allowed is 8 dBm.

Test procedures:

Details can be found in section 3.4 of this report.

Deviations from test standard:

No deviation.

Test setup:

Details can be found in section 3.4 of this report.

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test results:

Pass

Comments:

5. All the Power Spectral Density (PSD) plots can be found in the Appendix C.
6. All the measurements were found to be compliant.
7. The measurements are reported on the graph.

4.7 CONDUCTED AC MAINS EMISSIONS

Test Method: ANSI C63.10-2013, Section(s) 6.2

Limits for conducted emissions measurements:

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

Notes:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

Test Procedures:

- a. The EUT was placed 0.8m above a ground reference plane and 0.4 meters from the conducting wall of a shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). The LISN provides 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference as well as the ground.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels over 10dB under the prescribed limits are not reported.
- d. Results were compared to the 15.207 limits.

Deviation from the test standard:

No deviation

EUT operating conditions:

Details can be found in section 2.1 of this report.

Test Results:




Figure 15 - Conducted Emissions Plot, Line, TX

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		




Figure 16 - Conducted Emissions Plot, Neutral, TX




Figure 17 - Conducted Emissions Plot, Line, IDLE

	Report Number:	R20210128-20-E11	Rev	A
	Prepared for:	Garmin International, Inc.		




Figure 18 - Conducted Emissions Plot, Neutral, IDLE



Report Number: R20210128-20-E11

Rev

A

Prepared for: Garmin International, Inc.

APPENDIX A: SAMPLE CALCULATION

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF - (-CF + AG) + AV$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

AV = Averaging Factor (if applicable)

Assume a receiver reading of 55 dB μ V is obtained. The Antenna Factor of 12 and a Cable Factor of 1.1 is added. The Amplifier Gain of 20 dB is subtracted, giving a field strength of 48.1 dB μ V/m.

$$FS = 55 + 12 - (-1.1 + 20) + 0 = 48.1 \text{ dB}\mu\text{V/m}$$

The 48.1 dB μ V/m value can be mathematically converted to its corresponding level in μ V/m.

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(48.1 \text{ dB}\mu\text{V/m})/20] = 254.1 \mu\text{V/m}$$

AV is calculated by taking the $20 \cdot \log(T_{\text{on}}/100)$ where T_{on} is the maximum transmission time in any 100ms window.



Report Number: R20210128-20-E11

Rev

A

Prepared for: Garmin International, Inc.

EIRP Calculations

In cases where direct antenna port measurement is not possible or would be inaccurate, output power is measured in EIRP. The maximum field strength is measured at a specified distance and the EIRP is calculated using the following equation;

$$EIRP \text{ (Watts)} = [Field \text{ Strength (V/m)} \times \text{antenna distance (m)}]^2 / 30$$

$$\text{Power (watts)} = 10^{[Power \text{ (dBm)}/10]} / 1000$$

$$\text{Voltage (dB}\mu\text{V)} = \text{Power (dBm)} + 107 \text{ (for } 50\Omega \text{ measurement systems)}$$

$$\text{Field Strength (V/m)} = 10^{[Field \text{ Strength (dB}\mu\text{V/m)} / 20]} / 10^6$$

$$\text{Gain} = 1 \text{ (numeric gain for isotropic radiator)}$$

Conversion from 3m field strength to EIRP (d=3):

$$EIRP = [FS(V/m) \times d^2]/30 = FS [0.3] \quad \text{for } d = 3$$

$$EIRP(dBm) = FS(dB\mu V/m) - 10(\log 10^9) + 10\log[0.3] = FS(dB\mu V/m) - 95.23$$

$10\log(10^9)$ is the conversion from micro to milli



Report Number: R20210128-20-E11

Rev

A

Prepared for: Garmin International, Inc.


APPENDIX B – MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been for tests performed in this test report:

Test	Frequency Range	Uncertainty Value (dB)
Radiated Emissions, 3m	30MHz - 1GHz	3.82
Radiated Emissions, 3m	1GHz - 18GHz	4.44
Emissions limits, conducted	30MHz – 18GHz	±3.30 dB


Expanded uncertainty values are calculated to a confidence level of 95%.

APPENDIX C – GRAPHS AND TABLES




01 Peak Output Power, Low Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




02 Peak Output Power, Mid Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




03 Peak Output Power, High Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




04 Bandwidth, Low Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




05 Bandwidth, Mid Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




06 Bandwidth, High Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




07 PSD, Low Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




08 PSD, Mid Channel, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




09 PSD, High Channel, 2EDR




10 Lower Bandedge Restricted, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		



11 Higher Bandedge Restricted, 2EDR




12 Lower Bandedge Unrestricted, 2EDR




13 Higher Bandedge Unrestricted, 2EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




14 Peak Output Power, Low Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




15 Peak Output Power, Mid Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




16 Peak Output Power, High Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




17 Bandwidth, Low Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




18 Bandwidth, Mid Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




19 Bandwidth, High Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




20 PSD, Low Channel, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		




21 PSD, Mid Channel, 3EDR


Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		



22 PSD, High Channel, 3EDR



23 Lower Bandedge Restricted, 3EDR




24 Higher Bandedge Restricted, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		



25 Higher Bandedge Unrestricted, 3EDR

Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		



26 Lower Bandedge Unrestricted, 3EDR



Report Number:	R20210128-20-E11	Rev	A
Prepared for:	Garmin International, Inc.		

REPORT END