

MEASUREMENT REPORT

FCC PART 15.247 / ISD RSS-247 WLAN 802.11b/g/n (OFDM)

Applicant Name:
Garmin International Inc.
1200 E. 151st. Street
Olathe, Kansas 66062
United States


Date of Testing:
02/17/2026 - 07/07/2026
Test Report Issue Date:
7/10/2026
Test Site/Location:
Element Materials Technology, Morgan Hill, CA, USA
Test Report Serial No.:
1C2605260039-10.IPH

FCC ID:	IPH-A5171
IC:	1792A-A5171
APPLICANT:	Garmin International Inc.

Application Type:	Certification
Model/HVIN:	AA5171
EUT Type:	Portable Digital Transceiver
Frequency Range:	2412 – 2472MHz
Modulation Type	OFDM
FCC Classification:	Digital Transmission System (DTS)
FCC Rule Part(s):	Part 15 Subpart C (15.247)
ISED Specification:	RSS-247 Issue 4
Test Procedure(s):	ANSI C63.10:2020 + Cor. 1:2023 + C63.10a:2024 + Errata to C63.10a:2024, KDB 558074 D01 v05r02, KDB 662911 D01 v02r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.10-2020 and KDB 558074 D01 v05r02. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



RJ Ortanez
Executive Vice President



FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 1 of 93

Revision Summary


Revision	Date	Comments	Revised By
-	07/07/2026	Initial Release	WKR007077

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 2 of 93


TABLE OF CONTENTS

1.0	INTRODUCTION.....	5
1.1	Scope	5
1.2	Element Materials Technology Test Location.....	5
1.3	Test Facility / Accreditations	5
2.0	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities	6
2.3	Antenna Description	7
2.4	Test Configuration	8
2.5	Software and Firmware	8
2.6	EMI Suppression Device(s)/Modifications	8
3.0	DESCRIPTION OF TESTS	9
3.1	Evaluation Procedure	9
3.2	AC Line Conducted Emissions	9
3.3	Radiated Emissions.....	10
3.4	Environmental Conditions.....	10
4.0	ANTENNA REQUIREMENTS	11
5.0	MEASUREMENT UNCERTAINTY.....	12
6.0	TEST EQUIPMENT CALIBRATION DATA.....	13
7.0	TEST RESULTS.....	14
7.1	Summary.....	14
7.2	99% Occupied Bandwidth	15
7.3	6 dB Bandwidth	20
7.4	Output Power Measurement.....	25
7.5	Power Spectral Density	29
7.6	Conducted Authorized Band Edge	34
7.7	Conducted Spurious Emissions.....	48
7.8	Radiated Spurious Emissions – Above 1 GHz	55
7.9	Radiated Spurious Emissions – Below 1GHz.....	83
7.10	AC Line-Conducted Emissions.....	87
8.0	CONCLUSION	91
9.0	Appendix A – Data Referencing Spot-checks.....	92

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 3 of 93



MEASUREMENT REPORT



Mode	Tx Frequency (MHz)	Avg Conducted		Peak Conducted	
		Max. Power (mW)	Max. Power (dBm)	Max. Power (mW)	Max. Power (dBm)
802.11b	2412 - 2472	54.828	17.39	84.723	19.28
802.11g	2412 - 2472	56.234	17.50	144.212	21.59
802.11n	2412 - 2472	46.615	16.69	143.964	21.58

EUT Overview

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 4 of 93

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 Element Materials Technology Test Location

These measurement tests were conducted at the Element Materials Technology facility located at 18855 Adams Court, Morgan Hill, CA 95037. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014 and KDB 414788 D01 v01r01.

1.3 Test Facility / Accreditations

Measurements were performed at Element Materials Technology located in Morgan Hill, CA 95037, U.S.A.

- Element Materials Technology is an ISO 17025-2017 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.02 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- Element Washington DC LLC TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- Element Materials Technology facility is a registered test laboratory with the site description on file with ISSED (Wireless Test Lab number 22831) and FCC (Designation Number US1163).
- Element Washington DC LLC is a Recognized U.S. Certification Assessment Body (CAB # US0110) for ISSED Canada as designated by NIST under the U.S. and Canada Mutual Recognition Agreements (MRAs).

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 5 of 93

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **AA5171 Portable Digital Transceiver FCC ID: IPH-A5171** and **IC: 1792A-A5171**. The test data contained in this report pertains only to the emissions due to the EUT's WLAN (DTS) transmitter.

Test Device Serial No.: 3630652781, 3630652769, 3627311023

This device is a variant device that applies Data Referencing from a parent model approved under FCC ID: IPH-05171. A summary of the referenced data can be found in Section 7.0 and the corresponding data referencing spot-check data can be found in Section 9.0 of this test report.

2.2 Device Capabilities

This device contains the following capabilities:

Bluetooth (1x, EDR, LE), ANT+, 802.11b/g/n WLAN, NFC

Ch.	Frequency (MHz)	Ch.	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442		

Table 2-1. 802.11b/g/n Frequency/Channel Operations

The maximum achievable duty cycles for all modes were determined based on measurements performed on a spectrum analyzer in zero-span mode with RBW = 8MHz, VBW = 50MHz, and detector = peak per the guidance of Section 6.0 b) of KDB 558074 D01 v05r02 and ANSI C63.10-2020. The RBW and VBW were both greater than 50/T, where T is the minimum transmission duration, and the number of sweep points across T was greater than 100. The duty cycles are as follows:

Measured Duty Cycle			
802.11 Mode/Band		Duty Cycle [%]	DCCF
2.4GHz	b	100	N/A
	g	100	N/A
	n	100	N/A

Table 2-2. Measured Duty Cycles

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 6 of 93

The device supports the following data rates (shown in Mbps):

802.11b	802.11g	802.11n			
20MHz	20MHz	MCS Index HT	Spatial Stream	20MHz	
				0.8μs GI	0.4μs GI
1	6	0	1	6.5	7.2
2	9	1	1	13	14.4
5.5	12	2	1	19.5	21.7
11	18	3	1	26	28.9
-	24	4	1	39	43.3
-	36	5	1	52	57.8
-	48	6	1	58.5	65
-	54	7	1	65	72.2
-	-	8	2	13	14.4
-	-	9	2	26	28.9
-	-	10	2	39	43.3
-	-	11	2	52	57.8
-	-	12	2	78	86.7
-	-	13	2	104	115.6
-	-	14	2	117	130
-	-	15	2	130	144.4

Table 2-3. Supported Data Rates

2.3 Antenna Description

Following antenna gains provided by manufacturer were used for the testing. The validity of the calculated results is based on the accuracy of the information provided.

Frequency [GHz]	Antenna Gain (dBi)
2.4	-2.13

Table 2-4. Highest Antenna Gain

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 7 of 93

2.4 Test Configuration

The EUT was tested per the guidance of ANSI C63.10-2020 and KDB 558074 D01 v05r02. ANSI C63.10-2020 was used to reference the appropriate EUT setup for radiated spurious emissions testing and AC line conducted testing. See Sections 3.2 for AC line conducted emissions test setups, Section 3.3 for radiated emissions test setups, and 7.2, 7.3, 7.4, 7.5, 7.6, and 7.7 for antenna port conducted emissions test setups.

For emissions from 1GHz – 18GHz, low, mid, and high channels were tested with highest power and worst case configuration. The emissions below 1GHz and above 18GHz were tested with the highest transmitting power and the worst case channel were reported.

The EUT was manipulated through three orthogonal planes of X-orientation (flatbed), Y-orientation (landscape), and Z-orientation (portrait) during the testing. Only the worst case emissions were reported in this test report.

For AC line conducted and radiated test below 1GHz, following configuration were investigated and EUT powered by AC/DC was the worst case.

- EUT powered by AC/DC adaptor via USB-C cable with wire charger

2.5 Software and Firmware

The test was conducted with firmware version 5.00 installed on the EUT.

2.6 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and/or no modifications were made during testing.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 8 of 93

3.0 DESCRIPTION OF TESTS

3.1 Evaluation Procedure

The measurement procedures described in the American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices (ANSI C63.10-2020) and the guidance provided in KDB 558074 D01 v05r02 were used in the measurement of the EUT.

Deviation from measurement procedure.....None

3.2 AC Line Conducted Emissions

The line-conducted facility is located inside a 7m x 3.66m x 2.7m shielded enclosure. The shielded enclosure is manufactured by AP Americas. The shielding effectiveness of the shielded room is in accordance with MIL-Std-285 or NSA 65-6. A 1m x 1.5m wooden table 80cm high is placed 40cm away from the vertical wall and 80cm away from the sidewall of the shielded room. Two 10kHz-30MHz, 50Ω/50μH Line-Impedance Stabilization Networks (LISNs) are bonded to the shielded room floor. Power to the LISNs is filtered by external high-current high-insertion loss power line filters. The external power line filter is EPCOS 2X60A Power Line Filter (100dB Attenuation, 14kHz-18GHz) and the two EPCOs 2X48A filters (100dB Minimum Insertion Loss, 14kHz - 10GHz). These filters attenuate ambient signal noise from entering the measurement lines. These filters are also bonded to the shielded enclosure.

The EUT is powered from one LISN and the support equipment is powered from the second LISN. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and this supply line(s) will be connected to the second LISN. All interconnecting cables more than 1 meter were shortened to a 1 meter length by non-inductive bundling (serpentine fashion) and draped over the back edge of the test table. All cables were at least 40cm above the horizontal reference groundplane. Power cables for support equipment were routed down to the second LISN while ensuring that the cables were not draped over the second LISN.

Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the spectrum analyzer and exploratory measurements were made to determine the frequencies producing the maximum emission from the EUT. The spectrum was scanned from 150kHz to 30MHz with a spectrum analyzer. The detector function was set to peak mode for exploratory measurements while the bandwidth of the analyzer was set to 10kHz. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Once the worst case emissions have been identified, the one EUT cable configuration/arrangement and mode of operation that produced these emissions is used for final measurements on the same test site. The analyzer is set to CISPR quasi-peak and average detectors with a 9kHz resolution bandwidth for final measurements.

Line conducted emissions test results are shown in Section 7.9. Automated test software was used to perform the AC line conducted emissions testing. Automated measurement software utilized is Rohde & Schwarz EMC32, Version 10.50.40.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 9 of 93

3.3 Radiated Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. An 80cm tall test table made of Styrodur is placed on top of the turn table. For measurements above 1GHz, an additional Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

Per KDB 414788 D01 v01r01, radiated emission test sites other than open-field test sites (e.g., shielded anechoic chambers), may be employed for emission measurements below 30MHz if characterized so that the measurements correspond to those obtained at an open-field test site. To determine test site equivalency, a reference sample transmitting at 149kHz was measured on an open field test site (asphalt with no ground plane) and then measured in the 3m semi-anechoic chamber. A calibrated 60cm loop antenna was rotated about its vertical axis while the reference device was rotated through the X, Y and Z axis in order to capture the worst case level. A maximum deviation of 2.77dB at 149kHz was measured when comparing the 3 meter semi-anechoic chamber to the open field site.

For all measurements, the spectrum was scanned through all EUT azimuths and from 1 to 4 meter receive antenna height using a broadband antenna from 30MHz up to the upper frequency shown in 15.33 depending on the highest frequency generated or used in the device or on which the device operates or tunes. For frequencies above 1GHz, linearly polarized double ridge horn antennas were used. For frequencies below 30MHz, a calibrated loop antenna was used. When exploratory measurements were necessary, they were performed at 1 meter test distance inside the semi-anechoic chamber using broadband antennas, broadband amplifiers, and spectrum analyzers to determine the frequencies and modes producing the maximum emissions. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The test set-up was placed on top of the 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were arranged and manipulated to maximize each emission. Appropriate precaution was taken to ensure that all emissions from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth, and receive antenna height was noted for each frequency found.

Final measurements were made in the semi-anechoic chamber using calibrated, linearly polarized broadband and horn antennas. The test setup was configured to the setup that produced the worst case emissions. The spectrum analyzer was set to investigate all frequencies required for testing to compare the highest radiated disturbances with respect to the specified limits. The turntable containing the EUT was rotated through 360 degrees and the height of the receive antenna was varied 1 to 4 meters and stopped at the azimuth and height producing the maximum emission. Each emission was maximized by changing the orientation of the EUT through three orthogonal planes and changing the polarity of the receive antenna, whichever produced the worst-case emissions.

3.4 Environmental Conditions

The temperature is controlled within range of 15°C to 35°C. The relative humidity is controlled within range of 10% to 75%. The atmospheric pressure is monitored within the range 86-106kPa (860-1060mbar).

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 10 of 93

4.0 ANTENNA REQUIREMENTS

Excerpt from §15.203 of the FCC Rules/Regulations:

“An intentional radiator antenna shall be designed to ensure that no antenna other than that furnished by the responsible party can be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.”

- The antennas of the EUT are **permanently attached**.
- There are no provisions for connections to an external antenna.

Conclusion:

The EUT unit complies with the requirement of §15.203.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 11 of 93

5.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.23-2012. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	2.00
AC Line Conducted Disturbance	1.88
Radiated Disturbance (<30MHz)	4.24
Radiated Disturbance (30MHz - 1GHz)	4.96
Radiated Disturbance (1 - 18GHz)	5.18
Radiated Disturbance (>18GHz)	5.18

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 12 of 93

6.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance with the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
Agilent	N9020A	MXA Signal Analyzer	7/7/2025	Biennial	7/7/2027	MY56470202
Anritsu	ML2496A	Power Meter	4/6/2026	Annual	4/6/2027	1351001
Anritsu	MA2411B	Pulse Power Sensor	4/6/2026	Annual	4/6/2027	1315051
Anritsu	MA2411B	Pulse Power Sensor	7/3/2025	Annual	7/3/2026	1726261
ATM	180-442-KF	20dB Nominal Gain Horn Antenna	3/31/2026	Annual	3/31/2027	T058601-02
ETS-Lindgren	3117	Double Ridged Guide Horn (1-18 GHz)	4/21/2026	Annual	4/21/2027	218555
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2025	Annual	6/10/2026	-
Fairview Microwave/MCL	FMCA1975-36/BW-K10-2W44+	30MHz-40GHz RF Cable/Attenuator *	6/10/2026	Annual	6/10/2027	-
Keysight Technology	N9040B	UXA Signal Analyzer	6/9/2025	Annual	6/9/2026	MY60080210
Rohde & Schwarz	TS-PR18	Pre-Amplifier (1GHz - 18GHz)	8/6/2025	Annual	8/6/2026	101639
Rohde & Schwarz	FSW43	Spectrum Analyzer 2Hz to 43GHz	8/5/2025	Annual	8/5/2026	104093
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	12/2/2025	Annual	12/2/2026	102326
Rohde & Schwarz	TS-PR8	Pre-Amplifier (30MHz - 8GHz)	10/14/2025	Annual	10/14/2026	102328
Rohde & Schwarz	TS-PR1840	Pre-Amplifier (18GHz - 40GHz)	7/3/2025	Annual	7/3/2026	100057
Rohde & Schwarz	HFH2-Z2	Loop Antenna	6/26/2025	Annual	6/26/2026	100519
Rohde & Schwarz	ENV216	Two-Line V-Network	8/18/2025	Annual	8/18/2026	101363
Schwarzbeck	VULB 9162	Bilog Antenna (30MHz - 6GHz)	7/17/2025	Annual	7/17/2026	00302

Table 6-1. Test Equipment List

Note:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- * denotes passive equipment that have been internally verified/calibrated.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 13 of 93

7.0 TEST RESULTS

7.1 Summary

Company Name: Garmin International Inc.
 FCC ID: IPH-A5171
 IC: 1792A-A5171
 FCC Classification: Digital Transmission System (DTS)

FCC Part Section(s)	RSS Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference	Data Referencing
15.247(a)(2)	RSS-247 [6.3.1(a)]	6dB Bandwidth	> 500kHz	CONDUCTED	PASS	Section 7.3	Yes
2.1049	RSS-Gen [6.7]	Occupied Bandwidth	N/A		N/A	Section 7.3	Yes
15.247(b)(3)	RSS-247 [6.3.2]	Transmitter Output Power	< 1 Watt		PASS	Section 7.4	No
15.247(e)	RSS-247 [6.3.1(b)]	Transmitter Power Spectral Density	< 8dBm / 3kHz Band		PASS	Section 7.5	Yes
15.247(d)	RSS-247 [6.6]	Band Edge / Out-of-Band Emissions	≥ 20dBc		PASS	Section 7.6, 7.7	No
15.205 15.209	RSS-Gen [8.9]	General Field Strength Limits (Restricted Bands and Radiated Emission Limits)	Emissions in restricted bands must meet the radiated limits detailed in 15.209 (RSS-Gen [8.9])	RADIATED	PASS	Sections 7.8, 7.9	No
15.207	RSS-Gen [8.8]	AC Conducted Emissions 150kHz – 30MHz	< FCC 15.207 limits (RSS-Gen [8.8])	AC LINE CONDUCTED	PASS	Section 7.10	No

Table 7-1. Summary of Test Results

Notes:

1. All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
2. The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.
3. All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables and attenuators.
4. For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Conducted Automation," Version 1.5.0.
5. For radiated testing, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is Element "Chamber Automation," Version 3.6.1.
6. Data was referenced from model A05171 for the certification of AA5171. See Section 9.0 for spotcheck results.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 14 of 93

7.2 99% Occupied Bandwidth

§2.1049; RSS-Gen [6.7]

Test Overview and Limit

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2
RSS-Gen [6.7]

Test Settings

1. The signal analyzers' automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 99% occupied bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. Span = between 1.5x to 5x the OBW
3. RBW = in the range of 1- 5% of the OBW
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Trace mode = max hold
7. Sweep = auto couple
8. The trace was allowed to stabilize
9. If necessary, step 2 – 7 were repeated after changing the RBW such that it would be within 1 -5% of the 99% occupied bandwidth observed in Step 7

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 15 of 93

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes

1. All data rates and antenna configurations have been investigated, with tabular data reported for the worst-case data rate. Only the worst-case plot per mode was reported which corresponds to the narrowest 6dB bandwidth.


FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.	Page 16 of 93	

7.2.1 99% OBW Measurements


Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 99% Occupied Bandwidth [MHz]
2412	1	b	1Mbps	15.41
2437	6	b	1Mbps	15.75
2462	11	b	1Mbps	16.00
2412	1	g	6Mbps	19.95
2437	6	g	6Mbps	22.33
2462	11	g	6Mbps	18.30
2412	1	n	MCS0	18.07
2437	6	n	MCS0	18.06
2462	11	n	MCS0	18.26

Table 7-2. Conducted Bandwidth Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 17 of 93




Plot 7-1 99% OBW (20MHz BW 802.11b - Ch.11)



Plot 7-2 99% OBW (20MHz BW 802.11g - Ch.6)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 18 of 93



Plot 7-3 99% OBW (20MHz BW 802.11n - Ch.11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 19 of 93

7.3 6 dB Bandwidth

§15.247(a)(2); RSS-247 [6.3.1(a)]

Test Overview and Limit

The bandwidth at 6dB down from the highest in-band spectral density is measured with a spectrum analyzer connected to the transmitter antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The minimum permissible 6dB bandwidth is 500 kHz.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.8.2 Option 2
KDB 558074 D01 v05r02 – Section 8.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability of the spectrum analyzer was used to perform the 6dB bandwidth measurement. The "X" dB bandwidth parameter was set to X = 6. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 20 of 93

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-2. Test Instrument & Measurement Setup

Test Notes

1. All data rates and antenna configurations have been investigated, with tabular data reported for the worst-case data rate.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 21 of 93

7.3.1 6dB BW Measurements


Frequency [MHz]	Channel	802.11 MODE	Data Rate	Measured 6dB Bandwidth [MHz]	Minimum 6dB Bandwidth [MHz]	Pass/Fail
2412	1	b	1Mbps	10.06	0.50	Pass
2437	6	b	1Mbps	10.09	0.50	Pass
2462	11	b	1Mbps	10.09	0.50	Pass
2412	1	g	6Mbps	16.45	0.50	Pass
2437	6	g	6Mbps	16.39	0.50	Pass
2462	11	g	6Mbps	16.61	0.50	Pass
2412	1	n	MCS0	17.69	0.50	Pass
2437	6	n	MCS0	17.66	0.50	Pass
2462	11	n	MCS0	17.66	0.50	Pass

Table 7-3. Conducted Bandwidth Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 22 of 93




Plot 7-4 6dB BW Antenna 1 (20MHz BW 802.11b - Ch.1)



Plot 7-5 6dB BW Antenna 1 (20MHz BW 802.11g - Ch.6)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 23 of 93



Plot 7-6 6dB BW Antenna 1 (20MHz BW 802.11n - Ch.11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 24 of 93

7.4 Output Power Measurement

§15.247(b)(3); RSS-247 [6.3.2]

Test Overview and Limits

A transmitter antenna terminal of EUT is connected to the input of an RF power sensor. Measurement is made using a broadband power meter capable of making average measurements while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The average conducted output power of digital modulation systems operating in the 2400-2483.5 MHz band is 1 Watt. The conducted output power limit on paragraph above is based on the use of antennas with directional gains that do not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

For DTSs employing digital modulation techniques operating in the band 2400-2483.5 MHz, the average conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.9.2.3.2 Method AVGPM-G

KDB 558074 D01 v05r02 – Section 8.3.2.3 Measurement using a Power Meter (PM)

Test Settings

Method AVGPM-G (Average Power Measurement)

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter. The trace was averaged over 100 traces to obtain the final measured average power.

Test Setup

The EUT and measurement equipment were set up as shown in the diagrams below.



Figure 7-3. Test Instrument & Measurement Setup for Power Meter Measurements

Test Notes

1. All data rates have been investigated, and tabular data has been reported for the worst-case data rate.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 25 of 93

7.4.1 Output Power and Max EIRP Measurement

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	17.39	30.00	-12.61	-2.13	15.26	36.02	-20.76
2437	6	17.26	30.00	-12.74	-2.13	15.13	36.02	-20.89
2442	7	16.51	30.00	-13.49	-2.13	14.38	36.02	-21.65
2447	8	15.98	30.00	-14.02	-2.13	13.85	36.02	-22.17
2452	9	15.92	30.00	-14.08	-2.13	13.79	36.02	-22.23
2457	10	15.10	30.00	-14.90	-2.13	12.97	36.02	-23.05
2462	11	14.02	30.00	-15.98	-2.13	11.89	36.02	-24.13
2467	12	7.77	30.00	-22.23	-2.13	5.64	36.02	-30.38
2472	13	7.65	30.00	-22.35	-2.13	5.52	36.02	-30.50

Table 7-4. Average Conducted Output Power and Max EIRP Measurements (802.11b)

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	16.81	30.00	-13.19	-2.13	14.68	36.02	-21.34
2417	2	17.48	30.00	-12.52	-2.13	15.35	36.02	-20.67
2437	6	17.50	30.00	-12.50	-2.13	15.37	36.02	-20.65
2442	7	16.48	30.00	-13.52	-2.13	14.35	36.02	-21.67
2447	8	15.00	30.00	-15.00	-2.13	12.87	36.02	-23.15
2452	9	14.86	30.00	-15.14	-2.13	12.73	36.02	-23.29
2457	10	14.58	30.00	-15.42	-2.13	12.45	36.02	-23.57
2462	11	10.71	30.00	-19.29	-2.13	8.58	36.02	-27.44
2467	12	9.11	30.00	-20.89	-2.13	6.98	36.02	-29.04
2472	13	8.47	30.00	-21.53	-2.13	6.34	36.02	-29.68

Table 7-5. Average Conducted Output Power and Max EIRP Measurements (802.11g)

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	16.42	30.00	-13.58	-2.13	14.29	36.02	-21.73
2437	6	16.69	30.00	-13.31	-2.13	14.56	36.02	-21.47
2442	7	15.28	30.00	-14.72	-2.13	13.15	36.02	-22.87
2447	8	14.58	30.00	-15.42	-2.13	12.45	36.02	-23.57
2452	9	14.40	30.00	-15.60	-2.13	12.27	36.02	-23.75
2457	10	14.23	30.00	-15.77	-2.13	12.10	36.02	-23.92
2462	11	10.46	30.00	-19.54	-2.13	8.33	36.02	-27.69
2467	12	9.83	30.00	-20.17	-2.13	7.70	36.02	-28.32
2472	13	8.74	30.00	-21.26	-2.13	6.61	36.02	-29.41

Table 7-6. Average Conducted Output Power and Max EIRP Measurements (802.11n)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 26 of 93

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	19.28	30.00	-10.72	-2.13	17.15	36.02	-18.87
2437	6	19.17	30.00	-10.83	-2.13	17.04	36.02	-18.98
2442	7	18.53	30.00	-11.47	-2.13	16.40	36.02	-19.62
2447	8	17.99	30.00	-12.01	-2.13	15.86	36.02	-20.16
2452	9	17.92	30.00	-12.08	-2.13	15.79	36.02	-20.23
2457	10	17.17	30.00	-12.83	-2.13	15.04	36.02	-20.98
2462	11	16.13	30.00	-13.87	-2.13	14.00	36.02	-22.02
2467	12	10.14	30.00	-19.86	-2.13	8.01	36.02	-28.01
2472	13	10.03	30.00	-19.97	-2.13	7.90	36.02	-28.12

Table 7-7. Peak Conducted Output Power and Max EIRP Measurements (802.11b)

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	21.50	30.00	-8.50	-2.13	19.37	36.02	-16.65
2417	2	21.49	30.00	-8.51	-2.13	19.36	36.02	-16.66
2437	6	21.59	30.00	-8.41	-2.13	19.46	36.02	-16.56
2442	7	21.25	30.00	-8.75	-2.13	19.12	36.02	-16.90
2447	8	20.45	30.00	-9.55	-2.13	18.32	36.02	-17.70
2452	9	20.33	30.00	-9.67	-2.13	18.20	36.02	-17.82
2457	10	20.22	30.00	-9.78	-2.13	18.09	36.02	-17.93
2462	11	17.19	30.00	-12.81	-2.13	15.06	36.02	-20.96
2467	12	15.69	30.00	-14.31	-2.13	13.56	36.02	-22.46
2472	13	15.06	30.00	-14.94	-2.13	12.93	36.02	-23.09

Table 7-8. Peak Conducted Output Power and Max EIRP Measurements (802.11g)

Freq [MHz]	Channel	Conducted Power [dBm]	Conducted Power Limit [dBm]	Conducted Power Margin [dB]	Ant. Gain [dBi]	Max e.i.r.p. [dBm]	Max e.i.r.p. Limit [dBm]	e.i.r.p. Margin [dB]
2412	1	20.48	30.00	-9.52	-2.13	18.35	36.02	-17.67
2437	6	21.58	30.00	-8.42	-2.13	19.45	36.02	-16.57
2442	7	21.29	30.00	-8.71	-2.13	19.16	36.02	-16.86
2447	8	20.48	30.00	-9.52	-2.13	18.35	36.02	-17.67
2452	9	20.36	30.00	-9.64	-2.13	18.23	36.02	-17.79
2457	10	20.34	30.00	-9.66	-2.13	18.21	36.02	-17.81
2462	11	17.39	30.00	-12.61	-2.13	15.26	36.02	-20.76
2467	12	16.84	30.00	-13.16	-2.13	14.71	36.02	-21.31
2472	13	15.92	30.00	-14.08	-2.13	13.79	36.02	-22.23

Table 7-9. Peak Conducted Output Power and Max EIRP Measurements (802.11n)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 27 of 93



Sample e.i.r.p. Calculation:

At 2412MHz, the average conducted output power was calculated to be 17.39 dBm with directional gain of -2.13 dBi.

$$\text{e.i.r.p. (dBm)} = \text{Conducted Power (dBm)} + \text{Ant gain (dBi)}$$

$$17.39 \text{ dBm} + -2.13 \text{ dBi} = 15.26 \text{ dBm}$$

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 28 of 93

7.5 Power Spectral Density

§15.247(e); RSS-247 [6.3.1(b)]

Test Overview and Limit

The power spectral density is measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates were investigated and the worst case configuration results are reported in this section.

The maximum permissible power spectral density is 8 dBm in any 3 kHz band.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.10.3 & 11.10.5 Method AVGPSD-1 & AVGPSD-2
KDB 558074 D01 v05r02 – Section 8.4 DTS Maximum Power Spectral Density level in the fundamental emission

Test Settings

1. Analyzer was set to the center frequency of the DTS channel under investigation
2. Span > 1.5 times the OBW
3. RBW = 3kHz
4. VBW $\geq 3 \times$ RBW
5. Detector = power averaging (rms)
6. Number of sweep points $\geq 2 \times$ (span/RBW)
7. Sweep time = auto couple
8. Employ trace averaging (rms) mode over a minimum of 100 traces
9. Use the peak marker function to determine the maximum amplitude level

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 29 of 93

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.



Figure 7-4. Test Instrument & Measurement Setup

Test Notes

1. All data rates and channels were investigated, and tabular data has been reported. Only the worst-case plot was reported.



FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 30 of 93

7.5.1 Power Spectral Density Measurements


Frequency [MHz]	Channel No.	802.11 MODE	Data Rate	Measured Power Density [dBm/3kHz]	Max Power Density [dBm/3kHz]	Margin [dB]	Pass/Fail
2412	1	b	1Mbps	4.66	8.00	-3.34	Pass
2437	6	b	1Mbps	4.60	8.00	-3.40	Pass
2462	11	b	1Mbps	0.83	8.00	-7.17	Pass
2412	1	g	6Mbps	-8.14	8.00	-16.14	Pass
2437	6	g	6Mbps	-8.10	8.00	-16.10	Pass
2462	11	g	6Mbps	-13.46	8.00	-21.46	Pass
2412	1	n	MCS0	-8.92	8.00	-16.92	Pass
2437	6	n	MCS0	-9.39	8.00	-17.39	Pass
2462	11	n	MCS0	-14.76	8.00	-22.76	Pass

Table 7-10. Conducted Power Density Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 31 of 93



FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 32 of 93



Plot 7-9 PSD (20MHz BW 802.11n - Ch.1)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 33 of 93

7.6 Conducted Authorized Band Edge

§15.247(d); RSS-247 [6.6]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the PSD procedure (Section 7.5).

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.11.3
KDB 558074 D01 v05r02 – Section 8.7.2

Test Settings

1. Start and stop frequency were set such that the band edge would be placed in the center of the plot
2. Span was set large enough so as to capture all out of band emissions near the band edge
3. RBW = 100kHz
4. VBW $\geq 3 \times$ RBW
5. Detector = Peak
6. Number of sweep points $\geq 2 \times$ Span/RBW
7. Trace mode = Max hold
8. Sweep time = auto couple
9. The trace was allowed to stabilize

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-5. Test Instrument & Measurement Setup

Test Notes


1. All data rates have been investigated and only the worst case data rate is reported.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 34 of 93

7.6.1 Conducted Emissions at the Band Edge




Plot 7-10. Band Edge Plot (802.11b – Ch. 1)



Plot 7-11. Band Edge Plot (802.11b – Ch. 7)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 35 of 93




Plot 7-12. Band Edge Plot (802.11b – Ch. 8)




Plot 7-13. Band Edge Plot (802.11b – Ch. 9)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 36 of 93




Plot 7-14. Band Edge Plot (802.11b – Ch. 10)




Plot 7-15. Band Edge Plot (802.11b – Ch. 11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 37 of 93




Plot 7-18. Band Edge Plot (802.11g – Ch. 1)



Plot 7-19. Band Edge Plot (802.11g – Ch. 2)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 39 of 93



Plot 7-22. Band Edge Plot (802.11g – Ch. 8)




Plot 7-23. Band Edge Plot (802.11g – Ch. 9)


FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 41 of 93

Plot 7-24. Band Edge Plot (802.11g – Ch. 10)

Plot 7-25. Band Edge Plot (802.11g – Ch. 11)




Plot 7-26. Band Edge Plot (802.11g – Ch. 12)




Plot 7-27. Band Edge Plot (802.11g – Ch. 13)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 43 of 93



Plot 7-28. Band Edge Plot (802.11n (2.4GHz) – Ch. 1)




Plot 7-29. Band Edge Plot (802.11n (2.4GHz) – Ch. 7)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 44 of 93




Plot 7-30. Band Edge Plot (802.11n (2.4GHz) – Ch. 8)




Plot 7-31. Band Edge Plot (802.11n (2.4GHz) – Ch. 9)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 45 of 93




Plot 7-32. Band Edge Plot (802.11n (2.4GHz) – Ch. 10)




Plot 7-33. Band Edge Plot (802.11n (2.4GHz) – Ch. 11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 46 of 93



Plot 7-34. Band Edge Plot (802.11n (2.4GHz) – Ch. 12)



Plot 7-35. Band Edge Plot (802.11n (2.4GHz) – Ch. 13)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.	Page 47 of 93	

7.7 Conducted Spurious Emissions

§15.247(d); RSS-247 [6.6]

Test Overview and Limit

All out of band emissions are measured with a spectrum analyzer connected to the antenna terminal of the EUT while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies.

The limit for out-of-band spurious emissions at the band edge is 20dB below the fundamental emission level, as determined from the in-band power measurement of the DTS channel performed in a 100kHz bandwidth per the procedure in Section 11.11 of ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Test Procedure Used

ANSI C63.10-2020 – Subclause 11.11.3
 KDB 558074 D01 v05r02 – Section 8.5
 ANSI C63.10-2020 – Subclause 14.3.3
 KDB 662911 D01 v02r01 – Section E)3)b)

Test Settings

1. Start frequency was set to 30MHz and stop frequency was set to 25GHz (separated into two plots per channel)
2. RBW = 100kHz
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep time = auto couple
7. The trace was allowed to stabilize

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 48 of 93

sTest Setup

The EUT and measurement equipment were set up as shown in the diagram below.





Figure 7-6. Test Instrument & Measurement Setup

Test Notes


1. The conducted spurious emissions were measured to relative limits. Therefore, in accordance with ANSI C63.10-2020 and KDB 662911 D01 v02r01 Section E)3)b), it was unnecessary to show compliance through the summation of test results of the individual outputs.
2. All modes, data rates, and antenna configurations were investigated and only the worse case is reported.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 49 of 93

7.7.1 Conducted Spurious Emission




Plot 7-36. Conducted Spurious Plot (802.11b – Ch. 1)




Plot 7-37. Conducted Spurious Plot (802.11b – Ch. 6)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 50 of 93




Plot 7-38. Conducted Spurious Plot (802.11b – Ch. 11)




Plot 7-39. Conducted Spurious Plot (802.11g – Ch. 1)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 51 of 93




Plot 7-40. Conducted Spurious Plot (802.11g – Ch. 6)




Plot 7-41. Conducted Spurious Plot (802.11g – Ch. 11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 52 of 93




Plot 7-42. Conducted Spurious Plot (802.11n – Ch. 1)



Plot 7-43. Conducted Spurious Plot (802.11n – Ch. 6)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 53 of 93



Plot 7-44. Conducted Spurious Plot (802.11n – Ch. 11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 54 of 93

7.8 Radiated Spurious Emissions – Above 1 GHz

§15.247(d) §15.205 & §15.209; RSS-Gen [8.9]

Test Overview and Limit

All out of band radiated spurious emissions are measured with a spectrum analyzer connected to a receive antenna while the EUT is operating at its maximum duty cycle, at maximum power, and at the appropriate frequencies. All data rates and modes were investigated for radiated spurious emissions. Only the radiated emissions of the configuration that produced the worst case emissions are reported in this section.

All out of band emissions appearing in a restricted band as specified in Section 15.205 of the Title 47 CFR and Table 7 of RSS-Gen (8.10) must not exceed the limits shown in Table 7-11 per Section 15.209 and RSS-Gen (8.9).

Frequency	Field Strength [$\mu\text{V/m}$]	Measured Distance [Meters]
Above 960.0 MHz	500	3

Table 7-11. Radiated Limits

Test Procedures Used

ANSI C63.10-2020 – Subclause 6.6.4.3
KDB 558074 D01 v05r02 – Sections 8.6, 8.7

Test Settings

Average Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = power average (RMS)
5. Number of measurement points = 1001 (Number of points must be $\geq 2 \times \text{span/RBW}$)
6. Sweep time = auto
7. Trace (RMS) averaging was performed over at least 100 traces

Peak Field Strength Measurements

1. Analyzer center frequency was set to the frequency of the radiated spurious emission of interest
2. RBW = 1MHz
3. VBW = 3MHz
4. Detector = peak
5. Sweep time = auto couple
6. Trace mode = max hold
7. Trace was allowed to stabilize

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10-IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 55 of 93

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-7. Radiated Measurement Setup

Test Notes

1. The optional test procedures for antenna port conducted measurements of unwanted emissions per the guidance of KDB 558074 D01 v05r02 were not used to evaluate this device for compliance to radiated limits. All Radiated Spurious Emissions levels were measured in a radiated test setup.
2. All emissions lying in restricted bands specified in Section 15.205 and Section 8.10 of RSS-Gen are below the limit shown in Table 7-11.
3. The antenna is manipulated through typical positions, polarity and length during the tests. The EUT is manipulated through three orthogonal planes.
4. This unit was tested with its standard battery.
5. The spectrum is measured from 9kHz to the 10th harmonic of the fundamental frequency of the transmitter using CISPR quasi peak detector below 1GHz. Above 1 GHz, average and peak measurements were taken using linearly polarized horn antennas.
6. D is the measurement test distance and emissions 1-18GHz were measured at a 3 meters test distance while emissions above 18GHz were measured at a 1 meter test distance with the application of a distance correction factor.
7. The wide spectrum spurious emissions plots shown on the following pages are used only for the purpose of emission identification. Any emissions found to be within 20dB of the limit are fully investigated and the results are shown in this section.
8. The "-" shown in the following RSE tables are used to denote a noise floor measurement.
9. All data rates and antenna configurations were investigated and only the worst case is reported.
10. The unit was tested at its highest output power.
11. The unit was tested with all possible modes and only the highest emission is reported.

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 56 of 93

Sample Calculations

Determining Spurious Emissions Levels

- Field Strength Level $_{[dB\mu V/m]} = \text{Analyzer Level }_{[dBm]} + 107 + \text{AFCL }_{[dB/m]}$
- $\text{AFCL }_{[dB/m]} = \text{Antenna Factor }_{[dB/m]} + \text{Cable Loss }_{[dB]} - \text{Preamplifier Gain }_{[dB]}$
- $\text{Margin }_{[dB]} = \text{Field Strength Level }_{[dB\mu V/m]} - \text{Limit }_{[dB\mu V/m]}$


Radiated Band Edge Measurement Offset

- The amplitude offset shown in the radiated restricted band edge plots in Section 7.8.2 was calculated using the formula:

$$\text{Offset (dB)} = (\text{Antenna Factor} + \text{Cable Loss} + \text{Attenuator}) - \text{Preamplifier Gain}$$

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 57 of 93

7.8.1 Radiated Spurious Emission Measurements




Plot 7-45. Radiated Spurious Emissions above 1GHz (802.11b – Ch. 1)

Mode:	802.11b
Data Rate:	11Mbps
Distance of Measurements:	3 Meters
Operating Frequency:	2412MHz
Channel:	01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
4824.00	Avg	H	368	222	-76.73	7.04	37.31	53.98	-16.67
4824.00	Peak	H	368	222	-68.02	7.04	46.02	73.98	-27.96
12060.00	Avg	V	-	-	-83.70	18.38	41.68	53.98	-12.30
12060.00	Peak	V	-	-	-72.03	18.75	53.72	73.98	-20.26
14472.00	Avg	V	-	-	-83.81	20.70	43.89	53.98	-10.09
14472.00	Peak	V	-	-	-71.89	21.41	56.52	73.98	-17.46

Table 7-12. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 58 of 93




Plot 7-46. Radiated Spurious Emissions above 1GHz (802.11b – Ch. 6)

Mode: 802.11b
Data Rate: 11Mbps
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
4874.00	Avg	V	112	356	-79.09	7.97	35.88	53.98	-18.10
4874.00	Peak	V	112	356	-68.44	7.97	46.53	73.98	-27.45
7311.00	Avg	V	287	149	-67.77	10.78	50.01	53.98	-3.97
7311.00	Peak	V	287	149	-61.12	10.78	56.66	73.98	-17.32
12185.00	Avg	-	-	-	-83.75	18.22	41.46	53.98	-12.52
12185.00	Peak	-	-	-	-71.92	18.22	53.29	73.98	-20.69

Table 7-13. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 59 of 93



Plot 7-47. Radiated Spurious Emissions above 1GHz (802.11b – Ch. 11)



Plot 7-48. Radiated Spurious Emissions above 18GHz (802.11b – Ch.11)


FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 60 of 93

Mode: 802.11b
 Data Rate: 11Mbps
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	-	-	-	-80.32	7.34	0.00	34.02	53.98	-19.96
4924.00	Peak	-	-	-	-68.63	7.34	0.00	45.71	73.98	-28.27
7386.00	Avg	H	101	50	-68.02	11.06	0.00	50.04	53.98	-3.94
7386.00	Peak	H	101	50	-61.64	11.06	0.00	56.42	73.98	-17.56
12310.00	Avg	-	-	-	-84.01	18.65	0.00	41.64	53.98	-12.34
12310.00	Peak	-	-	-	-72.38	18.65	0.00	53.28	73.98	-20.70
19696.00	Avg	-	-	-	-60.24	-7.91	-9.54	29.31	53.98	-24.67
19696.00	Peak	-	-	-	-49.07	-7.91	-9.54	40.47	73.98	-33.51
22158.00	Avg	-	-	-	-60.92	-7.45	-9.54	29.08	53.98	-24.89
22158.00	Peak	-	-	-	-49.35	-7.45	-9.54	40.66	73.98	-33.32

Table 7-14. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.	Page 61 of 93	




Plot 7-49. Radiated Spurious Emissions above 1GHz (802.11g – Ch. 1)

Mode: 802.11g
Data Rate: MCS15
Distance of Measurements: 3 Meters
Operating Frequency: 2412MHz
Channel: 01

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBuV/m]	Limit [dBuV/m]	Margin [dB]
4824.00	Avg	-	-	-	-80.06	7.17	34.11	53.98	-19.87
4824.00	Peak	-	-	-	-68.77	7.17	45.40	73.98	-28.58
12060.00	Avg	-	-	-	-83.36	18.75	42.39	53.98	-11.59
12060.00	Peak	-	-	-	-72.86	18.75	52.89	73.98	-21.09
14472.00	Avg	-	-	-	-83.76	20.70	43.93	53.98	-10.05
14472.00	Peak	-	-	-	-71.89	20.70	55.80	73.98	-18.18

Table 7-15. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 62 of 93




Plot 7-50. Radiated Spurious Emissions above 1GHz (802.11g – Ch. 6)

Mode: 802.11g
Data Rate: MCS15
Distance of Measurements: 3 Meters
Operating Frequency: 2437MHz
Channel: 06


Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4874.00	Avg	-	-	-	-79.50	7.45	34.94	53.98	-19.04
4874.00	Peak	-	-	-	-68.45	7.45	45.99	73.98	-27.99
7311.00	Avg	V	289	143	-68.71	10.78	49.07	53.98	-4.91
7311.00	Peak	V	289	143	-56.69	10.78	61.09	73.98	-12.89
12185.00	Avg	-	-	-	-83.81	18.57	41.76	53.98	-12.22
12185.00	Peak	-	-	-	-72.26	18.57	53.31	73.98	-20.67

Table 7-16. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 63 of 93



Plot 7-51. Radiated Spurious Emissions above 1GHz (802.11g – Ch. 11)



Plot 7-52. Radiated Spurious Emissions above 18GHz (802.11g – Ch.11)

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.		Page 64 of 93

Mode: 802.11g
 Data Rate: MCS15
 Distance of Measurements: 3 Meters
 Operating Frequency: 2462MHz
 Channel: 11

Frequency [MHz]	Detector	Ant. Pol. [H/V]	Antenna Height [cm]	Turntable Azimuth [degree]	Analyzer Level [dBm]	AFCL [dB/m]	Distance Correction Factor [dB]	Field Strength [dBμV/m]	Limit [dBμV/m]	Margin [dB]
4924.00	Avg	-	-	-	-80.35	7.38	0.00	34.03	53.98	-19.95
4924.00	Peak	-	-	-	-68.92	7.38	0.00	45.46	73.98	-28.52
7386.00	Avg	H	103	51	-68.08	11.06	0.00	49.98	53.98	-4.00
7386.00	Peak	H	103	51	-55.41	11.06	0.00	62.65	73.98	-11.32
12310.00	Avg	-	-	-	-83.91	18.67	0.00	41.77	53.98	-12.21
12310.00	Peak	-	-	-	-72.43	18.67	0.00	53.24	73.98	-20.74
19696.00	Avg	-	-	-	-60.10	-7.85	-9.54	29.51	53.98	-24.47
19696.00	Peak	-	-	-	-48.82	-7.85	-9.54	40.79	73.98	-33.19
22158.00	Avg	-	-	-	-60.78	-7.45	-9.54	29.22	53.98	-24.75
22158.00	Peak	-	-	-	-48.68	-7.45	-9.54	41.33	73.98	-32.65

Table 7-17. Radiated Measurements

FCC ID: IPH-A5171 IC: 1792A-A5171		Test Dates: 02/17/2026 - 07/07/2026	EUT Type: Portable Digital Transceiver	Approved by: Technical Manager
Test Report S/N: 1C2605260039-10.IPH		This report is Blockchain Verified. To verify the report authenticity, please visit https://www.blockchain-verified.com or by clicking on the Blockchain logo.	Page 65 of 93	