


FCC Test Report

FCC ID : IPH-B3697
Equipment : Watch and activity monitor
Model No. : AB3697
Brand Name : GARMIN
Applicant : Garmin International, Inc.
Address : 1200 E. 151st Street Olathe, KS 66062 United States
Standard : 47 CFR FCC Part 15.225
Received Date : May 28, 2019
Tested Date : Jul. 22 ~ Jul. 24, 2019

We, International Certification Corp., would like to declare that the tested sample has been evaluated and in compliance with the requirement of the above standards. The test results contained in this report refer exclusively to the product. It may be duplicated completely for legal use with the approval of the applicant. It shall not be reproduced except in full without the written approval of our laboratory.

Reviewed by:



Along Chen / Assistant Manager

Approved by:



Gary Chang / Manager



Table of Contents

1	GENERAL DESCRIPTION	5
1.1	Information.....	5
1.2	Local Support Equipment List	6
1.3	Test Setup Chart	6
1.4	The Equipment List	7
1.5	Test Standards	8
1.6	Deviation from Test Standard and Measurement Procedure.....	8
1.7	Measurement Uncertainty	8
2	TEST CONFIGURATION.....	9
2.1	Testing Condition	9
2.2	The Worst Test Modes and Channel Details	9
3	TRANSMITTER TEST RESULTS	10
3.1	Conducted Emissions.....	10
3.2	20dB and Occupied Bandwidth.....	13
3.3	Field Strength of Fundamental Emissions and Spectrum Mask	15
3.4	Unwanted Emissions into Restricted Frequency Bands	17
3.5	Frequency Stability.....	24
4	TEST LABORATORY INFORMATION	26

Release Record

Report No.	Version	Description	Issued Date
FR952804NF	Rev. 01	Initial issue	Aug. 05, 2019

Summary of Test Results

FCC Rules	Test Items	Measured	Result
15.207	Conducted Emissions	[dBuV]: 0.779MHz 25.99 (Margin -20.01dB) - AV	Pass
15.225(a)	Field strength of fundamental emissions and spectrum mask	[dBuV/m at 3m]: 41.58 24.86 (Margin -15.14dB)	Pass
15.225(d)	Field strength of any emissions appearing outside of the 13.110-14.010 MHz band	Meet the requirement of limit	Pass
15.225(e)	Frequency tolerance	Meet the requirement of limit	Pass
15.215 (c)	20dB bandwidth	Meet the requirement of limit	Pass
15.203	Antenna Requirement	Meet the requirement of limit	Pass
N/A means Not Applicable.			

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

1 General Description

1.1 Information

The EUT comes in three different types of strap materials in the market. One is leather, another is metal, and the other is silicon.

1.1.1 Specification of the Equipment under Test (EUT)

RF General Information			
Frequency Range (MHz)	Modulation	Ch. Frequency (MHz)	Channel Number
13.553 – 13.567	ASK	13.56	1

1.1.2 Antenna Details

Ant. No.	Type	Gain (dBi)	Connector	Remark
1	Loop antenna	---	FPC	---

1.1.3 EUT Operational Condition

Supply Voltage	5.0Vdc from AC adapter 3.8Vdc from Battery		
Operational Voltage	☒ Vnom (3.8 V)	☒ Vmax (4.35 V)	☒ Vmin (3.4V)

1.1.4 Accessories

No.	Equipment	Description
1	Battery	Brand: Garmin Model: 361-00130-00 Power Rating: 3.8Vdc, 66mAh
2	USB cable	Brand: Garmin Model: 320-01069-10 Power Line: 0.52m shielded without core

1.1.5 Test Tool and Power Index


Test Tool	Garmin USB Monitor, Version: V3.00
Power Index	Default

1.2 Local Support Equipment List


Support Equipment List					
No.	Equipment	Brand	Model	FCC ID	Remarks
1	Adapter	Apple	A1385	---	---

1.3 Test Setup Chart

Battery Mode



Charging Mode



1.4 The Equipment List

Test Item	Conducted Emission				
Test Site	Conduction room 1 / (CO01-WS)				
Tested Date	Jul. 22, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Receiver	R&S	ESR3	101657	Jan. 08, 2019	Jan. 07, 2020
LISN	SCHWARZBECK	Schwarzbeck 8127	8127-667	Nov. 05, 2018	Nov. 04, 2019
RF Cable-CON	Woken	CFD200-NL	CFD200-NL-001	Oct. 23, 2018	Oct. 23, 2019
Measurement Software	AUDIX	e3	6.120210k	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	Radiated Emission				
Test Site	966 chamber 1 / (03CH01-WS)				
Tested Date	Jul. 24, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101498	Dec. 27, 2018	Dec. 26, 2019
Receiver	R&S	ESR3	101658	Dec. 11, 2018	Dec. 10, 2019
Bilog Antenna	SCHWARZBECK	VULB9168	VULB9168-522	Jul. 12, 2019	Jul. 11, 2020
Horn Antenna 1G-18G	SCHWARZBECK	BBHA 9120 D	BBHA 9120 D 1096	Dec. 18, 2018	Dec. 17, 2019
Horn Antenna 18G-40G	SCHWARZBECK	BBHA 9170	BBHA 9170517	Nov. 15, 2018	Nov. 14, 2019
Loop Antenna	R&S	HFH2-Z2	100330	Nov. 09, 2018	Nov. 08, 2019
Loop Antenna Cable	KOAX KABEL	101354-BW	101354-BW	Oct. 08, 2018	Oct. 07, 2019
Preamplifier	EMC	EMC02325	980225	Jul. 09, 2019	Jul. 08, 2020
Preamplifier	Agilent	83017A	MY39501308	Oct. 04, 2018	Oct. 03, 2019
Preamplifier	EMC	EMC184045B	980192	Aug. 09, 2018	Aug. 08, 2019
RF Cable	EMC	EMC104-SM-SM-8000	181106	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16019/4	Oct. 08, 2018	Oct. 07, 2019
RF Cable	HUBER+SUHNER	SUCOFLEX104	MY16014/4	Oct. 08, 2018	Oct. 07, 2019
LF cable 1M	EMC	EMCCFD400-NM-NM-1000	160502	Oct. 08, 2018	Oct. 07, 2019
LF cable 3M	Woken	CFD400NL-LW	CFD400NL-001	Oct. 08, 2018	Oct. 07, 2019
LF cable 10M	Woken	CFD400NL-LW	CFD400NL-002	Oct. 08, 2018	Oct. 07, 2019
Measurement Software	AUDIX	e3	6.120210g	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

Test Item	RF Conducted				
Test Site	(TH01-WS)				
Tested Date	Jul. 24, 2019				
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Calibration Until
Spectrum Analyzer	R&S	FSV40	101063	Apr. 17, 2019	Apr. 16, 2020
Power Meter	Anritsu	ML2495A	1241002	Oct. 09, 2018	Oct. 08, 2019
Power Sensor	Anritsu	MA2411B	1207366	Oct. 09, 2018	Oct. 08, 2019
TEMP&HUMIDITY CHAMBER	GIANT FORCE	GCT-225-40-SP-SD	MAF1212-002	Dec. 05, 2018	Dec. 04, 2019
DC POWER SOURCE	GW INSTRON	GPC-6030D	EM892433	Oct. 25, 2018	Oct. 24, 2019
AC POWER SOURCE	APC	AFC-500W	F312060012	Nov. 29, 2018	Nov. 28, 2019
Measurement Software	Sporton	SENSE-15247_FS	V5.10.1	NA	NA
Note: Calibration Interval of instruments listed above is one year.					

1.5 Test Standards

According to the specification of EUT, the EUT must comply with following standards and KDB documents.

47 CFR FCC Part 15.225

ANSI C63.10-2013

1.6 Deviation from Test Standard and Measurement Procedure

None

1.7 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty	
Parameters	Uncertainty
Bandwidth	±34.130 Hz
Conducted power	±0.808 dB
Frequency error	±1×10 ⁻⁹
Conducted emission	±2.715 dB
AC conducted emission	±2.92 dB
Radiated emission ≤ 1GHz	±3.41 dB
Temperature	±0.4 °C

2 Test Configuration

2.1 Testing Condition

Test Item	Test Site	Ambient Condition	Tested By
AC Conduction	CO01-WS	25°C / 59%	Alex Tsai
Radiated Emissions	03CH01-WS	28°C / 63%	Roger Lu
RF Conducted	TH01-WS	23°C / 63%	Brad Wu

- FCC Designation No.: TW2732
- FCC site registration No.: 181692
- ISSED#: 10807A-1
- CAB identifier: TW2732

2.2 The Worst Test Modes and Channel Details

Test item	Mode	Test Frequency (MHz)	Test Configuration
AC Power Line Conducted Emissions	Charging	---	2
Unwanted Emissions into Restricted Frequency Bands < 30MHz	NFC	13.56	1
Unwanted Emissions into Restricted Frequency Bands > 30MHz	NFC	13.56	1
	Charging	--	2
Frequency tolerance	NFC	13.56	1
20dB bandwidth	NFC	13.56	1

NOTE:

1. The EUT was pretested with 3 orientations placed on the table for the radiated emission measurement – X, Y, and Z-plane. The **Z-plane** results were found as the worst case and were shown in this report.
2. The test configurations are listed as follows:
Configuration 1 : Battery mode
Configuration 2 : Charging mode
3. Three different types of strap materials (leather, metal and silicon) had been covered during the pretest and found that silicon strap material was the worst case and was selected for final test.

3 Transmitter Test Results

3.1 Conducted Emissions

3.1.1 Limit of Conducted Emissions


Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: * Decreases with the logarithm of the frequency.

3.1.2 Test Procedures

1. The device is placed on a test table, raised 80 cm above the reference ground plane. The vertical conducting plane is located 40 cm to the rear of the device.
2. The device is connected to line impedance stabilization network (LISN) and other accessories are connected to other LISN. Measured levels of AC power line conducted emission are across the 50 Ω LISN port.
3. AC conducted emission measurements is made over frequency range from 150 kHz to 30 MHz.
4. This measurement was performed with AC 120V/60Hz


3.1.3 Test Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

3.1.4 Test Result of Conducted Emissions

Mode	Charging	Test Freq. (MHz)	---
Power Phase	Line		



	Freq	Level	Limit	Over	Read	LISN	cable	
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark
			dBuV	dB	dBuV	dB	dB	
1	0.171	17.13	54.90	-37.77	7.39	9.53	0.06	Average
2	0.171	31.74	64.90	-33.16	22.00	9.53	0.06	QP
3	0.336	20.39	49.31	-28.92	10.51	9.56	0.08	Average
4	0.336	29.23	59.31	-30.08	19.35	9.56	0.08	QP
5*	0.779	25.99	46.00	-20.01	16.02	9.59	0.09	Average
6	0.779	34.46	56.00	-21.54	24.49	9.59	0.09	QP
7	3.293	20.93	46.00	-25.07	10.70	9.61	0.25	Average
8	3.293	27.12	56.00	-28.88	16.89	9.61	0.25	QP
9	6.089	21.58	50.00	-28.42	11.21	9.63	0.35	Average
10	6.089	27.88	60.00	-32.12	17.51	9.63	0.35	QP
11	9.668	18.10	50.00	-31.90	7.62	9.65	0.43	Average
12	9.668	24.57	60.00	-35.43	14.09	9.65	0.43	QP

Note 1: Level (dBuV) = Read Level (dBuV) + LISN Factor (dB) + Cable Loss (dB).
 2: Over Limit (dB) = Level (dBuV) – Limit Line (dBuV).

Mode	Charging	Test Freq. (MHz)	---																																																																																																																																							
Power Phase	Neutral																																																																																																																																									
Level (dBUV) Frequency (MHz) <table><thead><tr><th></th><th>Freq</th><th>Level</th><th>Limit</th><th>Over</th><th>Read</th><th>LISN</th><th>cable</th><th></th></tr><tr><th></th><th>MHz</th><th>dBuV</th><th>Line</th><th>Limit</th><th>Level</th><th>factor</th><th>loss</th><th>Remark</th></tr><tr><th></th><th></th><th></th><th>dBuV</th><th>dB</th><th>dBuV</th><th>dB</th><th>dB</th><th></th></tr></thead><tbody><tr><td>1</td><td>0.162</td><td>28.23</td><td>55.34</td><td>-27.11</td><td>18.48</td><td>9.57</td><td>0.06</td><td>Average</td></tr><tr><td>2</td><td>0.162</td><td>37.20</td><td>65.34</td><td>-28.14</td><td>27.45</td><td>9.57</td><td>0.06</td><td>QP</td></tr><tr><td>3</td><td>0.243</td><td>17.57</td><td>52.00</td><td>-34.43</td><td>7.78</td><td>9.59</td><td>0.07</td><td>Average</td></tr><tr><td>4</td><td>0.243</td><td>29.30</td><td>62.00</td><td>-32.70</td><td>19.51</td><td>9.59</td><td>0.07</td><td>QP</td></tr><tr><td>5*</td><td>0.771</td><td>25.56</td><td>46.00</td><td>-20.44</td><td>15.64</td><td>9.63</td><td>0.09</td><td>Average</td></tr><tr><td>6</td><td>0.771</td><td>32.99</td><td>56.00</td><td>-23.01</td><td>23.07</td><td>9.63</td><td>0.09</td><td>QP</td></tr><tr><td>7</td><td>1.282</td><td>17.45</td><td>46.00</td><td>-28.55</td><td>7.45</td><td>9.64</td><td>0.12</td><td>Average</td></tr><tr><td>8</td><td>1.282</td><td>24.39</td><td>56.00</td><td>-31.61</td><td>14.39</td><td>9.64</td><td>0.12</td><td>QP</td></tr><tr><td>9</td><td>4.478</td><td>18.40</td><td>46.00</td><td>-27.60</td><td>8.17</td><td>9.67</td><td>0.30</td><td>Average</td></tr><tr><td>10</td><td>4.478</td><td>24.96</td><td>56.00</td><td>-31.04</td><td>14.73</td><td>9.67</td><td>0.30</td><td>QP</td></tr><tr><td>11</td><td>6.089</td><td>19.85</td><td>50.00</td><td>-30.15</td><td>9.54</td><td>9.68</td><td>0.35</td><td>Average</td></tr><tr><td>12</td><td>6.089</td><td>25.94</td><td>60.00</td><td>-34.06</td><td>15.63</td><td>9.68</td><td>0.35</td><td>QP</td></tr></tbody></table>					Freq	Level	Limit	Over	Read	LISN	cable			MHz	dBuV	Line	Limit	Level	factor	loss	Remark				dBuV	dB	dBuV	dB	dB		1	0.162	28.23	55.34	-27.11	18.48	9.57	0.06	Average	2	0.162	37.20	65.34	-28.14	27.45	9.57	0.06	QP	3	0.243	17.57	52.00	-34.43	7.78	9.59	0.07	Average	4	0.243	29.30	62.00	-32.70	19.51	9.59	0.07	QP	5*	0.771	25.56	46.00	-20.44	15.64	9.63	0.09	Average	6	0.771	32.99	56.00	-23.01	23.07	9.63	0.09	QP	7	1.282	17.45	46.00	-28.55	7.45	9.64	0.12	Average	8	1.282	24.39	56.00	-31.61	14.39	9.64	0.12	QP	9	4.478	18.40	46.00	-27.60	8.17	9.67	0.30	Average	10	4.478	24.96	56.00	-31.04	14.73	9.67	0.30	QP	11	6.089	19.85	50.00	-30.15	9.54	9.68	0.35	Average	12	6.089	25.94	60.00	-34.06	15.63	9.68	0.35	QP
	Freq	Level	Limit	Over	Read	LISN	cable																																																																																																																																			
	MHz	dBuV	Line	Limit	Level	factor	loss	Remark																																																																																																																																		
			dBuV	dB	dBuV	dB	dB																																																																																																																																			
1	0.162	28.23	55.34	-27.11	18.48	9.57	0.06	Average																																																																																																																																		
2	0.162	37.20	65.34	-28.14	27.45	9.57	0.06	QP																																																																																																																																		
3	0.243	17.57	52.00	-34.43	7.78	9.59	0.07	Average																																																																																																																																		
4	0.243	29.30	62.00	-32.70	19.51	9.59	0.07	QP																																																																																																																																		
5*	0.771	25.56	46.00	-20.44	15.64	9.63	0.09	Average																																																																																																																																		
6	0.771	32.99	56.00	-23.01	23.07	9.63	0.09	QP																																																																																																																																		
7	1.282	17.45	46.00	-28.55	7.45	9.64	0.12	Average																																																																																																																																		
8	1.282	24.39	56.00	-31.61	14.39	9.64	0.12	QP																																																																																																																																		
9	4.478	18.40	46.00	-27.60	8.17	9.67	0.30	Average																																																																																																																																		
10	4.478	24.96	56.00	-31.04	14.73	9.67	0.30	QP																																																																																																																																		
11	6.089	19.85	50.00	-30.15	9.54	9.68	0.35	Average																																																																																																																																		
12	6.089	25.94	60.00	-34.06	15.63	9.68	0.35	QP																																																																																																																																		
Note 1: Level (dBUV) = Read Level (dBUV) + LISN Factor (dB) + Cable Loss (dB). Note 2: Over Limit (dB) = Level (dBUV) – Limit Line (dBUV).																																																																																																																																										

3.2 20dB and Occupied Bandwidth


3.2.1 Limit of 20dB Bandwidth

The upper and lower frequency of the 20dB bandwidth shall within 13.553~13.567 MHz

3.2.2 Test Procedures


1. Set resolution bandwidth (RBW) = 1 kHz, Video bandwidth = 3 kHz.
2. Detector = Peak, Trace mode = max hold.
3. Sweep = auto couple, Allow the trace to stabilize.
4. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower) that are attenuated by 20dB relative to the maximum level measured in the fundamental emission.

3.2.3 Test Setup



3.2.4 Test Result of 20dB and Occupied Bandwidth

Modulation Mode	Freq. (MHz)	20dB Bandwidth (kHz)	F _L at 20dB BW (MHz)	F _H at 20dB BW (MHz)	99% Bandwidth (kHz)
NFC	13.56	2.67	13.558893	13.561563	2.38784705
Limit		N/A	13.553	13.567	N/A



3.3 Field Strength of Fundamental Emissions and Spectrum Mask


3.3.1 Field Strength of Fundamental Emissions and Spectrum Mask Limit

The field strength of any emissions within the band 13.553-13.567 MHz shall not exceed 15,848 microvolts/meter at 30 meters.

3.3.2 Test Procedures

1. Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
2. Measurement is made with the antenna positioned in both the open and close planes of polarization. . Distance between EUT and antenna is 3 m.
3. This investigation is performed with the EUT rotated 360°, and the antenna rotated to repeat the measurements for both the open and close antenna polarizations.

3.3.3 Test Setup



3.3.4 Test Result of Field Strength of Fundamental Emissions and Spectrum Mask

Field Strength of Fundamental Emissions Result							
Polarization	Emission Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA Reading (dBuV)	Factor	Remark
Open	13.56	45.08	105.39	-60.31	21.22	23.86	QP

Field Strength of Fundamental Emissions Result							
Polarization	Emission Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA Reading (dBuV)	Factor	Remark
Close	13.56	38.71	105.39	-66.68	14.85	23.86	QP

3.4 Unwanted Emissions into Restricted Frequency Bands

3.4.1 Limit of Unwanted Emissions into Restricted Frequency Bands

Restricted Band Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1:
Qusai-Peak value is measured for frequency below 1GHz except for 9–90 kHz, 110–490 kHz frequency band. Peak and average value are measured for frequency above 1GHz. The limit on average radio frequency emission is as above table. The limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit

Note 2:
Measurements may be performed at a distance other than what is specified provided. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor as below, Frequency at or above 30 MHz: 20 dB/decade Frequency below 30 MHz: 40 dB/decade.

Within the bands 13.410-13.553 MHz and 13.567-13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts/meter at 30 meters.

Within the bands 13.110-13.410 MHz and 13.710-14.010 MHz the field strength of any emissions shall not exceed 106 microvolts/meter at 30 meters.

The field strength of any emissions appearing outside of the 13.110-14.010 MHz band shall not exceed the general radiated emission limits in §15.209

3.4.2 Test Procedures


- Measurement is made at a semi-anechoic chamber that incorporates a turntable allowing a EUT rotation of 360°. A continuously-rotating, remotely-controlled turntable is installed at the test site to support the EUT and facilitate determination of the direction of maximum radiation for each EUT emission frequency. The EUT is placed at a height of 0.8 m test table above the ground plane.
- Measurement is made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna is varied in height (1m ~ 4m) above the reference ground plane to obtain the maximum signal strength. Distance between EUT and antenna is 3 m.
- This investigation is performed with the EUT rotated 360°, the antenna height scanned between 1 m and 4 m, and the antenna rotated to repeat the measurements for both the horizontal and vertical antenna polarizations.

Note:


- 120kHz measurement bandwidth of test receiver and Quasi-peak detector is for radiated emission below 1GHz.

3.4.3 Test Setup

Radiated Emissions below 30MHz



Radiated Emissions below 1 GHz



3.4.4 Transmitter Radiated Unwanted Emissions (Below 30MHz)


Field Strength of Fundamental Emissions Result							
Polarization	Emission Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA Reading (dBuV)	Factor(dB)	Remark
Open	13.41	34.3	62	-27.7	10.5	23.8	QP
Open	13.553	37.2	71.87	-34.67	13.35	23.85	QP
Open	13.567	37.21	71.86	-34.65	13.35	23.86	QP
Open	13.71	33.58	61.81	-28.23	9.67	23.91	QP
Open	27.12	27.73	49.54	-21.81	8.2	19.53	QP

Field Strength of Fundamental Emissions Result							
Polarization	Emission Frequency (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	SA Reading (dBuV)	Factor(dB)	Remark
Close	13.41	34.05	62	-27.95	10.25	23.8	QP
Close	13.553	38.69	71.87	-33.18	14.84	23.85	QP
Close	13.567	38.7	71.86	-33.16	14.84	23.86	QP
Close	13.71	34.66	61.81	-27.15	10.75	23.91	QP
Close	27.12	27.87	49.54	-21.67	8.34	19.53	QP

Note: Emission level = SA reading + Factor

3.4.5 Transmitter Radiated Unwanted Emissions (Above 30MHz)

Modulation	ASK	Test Freq. (MHz)	13.56
Polarization	Horizontal	Test Configuration	1




The graph displays the emission level in dBuV/m on the y-axis (0 to 90) against frequency in MHz on the x-axis (30 to 1000). A red line represents the FCC CLASS-B limit, which is 40 dBuV/m from 30 to 100 MHz, 45 dBuV/m from 100 to 300 MHz, and 55 dBuV/m from 300 to 1000 MHz. Six blue vertical lines indicate measured peaks at 40.24, 61.74, 79.56, 146.55, 159.50, and 271.87 MHz, labeled 1 through 6 respectively.

	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	40.24	23.25	40.00	-16.75	32.01	-8.76	Peak	---	---
2	61.74	20.28	40.00	-19.72	29.55	-9.27	Peak	---	---
3	79.56	19.89	40.00	-20.11	32.97	-13.08	Peak	---	---
4	146.55	22.25	43.50	-21.25	30.82	-8.57	Peak	---	---
5	159.50	21.69	43.50	-21.81	30.17	-8.48	Peak	---	---
6	271.87	20.20	46.00	-25.80	29.21	-9.01	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
 *Factor includes antenna factor , cable loss and amplifier gain
 Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Modulation	ASK	Test Freq. (MHz)	13.56
Polarization	Vertical	Test Configuration	1




	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	41.58	24.86	40.00	-15.14	33.35	-8.49	Peak	---	---
2	78.87	23.25	40.00	-16.75	36.17	-12.92	Peak	---	---
3	104.52	19.66	43.50	-23.84	32.01	-12.35	Peak	---	---
4	121.08	20.23	43.50	-23.27	30.89	-10.66	Peak	---	---
5	160.25	25.69	43.50	-17.81	34.22	-8.53	Peak	---	---
6	236.84	19.05	46.00	-26.95	29.70	-10.65	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)

*Factor includes antenna factor , cable loss and amplifier gain

Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).


Mode	Charging	Test Freq. (MHz)	---
Polarization	Horizontal	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	46.49	20.45	40.00	-19.55	28.91	-8.46	Peak	---	---
2	142.52	20.93	43.50	-22.57	29.71	-8.78	Peak	---	---
3	293.84	20.11	46.00	-25.89	28.36	-8.25	Peak	---	---
4	384.05	22.98	46.00	-23.02	28.85	-5.87	Peak	---	---
5	481.05	25.60	46.00	-20.40	29.15	-3.55	Peak	---	---
6	588.72	26.91	46.00	-19.09	28.29	-1.38	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

Mode	Charging	Test Freq. (MHz)	---
Polarization	Vertical	Test Configuration	2



	Freq. MHz	Emission level dBuV/m	Limit dBuV/m	Margin dB	SA reading dBuV	Factor dB	Remark	ANT High cm	Turn Table deg
1	52.31	26.26	40.00	-13.74	34.84	-8.58	Peak	---	---
2	163.86	19.95	43.50	-23.55	28.67	-8.72	Peak	---	---
3	304.51	21.34	46.00	-24.66	29.24	-7.90	Peak	---	---
4	473.29	25.30	46.00	-20.70	28.98	-3.68	Peak	---	---
5	578.05	26.94	46.00	-19.06	28.58	-1.64	Peak	---	---
6	640.13	27.75	46.00	-18.25	28.01	-0.26	Peak	---	---

Note 1: Emission Level (dBuV/m) = SA Reading (dBuV/m) + Factor* (dB)
*Factor includes antenna factor , cable loss and amplifier gain
Note 2: Margin (dB) = Emission level (dBuV/m) – Limit (dBuV/m).

3.5 Frequency Stability


3.5.1 Frequency Stability Limit

Carrier frequency stability shall be maintained to $\pm 0.01\%$ (± 100 ppm).

3.5.2 Test Procedures

Test Method	
☒	Refer as ANSI C63.10, clause 6.8 for frequency stability tests
☒	Frequency stability with respect to ambient temperature
☒	Frequency stability when varying supply voltage
☐	For conducted measurement.
☒	For radiated measurement. The equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted power level.

3.5.3 Test Setup



3.5.4 Test Result of Frequency Stability

Frequency: 13.56 MHz	Frequency Drift (ppm)			
Temperature (°C)	0 minute	2 minutes	5 minutes	10 minutes
T20°CVmax	11.06	10.91	11.36	12.24
T20°CVmin	10.32	10.32	10.91	12.68
T50CVnom	11.06	12.17	12.02	12.61
T40°CVnom	12.54	12.61	11.80	11.06
T30°CVnom	12.17	12.54	9.59	10.32
T20°CVnom	10.69	10.77	11.50	12.17
T10°CVnom	8.85	9.00	9.07	9.59
T0°CVnom	7.37	8.11	8.55	6.71
T-10°CVnom	6.27	7.08	8.41	6.34
T-20°CVnom	5.90	7.37	7.37	6.27
Vnom [V]: 3.8		Vmax [V]: 4.35		Vmin [V]: 3.4
Tnom [°C]: 20		Tmax [°C]: 50		Tmin [°C]: -20

4 Test laboratory information

Established in 2012, ICC provides foremost EMC & RF Testing and advisory consultation services by our skilled engineers and technicians. Our services employ a wide variety of advanced edge test equipment and one of the widest certification extents in the business.

International Certification Corp (EMC and Wireless Communication Laboratory), it is our definitive objective is to institute long term, trust-based associations with our clients. The expectation we set up with our clients is based on outstanding service, practical expertise and devotion to a certified value structure. Our passion is to grant our clients with best EMC / RF services by oriented knowledgeable and accommodating staff.

Our Test sites are located at Linkou District and Kwei Shan District. Location map can be found on our website <http://www.icertifi.com.tw>.

Linkou

Tel: 886-2-2601-1640

No. 30-2, Ding Fwu Tsuen, Lin
Kou District, New Taipei City,
Taiwan, R.O.C.

Kwei Shan

Tel: 886-3-271-8666

No. 3-1, Lane 6, Wen San 3rd St.,
Kwei Shan District, Tao Yuan City
333, Taiwan, R.O.C.

Kwei Shan Site II

Tel: 886-3-271-8640

No. 14-1, Lane 19, Wen San 3rd
St., Kwei Shan District, Tao Yuan
City 333, Taiwan, R.O.C.

If you have any suggestion, please feel free to contact us as below information.

Tel: 886-3-271-8666

Fax: 886-3-318-0155

Email: ICC_Service@icertifi.com.tw

==END==