

Test Report 2025-104

Version B

Issued 29 Dec 2025

Project GCL-0887

Model Identifier: AB5206

Primary Test Standard(s):

CFR 47, FCC Part 15.249

RSS-GEN Issue 5

RSS-210 Issue 11

Garmin Compliance Lab

Garmin International

1200 E 151st Street

Olathe Kansas 66062 USA

Client-supplied Information

FCC ID: IPH-B5206

IC ID: 1792A-B5206



See section 6 of this report regarding the presence or absence of accreditation logos or marks on this cover page.

1. Summary

The equipment or product described in section 5 of this report was tested at the Garmin Compliance Lab according to standards listed in section 6. This report focuses on the ANT transceiver(s). The results are as follows.

Parameter	Description	Key Performance Values	Result	Data starts at page
Radio Modulation	Summary of the kinds of communication this radio can achieve, as stated by the client. [RSS-GEN at Annex A item 10b]	Digitally modulated spread spectrum at rates as high as 60 kbps.	Reported	N/A
Adjacent Restricted Bands	The radio must not emit in certain designated restricted frequency bands to the transmission band above a set of limit values. This entry focuses on bands adjacent to the operating band. [15.205; RSS-210 at 7.1]	Emissions in the adjacent restricted bands were at least 9.98 dB below the applicable limits. Compliance for the remaining restricted bands is demonstrated by the spurious emission data.	PASS	13
Carrier, Harmonic, and Spurious Emissions	The field strength from the radio carrier and its harmonics must meet specific limits at a 3 m test distance. Other unwanted emissions also have to meet what is commonly called the Class B limit. [15.249(a); RSS-210 at B.10]	The limit is 50 mV/m (94 dBuV/m) in the carrier band, and 0.5 mV/m (54 dBuV/m) at all other frequencies. This sample demonstrated 10.3 dB of margin or greater. At other non-harmonic frequencies, unwanted emissions had at least 12.6 dB of margin.	PASS	17
Other Bandwidths	Regulatory agencies also require the reporting of signal bandwidths using alternate processes. [2.202; RSS-GEN at 6.7]	These values are reported but have no actual performance requirements.	Reported	32
20 dB occupied bandwidth	The 20 dB bandwidth of the emission must be contained entirely within the allocated frequency band. [15.215]	The 20 dB Bandwidth has 1.498 MHz of margin or better to the allocated band edge.	PASS	36
Frequency Stability	The radio tuning must be robust over a range of temperature and supply voltage conditions. [RSS-Gen at 6.11]	Radio emissions remained within the allowed radio band under all environmental conditions tested.	NT	NT
Unwanted Emissions (Mains Conducted)	While transmitting, the emissions conducted into the power mains must not be too strong. [15.207, RSS-Gen at 8.8]	Emissions other than the fundamental and harmonics must meet the 'Class B' limits. The measured emissions had at least 16.44 dB of margin.	PASS	39

NT (Not Tested) means the requirement may or may not be applicable, but the relevant measurement or test was not performed as part of this test project.

N/A (Not Applicable) means the lab judged that the test sample is exempt from the requirement.

Table 1: Summary of results

Report Organization

For convenience of the reader, this report is organized as follows:

1. Summary
2. Test Background
3. Report History and Approval
4. Test Sample Modifications and Special Conditions
5. Description of Equipment Tested
6. Test Standards Applied
7. Measurement Instrumentation Uncertainty
8. Selected Examples of Calculations
9. Environmental Conditions During Test
10. 3m RF Chamber Block Diagrams

Annex: Test records are provided for each type of test, following the order and page numbering stated in the summary table. Concluding notes appear on the final page of this report.

Due to confidentiality, certain material (such as test setup photographs) has been removed from this report and placed in GCL Test Report 2025-105. That report is treated as a part of this document by way of this reference.

2. Test Background

2.1 The Test Lab

The testing reported here was performed at the Garmin Compliance Lab, an organization within Garmin International, located at 1200 E 151st St, Olathe Kansas, USA. The contact telephone number is +1.913.397.8200.

2.2 The Client

The testing was performed on behalf of the Garmin design group, a separate organization located at 1200 E 151st St, Olathe Kansas, USA. Witnesses from the business group included: None.

2.3 Other Information

Test Sample received: 14 Nov 2025
Test Start Date: 17 Nov 2025
Test End Date: 16 Dec 2025

The data in this test report apply only to the specific samples tested.

Upon receipt all test samples were believed to be properly assembled and ready for testing.

3. Report History and Approval

This report was written by Majid Farah and initially issued on 17 Dec 2025 as Version A. Version B, issued on 29 Dec 2025, added FCC "Lab Registration Number" in section 6.4. Version B was written by Majid Farah.

Report Technical Review:

Majid Farah
Senior EMC Engineer



GCL only

Report Approval:

Shruti Kohli
Senior Manager Operations



GCL only

4. Test Sample Modifications and Special Conditions

The following special conditions or usage attributes were judged during test to be necessary to achieve compliance with one or more of the standards listed in section 6 of this report:
None.

The following modifications to the test sample(s) were made, and are judged necessary to achieve compliance with one or more of the standards listed in section 6 of this report:
None.

5. Description of the Equipment Tested

5.1 Unique Identification

Product Model	AB5206
Serial Numbers Tested	3621678869, 3621678871, 3621679750

The product tested is a mobile device for collecting and sharing data with the user and nearby electronic devices.

The client affirmed that the test samples will be representative of production in all relevant aspects.

5.2 Key Parameters

EUT Input Power:	5 Vdc
I/O Ports:	USB
Radio Transceivers:	Bluetooth Low Energy, ANT
Radio Receivers:	GPS L1, Galileo E1, BeiDou, GLONASS
Primary Functions:	Data collection and communication
Typical use:	Body worn
Highest internal frequency:	2.484 GHz
Highest digital frequency:	192 MHz
Firmware Revision	6.01

5.3 Operating modes

During test, the EUT was operated in one or more of the following modes.

M4 (BleTx): Bluetooth Low Energy radio transmitting consistently on a selected channel at 1 Mbps or 2 Mbps.

M6 (AntTx): ANT radio transmitting consistently on a selected channel.

M13 (RxBle): Bluetooth Low Energy radio was set to receive signals on a selected channel at 1 Mbps or 2 Mbps.

M14 (RxANT): ANT radio was set to receive signals on a selected channel.


M18 (Gnss): The Global Navigation Satellite System receiver is monitoring the GNSS bands, attempting to detect a constellation and determine location. Unless otherwise noted, the EUT was provided simulated GNSS signals representing one of more constellation types. In addition, the EUT was reporting signal levels and satellite data to an attached computer to monitor link health.

5.4 EUT Arrangement

During test, the EUT components and associated support equipment were selected including the following arrangement sets.

A1: The test sample is attached to a Mains-powered device connected that provides dc power to the sample and user data over a cable. See the block diagram in Figure 1.

A2: The test sample is attached to a Mains-powered device connected that provides dc power to the sample over a cable but no user data. See the block diagram in Figure 1.



*This interconnect drawing is not to scale.
It does not indicate the placement of devices.*

Figure 1: Block diagram of equipment arrangement A1 and A2

A3: The test sample operates from its battery and no external physical connections. No block diagram is needed for this arrangement.

5.5 Associated Equipment (AE) used

Description	Manufacturer	Model	Serial Number
USB C power adaptor	Phihong (Garmin)	AQ27A-59CFA	362-00118-00
Laptop	Dell	Precision 5540	3JYG33
AC/DC Power Adapter	Dell	HA130PM130	0V363H-CH200-78G-0DC1-A01

Table 2: List of associated equipment that may have been used during test

5.6 Cables used

Description	From	To	Length	EMC Treatment
USB C to custom cable	Power and/or Data source	EUT	0.5 m	None

Table 3: List of cables that may have been used during test

6. Test Standards Applied

6.1. Accredited Standards

The following test or measurement standards were applied and are within the scope of the lab's accreditation. All results in this report that cite these standards are presented as Accredited results consistent with ISO/IEC 17025.

CFR 47, FCC Part 15, Subpart C
ANSI C63.10: 2020 and ANSI C63.10: 2020 +Cor 1: 2023
AS/NZS 4268: 2017
RSS-GEN Issue 5 Amd 2
RSS-210 Issue 11

6.2 Non-accredited Standards

The following test or measurement standards were applied and are either outside the scope of the lab's accreditation, or were performed in such a way that results are not presented as being fully accredited.

FCC Part 2.202
TRC-43 Issue 3

6.3 Variances

The following variances were applied to standards cited in this section.

Where different test standards cover the same test parameter or phenomenon, and the standards have compatible differences, the stricter of the requirements is typically applied. For example, a consolidated limit may be applied to emission tests selecting the strictest of the limits at each frequency. Likewise, if one standard requires a vertical antenna sweep with boresighting and another does not, swept motion with boresighting will typically be used as it is the more stringent requirement.

Some standards that apply an Average detector provide a variety of methods to handle time-averaging, especially where the transmission is not continuous and the Duty Cycle (DC) is below a value such as 98%. The basic GCL process is to begin by applying an Average detector to the emission with the receiver in Max-Hold data mode. This Max Average method is worst-case compared to any of the methods of time-averaging provided. If the Max Average result complies with the limit, that result is provided in the test record and the emission judged to be compliant without additional detail. If the Max Average result is near or above the limit at one or more emission frequencies, then one of the appropriate time-averaging methods is applied to determine final compliance. When time-averaging is used, the test record will indicate which method of time-averaging was used.

Some standards ask for measurements made with a 'Time Domain Power' function, but that function is not defined in the standards. GCL addresses this gap as follows. Staff capture a zero-span Average detector data record of emission power, with a timespan covering a transmission burst. When the maximum power in the data record is clearly below the limit, this value will be reported. When the maximum power in the data record is near or above the limit, then the average of the power (in linear units) during a transmission burst is calculated and reported.

DISCLAIMER: In some test activities, the operation of a test or the result of a test depends on data provided by the client. The Garmin Compliance Lab disclaims responsibility for any error in the processes, results, or judgments in this report arising from incorrect client-provided data.

6.4 Laboratory Accreditation

The Garmin Compliance Lab, an organization within Garmin International, is registered with the US Federal Communication Commission (FCC) as:

Lab Registration Number: 273575
FCC Designation Number: US1311

The Garmin Compliance Lab, an organization within Garmin International, is recognized by the Canada Department of Innovation, Science, and Economic Development (ISED) under:

Company Number: 1792A
CAB Identifier: US0233

The Garmin Compliance Lab, an organization within Garmin International, is accredited by A2LA, Certificate No. 6162.01. The presence of the A2LA logo on the cover of this report indicates this is an accredited ISO/IEC 17025 test report. If the logo is absent, this report is not issued as an accredited report. Other marks and symbols adjacent to the A2LA logo are accreditation co-operations of which A2LA is a member under a mutual recognition agreement, and to which the Garmin Compliance Lab has been sublicensed.

7. Measurement Instrumentation Uncertainty

The lab has analyzed the sources of measurement instrumentation uncertainty. The analysis concludes that the actual measurement values cited in this report are accurate within the U_{LAB} intervals shown below with approximately 95% statistical confidence. Where the report shows a judgment that a test sample passes a test against a published limit based on these measured values, that judgment has a statistical confidence of 97.5% or greater. Measurement Instrumentation Uncertainty is one component of over-all measurement uncertainty, and other uncertainty components are not considered as part of this analysis.

The primary benchmark for measurement instrumentation uncertainty (MIU) in an electromagnetic compatibility (EMC) test lab is the set of U_{CISPR} values published in CISPR 16-4-2. In all cases where a U_{CISPR} value is published by CISPR, the analysis shows that U_{LAB} – this lab's estimated MIU – is better than the U_{CISPR} benchmark.

The secondary benchmark for MIU in an EMC lab performing radio transceiver tests is a set of uncertainty limit values published in various ETSI standards. In this report, U_{ETSI} is the most restrictive of the values found in the ETSI EN standards listed in section 5 of this report. The analysis principles are described in the ETSI TR documents listed there. In most cases U_{LAB} is better than the U_{ETSI} benchmark. Where U_{LAB} exceeds the U_{ETSI} benchmark cited here, that entry is preceded by an asterisk. When required by the ETSI EN standards, excess uncertainty will be added to the measurand before comparison to a limit. In an individual test report, staff may re-evaluate that excess uncertainty based on the uncertainty of the method used and the uncertainty limits of the actual ETSI EN standard being applied, and the revised uncertainty values will be shown in the test report.

Some measurement uncertainties analyzed and reported here are not addressed in CISPR 16-4-2 or the ETSI standards, as indicated by the entry 'None.'

Test Type	U_{LAB}	U_{CISPR}	U_{ETSI}
Conducted DC voltage	0.09% + 2 x LSDPV	None	1%
Conducted AC voltage below 500 Hz	1.0% + 3 x LSDPV	None	2%
Conducted Emissions, Mains Voltage	0.10% + 10 mV	None	None
Conducted Emissions, Mains Current	0.10% + 3 mA	None	None
Conducted Emissions, Mains Power	0.15% + 100 mW	None	None
Conducted Emissions, Power Mains, 9 kHz to 150 kHz	1.70 dB	3.8 dB	None
Conducted Emissions, Power Mains, 150 kHz to 30 MHz	1.48 dB	3.4 dB	None
Conducted Emissions, Cat 6 LCL, 150 kHz to 30 MHz	1.57 dB	5 dB	None
Conducted Emissions, Cat 5 LCL, 150 kHz to 30 MHz	3.06 dB	5 dB	None
Conducted Emissions, Cat 3 LCL, 150 kHz to 30 MHz	4.27 dB	5 dB	None
Radiated Emissions, below 30 MHz	0.88 dB	None	6 dB
Radiated Emissions, 30 MHz to 1000 MHz	2.79 dB	6.3 dB	6 dB
Radiated Emissions, 1 GHz to 18 GHz	2.54 dB	5.2 & 5.5 dB	6 dB
Radiated Emissions, 18 GHz to 26.5 GHz	2.68 dB	None	6 dB
Radiated Emissions, 26.5 GHz to 40 GHz	3.17 dB	None	6 dB
*Radio Signal Frequency Accuracy	1.55×10^{-7}	None	1.0×10^{-7}
Radio Signal Occupied Bandwidth	0.95%	None	5%
Radio Power or Power Spectral Density	0.98 dB	None	1 dB
Temperature	0.38 °C	None	1 °C
Barometric Pressure	0.38 kPa	None	None
Relative Humidity	2.85% RH	None	±5% RH
Signal Timing	The greater of these three... 0.63 µsec 0.01% of value 0.5 x LSDPV	None	None

Note: LSDPV stands for the Least Significant Digit Place Value reported. In the value 1470 msec, the least significant digit is the 7. It has a 10 msec place value. The LSDPV is thus 10 msec and the maximum error due to roundoff would be 5 msec. If the time value were reported as 1470 msec, the underscore indicates that the 0 is a significant figure and the error due to roundoff would be 0.5 msec. All digits provided to the right of a decimal point radix are significant.

8. Selected Example Calculations

Certain regulators require samples of the calculations that lead from the raw measurement to the final result for AC Mains conducted and unintended radiated emissions. The assumption is that the lab performs raw measurements, then adds, subtracts, multiplies, or divides based on transducer factors, amplifier gains, and losses in the signal transmission path. In this lab, our CISPR 16 Receiver does not work that way. The calibration factors and losses and gains are provided to the receiver as detailed data files. These factors are applied in the RF measurement path prior to the detector. But as a step in the lab measurement process, staff frequently verify that these factors are applied correctly. They make a measurement with the factors applied inside the receiver, then they disable the factors and remeasure the result manually adding in the various relevant factors.

The transmission loss is measured including the combined losses and gains of preamplifiers, cables, and any band-selective filters. In many cases above 1 GHz it is a negative value, indicating that the preamplifier gain is greater than these other losses.

Here are examples of these calculations. The data in these examples was not taken as part of this project:

8.1 AC Mains conducted emissions at 22 MHz

(Raw measurement) + (AMN factor) + (transmission loss) = Result

$$(7.145 \text{ dB}\mu\text{V}) + (9.812 \text{ dB}) + (0.216 \text{ dB}) = 17.173 \text{ dB}\mu\text{V}$$

8.2 Radiated Emissions at 630 MHz

(Raw measurement) + (Antenna factor) + (transmission loss) = Result

$$(2.25 \text{ dB}\mu\text{V}) + (27.80 \text{ dB/m}) + (2.89 \text{ dB}) = 32.94 \text{ dB}\mu\text{V/m}$$

8.3 Radiated Emissions at 2.7 GHz

(Raw measurement) + (Antenna factor) + (transmission loss) = Result

$$(43.72 \text{ dB}\mu\text{V}) + (32.22 \text{ dB/m}) + (-36.09 \text{ dB}) = 39.85 \text{ dB}\mu\text{V/m}$$

9. Environmental Conditions During Test

Environmental conditions in the test lab were monitored during the test period. Temperature and humidity are controlled by an air handling system. As information to the reader, the conditions were observed at the values or within the ranges noted below. For any tests where environmental conditions are critical to test results and require further constraints or details, the test records in the annex may provide more specific information.

Temperature:	20.6 to 22.9 °C
Relative Humidity:	41.5% to 49.3% (non-condensing)
Barometric Pressure	96.7 to 99.2 kPa

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
Barometer	Traceable	6453	240300703	9-Apr-2024	9-Apr-2027

Table 4: Environmental monitoring device

10. 3m RF Chamber Block Diagrams

The 3m chamber has three basic configurations which are shown in the figures below. These figures are not to scale.

Figure 1 shows a semi anechoic setup which is typically used for frequencies below 1 GHz. In this example, the antenna is mounted on a mast capable of 1-4 m elevation changes. If a preamplifier or RF filter is used, they are located at or just below floor level. The receiver is outside the chamber, typically in an adjacent separate shielded room.




Figure 1: Typical configuration for measurements below 1 GHz

Figure 2 shows an FSOATS setup which is typically used for frequencies above 1 GHz but below an upper limit such as 14 or 18 GHz. In this example, the antenna is mounted on a mast capable of 1-4 m elevation changes and bore sighting. If a preamplifier or RF filter is used, they are located at or just below floor level. The receiver is outside the chamber, typically in an adjacent separate shielded room.




Figure 2: Typical configuration for measurements between 1 GHz and 14 GHz

Figure 3 shows an alternate FSOATS setup which is typically used for frequencies above 14 GHz. In this example, the antenna is mounted on a mast capable of 1-4 m elevation changes and bore sighting. A preamplifier is located on the mast just behind the antenna. The receiver is located in the chamber near floor level but outside the antenna beam. The receiver may be operated manually by an operator in the chamber and or remotely via an Ethernet connection.




Figure 3: Typical configuration for measurements above 14 GHz

ANNEX

The remainder of this report is an Annex containing individual test data records. These records are the basis for the judgments summarized in section 1 of this report. The Annex ends with a set of concluding notes regarding use of the report.

Test Record
Radiated Emission Test RE04
Project GCL0887

Test Date(s) 18 Nov 2025
Test Personnel David Kerr

Product Model AB5206
Serial Number tested 3621678869

Operating Mode M6 (AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 15.249; RSS-210; RSS-GEN; ANSI C63.10 (as noted in Section 6 of the report)

Frequency Range: Restricted Bands (2310-2390 MHz, 2483.5-2500 MHz)
Pass/Fail Judgment: PASS

Test record created by: Aditya Prakash
Date of this record: 20 Nov 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 26 GHz	Keysight	N9048B	MY59290135	24-Oct-2024	29-Nov-2025
Antenna, Horn, 1-18 GHz	ETS Lindgren	3117	00259208	30-May-2024	30-May-2026
FSOATS 3m, above 1 GHz	Frankonia	SAC3	F199004	13-Dec-2024	13-Dec-2027
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013783	26-Jun-2024	26-Jun-2027
Preamplifier, 500 MHz 18 GHz	Com-Power	PAM-118A	18040133	Calibration	Not Required
Wifi Filter	K&L	8NSL26-2437/E82.2-0/0	1	Calibration	Not Required

Table RE04.1: Test Equipment Used

Software Used

Keysight PXE receiver software A.32.06, FCC Restricted Band 2p4GHz Data Analysis Template v2a 2025May27, RE Signal Maximization Tool v2021Feb25.xlsx,

Test Data

US and Canadian laws contain dozens of bands where radio operation is restricted. Compliance with most of those band restrictions is typically demonstrated by a series of spurious emission tests covering a very wide span of frequencies from kilohertz to Gigahertz. This test record focuses on restricted bands that are immediately adjacent to the authorized band in which the test sample radio operate. It shows whether the modulation products are sufficiently suppressed to meet the restricted band requirements.

The radiated emission test began with a preliminary scan in each restricted band at multiple turntable angles, antenna heights, and both antenna polarizations. For test standards that require reorienting the test sample, further preliminary scans were taken in those alternate orientations typically described as X, Y, and Z. Subsequent testing was done using on the orientation(s) producing the highest result relative to the test limit. Final field strength measurements were taken in that set of positions.

Restricted band measurements in the lower band were made while the transmitter was tuned to its lowest frequency of 2402 MHz. Measurements in the upper band were made while the transmitter was tuned to its highest frequency of 2480 MHz.

At azimuth angle 0° the 'front' reference mark of the turntable is pointed Southward. At 90° the reference mark points West. At -90° it points East. At -7° the turntable reference mark is pointed directly at the antenna. The designation of the X, Y, and Z orientations of the test sample are sample dependent, so these are reported by use of photographs.

The tables show the selected final measurement data between the FCC restricted bands. It includes a the strongest emissions observed relative to the test limit, along with other data points of interest. Where a data point is highlighted is yellow, this is an aid to indicate the data point(s) with the least margin to the test limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC restricted band 'Class B' Limit at 3 m listed at 15.209 and RSS-Gen clause 8.9.

Emissions within the restricted bands were measured with an averaging process described in the ANSI C63.10 methods noted in this paragraph. (See also section 6.3 of this test report.) The duty cycle for the ANT radio had a constant duty cycle less than 98% and so the trace-averaging method with duty cycle adjustment from clause 11.12.2.5.2.1 was applied.

Frequency	Avg Limit	Pk Limit	Avg Level	Pk Level	Av Margin	Pk Margin	Azimuth	Height	Polarity	Avg Type	DC Adjust
(MHz)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(degree)	(mm)	---	---	(dB)
2370	54	74	32.38	57.18	21.62	16.82	-113	3359	VERT	RMS	0.18
2390	54	74	33.55	50.38	20.45	23.62	-113	3359	VERT	RMS	0.18

Table RE04.2: FCC restricted bands from 2200 to 2390 MHz (ANT, 2402 MHz)

Frequency	Avg Limit	Pk Limit	Avg Level	Pk Level	Av Margin	Pk Margin	Azimuth	Height	Polarity	Avg Type	DC Adjust
(MHz)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dBμV/m)	(dB)	(dB)	(degree)	(mm)	---	---	(dB)
2483.5	54	74	34.84	64.02	19.16	9.98	-118	2865	VERT	RMS	0.18

Table RE04.3: FCC restricted band from 2483.5 to 2500 MHz (ANT, 2480 MHz)

The graphs below show the background spectrum observed during pre-scan, as well as the final data points from the tables above.




Figure RE04.1: FCC restricted band spectral data from 2200 to 2390 MHz (ANT, 2402 MHz)




Figure RE04.2: FCC restricted band spectral data from 2483.5 to 2500 MHz (ANT, 2480 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.



Figure RE04.3: EUT test setup, primary view



Figure RE04.4: EUT test setup, reverse view

This line is the end of the test record.

Test Record
Radiated Emission Test RE21
Project GCL0887

Test Date(s) 04 Dec 2025
Test Personnel David Kerr

Product Model AB5206
Serial Number tested 3621678869

Operating Mode M6 (AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 15, ANSI C63.10, RSS-247, RSS-GEN (as noted in Section 6 of the report).

Frequency Range: 9kHz - 30 MHz
Pass/Fail Judgment: PASS

Test record created by: Jim Solum
Date of this record: 08 Dec 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 44 GHz	Keysight	N9048B	MY65140100	21-Nov-2025	21-Nov-2026
Loop antenna, amplified	Schwarzbeck	FMZB 1519B	00174	18-Jul-2024	18-Jul-2026
SAC 3m, below 1 GHz	Frankonia	SAC3	F199004	11-Dec-2024	11-Dec-2027
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013783	26-Jun-2024	26-Jun-2027

Table RE21.1: Test Equipment Used

Software Used: Keysight PXE software A.41.06, RE 150k to 30M Signal Maximization Tool V1 2021Mar17.xlsx, RE 9k to 30M XYZ_orientations_TemplateV7.xlsm, RE 9k30m FccCanada Analysis4.xlsx

Test Data

For test standards that require reorienting the test sample, preliminary scans were taken in those alternate orientations to find the orientation that produced that largest field at the receive antenna. With intentional radiators, that highest field is usually found at the carrier frequency. The alternate orientations are typically described as X, Y, and Z and explained with a photograph. Subsequent testing was done using on the orientation identified in this way.

The radiated emission test process continued with a preliminary scan at multiple turntable angles, and in the three loop antenna polarizations. The loop antenna was positioned at a 1.5 m height. Where the test standard requires cable manipulation, this was done at one of more likely worst case frequencies selected by the test personnel while observing the receiver display. At each of the frequencies selected for final measurements, the loop was set to the worst case orientation for that frequency and the turntable angle was explored to find the worst-case settings. Final field strength measurements were taken in that set of positions. Full maximization was not performed at frequencies that are noise floor measurements included per the test standard requirements.

At azimuth angle 0° the 'front' reference mark of the turntable is pointed Southward. At 90° the reference mark points West. At -90° it points East. At -7° the turntable reference mark is pointed directly at the antenna mast for tests that involve changes in antenna elevation. At 0° the turntable reference mark is pointed directly at the loop antenna location. The designation of the X, Y, and Z orientations of the test sample are sample dependent, so these are reported by use of photographs.

The table shows the selected final measurement data between 9 kHz and 30 MHz. It includes at least the six strongest emissions observed relative to the test limit, along with other data points of interest. Where a data point is highlighted in yellow, this is an aid to indicate the data point(s) with the least margin to the test limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC Class B Limit at 3m. Any unintentional radio emission limits are not applied to intentional radio signals.

Test limits for electric fields above 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m with a factor of 20 dB per decade of distance. Test limits for electric or magnetic fields below 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m. The conservative method of ANSI C63.10 clause 6.4.4.1 is applied: 40 dB per decade for distances within the boundary (wavelength / 2 Pi), 20 dB per decade beyond that distance boundary.

In this test, fewer than six emissions were observed within 20 dB of the limit. The relevant emissions were measured, including one or more noise floor signals as judged appropriate to the spectrum.

Freq.	3 m Level	Detector	Distance	Dist Adj	Final Level	Limit	Margin	Peak 3 m	Peak Final	Pk Limit	Pk Margin	Antenna	Table
MHz	dBuV/m	Type	m	dB	dBuV/m	dBuV/m	dB	dBuV/m	dBuV/m	dBuV/m	dB	Orientation	Azimuth, deg
0.56175	32.67	QP	30	40.00	-7.33	32.61	39.95	39.33	-0.67	None	None	X	-48
0.933	29.61	QP	30	40.00	-10.39	28.21	38.60	37.51	-2.49	None	None	X	180
1.3065	30.52	QP	30	40.00	-9.48	25.28	34.76	36.56	-3.44	None	None	X	-2
1.6823	25.93	QP	30	39.52	-13.59	23.09	36.68	33.06	-6.46	None	None	X	180
2.058	23.91	QP	30	37.77	-13.86	29.54	43.40	32.39	-5.38	None	None	X	95

Table RE21.2: Emission summary (ANT, 2480 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE21.1: Spectral data (ANT, 2480 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.




Figure RE21.2: EUT test setup, first view




Figure RE21.3: EUT test setup, second view (Antenna in X Polarization)

This line is the end of the test record.

Test Record
Radiated Emission Test RE49
Project GCL0887

Test Date(s) 03 Dec 2025
Test Personnel David Kerr

Product Model AB5206
Serial Number tested 3621678869

Operating Mode M6 (AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 15.249; RSS-210; RSS-GEN; ANSI C63.10 (as noted in Section 6 of the report).

Frequency Range: 30 MHz to 1000 MHz
Pass/Fail Judgment: PASS

Test record created by: David A Kerr
Date of this record: 03 Dec 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 44 GHz	Keysight	N9048B	MY65140100	21-Nov-2025	21-Nov-2026
Antenna, Biconilog, 30M-6 GHz	ETS Lindgren	3142E	00233201	18-Jul-2024	18-Jul-2026
SAC 3m, below 1 GHz	Frankonia	SAC3	F199004	11-Dec-2024	11-Dec-2027
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013783	26-Jun-2024	26-Jun-2027

Table RE49.1: Test Equipment Used

Software Used: Keysight PXE software A.41.06, EPX test software Version 2025.01.000

Test Data

For test standards that require reorienting the test sample, preliminary scans were taken in those alternate orientations to find the orientation that produced that largest field at the receive antenna. With intentional radiators, that highest field is usually found at the carrier frequency. The alternate orientations are typically described as X, Y, and Z and explained with a photograph. Subsequent testing was done using on the orientation identified in this way.

The radiated emission test process continued with a preliminary scan at multiple turntable angles, antenna heights, and both antenna polarizations. Where the test standard requires cable manipulation, this was done at one of more likely worst case frequencies selected by the test personnel while observing the receiver display. At each of the frequencies selected for final measurements, the turntable angle, antenna height, and antenna polarization were explored to find the worst-case settings. Final field strength measurements were taken in that set of positions. Full maximization was not performed at frequencies that are noise floor measurements included per the test standard requirements.

At azimuth angle 180° the 'front' reference mark of the turntable is pointed Southward. At 270° the reference mark points West. At 90° it points East. At 173° the turntable reference mark is pointed directly at the antenna. The designation of the X, Y, and Z orientations of the test sample are sample dependent, so these are reported by use of photographs.

The table shows the selected final measurement data between 30 MHz and 1 GHz. It includes at least the six strongest emissions observed relative to the test limit, along with other data points of interest. Where a data point is highlighted in yellow, this is an aid to indicate the data point(s) with the least margin to the test limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC Class B Limit at 3m. Any unintentional radio emission limits are not applied to intentional radio signals.

Test limits for electric fields above 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m with a factor of 20 dB per decade of distance. Test limits for electric or magnetic fields below 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m. The conservative method of ANSI C63.10 clause 6.4.4.1 is applied: 40 dB per decade for distances within the boundary (wavelength / 2 Pi), 20 dB per decade beyond that distance boundary.

In this test, fewer than six emissions were observed within 20 dB of the limit. The relevant emissions were measured, including one or more noise floor signals as judged appropriate to the spectrum.

Frequency	Pol.	Reading	Factor	Level	Limit	Margin	Height	Angle
MHz		dB(μ V)	dB(1/m)	dB(μ V/m)	dB(μ V/m)	dB	cm	deg
		QP		QP	QP	QP		
44.220	V	12.2	15.2	27.4	40.0	12.6	100.0	200.0
72.000	V	10.8	14.2	25.0	40.0	15.0	100.0	0.0
135.030	V	3.4	15.9	19.3	43.5	24.2	280.6	188.0
403.440	V	3.6	27.2	30.8	46.0	15.2	331.7	321.0

Table RE49.2: Emission summary (ANT, 2480 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE49.1: Spectral data (ANT, 2480 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.



Figure RE49.2: EUT test setup, first view




Figure RE49.3: EUT test setup, second view

This line is the end of the test record.

Test Record
Radiated Emission Test RE10
Project GCL0887

Test Date(s) 21 Nov 2025
Test Personnel David Kerr

Product Model AB5206
Serial Number tested 3621678869

Operating Mode M6 (AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 15.249; RSS-210; RSS-GEN; ANSI C63.10 (as noted in Section 6 of the report).

Frequency Range: 1 GHz to 14 GHz
Pass/Fail Judgment: PASS

Test record created by: David A Kerr
Date of this record: 21 Nov 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 26 GHz	Keysight	N9048B	MY59290135	24-Oct-2024	29-Nov-2025
Antenna, Horn, 1-18 GHz	ETS Lindgren	3117	00259208	30-May-2024	30-May-2026
FSOATS 3m, above 1 GHz	Frankonia	SAC3	F199004	13-Dec-2024	13-Dec-2027
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013783	26-Jun-2024	26-Jun-2027
Preamplifier, 500 MHz 18 GHz	Com-Power	PAM-118A	18040133	Calibration	Not Required
Wifi Filter	K&L	8NSL26-2437/E82.2-0/	1	Calibration	Not Required
3 GHz High Pass filter	Anatech Electronics	OKOR2	01	Calibration	Not Required

Table RE10.1: Test Equipment Used

Software Used: Keysight PXE software A.32.06, EPX test software Version 2025.01.000

Test Data

For test standards that require reorienting the test sample, preliminary scans were taken in those alternate orientations to find the orientation that produced that largest field at the receive antenna. With intentional radiators, that highest field is usually found at the carrier frequency. The alternate orientations are typically described as X, Y, and Z and explained with a photograph. Subsequent testing was done using on the orientation identified in this way.

The radiated emission test process continued with a preliminary scan at multiple turntable angles, antenna heights, and both antenna polarizations. Where the test standard requires cable manipulation, this was done at one of more likely worst case frequencies selected by the test personnel while observing the receiver display. At each of the frequencies selected for final measurements, the turntable angle, antenna height, and antenna polarization were explored to find the worst-case settings. Final field strength measurements were taken in that set of positions. Full maximization was not performed at frequencies that are noise floor measurements included per the test standard requirements.

In the 1 GHz to 3.2 GHz frequency range, a Chebyshev 'Wifi' notch filter covering the 2.4 GHz ISM band was placed in series just before the preamplifier to ensure it operated in its linear range. This filter is accounted for in the system loss, so it appears in the prescan plots as high noise floor levels from 2400 – 2483 MHz. These are not failing emissions. A 3 GHz high pass filter was applied during testing between 3.2 GHz and 14 GHz to similarly protect the preamplifier.

In the 1 GHz to 14 GHz frequency range, pre-scan spectral data was taken at 1 meter and extrapolated to a 3 meter distance. Final measurements were made at 3 meters.

At azimuth angle 180° the 'front' reference mark of the turntable is pointed Southward. At 270° the reference mark points West. At 90° it points East. At 173° the turntable reference mark is pointed directly at the antenna. The designation of the X, Y, and Z orientations of the test sample are sample dependent, so these are reported by use of photographs.

The table shows the selected final measurement data between 1 GHz and 14 GHz. It includes at least the six strongest emissions observed relative to the test limit, along with other data points of interest. Where a data point is highlighted in yellow, this is an aid to indicate the data point(s) with the least margin to the test limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC Class B Limit at 3m. Any unintentional radio emission limits are not applied to intentional radio signals.

Test limits for electric fields above 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m with a factor of 20 dB per decade of distance. Test limits for electric or magnetic fields below 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m. The conservative method of ANSI C63.10 clause 6.4.4.1 is applied: 40 dB per decade for distances within the boundary (wavelength / 2 Pi), 20 dB per decade beyond that distance boundary.

Emissions within the restricted bands were measured with an averaging process described in the ANSI C63.10 methods noted in this paragraph. (See also section 6.3 of this test report.) The duty cycle for the ANT radio had a constant duty cycle less than 98% and so the trace-averaging method with duty cycle adjustment from clause 11.12.2.5.2.1 was applied.

In this test, fewer than six emissions were observed within 20 dB of the limit. The relevant emissions were measured, including one or more noise floor signals as judged appropriate to the spectrum.

The client states that the maximum duty cycle for the ANT protocol is 13%. The CISPR Average detector has a square law response for signal pulses with these ANT timing parameters. In the data table RE10.2 below, the Average detector values for the carrier frequencies have been adjusted downward by 17.7 dB, which comes from $20 * \log(13\%)$. The Peak detector values are not reduced for duty cycle, nor were the other emissions adjusted for duty cycle.

Frequency (MHz)	Avg Limit (dBµV/m)	Pk Limit (dBµV/m)	*Avg level (dBµV/m)	Pk Level (dBµV/m)	Av Margin (dB)	Pk Margin (dB)	Polarity ---	Height (mm)	Azimuth (degree)
2402	94	114	81.47	99.17	12.53	14.83	VERT	3899	-133.0
2440	94	114	80.31	97.71	13.69	16.29	VERT	3604	-137.0
2480	94	114	78.66	96.06	15.34	17.94	VERT	2316	-155.0

Table RE10.2: Emission summary (ANT Carrier measurements) *Avg adjusted for 13% duty cycle

Frequency	Pol.	Reading		Factor	Level		Limit		Margin		Height	Angle
MHz		dB(μ V)		dB(1/m)	dB(μ V/m)		dB(μ V/m)		dB		cm	deg
		RMS	PK		RMS	PK	AV	PK	RMS	PK		
7205.763	H	30.7	41.5	8.2	38.9	49.7	54.0	74.0	15.1	24.3	221.0	37.0
9607.622	H	27.9	39.5	13.1	41.0	52.6	54.0	74.0	13.0	21.4	201.2	355.0

Table RE10.3: Emission summary (ANT, 2402 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE10.1: Spectral data (ANT, 2402 MHz)

Frequency	Pol.	Reading		Factor	Level		Limit		Margin		Height	Angle
MHz		dB(μ V)		dB(1/m)	dB(μ V/m)		dB(μ V/m)		dB		cm	deg
		RMS	PK		RMS	PK	AV	PK	RMS	PK		
4879.981	H	32.0	43.7	4.8	36.8	48.5	54.0	74.0	17.2	25.5	100.0	12.0
9759.641	H	29.7	40.6	12.6	42.3	53.2	54.0	74.0	11.7	20.8	205.3	354.0

Table RE10.4: Emission summary (ANT, 2440 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE10.2: Spectral data (ANT, 2440 MHz)

Frequency	Pol.	Reading		Factor	Level		Limit		Margin		Height	Angle
MHz		dB(μ V)		dB(1/m)	dB(μ V/m)		dB(μ V/m)		dB		cm	deg
		RMS	PK		RMS	PK	AV	PK	RMS	PK		
7439.551	H	29.7	40.8	8.8	38.5	49.6	54.0	74.0	15.5	24.4	219.0	36.0
9920.704	H	30.3	40.3	13.4	43.7	53.7	54.0	74.0	10.3	20.3	191.7	28.0

Table RE10.5: Emission summary (ANT, 2480 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE10.3: Spectral data (ANT, 2480 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.



Figure RE10.4: EUT test setup, first view



Figure RE10.5: EUT test setup, second view

This line is the end of the test record.

Test Record

Radiated Emission Test RE18

Project GCL0887

Test Date(s) 07 Dec 2025
Test Personnel David Kerr

Product Model AB5206
Serial Number tested 3621678869

Operating Mode M6 (AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 15.249; RSS-210; RSS-GEN; ANSI C63.10 (as noted in Section 6 of the report).

Frequency Range: 14 GHz to 25 GHz
Pass/Fail Judgment: PASS

Test record created by: Vladimir Tolstik
Date of this record: 08 Dec 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 44 GHz	Keysight	N9048B	MY62220139	4-Sep-2025	4-Sep-2026
Antenna, Horn, 10-40 GHz	ETS Lindgren	3116C	00259186	8-May-2025	8-May-2027
FSOATS 3m, above 1 GHz	Frankonia	SAC3	F199004	13-Dec-2024	13-Dec-2027
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013783	26-Jun-2024	26-Jun-2027
Preamplifier, 14 GHz to 40 GHz	Com-Power	PAM-840A	461364	Calibration	Not Required

Table RE18.1: Test Equipment Used

Software Used: Keysight PXE software A.33.03, EPX test software Version 2025.01.001

Test Data

For test standards that require reorienting the test sample, preliminary scans were taken in those alternate orientations to find the orientation that produced that largest field at the receive antenna. With intentional radiators, that highest field is usually found at the carrier frequency. The alternate orientations are typically described as X, Y, and Z and explained with a photograph. Subsequent testing was done using on the orientation identified in this way.

The radiated emission test process continued with a preliminary scan at multiple turntable angles, antenna heights, and both antenna polarizations. Where the test standard requires cable manipulation, this was done at one of more likely worst case frequencies selected by the test personnel while observing the receiver display. At each of the frequencies selected for final measurements, the turntable angle, antenna height, and antenna polarization were explored to find the worst-case settings. Final field strength measurements were taken in that set of positions. Full maximization was not performed at frequencies that are noise floor measurements included per the test standard requirements.

In the 14 GHz to 26.5 GHz frequency range, pre-scan spectral data was taken at 1 meter and extrapolated to a 3 meter distance. Final measurements were made at 3 meters.

At azimuth angle 180° the 'front' reference mark of the turntable is pointed Southward. At 270° the reference mark points West. At 90° it points East. At 173° the turntable reference mark is pointed directly at the antenna. The designation of the X, Y, and Z orientations of the test sample are sample dependent, so these are reported by use of photographs.

The table shows the selected final measurement data between 14 GHz and 25 GHz. It includes at least the six strongest emissions observed relative to the test limit, along with other data points of interest. Where a data point is highlighted is yellow, this is an aid to indicate the data point(s) with the least margin to the test limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC Class B Limit at 3m. Any unintentional radio emission limits are not applied to intentional radio signals.

Test limits for electric fields above 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m with a factor of 20 dB per decade of distance. Test limits for electric or magnetic fields below 30 MHz that are stated for a distance other than 3 m are adjusted to 3 m by one of two methods. For ETSI testing, the extrapolation uses the curve of ETSI EN 300 330 Annex H figure H.2. For FCC and ISSED testing, the conservative method of ANSI C63.10 clause 6.4.4.1 is applied: 40 dB per decade for distances within the boundary (wavelength / 2 Pi), 20 dB per decade beyond that distance boundary.

In this test, fewer than six emissions were observed within 20 dB of the limit. The relevant emissions were measured, including one or more noise floor signals as judged appropriate to the spectrum.

Frequency	Pol.	Reading		Factor	Level		Limit		Margin		Height	Angle
MHz		dB(μ V)		dB(1/m)	dB(μ V/m)		dB(μ V/m)		dB		cm	deg
		RMS	PK		RMS	PK	AV	PK	RMS	PK		
21648.837	H	25.2	37.4	12.3	37.5	49.7	54.0	74.0	16.5	24.3	100.0	180.0

Table RE18.2: Emission summary (ANT, 2480 MHz)

The graph below shows the background spectrum observed during pre-scan, as well as the final data points from the table above.




Figure RE18.1: Spectral data (ANT, 2480 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.



Figure RE18.2: EUT test setup, first view




Figure RE18.3: EUT test setup, second view

This line is the end of the test record.

Test Record
Transmitter Bandwidth Tests
Test IDs TR16
Project GCL0887

Test Date(s) 18 Nov 2025
Test Personnel Vladimir Tolstik

Product Model AB5206
Serial Number tested 3621679750

Operating Mode M6(AntTx)
Arrangement A2
Input Power USB 5 Vdc

Test Standards: FCC Part 2.202, ANSI C63.10, TRC-43, RSS-GEN (as noted in Section 6 of the report).

Radio Protocol ANT
Radio Band 2480 to 2483.5 MHz

Pass/Fail Judgment: Reported

Test record created by: Jim Solum
Date of this record: 10 Dec 2025

Original record, Version A.

Test Equipment Used

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
MXE Receiver 8.4 GHz	Keysight	N9038B	MY63460112	17-Mar-2025	17-Mar-2026

Table TR16.1 Equipment Used

Software used: Keysight MXE software A.37.02

Background

There are regulatory requirements to present two additional types of bandwidth analyses: 99% Occupied Bandwidth and Necessary Bandwidth. There are no limits or functional requirements around these data, beyond a reporting requirement. The contents of this test record are for information, and do not affect compliance of the devices that are the subject of this report.

Test Setup

This block diagram shows the test equipment setup.




Figure TR16.1: Test setup

Occupied Bandwidth, 99% Test Method

During this test the transmitter output is fed directly, or through RF attenuators, to the spectrum analyzer. The analyzer has a built-in capability to identify the minimum bandwidth that contains a specified percentage of the total power observed. The spectrum is scanned hundreds of times so that the varied effects of modulation are appropriately assessed. Since the focus is on the relative distribution of energy across a range of frequencies, the absolute amplitudes recorded during this test are not relevant and may not include cable losses or attenuation factors.

Occupied Bandwidth, 99% Test Data

The data for each type of bandwidth is summarized below, followed by the spectral data for the cases highlighted in yellow. The analysis threshold for this test was the bandwidth containing 99% of the observed power using the ANSI C63.10 method. The standards require testing a frequency near the bottom, middle, and top of the band. The measured bandwidth data are in bold font and have MHz as their units of measure.

Frequency	(MHz)	2402	2440	2480
ANT	----	0.9988	0.9952	0.9892

Table TR16.2: Summary of 99% Occupied Bandwidth Data for ANT




Figure TR16.2: Occupied bandwidth data for ANT at low channel (2402 MHz)

Necessary Bandwidth Calculations

The Necessary Bandwidth is a theoretical value based on the specifications for a communication protocol, rather than the hardware implementation and a subsequent lab measurement. The analysis methods in FCC Part 2.202 and TRC-43 are the same for NFC, Bluetooth, ANT, and IEEE 802.11b WiFi. However, they differ for IEEE 802.11g and 11n systems because the Canadian TRC-43 standard provides different analysis methods for Orthogonal Frequency Division Multiplexing systems (OFDM). The tables below will show the analysis for most of the radios signals as a combined approach, then separately analyze the results for IEEE 802.11g and n systems. The tables below may include radio protocols that are not part of the product being evaluated.

NFC (Near Field Communication) at 13.56 MHz uses continuous wave telegraphy without tone modulation. The bit rate 'B' in the FCC and TRC equations is split into two parts here. B is the baud rate. C is a coding factor. C=1 for Miller encoding where the transition speed is as high as the bit rate, or C=2 for Manchester encoding where the transition speed is as high as twice the bit rate). K is a factor set to 3 for non-fading circuits under the standards.

The Necessary Bandwidth, B_N is then:

$$B_N = BCK$$

Radio Type	B (kbaud)	C	K	B_N (kHz)
NFC A	106	1	3	318.0
NFC B	212	2	3	1272.0
NFC B	424	2	3	2544.0

Table TR16.100: Necessary Bandwidth for NFC

The radio modulation schemes for Ant, for the various Bluetooth protocols, and for IEEE 802.11 b WiFi are a mix of Phase Shift Key (PSK) and Quadrature Amplitude Modulation (QAM) techniques. The Necessary Bandwidth calculations use the equations from 47CFR Part 2.202(g) table section 6. We have set the variable $K=1$, which leaves the equation for both PSK and QAM as:

$$B_N = 2R / \log_2(S)$$

where B_N is the Necessary Bandwidth, R is the bit rate, and S is the number of signaling states.

Radio Type	R Mbps	K	S	LogBase2 of (S)	B_N (MHz)
ANT / ANT+	1	1	2	1	2

Table TR16.101: Necessary Bandwidth for ANT and ANT+ Radio Protocols (FCC and TRC-43)

Radio Type	Sub-type	Method	R Mbps	K	S	LogBase2 of (S)	B_N (MHz)
Bluetooth	BR	GFSK	1	1	2	1	2
	EDR2	Pi/4 DPSK	2	1	4	2	2
	EDR3	8DPSK	3	1	8	3	2
BLE	1Mbps	GFSK	1	1	2	1	2
	2Mbps	DQPSK	2	1	4	2	2

Table TR16.102: Necessary Bandwidth for Bluetooth Radio Protocols (FCC and TRC-43)

Radio Type	Sub-type	R Mbps	K	S	LogBase2 of (S)	B_N (MHz)
802.11 b	1	1	1	2	1	2
	2	2	1	4	2	2
	5.5	5.5	1	4	2	5.5
	11	11	1	4	2	11

Table TR16.103: Necessary Bandwidth for IEEE 802.11 b Radio Protocol (FCC and TRC-43)

Radio Type	Sub-type	R Mbps	K	S	LogBase2 of (S)	B _N (MHz)
802.11 a/g	6	6	1	2	1	12
	9	9	1	2	1	18
	12	12	1	4	2	12
	18	18	1	4	2	18
	24	24	1	16	4	12
	36	36	1	16	4	18
	48	48	1	64	6	16
	54	54	1	64	6	18
802.11 n/ac	MCS0	7.2	1	2	1	14.4
	MCS1	14.4	1	4	2	14.4
	MCS2	21.7	1	4	2	21.7
	MCS3	28.9	1	16	4	14.5
	MCS4	43.3	1	16	4	21.7
	MCS5	57.8	1	64	6	19.3
	MCS6	65	1	64	6	21.7
	MCS7	72.2	1	64	6	24.1
	MCS8	86.7	1	256	8	21.7

Table TR16.104: Necessary Bandwidth for IEEE 802.11 a, g, n, and ac 20 MHz Radio Protocols (FCC)

Radio Type	Sub-type	R Mbps	K	S	LogBase2 of (S)	B _N (MHz)
802.11 n/ac	MCS0	15	1	2	1	30.0
	MCS1	30	1	4	2	30.0
	MCS2	45	1	4	2	45.0
	MCS3	60	1	16	4	30.0
	MCS4	90	1	16	4	45.0
	MCS5	120	1	64	6	40.0
	MCS6	135	1	64	6	45.0
	MCS7	150	1	64	6	50.0
	MCS8	180	1	256	8	45.0
	MCS9	200	1	256	8	50.0

Table TR16.105: Necessary Bandwidth for IEEE 802.11 n and ac 40 MHz Radio Protocols (FCC)

As a note, the bit rate for IEEE 802.11 n or ac WiFi is calculated based on the IEEE standard's short guard interval of 400 nsec. If only the long guard interval of 800 nsec were implemented, the bit rates would decrease by a small amount.

The TRC-43 method for OFDM signals simply multiplies the number of subcarriers, K, and the subcarrier spacing, N_s. In both cases, N_s is 312.5 kHz. The count of subcarriers includes nulls. So for example, 802.11 n uses 4 pilot subcarriers, 52 data subcarriers, and one null suppressed subcarrier in the middle for 57 total subcarrier channels.

$$B_N = N_s * K$$

Radio Type	Mode	N _s (MHz)	K	B _N (MHz)
802.11a/g	20 MHz	0.3125	53	16.6
802.11n/ac	20 MHz	0.3125	57	17.8
802.11n/ac	40 MHz	0.3125	117	36.6

Table TR16.106: Necessary Bandwidth for IEEE 802.11 a, g, n, and ac Radio Protocols (TRC-43)

This line is the end of the test record.

Test Record
Transmitter Bandwidth Tests
Test IDs TR89
Project GCL-0887

Test Date(s) 16 Dec 2025
Test Personnel Majid Farah

Product Model AB5206
Serial Number tested 3621679750

Operating Mode M6 (AntTx)
Arrangement A2
Input Power 5Vdc

Test Standards: FCC Part 15.215, ANSI C63.10 (as noted in Section 6 of the report).

Radio Protocol ANT
Radio Band 2400 to 2483.5 MHz

Pass/Fail Judgment: PASS

Test record created by: Majid Farah
Date of this record: 16 Dec 2025

Test Equipment Used

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 44 GHz	Keysight	N9048B	MY62220139	4-Sep-2025	4-Sep-2026

Table TR89.1: List of test equipment used

Test Software Used: Keysight PXE firmware version A.33.03

Test Method

During this test the transmitter output is fed directly, or through RF attenuators, to the spectrum analyzer. The analyzer has a built-in capability to identify the minimum bandwidth that contains a specified portion of the total power observed, and also identify parameters such as the edge frequencies for that bandwidth and the center frequency error. The spectrum is scanned many times so that the varied effects of modulation are appropriately assessed. Since the focus is on the relative distribution of energy across a range of frequencies, the absolute amplitudes recorded during this test are not relevant and may not include cable losses or attenuation factors.

Test Setup

This block diagram shows the test equipment setup.




Figure TR89.1: Test setup

Test Data

For intentional radiators (transmitters) the 20 dB bandwidth of the emission must be contained entirely within the frequency band specified for the equipment's operation. This ensures the device does not cause excessive interference outside its allocated spectrum.

The 20dB Bandwidth is measured using a spectrum analyzer operating with a defined resolution bandwidth. The analyzer finds the peak emission of the displayed trace. The amplitude level for the measurement is calculated by subtracting 20 dB from the peak reference value. The instrument reports the boundary of 20 dB occupied band width. The boundary of 20 dB occupied band width has remained in 2400-2483.5 MHz with calculated margin in table below.

ANT	(MHz)	(MHz)
Tx Frequency	2402	2480
20 dB OBW Edge freq.	2401.498	2480.535
Margin to band edge	1.498	2.965
20 dB OBW	1.036	1.036

Table TR89.2: Summary of 20dB occupied bandwidth data




Figure TR89.2: 20dB occupied bandwidth data at 2402 MHz




Figure TR89.2: 20dB occupied bandwidth data at 2480 MHz

This line is the end of the test record.

Test Record

Conducted Emissions Mains Test CE03

Project GCL0887

Test Date(s) 04-Dec-2025
Test Personnel Andy Heier

Product Model AB5206
Serial Number tested 3621678871

Operating Mode M5 (AntTx)
Arrangement A2
Input Power 120 Vac 60 Hz

Test Standards: FCC Part 15, ANSI C63.10, RSS-247, RSS-GEN (as noted in Section 6 of the report).

Frequency Range: 150 kHz to 30 MHz
Pass/Fail Judgment: PASS

Test record created by: Andy Heier
Date of this record: 05 Dec 2025

Original record, Version A.

Test Equipment

Description	Make	Model #	Serial #	Last Cal/Ver	Next Due
PXE Receiver 44 GHz	Keysight	N9048B	MY62220139	4-Sep-2025	4-Sep-2026
Tape Measure, 1-3/16 in x 33 ft	Crecent Lufkin	L1135CME-02	GMN0013782	26-Jun-2024	26-Jun-2027
LISN multiline; 20A 50uH	Com-Power	LIN-120C	20160005	3-Apr-2024	1-Apr-2027
Coaxial Power Cable	Com-Power	RG214/U	20230124-01	3-Apr-2024	1-Apr-2027

Table CE03.1: Test Equipment Used

Software Used

Keysight PXE software A.33.03, CE Mains 150k to 30M Data Analysis V3a 2025Oct23.xlsx

Test Data

The conducted emission test process began with a set of preliminary scans on both power conductors using both Quasi-Peak and Average detectors across the frequency range. Where the test standard requires cable manipulation, one or more likely worst case frequencies selected by the test personnel. Cables were manipulated to find the maximal signal strength while observing the receiver levels at those selected frequencies. At each of the frequencies selected for final measurements, Quasi-peak and Average detector readings were taken on each conductor.

The table shows the selected final measurement data. It includes at least the six strongest emissions observed relative to the limit lines, along with other data points of interest. The yellow highlight indicate the data points with the least margin to the quasi-peak detector limit and the average detector limit. A positive margin value indicates that the emission was below the test limit. The test limit is the FCC Class B Limit.

In this test, fewer than six emissions were observed within 20 dB of the limit. The relevant emissions were measured, including one or more noise floor signals as judged appropriate to the spectrum.

Frequency	QP Limit	AV Limit	L1 QP	L2 QP	L1 AV	L2 AV	QP Margin	AV Margin
(kHz)	(dBμV)	(dBμV)	(dBμV)	(dBμV)	(dBμV)	(dBμV)	(dB)	(dB)
503	56.00	46.00	33.52	29.25	29.56	24.80	22.48	16.44
30000	60.00	50.00	29.04	29.04	23.64	23.64	30.96	26.36

Table CE03.2: Emission summary (ANT, 2440 MHz)

The graph below shows preliminary scan data as continuous curves. Superimposed are the final measurement data points reported in the table above.




Figure CE03.1: Spectral data (ANT, 2440 MHz)

Setup Photographs

The following photographs show the EUT configured and arranged in the manner in which it was measured.




Figure CE03.2: Test setup, first view




Figure CE03.3: Test setup, second view

This line is the end of the test record.

Concluding Notes

This report stands as an integrated record of the tests performed and must be copied or distributed in its complete form. The reproduction of selected pages or sections separate from the complete report would require specific approval from the manager of the Garmin Compliance Lab.

This is the final page of the report.