

47 CFR PART 15 SUBPART E TEST REPORT

for

Tablet

Model No.: DP8

FCC ID: IR5DP8

of

Applicant: MilDef Crete Inc.

Address: 7F, No. 250, Sec.3, Pei Shen Rd., Shen Keng District,
New Taipei City Taiwan R.O.C.

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22603-25033-C-2

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: wts@wts-lab.com



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

TABLE OF CONTENTS

1	GENERAL INFORMATION	2
1.1	NOTES.....	2
1.2	TESTING LABORATORY	3
1.3	DETAILS OF APPROVAL HOLDER.....	3
1.4	APPLICATION DETAILS	3
1.5	GENERAL INFORMATION OF TEST ITEM	4
1.6	DUTY CYCLES.....	6
1.7	TEST STANDARDS.....	10
2	TECHNICAL TEST.....	11
2.1	SUMMARY OF TEST RESULTS	11
2.2	TEST ENVIRONMENT	11
2.3	TEST EQUIPMENT LIST.....	11
2.4	TEST PROCEDURE	14
3	TEST RESULTS (ENCLOSURE).....	17
3.1	PEAK TRANSMIT POWER, FCC 15.407 (A).....	18
3.2	UNDESIRABLE EMISSION LIMITS, FCC 15.407 (B)	128
3.3	RADIATED EMISSIONS FROM RECEIVER PART.....	130
3.4	POWER LINE CONDUCTED EMISSION	131

Appendix



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Specific Conditions:

Usage of the hereunder tested device in combination with other integrated or external antennas requires at least additional output power measurements, spurious emission measurements, conducted emission measurements (AC supply lines) and radio frequency exposure evaluations for each individual configuration performed, for certification by FCC.

Tester:

July 09, 2026

Rick Chen

Rick Chen.

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

July 09, 2026

Kevin Wang

Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.
6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,
Taipei City 114, Taiwan (R.O.C.)
Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd.:

Name: ./.
Accredited number: ./.
Street: ./.
Town: ./.
Country: ./.

1.3 Details of approval holder

Name: MilDef Crete Inc.
Street: 7F, No. 250, Sec.3, Pei Shen Rd., Shen Keng District,
Town: New Taipei City
Country: Taiwan R.O.C.

1.4 Application details

Date of receipt of test item: March 12, 2026

Date of test: from March 13, 2026 to July 03, 2026



Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

1.5 General information of Test item

Type of test item: Tablet
Model number: DP8
Brand name: MilDef Crete
Multi-listing model number: ./.
Sample no.: #02

Technical data

Frequency band: WLAN 5G
Band 1: 5.150 GHz-5.250 GHz
Band 4: 5.725 GHz-5.850 GHz

Band	Mode	Channel	Conducted Power (dBm)
NII-1	802.11a	Ch 36 : 5180 MHz	4.04
		Ch 44 : 5220 MHz	4.37
		Ch 48 : 5240 MHz	4.48
	802.11ax 20MHz	Ch 36 : 5180 MHz	8.93
		Ch 44 : 5220 MHz	9.34
		Ch 48 : 5240 MHz	9.23
	802.11ax 40MHz	Ch 38 : 5190 MHz	9.40
		Ch 46 : 5230 MHz	9.49
	802.11ax 80MHz	Ch 42 : 5210 MHz	9.38

Band	Mode	Channel	Conducted Power (dBm)
NII-3	802.11a	Ch 149 : 5745 MHz	4.90
		Ch 157 : 5785 MHz	4.82
		Ch 165 : 5825 MHz	4.73
	802.11ax 20MHz	Ch 149 : 5745 MHz	9.46
		Ch 157 : 5785 MHz	9.39
		Ch 165 : 5825 MHz	9.35
	802.11ax 40MHz	Ch 151 : 5755 MHz	9.61
		Ch 159 : 5795 MHz	9.63
	802.11ax 80MHz	Ch 155: 5775 MHz	9.48



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

Operating modes: Duplex

Type of modulation: OFDM/DSSS

Fixed point to point operation: Yes / No

Type of antenna: PIFA antenna

Antenna gain: ANT 1
Band 1: 5.39 dBi
Band 4: 4.37 dBi
ANT 2
Band 1: 4.72 dBi
Band 4: 4.42 dBi

Directional gain: Band 1: 8.07 dBi
Band 4: 7.41 dBi

Power supply: Adapter (I/P: 100-240V~50-60Hz 0.85A MAX.
O/P: 5.0V=3.0A 15.0W/
or 9.0V=3.0A 27.0W or 12.0V=3.0A 36.0W/
or 15.0V=3.0A 45.0W/20.0V=3.0A 60.0W)
Battery 7.27V=6300mAh/45.8Wh

Note: Tests were performed under worst case mode 802.11a 6 Mbps, 802.11ax 20MHz(MCS0), 802.11ax 40MHz(MCS0) and 802.11ax 80MHz(MCS0).

Note: This device was functioned as a ☐ Master ☐ Slave device during the DFS

Manufacturer: (if applicable)

Name: ./.
Street: ./.
Town: ./.
Country: ./.




Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

1.6 Duty Cycles

A correction factor shall be added to the measurement results prior to comparing with the emission limit to compute the emission level that would have been measured had the test been performed at 100% duty cycle.

The correction factor is computed as $[10 \log (1 / D)]$, where D is the duty cycle.


Mode	T _{on} (ms)	T _{on} +T _{off} (ms)	Duty cycle (%)	Duty Factor (dB)	1/T - VBW (kHz)
802.11a	2.115	2.131	99.25	0.03	0.01
802.11ax 20MHz	2.604	2.628	99.09	0.04	0.01
802.11ax 40MHz	2.612	2.652	98.49	0.07	0.01
802.11ax 80MHz	2.604	2.636	98.79	0.05	0.01




DUTY 802.11A
Date: 18.MAR.2026 18:24:49



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




DUTY 802.11A
Date: 18.MAR.2026 18:25:10




DUTY 802.11AX 20MHZ
Date: 18.MAR.2026 18:21:33



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




DUTY 802.11AX 20MHZ
Date: 18.MAR.2026 18:21:49




DUTY 802.11AX 40MHZ
Date: 18.MAR.2026 18:17:07



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




DUTY 802.11AX 40MHZ
Date: 18.MAR.2026 18:17:24



DUTY 802.11AX 80MHZ
Date: 18.MAR.2026 18:22:44



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



DUTY 802.11AX 80MHZ
Date: 18.MAR.2026 18:23:10

1.7 Test standards

47 CFR PART 15 SUBPART E § 15.407 (2024-10)
ANSI C63.10-2020+Cor.1-2023+C63.10a-2024



Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.



or

The deviations were ascertained in the course of the tests performed.



2.2 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (CR) (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 1.04 dB
Estimation Result of Uncertainty of Radiated Emission(3M-966A) (Undesirable emission limits, Radiated Emissions from Receiver Part)	Expanded Uncertainty : 0.009-30 MHz : 1.85 dB 30-1000 MHz : 4.21 dB 1-18 GHz : 3.19 dB 18-40 GHz : 1.90 dB
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Transmit Power)	Expanded Uncertainty : 1.49 dB
Estimation Result of Uncertainty of EIRP Measurement (Equivalent Isotropic Radiated Power (EIRP), Radiated Emissions from Receiver Part)	Expanded Uncertainty : 30-200MHz : 1.97 dB 200-1000MHz : 1.96 dB 1-18GHz : 3.88 dB 18-40GHz : 2.81 dB

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

2.3 Test Equipment List

Max Output Power

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2026/2/13	2027/2/12
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2026/3/12	2027/3/11
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2026/2/13	2027/2/12
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2026/2/13	2027/2/12

Spurious Emission (966A)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2025/9/10	2026/9/9
ETSTW-RE 154	EMI Test Receiver	ESR3	102829	R&S	2026/4/20	2027/4/19
ETSTW-RE 160	Amplifier Module	CHC 3	None	WTS	2025/7/11	2026/7/10
ETSTW-RE 177	TRILOG Broadband Antenna	VULB 9168&EMCI-N-6-06	01380&AT-06007	SCHWARZBECK&EMC	2026/4/17	2027/4/16
ETSTW-RE 178	Double Ridged Guide Horn Antenna	DRH18-E	210505A18ES	RFSPIN	2026/3/26	2027/3/25
ETSTW-Cable 077	SMA type cable (10m)	EMC104-SM-SM-10000	230511	EMCI	2025/7/11	2026/7/10
ETSTW-Cable 084	SMA type cable (1m)	SF104-11SMA-1000	816477/4	HONOVA	2025/7/11	2026/7/10
ETSTW-Cable 089	SMA type cable (2m)	SF104-11SMA-2000	SN 811889/4	HUBER+SUHNER	2025/7/11	2026/7/10
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2025/7/31	2026/7/30
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2025/9/12	2026/9/11
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2025/9/12	2026/9/11
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2025/9/12	2026/9/11
ETSTW-RE 019	MICROWAVE HORN ANTENNA	22240-25	121074	FM	2025/9/3	2026/9/2
ETSTW-Cable 049	Microwave Cable	FA147A0015M2020	30064-1	UTIFLEX	2025/8/14	2026/8/13



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

AC Conducted Emission (CR)

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-CE 032	EMI Test Receiver	ESR3	102830	R&S	2026/5/8	2027/5/7
ETSTW-CE 035	AC Power Source	AFC-150	A2000386	All power	Function Test	
ETSTW-CE 034	Line-Impedance Stabilisation Network	NSLK8127	01087	SCHWARZBECK	2025/7/17	2026/7/16
ETSTW-Cable 092	BNC Cable (3m)	EMCCFD-300-BM-BM-3000	240108	EMCI	2026/1/8	2027/1/7
WTSTW-SW 002	EMI TEST SOFTWARE	EZ_EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	



Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

2.4 Test Procedure

The test procedures are performed following the test stands ANSI STANDARD C63.10 and FCC 789033 D02 General UNII Test Procedures New Rules v01r04.

■ Minimum Emission Bandwidth for the band 5.150-5.250 GHz, 5.725-5.850 GHz

Section 15.407(e) specifies the minimum 6 dB emission bandwidth of at least 500 KHz for the band 5.715-5.85 GHz. The following procedure shall be used for measuring this bandwidth:

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Note: The automatic bandwidth measurement capability of a spectrum analyzer or EMI receiver may be employed if it implements the functionality described above.

■ 99 Percent Occupied Bandwidth

The 99-percent occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5 % of the total mean power of the given emission. Measurement of the 99-percent occupied bandwidth is required only as a condition for using the optional band-edge measurement techniques described in section H)3)d). Measurements of 99-percent occupied bandwidth may also optionally be used in lieu of the 6-dB emission bandwidth to define the minimum frequency range over which the spectrum is integrated when measuring maximum conducted output power as described in section E). However, the 6-dB bandwidth must be measured to determine bandwidth dependent limits on maximum conducted output power in accordance with 15.407(a).

The following procedure shall be used for measuring (99 %) power bandwidth.

1. Set center frequency to the nominal EUT channel center frequency.
2. Set span = 1.5 times to 5.0 times the OBW.
3. Set RBW = 1 % to 5 % of the OBW
4. Set VBW $\geq 3 \cdot$ RBW
5. Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
6. Use the 99 % power bandwidth function of the instrument (if available).
7. If the instrument does not have a 99 % power bandwidth function, the trace data points are recovered and directly summed in power units. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 % of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5 % of the total is reached; that frequency is recorded as the upper frequency. The 99% occupied bandwidth is the difference between these two frequencies.



Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

■ Maximum conducted output power

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW ≥ 3 MHz.
- (iv) Number of points in sweep ≥ 2 Span / RBW. (This ensures that bin-to-bin spacing is $\leq$ RBW/2, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle < 98 percent, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle ≥ 98 percent, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to “free run”.
- (viii) Trace average at least 100 traces in power averaging (i.e., RMS) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument’s band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.

■ Power Density

The rules requires “maximum power spectral density” measurements where the intent is to measure the maximum value of the time average of the power spectral density measured during a period of continuous transmission.

1. Create an average power spectrum for the EUT operating mode being tested by following the instructions in section II.E.2. for measuring maximum conducted output power using a spectrum analyzer or EMI receiver: select the appropriate test method (SA-1, SA-2, SA-3, or alternatives to each) and apply it up to, but not including, the step labeled, “Compute power...”. (This procedure is required even if the maximum conducted output power measurement was performed using a power meter, method PM.)
2. Use the peak search function on the instrument to find the peak of the spectrum and record its value.
3. Make the following adjustments to the peak value of the spectrum, if applicable:
 - a) If Method SA-2 or SA-2 Alternative was used, add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum.
 - b) If Method SA-3 Alternative was used and the linear mode was used in step II.E.2.g)(viii), add 1 dB to the final result to compensate for the difference between linear averaging and power averaging.
4. The result is the Maximum PSD over 1 MHz reference bandwidth.
5. For devices operating in the bands 5.15-5.25 GHz, 5.25-5.35 GHz, and 5.47-5.725 GHz, the above procedures make use of 1 MHz RBW to satisfy directly the 1 MHz reference bandwidth specified in § 15.407(a)(5). For devices operating in the band 5.725-5.85 GHz, the rules specify a measurement bandwidth of 500 kHz. Many spectrum analyzers do not have 500 kHz RBW, thus




Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

a narrower RBW may need to be used. The rules permit the use of a RBWs less than 1 MHz, or 500 kHz, “provided that the measured power is integrated over the full reference bandwidth” to show the total power over the specified measurement bandwidth (i.e., 1 MHz, or 500 kHz). If measurements are performed using a reduced resolution bandwidth (< 1 MHz, or < 500 kHz) and integrated over 1 MHz, or 500 KHz bandwidth, the following adjustments to the procedures apply:

- a) Set RBW $\geq 1/T$, where T is defined in section II.B.1.a).
- b) Set VBW ≥ 3 RBW.
- c) If measurement bandwidth of Maximum PSD is specified in 500 kHz, add $10\log(500\text{kHz}/\text{RBW})$ to the measured result, whereas RBW (< 500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement.
- d) If measurement bandwidth of Maximum PSD is specified in 1 MHz, add $10\log(1\text{MHz}/\text{RBW})$ to the measured result, whereas RBW (< 1 MHz) is the reduced resolution bandwidth of spectrum analyzer set during measurement.
- e) Care must be taken to ensure that the measurements are performed during a period of continuous transmission or are corrected upward for duty cycle.

Note: As a practical matter, it is recommended to use reduced RBW of 100 kHz for the sections 5.c) and 5.d) above, since RBW=100 kHz is available on nearly all spectrum analyzers.

Conducted measurement test setup





Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

3 Test results (enclosure)

Test case	Para. Number	Required	Test passed	Test failed
Peak Transmit Power	15.407(a)	☒	☒	☐
Radiated Emission from Receiver Part	15.109	☐	☐	☐
AC Conducted Emissions	15.207	☒	☒	☐

The following is intentionally left blank.



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

3.1 Peak Transmit Power, FCC 15.407 (a)

According to §15.407(a)

1. For the band 5.15-5.25 GHz, the maximum conducted power over the frequency of operation shall not exceed the lesser of 30 dBm (1 W) for master device and 24 dBm (250 mW) for mobile/portable client device.
2. For the band 5.25-5.35 GHz and 5.47-5.725 GHz, the maximum conducted power over the frequency of operation shall not exceed the lesser of 24 dBm (250 mW) or $11\text{dBm} + 10 \log B$, whichever is lower ($B = 26\text{-dB emission BW}$).
3. For the band 5.725-5.850 GHz, the maximum conducted power over the frequency of operation shall not exceed the lesser of 30 dBm (1 W).

Test date: May 21, 2026

Temperature: 26.9°C

Humidity: 58.8 %

Tester: Rick

Band	Mode	Channel	RU(AX)	Conducted power with DF		Combine (dBm)	DF (dB)	Limit (dBm)
				Antenna 1 (dBm)	Antenna 2 (dBm)			
NII-1	802.11a	Ch 36 : 5180 MHz	-	3.71	4.04	-	0.03	21.93
		Ch 44 : 5220 MHz	-	4.13	4.37	-	0.03	21.93
		Ch 48 : 5240 MHz	-	4.40	4.48	-	0.03	21.93
	802.11ax 20MHz	Ch 36 : 5180 MHz	26RU1	4.79	6.32	8.63	0.04	21.93
			26RU9	5.73	5.97	8.86	0.04	21.93
			52RU1	4.94	6.41	8.75	0.04	21.93
			52RU4	5.73	5.75	8.75	0.04	21.93
			106RU1	5.02	6.37	8.76	0.04	21.93
			106RU2	5.64	6.18	8.93	0.04	21.93
			242RU1	5.13	6.17	8.69	0.04	21.93
		Ch 44 : 5220 MHz	26RU1	5.84	6.13	9.00	0.04	21.93
			26RU9	5.33	6.65	9.05	0.04	21.93
			52RU1	5.93	6.31	9.13	0.04	21.93
			52RU4	5.43	6.88	9.23	0.04	21.93
			106RU1	5.95	6.48	9.23	0.04	21.93
			106RU2	5.63	6.93	9.34	0.04	21.93
			242RU1	5.69	6.60	9.18	0.04	21.93
		Ch 48 : 5240 MHz	26RU1	6.05	6.21	9.14	0.04	21.93



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

			26RU9	5.57	6.55	9.10	0.04	21.93
			52RU1	6.06	6.29	9.19	0.04	21.93
			52RU4	5.65	6.62	9.17	0.04	21.93
			106RU1	6.03	6.41	9.23	0.04	21.93
			106RU2	5.74	6.64	9.22	0.04	21.93
			242RU1	5.77	6.48	9.15	0.04	21.93
	802.11ax 40MHz	Ch 38 : 5190 MHz	26RU1	5.54	6.25	8.92	0.07	21.93
			26RU18	5.80	6.84	9.36	0.07	21.93
			52RU1	3.98	6.24	8.26	0.07	21.93
			52RU8	5.85	6.81	9.36	0.07	21.93
			106RU1	5.75	6.23	9.00	0.07	21.93
			106RU4	6.00	6.75	9.40	0.07	21.93
			242RU1	5.75	6.26	9.02	0.07	21.93
			242RU2	5.99	6.57	9.30	0.07	21.93
			484RU1	5.45	5.99	8.73	0.07	21.93
		Ch 46 : 5230 MHz	26RU1	6.32	6.60	9.47	0.07	21.93
			26RU18	6.41	6.32	9.37	0.07	21.93
			52RU1	6.32	6.65	9.49	0.07	21.93
			52RU8	6.39	6.37	9.39	0.07	21.93
			106RU1	6.31	6.66	9.49	0.07	21.93
			106RU4	6.33	6.46	9.40	0.07	21.93
			242RU1	6.15	6.58	9.38	0.07	21.93
			242RU2	6.26	6.53	9.40	0.07	21.93
			484RU1	5.91	6.11	9.02	0.07	21.93
	802.11ax 80MHz	Ch 42 : 5210 MHz	26RU1	4.99	6.43	8.78	0.05	21.93
			26RU37	6.01	6.54	9.30	0.05	21.93
			52RU1	5.13	6.38	8.81	0.05	21.93
			52RU16	6.02	6.55	9.31	0.05	21.93
			106RU1	5.23	6.40	8.87	0.05	21.93
			106RU8	6.11	6.60	9.38	0.05	21.93
			242RU1	5.52	6.22	8.90	0.05	21.93
			242RU4	6.12	6.52	9.34	0.05	21.93
			484RU1	5.38	5.90	8.66	0.05	21.93
			484RU2	5.80	6.10	8.97	0.05	21.93
			966RU1	5.70	6.13	8.93	0.05	21.93



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

NII-3	802.11a	Ch 149 : 5745 MHz	-	4.43	4.90	-	0.03	28.59
		Ch 157 : 5785 MHz	-	4.47	4.82	-	0.03	28.59
		Ch 165 : 5825 MHz	-	4.45	4.73	-	0.03	28.59
	802.11ax 20MHz	Ch 149 : 5745 MHz	26RU1	5.69	6.85	9.32	0.04	28.59
			26RU9	6.06	6.40	9.24	0.04	28.59
			52RU1	5.80	6.93	9.41	0.04	28.59
			52RU4	6.10	6.56	9.35	0.04	28.59
			106RU1	5.85	6.97	9.46	0.04	28.59
			106RU2	6.06	6.70	9.40	0.04	28.59
			242RU1	5.84	6.78	9.35	0.04	28.59
		Ch 157 : 5785 MHz	26RU1	5.74	6.60	9.20	0.04	28.59
			26RU9	5.65	6.77	9.26	0.04	28.59
			52RU1	5.86	6.69	9.30	0.04	28.59
			52RU4	5.75	6.77	9.30	0.04	28.59
			106RU1	5.89	6.72	9.33	0.04	28.59
			106RU2	5.87	6.84	9.39	0.04	28.59
			242RU1	5.78	6.67	9.26	0.04	28.59
		Ch 165 : 5825 MHz	26RU1	6.07	6.24	9.17	0.04	28.59
			26RU9	5.62	6.64	9.17	0.04	28.59
			52RU1	6.11	6.39	9.26	0.04	28.59
			52RU4	5.74	6.77	9.30	0.04	28.59
			106RU1	6.09	6.53	9.33	0.04	28.59
			106RU2	5.78	6.83	9.35	0.04	28.59
			242RU1	5.82	6.61	9.24	0.04	28.59
	802.11ax 40MHz	Ch 151 : 5755 MHz	26RU1	6.34	6.35	9.35	0.07	28.59
			26RU18	6.27	6.73	9.51	0.07	28.59
			52RU1	6.30	6.77	9.55	0.07	28.59
			52RU8	6.30	6.80	9.56	0.07	28.59
			106RU1	6.33	6.87	9.61	0.07	28.59
			106RU4	6.32	6.87	9.61	0.07	28.59
			242RU1	6.20	6.82	9.53	0.07	28.59
			242RU2	5.24	6.87	9.14	0.07	28.59
			484RU1	5.92	6.48	9.22	0.07	28.59
		Ch 159 : 5795 MHz	26RU1	6.22	6.97	9.62	0.07	28.59
			26RU18	6.06	6.94	9.53	0.07	28.59
			52RU1	6.27	6.94	9.62	0.07	28.59
			52RU8	6.08	6.95	9.54	0.07	28.59



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

			106RU1	6.34	6.89	9.63	0.07	28.59
			106RU4	6.14	6.95	9.57	0.07	28.59
			242RU1	6.27	6.81	9.55	0.07	28.59
			242RU2	6.20	6.86	9.55	0.07	28.59
			484RU1	6.02	6.37	9.20	0.07	28.59
	802.11ax 80MHz	Ch 155: 5775 MHz	26RU1	5.96	6.69	9.35	0.05	28.59
			26RU37	5.60	6.97	9.35	0.05	28.59
			52RU1	5.99	6.68	9.36	0.05	28.59
			52RU16	5.67	6.94	9.36	0.05	28.59
			106RU1	6.09	6.77	9.46	0.05	28.59
			106RU8	5.87	6.89	9.42	0.05	28.59
			242RU1	6.25	6.67	9.48	0.05	28.59
			242RU4	6.20	6.60	9.42	0.05	28.59
			484RU1	5.99	6.27	9.15	0.05	28.59
			484RU2	6.01	6.06	9.05	0.05	28.59
			966RU1	6.06	6.41	9.25	0.05	28.59




Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8


ANT 1

5.15 GHz ~ 5.25 GHz



MAXIMUM CONDUCTED POWER ANT1_11aCH36

Date: 21.MAY.2026 19:11:21




MAXIMUM CONDUCTED POWER ANT1_11aCH44


Date: 21.MAY.2026 19:10:24



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11aCH48
Date: 21.MAY.2026 18:27:16




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_26RU1
Date: 21.MAY.2026 19:17:47



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_26RU9
Date: 21.MAY.2026 19:18:25




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_52RU1
Date: 21.MAY.2026 19:19:59



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_52RU4
Date: 21.MAY.2026 19:20:39




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_106RU1
Date: 21.MAY.2026 19:21:29



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_106RU2
Date: 21.MAY.2026 19:22:10




MAXIMUM CONDUCTED POWER ANT1_11ax20CH36_242RU1
Date: 21.MAY.2026 19:23:03



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_26RU1
Date: 21.MAY.2026 19:24:28




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_26RU9
Date: 21.MAY.2026 19:25:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_52RU1
Date: 21.MAY.2026 19:25:53




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_52RU4
Date: 21.MAY.2026 19:26:34



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_106RU1
Date: 21.MAY.2026 19:27:16




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_106RU2
Date: 21.MAY.2026 19:27:59



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH44_242RU1
Date: 21.MAY.2026 19:28:53




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_26RU1
Date: 21.MAY.2026 19:30:25



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_26RU9
Date: 21.MAY.2026 19:31:06




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_52RU1
Date: 21.MAY.2026 19:31:52



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_52RU4
Date: 21.MAY.2026 19:32:33




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_106RU1
Date: 21.MAY.2026 19:33:21



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_106RU2
Date: 21.MAY.2026 19:34:06




MAXIMUM CONDUCTED POWER ANT1_11ax20CH48_242RU1
Date: 21.MAY.2026 19:35:00



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_26RU1
Date: 21.MAY.2026 20:46:24




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_26RU18
Date: 21.MAY.2026 20:48:33



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_52RU1
Date: 21.MAY.2026 20:49:32




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_52RU8
Date: 21.MAY.2026 20:50:20



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_106RU1
Date: 21.MAY.2026 20:51:04




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_106RU4
Date: 21.MAY.2026 20:51:52



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_242RU1
Date: 21.MAY.2026 20:54:22




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_242RU2
Date: 21.MAY.2026 20:55:24



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH38_484RU1
Date: 21.MAY.2026 20:56:26




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_26RU1
Date: 21.MAY.2026 20:58:18



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_26RU18
Date: 21.MAY.2026 20:59:01




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_52RU1
Date: 21.MAY.2026 20:59:42



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_52RU8
Date: 21.MAY.2026 21:00:24




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_106RU1
Date: 21.MAY.2026 21:01:20



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_106RU4
Date: 21.MAY.2026 21:02:02




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_242RU1
Date: 21.MAY.2026 21:02:45



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_242RU2
Date: 21.MAY.2026 21:03:26




MAXIMUM CONDUCTED POWER ANT1_11ax40CH46_484RU1
Date: 21.MAY.2026 21:04:33



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_26RU1
Date: 21.MAY.2026 21:44:08




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_26RU37
Date: 21.MAY.2026 21:45:06



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_52RU1
Date: 21.MAY.2026 21:46:04




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_52RU16
Date: 21.MAY.2026 21:46:53



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_106RU1
Date: 21.MAY.2026 21:47:48




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_106RU8
Date: 21.MAY.2026 21:48:41



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_242RU1
Date: 21.MAY.2026 21:49:36




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_242RU4
Date: 21.MAY.2026 21:50:29



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_484RU1
Date: 21.MAY.2026 21:51:22



MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_484RU2
Date: 21.MAY.2026 21:52:14




Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



MAXIMUM CONDUCTED POWER ANT1_11ax80CH42_966RU1
Date: 21.MAY.2026 21:53:19


5.725 GHz ~ 5.85 GHz




MAXIMUM CONDUCTED POWER ANT1_11aCH149
Date: 21.MAY.2026 19:12:21



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11aCH157
Date: 21.MAY.2026 19:13:23




MAXIMUM CONDUCTED POWER ANT1_11aCH165
Date: 21.MAY.2026 19:14:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_26RU1
Date: 21.MAY.2026 19:36:15




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_26RU9
Date: 21.MAY.2026 19:36:59



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_52RU1
Date: 21.MAY.2026 19:37:42




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_52RU4
Date: 21.MAY.2026 19:41:26



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_106RU1
Date: 21.MAY.2026 19:42:25




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_106RU2
Date: 21.MAY.2026 19:43:02



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH149_242RU1
Date: 21.MAY.2026 19:44:05




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_26RU1
Date: 21.MAY.2026 19:45:38



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_26RU9
Date: 21.MAY.2026 19:46:34




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_52RU1
Date: 21.MAY.2026 19:47:22



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_52RU4
Date: 21.MAY.2026 19:48:08




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_106RU1
Date: 21.MAY.2026 19:48:48



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_106RU2
Date: 21.MAY.2026 19:49:31




MAXIMUM CONDUCTED POWER ANT1_11ax20CH157_242RU1
Date: 21.MAY.2026 19:50:33



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_26RU1
Date: 21.MAY.2026 19:51:57




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_26RU9
Date: 21.MAY.2026 19:52:45



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_52RU1
Date: 21.MAY.2026 19:53:30




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_52RU4
Date: 21.MAY.2026 19:54:16



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_106RU1
Date: 21.MAY.2026 19:55:59




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_106RU2
Date: 21.MAY.2026 19:56:47



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax20CH165_242RU1
Date: 21.MAY.2026 19:58:07




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_26RU1
Date: 21.MAY.2026 21:06:37



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_26RU18
Date: 21.MAY.2026 21:07:21




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_52RU1
Date: 21.MAY.2026 21:23:56



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_52RU8
Date: 21.MAY.2026 21:24:46




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_106RU1
Date: 21.MAY.2026 21:25:24



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_106RU4
Date: 21.MAY.2026 21:26:04




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_242RU1
Date: 21.MAY.2026 21:27:36



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_242RU2
Date: 21.MAY.2026 21:28:14




MAXIMUM CONDUCTED POWER ANT1_11ax40CH151_484RU1
Date: 21.MAY.2026 21:29:04



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_26RU1
Date: 21.MAY.2026 21:30:44




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_26RU18
Date: 21.MAY.2026 21:31:28



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_52RU1
Date: 21.MAY.2026 21:32:09




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_52RU8
Date: 21.MAY.2026 21:32:53



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_106RU1
Date: 21.MAY.2026 21:33:47




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_106RU4
Date: 21.MAY.2026 21:34:31



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_242RU1
Date: 21.MAY.2026 21:35:21




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_242RU2
Date: 21.MAY.2026 21:36:02



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax40CH159_484RU1
Date: 21.MAY.2026 21:36:55




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_26RU1
Date: 21.MAY.2026 22:03:25



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_26RU37
Date: 21.MAY.2026 22:10:25




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_52RU1
Date: 21.MAY.2026 22:11:25



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_52RU16
Date: 21.MAY.2026 22:12:16




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_106RU1
Date: 21.MAY.2026 22:13:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_106RU8
Date: 21.MAY.2026 22:14:08




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_242RU1
Date: 21.MAY.2026 22:15:09



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_242RU4
Date: 21.MAY.2026 22:16:01




MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_484RU1
Date: 21.MAY.2026 22:16:54



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_484RU2
Date: 21.MAY.2026 22:18:24



MAXIMUM CONDUCTED POWER ANT1_11ax80CH155_966RU1
Date: 21.MAY.2026 22:19:32




Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8


ANT 2

5.15 GHz ~ 5.25 GHz



MAXIMUM CONDUCTED POWER ANT2_11aCH36

Date: 21.MAY.2026 18:24:13




MAXIMUM CONDUCTED POWER ANT2_11aCH44


Date: 21.MAY.2026 18:25:07



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11aCH48
Date: 21.MAY.2026 18:25:56




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_26RU1
Date: 21.MAY.2026 14:24:23



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_26RU9
Date: 21.MAY.2026 14:25:24




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_52RU1
Date: 21.MAY.2026 14:26:10



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_52RU4
Date: 21.MAY.2026 14:29:04




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_106RU1
Date: 21.MAY.2026 14:30:00



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_106RU2
Date: 21.MAY.2026 14:33:00




MAXIMUM CONDUCTED POWER ANT2_11ax20CH36_242RU1
Date: 21.MAY.2026 14:34:20



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_26RU1
Date: 21.MAY.2026 14:38:48




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_26RU9
Date: 21.MAY.2026 15:00:42



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_52RU1
Date: 21.MAY.2026 15:01:35




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_52RU4
Date: 21.MAY.2026 15:02:19



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_106RU1
Date: 21.MAY.2026 15:03:08




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_106RU2
Date: 21.MAY.2026 15:04:00



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH44_242RU1
Date: 21.MAY.2026 15:05:02




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_26RU1
Date: 21.MAY.2026 15:10:54



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_26RU9
Date: 21.MAY.2026 15:11:44




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_52RU1
Date: 21.MAY.2026 15:13:29



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_52RU4
Date: 21.MAY.2026 15:14:09




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_106RU1
Date: 21.MAY.2026 15:14:57



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_106RU2
Date: 21.MAY.2026 15:15:54




MAXIMUM CONDUCTED POWER ANT2_11ax20CH48_242RU1
Date: 21.MAY.2026 15:17:02



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_26RU1
Date: 21.MAY.2026 15:43:00




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_26RU18
Date: 21.MAY.2026 15:43:44



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_52RU1
Date: 21.MAY.2026 15:44:52




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_52RU8
Date: 21.MAY.2026 15:47:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_106RU1
Date: 21.MAY.2026 15:48:05




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_106RU4
Date: 21.MAY.2026 15:49:05



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_242RU1
Date: 21.MAY.2026 15:49:59




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_242RU2
Date: 21.MAY.2026 15:51:02



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH38_484RU1
Date: 21.MAY.2026 15:54:38




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_26RU1
Date: 21.MAY.2026 16:24:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_26RU18
Date: 21.MAY.2026 16:25:36




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_52RU1
Date: 21.MAY.2026 16:26:20



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_52RU8
Date: 21.MAY.2026 16:27:25




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_106RU1
Date: 21.MAY.2026 16:28:13



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_106RU4
Date: 21.MAY.2026 16:28:50




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_242RU1
Date: 21.MAY.2026 16:29:31



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_242RU2
Date: 21.MAY.2026 16:30:13




MAXIMUM CONDUCTED POWER ANT2_11ax40CH46_484RU1
Date: 21.MAY.2026 16:31:04



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_26RU1
Date: 21.MAY.2026 16:54:54




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_26RU37
Date: 21.MAY.2026 16:56:21



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_52RU1
Date: 21.MAY.2026 17:00:12




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_52RU16
Date: 21.MAY.2026 17:01:04



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_106RU1
Date: 21.MAY.2026 17:01:52




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_106RU8
Date: 21.MAY.2026 17:02:44



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_242RU1
Date: 21.MAY.2026 17:03:41




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_242RU4
Date: 21.MAY.2026 17:06:18



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_484RU1
Date: 21.MAY.2026 17:07:18



MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_484RU2
Date: 21.MAY.2026 17:08:06




Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



MAXIMUM CONDUCTED POWER ANT2_11ax80CH42_966RU1
Date: 21.MAY.2026 17:38:39


5.725 GHz ~ 5.85 GHz




MAXIMUM CONDUCTED POWER ANT2_11aCH149
Date: 21.MAY.2026 18:02:45



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11aCH157
Date: 21.MAY.2026 18:04:07




MAXIMUM CONDUCTED POWER ANT2_11aCH165
Date: 21.MAY.2026 18:05:26



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_26RU1
Date: 21.MAY.2026 15:19:23




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_26RU9
Date: 21.MAY.2026 15:20:18



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_52RU1
Date: 21.MAY.2026 15:21:17




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_52RU4
Date: 21.MAY.2026 15:22:00



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_106RU1
Date: 21.MAY.2026 15:22:45




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_106RU2
Date: 21.MAY.2026 15:23:25



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH149_242RU1
Date: 21.MAY.2026 15:24:27




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_26RU1
Date: 21.MAY.2026 15:26:06



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_26RU9
Date: 21.MAY.2026 15:26:52




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_52RU1
Date: 21.MAY.2026 15:27:46



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_52RU4
Date: 21.MAY.2026 15:30:00




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_106RU1
Date: 21.MAY.2026 15:30:54



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_106RU2
Date: 21.MAY.2026 15:31:33




MAXIMUM CONDUCTED POWER ANT2_11ax20CH157_242RU1
Date: 21.MAY.2026 15:32:36



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_26RU1
Date: 21.MAY.2026 15:34:31




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_26RU9
Date: 21.MAY.2026 15:35:19



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_52RU1
Date: 21.MAY.2026 15:36:16




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_52RU4
Date: 21.MAY.2026 15:37:02



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_106RU1
Date: 21.MAY.2026 15:37:54




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_106RU2
Date: 21.MAY.2026 15:38:37



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax20CH165_242RU1
Date: 21.MAY.2026 15:39:35




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_26RU1
Date: 21.MAY.2026 16:34:26



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_26RU18
Date: 21.MAY.2026 16:35:13




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_52RU1
Date: 21.MAY.2026 16:35:56



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_52RU8
Date: 21.MAY.2026 16:37:03




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_106RU1
Date: 21.MAY.2026 16:37:49



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_106RU4
Date: 21.MAY.2026 16:38:29




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_242RU1
Date: 21.MAY.2026 16:39:15



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_242RU2
Date: 21.MAY.2026 16:40:03




MAXIMUM CONDUCTED POWER ANT2_11ax40CH151_484RU1
Date: 21.MAY.2026 16:40:54



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_26RU1
Date: 21.MAY.2026 16:42:29




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_26RU18
Date: 21.MAY.2026 16:43:11



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_52RU1
Date: 21.MAY.2026 16:43:52




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_52RU8
Date: 21.MAY.2026 16:44:33



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_106RU1
Date: 21.MAY.2026 16:45:17




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_106RU4
Date: 21.MAY.2026 16:45:58



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_242RU1
Date: 21.MAY.2026 16:46:51




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_242RU2
Date: 21.MAY.2026 16:47:35



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax40CH159_484RU1
Date: 21.MAY.2026 16:48:32




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_26RU1
Date: 21.MAY.2026 17:41:01



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_26RU37
Date: 21.MAY.2026 17:48:16




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_52RU1
Date: 21.MAY.2026 17:49:15



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_52RU16
Date: 21.MAY.2026 17:50:10




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_106RU1
Date: 21.MAY.2026 17:51:09



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_106RU8
Date: 21.MAY.2026 17:52:04




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_242RU1
Date: 21.MAY.2026 17:53:01



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_242RU4
Date: 21.MAY.2026 17:53:50




MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_484RU1
Date: 21.MAY.2026 17:54:42



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_484RU2
Date: 21.MAY.2026 17:55:34



MAXIMUM CONDUCTED POWER ANT2_11ax80CH155_966RU1
Date: 21.MAY.2026 17:56:34



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

3.2 Undesirable emission limits, FCC 15.407 (b)

1. For transmitters operating in the 5.15–5.25 GHz band: all emissions out-side of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz.
2. For transmitters operating in the 5.25–5.35 GHz band: all emissions out-side of the 5.15–5.35 GHz band shall not exceed an EIRP of –27 dBm/MHz. De-vices operating in the 5.25–5.35 GHz band that generate emissions in the 5.15–5.25 GHz band must meet all appli-cable technical requirements for operation in the 5.15–5.25 GHz band (including indoor use) or alternatively meet an out-of-band emission EIRP limit of -27 dBm/MHz in the 5.15–5.25 GHz band.
3. For transmitters operating in the 5.47–5.725 GHz band: all emissions out-side of the 5.47–5.725 GHz band shall not exceed an EIRP of -27 dBm/MHz.
4. For transmitters operating in the 5.725–5.850 GHz band: All emissions shall be limited to a level of –27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.
5. The emission measurements shall be performed using a minimum resolution bandwidth of 1 MHz. A lower resolution bandwidth may be employed near the band edge, when necessary, provided the measured energy is integrated to show the total power over 1 MHz.
6. Unwanted emissions below 1 GHz must comply with the general field strength limits set forth in § 15.209.
7. According to According to KDB 789033 D02 General UNII Test Procedures v01, as specified in 15.407(b), emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz (or -17 dBm/MHz as specified in 15.407(b)(4)). However, an out-of-band emission that complies with both the average and peak limits of 15.209 is not required to satisfy the -27 dBm/MHz or -17 dBm/MHz peak emission limit.
8. If radiated measurements are performed, field strength is then converted to EIRP as follows:
 - (i) $EIRP = ((E \cdot d)^2) / 30$, where: E is the field strength in V/m; d is the measurement distance in meters. EIRP is the equivalent isotropically radiated power in watts.
 - (ii) Working in dB units, the above equation is equivalent to: $EIRP[dBm] = E[dB\mu V/m] + 20 \log(d[meters]) - 104.77$.
 - (iii) Or, if d is 3 meters: $EIRP[dBm] = E[dB\mu V/m] - 95.2$.

Applicable to	Limit	
☒	FIELD STRENGTH at 3m (dBμV/m)	
	PK	AV
	74	54
☐	EIRP LIMIT (dBm)	EQUIVALENT FIELD STRENGTH at 3m (dBμV/m)
	PK	PK
	-27	68.3



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

Explanation: After evaluated, the test result in this report adopt the worst case to measure,
please see attached diagrams in appendix.



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

3.3 Radiated Emissions from Receiver Part

FCC Rule: 15.109

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Explanation: The test results are listed in the separated test report no.: W6M22603-25033-P-15B.




Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

3.4 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.



*:Maximum data x:Over limit !:over margin

Engineer Signature:

Echo




Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8



Address: No.99, Sec.1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533



*:Maximum data x:Over limit !:over margin

Engineer Signature: Echo

- Note: 1. The formula of measured value as: Test Result = Reading + Correction Factor
2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
4. All not in the table noted test results are more than 20 dB below the relevant limits.
5. Up Line: QP Limit Line, Down Line: Ave Limit Line.



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22603-25033-C-2

FCC ID: IR5DP8

Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50



Registration number: W6M22603-25033-C-2
FCC ID: IR5DP8

Appendix

Measurement diagrams

Spurious Emissions radiated




Radiated Emission Measurement

Operator: Jeff

File :1_WiFi 5G_ant1_TX 802 Data :#1 Date: 2026/4/17 Temperature:26.0 °C

80.0 dBuV/m Time: 上午 09:28:55 Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class E_30-1000MHz

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	51.3400	34.10	peak	-12.62	21.48	40.00	100	263	-18.52	
	179.3800	35.78	peak	-13.62	22.16	43.50	100	297	-21.34	
*	263.7700	47.53	peak	-13.16	34.37	46.00	100	39	-11.63	
	627.5200	35.04	peak	-4.23	30.81	46.00	100	157	-15.19	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File: 1_WiFi 5G_ant1_TX 802

Data: #2


Date: 2026/4/17

Temperature: 26.0 °C

80.0 dBuV/m

Time: 上午 09:29:40

Humidity: 40.1 %



Site: 966A Chamber

Condition: FCC_part 15 RE-Class E_30-1000MHz

EUT: W6M22603-25033

M/N:

Test Mode: TX 802.11a CH36

Note:

Polarization: Vertical

Power: 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	43.5800	35.26	peak	-13.34	21.92	40.00	100	348	-18.08	
	175.5000	35.74	peak	-13.31	22.43	43.50	100	352	-21.07	
	264.7400	38.05	peak	-13.12	24.93	46.00	100	130	-21.07	
*	718.7000	35.51	peak	-2.94	32.57	46.00	100	331	-13.43	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 01:27:28

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:30:51

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:28:10

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:31:33

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:28:52

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.50	peak	14.46	47.96	74.00	150	160	-26.04	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:32:15

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.48	peak	14.46	47.94	74.00	150	112	-26.06	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:29:38

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	23.01	peak	23.34	46.35	74.00	150	342	-27.65	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:33:01

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	22.95	peak	23.34	46.29	74.00	150	342	-27.71	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:29:48

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#11


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 01:33:11

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:29:58

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:33:21

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:40:34

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:43:55

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:41:15

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:44:37

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:41:57

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	32.79	peak	14.63	47.42	74.00	150	152	-26.58	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:45:19

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	33.03	peak	14.63	47.66	74.00	150	359	-26.34	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:42:43

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	23.66	peak	23.28	46.94	74.00	150	128	-27.06	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:46:06

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	22.78	peak	23.28	46.06	74.00	150	359	-27.94	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:42:53

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:46:15

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:43:03

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#12


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 01:46:26

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:49:09

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 01:52:31

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:49:51

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:53:13

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:50:33

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.40	peak	14.80	48.20	74.00	150	261	-25.80	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3


Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

Time: 上午 01:53:56

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.62	peak	14.80	48.42	74.00	150	330	-25.58	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:51:19

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.49	peak	23.22	46.71	74.00	150	336	-27.29	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:54:42

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.24	peak	23.22	46.46	74.00	150	127	-27.54	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:51:29

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:54:52

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:51:39

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:55:02

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 1_WiFi 5G_ant2_TX 802

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

80.0 dBuV/m

Time: 上午 09:32:39

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class E_30-1000MHz

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	48.4300	34.46	peak	-12.78	21.68	40.00	100	7	-18.32	
	158.0400	34.54	peak	-12.15	22.39	43.50	100	67	-21.11	
*	263.7700	48.64	peak	-13.16	35.48	46.00	100	67	-10.52	
	820.5500	34.52	peak	-1.72	32.80	46.00	100	56	-13.20	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Jeff

File : 1_WiFi 5G_ant2_TX 802

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

80.0 dBuV/m

Time: 上午 09:33:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15 RE-Class E_30-1000MHz

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	53.2800	34.02	peak	-12.66	21.36	40.00	100	34	-18.64	
	161.9200	34.79	peak	-12.21	22.58	43.50	100	234	-20.92	
	263.7700	37.61	peak	-13.16	24.45	46.00	100	134	-21.55	
*	849.6500	35.70	peak	-1.51	34.19	46.00	100	349	-11.81	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:58:04

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:01:25

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:58:45

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:02:07

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 01:59:27

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.08	peak	14.46	47.54	74.00	150	220	-26.46	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:02:49

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.44	peak	14.46	47.90	74.00	150	218	-26.10	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:00:13

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	22.78	peak	23.34	46.12	74.00	150	254	-27.88	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:03:36

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	22.94	peak	23.34	46.28	74.00	150	212	-27.72	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:00:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:03:45

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:00:33

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:03:56

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:09:09

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #7


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:12:31

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#2


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:09:51

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:13:13

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:10:33

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	33.13	peak	14.63	47.76	74.00	150	0	-26.24	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:13:55

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	33.67	peak	14.63	48.30	74.00	150	141	-25.70	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:11:19

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	23.25	peak	23.28	46.53	74.00	150	253	-27.47	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:14:42

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	22.70	peak	23.28	45.98	74.00	150	44	-28.02	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:11:28

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:14:51

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:11:38

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:15:02

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:18:00

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:21:21

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:18:41

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:22:03

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:19:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.56	peak	14.80	48.36	74.00	150	265	-25.64	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:22:45

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.02	peak	14.80	47.82	74.00	150	293	-26.18	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:20:09

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.72	peak	23.22	46.94	74.00	150	336	-27.06	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:23:31

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.65	peak	23.22	46.87	74.00	150	359	-27.13	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:20:19

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:23:41

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #6

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:20:29

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#12


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:23:51

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11a CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:38:42

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:42:03

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:39:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#8


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:42:45

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:40:05

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.05	peak	14.46	47.51	74.00	150	79	-26.49	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:43:27

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10360.000	33.61	peak	14.46	48.07	74.00	150	202	-25.93	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:40:51

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	22.29	peak	23.34	45.63	74.00	150	214	-28.37	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:44:13

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15540.000	22.20	peak	23.34	45.54	74.00	150	6	-28.46	

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#5


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:41:01

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:44:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:41:11

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:44:33

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH36

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:49:09

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:52:30

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:49:50

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:53:12

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: **Vertical**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:50:32

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	33.32	peak	14.63	47.95	74.00	150	23	-26.05	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:53:54

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10440.000	33.80	peak	14.63	48.43	74.00	150	0	-25.57	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:51:18

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	23.18	peak	23.28	46.46	74.00	150	44	-27.54	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10


Date: 2026/4/17

Temperature: 26.0 °C

Time: 上午 02:54:40

Humidity: 40.1 %

90.0 dBuV/m



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15660.000	22.75	peak	23.28	46.03	74.00	150	359	-27.97	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:51:28

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:54:50

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:51:38

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:55:00

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH44

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#1


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 02:58:02

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Horizontal

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 03:01:26

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:58:44

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #8


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:02:08

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #3

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 02:59:26

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.22	peak	14.80	48.02	74.00	150	1	-25.98	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #9

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:02:50

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	10480.000	33.68	peak	14.80	48.48	74.00	150	52	-25.52	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #4


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:00:13

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.44	peak	23.22	46.66	74.00	150	336	-27.34	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #10

Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:03:37

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Vertical

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	15720.000	23.54	peak	23.22	46.76	74.00	150	359	-27.24	

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #5


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:00:23

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #11


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:03:46

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#6


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 03:00:33

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #12


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:03:56

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax20 CH48

Note :

Polarization: Vertical

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #1


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:11:03

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax40 CH38

Note :

Polarization: **Horizontal**

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address:No.99,Sec.1,Balian Rd.,Xizhi Dist.,New Taipei City
Tel:+886-2-2646-1508
Fax:+886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File :3

Data :#7


Date: 2026/4/17

Temperature:26.0 °C

90.0 dBuV/m

Time: 上午 03:14:24

Humidity:40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax40 CH38

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin



Address: No. 99, Sec. 1, Balian Rd., Xizhi Dist., New Taipei City
Tel: +886-2-2646-1508
Fax: +886-2-2646-1533

Radiated Emission Measurement

Operator: Echo

File : 3

Data : #2


Date: 2026/4/17

Temperature: 26.0 °C

90.0 dBuV/m

Time: 上午 03:11:44

Humidity: 40.1 %



Site : 966A Chamber

Condition : FCC_part 15E RE_Above 1GHz_PK

EUT : W6M22603-25033

M/N:

Test Mode : TX 802.11ax40 CH38

Note :

Polarization: *Horizontal*

Power : 120 V.a.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

*:Maximum data x:Over limit !:over margin