


SAR Test exclusion documentation according to FCC KDB 447498, RSS-102 and EN 62479

Report identification number: 1-7883/18-01-45

Certification numbers and labeling requirements	
FCC ID	IYZLK1
IC number	2701A-LK1
HVIN (Hardware Version Identification Number)	H10
PMN (Product Marketing Name)	LK1
FVIN (Firmware Version Identification Number)	-/-
HMN (Host Marketing Name)	-/-



This test report is electronically signed and valid without handwriting signature. For verification of the electronic signatures, the public keys can be requested at the testing laboratory.

Document authorized:



DN: cn=Thomas Vogler, o=CTC advanced GmbH, ou=VOG-161125, email=thomas.vogler@ctcadvanced.com, c=DE
Datum: 2019.03.01 12:55:34 +01'00'

Thomas Vogler
Lab Manager
Radio Communications & EMC



EUT technologies:

Technologies:	Max. power: (AVG)	Max. EIRP (AVG):
434 MHz radio module	---	Fieldstrength: 70.7 dB μ V/m @ 3 m = - 24.7 dBm = 0.0034 mW

Applied worst case averaged field strength see CTC advanced GmbH test report 1-7883/19-01-04 section 10.4.

SAR test exclusion according to KDB447498 (General RF Exposure Guidance)

Equations from Chapter 4.3.1: Standalone SAR test exclusion considerations page 11 and ff. and tables in Annex C

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

f in [MHz]	d _{separation} [mm]	Powerlimit [mW]	P _{max-declared} [mW]	Exclusion
434.0	5	22.00	< 1 mW	yes

SAR test exclusion according to RSS-102 Issue 5 Section 2.5.1/Table 1

The table below gives the calculated maximal power that could be used for source based time averaged conducted or radiated power, adjusted for tune up tolerance. If this is at or below the calculated value the DUT is exempted from SAR evaluation.

f in [MHz]	d _{separation} [mm]	tissue volume	Powerlimit [mW]	P _{max-declared} [mW]	Exclusion
434.00	5	1 g	52.00	< 1 mW	yes

SAR test exclusion according to EN 62479

Compliance is given according to EN 62479 because the output power of the DUT is smaller than 20 mW.